

EXPLORING DATA #1

DATA FROM R PACKAGES

DATA FROM R PACKAGES

So far we've covered three ways to get data into R:

- ① From flat files (either on your computer or online)
- ② From files like SAS and Excel
- ③ From R objects (i.e., using `load()`)

Many R packages come with their own data, which is very easy to load and use.

DATA FROM R PACKAGES

For example, the `faraway` package has a dataset called `worldcup` that you'll use today. To load it, use the `data()` function once you've loaded the package with the name of the dataset as its argument:

```
library(faraway)  
data("worldcup")
```

DATA FROM R PACKAGES

Unlike most data objects you'll work with, the data that comes with an R package will often have its own help file. You can access this using the `?` operator:

```
?worldcup
```

DATA FROM R PACKAGES

To find out all the datasets that are available in the packages you currently have loaded, run `data()` without an option inside the parentheses:

```
data()
```

To find out all of the datasets available within a certain package, run `data` with the argument `package`:

```
data(package = "faraway")
```

As a note, you can similarly use `library()`, without the name of a package, to list all of the packages you have installed that you could call with `library()`:

```
library()
```

PLOTS TO EXPLORE DATA

PLOTS TO EXPLORE DATA

Plots can be invaluable in exploring your data.

This week, we will focus on **useful**, rather than **attractive** graphs, since we are focusing on exploring rather than presenting data.

Next week, we will talk more about customization, to help you make more attractive plots that would go into final reports.

GGPLOT CONVENTIONS

Here, we'll be using functions from the `ggplot2` library, so you'll need to install that package:

```
library(ggplot2)
```

The basic steps behind creating a plot with `ggplot2` are:

- ① You'll create an object of the `ggplot` class, typically specifying the **aesthetics**;
- ② You'll add on **geoms** and other elements to create and customize the plot, using `+`.

Note: To avoid errors, end lines with `+`, don't start lines with it.

INITIALIZING THE OBJECT

Use the following conventions to initialize a ggplot object:


```
## Generic code  
object <- ggplot(dataframe, aes(x = column_1, y = column_2))
```

Notice that you first specify the dataframe with the data you want to plot and then you might specify either **mappings** or constant values for some or all of the aesthetics (aes).

PLOT AESTHETICS

Aesthetics are elements that can show certain elements of the data.

For example, color might show gender, x-position might show height, and y-position might show weight.



In this graph, the mapped aesthetics are color, x, and y.

Note: Any of these aesthetics could also be given a constant value, instead of being mapped to an element of the data. For example, all the points could be red, instead of showing gender.

PLOT AESTHETICS

Here are some common plot aesthetics you might want to specify:

Code	Description
<code>x</code>	Position on x-axis
<code>y</code>	Position on y-axis
<code>shape</code>	Shape
<code>color</code>	Color of border of elements
<code>fill</code>	Color of inside of elements
<code>size</code>	Size
<code>alpha</code>	Transparency (1: opaque; 0: transparent)
<code>linetype</code>	Type of line (e.g., solid, dashed)

PLOT AESTHETICS

Which aesthetics you must specify depend on which geoms (more on those in a second) you're adding to the plot.

You can find out the aesthetics you can use for a geom in the "Aesthetics" section of the geom's help file (e.g., `?geom_point`).

Required aesthetics are in bold in this section of the help file and optional ones are not.

ADDING GEOMS


Next, you'll want to add one or more geoms to create the plot. You can add these with `+` after the `ggplot` statement to initialize the `ggplot` object.

Some of the most common geoms are:

Plot type	ggplot2 function
Histogram (1 numeric variable)	<code>geom_histogram</code>
Scatterplot (2 numeric variables)	<code>geom_point</code>
Boxplot (1 numeric variable, possibly 1 factor variable)	<code>geom_boxplot</code>
Line graph (2 numeric variables)	<code>geom_line</code>

CONSTANT AESTHETICS

Instead of mapping an aesthetic to an element of your data, you can use a constant value for it. For example, you may want to make all the points green, rather than having color map to gender:



In this case, you'll define that aesthetic when you add the geom, outside of an aes statement.

CONSTANT AESTHETICS

If you're using a constant shape, you specify the shape with a number.

Here are the shapes that correspond to the numbers 1 to 25:

1 ○	2 △	3 +	4 ×	5 ◇
6 ▽	7 ☒	8 ✱	9 ⬡	10 ⊕
11 ⬠	12 ▤	13 ⬢	14 ◩	15 ■
16 ●	17 ▲	18 ◆	19 ●	20 ●
21 ●	22 ■	23 ◆	24 ▲	25 ▼

CONSTANT AESTHETICS

If you are using a constant color, R has character names for different colors. For example:

- blue
- blue4
- darkorchid
- deepskyblue2
- steelblue1
- dodgerblue3

Google “R colors” and search the images to find links to listings of different R colors.

USEFUL PLOT ADDITIONS

There are also a number of elements that you can add onto a `ggplot` object using `+`. A few very frequently used ones are:

Element	Description
<code>ggtitle</code>	Plot title
<code>xlab, ylab</code>	x- and y-axis labels
<code>xlim, ylim</code>	Limits of x- and y-axis

EXAMPLE PLOTS

For the example plots, I'll use a dataset in the `faraway` package called `nepali`. This gives data from a study of the health of a group of Nepalese children.

```
library(faraway)
data(nepali)
```

I'll be using functions from `dplyr` and `ggplot2`:

```
library(dplyr)
library(ggplot2)
```

EXAMPLE PLOTS

Each observation is a single measurement for a child; there can be multiple observations per child.

I'll subset out child id, sex, weight, height, and age, and I'll limit to each child's first measurement.

```
nepali <- nepali %>%  
  # Subset to certain columns  
  select(id, sex, wt, ht, age) %>%  
  # Convert id and sex to factors  
  mutate(id = factor(id),  
          sex = factor(sex, levels = c(1, 2),  
                        labels = c("Male", "Female"))) %>%  
  # Limit to first obs. per child  
  distinct(id, .keep_all = TRUE)
```

NEPALI EXAMPLE DATA

The data now looks like:


```
head(nepali)
```

##		id	sex	wt	ht	age
## 1	120011	Male	12.8	91.2	41	
## 2	120012	Female	14.9	103.9	57	
## 3	120021	Female	7.7	70.1	8	
## 4	120022	Female	12.1	86.4	35	
## 5	120023	Male	14.2	99.4	49	
## 6	120031	Male	13.9	96.4	46	

HISTOGRAM EXAMPLE

For `hist()`, the main aesthetic is `x`, the (numeric) vector for which you want to create a histogram:


```
ggplot(nepali, aes(x = ht)) +  
  geom_histogram()
```



HISTOGRAM EXAMPLE

You can try out some of the options on the histogram, like `main`, `xlab`, and `xlim`:


```
ggplot(nepali, aes(x = ht)) +  
  geom_histogram(fill = "lightblue", color = "black") +  
  ggtitle("Height of children") +  
  xlab("Height (cm)") + xlim(c(0, 120))
```



HISTOGRAM EXAMPLE

`geom_histogram` also has its own special argument, `bins`. You can use this to change the number of bins that are used to make the histogram:


```
ggplot(nepali, aes(x = ht)) +  
  geom_histogram(fill = "lightblue", color = "black",  
                 bins = 40)
```



SCATTERPLOT EXAMPLE

You can use the `geom_point` geom to create a scatterplot. For example, to create a scatterplot of height versus age for the Nepali data:


```
ggplot(nepali, aes(x = ht, y = wt)) +  
  geom_point()
```



SCATTERPLOT EXAMPLE

Again, you can use some of the options and additions to change the plot appearance:


```
ggplot(nepali, aes(x = ht, y = wt)) +  
  geom_point(color = "blue", size = 0.5) +  
  ggtitle("Weight versus Height") +  
  xlab("Height (cm)") + ylab("Weight (kg)")
```



BOXPLOT EXAMPLE

To create a boxplot, use `geom_boxplot`:


```
ggplot(nepali, aes(x = 1, y = ht)) +  
  geom_boxplot() +  
  xlab("") + ylab("Height (cm)")
```



BOXPLOT EXAMPLE

You can also do separate boxplots by a factor. In this case, you'll need to include two aesthetics (x and y) when you initialize the ggplot object.

```
ggplot(nepali, aes(x = sex, y = ht, group = sex)) +  
  geom_boxplot() +  
  xlab("Sex")+ ylab("Height (cm)")
```



GGPAIRS() EXAMPLE


There are lots of R extensions for creating other interesting plots.

For example, you can use the `ggpairs` function from the `GGally` package to plot all pairs of scatterplots for several variables.

Notice how this output shows continuous and binary variables differently.

The next slide shows the output for:

```
library(GGally)
ggpairs(nepali[, c("sex", "wt", "ht", "age")])
```



SIMPLE STATISTICS TO EXPLORE DATA

SIMPLE STATISTICS FUNCTIONS

Here are some simple statistics functions you will likely use often:

Function	Description
<code>range()</code>	Range (minimum and maximum) of vector
<code>min(), max()</code>	Minimum or maximum of vector
<code>mean(), median()</code>	Mean or median of vector
<code>table()</code>	Number of observations per level for a factor vector
<code>cor()</code>	Determine correlation(s) between two or more vectors
<code>summary()</code>	Summary statistics, depends on class

SIMPLE STATISTIC EXAMPLES

All of these take, as the main argument, the vector(s) for which you want the statistic. If there are missing values in the vector, you'll need to add an option to say what to do when them (e.g., `na.rm` or `use="complete.obs"`).

```
mean(nepali$wt, na.rm = TRUE)
```

```
## [1] 10.18432
```

```
range(nepali$ht, na.rm = TRUE)
```

```
## [1] 52.4 104.1
```

```
table(nepali$sex)
```

```
##
```

```
##   Male Female
```

```
##   107     93
```

SIMPLE STATISTIC EXAMPLES

You can also perform most of these tasks using dplyr:

```
nepali %>%  
  summarize(mean_wt = mean(wt, na.rm = TRUE))
```

```
##      mean_wt  
## 1 10.18432
```

SIMPLE STATISTIC EXAMPLES

The `cor` function can take two or more vectors. If you give it multiple values, it will give the correlation matrix for all the vectors.

```
cor(nepali$wt, nepali$ht, use = "complete.obs")
```

```
## [1] 0.9571535
```

```
cor(nepali[, c("wt", "ht", "age")], use = "complete.obs")
```

```
##           wt           ht           age
## wt  1.0000000 0.9571535 0.8931195
## ht  0.9571535 1.0000000 0.9287129
## age 0.8931195 0.9287129 1.0000000
```

SUMMARY(): A BIT OF OOP

R supports object-oriented programming. This shows up with `summary()`. R looks to see what type of object it's dealing with, and then uses a method specific to that object type.

```
summary(nepali$wt)
```

```
##      Min. 1st Qu.  Median    Mean 3rd Qu.    Max.
##      3.80    7.90   10.10   10.18   12.40   16.70
##      NA's
##         15
```

```
summary(nepali$sex)
```

```
##      Male Female
##      107      93
```

We'll see more of this when we do regression models.

A BIT MORE ON LOGICAL STATEMENTS

LOGICAL STATEMENTS

Last week, you learned a lot about logical statements and how to use them with the `subset()` function.

You can also use logical vectors, created with these statements, for a lot of other things. For example, you can use them directly in the square bracket indexing (`[..., ...]`).

LOGICAL VECTORS

A logical statement run on a vector will create a logical vector the same length as the original vector:

```
is_male <- nepali$sex == "Male"  
length(nepali$sex)
```

```
## [1] 200
```

```
length(is_male)
```

```
## [1] 200
```

LOGICAL VECTORS

The logical vector will have the value TRUE at any position where the original vector met the logical condition you tested, and FALSE anywhere else:

```
head(nepali$sex)
```

```
## [1] Male   Female Female Female Male    Male  
## Levels: Male Female
```

```
head(is_male)
```

```
## [1] TRUE FALSE FALSE FALSE TRUE TRUE
```


LOGICAL VECTORS

You can “flip” this logical vector (i.e., change every TRUE to FALSE and vice-versa) using `!`:

```
head(is_male)
```

```
## [1] TRUE FALSE FALSE FALSE TRUE TRUE
```

```
head(!is_male)
```

```
## [1] FALSE TRUE TRUE TRUE FALSE FALSE
```

LOGICAL VECTORS

You can do a few cool things now with this vector. For example, you can use it with indexing to pull out just the rows where `is_male` is TRUE:

```
head(nepali[is_male, ])
```

##		id	sex	wt	ht	age
## 1	120011	Male	12.8	91.2	41	
## 5	120023	Male	14.2	99.4	49	
## 6	120031	Male	13.9	96.4	46	
## 7	120051	Male	8.3	69.5	8	
## 9	120053	Male	15.8	96.0	54	
## 11	120062	Male	12.1	89.9	57	

LOGICAL VECTORS

Or, with `!`, just the rows where `is_male` is `FALSE`:

```
head(nepali[!is_male, ])
```

##		id	sex	wt	ht	age
## 2	120012	Female	14.9	103.9	57	
## 3	120021	Female	7.7	70.1	8	
## 4	120022	Female	12.1	86.4	35	
## 8	120052	Female	11.8	83.6	32	
## 10	120061	Female	8.7	78.5	26	
## 15	120082	Female	11.2	79.8	36	

LOGICAL VECTORS

You can also use `sum()` and `table()` to find out how many males and females are in the dataset:

```
sum(is_male); sum(!is_male)
```

```
## [1] 107
```

```
## [1] 93
```

```
table(is_male)
```

```
## is_male
```

```
## FALSE TRUE
```

```
##    93   107
```

USING REGRESSION MODELS TO EXPLORE DATA

FORMULA STRUCTURE

In R, formulas take this structure:

```
[response variable] ~ [indep. var. 1] + [indep. var. 2] + ...
```

Notice that `~` used to separate the independent and dependent variables and the `+` used to join independent variables.

You will use this type of structure in a lot of different function calls, including those for linear models (`lm`) and generalized linear models (`glm`).

LINEAR MODELS

To fit a linear model, you can use the function `lm()`. Use the `data` option to specify the dataframe from which to get the vectors. You can save the model as an object.

```
mod_a <- lm(wt ~ ht, data = nepali)
```

This call fits the model:

$$Y_i = \beta_0 + \beta_1 X_{1,i} + \epsilon_i$$

where:

- Y_i : weight of child i
- $X_{1,i}$: height of child i

USING MODEL OBJECTS

Some functions you can use on model objects:

Function	Description
<code>summary()</code>	Get a variety of information on the model, including coefficients and p-values for the coefficients
<code>coef()</code>	Pull out just the coefficients for a model
<code>residuals()</code>	Get the model residuals
<code>fitted()</code>	Get the fitted values from the model (for the data used to fit

EXAMPLES OF USING A MODEL OBJECT

For example, you can get the coefficients from the model we just fit:

```
coef(mod_a)
```

```
## (Intercept)          ht  
##   -8.694768    0.235050
```

You can also pull out the residuals:


```
head(residuals(mod_a))
```

```
##           1           2           3           4  
## 0.05820415 -0.82693141 -0.08223993 0.48644436  
##           5           6  
## -0.46920621 -0.06405608
```

EXAMPLES OF USING A MODEL OBJECT

You can also plot the data you used to fit the model and add a regression based on the model fit, using `abline()`:

```
mod_coef <- coef(mod_a)
ggplot(nepali, aes(x = ht, y = wt)) +
  geom_point(size = 0.2) +
  xlab("Height (cm)") + ylab("Weight (kg)") +
  geom_abline(aes(intercept = mod_coef[1],
                  slope = mod_coef[2]), col = "blue")
```



EXAMPLES OF USING A MODEL OBJECT

The `summary()` function gives you a lot of information about the model:

```
summary(mod_a)
```

(see next slide)

```
##
## Call:
## lm(formula = wt ~ ht, data = nepali)
##
## Residuals:
```

	Min	1Q	Median	3Q	Max
	-2.44736	-0.55708	0.01925	0.49941	2.73594

```
##
## Coefficients:
```

	Estimate	Std. Error	t value	Pr(> t)
(Intercept)	-8.694768	0.427398	-20.34	<2e-16
ht	0.235050	0.005257	44.71	<2e-16

```
##
## (Intercept) ***
## ht ***
## ---
## Signif. codes:
## 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 0.9017 on 183 degrees of freedom
## (15 observations deleted due to missingness)
```

SUMMARY FOR LM OBJECTS

The object created when you use the `summary()` function on an `lm` object has several different parts you can pull out using the `$` operator:

```
names(summary(mod_a))
```

```
## [1] "call"          "terms"
## [3] "residuals"     "coefficients"
## [5] "aliased"       "sigma"
## [7] "df"            "r.squared"
## [9] "adj.r.squared" "fstatistic"
## [11] "cov.unscaled"  "na.action"
```

```
summary(mod_a)$coefficients
```





```
##           Estimate Std. Error  t value
## (Intercept) -8.694768  0.427397843 -20.34350
## ht          0.235050  0.005256822  44.71334
##           Pr(>|t|)
## (Intercept)  7.424640e-49
## ht          1.962647e-100
```

USING `plot()` WITH `LM` OBJECTS

You can use `plot` with an `lm` object to get a number of useful diagnostic plots to check regression assumptions:

```
plot(mod_a)
```

(See next slide)



FITTING A MODEL WITH A FACTOR

You can also use binary variables or factors as independent variables in regression models:

```
mod_b <- lm(wt ~ sex, data = nepali)
summary(mod_b)$coefficients
```

```
##              Estimate Std. Error   t value
## (Intercept) 10.497980   0.3110957 33.745177
## sexFemale   -0.674724   0.4562792 -1.478752
##              Pr(>|t|)
## (Intercept) 1.704550e-80
## sexFemale   1.409257e-01
```

This call fits the model:

$$Y_i = \beta_0 + \beta_1 X_{1,i} + \epsilon_i$$

where $X_{1,i}$: sex of child i , where 0 = male; 1 = female

LINEAR MODELS VERSUS GLMs

You can fit a variety of models, including linear models, logistic models, and Poisson models, using generalized linear models (GLMs).

For linear models, the only difference between `lm` and `glm` is how they're fitting the model (least squares versus maximum likelihood). You should get the same results regardless of which you pick.

LINEAR MODELS VERSUS GLMs

For example:

```
mod_c <- glm(wt ~ ht, data = nepali)
summary(mod_c)$coef
```

```
##              Estimate Std. Error  t value
## (Intercept) -8.694768  0.427397843 -20.34350
## ht          0.235050  0.005256822  44.71334
##              Pr(>|t|)
## (Intercept)  7.424640e-49
## ht          1.962647e-100
```

```
summary(mod_a)$coef
```

```
##              Estimate Std. Error  t value
## (Intercept) -8.694768  0.427397843 -20.34350
## ht          0.235050  0.005256822  44.71334
##              Pr(>|t|)
## (Intercept)  7.424640e-49
## ht          1.962647e-100
```

GLMs

You can fit other model types with `glm()` using the `family` option:

Model type	family option
Linear	<code>family = gaussian(link = "identity")</code>
Logistic	<code>family = binomial(link = "logit")</code>
Poisson	<code>family = poisson(link = "log")</code>

LOGISTIC EXAMPLE

For example, say we wanted to fit a logistic regression for the `nepali` data of whether the probability that a child weighs more than 13 kg is associated with the child's height.

First, create a binary variable for `wt_over_13`:

```
nepali <- nepali %>%  
  mutate(wt_over_13 = wt > 13)  
head(nepali)
```

##	id	sex	wt	ht	age	wt_over_13
## 1	120011	Male	12.8	91.2	41	FALSE
## 2	120012	Female	14.9	103.9	57	TRUE
## 3	120021	Female	7.7	70.1	8	FALSE
## 4	120022	Female	12.1	86.4	35	FALSE
## 5	120023	Male	14.2	99.4	49	TRUE
## 6	120031	Male	13.9	96.4	46	TRUE

LOGISTIC EXAMPLE

Now you can fit a logistic regression:

```
mod_d <- glm(wt_over_13 ~ ht, data = nepali,
              family = binomial(link = "logit"))
summary(mod_d)$coef
```

```
##              Estimate Std. Error   z value
## (Intercept) -32.7016520  5.85196755 -5.588147
## ht           0.3495227  0.06331892  5.520036
##              Pr(>|z|)
## (Intercept) 2.295060e-08
## ht          3.389307e-08
```

Here, the model coefficient gives the **log odds** of having a weight higher than 13 kg associated with a unit increase in height.

FORMULA STRUCTURE

Here are some conventions used in R formulas:

Convention	Meaning
I()	calculate the value inside before fitting (e.g., $I(x1 + x2)$)
:	fit the interaction between two variables (e.g., $x1:x2$)
*	fit the main effects and interaction for both variables (e.g., $x1*x2$ equals $x1 + x2 + x1:x2$)
.	fit all variables other than the response (e.g., $y \sim .$)
-	do not include a variable (e.g., $y \sim . - x1$)
1	intercept (e.g., $y \sim 1$)

TO FIND OUT MORE

A great (and free-to-you) resource to find out more about using R for basic statistics:

- Introductory Statistics with R

If you want all the details about fitting linear models and GLMs in R, Faraway's books are fantastic:

- Linear Models with R
- Extending the Linear Model with R