

Python3 文法

<https://docs.python.org/3/reference/grammar.html>

Grammar for Python

NOTE WELL: You should also follow all the steps listed at
<https://devguide.python.org/grammar/>

Start symbols for the grammar:
single_input is a single interactive statement;
file_input is a module or sequence of commands read from an input
file;
eval_input is the input for the eval() functions.
NB: compound_stmt in single_input is followed by extra NEWLINE!
single_input: NEWLINE | simple_stmt | compound_stmt NEWLINE
file_input: (NEWLINE | stmt)* ENDMARKER
eval_input: testlist NEWLINE* ENDMARKER

decorator: '@' dotted_name ['(' [arglist] ')'] NEWLINE
decorators: decorator+
decorated: decorators (classdef | funcdef | async_funcdef)

async_funcdef: ASYNC funcdef
funcdef: 'def' NAME parameters ['>' test] ':' suite

parameters: '(' [typedarglist] ')'
typedarglist: (tfpdef ['=' test] (',' tfpdef ['=' test])* [',' [
 '*' [tfpdef] (',' tfpdef ['=' test])* [',' ['**' tfpdef [',']]
 | '**' tfpdef [',']]
 | '*' [tfpdef] (',' tfpdef ['=' test])* [',' ['**' tfpdef [',']]
 | '**' tfpdef [','])
tfpdef: NAME [':' test]
vararglist: (vfpdef ['=' test] (',' vfpdef ['=' test])* [',' [
 '*' [vfpdef] (',' vfpdef ['=' test])* [',' ['**' vfpdef [',']]
 | '**' vfpdef [',']]
 | '*' [vfpdef] (',' vfpdef ['=' test])* [',' ['**' vfpdef [',']]
 | '**' vfpdef [','])
)
vfpdef: NAME

stmt: simple_stmt | compound_stmt
simple_stmt: small_stmt (';' small_stmt)* [';'] NEWLINE

```

small_stmt: (expr_stmt | del_stmt | pass_stmt | flow_stmt |
            import_stmt | global_stmt | nonlocal_stmt | assert_stmt)
expr_stmt: testlist_star_expr (annassign | augassign
(yield_expr|testlist) |
            ('=' (yield_expr|testlist_star_expr))*
annassign: ':' test ['=' test]
testlist_star_expr: (test|star_expr) (',' (test|star_expr))* [',']
augassign: ('+=' | '-=' | '*=' | '@=' | '/=' | '%=' | '&=' | '|=' | '^='
|
            '<<=' | '>>=' | '**=' | '//=')
# For normal and annotated assignments, additional restrictions enforced
by the interpreter
del_stmt: 'del' exprlist
pass_stmt: 'pass'
flow_stmt: break_stmt | continue_stmt | return_stmt | raise_stmt |
yield_stmt
break_stmt: 'break'
continue_stmt: 'continue'
return_stmt: 'return' [testlist]
yield_stmt: yield_expr
raise_stmt: 'raise' [test ['from' test]]
import_stmt: import_name | import_from
import_name: 'import' dotted_as_names
# note below: the ('.' | '...') is necessary because '...' is tokenized
as ELLIPSIS
import_from: ('from' (('.' | '...')* dotted_name | ('.' | '...')+
            'import' ('*' | '(' import_as_names ')') |
import_as_names))
import_as_name: NAME ['as' NAME]
dotted_as_name: dotted_name ['as' NAME]
import_as_names: import_as_name (',' import_as_name)* [',']
dotted_as_names: dotted_as_name (',' dotted_as_name)*
dotted_name: NAME ('.' NAME)*
global_stmt: 'global' NAME (',' NAME)*
nonlocal_stmt: 'nonlocal' NAME (',' NAME)*
assert_stmt: 'assert' test [', test]

compound_stmt: if_stmt | while_stmt | for_stmt | try_stmt | with_stmt |
funcdef | classdef | decorated | async_stmt
async_stmt: ASYNC (funcdef | with_stmt | for_stmt)
if_stmt: 'if' test ':' suite ('elif' test ':' suite)* ['else' ':' suite]
while_stmt: 'while' test ':' suite ['else' ':' suite]
for_stmt: 'for' exprlist 'in' testlist ':' suite ['else' ':' suite]
try_stmt: ('try' ':' suite

```

```

        ((except_clause ':' suite)+
        ['else' ':' suite]
        ['finally' ':' suite] |
        'finally' ':' suite))
with_stmt: 'with' with_item (',' with_item)* ':' suite
with_item: test ['as' expr]
# NB compile.c makes sure that the default except clause is last
except_clause: 'except' [test ['as' NAME]]
suite: simple_stmt | NEWLINE INDENT stmt+ DEDENT

test: or_test ['if' or_test 'else' test] | lambdadef
test_nocond: or_test | lambdadef_nocond
lambdadef: 'lambda' [vararglist] ':' test
lambdadef_nocond: 'lambda' [vararglist] ':' test_nocond
or_test: and_test ('or' and_test)*
and_test: not_test ('and' not_test)*
not_test: 'not' not_test | comparison
comparison: expr (comp_op expr)*
# <> isn't actually a valid comparison operator in Python. It's here for
the
# sake of a __future__ import described in PEP 401 (which really works :-)
comp_op: '<' | '>' | '==' | '>=' | '<=' | '<>' | '!=' | 'in' | 'not in' | 'is' | 'is not'
star_expr: '*' expr
expr: xor_expr ('|' xor_expr)*
xor_expr: and_expr ('^' and_expr)*
and_expr: shift_expr ('&' shift_expr)*
shift_expr: arith_expr (('<<' | '>>') arith_expr)*
arith_expr: term (('+' | '-') term)*
term: factor (('*' | '@' | '/' | '%' | '//') factor)*
factor: ('+' | '-' | '~') factor | power
power: atom_expr ['**' factor]
atom_expr: [AWAIT] atom trailer*
atom: ('(' [yield_expr|testlist_comp] ')') |
      '[' [testlist_comp] ']' |
      '{' [dictorsetmaker] '}' |
      NAME | NUMBER | STRING+ | '...' | 'None' | 'True' | 'False')
testlist_comp: (test|star_expr) ( comp_for | (',' (test|star_expr))*
[','] )
trailer: '(' [arglist] ')' | '[' subscriptlist ']' | '.' NAME
subscriptlist: subscript (',' subscript)* [' ','']
subscript: test | [test] ':' [test] [sliceop]
sliceop: ':' [test]
exprlist: (expr|star_expr) (',' (expr|star_expr))* [' ','']

```

```

testlist: test (',' test)* [',']
dictorsetmaker: ( ((test ':' test | '**' expr)
                   (comp_for | (',' (test ':' test | '**' expr))* [',']))
|
                   ((test | star_expr)
                    (comp_for | (',' (test | star_expr))* [','])) )

classdef: 'class' NAME ['(' [arglist] ')'] ':' suite

arglist: argument (',' argument)* [',']

# The reason that keywords are test nodes instead of NAME is that using
NAME
# results in an ambiguity. ast.c makes sure it's a NAME.
# "test '=' test" is really "keyword '=' test", but we have no such token.
# These need to be in a single rule to avoid grammar that is ambiguous
# to our LL(1) parser. Even though 'test' includes '*expr' in star_expr,
# we explicitly match '*' here, too, to give it proper precedence.
# Illegal combinations and orderings are blocked in ast.c:
# multiple (test comp_for) arguments are blocked; keyword unpackings
# that precede iterable unpackings are blocked; etc.
argument: ( test [comp_for] |
            test '=' test |
            '**' test |
            '*' test )

comp_iter: comp_for | comp_if
comp_for: [ASYNC] 'for' exprlist 'in' or_test [comp_iter]
comp_if: 'if' test_nocond [comp_iter]

# not used in grammar, but may appear in "node" passed from Parser to
Compiler
encoding_decl: NAME

yield_expr: 'yield' [yield_arg]
yield_arg: 'from' test | testlist

```