

@id Maps

```
{
  "@context": {
    {
      "@version": 1.1,
      "schema": "http://schema.org/",
      "name": "schema:name",
      "body": "schema:articleBody",
      "words": "schema:wordCount",
      "post": {
        "@id": "schema:blogPost",
        "@container": "@id"
      }
    },
    "@id": "http://example.com/",
    "@type": "schema:Blog",
    "name": "World Financial News",
    "post": {
      "http://example.com/posts/1/en": {
        "body": "World commodities were up today with heavy trading of crude oil...",
        "words": 1539
      },
      "http://example.com/posts/1/de": {
        "body": "Die Werte an Warenbörsen stiegen im Sog eines starken Handels von Rohöl...",
        "words": 1204
      }
    }
  }
}
```

- Also supports @type and @graph Maps.

Graph Containers (@graph Maps)

- Property values can reference anonymously/implicitly named graphs:

```
{
  "@context": {
    "@version": 1.1,
    "@base": "http://dbpedia.org/resource/",
    "said": "http://example.com/said",
    "wrote": {"@id": "http://example.com/wrote", "@container": "@graph"}
  },
  "@id": "William_Shakespeare",
  "wrote": {
    "@id": "Richard_III_of_England",
    "said": "My kingdom for a horse"
  }
}
```