

Framing Improvements (@included)

```
{
  "@context": {
    "@version": 1.1,
    "@vocab": "http://example.org/"
  },
  "@requireAll": true,
  "foo": "bar",
  "prop": "value",
  "@included": [{
    "@requireAll": true,
    "foo": "bar",
    "prop": "value2"
  }]
}
```

- For adding nodes without a direct property relationship.

Framing Improvements (Value Patterns)

Exact Value Match

```
{
  "@context": {"ex": "http://example.org/"},
  "@id": "ex:Sub1",
  "ex:p": "P",
  "ex:q": {"@value": "Q", "@type": "ex:q"},
  "ex:r": {"@value": "R", "@language": "r"}
}
```

Match on exact type/ language but wildcard value

```
{
  "@context": {"ex": "http://example.org/"},
  "ex:p": {"@value": {}},
  "ex:q": {"@value": {}, "@type": "ex:q"},
  "ex:r": {"@value": {}, "@language": "r"}
}
```

Match on exact value wildcard type/language

```
{
  "@context": {"ex": "http://example.org/"},
  "ex:q": {"@value": "Q", "@type": {}}
}
```

Match on no value

```
{
  "@context": {"ex": "http://example.org/"},
  "ex:p": {"@value": {}, "@type": []},
  "ex:q": {"@value": {}, "@type": "ex:q"},
  "ex:r": {"@value": {}, "@language": "r"}
}
```

- Also match on any selected value/type/language with [...]