

# fabric8io/docker-maven-plugin

Roland Huß

Version 0.30.0, 2019-04-21

# docker-maven-plugin

1. Introduction	2
1.1. Building Images	2
1.2. Running Containers	2
1.3. Configuration	2
1.4. Example	3
1.5. Features	5
2. Installation	6
3. Global configuration	8
4. Image configuration	13
4.1. Image Names	14
4.2. Container Names	14
5. Maven Goals	16
5.1. <b>docker:build</b>	16
5.1.1. Configuration	20
5.1.2. Assembly	25
5.1.3. Startup Arguments	29
5.1.4. Build Args	30
5.1.5. Healthcheck	30
5.2. <b>docker:start</b>	31
5.2.1. Configuration	32
5.2.2. Environment and Labels	35
5.2.3. Port Mapping	36
5.2.4. Links	38
5.2.5. Network	39
5.2.6. Depends-On	40
5.2.7. Restart Policy	41
5.2.8. Volumes	41
5.2.9. Wait	43
5.2.10. Logging	45
5.3. <b>docker:stop</b>	47
5.4. <b>docker:push</b>	48
5.5. <b>docker:watch</b>	49
5.6. <b>docker:remove</b>	52
5.7. <b>docker:logs</b>	53
5.8. <b>docker:source</b>	54
5.9. <b>docker:save</b>	55
5.10. <b>docker:volume-create</b>	56
5.11. <b>docker:volume-remove</b>	57

6. External Configuration .....	58
6.1. Properties .....	58
6.2. Docker Compose .....	69
6.2.1. Limitations .....	71
7. Registry handling .....	72
8. Authentication .....	74
8.1. Pull vs. Push Authentication .....	75
8.2. OpenShift Authentication .....	76
8.3. Password encryption .....	77
8.4. Extended Authentication .....	77
9. Implicit properties .....	78
10. Further reading .....	79



# Chapter 1. Introduction

This is a Maven plugin for managing Docker images and containers. It focuses on two major aspects for a Docker build integration:

## 1.1. Building Images

One purpose of this plugin is to create Docker images holding the actual application. This is done with the `docker:build` goal. It is easy to include build artefacts and their dependencies into an image.

Several ways for configuring the builds are supported:

- An own configuration syntax can be used to create a Dockerfile. For specifying artefacts and other files, the plugin uses the assembly descriptor format from the maven-assembly-plugin to copy over those file into the Docker image.
- An external Dockerfile can be specified in which Maven properties can be inserted. This is also the default mode, if only a single image should be built and a top-level `Dockerfile` exists. See [Simple Dockerfile build](#) for details of this zero XML configuration mode.

Images that are built with this plugin can be pushed to public or private Docker registries with `docker:push`.

## 1.2. Running Containers

With this plugin it is possible to run completely isolated integration tests so you don't need to take care of shared resources. Ports can be mapped dynamically and made available as Maven properties to your integration test code.

Multiple containers can be managed at once, which can be linked together or share data via volumes. Containers are created and started with the `docker:start` goal and stopped and destroyed with the `docker:stop` goal. For integration tests both goals are typically bound to the pre-integration-test and post-integration-test phase, respectively. It is recommended to use the maven-failsafe-plugin for integration testing in order to stop the docker container even when the tests fail.

For proper isolation, container exposed ports can be dynamically and flexibly mapped to local host ports. It is easy to specify a Maven property which will be filled in with a dynamically assigned port after a container has been started. This can then be used as parameter for integration tests to connect to the application.

## 1.3. Configuration

The plugin configuration contains a global part and a list of image-specific configuration within a `<images>` list, where each image is defined within a `<image>` tag. See [below](#) for an example.

The `global part` contains configuration applicable to all images like the Docker URL or the path to the SSL certificates for communication with the Docker Host.

Then, each specific image configuration has three parts:

- A general image part containing the image name and alias.
- A `<build>` configuration specifying how images are built
- A `<run>` configuration describing how containers should be created and started.

The `<build>` and `<run>` parts are optional and can be omitted.

## 1.4. Example

In the following examples, two images are specified. One is the official PostgreSQL 9 image from Docker Hub, which internally is referenced with an alias "database". It only has a `<run>` section which declares that the startup should wait until the given text pattern is matched in the log output. Next is a "service" image, which has a `<build>` section. It creates an image which has artifacts and dependencies in the `/maven` directory (and which are specified with an assembly descriptor). Additionally, it specifies the startup command for the container, which in this example fires up a microservice from a jar file copied over via the assembly descriptor. It also exposes port 8080. In the `<run>` section this port is mapped to a dynamically chosen port and then assigned to the Maven property `${tomcat.port}`. This property could be used, for example, by an integration test to access this microservice. An important part is the `<links>` section which indicates that the image with the alias of "database" is linked into the "service" container, which can access the internal ports in the usual Docker way (via environment variables prefixed with `DB_`).

Images can be specified in any order and the plugin will take care of the proper startup order (and will bail out if it detects circular dependencies).

```
<configuration>
  <images>
    <image>
      <alias>service</alias> ①
      <name>fabric8/docker-demo:${project.version}</name>

      <build> ②
        <from>java:8</from> ③
        <assembly>
          <descriptor>docker-assembly.xml</descriptor> ④
        </assembly>
        <cmd> ⑤
          <shell>java -jar /maven/service.jar</shell>
        </cmd>
      </build>

      <run> ⑥
        <ports> ⑦
          <port>tomcat.port:8080</port>
        </ports>
        <wait> ⑧
          <http>
            <url>http://localhost:${tomcat.port}/access</url>
          </http>
          <time>10000</time>
        </wait>
        <links> ⑨
          <link>database:db</link>
        </links>
      </run>
    </image>

    <image>
      <alias>database</alias> ⑩
      <name>postgres:9</name>
      <run>
        <wait> ⑪
          <log>database system is ready to accept connections</log>
          <time>20000</time>
        </wait>
      </run>
    </image>
  </images>
</configuration>
```

① Image configuration for a Java service with alias "service" and name `fabric8/docker-demo:${project.version}`

② [build configuration](#) defines how a Docker image should be created

- ③ Base image, in this case `java:8`
- ④ Content of the image can be specified with an `assembly descriptor`
- ⑤ `Default command` to run when a container is created.
- ⑥ `Run configuration` defines how a container should be created from this image
- ⑦ `Port mapping` defines how container ports should be mapped to host ports
- ⑧ `Wait` section which is a readiness check when starting the service
- ⑨ `Network link` describes how this service's container is linked to the database container
- ⑩ Second image is a plain database image which is only needed for running (hence there is no `<build>` section). The alias is used in the network link section above
- ⑪ Wait until the corresponding output appears on stdout when starting the Docker container.

## 1.5. Features

Some other highlights, in random order:

- Auto pulling of images with a progress indicator
- Waiting for a container to startup based on time, the reachability of an URL, or a pattern in the log output
- Support for SSL `Authentication` and OpenShift credentials
- Docker machine support
- Flexible registry handling (i.e. registries can be specified as metadata)
- Specification of `encrypted` registry passwords for push and pull in `~/m2/settings.xml` (i.e., outside the `pom.xml`)
- Color output
- `Watching` on project changes and automatic recreation of image
- `Properties` as alternative to the XML configuration
- Support for Docker daemons accepting http or https request via TCP and for Unix sockets



## Chapter 2. Installation

This plugin is available from Maven central and can be connected to pre- and post-integration phase as seen below. The configuration and available goals are described below.

*Example*

```
<plugin>
  <groupId>io.fabric8</groupId>
  <artifactId>docker-maven-plugin</artifactId>
  <version>0.30.0</version>

  <configuration>
    ....
    <images>
      <!-- A single's image configuration -->
      <image>
        ....
      </image>
      ....
    </images>
  </configuration>

  <!-- Connect start/stop to pre- and
  post-integration-test phase, respectively if you want to start
  your docker containers during integration tests -->
  <executions>
    <execution>
      <id>start</id>
      <phase>pre-integration-test</phase>
      <goals>
        <!-- "build" should be used to create the images with the
        artifact -->
        <goal>build</goal>
        <goal>start</goal>
      </goals>
    </execution>
    <execution>
      <id>stop</id>
      <phase>post-integration-test</phase>
      <goals>
        <goal>stop</goal>
      </goals>
    </execution>
  </executions>
</plugin>
```

When working with this plugin you can use an own packaging with a specialized lifecycle in order to keep your pom files small. Three packaging variants are available:

- **docker** : This binds `docker:build` to the package phase and `docker:start` / `docker:stop` to the pre- and post-integration phase respectively. Also `docker:push` is bound to the deploy phase.
- **docker-build** : Much like the *docker* packaging, except that there are no integration tests configured by default.
- **docker-tar** : Create a so called *Docker tar* archive which is used as the artifact and which later can be used for building an image. It contains essentially a `Dockerfile` with supporting files. See [docker:source](#) for more details.

These packaging definitions include the *jar* lifecycle methods so they are well suited for simple Microservice style projects.

#### Example

```
<pom>
  <artifactId>demo</artifactId>
  <version>0.0.1</version>
  <packaging>docker</packaging>
  ...
  <build>
    <plugins>
      <plugin>
        <groupId>io.fabric8</groupId>
        <artifactId>docker-maven-plugin</artifactId>
        <extensions>true</extensions>
        <configuration>
          <images>
            <image>
              ...
            </image>
          </images>
        </configuration>
      </plugin>
    </plugins>
    ....
  </build>
</pom>
```

This will create the jar (if any), build the Docker images, start the configured Docker containers, runs the integration tests, stops the configured Docker container when you enter `mvn install`. With `mvn deploy` you can additionally push the images to a Docker configuration. Please note the `<extensions>true</extensions>` which is mandatory when you use a custom lifecycle.

The rest of this manual is now about how to configure the plugin for your images.

# Chapter 3. Global configuration

Global configuration parameters specify overall behavior like the connection to the Docker host. The corresponding system properties which can be used to set it from the outside are given in parentheses.

The docker-maven-plugin uses the Docker remote API so the URL of your Docker Daemon must somehow be specified. The URL can be specified by the dockerHost or machine configuration, or by the `DOCKER_HOST` environment variable.

The Docker remote API supports communication via SSL and authentication with certificates. The path to the certificates can be specified by the certPath or machine configuration, or by the `DOCKER_CERT_PATH` environment variable.

Table 1. Global Configuration

Element	Description	Property
<b>apiVersion</b>	Use this variable if you are using an older version of docker not compatible with the current default use to communicate with the server.	<code>docker.apiVersion</code>
<b>authConfig</b>	Authentication information when pulling from or pushing to Docker registry. There is a dedicated section <a href="#">Authentication</a> for how doing security.	
<b>autoCreateCustomNetworks</b>	Create automatically Docker networks during <code>docker:start</code> and remove it during <code>docker:stop</code> if you provide a custom network in the run configuration of an image. The default is <code>false</code> .	<code>docker.autoCreateCustomNetworks</code>
<b>autoPull</b>	Decide how to pull missing base images or images to start. This option is <b>deprecated</b> , please use <code>imagePullPolicy</code> instead.  The following values are supported: <ul style="list-style-type: none"><li>• <code>on</code> or <code>once</code>: Automatic download any missing images (default)</li><li>• <code>off</code>: Automatic pulling is switched off always</li><li>• <code>always</code>: Pull images always even when they already exist locally.</li></ul>	<code>docker.autoPull</code>
<b>certPath</b>	Path to SSL certificate when SSL is used for communicating with the Docker daemon. These certificates are normally stored in <code>~/.docker/</code> . With this configuration the path can be set explicitly. If not set, the fallback is first taken from the environment variable <code>DOCKER_CERT_PATH</code> and then as last resort <code>~/.docker/</code> . The keys in this are expected with it standard names <code>ca.pem</code> , <code>cert.pem</code> and <code>key.pem</code> . Please refer to the <a href="#">Docker documentation</a> for more information about SSL security with Docker.	<code>docker.certPath</code>

Element	Description	Property
<b>dockerHost</b>	<p>The URL of the Docker Daemon. If this configuration option is not given, then the optional <code>&lt;machine&gt;</code> configuration section is consulted. The scheme of the URL can be either given directly as <code>http</code> or <code>https</code> depending on whether plain HTTP communication is enabled or SSL should be used. Alternatively the scheme could be <code>tcp</code> in which case the protocol is determined via the IANA assigned port: 2375 for <code>http</code> and 2376 for <code>https</code>. Finally, Unix sockets are supported by using the scheme <code>unix</code> together with the filesystem path to the unix socket. The discovery sequence used by the docker-maven-plugin to determine the URL is:</p> <ol style="list-style-type: none"> <li>1. value of <b>dockerHost</b> (<code>docker.host</code>)</li> <li>2. the Docker host associated with the docker-machine named in <code>&lt;machine&gt;</code>, i.e. the <code>DOCKER_HOST</code> from <code>docker-machine env</code>. See <a href="#">below</a> for more information about Docker machine support. If <code>&lt;machine&gt;</code> is not set, then no docker-machine detection is used.</li> <li>3. the value of the environment variable <code>DOCKER_HOST</code>.</li> <li>4. <code>/var/run/docker.sock</code> if it is a readable socket (Unix &amp; OS X).</li> <li>5. <code>./pipe/docker_engine</code> if it is a readable named pipe (Windows)</li> </ol>	<code>docker.host</code>
<b>filter</b>	In order to temporarily restrict the operation of plugin goals this configuration option can be used. Typically this will be set via the system property <code>docker.filter</code> when Maven is called. The value can be a single image name (either its alias or full name) or it can be a comma separated list with multiple image names. Any name which doesn't refer an image in the configuration will be ignored.	<code>docker.filter</code>
<b>imagePullPolicy</b>	<p>Specify whether images should be pull when looking for base images while building or images for starting. This property can take the following values (case insensitive):</p> <ul style="list-style-type: none"> <li>• <code>IfNotPresent</code>: Automatic download any missing images (default)</li> <li>• <code>Never</code> : Automatic pulling is switched off always</li> <li>• <code>Always</code> : Pull images always even when they already exist locally.</li> </ul> <p>By default a progress meter is printed out on the console, which is omitted when using Maven in batch mode (option <code>-B</code>). A very simplified progress meter is provided when using no color output (i.e. with <code>-Ddocker.useColor=false</code>).</p>	<code>docker.imagePullPolicy</code>
<b>logDate</b>	Date format which is used for printing out container logs. This configuration can be overwritten by individual run configurations and described below. The format is described in <a href="#">Logging</a> .	<code>docker.logDate</code>
<b>logStdout</b>	For all container logging to standard output if set to <code>true</code> , regardless whether a <code>file</code> for log output is specified. See also <a href="#">Logging</a>	<code>docker.logStdout</code>

Element	Description	Property
<b>machine</b>	Docker machine configuration. See <a href="#">Docker Machine</a> for possible values	
<b>maxConnections</b>	Number of parallel connections are allowed to be opened to the Docker Host. For parsing log output, a connection needs to be kept open (as well for the wait features), so don't put that number to low. Default is 100 which should be suitable for most of the cases.	<code>docker.maxConnections</code>
<b>outputDirectory</b>	Default output directory to be used by this plugin. The default value is <code>target/docker</code> and is only used for the goal <code>docker:build</code> .	<code>docker.target.dir</code>
<b>portPropertyFile</b>	Global property file into which the mapped properties should be written to. The format of this file and its purpose are also described in <a href="#">Port Mapping</a> .	
<b>registry</b>	Specify globally a registry to use for pulling and pushing images. See <a href="#">Registry handling</a> for details.	<code>docker.registry</code>
<b>skip</b>	With this parameter the execution of this plugin can be skipped completely.	<code>docker.skip</code>
<b>skipBuild</b>	If set no images will be build (which implies also <i>skip.tag</i> ) with <code>docker:build</code>	<code>docker.skip.build</code>
<b>skipPush</b>	If set dont push any images even when <code>docker:push</code> is called.	<code>docker.skip.push</code>
<b>skipRun</b>	If set dont create and start any containers with <code>docker:start</code> or <code>docker:run</code>	<code>docker.skip.run</code>
<b>skipTag</b>	If set to <code>true</code> this plugin won't add any tags to images that have been built with <code>docker:build</code> . If set to <code>true</code> this plugin won't push any tags with <code>docker:push</code> . If set to <code>true</code> this plugin won't remove any tags with <code>docker:remove</code> .	<code>docker.skip.tag</code>
<b>skipMachine</b>	Skip using docker machine in any case	<code>docker.skip.machine</code>
<b>sourceDirectory</b>	Default directory that contains the assembly descriptor(s) used by the plugin. The default value is <code>src/main/docker</code> . This option is only relevant for the <code>docker:build</code> goal.	<code>docker.source.dir</code>
<b>useColor</b>	Whether to use colored log output. By default this is switched on when running on a console, off otherwise.	<code>docker.useColor</code>

Element	Description	Property
<b>verbose</b>	<p>String attribute for switching on verbose output on standard output (stdout). It takes a comma separated list of string values to switch on various verbosity groups.</p> <p>The currently known groups are:</p> <p><b>build</b> Print out Docker build instructions</p> <p><b>api</b> API calls to the Docker daemons are logged</p> <p><b>all</b> All levels are enabled</p> <p>If you set an empty string (or only e.g. <code>-Ddocker.verbose</code>) then the "build" group is enabled. You can also use "true" / "false" to switch on / off verbose logging.</p> <p>Default is that verbose logging is disabled.</p>	<code>docker.verbose</code>

#### Example

```
<configuration>
  <dockerHost>https://localhost:2376</dockerHost>
  <certPath>src/main/dockerCerts</certPath>
  <useColor>true</useColor>
  . . . . .
</configuration>
```

#### Docker Machine

This plugin supports also Docker machine (which must be installed locally, of course). A Docker machine configuration can be provided with a top-level `<machine>` configuration section. This configuration section knows the following options:

Table 2. Docker Machine Options

Element	Description
<b>name</b>	Docker machine's name. Default is <code>default</code>
<b>autoCreate</b>	if set to <code>true</code> then a Docker machine will automatically created. Default is <code>false</code> .
<b>regenerateCertsAfterStart</b>	if set to <code>true</code> then certificates will be regenerated after starting the Docker Machine. This is useful if using the AWS EC2 driver, which will assign machines new IP addresses after each start. Default is <code>false</code> .
<b>createOptions</b>	Map with options for Docker machine when auto-creating a machine. See the docker machine documentation for possible options.

When no Docker host is configured or available as an environment variable, then the configured Docker machine is used. If the machine exists but is not running, it is started automatically. If it does not exist but `autoCreate` is true, then the machine is created and started. Otherwise, an error is printed. Please note, that a machine which has been created because of `autoCreate` gets never deleted by docker-maven-plugin. This needs to be done manually if required.

In absence of a `<machine>` configuration section the Maven property `docker.machine.name` can be used to provide the name of a Docker machine. Similarly, the property `docker.machine.autoCreate` can be set to true for creating a Docker machine, too.

You can use the property `docker.skip.machine` if you want to override the internal detection mechanism to always disable docker machine support.

#### Example

```
<!-- Work with a docker-machine -->
<configuration>
  <machine>
    <name>maven</name>
    <autoCreate>true</autoCreate>
    <createOptions>
      <driver>virtualbox</driver>
      <virtualbox-cpu-count>2</virtualbox-cpu-count>
    </createOptions>
  </machine>
  . . . . .
</configuration>
```

# Chapter 4. Image configuration

The plugin's configuration is centered around *images*. These are specified for each image within the `<images>` element of the configuration with one `<image>` element per image to use.

The `<image>` element can contain the following sub elements:

Table 3. Image Configuration

Element	Description
<b>name</b>	Each <code>&lt;image&gt;</code> configuration has a mandatory, unique docker repository <i>name</i> . This can include registry and tag parts, but also placeholder parameters. See below for a detailed explanation.
<b>alias</b>	Shortcut name for an image which can be used for identifying the image within this configuration. This is used when linking images together or for specifying it with the global <b>image</b> configuration element.
<b>registry</b>	Registry to use for this image. If the <b>name</b> already contains a registry this takes precedence. See <a href="#">Registry handling</a> for more details.
<b>build</b>	Element which contains all the configuration aspects when doing a <b>docker:build</b> . This element can be omitted if the image is only pulled from a registry e.g. as support for integration tests like database images.
<b>run</b>	Element which describe how containers should be created and run when <b>docker:start</b> is called. If this image is only used a <i>data container</i> (i.e. is supposed only to be mounted as a volume) for exporting artifacts via volumes this section can be missing.
<b>external</b>	Specification of external configuration as an alternative to this XML based configuration with <code>&lt;run&gt;</code> and <code>&lt;build&gt;</code> . It contains a <code>&lt;type&gt;</code> element specifying the handler for getting the configuration. See <a href="#">External configuration</a> for details.

Either a `<build>` or `<run>` section must be present (except when you are using the [simple Dockerfile build](#) mode). These are explained in details in the corresponding goal sections.

Example

```
<configuration>
....
<images>
  <image>
    <name>%g/docker-demo:0.1</name>
    <alias>service</alias>
    <run>....</run>
    <build>....</build>
  </image>
</images>
</configuration>
```



## 4.1. Image Names

When specifying the image name in the configuration with the `<name>` field you can use several placeholders which are replaced during runtime by this plugin. In addition you can use regular Maven properties which are resolved by Maven itself.

Placeholder	Description
<code>%g</code>	The last part of the Maven group name, sanitized so that it can be used as username on GitHub. Only the part after the last dot is used. E.g. for a group id <code>io.fabric8</code> this placeholder would insert <code>fabric8</code>
<code>%a</code>	A sanitized version of the artefact id so that it can be used as part of an Docker image name. I.e. it is converted to all lower case (as required by Docker)
<code>%v</code>	The project version. Synonym to <code>\${project.version}</code>
<code>%l</code>	If the project version ends with <code>-SNAPSHOT</code> then this placeholder is <code>latest</code> , otherwise its the full version (same as <code>%v</code> )
<code>%t</code>	If the project version ends with <code>-SNAPSHOT</code> this placeholder resolves to <code>snapshot-&lt;timestamp&gt;</code> where timestamp has the date format <code>yyMMdd-HHmss-SSSS</code> (eg <code>snapshot-20170501-120000-0000</code> ). This feature is especially useful during development in order to avoid conflicts when images are to be updated which are still in use. You need to take care yourself of cleaning up old images afterwards, though.

## 4.2. Container Names

Similar to image name placeholders, for starting and stopping containers and alternate set of placeholders can be configured in order to the name the containers to create.

These placeholders can be used in the top-level configuration value `containerNamePattern` which is used globally for every container that is created. This global pattern can be overwritten individually by each image's `run` configuration. If neither is given, then by default the pattern `%n-%i` is used.

When specifying the container name pattern the following placeholders can be used:

Placeholder	Description
<code>%a</code>	The <code>&lt;alias&gt;</code> of an image which must be set. The alias is set in the top-level image configuration
<code>%n</code>	A sanitized version of the image's short name from which this container is created. "Sanitized" means that any non letter, digit, dot or dash is replaced by an underscore.
<code>%t</code>	The build time stamp. This is the timestamp which created during the building of an image and locally cached. A rebuild of the image will update the timestamp.
<code>%i</code>	An index which is incremented if a container has already been created. With this parameter it is easily possible to have multiple, similar containers. See the example below for more details.

You can combine the placeholders in any combination and will be resolved during `docker:start`,

`docker:stop` and `docker:watch`.

The following example is using a container name pattern of `%n-%i` which is also the default. Given an image `fabric8io/dmp-sample-jolokia:latest`, then during `mvn docker:start` a container with the name `dmp-sample-jolokia-1` is first tried. If there is already a container with this name, then `dmp-sample-jolokia-2` is the second attempt. This goes on until a "free" name is found.

Similar, when stopping containers with `mvn docker:stop` then only the container with the highest index is stopped. However, if you don't use an index via `%i` then *all* containers started with `docker:start` are stopped. Use `mvn docker:stop -Ddocker.allContainers` to also stop every container named via a `%i` pattern.

# Chapter 5. Maven Goals

This plugin supports the following goals which are explained in detail in the next sections.

Table 4. Plugin Goals

Goal	Description	Default Lifecycle Phase
<code>docker:build</code>	Build images	install
<code>docker:start</code> or <code>docker:run</code>	Create and start containers	pre-integration-test
<code>docker:stop</code>	Stop and destroy containers	post-integration-test
<code>docker:push</code>	Push images to a registry	deploy
<code>docker:watch</code>	Watch for doing rebuilds and restarts	
<code>docker:remove</code>	Remove images from local docker host	post-integration-test
<code>docker:logs</code>	Show container logs	
<code>docker:source</code>	Attach docker build archive to Maven project	package
<code>docker:save</code>	Save images to a file	
<code>docker:volume-create</code>	Create a volume for containers to share data	pre-integration-test
<code>docker:volume-remove</code>	Remove a volume	post-integration-test

Note that all goals are orthogonal to each other. For example in order to start a container for your application you typically have to build its image before. `docker:start` does **not** imply building the image so you should use it then in combination with `docker:build`.

## 5.1. docker:build

This goal will build all images which have a `<build>` configuration section, or, if the global configuration variable `filter` (property: `docker.filter`) is set, only the images contained in this variable (comma separated) will be built.

There are two different modes how images can be built:

### Inline plugin configuration

With an inline plugin configuration all information required to build the image is contained in the plugin configuration. By default its the standard XML based configuration for the plugin but can be switched to a property based configuration syntax as described in the section [External configuration](#). The XML configuration syntax is recommended because of its more structured and typed nature.

When using this mode, the Dockerfile is created on the fly with all instructions extracted from the configuration given.

### External Dockerfile or Docker archive

Alternatively an external Dockerfile template or Docker archive can be used. This mode is switched on by using one of these three configuration options within

- **contextDir** specifies docker build context if an external dockerfile is located outside of Docker build context. If not specified, Dockerfile's parent directory is used as build context.
- **dockerFile** specifies a specific Dockerfile path. The Docker build context directory is set to **contextDir** if given. If not the directory by default is the directory in which the Dockerfile is stored.
- **dockerArchive** specifies a previously saved image archive to load directly. Such a tar archive can be created with **docker save** or the **docker:save** goal. If a **dockerArchive** is provided, no **dockerFile** or **dockerFileDir** must be given.
- **dockerFileDir** (*deprecated*, use **contextDir**) specifies a directory containing a Dockerfile that will be used to create the image. The name of the Dockerfile is **Dockerfile** by default but can be also set with the option **dockerFile** (see below).

All paths can be either absolute or relative paths (except when both **dockerFileDir** and **dockerFile** are provided in which case **dockerFile** must not be absolute). A relative path is looked up in **\${project.basedir}/src/main/docker** by default. You can make it easily an absolute path by using **\${project.basedir}** in your configuration.

#### *Adding assemblies in Dockerfile mode*

Any additional files located in the **dockerFileDir** directory will also be added to the build context as well. You can also use an assembly if specified in an **assembly configuration**. However, you need to add the files on your own in the Dockerfile with an **ADD** or **COPY** command. The files of the assembly are stored in a build context relative directory **maven/** but can be changed by changing the assembly name with the option **<name>** in the assembly configuration.

E.g. the files can be added with

#### *Example*

```
COPY maven/ /my/target/directory
```

so that the assembly files will end up in **/my/target/directory** within the container.

If this directory contains a **.maven-dockerignore** (or alternatively, a **.maven-dockerexclude** file), then it is used for excluding files for the build. Each line in this file is treated as a **FileSet exclude pattern** as used by the **maven-assembly-plugin**. It is similar to **.dockerignore** when using Docker but has a slightly different syntax (hence the different name). **Example .maven-dockerexclude or .maven-dockerignore** is an example which excludes all compiled Java classes.

#### *Example 1. Example .maven-dockerexclude or .maven-dockerignore*

```
target/classes/** ①
```

① Exclude all compiled classes

If this directory contains a `.maven-dockerinclude` file, then it is used for including only those files for the build. Each line in this file is also treated as a `FileSet exclude pattern` as used by the `maven-assembly-plugin`. Example `.maven-dockerinclude` shows how to include only jar file that have build to the Docker build context.

Example 2. Example `.maven-dockerinclude`

```
target/*.jar ①
```

① Only add jar file to you Docker build context.

Except for the `assembly configuration` all other configuration options are ignored for now.

### Simple Dockerfile build

When only a single image should be built with a Dockerfile no XML configuration is needed at all. All what need to be done is to place a `Dockerfile` into the top-level module directory, alongside to `pom.xml`. You can still configure `global aspects` in the plugin configuration, but as soon as you add an `<image>` in the XML configuration, you need to configure also the build explicitly.

The image name is by default set from the Maven coordinates (`%g/%a:%l`, see `Image Name` for an explanation of the params which are essentially the Maven GAV) This name can be set with the property `docker.name`.

If you want to add some `<run>` configuration to this image for starting it with `docker:run` then you can add an image configuration but without a `<build>` section in which case the Dockerfile will be picked up, too. This works only for a single image, though.

### Filtering

fabric8-maven-plugin filters given Dockerfile with Maven properties, much like the `maven-resource-plugin` does. Filtering is enabled by default and can be switched off with a build config `<filter>false</filter>`. Properties which we want to replace are specified with the `${..}` syntax. Replacement includes Maven project properties such as `${project.artifactId}`, properties set in the build, command-line properties, and system properties. Unresolved properties remain untouched.

This partial replacement means that you can easily mix it with Docker build arguments and environment variable reference, but you need to be careful. If you want to be more explicit about the property delimiter to clearly separate Docker properties and Maven properties you can redefine the delimiter. In general, the `filter` option can be specified the same way as delimiters in the resource plugin. In particular, if this configuration contains a `*` then the parts left, and right of the asterisks are used as delimiters.

For example, the default `<filter>${*}</filter>` parse Maven properties in the format that we know. If you specify a single character for `<filter>` then this delimiter is taken for both, the start and the end. E.g a `<filter>@</filter>` triggers on parameters in the format `@...@`, much like in the `maven-invoker-plugin`. Use something like this if you want to clearly separate from Docker builds args. This form of property replacement works for Dockerfile only. For replacing other data in other files targeted for the Docker image, please use the `maven-resource-plugin` or an `assembly configuration` with filtering to make them available in the docker build context.

### Example

The following example uses a Dockerfile in the directory `src/main/docker/demo` and replaces all properties in the format `@property@` within the Dockerfile.

```
<plugin>
  <configuration>
    <images>
      <image>
        <name>user/demo</name>
        <build>
          <dockerFileDir>demo</dockerFileDir>
          <filter>@</filter>
        </build>
      </image>
    </images>
  </configuration>
  ...
</plugin>
```

### Build Plugins

This plugin supports so call **dmp-plugins** which are used during the build phase. dmp-plugins are enabled by just declaring a dependency in the plugin declaration:

```
<plugin>
  <groupId>io.fabric8</groupId>
  <artifactId>docker-maven-plugin</artifactId>

  <dependencies>
    <dependency>
      <groupId>io.fabric8</groupId>
      <artifactId>run-java-sh</artifactId>
      <version>1.2.2</version>
    </dependency>
  </dependencies>
</plugin>
```

These plugins contain a descriptor `META-INF/maven/io.fabric8/dmp-plugin` with class names, line-by-line:

```
io.fabric8.runsh.RunShLoader
```

During a build with `docker:build`, those classes are loaded and certain fixed method are called.

The following methods are supported:

Method	Description
<b>addExtraFiles</b>	A <i>static</i> method called by dmp with a single <b>File</b> argument. This will point to a directory <b>docker-extra</b> which can be referenced easily by a Dockerfile or an assembly. A dmp plugin typically will create an own subdirectory to avoid a clash with other dmp-plugins.

If a configured plugin does not provide method of this name and signature, then it will be simply ignored. Also, no interface needs to be implemented to keep the coupling low.

The following official dmp-plugins are known and supported:

Name	G,A	Description
<a href="#">run-java.sh</a>	<a href="#">fabric8.io</a> , <a href="#">run-java</a>	General purpose startup script fo running Java applications. The dmp plugin creates a <b>target/docker-extra/run-java/run-java.sh</b> which can be included in a Dockerfile (see the example above). See the <a href="#">run-java.sh Documentation</a> for more details.

Check out [samples/run-java](#) for a fully working example.

### 5.1.1. Configuration

All build relevant configuration is contained in the **<build>** section of an image configuration. The following configuration options are supported:

Table 5. Build configuration (**<image>** )

Element	Description
<b>assembly</b>	specifies the assembly configuration as described in <a href="#">Build Assembly</a>
<b>args</b>	Map specifying the value of <a href="#">Docker build args</a> which should be used when building the image with an external Dockerfile which uses build arguments. The key-value syntax is the same as when defining Maven properties (or <b>labels</b> or <b>env</b> ). This argument is ignored when no external Dockerfile is used. Build args can also be specified as properties as described in <a href="#">Build Args</a>
<b>buildOptions</b>	Map specifying the build options to provide to the docker daemon when building the image. These options map to the ones listed as query parameters in the <a href="#">Docker Remote API</a> and are restricted to simple options (e.g.: memory, shmsize). If you use the respective configuration options for build options natively supported by the build configuration (i.e. <b>noCache</b> , <b>cleanup=remove</b> for buildoption <b>forcerm=1</b> and <b>args</b> for build args) then these will override any corresponding options given here. The key-value syntax is the same as when defining environment variables or labels as described in <a href="#">Setting Environment Variables and Labels</a> .
<b>cleanup</b>	Cleanup dangling (untagged) images after each build (including any containers created from them). Default is <b>try</b> which tries to remove the old image, but doesn't fail the build if this is not possible because e.g. the image is still used by a running container. Use <b>remove</b> if you want to fail the build and <b>none</b> if no cleanup is requested.

Element	Description
<b>contextDir</b>	Path to a directory used for the build's context. You can specify the <b>Dockerfile</b> to use with <b>dockerFile</b> , which by default is the Dockerfile found in the <b>contextDir</b> . The Dockerfile can be also located outside of the <b>contextDir</b> , if provided with an absolute file path. See <a href="#">External Dockerfile</a> for details.
<b>cmd</b>	A command to execute by default (i.e. if no command is provided when a container for this image is started). See <a href="#">Startup Arguments</a> for details.
<b>compression</b>	The compression mode how the build archive is transmitted to the docker daemon ( <b>docker:build</b> ) and how docker build archives are attached to this build as sources ( <b>docker:source</b> ). The value can be <b>none</b> (default), <b>gzip</b> or <b>bzip2</b> .
<b>dockerFile</b>	Path to a <b>Dockerfile</b> which also triggers <i>Dockerfile mode</i> . See <a href="#">External Dockerfile</a> for details.
<b>dockerFileDir</b> ( <i>deprecated in favor of <b>contextDir</b></i> )	Path to a directory holding a <b>Dockerfile</b> and switch on <i>Dockerfile mode</i> . See <a href="#">External Dockerfile</a> for details. <i>This option is deprecated in favor of <b>_contextDir</b> and will be removed for the next major release.</i>
<b>dockerArchive</b>	Path to a saved image archive which is then imported. See <a href="#">Docker archive</a> for details.
<b>entryPoint</b>	An entrypoint allows you to configure a container that will run as an executable. See <a href="#">Startup Arguments</a> for details.
<b>env</b>	The environments as described in <a href="#">Setting Environment Variables and Labels</a> .
<b>filter</b>	Enable and set the delimiters for property replacements. By default properties in the format <b>\${..}</b> are replaced with Maven properties. You can switch off property replacement by setting this property to <b>false</b> . When using a single char like <b>@</b> then this is used as a delimiter (e.g <b>@...@</b> ). See <a href="#">Filtering</a> for more details.
<b>from</b>	The base image which should be used for this image. If not given this default to <b>busybox:latest</b> and is suitable for a pure data image.
<b>fromExt</b>	<p>Extended definition for a base image. This field holds a map of defined in <b>&lt;key&gt;value&lt;/key&gt;</b> format. The known keys are:</p> <ul style="list-style-type: none"> <li><b>&lt;name&gt;</b> : Name of the base image</li> </ul> <p>A provided <b>&lt;from&gt;</b> takes precedence over the name given here. This tag is useful for extensions of this plugin like the <a href="#">fabric8-maven-plugin</a> which can evaluate the additional information given here.</p>
<b>healthCheck</b>	Definition of a health check as described in <a href="#">Healthcheck</a>
<b>imagePullPolicy</b>	Specific pull policy for the base image. This overwrites any global pull policy. See the globale configuration option <a href="#">imagePullPolicy</a> for the possible values and the default.



Element	Description
<b>loadNamePattern</b>	<p>Scan the images in the archive specified in <code>dockerArchive</code> and match the associated repository and tag information against this pattern. When a matching repository and tag is found, create a tag linking the <code>name</code> for this image to the repository and tag that matched the pattern.</p> <p>The wildcards are:</p> <ul style="list-style-type: none"> <li>• <code>?</code> matches a single character</li> <li>• <code>*</code> matches within one component, where components are separated by slashes, or the final colon that separates the repository from the tag</li> <li>• <code>**</code> matches multiple components, stopping at the final colon</li> <li>• <code>**/</code> matches multiple components, but must stop at a slash, or the final colon</li> </ul> <p>When matching multiple components, <code>**/</code> is likely to be more useful than <code>**</code>. The pattern <code>**image-name:*</code> will match <code>my-group/my-image-name:some-tag</code>, whereas <code>**/image-name:*</code> will not, because the wildcard has to stop at a slash. Note that <code>**/image-name:*</code> will also match <code>'image-name:some-tag'</code>, since the <code>**/</code> wildcard can be empty.</p>
<b>labels</b>	Labels as described in <a href="#">Setting Environment Variables and Labels</a> .
<b>maintainer</b>	The author ( <code>MAINTAINER</code> ) field for the generated image
<b>noCache</b>	Don't use Docker's build cache. This can be overwritten by setting a system property <code>docker.noCache</code> when running Maven.
<b>cacheFrom</b>	A list of <code>&lt;image&gt;</code> elements specifying image names to use as cache sources.
<b>optimise</b>	if set to true then it will compress all the <code>runCmds</code> into a single <code>RUN</code> directive so that only one image layer is created.
<b>ports</b>	The exposed ports which is a list of <code>&lt;port&gt;</code> elements, one for each port to expose. Whitespace is trimmed from each element and empty elements are ignored. The format can be either pure numerical ("8080") or with the protocol attached ("8080/tcp").
<b>shell</b>	Shell to be used for the <code>runCmds</code> . It contains <code>arg</code> elements which are defining the executable and its params.
<b>runCmds</b>	Commands to be run during the build process. It contains <code>run</code> elements which are passed to the shell. Whitespace is trimmed from each element and empty elements are ignored. The run commands are inserted right after the assembly and after <code>workdir</code> into the Dockerfile. This tag is not to be confused with the <code>&lt;run&gt;</code> section for this image which specifies the runtime behaviour when starting containers.
<b>skip</b>	if set to true disables building of the image. This config option is best used together with a maven property
<b>skipTag</b>	If set to <code>true</code> this plugin won't add any tags to images. Property: <code>docker.skip.tag</code>
<b>tags</b>	List of additional <code>tag</code> elements with which an image is to be tagged after the build. Whitespace is trimmed from each element and empty elements are ignored.

Element	Description
<b>user</b>	User to which the Dockerfile should switch to the end (corresponds to the <b>USER</b> Dockerfile directive).
<b>volumes</b>	List of <b>volume</b> elements to create a container volume. Whitespace is trimmed from each element and empty elements are ignored.
<b>workdir</b>	Directory to change to when starting the container.

From this configuration this Plugin creates an in-memory Dockerfile, copies over the assembled files and calls the Docker daemon via its remote API.

## Example

```
<build>
  <from>java:8u40</from>
  <maintainer>john.doe@example.com</maintainer>
  <tags>
    <tag>latest</tag>
    <tag>${project.version}</tag>
  </tags>
  <ports>
    <port>8080</port>
  </ports>
  <volumes>
    <volume>/path/to/expose</volume>
  </volumes>
  <buildOptions>
    <shmsize>2147483648</shmsize>
  </buildOptions>

  <shell>
    <exec>
      <arg>/bin/sh</arg>
      <arg>-c</arg>
    </exec>
  </shell>
  <runCmds>
    <run>groupadd -r appUser</run>
    <run>useradd -r -g appUser appUser</run>
  </runCmds>

  <entryPoint>
    <!-- exec form for ENTRYPOINT -->
    <exec>
      <arg>java</arg>
      <arg>-jar</arg>
      <arg>/opt/demo/server.jar</arg>
    </exec>
  </entryPoint>

  <assembly>
    <mode>dir</mode>
    <targetDir>/opt/demo</targetDir>
    <descriptor>assembly.xml</descriptor>
  </assembly>
</build>
```

In order to see the individual build steps you can switch on **verbose** mode either by setting the property `docker.verbose` or by using `<verbose>true</verbose>` in the [Global configuration](#)

## 5.1.2. Assembly

The `<assembly>` element within `<build>` is has an XML struture and defines how build artifacts and other files can enter the Docker image.

Table 6. Assembly Configuration (`<image>` : `<build>` )

Element	Description
<b>name</b>	Assembly name, which is <code>maven</code> by default. This name is used for the archives and directories created during the build. This directory holds the files specified by the assembly. If an <a href="#">external Dockerfile</a> is used than this name is also the relative directory which contains the assembly files.
<b>targetDir</b>	Directory under which the files and artifacts contained in the assembly will be copied within the container. The default value for this is <code>/&lt;assembly name&gt;</code> , so <code>/maven</code> if <b>name</b> is not set to a different value. This option has no meaning when an <a href="#">external Dockerfile</a> is used.
<b>inline</b>	Inlined assembly descriptor as described in <a href="#">Assembly Descriptor</a> below.
<b>descriptor</b>	Path to an assembly descriptor file, whose format is described <a href="#">Assembly Descriptor</a> below.
<b>descriptorRef</b>	Alias to a predefined assembly descriptor. The available aliases are also described in <a href="#">Assembly Descriptor</a> below.
<b>dockerFileDir</b>	Directory containing an external Dockerfile. <i>This option is deprecated, please use <code>&lt;dockerFileDir&gt;</code> directly in the <code>&lt;build&gt;</code> section.</i>
<b>exportTargetDir</b>	Specification whether the <code>targetDir</code> should be exported as a volume. This value is <code>true</code> by default except in the case the <code>targetDir</code> is set to the container root ( <code>/</code> ). It is also <code>false</code> by default when a base image is used with <code>from</code> since exporting makes no sense in this case and will waste disk space unnecessarily.
<b>ignorePermissions</b>	Specification if existing file permissions should be ignored when creating the assembly archive with a mode <code>dir</code> . This value is <code>false</code> by default. <i>This property is deprecated, use a <code>permissions</code> of <code>ignore</code> instead.</i>
<b>mode</b>	<p>Mode how the how the assembled files should be collected:</p> <ul style="list-style-type: none"><li>• <code>dir</code> : Files are simply copied (default),</li><li>• <code>tar</code> : Transfer via tar archive</li><li>• <code>tgz</code> : Transfer via compressed tar archive</li><li>• <code>zip</code> : Transfer via ZIP archive</li></ul> <p>The archive formats have the advantage that file permission can be preserved better (since the copying is independent from the underlying files systems), but might triggers internal bugs from the Maven assembler (as it has been reported in <a href="#">#171</a>)</p>

Element	Description
<b>permissions</b>	<p>Permission of the files to add:</p> <ul style="list-style-type: none"> <li>• <b>ignore</b> to use the permission as found on files regardless on any assembly configuration</li> <li>• <b>keep</b> to respect the assembly provided permissions, <b>exec</b> for setting the executable bit on all files (required for Windows when using an assembly mode <b>dir</b>)</li> <li>• <b>auto</b> to let the plugin select <b>exec</b> on Windows and <b>keep</b> on others.</li> </ul> <p><b>keep</b> is the default value.</p>
<b>tarLongFileMode</b>	<p>Sets the TarArchiver behaviour on file paths with more than 100 characters length. Valid values are: "warn"(default), "fail", "truncate", "gnu", "posix", "posix_warn" or "omit"</p>
<b>user</b>	<p>User and/or group under which the files should be added. The user must already exist in the base image.</p> <p>It has the general format <b>user[:group[:run-user]]</b>. The user and group can be given either as numeric user- and group-id or as names. The group id is optional.</p> <p>If a third part is given, then the build changes to user <b>root</b> before changing the ownerships, changes the ownerships and then change to user <b>run-user</b> which is then used for the final command to execute. This feature might be needed, if the base image already changed the user (e.g. to 'jboss') so that a <b>chown</b> from root to this user would fail.</p> <p>For example, the image <b>jboss/wildfly</b> use a "jboss" user under which all commands are executed. Adding files in Docker always happens under the UID root. These files can only be changed to "jboss" is the <b>chown</b> command is executed as root. For the following commands to be run again as "jboss" (like the final <b>standalone.sh</b>), the plugin switches back to user <b>jboss</b> (this is this "run-user") after changing the file ownership. For this example a specification of <b>jboss:jboss:jboss</b> would be required.</p>

In the event you do not need to include any artifacts with the image, you may safely omit this element from the configuration.

## Assembly Descriptor

With using the **inline**, **descriptor** or **descriptorRef** option it is possible to bring local files, artifacts and dependencies into the running Docker container. A **descriptor** points to a file describing the data to put into an image to build. It has the same **format** as for creating assemblies with the [maven-assembly-plugin](#) with following exceptions:

- **<formats>** are ignored, the assembly will allways use a directory when preparing the data container (i.e. the format is fixed to **dir**)
- The **<id>** is ignored since only a single assembly descriptor is used (no need to distinguish multiple descriptors)

Also you can inline the assembly description with a `inline` description directly into the pom file. Adding the proper namespace even allows for IDE autocompletion. As an example, refer to the profile `inline` in the `data-jolokia-demo`'s pom.xml.

Alternatively `descriptorRef` can be used with the name of a predefined assembly descriptor. The following symbolic names can be used for `descriptorRef`:

Table 7. Predefined Assembly Descriptors

Assembly Reference	Description
<b>artifact-with-dependencies</b>	Attaches project's artifact and all its dependencies. Also, when a <code>classpath</code> file exists in the target directory, this will be added to.
<b>artifact</b>	Attaches only the project's artifact but no dependencies.
<b>project</b>	Attaches the whole Maven project but with out the <code>target/</code> directory.
<b>rootWar</b>	Copies the artifact as <code>ROOT.war</code> to the exposed directory. I.e. Tomcat will then deploy the war under the root context.

#### Example

```
<images>
  <image>
    <build>
      <assembly>
        <descriptorRef>artifact-with-dependencies</descriptorRef>
      .....
```

will add the created artifact with the name `${project.build.finalName}.${artifact.extension}` and all jar dependencies in the the `targetDir` (which is `/maven` by default).

All declared files end up in the configured `targetDir` (or `/maven` by default) in the created image.

#### Maven peculiarities when including the artifact

If the assembly references the artifact to build with this pom, it is required that the `package` phase is included in the run. Otherwise the artifact file, can't be found by `docker:build`. This is an old [outstanding issue](#) of the assembly plugin which probably can't be fixed because of the way how Maven works. We tried hard to workaround this issue and in 90% of all cases, you won't experience any problem. However, when the following warning happens which might lead to the given error:

```
[WARNING] Cannot include project artifact: io.fabric8:helloworld:jar:0.20.0; it
doesn't have an associated file or directory.
[WARNING] The following patterns were never triggered in this artifact inclusion
filter:
o 'io.fabric8:helloworld'

[ERROR] DOCKER> Failed to create assembly for docker image (with mode 'dir'): Error
creating assembly archive docker: You must set at least one file.
```

then you have two options to fix this:

- Call `mvn package docker:build` to explicitly run "package" and "docker:build" in a chain.
- Bind `build` to an execution phase in the plugin's definition. By default `docker:build` will bind to the `install` phase is set in an execution. Then you can use a plain `mvn install` for building the artifact and creating the image.

```
<executions>
  <execution>
    <id>docker-build</id>
    <goals>
      <goal>build</goal>
    </goals>
  </execution>
</executions>
```

#### Example

In the following example a dependency from the pom.xml is included and mapped to the name `jolokia.war`. With this configuration you will end up with an image, based on `busybox` which has a directory `/maven` containing a single file `jolokia.war`. This volume is also exported automatically.

```
<assembly>
  <inline>
    <dependencySets>
      <dependencySet>
        <includes>
          <include>org.jolokia:jolokia-war</include>
        </includes>
        <outputDirectory>./outputDirectory</outputDirectory>
        <outputFileNameMapping>jolokia.war</outputFileNameMapping>
      </dependencySet>
    </dependencySets>
  </inline>
</assembly>
```

Another container can now connect to the volume and 'mount' the `/maven` directory. A container from `consol/tomcat-7.0` will look into `/maven` and copy over everything to `/opt/tomcat/webapps` before starting Tomcat.

If you are using the `artifact` or `artifact-with-dependencies` descriptor, it is possible to change the name of the final build artifact with the following:

#### Example

```
<build>
  <finalName>your-desired-final-name</finalName>
  ...
</build>
```

Please note, based upon the following documentation listed [here](#), there is no guarantee the plugin creating your artifact will honor it in which case you will need to use a custom descriptor like above to achieve the desired naming.

Currently the `jar` and `war` plugins properly honor the usage of `finalName`.

### 5.1.3. Startup Arguments

Using `entryPoint` and `cmd` it is possible to specify the `entry point` or `cmd` for a container.

The difference is, that an `entrypoint` is the command that always be executed, with the `cmd` as argument. If no `entryPoint` is provided, it defaults to `/bin/sh -c` so any `cmd` given is executed with a shell. The arguments given to `docker run` are always given as arguments to the `entrypoint`, overriding any given `cmd` option. On the other hand if no extra arguments are given to `docker run` the default `cmd` is used as argument to `entrypoint`.

See this [stackoverflow question](#) for a detailed explanation.

An entry point or command can be specified in two alternative formats:

Table 8. Entrypoint and Command Configuration

Mode	Description
<b>shell</b>	Shell form in which the whole line is given to <code>shell -c</code> for interpretation.
<b>exec</b>	List of arguments (with inner <code>&lt;args&gt;</code> ) arguments which will be given to the <code>exec</code> call directly without any shell interpretation.

Either shell or params should be specified.

Example

```
<entryPoint>
  <!-- shell form -->
  <shell>java -jar $HOME/server.jar</shell>
</entryPoint>
```

or

Example

```
<entryPoint>
  <!-- exec form -->
  <exec>
    <arg>java</arg>
    <arg>-jar</arg>
    <arg>/opt/demo/server.jar</arg>
  </exec>
</entryPoint>
```



This can be formulated also more dense with:

*Example*

```
<!-- shell form -->
<entryPoint>java -jar $HOME/server.jar</entryPoint>
```

or

*Example*

```
<entryPoint>
  <!-- exec form -->
  <arg>java</arg>
  <arg>-jar</arg>
  <arg>/opt/demo/server.jar</arg>
</entryPoint>
```

### 5.1.4. Build Args

As described in section [Configuration](#) for external Dockerfiles [Docker build arg](#) can be used. In addition to the configuration within the plugin configuration you can also use properties to specify them:

- Set a system property when running Maven, eg.:  
`-Ddocker.buildArg.http_proxy=http://proxy:8001`. This is especially useful when using predefined Docker arguments for setting proxies transparently.
- Set a project property within the `pom.xml`, eg.:

*Example*

```
<docker.buildArg.myBuildArg>myValue</docker.buildArg.myBuildArg>
```

Please note that the system property setting will always override the project property. Also note that for all properties which are not Docker [predefined](#) properties, the external Dockerfile must contain an `ARG` instruction.

### 5.1.5. Healthcheck

Healthchecks has been introduced since Docker 1.12 and are a way to tell Docker how to test a container to check that it's still working. With a health check you specify a command which is periodically executed and checked for its return value. If the healthcheck return with an exit 0 the container is considered to be healthy, if it returns with 1 then the container is not working correctly.

The healthcheck configuration can have the following options

*Table 9. Healthcheck Configuration*

Element	Description
<b>cmd</b>	Command to execute, which can be given in an shell or exec format as described in <a href="#">Startup Arguments</a> .
<b>interval</b>	Interval for how often to run the healthcheck. The time is specified in seconds, but a time unit can be appended to change this.
<b>mode</b>	Mode of the healthcheck. This can be <b>cmd</b> which is the default and specifies that the health check should be executed. Or <b>none</b> to disable a health check from the base image. Only use this option with <b>none</b> for disabling some healthcheck from the base image.
<b>retries</b>	How many retries should be performed before the container is to be considered unhealthy.
<b>startPeriod</b>	Initialization time for containers that need time to bootstrap. Probe failure during that period will not be counted towards the maximum number of retries. However, if a health check succeeds during the start period, the container is considered started and all consecutive failures will be counted towards the maximum number of retries. Given in seconds, but another time unit can be appended.
<b>timeout</b>	Timeout after which healthckeck should be stopped and considered to have failed. Given in seconds, but another time unit can be appended.

The following example queries an URL every 10s as an healthcheck:

#### Example

```
<healthCheck>
  <!-- Check every 5 minutes -->
  <interval>5m</interval>
  <!-- Fail if no response after 3 seconds -->
  <timeout>3s</timeout>
  <!-- Allow 30 minutes for the container to start before being flagged as unhealthy -->
  <startPeriod>30m</startPeriod>
  <!-- Fail 3 times until the container is considerd unhealthy -->
  <retries>3</retries>
  <!-- Command to execute in shell form -->
  <cmd>curl -f http://localhost/ || exit 1</cmd>
</healthCheck>
```

## 5.2. docker:start

This goal creates and starts docker containers. This goals evaluates the configuration's **<run>** section of all given (and enabled images).

Also you can specify **docker.follow** as system property so that the **docker:start** will never return but block until CTRL-C is pressed. That similar to the option **-i** for **docker run**. This will automatically switch on **showLogs** so that you can see what is happening within the container. Also, after stopping with CTRL-C, the container is stopped (but not removed so that you can make postmortem analysis).

`docker:run` is an alias for `docker:start` with `docker.follow` enabled.

By default container specific properties are exposed as Maven properties. These properties have the format `docker.container.<alias>.<prop>` where `<alias>` is the name of the container (see below) and `<prop>` is one of the following container properties:

Table 10. Properties provided

Property	Description
<b>ip</b>	Internal IP address of the container.
<b>id</b>	Container id
<b>net.&lt;network&gt;.ip</b>	Internal IP address of the container in the specified custom network. This works only for custom networks.

Instead of the `<alias>` a fixed property key can be configured in the image's `<run>` configuration with the option `exposedPropertyKey`.

For example the Maven property `docker.container.tomcat.ip` would hold the Docker internal IP for a container with an alias "tomcat". You can set the global configuration `exposeContainerInfo` to an empty string to not expose container information that way or to a string for an other prefix than `docker.container`.

### 5.2.1. Configuration

In addition to the [Global configuration](#), this goal supports the following global configuration options.

Table 11. Start options

Element	Description	Property
<b>containerNamePattern</b>	Default pattern for naming all containers when they are created. See <a href="#">Container Names</a> for details.	<code>docker.containerNamePattern</code>
<b>showLogs</b>	In order to switch on globally the logs <b>showLogs</b> can be used as global configuration (i.e. outside of <code>&lt;images&gt;</code> ). If set it will print out all standard output and standard error messages for all containers started. As value the images for which logs should be shown can be given as a comma separated list. This is probably most useful when used from the command line as system property <code>docker.showLogs</code> .	<code>docker.showLogs</code>
<b>startParallel</b>	Starts docker images in parallel while dependencies expressed as <a href="#">Link</a> or <a href="#">dependsOn</a> are respected. This option can significantly reduce the startup time because independent containers do not need to wait for each other.	<code>docker.startParallel</code>

The `<run>` configuration element knows the following sub elements:

Table 12. Run configuration (`<image>`)

Element	Description
<b>capAdd</b>	List of <code>add</code> elements to specify kernel parameters to add to the container.

Element	Description
<b>capDrop</b>	List of <b>drop</b> elements to specify kernel parameters to remove from the container.
<b>cmd</b>	Command which should be executed at the end of the container's startup. If not given, the image's default command is used. See <a href="#">Startup Arguments</a> for details.
<b>containerNamePattern</b>	Pattern for naming the container when it is created. See <a href="#">Container Naming Strategy</a> for details.
<b>domainname</b>	Domain name for the container
<b>dns</b>	List of <b>host</b> elements specifying dns servers for the container to use
<b>dnsSearch</b>	List of <b>host</b> elements specifying dns search domains
<b>entrypoint</b>	Entry point for the container. See <a href="#">[misc-startup, Startup Arguments]</a> for details.
<b>env</b>	Environment variables as subelements which are set during startup of the container. They are specified in the typical maven property format as described <a href="#">Environment and Labels</a> .
<b>envPropertyFile</b>	Path to a property file holding environment variables. If given, the variables specified in this property file overrides the environment variables specified in the configuration.
<b>extraHosts</b>	List of <b>host</b> elements in the form <b>host:ip</b> to add to the container's <code>/etc/hosts</code> file. Additionally, you may specify a <b>host</b> element in the form <b>host:host</b> to have the right side host ip address resolved at container startup.
<b>exposedPropertyKey</b>	Set the property part for the exposed container properties as described <a href="#">above</a> . This will take precedence of the image's <b>alias</b> which is the default value. For example, when this property is set to <b>jboss</b> , then for this container its IP address is exposed in Maven property <code>docker.container.jboss.ip</code> regardless how the image is named.
<b>hostname</b>	Hostname of the container
<b>imagePullPolicy</b>	Specific pull policy for downloading the image. This overwrites any global pull policy. See the global <a href="#">imagePullPolicy</a> configuration option for the possible values and the default.
<b>labels</b>	Labels which should be attached to the container. They are specified in the typical maven property format as described in <a href="#">Environment and Labels</a> .
<b>links</b>	Network links for connecting containers together as described in <a href="#">Network Links</a> .
<b>log</b>	Log configuration for whether and how log messages from the running containers should be printed. This also can configure the <a href="#">log driver</a> to use. See <a href="#">Logging</a> for a detailed description.
<b>memory</b>	Memory limit in bytes
<b>memorySwap</b>	Total memory usage (memory + swap); use -1 to disable swap.
<b>namingStrategy</b>	<p><b>This option is deprecated, please use a <code>containerNamePattern</code> instead</b> Naming strategy for how the container name is created:</p> <ul style="list-style-type: none"> <li>• <b>none</b> : uses randomly assigned names from docker (default)</li> <li>• <b>alias</b> : uses the <b>alias</b> specified in the <b>image</b> configuration. An error is thrown, if a container already exists with this name.</li> </ul>

Element	Description
<b>network</b>	Network configuration for your container.
<b>portPropertyFile</b>	File path into which the mapped port properties are written. The format of this file and its purpose are also described in <a href="#">Port mapping</a>
<b>ports</b>	<a href="#">Port mappings</a> for exposing container ports to host ports.
<b>privileged</b>	If <b>true</b> give container full access to host
<b>readOnly</b>	If <b>true</b> mount the container's root filesystem as read only
<b>autoRemove</b>	If <b>true</b> automatically remove the container when it exits. This has no effect if <a href="#">Restart Policy</a> has been set.
<b>restartPolicy</b>	Restart Policy
<b>securityOpts</b>	List of <b>&lt;opt&gt;</b> elements to specify kernel security options to add to the container. See below for an example.
<b>shmSize</b>	Size of <b>/dev/shm</b> in bytes.
<b>skip</b>	If <b>true</b> disable creating and starting of the container. This option is best used together with a Maven property which can be set from the outside.
<b>tmpfs</b>	List countaintin <b>&lt;mount&gt;</b> elements for directories to mount with a temporary filesystem. Optionally, mount options can be appended after a ':'. See below for an example.
<b>ulimits</b>	<p>ulimits for the container. This list contains <b>&lt;ulimit&gt;</b> elements which three sub elements:</p> <ul style="list-style-type: none"> <li><b>&lt;name&gt;</b> : The ulimit to set (e.g. <b>memlock</b>). Please refer to the Docker documentation for the possible values to set</li> <li><b>&lt;hard&gt;</b> : The hard limit</li> <li><b>&lt;soft&gt;</b> : The soft limit</li> </ul> <p>See below for an example.</p>
<b>user</b>	User used inside the container
<b>volumes</b>	Volume configuration for binding to host directories and from other containers. See Volumes for details.
<b>wait</b>	Condition which must be fulfilled for the startup to complete. See <a href="#">Wait</a> for all possible ways to wait for a startup condition.
<b>workingDir</b>	Working directory for commands to run in

## Example

```
<run>
  <env>
    <CATALINA_OPTS>-Xmx32m</CATALINA_OPTS>
    <JOLOKIA_OFF/>
  </env>
  <labels>
    <environment>development</environment>
    <version>${project.version}</version>
  </labels>
  <ports>
    <port>jolokia.port:8080</port>
  </ports>
  <ulimits>
    <ulimit>
      <name>memlock</name>
      <hard>-1</hard>
      <soft>-1</soft>
    </ulimit>
  </ulimits>
  <tmpfs>
    <mount>/var/lib/mysql:size=10m</mount>
    <mount>/opt/mydata</mount>
  </tmpfs>
  <securityOpts>
    <opt>seccomp=unconfined</opt>
  </securityOpts>
  <links>
    <link>db</db>
  </links>
  <wait>
    <http>
      <url>http://localhost:${jolokia.port}/jolokia</url>
    </http>
    <time>10000</time>
  </wait>
  <log>
    <prefix>DEMO</prefix>
    <date>ISO8601</date>
    <color>blue</color>
  </log>
  <cmd>java -jar /maven/docker-demo.jar</cmd>
</run>
```

### 5.2.2. Environment and Labels

When creating a container one or more environment variables can be set via configuration with the `env` parameter

### Example

```
<env>
  <JAVA_HOME>/opt/jdk8</JAVA_HOME>
  <CATALINA_OPTS>-Djava.security.egd=file:/dev/./urandom</CATALINA_OPTS>
</env>
```

If you put this configuration into profiles you can easily create various test variants with a single image (e.g. by switching the JDK or whatever).

It is also possible to set the environment variables from the outside of the plugin's configuration with the parameter `envPropertyFile`. If given, this property file is used to set the environment variables where the keys and values specify the environment variable. Environment variables specified in this file override any environment variables specified in the configuration.

Labels can be set inline the same way as environment variables:

### Example

```
<labels>
  <com.example.label-with-value>foo</com.example.label-with-value>
  <version>${project.version}</version>
  <artifactId>${project.artifactId}</artifactId>
</labels>
```

## 5.2.3. Port Mapping

The `<ports>` configuration contains a list of port mappings. Whitespace is trimmed from each element and empty elements are ignored. Each mapping has multiple parts, each separate by a colon. This is equivalent to the port mapping when using the Docker CLI with option `-p`.

A `port` stanza may take one of the following forms:

Table 13. Port mapping format

Format	Description
18080:8080	Tuple consisting of two numeric values separated by a <code>:</code> . This form will result in an explicit mapping between the docker host and the corresponding port inside the container. In the above example, port 18080 would be exposed on the docker host and mapped to port 8080 in the running container.

Format	Description
<b>host.port:80</b>	Tuple consisting of a string and a numeric value separated by a <b>:</b> . In this form, the string portion of the tuple will correspond to a Maven property. If the property is undefined when the <b>start</b> task executes, a port will be dynamically selected by Docker in the ephemeral port range and assigned to the property which may then be used later in the same POM file. The ephemeral port range is configured by the <code>/proc/sys/net/ipv4/ip_local_port_range</code> kernel parameter, which typically ranges from 32678 to 61000. If the property exists and has numeric value, that value will be used as the exposed port on the docker host as in the previous form. In the above example, the docker service will elect a new port and assign the value to the property <b>host.port</b> which may then later be used in a property expression similar to <code>&lt;value&gt;\${host.port}&lt;/value&gt;</code> . This can be used to pin a port from the outside when doing some initial testing similar to <code>mvn -Dhost.port=10080 docker:start</code>
<b>bindTo:host.port:80</b>	Tuple consisting of two strings and a numeric value separated by a <b>:</b> . In this form, <b>bindTo</b> is an ip address on the host the container should bind to. As a convenience, a hostname pointing to the docker host may also be specified. The container will fail to start if the hostname can not be resolved.
<b>+host.ip:host.port:80</b>	Tuple consisting of two strings and a numeric value separated by a <b>:</b> . In this form, the host ip of the container will be placed into a Maven property name <b>host.ip</b> . If docker reports that value to be <code>0.0.0.0</code> , the value of <b>docker.host.address</b> will be substituted instead. In the event you want to use this form and have the container bind to a specific hostname/ip address, you can declare a Maven property of the same name ( <b>host.ip</b> in this example) containing the value to use. <b>host:port</b> works in the same way as described above.

By default TCP is used as protocol but you can also use UDP by appending `'/udp'` to the port number.

The following are examples of valid configuration entries:



### Example

```
<properties>
  <bind.host.ip>1.2.3.4</bind.host.ip>
  <bind.host.name>some.host.pvt</bind.host.name>
</properties>

...

<ports>
  <port>18080:8080</port>
  <port>15060:5060/udp</port>
  <port>host.port:80</port>
  <port>127.0.0.1:80:80</port>
  <port>localhost:host.port:80</port>
  <port>+container.ip.property:host.port:5678</port>
  <port>+bind.host.ip:host.port:5678</port>
  <port>+bind.host.name:5678:5678</port>
</ports>
```

Another useful configuration option is `portPropertyFile` which can be used to write out the container's host ip and any dynamic ports that have been resolved. The keys of this property file are the property names defined in the port mapping configuration and their values those of the corresponding docker attributes.

This property file might be useful with tests or with other maven plugins that will be unable to use the resolved properties because they can only be updated after the container has started and plugins resolve their properties in an earlier lifecycle phase.

If you don't need to write out such a property file and thus don't need to preserve the property names, you can use normal maven properties as well. E.g. `${host.var}:${port.var}:8080` instead of `+host.var:port.var:8080`.

## 5.2.4. Links

The `<links>` configuration contains a list of containers that should be linked to this container according to [Docker Links](#). Each link can have two parts where the optional right side is separated by a `:` and will be used as the name in the environment variables and the left side refers to the name of the container linking to. This is equivalent to the linking when using the Docker CLI `--link` option.

Example for linking to a container with name or alias *postgres* :

### Example

```
<links>
  <link>postgres:db</link>
</links>
```

This will create the following environment variables, given that the postgres image exposes TCP port 5432:

*Example*

```
DB_NAME=/web2/db
DB_PORT=tcp://172.17.0.5:5432
DB_PORT_5432_TCP=tcp://172.17.0.5:5432
DB_PORT_5432_TCP_PROTO=tcp
DB_PORT_5432_TCP_PORT=5432
DB_PORT_5432_TCP_ADDR=172.17.0.5
```

Additionally, each `<link>` element can specify a comma separated set of links. Comma (and whitespace) can be used to separate links since valid docker link names/aliases contain only characters, digits, underscores, periods and dashes.

*Example*

```
<links>
  <link>postgres:db, search, saml:identity</link>
</links>
```

If you wish to link to existing containers not managed by the plugin, you may do so by specifying the container name obtained via `docker ps` in the configuration.

Please note that the link behaviour also depends on the network mode selected. Links as described are referred to by Docker as *legacy links* and might vanish in the future. For custom networks no environments variables are set and links create merely network aliases for the linked container. To express start order dependencies using custom networks refer to the [dependsOn](#) configuration.

For a more detailed documentation for the new link handling please refer to the [Docker network documentation](#)

## 5.2.5. Network

The `<network>` element in the `<run>` configuration section can be used to configure the network mode of the container. This is now the preferred way for linking containers together. It knows the following sub elements:

*Table 14. Network configuration*

Element	Description
<b>mode</b>	<p>The network mode, which can be one of the following values:</p> <ul style="list-style-type: none"> <li>• <b>bridge</b> : Bridged mode with the default Docker bridge (default)</li> <li>• <b>host</b> : Share the Docker host network interfaces</li> <li>• <b>container</b> : Connect to the network of the specified container. The name of the container is taken from the <code>&lt;name&gt;</code> element.</li> <li>• <b>custom</b> : Use a custom network, which must be created before by using <code>docker network create</code>. Alternatively you can set the <code>docker.autoCreateCustomNetworks</code> <a href="#">global configuration</a> parameter to <code>true</code> to automatically create custom networks. Custom networks are available for Docker 1.9 and newer. For more about the networking options please refer to the <a href="#">Docker documentation</a>.</li> <li>• <b>none</b> : No network will be setup.</li> </ul>
<b>name</b>	For mode <code>container</code> this is the container name, which is this image alias. For Mode <code>custom</code> this is the name of the custom network.
<b>alias</b>	One or more alias element can be provided which gives a way for a container to be discovered by alternate names by any other container within the scope of a particular network. This configuration only has effect for when the network mode is <code>custom</code> . More than one alias can be given by providing multiple entries.

If no `mode` is given but a `name`, then a `custom` network mode is assumed. For the simple modes which does not take an argument (`none`, `bridge` or `host`) a single `<net> mode </net>` can be used as alternative to using `<network>` with a `<mode>` subelement.

Example `<network>`

```
<network>
  <mode>custom</mode>
  <name>my-network</name>
  <alias>box1</alias>
  <alias>box2</alias>
</network>
```

or for a simple `host` network:

Example `<net>`

```
<net>host</net>
```

## 5.2.6. Depends-On

Custom networks do not provide a mechanism like `<links>` to express strong links between containers. They are normally not required because docker ensures that all containers within the same custom network can eventually resolve each other via DNS.

Your containers should preferably be able to deal with temporarily unresolvable dependencies but in some cases it is helpful to be able to rely the availability of other infrastructure containers.

The `<dependsOn>` configuration can be used to express custom network dependencies between your containers. `docker:start` will ensure that all dependencies a container depends on are completely started (fulfilling all `<wait>` conditions) before the depending container is started.

Additionally, each `<container>` element can specify a comma separated set of containers. Comma (and whitespace) can be used to separate containers since valid docker container names contain only characters, digits, underscores, periods and dashes.

*Example*

```
<configuration>
  <!-- .... -->
  <run>
    <dependsOn>
      <container>postgres</container>
      <container>logstash</container>
    </dependsOn>
  </run>
</configuration>
```

### 5.2.7. Restart Policy

Specify the behavior to apply when the container exits. These values can be specified withing a `<restartPolicy>` section with the following sub-elements:

*Table 15. Restart Policy configuration*

Element	Description
<b>name</b>	Restart policy name, choose from: <ul style="list-style-type: none"><li>• <code>always</code> (v1.15) always restart</li><li>• <code>on-failure</code> (v1.15) restart on container non-exit code of zero</li></ul>
<b>retry</b>	If <code>on-failure</code> is used, controls max number of attempts to restart before giving up.

The behavior to apply when the container exits. The value is an object with a name property of either "always" to always restart or "on-failure" to restart only when the container exit code is non-zero. If on-failure is used, MaximumRetryCount controls the number of times to retry before giving up. The default is not to restart. (optional)

### 5.2.8. Volumes

A container can bind (or "mount") volumes from various source when starting up: Either from a directory of the host system or from another container which exports one or more directories. The mount configuration is specified within a `<volumes>` section of the run configuration. It can contain the following sub elements:

Table 16. Volume configuration

Element	Description
<b>from</b>	List of <code>&lt;image&gt;</code> elements which specify image names or aliases of containers whose volumes should be imported.
<b>bind</b>	List of <code>&lt;volume&gt;</code> specifications (or <i>host mounts</i> ). Use <code>/path</code> to create and expose a new volume in the container, <code>/host_path:/container_path</code> to mount a host path into the container and <code>/host_path:/container_path:ro</code> to bind it read-only.

#### Volumes example

```
<volumes>
  <bind>
    <volume>/logs</volume>
    <volume>/opt/host_export:/opt/container_import</volume>
  </bind>
  <from>
    <image>jolokia/docker-demo</image>
  </from>
</volumes>
```

In this example the container creates a new volume named `/logs` on the container and mounts `/opt/host_export` from the host as `/opt/container_import` on the container. In addition all exported volumes from the container which has been created from the image `jolokia/docker-demo` are mounted directly into the container (with the same directory names under which the exporting container exposes these directories). This image must be also configured for this plugin. Instead of the full image name, an alias name can be used, too.

If a volume name instead of a path is referenced to in `<bind>` and a [volume configuration](#) exists with this name, then this this volume is created upfront with the provided options instead of using default options.

You can use Maven variables in the path specifications. This should even work for boot2docker and docker-machine:

#### Example with absolute paths

```
<volumes>
  <bind>
    <volume>${project.build.directory}/${project.artifactId}-
    ${project.version}:/usr/local/tomcat/webapps/${project.name}</volume>
    <volume>${project.basedir}/data:/data</volume>
  </bind>
</volumes>
```

You can also use relative paths. Relative paths are interpreted relative to the Maven project base directory. Paths that begin with `~` are interpreted relative to the JVM's `user.home` directory.

```
<volumes>
  <bind>
    <volume>src/main/webapps/foo:/usr/local/tomcat/webapps/foo</volume>
    <volume>./target:/data</volume>
    <volume>~/home/user</volume>
    <volume>~/m2/repository:/home/user/.m2/repository</volume>
  </bind>
</volumes>
```

If you wish to mount volumes from an existing container not managed by the plugin, you may do by specifying the container name obtained via `docker ps` in the configuration.

### 5.2.9. Wait

While starting a container is it possible to block the execution until some condition is met. These conditions can be specified within a `<wait>` section which the following sub-elements:

Table 17. Wait configuration

Element	Description
<b>http</b>	<p>HTTP ping check which periodically polls an URL. It knows the following sub-elements:</p> <ul style="list-style-type: none"> <li>• <b>url</b> holds an URL and is mandatory</li> <li>• <b>method</b> Optional HTTP method to use.</li> <li>• <b>status</b> Status code which if returned is considered to be a successful ping. This code can be given either as a single number (200) or as a range (200..399). The default is <code>200..399</code></li> <li>• <b>allowAllHosts</b> If <code>url</code> is an HTTPS url and this option is set, then server certificates are not validated. By default they are checked for a proper CA signature.</li> </ul>
<b>log</b>	Regular expression which is applied against the log output of an container and blocks until the pattern is matched. You can use <code>(?s)</code> in the pattern to switch on multi line matching.
<b>time</b>	Time in milliseconds to block.
<b>kill</b>	Time in milliseconds between sending <code>SIGTERM</code> and <code>SIGKILL</code> when stopping a container. Since docker itself uses second granularity, you should use at least 1000 milliseconds.
<b>shutdown</b>	Time to wait in milliseconds between stopping a container and removing it. This might be helpful in situation where a Docker croaks with an error when trying to remove a container to fast after it has been stopped.

Element	Description
<b>exec</b>	<p>Commands to execute during specified lifecycle of the container. It knows the following sub-elements:</p> <ul style="list-style-type: none"> <li>• <b>postStart</b> Command to run after the above wait criteria has been met</li> <li>• <b>preStop</b> Command to run before the container is stopped.</li> <li>• <b>breakOnError</b> If set to <b>true</b> then break the build if a <b>postStart</b> or <b>preStop</b> command exits with a return code other than 0, otherwise only print an error message.</li> </ul>
<b>tcp</b>	<p>TCP port check which periodically polls given tcp ports. It knows the following sub-elements:</p> <ul style="list-style-type: none"> <li>• <b>mode</b> can be either <b>mapped</b> which uses the mapped ports or <b>direct</b> in which case the container ports are addressed directly. In the later case the host field should be left empty in order to select the container ip (which must be routed which is only the case when running on the Docker daemon's host directly). Default is <b>direct</b> when host is <i>localhost</i>, <b>mapped</b> otherwise. The direct mode might help when a so called <i>user-proxy</i> is enabled on the Docker daemon which makes the mapped ports directly available even when the container is not ready yet.</li> <li>• <b>host</b> is the hostname or the IP address. It defaults to <code>`\${docker.host.address}`</code> for a mapped mode and the container ip address for the direct mode.</li> <li>• <b>ports</b> is a list of TCP ports to check. These are supposed to be the container internal ports.</li> </ul>
<b>healthy</b>	<p>Check that waits until the container health state becomes <b>healthy</b>. A container is considered healthy when its <b>configured healthcheck</b> succeeds.</p> <p>This behaviour mimics the docker compose dependsOn <b>condition: service_healthy</b>.</p>
<b>exit</b>	Check that waits until a container finishes with the given exit code.

As soon as one condition is met the build continues. If you add a **<time>** constraint this works more or less as a timeout for other conditions. The build will abort if you wait on an url or log output and reach the timeout. If only a **<time>** is specified, the build will wait that amount of milliseconds and then continues.

```

<wait>
  <http>
    <url>http://localhost:${host.port}</url>
    <method>GET</method>
    <status>200..399</status>
  </http>
  <time>10000</time>
  <kill>1000</kill>
  <shutdown>500</shutdown>
  <exec>
    <postStart>/opt/init_db.sh</postStart>
    <preStop>/opt/notify_end.sh</preStop>
  </exec>
  <tcp>
    <host>192.168.99.100</host>
    <ports>
      <port>3306</port>
      <port>9999</port>
    </ports>
  </tcp>
  <healthy>true</healthy>
</wait>

```

This setup will wait for the given URL to be reachable but ten seconds at most. Additionally, it will wait for the TCP ports 3306 and 9999. Also, when stopping the container after integration tests, the build wait for 500 ms before it tries to remove the container (if not `keepContainer` or `keepRunning` is used). You can use maven properties in each condition, too. In the example, the `${host.port}` property is probably set before within a port mapping section.

The property `${docker.host.address}` is set implicitly to the address of the Docker host. This host will be taken from the `docker.host` configuration if HTTP or HTTPS is used. If a Unix socket is used for communication with the docker daemon, then `localhost` is assumed. You can override this property always by setting this Maven property explicitly.

## 5.2.10. Logging

When running containers the standard output and standard error of the container can be printed out. Several options are available for configuring the log output:

Table 18. Logging configuration

Element	Description
<b>enabled</b>	If set to <code>false</code> log output is disabled. This is useful if you want to disable log output by default but want to use the other configuration options when log output is switched on on the command line with <code>-Ddocker.showLogs</code> . Logging is enabled by default if a <code>&lt;log&gt;</code> section is given.



Element	Description
<b>prefix</b>	<p>Prefix to use for the log output in order to identify the container. You can use placeholders in the prefix which are replaced on the fly:</p> <ul style="list-style-type: none"> <li>• <b>%a</b>: Alias of the image, or, if not set, the short container id.</li> <li>• <b>%c</b>: Short container id (i.e. the first 6 chars of the container id)</li> <li>• <b>%C</b>: The full container id</li> <li>• <b>%n</b>: The image name</li> <li>• <b>%z</b>: An empty string</li> </ul> <p>By default the format is "%a&gt; ".</p>
<b>date</b>	<p>Dateformat to use for log timestamps. If <b>&lt;date&gt;</b> is not given no timestamp will be shown. The date specification can be either a constant or a date format. The recognized constants are:</p> <ul style="list-style-type: none"> <li>• <b>NONE</b> Switch off timestamp output. Useful on the command line ( <b>-Ddocker.logDate=NONE</b>) for switching off otherwise enabled logging.</li> <li>• <b>DEFAULT</b> A default format in the form <b>HH:mm:ss.SSS</b></li> <li>• <b>MEDIUM</b> Joda medium date time format</li> <li>• <b>SHORT</b> Joda short date time format</li> <li>• <b>LONG</b> Joda long date time format</li> <li>• <b>ISO8601</b> Full ISO-8601 formatted date time with milliseconds</li> </ul> <p>As an alternative a date-time format string as recognized by <b>JodaTime</b> is possible. In order to set a consistent date format, the global configuration parameter <b>logDate</b> can be used.</p>
<b>color</b>	<p>Color used for coloring the prefix when coloring is enabled (i.e. if running in a console and <b>useColor</b> is set). The available colors are <b>YELLOW</b>, <b>CYAN</b>, <b>MAGENTA</b>, <b>GREEN</b>, <b>RED</b>, <b>BLUE</b>. If coloring is enabled and now color is provided a color is picked for you.</p>
<b>file</b>	<p>Path to a file to which the log output is written. This file is overwritten for every run and colors are switched off.</p>
<b>driver</b>	<p>Section which can specify a dedicated log driver to use. A <b>&lt;name&gt;</b> tag within this section depicts the logging driver with the options specified in <b>&lt;opts&gt;</b>. See the example below for how to use this.</p>

### Example

```
<log>
  <prefix>TC</prefix>
  <date>default</date>
  <color>cyan</color>
</log>
```

The following example switches on the **gelf logging driver**. This is equivalent to the options `--log-driver=gelf --log-opt gelf-address=udp://localhost:12201` when using `docker run`.

```
<log>
  ...
  <driver>
    <name>gelf</name>
    <opts>
      <gelf-address>udp://localhost:12201</gelf-address>
    </opts>
  </driver>
</log>
```

## 5.3. docker:stop

Stops and removes a docker container. This goal stops every container started with `<docker:start>` either during the same build (e.g. when bound to lifecycle phases when doing integration tests) or for containers created by a previous call to `<docker:start>`

If called within the same build run, only the containers that were explicitly started during the run will be stopped. Existing containers started using `docker:start` for the project will not be affected.

If called as a separate invocation, the plugin will stop and remove any container it finds whose image is defined in the project's configuration. Any existing containers found running whose image name matches but were not started by the plugin will not be affected.

In case the naming strategy for an image is **alias** (i.e. the container name is set to the given alias), then only the container with this alias is stopped. Other containers originating from the same image are not touched.

It should be noted that any containers created prior to version **0.13.7** of the plugin may not be stopped correctly by the plugin because the label needed to tie the container to the project may not exist. Should this happen, you will need to use the Docker CLI to clean up the containers and/or use the `docker.allContainers` option listed below.

For tuning what should happen when stopping there are four global parameters which are typically used as system properties:

Table 19. Stop configuration

Element	Description	Parameter
<b>allContainers</b>	Stops and removes any container that matches an image defined in the current project's configuration. This was the default behavior of the plugin prior up to version 0.13.6	<code>docker.allContainers</code>
<b>containerNamePattern</b>	Default pattern for naming all containers when they are created. See <a href="#">Container Names</a> for details.	<code>docker.containerNamePattern</code>
<b>keepContainer</b>	If set to <code>true</code> not destroy container after they have been stopped. Default is false.	<code>docker.keepContainer</code>
<b>keepRunning</b>	If set to <code>true</code> actually don't stop the container. This apparently makes only sense when used on the command line when doing integration testing (i.e. calling <code>docker:stop</code> during a lifecycle binding) so that the container are still running after an integration test. This is useful for analysis of the containers (e.g. by entering it with <code>docker exec</code> ).	<code>docker.keepRunning</code>
<b>removeVolumes</b>	If set to <code>true</code> will remove any volumes associated to the container as well. This option will be ignored if either <code>keepContainer</code> or <code>keepRunning</code> are true.	<code>docker.removeVolumes</code>

*Example*

```
$ mvn -Ddocker.keepRunning clean install
```

## 5.4. docker:push

This goal uploads images to the registry which have a `<build>` configuration section. The images to push can be restricted with the global option `filter` (see [Global Configuration](#) for details). The registry to push is by default `docker.io` but can be specified as part of the images's `name` the Docker way. E.g. `docker.test.org:5000/data:1.5` will push the image `data` with tag `1.5` to the registry `docker.test.org` at port `5000`. Security information (i.e. user and password) can be specified in multiple ways as described in section [Authentication](#).

By default a progress meter is printed out on the console, which is omitted when using Maven in batch mode (option `-B`). A very simplified progress meter is provided when using no color output (i.e. with `-Ddocker.useColor=false`).

Table 20. Push options

Element	Description	Property
<b>skipPush</b>	If set to <code>true</code> the plugin won't push any images that have been built.	<code>docker.skip.push</code>
<b>skipTag</b>	If set to <code>true</code> this plugin won't push any tags	<code>docker.skip.tag</code>
<b>pushRegistry</b>	The registry to use when pushing the image. See <a href="#">Registry Handling</a> for more details.	<code>docker.push.registry</code>
<b>retries</b>	How often should a push be retried before giving up. This useful for flaky registries which tend to return 500 error codes from time to time. The default is 0 which means no retry at all.	<code>docker.push.retries</code>

## 5.5. docker:watch

When developing and testing applications you will often have to rebuild Docker images and restart containers. Typing `docker:build` and `docker:start` all the time is cumbersome. With `docker:watch` you can enable automatic rebuilding of images and restarting of containers in case of updates.

`docker:watch` is the top-level goal which performs these tasks. There are two watch modes, which can be specified in multiple ways:

- **build** : Automatically rebuild one or more Docker images when one of the files selected by an assembly changes. This works for all files included directly in `assembly.xml` but also for arbitrary dependencies.

*Example*

```
$ mvn package docker:build docker:watch -Ddocker.watchMode=build
```

This mode works only when there is a `<build>` section in an image configuration. Otherwise no automatic build will be triggered for an image with only a `<run>` section. Note that you need the `package` phase to be executed before otherwise any artifact created by this build can not be included into the assembly. As described in the section about `docker:start` this is a Maven limitation. \* **run** : Automatically restart container when their associated images changes. This is useful if you pull a new version of an image externally or especially in combination with the **build** mode to restart containers when their image has been automatically rebuilt. This mode works reliably only when used together with `docker:start`.

*Example*

```
$ mvn docker:start docker:watch -Ddocker.watchMode=run
```

- **both** : Enables both **build** and **run**. This is the default.
- **none** : Image is completely ignored for watching.
- **copy** : Copy changed files into the running container. This is the fast way to update a container, however the target container must support hot deploy, too so that it makes sense. Most application servers like Tomcat supports this.

The mode can also be **both** or **none** to select both or none of these variants, respectively. The default is **both**.

`docker:watch` will run forever until it is interrupted with **CTRL-C** after which it will stop all containers. Depending on the configuration parameters `keepContainer` and `removeVolumes` the stopped containers with their volumes will be removed, too.

When an image is removed while watching it, error messages will be printed out periodically. So don't do that ;-)

Dynamically assigned ports stay stable in that they won't change after a container has been stopped and a new container is created and started. The new container will try to allocate the same ports as

the previous container.

If containers are linked together network or volume wise, and you update a container which other containers dependent on, the dependant containers are not restarted for now. E.g. when you have a "service" container accessing a "db" container and the "db" container is updated, then you "service" container will fail until it is restarted, too.

A future version of this plugin will take care of restarting these containers, too (in the right order), but for now you would have to do this manually.

This maven goal can be configured with the following top-level parameters:

Table 21. Watch configuration

Element	Description	Property
<b>containerNamePattern</b>	Default pattern for naming all containers when they are created. See <a href="#">Container Names</a> for details.	<code>docker.containerNamePattern</code>
<b>keepContainer</b>	As for <code>docker:stop</code> , if this is set to <code>true</code> (and <code>keepRunning</code> is disabled) then all container will be removed after they have been stopped. The default is <code>true</code> .	<code>docker.keepContainer</code>
<b>keepRunning</b>	If set to <code>true</code> all container will be kept running after <code>docker:watch</code> has been stopped. By default this is set to <code>false</code> .	<code>docker.keepRunning</code>
<b>removeVolumes</b>	if set to <code>true</code> will remove any volumes associated to the container as well. This option will be ignored if either <code>keepContainer</code> or <code>keepRunning</code> are <code>true</code> .	<code>docker.removeVolumes</code>
<b>watchInterval</b>	Interval in milliseconds how often to check for changes, which must be larger than 100ms. The default is 5 seconds.	<code>docker.watchInterval</code>
<b>watchMode</b>	Watch mode specifies what should be watched <ul style="list-style-type: none"><li>• <code>build</code> : Watch changes in the assembly and rebuild the image in case</li><li>• <code>run</code> : Watch a container's image whether it changes and restart the container in case</li><li>• <code>copy</code> : Changed files are copied into the container. The container can be either running or might be already exited (when used as a <i>data container</i> linked into a <i>platform container</i>). Requires Docker <math>\geq 1.8</math>.</li><li>• <code>both</code> : <code>build</code> and <code>run</code> combined</li><li>• <code>none</code> : Neither watching for builds nor images. This is useful if you use prefactored images which won't be changed and hence don't need any watching. <code>none</code> is best used on an per image level, see below how this can be specified.</li></ul>	<code>docker.watchMode</code>

Element	Description	Property
<b>watchPostExecute</b>	A command which is executed within the container after files are copied into this container when <b>watchMode</b> is <b>copy</b> . Note that this container must be running.	
<b>watchPostGoal</b>	A maven goal which should be called if a rebuild or a restart has been performed. This goal must have the format <code>&lt;pluginGroupId&gt;:&lt;pluginArtifactId&gt;:&lt;goal&gt;</code> and the plugin must be configured in the <b>pom.xml</b> . For example a post-goal <code>io.fabric8:fabric8:delete-pods</code> will trigger the deletion of PODs in Kubernetes which in turn triggers a new start of a POD within the Kubernetes cluster. The value specified here is the default post goal which can be overridden by <code>&lt;postGoal&gt;</code> in a <code>&lt;watch&gt;</code> configuration.	

Image specific watch configuration goes into an extra image-level `<watch>` section (i.e. `<image><watch>...</watch></image>`). The following parameters are recognized:

Table 22. Watch configuration for a single image

Element	Description
<b>mode</b>	Each image can be configured for having individual watch mode. These take precedence of the global watch mode. The mode specified in this configuration takes precedence over the globally specified mode.
<b>interval</b>	Watch interval can be specified in milliseconds on image level. If given this will override the global watch interval.
<b>postGoal</b>	Post Maven plugin goal after a rebuild or restart. The value here must have the format <code>&lt;pluginGroupId&gt;:&lt;pluginArtifactId&gt;:&lt;goal&gt;</code> (e.g. <code>io.fabric8:fabric8:delete-pods</code> )
<b>postExec</b>	Command to execute after files are copied into a running container when <b>mode</b> is <b>copy</b> .

Here is an example how the watch mode can be tuned:

### Example

```
<configuration>
  <!-- Check every 10 seconds by default -->
  <watchInterval>10000</watchInterval>
  <!-- Watch for doing rebuilds and restarts -->
  <watchMode>both</watch>
  <images>
    <image>
      <!-- Service checks every 5 seconds -->
      <alias>service</alias>
      ....
      <watch>
        <interval>5000</interval>
      </watch>
    </image>
    <image>
      <!-- Database needs no watching -->
      <alias>db</alias>
      ....
      <watch>
        <mode>none</mode>
      </watch>
    </image>
    ....
  </images>
</configuration>
```

Given this configuration

### Example

```
mvn package docker:build docker:start docker:watch
```

You can build the service image, start up all containers and go into a watch loop. Again, you need the `package` phase in order that the assembly can find the artifact build by this project. This is a Maven limitation. The `db` image will never be watch since it assumed to not change while watching.

## 5.6. docker:remove

This goal can be used to clean up images and containers. By default all images with a build configuration are removed. You can tune this by setting the property `removeMode` (property: `docker.removeMode`) to one of the following values:

Table 23. *removeMode* Values

Value	Description
<code>build</code>	All images with a <a href="#">build configuration</a>
<code>run</code>	All images with a <a href="#">run configuration</a>

Value	Description
<code>all</code>	All configured images
<code>data</code>	All data images, which are images without a run configuration.

Previously, this could be tuned also by providing the property `removeAll` which indicates to remove all images managed by this build. Otherwise only data images were delete before 0.24.0. `removeAll` is deprecated and will be removed soone. Please use `removeMode` instead.

As with the other goals, the configuration `image` can be used to tune the images to remove. All containers belonging to the images are removed as well as the all tags assigned to this image

Considering three images 'db','tomcat' and 'data' where 'data' is the only image with a build configuration:

- `mvn docker:remove` will remove 'data'
- `mvn -Ddocker.removeMode=all docker:remove` will remove all three images
- `mvn -Ddocker.filter=data,tomcat docker:remove` will remove 'data'
- `mvn -Ddocker.filter=data,tomcat -Ddocker.removeMode=all docker:remove` will remove 'data' and 'tomcat'

Table 24. Remove options

Element	Description	Property
<b>skipTag</b>	If set to <code>true</code> this plugin won't remove any tags	<code>docker.skip.tag</code>

## 5.7. docker:logs

With this goal it is possible to print out the logs of containers started from images configured in this plugin. By default only the latest container started is printed, but this can be changed with a property. The format of the log output is influenced by run configuration of the configured images. The following system properties can the behaviour of this goal:

Table 25. Logging options

Property	Description
<b>docker.logAll</b>	If set to <code>true</code> the logs of all containers created from images configured for this plugin are printed. The container id is then prefixed before every log line. These images can contain many containers which are already stopped. It is probably a better idea to use <code>docker logs</code> directly from the command line.
<b>docker.follow</b>	If given will wait for subsequent log output until CTRL-C is pressed. This is similar to the behaviour of <code>docker logs -f</code> (or <code>tail -f</code> ).
<b>docker.filter</b>	Filter to restrict the set of images for which log should be fetched. This can be a comma separated list of image or alias names.
<b>docker.logDate</b>	Date format to use. See " <a href="#">Logging</a> " for available formats.



### Example

```
$ mvn docker:logs -Ddocker.follow -Ddocker.logDate=DEFAULT
```

## 5.8. docker:source

The `docker:source` target can be used to attach a docker build archive containing the Dockerfile and all added files to the Maven project with a certain classifier. It reuses the configuration from `[docker:build>]`.

By default, only the first image configuration is used for creating the source archive. You can export all image configurations by setting the `sourceMode` configuration to `all`:

*Export all image configs*

```
<plugin>
  <artifactId>docker-maven-plugin</artifactId>
  <configuration>
    <!-- source mode can be "first" or "all" -->
    <sourceMode>all</sourceMode>
    <!-- .... -->
  </configuration>
</plugin>
```

For exporting all image configurations, `docker:source` uses the image's `alias` as part of the classifier, so it is mandatory that the alias is set for this goal to work when all images should be exported this way. The classifier is calculated as `docker-<alias>` so when the alias is set to `service`, then the classifier is `docker-service`.

If you only export the first image configuration (which is the default), then the classifier is just `docker` (without alias).

`docker:source` can be attached to a Maven execution phase, which is `generate-sources` by default.

For example, this configuration will attach the docker build archive to the artifacts to store in the repository:

```

<plugin>
  <artifactId>docker-maven-plugin</artifactId>
  <!-- ..... -->
  <executions>
    <execution>
      <id>sources</id>
      <goals>
        <goal>source</goal>
      </goals>
    </execution>
  </executions>
</plugin>

```

If not bound to an execution phase, `docker:source` requires that the artifact has been created so you call it best together with `package`

## 5.9. docker:save

The `docker:save` target saves an image defined in the build configuration to a local file, analogous to `docker save`. If the option `saveFile` is not set, the file name is calculated automatically:

- If `saveAlias` is used then the file is stored as `target/<alias>-<project version>.tar.gz`
- Otherwise the archive is stored as `target/<image name without registry and user part>-<image tag>.tar.gz`

Please note that the exported image contains all image layers and can be quite large (also, it takes a bit to export the image).

### Controlling image compression

The file name extension is used to select a compression method for the output.

Extensions	Compression	Type
.tar or unrecognized	No compression	.tar
.tar.gz, .tgz	GZIP compression	.tar.gz
.tar.bz, .tar.bz2, .tar.bzip2	BZIP2 compression	.tar.bz

### Attaching the saved image as an artifact

If `saveClassifier` is set, the saved archive will be attached to the project using the provided classifier and the type determined from the file name. The placeholder `%a` will be replaced with the image alias.

Note that using overriding the default to use `docker` or `docker-%a` may lead to a conflict if a source archive is also attached with `docker:source`.

Table 26. Save options

Element	Description	Property
<b>saveName</b>	The name of the image configuration to save. Must not be used together with <b>alias</b> .	<code>docker.save.name</code>
<b>saveAlias</b>	The alias of the image configuration to save. Must not be used together with <b>name</b> .	<code>docker.save.alias</code>
<b>saveFile</b>	The filename to save.	<code>docker.save.file</code> or <code>docker.file</code> or <code>file</code>
<b>saveClassifier</b>	If set, attach the the saved archive to the project with the provided classifier. A placeholder of <code>%a</code> will be replaced with the image alias.	<code>docker.save.classifier</code>
<b>skipSave</b>	A boolean flag whether to skip execution of the goal.	<code>docker.skip.save</code>

## 5.10. docker:volume-create

This goal creates one or more standalone [Docker volume](#), which can be referenced in a [docker:start](#) configuration for linking to a volume during runtime. Each volume has therefore a unique and referenceable name. Beside the volume driver and driver options can be specified.

*Example for a volume configuration*

```
<plugin>
  <configuration>
    <volumes>
      <volume>
        <name>temp-volume</name>
        <driver>local</driver>
        <opts>
          <type>tmpfs</type>
          <device>tmpfs</device>
          <o>size=100m,uid=1000</o>
        </opts>
        <labels>
          <volatileData>true</volatileData>
        </labels>
      </volume>
    </volumes>
    ...
  </configuration>
</plugin>
```

*Configuration*

The following options are available when creating volumes:

*Table 27. Volume configuration*

Element	Description
<b>name</b>	Name of the volume
<b>driver</b>	Volume driver to use. By default the driver <b>local</b> is used which is created on the local file system. Please refer to your Docker installation which additional drivers are available.
<b>opts</b>	Driver specific options passed in as custom <code>&lt;key&gt;value&lt;/key&gt;</code> where its maps to <code>key=value</code> pairs for driver options as they can be provided from the Docker CLI, too. Each volume driver supports different options. The options supported by the <b>local</b> driver are the well known <a href="#">Linux mount options</a> .
<b>labels</b>	Labels given as <code>&lt;key&gt;value&lt;/key&gt;</code> similar to image labels described in <a href="#">Environment and Labels</a> . These labels are used to tag the volumes themselves.

## 5.11. docker:volume-remove

This goal is the counterpart to [docker:volume-create](#) and removes a volume. Docker volumes are configured outside of Docker images, but can be referenced by them. The configuration is the same as for [docker:volume-create](#)

**Example:**

```
<plugin>
  <configuration>
    <volumes>
      <volume>
        <name>temp-volume</name>
        ....
      </volume>
    </volumes>
    ...
  </configuration>
</plugin>
```

*Configuration*

The configuration is quite simple. Only the name of the volume to delete is required.

Table 28. Volume configuration

Element	Description
<b>name</b>	Name of the volume

# Chapter 6. External Configuration

For special configuration needs, there is the possibility to get the runtime and build configuration from places outside the plugin's configuration. This is done with the help of `<external>` configuration sections which at least has a `<type>` subelement. This `<type>` element selects a specific so called "handler" which is responsible for creating the full image configuration. A handler can decide to use the `<run>` and `<build>` configuration which could be provided in addition to this `<external>` section or it can decide to completely ignore any extra configuration option.

A handler can also decide to expand this single image configuration to a list of image configurations. The image configurations resulting from such a external configuration are added to the *regular* `<image>` configurations without an `<external>` section.

The available handlers are described in the following.

## 6.1. Properties

For simple needs the image configuration can be completely defined via Maven properties which are defined outside of this plugin's configuration. Such a property based configuration can be selected with an `<type>` of `properties`. As extra configuration a prefix for the properties can be defined which by default is `docker`.

For single-image configurations it is also possible to active property based configuration via an externally set property.

By default, property based configuration uses only properties, ignoring any `<build>` and `<run>` sections. To combine values from both sources, use the [property mode configuration](#).

Properties are read from the Maven project (defined in `<properties>` or global Maven configuration from `settings.xml`) and, since 0.25.0, from any `-D` flags given to Maven (takes priority over project properties).

*Example*

```
<image>
  <external>
    <type>properties</type>
    <prefix>docker</prefix> <!-- this is the default -->
    <mode>only</mode> <!-- this is the default -->
  </external>
</image>
```

Given this example configuration a single image configuration is built up from the following properties, which correspond to the corresponding values in the `<build>` and `<run>` sections. A build configuration is only created when a `docker.from` or a `docker.fromExt` is set.

Table 29. External properties

<code>docker.alias</code>	Alias name
---------------------------	------------

<b>docker.args.BUILDVAR</b>	Set the value of a build variable. The syntax is the same as for specifying environment variables (see below).
<b>docker.assembly.baseDir</b>	Directory name for the exported artifacts as described in an assembly (which is <code>/maven</code> by default).
<b>docker.assembly.descriptor</b>	Path to the assembly descriptor when building an image
<b>docker.assembly.descriptorRef</b>	Name of a predefined assembly to use.
<b>docker.assembly.exportBaseDir</b>	If <code>true</code> export base directory
<b>docker.assembly.ignorePermissions</b>	If set to <code>true</code> existing file permissions are ignored when creating the assembly archive. Deprecated, use a permission mode of <code>ignore</code> instead.
<b>docker.assembly.permissions</b>	can be <code>ignore</code> to use the permission as found on files regardless on any assembly configuration, <code>keep</code> to respect the assembly provided permissions, <code>exec</code> for setting the executable bit on all files (required for Windows when using an assembly mode <code>dir</code> ) or <code>auto</code> to let the plugin select <code>exec</code> on Windows and <code>keep</code> on others. <code>keep</code> is the default value.
<b>docker.assembly.dockerFileDir</b>	specifies a directory containing an external Dockerfile that will be used to create the image. This is deprecated please use <code>docker.dockerFileDir</code> or <code>docker.dockerFile</code> instead.
<b>docker.noCache</b>	Don't use Docker's build cache. This can be overwritten by setting a system property <code>docker.noCache</code> when running Maven.
<b>docker.bind.idx</b>	Sets a list of paths to bind/expose in the container
<b>docker.buildArg.VARIABLE</b>	Set a ARG to be available during build of image. <b>Note:</b> this is handled separately from external configuration, and is always available. See <a href="#">Build Args</a> for more details.
<b>docker.capAdd.idx</b>	List of kernel capabilities to add to the container
<b>docker.capDrop.idx</b>	List of kernel capabilities to remove from the container
<b>docker.cleanup</b>	Cleanup dangling (untagged) images after each build (including any containers created from them). Default is <code>try</code> (which wont fail the build if removing fails), other possible values are <code>none</code> (no cleanup) or <code>remove</code> (remove but fail if unsuccessful)
<b>docker.cmd</b>	Command to execute. This is used both when running a container and as default command when creating an image.
<b>docker.cpus</b>	Specify how much of the available CPU resources a container can use
<b>docker.cpuset</b>	Limit the container to specific CPUs or cores. This can be provided either as a comma-separated list or a hyphen-separated range.
<b>docker.cpushares</b>	Set the proportion of the host machine's cpu cycles available to the container

<b>docker.cacheFrom</b>	List of image names to use as cache sources
<b>docker.domainname</b>	Container domain name
<b>docker.dnsindex</b>	List of dns servers to use
<b>docker.dnsSearchindex</b>	List of dns search domains
<b>docker.dockerArchive</b>	specify an archive which can be loaded with <code>docker load</code> . Use this as an alternative to <code>docker.dockerFile</code> or <code>docker.dockerFileDir</code>
<b>docker.dockerFile</b>	specifies a Dockerfile to use. This property must point to the Dockerfile itself.
<b>docker.dockerFileDir</b>	specifies a directory containing an external dockerfile that will be used to create the image. The dockerfile must be name <code>Dockerfile</code>
<b>docker.entrypoint</b>	Container entry point
<b>docker.exposedPropertyKey</b>	Property part for the exposed container properties like internal IP addresses as described in <a href="#">docker:start</a> .
<b>docker.envVARIABLE</b>	Sets an environment variable used in build and run. E.g. <code>&lt;docker.env.JAVA_OPTS&gt;-Xmx512m&lt;/docker.env.JAVA_OPTS&gt;</code> sets the environment variable <code>JAVA_OPTS</code> . Multiple such entries can be provided. This environment is used both for building images and running containers. The value cannot be empty but can contain Maven property names which are resolved before the Dockerfile is created.
<b>docker.envBuild.VARIABLE</b>	Sets an environment variable used in build only. E.g. <code>&lt;docker.envBuild.JAVA_OPTS&gt;-Xmx512m&lt;/docker.envBuild.JAVA_OPTS&gt;</code> sets the environment variable <code>JAVA_OPTS</code> . Multiple such entries can be provided. This environment is building images only. The value cannot be empty but can contain Maven property names which are resolved before the Dockerfile is created.
<b>docker.envRun.VARIABLE</b>	Sets an environment variable used in run only. E.g. <code>&lt;docker.envRun.JAVA_OPTS&gt;-Xmx512m&lt;/docker.envRun.JAVA_OPTS&gt;</code> sets the environment variable <code>JAVA_OPTS</code> . Multiple such entries can be provided. This environment is used both for running containers only. The value cannot be empty but can contain Maven property names which are resolved before the Dockerfile is created.
<b>docker.envPropertyFile</b>	specifies the path to a property file whose properties are used as environment variables in run. The environment variables takes precedence over any other environment variables specified.
<b>docker.extraHostsindex</b>	List of <code>host:ip</code> to add to <code>/etc/hosts</code>
<b>docker.filter</b>	Enable and set the delimiters for property replacements. By default properties in the format <code>\${..}</code> are replaced with Maven properties. You can switch off property replacement by setting this property to <code>false</code> . When using a single char like <code>@</code> then this is used as a delimiter (e.g <code>@...@</code> ). See <a href="#">Filtering</a> for more details.
<b>docker.from</b>	Base image for building an image. Must be set when an image is created (or <code>fromExt</code> )

<b>docker.fromExt.VARIABLE</b>	Base image for building an image (extended format), which also triggers a build of an image.
<b>docker.healthcheck.cmd</b>	Command to use for a healthcheck
<b>docker.healthcheck.interval</b>	Interval for how often to run a healthcheck (in seconds or with a given time unit)
<b>docker.healthcheck.mode</b>	If set to <b>none</b> disable a healthcheck from a base image
<b>docker.healthcheck.retries</b>	Number of retries for how often to retry a healthcheck until it is considered to have failed
<b>docker.healthcheck.startPeriod</b>	Initialization time for containers that need time to bootstrap. Probe failure during that period will not be counted towards the maximum number of retries. However, if a health check succeeds during the start period, the container is considered started and all consecutive failures will be counted towards the maximum number of retries. (in seconds or with a given time unit)
<b>docker.healthcheck.timeout</b>	Timeout after which a healthcheck command is considered to be failed (in seconds or with a given time unit)
<b>docker.hostname</b>	Container hostname
<b>docker.imagePropertyConfiguration</b>	Special property to activate property configuration without altering XML file (see <a href="#">Activating property configuration externally</a> ).
<b>docker.imagePullPolicy.build</b>	Specific pull policy used when building images. See <a href="#">imagePullPolicy</a> for the possible values.
<b>docker.imagePullPolicy.run</b>	Specific pull policy used for downloading images to run. See <a href="#">imagePullPolicy</a> for the possible values.
<b>docker.labels.LABEL</b>	Sets a label which works similarly like setting environment variables.
<b>docker.loadNamePattern</b>	Search the archive specified in <b>docker.dockerArchive</b> for the specified image name and creates a tag from the matched name to the build image name specified in <b>docker.name</b> .
<b>docker.log.enabled</b>	Use logging (default: <b>true</b> )
<b>docker.log.prefix</b>	Output prefix
<b>docker.log.color</b>	ANSI color to use for the prefix
<b>docker.log.date</b>	Date format for printing the timestamp
<b>docker.log.driver.name</b>	Name of an alternative log driver
<b>docker.log.driver.opts.VARIABLE</b>	Logging driver options (specified similarly as in <b>docker.env.VARIABLE</b> )



<b>docker.links.idx</b>	defines a list of links to other containers when starting a container. <i>idx</i> can be any suffix which is not used except when <i>idx</i> is numeric it specifies the order within the list (i.e. the list contains first entries with numeric indexes sorted and the all non-numeric indexes in arbitrary order). For example <code>&lt;docker.links.1&gt;db&lt;/docker.links.1&gt;</code> specifies a link to the image with alias 'db'.
<b>docker.maintainer</b>	defines the maintainer's email as used when building an image
<b>docker.memory</b>	Container memory (in bytes)
<b>docker.memorySwap</b>	Total memory (swap + memory) <code>-1</code> to disable swap
<b>docker.name</b>	Image name
<b>docker.namingStrategy</b>	Container naming (either <code>none</code> or <code>alias</code> )
<b>docker.network.mode</b>	Network mode to use which can be <code>none</code> , <code>host</code> , <code>bridged</code> , <code>container</code> or <code>custom</code>
<b>docker.network.name</b>	Name of the custom network when mode is <code>custom</code> , or for mode <code>container</code> the image alias name used to create the container.
<b>docker.network.alias.idx</b>	One or more alias for a custom network. Only used when the network mode is <code>custom</code>
<b>docker.noCache</b>	Don't use a cache when building the image
<b>docker.optimize</b>	if set to true then it will compress all the <code>runCmds</code> into a single RUN directive so that only one image layer is created.
<b>docker.portPropertyFile</b>	specifies a path to a port mapping used when starting a container.
<b>docker.ports.idx</b>	Sets a port mapping. For example <code>&lt;docker.ports.1&gt;jolokia.ports:8080&lt;/docker.ports.1&gt;</code> maps the container port 8080 dynamically to a host port and assigns this host port to the Maven property <code>\${jolokia.port}</code> . See <a href="#">Port mapping</a> for possible mapping options. When creating images only the right most port is used for exposing the port. For providing multiple port mappings, the index should be count up.
<b>docker.registry</b>	Registry to use for pushing images.
<b>docker.restartPolicy.name</b>	Container restart policy
<b>docker.restartPolicy.retry</b>	Max restart retries if <code>on-failure</code> used
<b>docker.run.idx</b>	List of commands to <code>RUN</code> when creating the image
<b>docker.securityOpts.idx</b>	List of <code>opt</code> elements to specify kernel security options to add to the container. For example <code>docker.securityOpt.1=seccomp=unconfined</code>
<b>docker.shmsize</b>	Size of <code>/dev/shm</code> in bytes.

<b>docker.tags.idx</b>	List of tags to apply to a built image
<b>docker.tmpfs.idx</b>	One or more mount points for a <b>tmpfs</b> . Add mount options after a <b>:</b>
<b>docker.ulimits.idx</b>	Ulimits for the container. Ulimit is specified with a soft and hard limit <b>&lt;type&gt;=&lt;soft limit&gt;[:&lt;hard limit&gt;]</b> . For example <b>docker.ulimits.1=memlock=-1:-1</b>
<b>docker.user</b>	User to switch to at the end of a Dockerfile. Not to confuse with <b>docker.username</b> which is used for authentication when interacting with a Docker registry.
<b>docker.volumes.idx</b>	defines a list of volumes to expose when building an image
<b>docker.volumesFrom.idx</b>	defines a list of image aliases from which the volumes should be mounted of the container. The list semantics is the same as for links (see above). For examples <b>&lt;docker.volumesFrom.1&gt;data&lt;/docker.volumesFrom.1&gt;</b> will mount all volumes exported by the <b>data</b> image.
<b>docker.wait.http.url</b>	URL to wait for during startup of a container
<b>docker.wait.http.method</b>	HTTP method to use for ping check
<b>docker.wait.http.status</b>	Status code to wait for when doing HTTP ping check
<b>docker.wait.time</b>	Amount of time to wait during startup of a container (in ms)
<b>docker.wait.logging</b>	Wait for a log output to appear.
<b>docker.wait.exec.postStart</b>	Command to execute after the container has start up.
<b>docker.wait.exec.preStop</b>	Command to execute before command stops.
<b>docker.wait.exec.breakOnError</b>	If set to "true" then stop the build if the a <b>postStart</b> or <b>preStop</b> command failed
<b>docker.wait.shutdown</b>	Time in milliseconds to wait between stopping a container and removing it.
<b>docker.wait.tcp.mode</b>	Either <b>mapped</b> or <b>direct</b> when waiting on TCP connections
<b>docker.wait.tcp.host</b>	Hostname to use for a TCP wait checks
<b>docker.wait.tcp.port.idx</b>	List of ports to use for a TCP check.
<b>docker.wait.kill</b>	Time in milliseconds to wait between sending SIGTERM and SIGKILL to a container when stopping it.
<b>docker.workdir</b>	Container working directory where the image is build in

<b>docker.workingDir</b>	Current Working dir for commands to run in when running containers
--------------------------	--

Multiple property configuration handlers can be used if they use different prefixes. As stated above the environment and ports configuration are both used for running container and building images. If you need a separate configuration you should use explicit run and build configuration sections.

#### *Combining property and XML configuration*

By default the property handler will only consider properties and ignore any other image configuration in the XML/POM file. This can be changed by adding the `<mode>` configuration (since version 0.25.0), which can have one of the following values:

Table 30. Property mode

<code>only</code>	Only look at properties, ignore any <code>&lt;run&gt;</code> or <code>&lt;build&gt;</code> sections for this image. This is the default, and also the behavior in versions before 0.25.0.
<code>override</code>	Use property if set, else fall back to value found in <code>&lt;run&gt;</code> or <code>&lt;build&gt;</code> sections for this image.
<code>fallback</code>	Use value found in <code>&lt;run&gt;</code> or <code>&lt;build&gt;</code> sections for this image, else fall back to to property value.
<code>skip</code>	Effectively disable properties, same as not specifying the <code>&lt;external&gt;</code> section at all.

#### *Activating property configuration externally*

It also possible to activate property configuration by setting the property `docker.imagePropertyConfiguration` to a valid `property mode`, without adding an `<external>` section. The plugin will then use any properties with default `docker.` prefix. This can be useful if most of the configuration is specified in XML/POM file, but there is need to override certain configuration values without altering the POM file (instead add this to a parent POM or global settings.xml).

If set in parent POM, but not wanted in specific project, the property could be overridden locally with the value `skip` to disabled property configuration for that particular project. If set in settings.xml however, by Maven design, that value will always take precedence over any properties defined in pom.xml.

For configurations with multiple images, using this property will by default produce an error. All images would then use the same `docker` property prefix, resulting in multiple identical configurations. This can be overruled by adding an explicit `<external>` configuration element with an explicit `<prefix>` to all images (or at least all but one). Normally you'd want to use different prefix for each image, but if explicitly set it does allow you to use the same prefix (even `docker`) on all images. This is useful in case you just want to share a few properties. This only makes sense when `property mode` is `override` or `fallback` and image-specific configuration are defined in the POM configuration.

For examples, see [here](#)

#### *Merging POM and property values*

For some fields it may be desired to merge values from both POM and properties. For example, in a certain run environment we might want to inject a `http_proxy` environment variable, but we do not want to add this to the POM file.

This is solved using a **Combine policy** which can be either `replace` or `merge`. Merge is only available for configuration of Map or List type. For scalar values such as strings and integers, it is not supported. For Maps, both sources are merged, with the priority source taking precedence. For Lists, they are concatenated, with values from the priority source being added first.

Combine policy is specified per configuration key/property, and the default in most cases is currently `replace`. The following keys have `merge` as default policy:

- `docker.args`
- `docker.envBuild`
- `docker.envRun`
- `docker.labels`
- `docker.ports`
- `docker.tags`

This can be overridden individually for all configuration keys (of map/list type) by setting an additional property suffixed `._combine`. For example, to not merge ports, set `docker.ports._combine=replace`, and to enable merging of dns, set `docker.dns._combine=merge`.

```
<properties>
  <docker.name>jolokia/demo</docker.name>
  <docker.alias>service</docker.alias>
  <docker.from>consol/tomcat:7.0</docker.from>
  <docker.assembly.descriptor>src/main/docker-
assembly.xml</docker.assembly.descriptor>
  <docker.env.CATALINA_OPTS>-Xmx32m</docker.env.CATALINA_OPTS>
  <docker.label.version>${project.version}</docker.label.version>
  <docker.ports.jolokia.port>8080</docker.ports.jolokia.port>
  <docker.wait.url>http://localhost:${jolokia.port}/jolokia</docker.wait.url>
</properties>

<build>
  <plugins>
    <plugin>
      <groupId>io.fabric8</groupId>
      <artifactId>docker-maven-plugin</artifactId>
      <configuration>
        <images>
          <image>
            <external>
              <type>properties</type>
              <prefix>docker</prefix>
            </external>
          </image>
        </images>
      </configuration>
    </plugin>
  </plugins>
</build>
```

```
<properties>
  <docker.assembly.descriptor>src/main/docker-
assembly.xml</docker.assembly.descriptor>
  <docker.env.CATALINA_OPTS>-Xmx32m</docker.env.CATALINA_OPTS>
  <docker.label.version>${project.version}</docker.label.version>
  <docker.ports.jolokia.port>8080</docker.ports.jolokia.port>
  <docker.wait.url>http://localhost:${jolokia.port}/jolokia</docker.wait.url>
</properties>

<build>
  <plugins>
    <plugin>
      <groupId>io.fabric8</groupId>
      <artifactId>docker-maven-plugin</artifactId>
      <configuration>
        <images>
          <image>
            <external>
              <type>properties</type>
              <prefix>docker</prefix>
              <mode>override</mode>
            </external>

            <name>jolokia/demo</name>
            <alias>service</alias>

            <build>
              <from>consol/tomcat:7.0</from>
              <labels>
                <software>tomcat</software>
              </labels>
            </build>
          </image>
        </images>
      </configuration>
    </plugin>
  </plugins>
</build>
```

This would build the same image as the previous example. If instead built with `mvn docker:build -Ddocker.from=console/tomcat:8.0 -Ddocker.tags.0=tc8-test` it would build from that image instead, and also add that tag to the image.

If `-Ddocker.labels.status=beta` is added, the image would be given two labels: `status=beta` and `software=tomcat`. If `-Ddocker.labels._combine=replace` is added, the image would be given one label only: `status=beta`.

Global ~/.m2/settings.xml file:

```
<profiles>
  <profile>
    <id>http-proxy</id>
    <properties>
      <docker.buildArg.http_proxy>
http://proxy.example.com:8080</docker.buildArg.http_proxy>
      <docker.runArg.http_proxy>
http://proxy.example.com:8080</docker.runArg.http_proxy>
      <docker.imagePropertyConfiguration>override</docker.imagePropertyConfiguration>
    </properties>
  </profile>
</profiles>
```

```
<build>
  <plugins>
    <plugin>
      <groupId>io.fabric8</groupId>
      <artifactId>docker-maven-plugin</artifactId>
      <configuration>
        <images>
          <image>
            <name>jolokia/demo</name>
            <alias>service</alias>
            <build>
              <from>consol/tomcat:7.0</from>
            </build>
          </image>
        </images>
      </configuration>
    </plugin>
  </plugins>
</build>
```

When the plugin is executed, on a machine with the given settings.xml, the plugin will see the `docker.imagePropertyConfiguration` configuration and enable the property merging feature. When building, it will inject the `http_proxy` build ARG, and when running, it will inject the `http_proxy` ENV variable. The rest of the configuration will be sourced from the XML, unless the Maven project has any other `docker.*` properties defined.

*Example, external activation of property configuration, two images*

Using the same global ~/.m2/settings.xml file as in previous example, but with two image definitions and no extra configuration will cause an error, saying that you cannot use property `docker.imagePropertyConfiguration` on projects with multiple images.

By adding an explicit external configuration directive with the same prefix in both images, this error is disabled.

```

<build>
  <plugins>
    <plugin>
      <groupId>io.fabric8</groupId>
      <artifactId>docker-maven-plugin</artifactId>
      <configuration>
        <images>
          <image>
            <external>
              <type>properties</type>
              <prefix>docker</prefix>
              <mode>override</mode>
            </external>

            <name>jolokia/demo</name>
            <alias>service</alias>
            <build>
              <from>consol/tomcat:7.0</from>
            </build>
          </image>

          <image>
            <external>
              <type>properties</type>
              <prefix>docker</prefix>
              <mode>override</mode>
            </external>

            <name>jolokia/demo2</name>
            <alias>service2</alias>
            <build>
              <from>consol/tomcat:7.0</from>
            </build>
          </image>
        </images>
      </configuration>
    </plugin>
  </plugins>
</build>

```

The behaviour will now be same as previous example. Note that you must explicitly state `<mode>override</mode>`, otherwise it will use the default `only`.

## 6.2. Docker Compose

This plugin supports also configuration via a [docker-compose](#) file, especially for running containers specified in `docker-compose.yml`. Docker Compose handling is available also as an external configuration provider.



## Example

```
<image>
  <alias>webapp</alias> ①
  <name>fabric8/compose-demo:latest</name>

  <external> ②
    <type>compose</type> ③
    <basedir>src/main/docker</basedir> ④
    <composeFile>docker-compose.yml</composeFile>
  </external>

  <build> ⑤
    <assembly>....</assembly>
  </build>
  <run>...</run>
  <watch>...</watch>
</image>
```

- ① The alias of the image is used as correlation key mapping to a service in the Docker Compose file
- ② An `<external>` configuration handler needs to be used for Docker Compose support
- ③ The type for the external configuration provider must be set to **compose**
- ④ Additional configuration for the handler where to find the compose file
- ⑤ Extra `<build>`, `<run>` and `<watch>` configuration can be provided which are used as default configuration for the Docker compose service **webapp** (as specified with the alias)

The following options can be provided:

Table 31. Docker compose configuration

Element	Description	Default
<b>basedir</b>	Basedir where to find the compose file and which is also used as the current directory when examining the compose file. Any relative volume bindings will be resolved relative to this directory.	<code>\${basedir}/src/main/docker</code>
<b>composeFile</b>	Name of the compose file to use	<code>docker-compose.yml</code>
<b>ignoreBuild</b>	Ignore the compose file's <b>build</b> : section and use the plugin's build configuration exclusively.	<code>false</code>

The Docker Compose file can contain variables as described in the [Docker Compose documentation](#). These are substituted with Maven project properties. Please note, when the `docker-compose.yml` with variables is to be used with the `docker-compose` CLI command, that these variables must also be valid environment variables (i.e. must not contain a `.`).

In addition to the `docker-compose.yml` you can add all known options for `<build>`, `<run>` and `<watch>` configuration elements which are then used as defaults and are overwritten by the configuration defined in the `docker-compose.yml` file. The merging between the XML configuration and the information found in `docker-compose.yml` is correlated via the `<alias>` name. E.g. if the XML

image configuration is aliased with `webapp` then its is used as a default configuration for a Docker Compose service name `webapp`. All other services defined in the compose file are left untouched.

### 6.2.1. Limitations

The following Docker Compose file keywords are not yet supported:

- `cgroup_parent`, `devices`, `env_file`, `expose`, `pid`, `security_opt`, `stop_signal`, `cpu_quota`, `ipc`, `mac_address`, `read_only` are not yet supported (but might be in a future version).
- `extend` for including other Docker Compose files is not yet implemented.
- Only **services** are currently evaluated, there is no supported yet for **volumes** and **networks**.

# Chapter 7. Registry handling

Docker uses registries to store images. The registry is typically specified as part of the name. I.e. if the first part (everything before the first `/`) contains a dot (`.`) or colon (`:`) this part is interpreted as an address (with an optionally port) of a remote registry. This registry (or the default `docker.io` if no registry is given) is used during push and pull operations. This plugin follows the same semantics, so if an image name is specified with a registry part, this registry is contacted. Authentication is explained in the next [section](#).

There are some situations however where you want to have more flexibility for specifying a remote registry. This might be because you do not want to hard code a registry into `pom.xml` but provide it from the outside with an environment variable or a system property.

This plugin supports various ways of specifying a registry:

- If the image name contains a registry part, this registry is used unconditionally and can not be overwritten from the outside.
- If an image name doesn't contain a registry, then by default the default Docker registry `docker.io` is used for push and pull operations. But this can be overwritten through various means:
  - If the `<image>` configuration contains a `<registry>` subelement this registry is used.
  - Otherwise, a global configuration element `<registry>` is evaluated which can be also provided as system property via `-Ddocker.registry`.
  - Finally an environment variable `DOCKER_REGISTRY` is looked up for detecting a registry.

This registry is used for pulling (i.e. for autopull the base image when doing a `docker:build`) and pushing with `docker:push`. However, when these two goals are combined on the command line like in `mvn -Ddocker.registry=myregistry:5000 package docker:build docker:push` the same registry is used for both operation. For a more fine grained control, separate registries for *pull* and *push* can be specified.

- In the plugin's configuration with the parameters `<pullRegistry>` and `<pushRegistry>`, respectively.
- With the system properties `docker.pull.registry` and `docker.push.registry`, respectively.

### Example

```
<configuration>
  <registry>docker.jolokia.org:443</registry>
  <images>
    <image>
      <!-- Without an explicit registry ... -->
      <name>jolokia/jolokia-java</name>
      <!-- ... hence use this registry -->
      <registry>docker.ro14nd.de</registry>
      ....
    </image>
    <image>
      <name>postgresql</name>
      <!-- No registry in the name, hence use the globally
            configured docker.jolokia.org:443 as registry -->
      ....
    </image>
    <image>
      <!-- Explicitely specified always wins -->
      <name>docker.example.com:5000/another/server</name>
    </image>
  </images>
</configuration>
```

There is some special behaviour when using an externally provided registry like described above:

- When *pulling*, the image pulled will be also tagged with a repository name **without** registry. The reasoning behind this is that this image then can be referenced also by the configuration when the registry is not specified anymore explicitly.
- When *pushing* a local image, temporarily a tag including the registry is added and removed after the push. This is required because Docker can only push registry-named images.

# Chapter 8. Authentication

When pulling (via the `autoPull` mode of `docker:start`) or pushing image, it might be necessary to authenticate against a Docker registry.

There are five different locations searched for credentials. In order, these are:

- Providing system properties `docker.username` and `docker.password` from the outside.
- Using a `<authConfig>` section in the plugin configuration with `<username>` and `<password>` elements.
- Using OpenShift configuration in `~/.config/kube`
- Using a `<server>` configuration in `~/.m2/settings.xml`
- Login into a registry with `docker login` (credentials in a credential helper or in `~/.docker/config.json`)

Using the username and password directly in the `pom.xml` is not recommended since this is widely visible. This is easiest and transparent way, though. Using an `<authConfig>` is straight forward:

```
<plugin>
  <configuration>
    <image>consol/tomcat-7.0</image>
    ...
    <authConfig>
      <username>jolokia</username>
      <password>s!cr!t</password>
    </authConfig>
  </configuration>
</plugin>
```

The system property provided credentials are a good compromise when using CI servers like Jenkins. You simply provide the credentials from the outside:

*Example*

```
mvn -Ddocker.username=jolokia -Ddocker.password=s!cr!t docker:push
```

The most *mavenish* way is to add a server to the Maven settings file `~/.m2/settings.xml`:

### Example

```
<servers>
  <server>
    <id>docker.io</id>
    <username>jolokia</username>
    <password>s!cr!t</password>
  </server>
  ....
</servers>
```

The server id must specify the registry to push to/pull from, which by default is central index `docker.io` (or `index.docker.io` / `registry.hub.docker.com` as fallbacks). Here you should add your `docker.io` account for your repositories. If you have multiple accounts for the same registry, the second user can be specified as part of the ID. In the example above, if you have a second account 'fabric8io' then use an `<id>docker.io/fabric8io</id>` for this second entry. I.e. add the username with a slash to the id name. The default without username is only taken if no server entry with a username appended id is chosen.

The most *secure* way is to rely on docker's credential store or credential helper and read confidential information from an external credentials store, such as the native keychain of the operating system. Follow the instruction on [the docker login documentation](#).

As a final fallback, this plugin consults `$DOCKER_CONFIG/config.json` if `DOCKER_CONFIG` is set, or `~/.docker/config.json` if not, and reads credentials stored directly within this file. This unsafe behavior happened when connecting to a registry with the command `docker login` from the command line with older versions of docker (pre 1.13.0) or when docker is not configured to use a [credential store](#).

## 8.1. Pull vs. Push Authentication

The credentials lookup described above is valid for both push and pull operations. In order to narrow things down, credentials can be provided for pull or push operations alone:

In an `<authConfig>` section a sub-section `<pull>` and/or `<push>` can be added. In the example below the credentials provider are only used for image push operations:

### Example

```
<plugin>
  <configuration>
    <image>consol/tomcat-7.0</image>
    ...
    <authConfig>
      <push>
        <username>jolokia</username>
        <password>s!cr!t</password>
      </push>
    </authConfig>
  </configuration>
</plugin>
```

When the credentials are given on the command line as system properties, then the properties `docker.pull.username` / `docker.pull.password` and `docker.push.username` / `docker.push.password` are used for pull and push operations, respectively (when given). Either way, the standard lookup algorithm as described in the previous section is used as fallback.

## 8.2. OpenShift Authentication

When working with the default registry in OpenShift, the credentials to authenticate are the OpenShift username and access token. So, a typical interaction with the OpenShift registry from the outside is:

```
oc login
...
mvn -Ddocker.registry=docker-registry.domain.com:80/default/myimage \
    -Ddocker.username=$(oc whoami) \
    -Ddocker.password=$(oc whoami -t)
```

(note, that the image's username part ("default" here") must correspond to an OpenShift project with the same name to which you currently connected account has access).

This can be simplified by using the system property `docker.useOpenShiftAuth` in which case the plugin does the lookup. The equivalent to the example above is

```
oc login
...
mvn -Ddocker.registry=docker-registry.domain.com:80/default/myimage \
    -Ddocker.useOpenShiftAuth
```

Alternatively the configuration option `<useOpenShiftAuth>` can be added to the `<authConfig>` section.

For dedicated *pull* and *push* configuration the system properties `docker.pull.useOpenShiftAuth` and `docker.push.useOpenShiftAuth` are available as well as the configuration option `<useOpenShiftAuth>`

in an `<pull>` or `<push>` section within the `<authConfig>` configuration.

If `useOpenShiftAuth` is enabled then the OpenShift Konfiguration will be looked up in `$KUBECONFIG` or, if this environment variable is not set, in `~/.kube/config`.

## 8.3. Password encryption

Regardless which mode you choose you can encrypt password as described in the [Maven documentation](#). Assuming that you have setup a *master password* in `~/.m2/security-settings.xml` you can create easily encrypt passwords:

*Example*

```
$ mvn --encrypt-password  
Password:  
{QJ6wvuEfacMHklqsmrtrn1/C10LqLm8hB7yUL23K0Ko=}
```

This password then can be used in `authConfig`, `docker.password` and/or the `<server>` setting configuration. However, putting an encrypted password into `authConfig` in the `pom.xml` doesn't make much sense, since this password is encrypted with an individual master password.

## 8.4. Extended Authentication

Some docker registries require additional steps to authenticate. [Amazon ECR](#) requires using an IAM access key to obtain temporary docker login credentials. The `docker:push` and `docker:pull` goals automatically execute this exchange for any registry of the form `<awsAccountId> .dkr.ecr.<awsRegion> .amazonaws.com`, unless the `skipExtendedAuth` configuration (`docker.skip.extendedAuth` property) is set true.

Note that for an ECR repository with URI `123456789012.dkr.ecr.eu-west-1.amazonaws.com/example/image` the d-m-p's `docker.registry` should be set to `123456789012.dkr.ecr.eu-west-1.amazonaws.com` and `example/image` is the `<name>` of the image.

You can use any IAM access key with the necessary permissions in any of the locations mentioned above except `~/.docker/config.json`. Use the IAM **Access key ID** as the username and the **Secret access key** as the password. In case you're using temporary security credentials provided by the AWS Security Token Service (AWS STS), you have to provide the **security token** as well. To do so, either specify the `docker.authToken` system property or provide an `<auth>` element alongside username & password in the `authConfig`.

In case you are running on an EC2 instance that has an appropriate IAM role assigned (e.g. a role that grants the AWS built-in policy *AmazonEC2ContainerRegistryPowerUser*) authentication information doesn't need to be provided at all. Instead the instance meta-data service is queried for temporary access credentials supplied by the assigned role.



# Chapter 9. Implicit properties

There are some implicit configurations in docker maven plugin that are not so straightforward. These are simply workarounds to get docker-maven-plugin's flow right; just to overcome limitations of Maven and other things. Some of these are mentioned below:

- If the only value of the `env` parameter is a docker-maven-plugin internal property which has been set implicitly you have to prefix the property with a single `+` like in `+${docker.container.test.ip}`. This is necessary due to some Maven limitations which simply interpolates a lone, non defined property, to an empty string which can't then be replaced by this plugin after the initial interpolation phase.
- When providing port mapping in a format like `host.ip:host.port:80`, you need to prefix property with a single `+`. In this form, the host ip of the container will be placed into a Maven property name `host.ip`. If docker reports that value to be `0.0.0.0`, the value of `docker.host.address` will be substituted instead. In the event you want to use this form and have the container bind to a specific hostname/ip address, you can declare a Maven property of the same name (`host.ip` in this example) containing the value to use. `host:port` works in the same way as described above.

# Chapter 10. Further reading

- Examples:
  - [Examples](#) are below [samples/](#) and contain example setups which you can use as blueprints for your own projects.
  - A [Shootout](#) for comparing docker maven plugins
  - Another [sample project](#) with a Microservice and a Database.
- [ChangeLog](#) has the release history of this plugin.
- [Contributing](#) explains how you can contribute to this project. Pull requests are highly appreciated!