

EXPERIMENT 2

Student Name: ARNAV SHARMA

Branch: AIT-CSE-AIML

Semester: 5

Subject Name: ADBMS

UID: 24BAI70781

Section/Group: 24AIT_KRG1_B

Subject Code: 24CSP-310

Question A:

A university administration requires an analytical performance report for each academic unit. Write a PostgreSQL solution to calculate the average marks scored by students grouped by their respective departments. The solution must join the student profile, course subjects, and grade marks tables, returning a breakdown sorted by the highest average marks down to the lowest.

Solution:

1. Query:

```
SELECT D.DEPT_NAME AS DEPARTMENT,
ROUND(AVG(M.MARKS_SCORED), 2) AS AVERAGE_MARKS
FROM DEPARTMENTS AS D
JOIN
STUDENTS AS S
ON D.DEPT_ID=S.DEPT_ID
JOIN
MARKS AS M
ON
S.STUDENT_ID = M.STUDENT_ID
GROUP BY D.DEPT_NAME
ORDER BY AVERAGE_MARKS DESC;
```

2. Output

department	average_marks
character varying (50)	numeric
1 Mathematics	95.00
2 Computer Science	83.33

EXPERIMENT 2

Question B:

Two legacy HR systems (A and B) have separate records of employee salaries. These records may overlap. Management wants to **merge these datasets** and identify **each unique employee** (by EmpID) along with their **lowest recorded salary** across both systems.

Objective

1. Combine two tables A and B.
2. Return each EmpID with their **lowest salary**, and the corresponding **Ename**.

Table A

EmpID	Ename	Salary
1	AA	1000
2	BB	300

Table B

EmpID	Ename	Salary
2	BB	400
3	CC	100

Query:

```
SELECT EMPID, MIN(ENAME) AS ENAME, MIN(SALARY) AS SALARY
FROM
(
SELECT * FROM A
UNION ALL
SELECT * FROM B
) AS INTERMEDIATE_RES
GROUP BY EMPID;
```

Output:

	empid integer	ename text	salary integer
1	3	CC	100
2	2	BB	300
3	1	AA	1000

EXPERIMENT 2

Question C:

A multinational organization maintains separate records for employee information and department details. The management wants to identify the employees who receive the highest salary within their respective departments for an annual performance report.

If more than one employee earns the same highest salary in a department, all such employees should be included in the report. The final output should display the **Department Name**, **Employee Name**, and **Salary**, arranged in ascending order of department name.

Note: The employee and department information are maintained in separate normalized tables.

Input Table: **Employee**

ID	NAME	SALARY	DEPT_ID
1	JOE	70000	1
2	JIM	90000	1
3	HENRY	80000	2
4	SAM	60000	2
4	MAX	90000	1

Department

ID	DEPT_NAME
1	IT
2	SALES

Query :

a)

```
SELECT D.DEPT_NAME, E.NAME, E.SALARY
FROM
EMPLOYEE AS E
JOIN
DEPARTMENT AS D
ON E.DEPARTMENT_ID = D.ID
WHERE E.SALARY IN
(
SELECT MAX(SALARY)
FROM EMPLOYEE AS E1
WHERE E1.DEPARTMENT_ID = E.DEPARTMENT_ID
)
ORDER BY DEPT_NAME;
```

b)

```
SELECT D.DEPT_NAME, E.NAME, E.SALARY
FROM
EMPLOYEE AS E
JOIN
DEPARTMENT AS D
ON E.DEPARTMENT_ID = D.ID
WHERE E.SALARY IN
```

EXPERIMENT 2

```
(  
SELECT MAX(SALARY)  
FROM EMPLOYEE AS E1  
WHERE E1.DEPARTMENT_ID = E.DEPARTMENT_ID  
AND E1.SALARY NOT IN  
(  
SELECT MAX(SALARY)  
FROM EMPLOYEE AS E2  
WHERE E2.DEPARTMENT_ID = E1.DEPARTMENT_ID  
)  
)  
ORDER BY DEPT_NAME
```

Output:

	dept_name character varying (50) 🔒	name character varying (50) 🔒	salary integer 🔒
1	IT	JOE	70000
2	SALES	SAM	60000