

EXPERIMENT 3

Student Name: ARNAV SHARMA

Branch: AIT-CSE-AIML

Semester: 5

Subject Name: ADBMS

UID: 24BAI70781

Section/Group: 24AIT_KRG1_B

Subject Code: 24CSP-310

QUESTION A:

You are given with the Employee schema; the task is to find the highest score for each respective department.

For eg: department D1 have the highest score as 5.28. Hence in the output, final updated score for D1 should be 5.28.

Same with the other departments i.e., D2, D3 and D4.

QUERY:

```
INSERT INTO Employee (EID, DEPT, SCORES)  
VALUES
```

```
(1, 'D1', 1.00),  
(2, 'D1', 5.28),  
(3, 'D1', 4.00),  
(4, 'D2', 8.00),  
(5, 'D1', 2.50),  
(6, 'D2', 7.00),  
(7, 'D3', 9.00),  
(8, 'D4', 10.20);
```

```
update employee as e1  
set scores =  
(  
select max(scores)  
from employee  
where dept = e1.dept  
)
```

```
select * from employee;
```

EXPERIMENT 3

RESULT:

Showing rows: 1 to 8   Page No: 1 of

	eid [PK] integer 	dept character varying (20) 	scores numeric 
1	1	D1	5.28
2	2	D1	5.28
3	3	D1	5.28
4	4	D2	8.00
5	5	D1	5.28
6	6	D2	8.00
7	7	D3	9.00
8	8	D4	10.20

EXPERIMENT 3

QUESTION B:

A company maintains records of products sold by different salespersons. The management wants to prepare a sales performance report by identifying the salesperson(s) who generated the highest overall sales revenue. If multiple salespersons have the same highest total sales amount, all of them must be included in the final report. Return the seller ID(s) satisfying this condition

QUERY:

```
select seller_id
from
(select
seller_id, sum(amount) as max_amt
from orders
group by seller_id
)
where max_amt =
(select
max(max_amt)
from
(select
seller_id, sum(amount) as max_amt
from orders
group by seller_id
));
```

RESULT:

Showing rows: 1 to 1

seller_id
integer

1 3

EXPERIMENT 3

QUESTION C:

A company maintains employee salary records for different departments. The management wants to prepare a report containing employees whose salaries fall among the top three highest distinct salary values within their respective departments. If multiple employees receive the same qualifying salary, all such employees must be included in the final report. Display the department name, employee name, and salary for every qualifying employee.

QUERY:

```
select d.name as department,
       e.name as employee,
       e.salary as salary
from   employee as e
join   department as d
on     e.departmentid = d.id
where  (
        select count(distinct e2.salary)
        from employee as e2
        where e2.departmentid = e.departmentid
        and   e2.salary > e.salary
      ) < 3
order by department;
```

EXPERIMENT 3

RESULT:

Showing rows: 1 to 6   Page No: 1 of 1  			
	department character varying (50) 	employee character varying (50) 	salary integer 
1	IT	Joe	85000
2	IT	Max	90000
3	IT	Randy	85000
4	IT	Will	70000
5	Sales	Henry	80000
6	Sales	Sam	60000