


Diffuse Reflection



Two Key Characteristics:

1. The surface with reflectivity as $K_d = (k_r, k_g, k_b)$, e.g., diffuse coefficients;

2. The decay of incident light is inverse proportional to its distance from the source to the surface point. e.g., $1/(r^2)$, where r is being the distance from the light source to the surface.

Specular vs. diffuse reflection

https://en.wikipedia.org/wiki/Diffuse_reflection

Diffuse Reflection: the reflection of light uniformly in all different directions, the surface of this reflection exhibits Lambert reflection, e.g., equal luminance when viewed from all directions.

Diffuse Reflection Formulation

$$\vec{I}(x, y, z) = (I_r(x, y, z), I_g(x, y, z), I_b(x, y, z))$$

... (1)

Object $I(x, y, z)$ consists of r, g, b 3 primitive colors, as denoted in (1).

Light source $I_s(x, y)$ consists of r, g, b 3 primitive colors as follows, but let's simplify it as white color, so r, g, b all equal and have the highest value (if in graphics, they are 255)

$$\vec{I}_s(x, y, z) = (I_r(x, y, z), I_g(x, y, z), I_b(x, y, z))$$

... (2)

Object surface consists of reflectivity, e.g., coefficient of reflection

$$\vec{K}_d = (K_r, K_g, K_b)$$

... (3)

\vec{r}_d vector in Equation (1) is a ray equation, just like $I_s(x, y, z)$ but has no r, g, b primitive color defined in it for the matter of simplicity.

Diffuse Reflection Equation

$$\vec{I}(x, y, z) = (I_r(x, y, z), I_g(x, y, z), I_b(x, y, z))$$

Each primitive color of the object $I(x, y, z)$ can be written as


$$I_r = K_{dr} \frac{\vec{n} \cdot \vec{r}}{\|\vec{n}\| \|\vec{r}\|} \frac{1}{\|\vec{r}\|_2^2} \quad \dots (1.1)$$

where

$$\|\vec{r}\|_2^2 = x_r^2 + y_r^2 + z_r^2$$

$$I_g = K_{dg} \frac{\vec{n} \cdot \vec{r}}{\|\vec{n}\| \|\vec{r}\|} \cdot \frac{1}{\|\vec{r}\|_2^2} \quad \dots (1.2)$$

$$I_b = K_{db} \frac{\vec{n} \cdot \vec{r}}{\|\vec{n}\| \|\vec{r}\|} \cdot \frac{1}{\|\vec{r}\|_2^2} \quad \dots (1.3)$$




Reference: Computer Graphics, C. K. Pokorny, C. F. Gerald, pp. 514

11-8-2018 Diffuse Reflection Equation

CMPE163 CG & AR. Nov 8, 2018

1) Homework: Bring LSM303 Sensor w/ Pie Board to the class for Show & Tell; Transformation


Diffuse Reflection: Background. 


$I(x,y) = (r(x,y), g(x,y), b(x,y)) \dots (1)$
 Primitive Colour Texture
 Dark Black $(0,0,0)$
 Brightest White $(1,1,1)$
 Brightest Red
 Colour Space

$\vec{I}(x,y) = \vec{I}_{dif}(x,y) + \vec{I}_{spe}(x,y) + \vec{I}_{amb}(x,y) \dots (2)$
 pixel Graphics
 VS Vector Graphics

I_{dif} Uniformly Distributed in All Directions
 (Not Function of "Eye"). \vec{I}_{spe} function of "The Eye"
 \vec{I}_{amb} generated from Indirect "offset" Light Source. Produces High Lights.

Consider Diffuse Reflection.


$K_d = (k_r, k_g, k_b) \dots (3)$ Normalized $[0,1]$
 Reflectivity Blue Red $k_r = k_g = k_b = 1$ full Reflection
 VIS 

CMPE163 CG & AR 2/1. 

$$\vec{n} \cdot \vec{r} = \|\vec{n}\| \|\vec{r}\| \cos \alpha \dots (4)$$

(@ pixel location) From P_s to the pixel location

$$\cos \alpha = \frac{\vec{n} \cdot \vec{r}}{\|\vec{n}\| \|\vec{r}\|} \dots (4*)$$



Property 1: ~ Max Intensity when $\alpha = 0$ (\vec{P}_s Light Ray w/ \vec{n})
 ~ Intensity = 0, when $\alpha = \pm \pi/2$
 Intensity Decay follows $\cos \alpha$ function.

Property 2: Intensity Decay follows $\frac{1}{\|\vec{r}\|^2}$ (Squared distance from the pt. light Source to that pixel location).

Property 3: Colour & Intensity combined is computed Base Reflectivity K_d and Property 1 & 2 (@ this pixel location)

11-8-2018 Diffuse Reflection Calculation

CMPE163 CG & AR. Nov 8, 2018

From Egn (1.1) (on github) Example: pp.4.

$$I_r = K_{dr} \frac{\vec{n} \cdot \vec{r}}{\|\vec{n}\| \|\vec{r}\|} \frac{1}{\|\vec{r}\|^2} \dots (1.1)$$

$$\vec{T}_s(x_s, y_s, z_s) = (10, 200, 500), \vec{P}_i(x_i, y_i, z_i), i=2.$$

$$\vec{n} = (0, 0, 1), \vec{r} = \vec{P}_s + \lambda(\vec{P}_s - \vec{P}_i) = (x_s, y_s, z_s) + \lambda(x_s - x_i, y_s - y_i, z_s - z_i) \mid \lambda = -1 \quad \vec{P}_i$$

Assume $K_{dr} = 0.85$, therefore $[0, 255]$

$$I_r = 0.85 \cdot \frac{(0, 0, 1) \cdot (x_i, y_i, z_i)}{\|(0, 0, 1)\| \|(x_i, y_i, z_i)\|} \cdot \frac{1}{\sqrt{(x_s - x_i)^2 + (y_s - y_i)^2 + (z_s - z_i)^2}}$$

further colour
C/C++ #define $K_{d,red} = 0.85$ $(z_s - z_i)^2$

$$I_{red} = K_{d,red} * z[i];$$

$$\text{float tmp} = \text{Sqrt}(x[i] * x[i] + y[i] * y[i] + z[i] * z[i])$$

$$\text{float tmp2} = \text{Sqrt}((x_s - x[i]) * (x_s - x[i]) + (y_s - y[i]) * (y_s - y[i]) + (z_s - z[i]) * (z_s - z[i]));$$

$$I_{red} = I_{red} / (\text{tmp} * \text{tmp2});$$

CMPE163 CG & AR 4/

Interp. 200 - - - $\gamma(x_i, y_i)$ Linear Interpolation.
 (x_1, y_1) dist $x \frac{y_2 - y_1}{y_2 - y_1} = \frac{x_2 - x_1}{x_2 - x_1} \dots (6)$
 Min $\vec{P}_4(\text{Near}) \vec{P}_2(\text{far})$

$$\frac{y_2 - y_1}{x_2 - x_1} = \frac{y_2 - y_1}{x_2 - x_1}, y_2 - y_1 = \frac{y_2 - y_1}{x_2 - x_1} (x_2 - x_1)$$

$$-y = -y_2 + \frac{y_2 - y_1}{x_2 - x_1} (x_2 - x) = -y_2 - \frac{y_2 - y_1}{x_2 - x_1} x +$$

$$y = y_2 + \frac{y_2 - y_1}{x_2 - x_1} x - x_2 \frac{y_2 - y_1}{x_2 - x_1} \frac{y_2 - y_1}{x_2 - x_1} x_2$$

$$y = \frac{y_2 - y_1}{x_2 - x_1} x + (y_2 - x_2 \frac{y_2 - y_1}{x_2 - x_1}) \dots (6*)$$

Suppose: $\frac{1}{\sqrt{x_i^2 + y_i^2 + z_i^2} \sqrt{(x_s - x_i)^2 + (y_s - y_i)^2 + (z_s - z_i)^2}} = \Delta_i$
 find $\min \{ \Delta \}, \max \{ \Delta \}$
 $i \in [0, 1, \dots, 6]$ $i \in [0, 1, \dots, 6]$ $\dots (7*)$

Hence, 2 pts can be found, in Egn (6*)
 Indep. Variable is Δ_i , function $(y, \text{Intensity})$ is intensity.

$$(x_2, y_2) = (\min \Delta_i, 50)$$

$$(x_1, y_1) = (\max \Delta_i, 200) \dots (8)$$

11-8-2018 Diffuse Reflection Calculation (2)

CMPE130 C.G. & A.R. Nov 8, 2018

From Eqn (8), we have \vec{P}_4 (Shortest Distance to \vec{P}_5) $\Rightarrow \text{Max } \Delta_i =$

\vec{P}_0 (Farset Point from \vec{P}_5) $\Rightarrow \text{Min } \Delta_0 \quad \text{Max } \Delta_4$.

Hence Eqn (6*) is well defined.

Now, For the rest of the pts, $\vec{P}_i(x_i, y_i, z_i)$

From Diffuse Reflection Eqn (1.1), we have

$$\Delta_j = \frac{1}{\sqrt{x_j^2 + y_j^2 + z_j^2} \sqrt{(x_s - x_j)^2 + (y_s - y_j)^2 + (z_s - z_j)^2}}$$

then. Let $\Delta_j = X$ in Eqn (6),

find the Intensity with this X value.

Example: $I_{d, \text{red}} = \frac{50 - 220}{\text{Min } \Delta_0 - \text{Max } \Delta_4} \Delta_j +$

$\vec{P}_5(10, 200, 500), + \left(50 - \text{Min } \Delta_0 \cdot \frac{50 - 220}{\text{Min } \Delta_0 - \text{Max } \Delta_4} \right) \dots (9)$


$\vec{P}_4(20, 200, 200) \Rightarrow I_{d, \text{red}} = 220$

$\vec{P}_0(100, 100, 200) \Rightarrow I_{d, \text{red}} = 50 \quad \text{Min } \Delta_0 = ? \checkmark$

$\vec{P}_2(60, 150, 200) \Rightarrow I_{d, \text{red}} = ? \quad \text{Max } \Delta_4 = ? \checkmark$

$\Delta_j = \Delta_2 = \frac{1}{\sqrt{60^2 + 150^2 + 200^2} \sqrt{(100 - 60)^2 + (200 - 150)^2 + (500 - 200)^2}}$

Diffuse Reflection Example



Example: Suppose we have a single light source $P_s(10, 200, 500)$, now define its (r, g, b) color, so we have single color light source as $I_s(r_s, g_s, b_s) = (1.0, 0.0, 0.0)$, Find the diffuse reflection on the 3D floating arrow by first find color intensity on each of the marked vertex, and then find the color of each pixel of the cursor.

Assume reflection coefficient $K_d = (1.0, 0.0, 0.0)$

Harry Li, Ph.D

From equation (1.1),

$$I_r = K_{dr} \frac{\vec{n} \cdot \vec{r}}{\|\vec{n}\| \|\vec{r}\|} \frac{1}{\|\vec{r}\|_2^2}$$

... (1.1)

First, find ray equation to, say, one of the vertex, $P_2(25, 70, 50)$.

Then find the distance from light source to P_2 .

Then use the given condition, find the color intensity at P_2 location.

Repeat this process to find color intensity for all the vertex from P_0 to P_6 .

Calculation After Perspective Projection








Image (graphics) plane after perspective projection.



Color On The Line Segments (DDA)



Given P_i and P_{i+1} , find line equation first;

Then, rasterization of the line by using DDA (Digital Differential Algorithm);

Then use bilinear interpolation to find the color on each point on the line. As a result you will have figure labeled as figure 2.


DDA Algorithm Example

The key :


Slop $|a|$ should be less than or equal to 1,
Otherwise will have to swap x and y;

$$y_{k+1} = a * x_{k+1} + b \quad \dots (1)$$

$$x_{k+1} = x_k; \quad \dots (2)$$




Color On The Line Segments (Interpolation)




Example: when rasterization is done, then find color for each point on the line by interpolation.

Example (Interpolation)

Step 1. Interpolation along x-direction;
Step 2. Interpolation along y-direction;
Where at each direction, we just use one dimensional interpolation.




Color Inside the Line Boundary (Interpolation)




Example: when rasterization is done, then find color for each point on the line inside the boundary lines by interpolation.

Example (Interpolation)

Raster scan the image, use linear interpolation find the color between boundaries.



Diffuse Reflection Example



From equation (1.1),

$$I_r = K_{dr} \frac{\vec{n} \cdot \vec{r}}{\|\vec{n}\| \|\vec{r}\|} \frac{1}{\|\vec{r}\|^2}$$

... (1.1)

First, find ray equation to, say, one of the vertex, P₂(25, 70, 50).

Then find the distance from light source to P₂.

Then use the given condition, find the color intensity at P₂ location.

Repeat this process to find color intensity for all the vertex from P₀ to P₆.

Example: Suppose we have a single light source P_s(10,200, 500), now define its (r, g, b) color, so we have single color light source as I_s(r_s, g_s, b_s) = (1.0, 0.0, 0.0), Find the diffuse reflection on the 3D floating arrow by first find color intensity on each of the marked vertex, and then find the color of each pixel of the cursor.

Assume reflection coefficient K_d=(1.0, 0.0, 0.0)

Harry Li, Ph.D

Calculation After Perspective Projection





Image (graphics) plane after perspective projection.

