

A value that can change, depending on conditions or on information passed to program. ← Variables

vars:
player: sachin

{{ 'player' }} is a batsman and plays for india.{{ 'player' }} kohli was a key member of team which won worldcup in 2011 and 2025,,,
,,,,,,,,,,{{ 'player' }}{{ 'player' }}.....{{ 'player' }}

10000 word article



```
---
- hosts: all
  become: true
  vars:
    pkgname1: wget
    pkgname2: unzip
    sentence: hello welcome to the world
  tasks:
    - name: Install a package
      ansible.builtin.package:
        name: "{{ pkgname1 }}"
        state: present
    - name: install "{{ pkgname2 }}"
      ansible.builtin.package:
        name: "{{ pkgname2 }}"
        state: present
    - name: printing a message
      ansible.builtin.debug:
        msg: "{{ sentence }}"
```

we can separately create variables.yml and different playbook

vi variables.yml

```
pkg_name: apache2
pkg_state: present
file_path: /home/devops/mydemo.txt
file_state: touch
~
```

Now we will call these variables in a separate playbook.

vi myplaybook1.yml

```
---
- hosts: all
  become: true
  vars_files:
    - variables.yml
  tasks:
    - name: install {{ pkg_name }} on hostmachnes
      ansible.builtin.package:
        name: "{{ pkg_name }}"
        state: "{{ pkg_state }}"
    - name: create a new file on hostserver
      ansible.builtin.file:
        path: "{{ file_path }}"
        state: "{{ file_state }}"
~
```

Prompt the user to enter the value of the variable at runtime

```
---
- hosts: all
  become: true
  vars_prompt:
    - name: pkg_name
      prompt: enter the package name
    - name: pkg_state
      prompt: enter the package state
  tasks:
    - name: install a package "{{ pkg_name }}"
      ansible.builtin.package:
        name: "{{ pkg_name }}"
        state: "{{ pkg_state }}"
~
```