

A \LaTeX Tutorial

Johann von Tiesenhausen

Ingenuity Labs Research Institute
Queen's University, Kingston, Canada

June 8, 2022

Introduction

Documents

Lists

Tables

Math

Figures

References

Commands

Goals of this presentation

A \LaTeX Tutorial

2 of 24

- **Not** comprehensive
- Starting reference to show that \LaTeX isn't *that* scary
- Provide some tips & tricks
- Tons of useful \LaTeX tutorials by [Overleaf](#)

Introduction

Documents

Lists

Tables

Math

Figures

References

Commands

Why \LaTeX is cool

Some Important Person

May 13, 2022

What is L^AT_EX?

- From [Encyclopædia Britannica](#):

“TeX, a page-description computer programming language developed during 1977–86 by Donald Knuth, a Stanford University professor, to improve the quality of mathematical notation in his books. Text formatting systems [...] embed plain text formatting commands in a document, which are then interpreted by the language processor to produce a formatted document for display or printing.”

- L^AT_EX is the corresponding software package
- TeX consists of the greek letters τ , ϵ , χ , and is pronounced “lay-tech”

A L^AT_EX document

```
\documentclass[12pt]{article}

% remaining preamble goes here

\begin{document}

% content goes here

\end{document}
```

A L^AT_EX Tutorial

4 of 24

Introduction

Documents

Lists

Tables

Math

Figures

References

Commands

Creating a title

A L^AT_EX Tutorial

5 of 24

```
\documentclass[12pt]{article}

\title{Automatic Material Classification}
\author{Unal Artan \thanks{Thank you to Natalie \& Johann}}
\date{August 24, 2021}

\begin{document}

\maketitle
...
```

Introduction

Documents

Lists

Tables

Math

Figures

References

Commands

Adding sections

A L^AT_EX Tutorial

6 of 24

Introduction

Documents

Lists

Tables

Math

Figures

References

Commands

```
...
\section{Wavelet Analysis}
```

Researchers began studying wavelets in the 30s, because of their inherent cuteness in comparison to waves.

```
\subsection{Digression}
```

Would that this were a whiteboard instead \dots

```
\end{document}
```

Automatic Material Classification

Unal Artan *

August 24, 2021

1 Wavelet Analysis

Researchers began studying wavelets in the 30s, because of their inherent cuteness in comparison to waves.

1.1 Digression

Would that this were a whiteboard instead ...

*Thank you to Natalie & Johann

Common commands

comments	% ...
bold	\textbf{...}
<i>italic</i>	\textit{...} or \emph{...}
<u>underline</u>	\underline{...}
inline equations	\$...\$
block equations	\$\$...\$\$ or \[...\]
...and many more!	\ldots

\include{...} is used to insert L^AT_EX code from another file in-place

Dimensions

Introduction

Documents

Lists

Tables

Math

Figures

References

Commands

Dimension	Description
pt	point, smallest unit of measure
in	inch (72.27 pt)
cm	centimeter
mm	millimeter
em	relative to current point size (e.g., for 11pt font, 1em = 11pt)
en	half the width of em

Command	Description
\vspace{...}	add vertical space
\hspace{...}	add horizontal space

Typesetting notes

- Extra spaces between words are ignored
- An empty line starts a new **paragraph**
- Two backslashes (\\\) **forces** a line break, but does not start a new paragraph (i.e., no indent)
- Periods are treated as the **end of a sentence**, unless followed by a comma or backslash (e.g., i.e.\.)
- Tilde (~) inserts **non-breaking whitespace**
- **Opening quotes** are denoted by 1–2 grave accents (` or ``)
- **Closing quotes** are denoted by 1–2 apostrophes (' or ")

Lists I: Itemize

```
\begin{itemize}
  \item Lima
  \item[-] Navy
  \item Kidney
  \begin{itemize}
    \item[yes] Bean
    \item[no] Stone
  \end{itemize}
\end{itemize}
```

- Lima
- Navy
- Kidney
 - yes Bean
 - no Stone

Lists II: Enumerate

```
\begin{enumerate}
  \item One
  \item Two
  \item Three
  \begin{enumerate}
    \item Three Eh
    \item Three Bee
  \end{enumerate}
\end{enumerate}
```

1. One
2. Two
3. Three
 - 3.a Three Eh
 - 3.b Three Bee
- 4 Four?!

Introduction

Documents

Lists

Tables

Math

Figures

References

Commands

Tables

```
\begin{tabular}{ | r | c c | }
```

```
\hline
    & col1 & col2 \\
\hline
row1 & r1c1 &
row2 &       & r2c2 \\
\hline
\end{tabular}
```

	col1	col2
row1	r1c1	
row2		r2c2

[Introduction](#)[Documents](#)[Lists](#)[Tables](#)[Math](#)[Figures](#)[References](#)[Commands](#)

Common math syntax

A L^AT_EX Tutorial

13 of 24

[Introduction](#)[Documents](#)[Lists](#)[Tables](#)[Math](#)[Figures](#)[References](#)[Commands](#)

Description	Code	Output
subscript	<code>x_y</code>	x_y
superscript	<code>x^y</code>	x^y
grouping	<code>x^{y+z}</code>	x^{y+z}
fraction	<code>\frac{x}{y}</code>	$\frac{x}{y}$
square root	<code>\sqrt{x+y}</code>	$\sqrt{x+y}$
greek letters	<code>\alpha \beta \gamma</code>	$\alpha \beta \gamma$
spacing	<code>\; \: \, \!</code>	contextual

Equations

```
\begin{equation}
\beta(s) = \int^{\infty}_{-\infty} CWT(s, \tau) d\tau
\label{eq:CWTint}
\end{equation}
```

[Introduction](#)[Documents](#)[Lists](#)[Tables](#)[Math](#)[Figures](#)[References](#)[Commands](#)

$$\beta(s) = \int_{-\infty}^{\infty} CWT(s, \tau) d\tau \quad (1)$$

Multiline equations

A L^AT_EX Tutorial

15 of 24

Introduction

Documents

Lists

Tables

Math

Figures

References

Commands

```
\begin{equation}
\begin{split}
a_{1, X} = & a_{1,x} \cos{\alpha} \\
& - a_{1,z} \sin{\alpha}
\end{split}
\end{equation}
```

$$a_{1,X} = a_{1,x} \cos \alpha \quad (2)$$
$$- a_{1,z} \sin \alpha$$

Creating a figure I

```
\begin{figure}[t]
  \centering
  \includegraphics[height=0.65\textheight]{figures/loader_
    diagram.png}
  \caption{The Kubota R520s robotic 1-tonne-capacity wheel
    loader that was used for field experiments.}
  \label{fig:loader}
\end{figure}
```

Introduction

Documents

Lists

Tables

Math

Figures

References

Commands

Creating a figure II

A L^AT_EX Tutorial

17 of 24

Introduction

Documents

Lists

Tables

Math

Figures

References

Commands



Figure 1: The Kubota R520s robotic 1-tonne-capacity wheel loader that was used for field experiments.

Label references

A L^AT_EX Tutorial

18 of 24

Introduction

Documents

Lists

Tables

Math

Figures

References

Commands

```
| ``\dots the Kubota Loader in Figure~\ref{fig:loader}''
```

“...the Kubota Loader in Figure 1”

```
| ``see Equation~\ref{eq:CWTint}''
```

“see Equation 1”

Bibliography references

BibTeX entry (.bib files):

```
@inproceedings{artan2021,
  author    = {Artan, Unal and Fernando, Heshan and Marshall, Joshua A.},
  booktitle = {2021 IEEE/ASME International Conference on Advanced Intelligent Mechatronics (AIM)},
  title     = {Automatic Material Classification via Proprioceptive Sensing and Wavelet Analysis During
              Excavation},
  year      = {2021},
  pages     = {612–617},
  doi       = {10.1109/AIM46487.2021.9517696}
}
```

```
‘‘\dots due to breakthrough research \cite{artan2021}’’
```

“...due to breakthrough research [1]”

[Introduction](#)[Documents](#)[Lists](#)[Tables](#)[Math](#)[Figures](#)[References](#)[Commands](#)

Inserting a bibliography

A L^AT_EX Tutorial

20 of 24

Introduction

Documents

Lists

Tables

Math

Figures

References

Commands

Often requires you to precompile your document, run bibtex, then compile it again with resolved references ...

```
\bibliographystyle{ieeetr}  
\bibliography{references.bib}
```

- [1] U. Artan, H. Fernando, and J. A. Marshall, “Automatic material classification via proprioceptive sensing and wavelet analysis during excavation,” in *2021 IEEE/ASME International Conference on Advanced Intelligent Mechatronics (AIM)*, pp. 612–617, 2021.

Hyperlinks

A L^AT_EX Tutorial

21 of 24

```
| \ href{https://ieeexplore.ieee.org/document/9517696}{Paper}
```

[Paper](https://ieeexplore.ieee.org/document/9517696)

```
| \hypertarget{link:resolved}{This part}
| \hyperlink{link:resolved}{That part}
```

This part

That part

Introduction

Documents

Lists

Tables

Math

Figures

References

Commands

Custom commands

A L^AT_EX Tutorial

22 of 24

```
| \newcommand{cmd}{[args][ default]{ def}}
```

cmd	name of the command
args	number of parameters
default	default value for optional first parameter #1
def	command body

[Introduction](#)[Documents](#)[Lists](#)[Tables](#)[Math](#)[Figures](#)[References](#)[Commands](#)

```
| \newcommand{\proot}[2][]{\sqrt[\dim{#1}]{#2}}  
| \[ \proot[3]{x + y} + \proot{x} \]
```

$$\sqrt[3]{x+y} + \sqrt{x}$$

Custom environments I

A L^AT_EX Tutorial

23 of 24

Introduction

Documents

Lists

Tables

Math

Figures

References

Commands

```
| \newenvironment{name}[args][default]{begdef}{enddef}
```

name name of the environment

args number of parameters

default default value for optional first parameter #1

begdef \begin command body

enddef \end command body

Custom environments II

```
\newenvironment{LARGEcenter}{\begin{center}\LARGE}{\end{center}}  
  
\begin{tinycenter}  
    Thank you for your time!  
\end{tinycenter}
```

Any questions?

A L^AT_EX Tutorial

24 of 24

Introduction

Documents

Lists

Tables

Math

Figures

References

Commands