

Homework 4: Implementing Graphs

You have been provided with two different implementations of a *Graph*: an adjacency matrix implementation (*GraphAdjMatrix.cpp*) and an adjacency list implementation (*GraphAdjList.cpp*). Please go through the two files thoroughly to understand each and every line of the program. This time we are using object oriented programming concepts. So, graph data structure has been implemented using a C++ class *Graph*. In addition to this class, two other classes are **already and fully implemented** in the file: *Queue* class to be used later by the BFS function of *Graph* and *ArrayList* class that has been used by the *Graph* class to store adjacency list information. Please understand them carefully including the constructor and destructor functions.

The following functions are already implemented in the *Graph* class:

- *void setnVertices(int n)* : Sets the number of vertices in the graph. This function initializes the graph data structure by allocating memory for the graph storage.
- *void addEdge(int u, int v)* : Adds an edge (*u, v*) to the graph.
- *void printGraph()*: Prints the graph in adjacency list format.

For this homework, you are required to add the following functions to the above implementations (**both files**):

Task 1: *void removeEdge(int u, int v)*. Removes the edge (*u, v*) from the graph.

Task 2: *bool isEdge(int u, int v)*. Returns true if (*u, v*) is an edge, otherwise returns false.

Task 3: *int getDegree(int u)*. Returns the degree of a vertex *u*.

Task 4: *bool hasCommonAdjacent(int u, int v)*. Returns true if vertices *u* and *v* have some common adjacent vertices. Otherwise, it should return false.

Task 5: *void bfs(int source)*. Runs BFS algorithm on the graph using *source* as the source vertex. BFS statistics like parent, distance, and color information must be saved in class variables. So, you will need to define these as class private variables. Use the given *Queue* class in BFS. Define BFS related variables, i.e., parent, distance, and color, as class variables and initialize them memory appropriately in the *Graph* constructor. See Coreman book for the algorithm.

Task 6: *int getDist(int u, int v)*. Returns the shortest path distance from vertex *u* to vertex *v*. You will first need to run BFS on the graph using *u* as the source vertex. Then, you will use the *dist* array to find the distance.

Task 7: *void dfs()*. Runs DFS algorithm on the graph. DFS statistics like parent, color, discovery time, and finish time must be saved in class variables (declare the required variables inside the class). See Coreman book for the algorithm.

Task 8: *Graph destructor function*. Implement the destructor function for the *Graph* class. View the destructor functions of *Queue* and *ArrayList* to get some hints.

You must also satisfy the following requirements:

- **Write main function codes to test all of the above tasks.**
- You must extend the given code.
- You may be provided an updated and corrected version of this document later if It is required.
- *You must not use other's code. You must not share your code. You must not copy from any other sources such as web, friends, relatives, etc. In all cases, you will earn a 0 and will move closer to getting an "F" grade in the course.*