

| Comment | Description | Designator | Footprint | LibRef | Quantity |
|--------------------|--|--|----------------------------|--------------------|----------|
| 100uF | Capacitor pol | C1, C5 | C SMD TAN 2917 (E) | Capacitor | 2 |
| 100nF | Capacitor non-pol | C2, C3, C8 | C 0805 (2012) | Capacitor NP | 3 |
| 47uF | Capacitor pol | C4 | C SMD TAN 2312 (C) | Capacitor | 1 |
| 1uF | Capacitor non-pol | C6 | C 0805 (2012) | Capacitor NP | 1 |
| 0.1F/5.5V | Capacitor pol | C7 | C Super Case A | Capacitor | 1 |
| 33pF | Capacitor non-pol | C9, C10, C11, C12, C13 | C 0603 (1608) | Capacitor NP | 5 |
| 10pF | Capacitor non-pol | C14, C15, C16 | C 0603 (1608) | Capacitor NP | 3 |
| С | Capacitor non-pol | C17, C18, C19, C20 | C 0603 (1608) | Capacitor NP | 4 |
| CON DC PWR | DC input connector | CON1 | CON PWR 3.5mm | CON DC PWR | 1 |
| AD 10 005004 | Connector Stereo Phone | CONIO CONIO | CON Stereo pnone 4- | CON Stereo Phone 4 | |
| APJ3-095S64 | 4 poles Arauino Uno sniela pins | CON2, CON3 | pole Arauino Uno Snieia | poles | 2 |
| Arduino Uno shield | connection | CON4 | 2xPins | Arduino Uno shield | 1 |
| SMA | SMA connectors | CON5, CON7 | CON SMA R/A | CON SMA | 2 |
| SIM Holder | SIM Card holder, 6 pins | CON6 | FMS006-2600 | SIM holder 6 pin | 1 |
| 3mm | | Hole1, Hole2, Hole3, Hole4 | SCREW/3M/7M | Screw | 4 |
| JUMP 2 | | J1, J2, J3, J6, J7, J8, J9, J10, J11, J12 | JUMP2 SMD | JUMP 2 | 10 |
| JUMP 3 | | J4, J5, J13, J14 | Header 3 | JUMP 3 | 4 |
| LED | Typical LED | LED1, LED2 | Led SMD 0805 | LED | 2 |
| Header 2 | Header, 2-Pin | P1 | CON Header 2 | Header 2 | 1 |
| Header 5X2 | Header, 5-Pin, Dual row | P2 | Header 5x2 | Header 5X2 | 1 |
| C1815 | NPN Bipolar Transistor | Q1, Q2 | SOT-23 | NPN | 2 |
| 1k | Resistor | R1, R2, R3, R4, R6, R7, R8, R12 | R 0805 (2012) | Resistor | 8 |
| 68 | Resistor | R5 | R 0603 (1608) | Resistor | 1 |
| 200k | Resistor | R9 | R 0805 (2012) | Resistor | 1 |
| 47k | Resistor | R10, R15, R22 | R 0805 (2012) | Resistor | 3 |
| 100k | Resistor | R11 | R 0805 (2012) | Resistor | 1 |
| 4k7 | Resistor | R13, R21 | R 0805 (2012) | Resistor | 2 |
| 330 | Resistor | R14 | R 0805 (2012) | Resistor | 1 |
| 22 | Resistor | R16, R17, R18 | R 0805 (2012) | Resistor | 3 |
| R | Resistor | R19, R20 | R 0603 (1608) | Resistor | 2 |
| Button | Tact switch 2 pin | SW1, SW2 | SW/2/SMD | SW SPST | 2 |
| MIC29302WT | 3.0A LDO Regulator with ADJ. voltage output | U1 | TO-263 5-Lead SMD | MIC29302WT | 1 |
| GTL2003 | 8-bit bidirectional low voltage translator | U2 | TSSOP 20 65P | GTL2003 | 1 |
| 78M05 | regulator | U3 | TO-252 (D-PAK) | 78xx | 1 |
| SIM908 | Module GSM/ GPRS 850/ 900/ 1800/ 1900MHz & GPS | U4 | SIM908 | SIM908 | 1 |
| SMF05C | 5-Line Transient Voltage S | U5 | SOT-363-6 | SMF05C | 1 |
| | | | | | |