

Bringing RIoT-OS to the RIoTboard

Leon Martin George Freie Universität Berlin

Softwareproject - Telematics, 2014





► Designed for developing



- ► Designed for developing
- ► Cortex-A9-based



- Designed for developing
- ► Cortex-A9-based
- ► Freescale i.MX6-architecture



- Designed for developing
- ► Cortex-A9-based
- ► Freescale i.MX6-architecture
- ► Co-processing power



- Designed for developing
- ► Cortex-A9-based
- ► Freescale i.MX6-architecture
- ► Co-processing power
- ► Many different interfaces





Automotive



- Automotive
- ► Industrial



- Automotive
- ► Industrial
- ► Handheld consoles



- Automotive
- ► Industrial
- ► Handheld consoles
- ► Easy developement



► Assess the situation



- Assess the situation
- ▶ Try running anything on the board



- Assess the situation
- ▶ Try running anything on the board
- ► Run our own code



- Assess the situation
- ▶ Try running anything on the board
- ► Run our own code
- ► Get a framework to run
- Split to work on different components individually





▶ UART I/O for debugging and shell communication



- ▶ UART I/O for debugging and shell communication
- ▶ Timer(s) so the kernel can run



- ▶ UART I/O for debugging and shell communication
- ▶ Timer(s) so the kernel can run
- Interrupts



- ▶ UART I/O for debugging and shell communication
- ▶ Timer(s) so the kernel can run
- Interrupts
- ► Set up a stack



- lacktriangle UART I/O for debugging and shell communication
- ► Timer(s) so the kernel can run
- Interrupts
- ► Set up a stack
- ▶ Build it successfully (probably the hardest part :-) )

#### **Unfinished Work**





► The UART



- ► The UART
- ► Timers



- ► The UART
- ▶ Timers
- Interrupts



► Going from u-boot to SDK



- ► Going from u-boot to SDK
- ► The UART initialisation process



▶ Try altering IOMux-configurations for other boards



- ▶ Try altering IOMux-configurations for other boards
- ▶ JTAG-debugging