



GBMParameters::Defining Data

- **training_frame:** H2OFrame used to train model
- **validation_frame:** H2OFrame used to validate model (optional)
- **y:** column name or index of target variable
- **x:** column names (of indices) of predictor variables
(default: all but y and ignored_columns)
- **ignored_columns:** columns to ignore (e.g. ID column)
- **ignore_const_cols:** ignore constant columns (default: True)
- **weights_column:** column by which to weight the data points
- **categorical_encoding:** encoding scheme for categorical variables:
{"enum", "one_hot_explicit", "binary", "eigen",
"label_encoder", "sort_by_response"} (default: "enum")

ISSUES RE

GBM Parameters: Loss Function

(same as RF)

- **distribution:** specifies the loss function, for use in determining gradients
 - 'bernoulli'
 - 'multinomial'
 - 'gaussian'
 - 'poisson'
 - 'gamma'
 - 'laplace'
 - 'quantile'
 - 'huber'
 - 'tweedie'
- **huber_alpha, quantile_alpha**

GBM Parameters: Defining Data

(same as RF)

- **training_frame:** H2OFrame used to train model
- **validation_frame:** H2OFrame used to validate model (optional)
- **y:** column name or index of target variable
- **x:** column names (of indices) of predictor variables
(default: all but y and ignored_columns)
- **ignored_columns:** columns to ignore (e.g. ID column)
- **ignore_const_cols:** ignore constant columns (default: True)
- **weights_column:** column by which to weight the data points
- **categorical_encoding:** encoding scheme for categorical variables:
{"enum", "one_hot_explicit", "binary", "eigen",
"label_encoder", "sort_by_response"} (default: "enum")