## Telemetry Report Revised Format

January 18, 2018

Mickey Spiegel, Jeongkeun Lee: Barefoot Networks

Gordon Brebner: Xilinx

Mukesh Hira: VMware

### Proposed Telemetry Report Format Changes

Promote Switch id to fixed portion of the header, always present


**Switch id**: The unique ID of a switch (generally administratively assigned). Switch IDs must be unique within a management domain.

**hw\_id**: Identifies the hardware subsystem that generated this report, e.g. a specific linecard in a chassis.

**Sequence Number**: From a specific combination of (Switch id, hw\_id) to a particular telemetry report destination, used to detect loss of telemetry reports.

- Flexible format allowing arbitrary combinations of telemetry metadata in the Telemetry Report Header
  - Replaces current Telemetry Drop Report Header and Telemetry Switch Local Report Header
  - Add a small 4 bit length field indicating the Telemetry Report Header length in multiples of 4 octets
  - Add a bitmap indicating which optional metadata is present in the Telemetry Report Header
- Rearrange fields in the first 32 bits of the Telemetry Report Header

#### Current Telemetry Report Fixed Header (12 octets)



NProto: Next Protocol

- 0 Ethernet
- 1 Telemetry Drop header, followed by Ethernet
- 2 Telemetry Switch Local header, followed by Ethernet
- D: Dropped At least one packet matching a drop watchlist was dropped
- Q: Congested Queue Association Indicates the presence of congestion on a monitored queue
- F: Tracked Flow Association Matched a flow watchlist somewhere (INT or iOAM) or locally (postcard)
- hw\_id: Identifies the hardware subsystem that generated this report, e.g. a specific linecard in a chassis
- Sequence Number: From a specific hw\_id to a particular destination, used to detect loss of telemetry reports
- Ingress Timestamp: In nanoseconds

### Revised Telemetry Report Header (16+ octets)

Length of the telemetry report header in multiples of 4 octets

NProto: Next Protocol { 0 Ethernet, 1 IPv4, 2 IPv6 }

RepBits: Report Metadata Bits indicate which optional metadata (4 octets each) is present


bit 0 (MSB): Ingress port id (16 bits) + Egress port id (16 bits)

bit 1: Queue id (8 bits) + Queue occupancy (24 bits)

bit 2: Egress Timestamp (32 bits)

bit 3: Queue id (8 bits) + Drop reason (8 bits) + Padding (16 bits)

#### Simple Ethernet/IP Transport of Telemetry Report



# Backup Slides

#### Telemetry Drop Report Header (12 octets)

```
0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4
```

#### • Defined in [INT]:

Switch id

Ingress port id

Egress port id

Queue id

#### Drop reason

An enumeration that indicates the reason why a packet was dropped, for example as defined in <a href="mailto:github.com/p4lang/switch">github.com/p4lang/switch</a>.

### Telemetry Switch Local Report Header (16 octets)

#### • Defined in [INT]:

Switch id
Ingress port id
Egress port id
Queue id
Queue occupancy
Egress timestamp