

Guia d'Instal·lació

@joan_bono

Què necessites?

- Un ordinador amb:
 - **Debian**
 - **Kali Linux**
 - **Raspbian Jessie**
- Oinkcode:
 - És **GRATUÏT!** 😊
 - Molt recomanable
 - Obtenir el teu [aquí](#).
- Interfície de xarxa identificada:
 - `ip link show`
- Dependències prèvies:
 - `sudo apt-get install git`
- Pacència.

Primeres passes

- Clonar el repositori:

```
git clone https://github.com/joanbono/Snorter.git`  
cd Snorter/src  
bash Snorter.sh -h
```

- **Recomanat:** Executa el programa fent servir un **oinkcode**

```
bash Snorter.sh -o <oinkcode> -i <interface>  
Ex: bash Snorter.sh -o XXXXXXXXXXXXXXXX -i eth0
```

- **No Recomanat:** Executa el programa sense cap **oinkcode**


```
bash Snorter.sh -i interface  
bash Snorter.sh -i eth0
```

Instal·lació de Snort

- Contrassenya de superusuari, i esperar...

```
debian@debian:~/Snorter/src$ bash Snorter.sh -o [redacted] -i eth0
```

```
      ,-,-----,
      \(\(_,-,--
<\--/\>/(/(_--
/./      \
(')      ,      @
\.-,      /
   )-)_/--( >
   ',',  ',,'
```



```
[+] OINKCODE: [redacted]
[+] INTERFACE: eth0
[+] DAQ: daq-2.0.6
[+] SNORT: snort-2.9.9.0
[+] ARCH: x86_64
```

```
[i] INFO: Updating and Upgrading repositories...
```

```
[sudo] password for debian: [redacted]
```

- `Snort` i `daq` s'han instal·lat.

```
[+] INFO: snort-2.9.9.0 installed successfully.
```

```
[i] INFO: Adding user and group SNORT.
```

```
[i] INFO: /var/log/snort and /etc/snort created and configured.
```

```
,,-      -*> Snort! <*-  
o"  )~   Version 2.9.9.0 GRE (Build 56)  
' ' '   By Martin Roesch & The Snort Team: http://www.snort.org/contact#team  
        Copyright (C) 2014-2016 Cisco and/or its affiliates. All rights reserved.  
        Copyright (C) 1998-2013 Sourcefire, Inc., et al.  
        Using libpcap version 1.6.2  
        Using PCRE version: 8.35 2014-04-04  
        Using ZLIB version: 1.2.8
```

```
[+] INFO: SNORT is successfully installed and configured!
```

- Ara toca afegir la `HOME_NET` i la `EXTERNAL_NET` .

```
[!] INFO: Now it's time to edit the SNORT configuration file.
```

```
[i] INFO: Add your HOME_NET address [Ex: 192.168.1.0/24]
```

```
[!] WARNING: Press ENTER to continue. █
```

- Prémer `Intro` per continuar. Obrirà `vim` :
 - Prémer `A` per anar al final de la línia.
 - Afegeix l'adreça i la màscara de la xarxa a protegir.
 - Prémer `Esc` i després `:wq!` per desar canvis.

```
39
40 #####
41 # Step #1: Set the network variables. For more information, see README.variables
42 #####
43
44 # Setup the network addresses you are protecting
45 ipvar HOME_NET 172.16.77.0/24
46
```

- Fes el mateix per a la `EXTERNAL_NET` :

```
[i] INFO: Add your EXTERNAL_NET address [Ex: !$HOME_NET]  
[!] WARNING: Press ENTER to continue. █
```

- Prémer `Intro` per continuar. Obrirà `vim` :
 - Prémer `A` per anar al final de la línia.
 - Afegir l'adreça *atacant*. **Recomanat:** `!$HOME_NET` .
 - Prémer `Esc` i després `:wq!` per desar canvis.

```
46  
47 # Set up the external network addresses. Leave as "any" in most situations  
48 ipvar EXTERNAL_NET !$HOME_NET  
49
```

- Ara la **sortida**. Per defecte, s'habilita el format de sortida `unified2`, però pots habilitar més d'una sortida. Vaig a habilitar la sortida en **CSV** i format **TCPdump**.

```
[i] INFO: Enabling local.rules and adding a PING detection rule...  
[!] WARNING: Unified2 output configured. Configure another output?  
    1 - CSV output  
    2 - TCPdump output  
    3 - CSV and TCPdump output  
    4 - None  
  
Option [1-4]: █
```


- Ara **SNORT** arrancarà en mode **console** . Mana un **PING** des d'altra màquina per comprovar el funcionament.

```
[!] WARNING: Attempting to test ICMP rule in eth0. Send a PING to your SNORT machine. Press Ctrl+C once and wait few seconds to stop the process...

[!] WARNING: Press ENTER to continue.
01/09-12:39:29.229291  [**] [1:10000001:1] Atac per PINGS [**] [Priority: 0] {ICMP} 172.16.77.1 -> 172.16.77.137
01/09-12:39:29.229320  [**] [1:10000001:1] Atac per PINGS [**] [Priority: 0] {ICMP} 172.16.77.137 -> 172.16.77.1
01/09-12:39:30.229230  [**] [1:10000001:1] Atac per PINGS [**] [Priority: 0] {ICMP} 172.16.77.1 -> 172.16.77.137
01/09-12:39:30.229294  [**] [1:10000001:1] Atac per PINGS [**] [Priority: 0] {ICMP} 172.16.77.137 -> 172.16.77.1
01/09-12:39:31.230473  [**] [1:10000001:1] Atac per PINGS [**] [Priority: 0] {ICMP} 172.16.77.1 -> 172.16.77.137
01/09-12:39:31.230526  [**] [1:10000001:1] Atac per PINGS [**] [Priority: 0] {ICMP} 172.16.77.137 -> 172.16.77.1
01/09-12:39:32.231436  [**] [1:10000001:1] Atac per PINGS [**] [Priority: 0] {ICMP} 172.16.77.1 -> 172.16.77.137
01/09-12:39:32.231553  [**] [1:10000001:1] Atac per PINGS [**] [Priority: 0] {ICMP} 172.16.77.137 -> 172.16.77.1
01/09-12:39:33.236303  [**] [1:10000001:1] Atac per PINGS [**] [Priority: 0] {ICMP} 172.16.77.1 -> 172.16.77.137
01/09-12:39:33.236387  [**] [1:10000001:1] Atac per PINGS [**] [Priority: 0] {ICMP} 172.16.77.137 -> 172.16.77.1
01/09-12:39:34.241661  [**] [1:10000001:1] Atac per PINGS [**] [Priority: 0] {ICMP} 172.16.77.1 -> 172.16.77.137
01/09-12:39:34.241796  [**] [1:10000001:1] Atac per PINGS [**] [Priority: 0] {ICMP} 172.16.77.137 -> 172.16.77.1
^C*** Caught Int-Signal
snort: no process found
```

- Mostrarà una alerta de **PING** . Prémer **Ctrl+C** una vegada, i continua la instal·lació.

Instal·lació de Barnyard2

- Ara toca instal·lar **BARNYARD2** si vols.
- Es demana inserir una contrassenya per la base de dades de **SNORT** que es va a crear. En l'exemple utilitzo **SNORTSQL** .

```
[!] IMPORTANT: Would you like to install BARNYARD2? [Y/n] Y
```

```
[!] WARNING: Insert new SNORT Database Password: SNORTSQL
```

- Ara el programa instal·larà algunes dependències.
- Instal·larà `MySQL` , si no està instal·lat prèviament, hauràs d'introduir una contrassenya de `root` . En l'exemple, poso `ROOTSQL` .

```
[i] INFO: Installing dependencies.  
[!] WARNING: You will be asked for a password for MySQL service if it isn't installed in the system.  
[!] WARNING: Press ENTER to continue. █
```

- I la contrassenya del servei MySQL .

Configuring mysql-server-5.5

Repeat password for the MySQL "root" user:

<Ok>

- Ara el programa pregunta la contrassenya de **MySQL** **3 vegades**
- Tenir en compte: contrassenya **root** de **MySQL** **3 vegades**.

```
[+] INFO: BARNYARD2 installed successfully.
```

```
[i] INFO: The SNORT database is going to be created. You will be asked for MySQL password 3 times
```

```
[!] WARNING: Press ENTER to continue.
```

```
Enter password:
```

```
Enter password:
```

```
Enter password: █
```

Instal·lació de PulledPork

- Ara toca instal·lar PulledPork si vols.

```
[!] IMPORTANT: Would you like to install PULLEDPORK? [Y/n] Y
```

```
[i] INFO: Downloading PULLEDPORK.
```

```
Cloning into 'pulledpork'...
```

```
remote: Counting objects: 1207, done.
```

```
remote: Total 1207 (delta 0), reused 0 (delta 0), pack-reused 1207
```

```
Receiving objects: 100% (1207/1207), 249.49 KiB | 0 bytes/s, done.
```

```
Resolving deltas: 100% (814/814), done.
```

```
Checking connectivity... done.
```

```
[i] INFO: Adding PULLEDPORK to crontab. [Everyday at 4:15 AM].
```

```
PulledPork v0.7.3 - Making signature updates great again!
```

```
[+] INFO: PULLEDPORK is successfully installed and configured!
```

Regles d'Emerging Threats

- Vols afegir les regles d'Emerging Threats junt a las regles **community** (s'instal·len per defecte)?

```
[!] IMPORTANT: Would you like to enable Emerging Threats rules? [Y/n] Y
[+] INFO: Emerging Threats rules enabled!
[i] INFO: Editing pulledpork.conf settings...

[!] IMPORTANT: Now edit your /etc/snort/snort.conf and enable the rules you need by uncomment the lines
[!] EXAMPLE: If you want to enable the Exploit rules, remove the #:
    #include $RULE_PATH/exploit.rules --> include $RULE_PATH/exploit.rules
```

- Recordar editar l'arxiu `/etc/snort/snort.conf` i borra el `#` per habilitar las regles que necessites.

Crear un `servei`

- Crear un `servei` del sistema:

```
[!] IMPORTANT: Would you like to create a service snort? [Y/n] Y  
[i] INFO: Now you can run sudo service snort {start|stop|status}.
```


Descarregar i instal·lar noves regles

- Pots descarregar i instal·lar noves regles quan tot estiga instal·lat i configurat.

```
[!] IMPORTANT: Would you like to download new rules using PULLEDPORK? [Y/n] Y
https://github.com/shirkdog/pulledpork
  -----
  \-----,\      )
  \--==\\  /      PulledPork v0.7.3 - Making signature updates great again!
  \--==\\ /
  .-~~~~-.Y|\\_ Copyright (C) 2009-2016 JJ Cummings
@_/_      / 66\_ cummingsj@gmail.com
  |      \  \ _(")
  \      /-| ||'--' Rules give me wings!
  \_ \  \_ \ \
~~~~~
```

Reiniciar

- Reiniciar el sistema.

```
[!] IMPORTANT: Would you like to REBOOT now? [Y/n] Y
```

```
[i] INFO: Rebooting...
```

A disfrutar!

Per favor, s'agraeix que s'obriga **issues** si es troba cap error al programa.