

## Lecture 08


# Model Evaluation 1: Introduction to Overfitting and Underfitting

STAT 479: Machine Learning, Fall 2018

Sebastian Raschka

<http://stat.wisc.edu/~sraschka/teaching/stat479-fs2018/>

# Overview



# Overfitting and Underfitting

# Overfitting and Underfitting

## "Generalization Performance"

- Want a model to "generalize" well to unseen data  
("high generalization accuracy" or "low generalization error")

# Overfitting and Underfitting

## Assumptions


- i.i.d. assumption: inputs are independent, and training and test examples are identically distributed (drawn from the same probability distribution)
- For some random model that has not been fitted to the training set, we expect both the training and test error to be equal
- The training error or accuracy provides an (optimistically) biased estimate of the generalization performance

# Overfitting and Underfitting

## Model Capacity

- Underfitting: both training and test error are large
- Overfitting: gap between training and test error (where test error is higher)
- Large hypothesis space being searched by a learning algorithm  
-> high tendency to overfit

# Overfitting and Underfitting



# "[...] model has high bias/variance" -- What does that mean?

Google Scholar

"model has high variance"

Articles

About 49 results (0.25 sec)

## Any time

Since 2018  
Since 2017  
Since 2014  
Custom range...

## Sort by relevance

Sort by date

☒ include patents  
☒ include citations

☐ Create alert

## Signalling and the pricing of new issues

M Grinblatt, CY Hwang - The Journal of Finance, 1989 - Wiley Online Library

By continuing to browse this site you agree to us using cookies as described in About Cookies. Remove maintenance message ...

☆ [Cited by 1565](#) [Related articles](#) [All 6 versions](#) [⌕](#)

## Consensus inference in neuroimaging

LK Hansen, FA Nielsen, SC Strother, N Lange - NeuroImage, 2001 - Elsevier

... images. For instance, if we know that the summary image of a specific **model has high variance**, we might reduce the overall variance of the consensus image by giving that model lower weight. 3. MATERIALS AND METHODS ...

☆ [Cited by 29](#) [Related articles](#) [All 7 versions](#)

## Training efficient tree-based models for document ranking

N Asadi, J Lin - European Conference on Information Retrieval, 2013 - Springer

...  $G(N, \langle f, \theta \rangle_N) = \sum_{x_i \in N} (y_i - \hat{y}_N)^2 - C(N, \langle f, \theta \rangle_N)$ , (2) where  $x_i \in N$  denotes the set of instances that are present in node  $N$ . The final LambdaMART model has low bias but is prone to overfitting training data (ie, the **model has high variance**) ...

☆ [Cited by 23](#) [Related articles](#) [All 9 versions](#)

## The operational value of social media information

R Cui, S Gallino, A Moreno... - Production and ..., 2017 - Wiley Online Library

Skip to Main Content ...

☆ [Cited by 29](#) [Related articles](#) [All 4 versions](#)

## Temporal convolutional networks: A unified approach to action segmentation

C Lea, R Vidal, A Reiter, GD Hager - European Conference on Computer ..., 2016 - Springer

... this setup. We found performance of our **model has high variance** between different trials on GTEA— even with the same hyper parameters — thus, the difference in accuracy is not likely to be statistically significant. Our approach ...

☆ [Cited by 26](#) [Related articles](#) [All 7 versions](#)

## [PDF] Model-based motion planning

B Burns, O Brock - Computer Science Department Faculty ..., 2004 - scholarworks.umass.edu

... random. Cohn et al. [10] note that hill-climbing may also be used to find  $\hat{x}$ , but we have not found this to be necessary. The result is a sampling strategy that only queries sample points at which the **model has high variance**. A ...

☆ [Cited by 9](#) [Related articles](#) [All 10 versions](#)

## Efficient sequential Monte Carlo sampling for continuous monitoring of a radiation situation

V Šmídl, R Hofman - Technometrics, 2014 - amstat.tandfonline.com

... therein. A specific property of the studied model is a computationally expensive evaluation of the likelihood function. Moreover, the likelihood is sharply peaked and the parameter evolution **model has high variance**. These properties ...

Google Scholar

"model has high bias"

Articles

About 36 results (0.22 sec)

## Any time

Since 2018  
Since 2017  
Since 2014  
Custom range...

## Sort by relevance

Sort by date

☒ include patents  
☒ include citations

☐ Create alert

## Ensemble methods in data mining: improving accuracy through combining predictions

G Seni, JF Elder - Synthesis Lectures on Data Mining and ..., 2010 - morganclaypool.com

Page 1. Ensemble Methods in Data Mining: Improving Accuracy Through Combining Predictions Page 2. Page 3. Synthesis Lectures on Data Mining and Knowledge Discovery Editor Robert Grossman, University of Illinois, Chicago ...

☆ [Cited by 316](#) [Related articles](#) [All 8 versions](#) [⌕](#)

## [PDF] Exponential Family Hybrid Semi-Supervised Learning.

A Agarwal, H Daumé III - IJCAI, 2009 - aaai.org

... labeled examples. Since the generative **model has high bias**, a generative "bias-correction" model is trained in a discriminative manner to discriminatively combine the bias-correction model with the generative model. Most ...

☆ [Cited by 12](#) [Related articles](#) [All 17 versions](#) [⌕](#)

## [PDF] Prediction of Yelp Review Star Rating using Sentiment Analysis

C Li, J Zhang - 2014 - cs229.stanford.edu

... Final Report Figure 4: Ablative Analysis for 5-star Classification. As we can see, removing features may lead to higher mean square error, which supported our hypothesis that the resulted **model has high bias** and needs more features. 5.2 Recommendation Model ...

☆ [Cited by 3](#) [Related articles](#) [All 2 versions](#) [⌕](#)

## Detailed study on fusion characteristics of rigid poly (vinyl chloride) nanocomposites: The comparison of using multiple regression analysis and artificial neural ...

M Moghri, H Shamaee, R Tavana... - Journal of Vinyl and ..., 2015 - Wiley Online Library

... A complex ANN model having a large number of hidden neurons or trained with excessively large number of epochs has low bias but high variance. On the other hand, a simple ANN **model has high bias** but low variance. In ...

☆ [Cited by 3](#) [Related articles](#) [All 2 versions](#)

## Measuring supply chain risk: Predicting motor carriers' ability to withstand disruptive environmental change using conjoint analysis

C Atwater, R Gopalan, R Lancioni, J Hunt - Transportation Research Part C ..., 2014 - Elsevier

Skip to main content ...

☆ [Cited by 10](#) [Related articles](#) [All 4 versions](#)

## [PDF] Support Vector Machines

P Hoffman - 2010 - patriciahoffmanphd.com

Page 1. Support Vector Machines Patricia Hoffman, PhD. June 3, 2010 Contents I Support Vector Machine Concepts 3 1 Review of Generalized Learning Algorithms 3 2 Intuition for Support Vector Machines 5 3 Support Vector Machines: Mathematical Derivation 7 ...

☆ [Cited by 3](#) [Related articles](#) [All 3 versions](#) [⌕](#)

## [PDF] Modeling Of Surface Roughness Using Mra And Ann Method

M Radovanović, M Madić - 2011 - imtuoradea.ro

... epochs). A complex ANN model having large number of hidden neurons or trained



# "[...] model has high bias/variance" -- What does that mean?

Google Scholar

"model has high variance"

Articles

About 49 results (0.25 sec)

Any time  
Since 2018  
Since 2017  
Since 2014  
Custom range...

Sort by relevance  
Sort by date

☒ include patents  
☒ include citations

☐ Create alert

## Signalling and the pricing of new issues

M Grinblatt, CY Hwang - The Journal of Finance, 1989 - Wiley Online Library

By continuing to browse this site you agree to us using cookies as described in About Cookies. Remove maintenance message ...

☆ Cited by 1565 Related articles All 6 versions

## Consensus inference in neuroimaging

LK Hansen, FA Nielsen, SC Strother, N Lange - NeuroImage, 2001 - Elsevier

... images. For instance, if we know that the summary image of a specific **model has high variance**, we might reduce the overall variance of the consensus image by giving that model lower weight. 3. MATERIALS AND METHODS

☆ Cited by 29 Related articles

## Training efficient tree-based models

N Asadi, J Lin - European Conference on Artificial Intelligence, 2016 - Springer

...  $G(N, \langle f, \theta \rangle_N) = \sum_{x_i \in N} (y_i - \hat{y}_N)^2 - C(f, \theta)$  instances that are present in node  $N$ . The model is prone to overfitting training data (ie, the model is overfitted to the training data).

☆ Cited by 23 Related articles

## The operational value of social media

R Cui, S Gallino, A Moreno... - Production and Operations Management, 2016 - Wiley Online Library

Skip to Main Content ...

☆ Cited by 29 Related articles

## Temporal convolutional networks: A unified approach to action segmentation

C Lea, R Vidal, A Reiter, GD Hager - European Conference on Computer Vision, 2016 - Springer

... this setup. We found performance of our **model has high variance** between different trials on GTEA— even with the same hyper parameters — thus, the difference in accuracy is not likely to be statistically significant. Our approach ...

☆ Cited by 26 Related articles All 7 versions

## [PDF] Model-based motion planning

B Burns, O Brock - Computer Science Department Faculty ..., 2004 - scholarworks.umass.edu

... random. Cohn et al. [10] note that hill-climbing may also be used to find  $x$ , but we have not found this to be necessary. The result is a sampling strategy that only queries sample points at which the **model has high variance**. A ...

☆ Cited by 9 Related articles All 10 versions

## Efficient sequential Monte Carlo sampling for continuous monitoring of a radiation situation

V Šmídl, R Hofman - Technometrics, 2014 - amstat.tandfonline.com

... therein. A specific property of the studied model is a computationally expensive evaluation of the likelihood function. Moreover, the likelihood is sharply peaked and the parameter evolution **model has high variance**. These properties ...

Google Scholar

"model has high bias"

Articles

About 36 results (0.22 sec)

Any time

Since 2018  
Since 2017  
Since 2014  
Custom range...

Sort by relevance  
Sort by date

## Ensemble methods in data mining: improving accuracy through combining predictions

G Seni, JF Elder - Synthesis Lectures on Data Mining and ..., 2010 - morganclaypool.com

Page 1. Ensemble Methods in Data Mining: Improving Accuracy Through Combining Predictions Page 2. Page 3. Synthesis Lectures on Data Mining and Knowledge Discovery Editor Robert Grossman, University of Illinois, Chicago ...

☆ Cited by 316 Related articles All 8 versions

## [PDF] Exponential Family Hybrid Semi-Supervised Learning.

A Agarwal, H Daumé III - IJCAI, 2009 - aaai.org

generative **model has high bias**, a generative model trained in a discriminative manner to discriminatively combine the generative model. Most ...

☆ Cited by 17 versions

## Review Star Rating using Sentiment Analysis

ford.edu

Analysis for 5-star Classification. As we can see, removing features from the model reduces the error, which supported our hypothesis that the resulted **model** is more accurate. 5.2 Recommendation Model ...

☆ Cited by 2 versions

## Characteristics of rigid poly (vinyl chloride)

Comparison of using multiple regression analysis and

M Moghri, H Shamaee, R Tavana... - Journal of Vinyl and ..., 2015 - Wiley Online Library

... A complex ANN model having a large number of hidden neurons or trained with excessively large number of epochs has low bias but high variance. On the other hand, a simple ANN **model has high bias** but low variance. In ...

☆ Cited by 3 Related articles All 2 versions

## Measuring supply chain risk: Predicting motor carriers' ability to withstand disruptive environmental change using conjoint analysis

C Atwater, R Gopalan, R Lancioni, J Hunt - Transportation Research Part C ..., 2014 - Elsevier

Skip to main content ...

☆ Cited by 10 Related articles All 4 versions

## [PDF] Support Vector Machines

P Hoffman - 2010 - patriciahoffmanphd.com

Page 1. Support Vector Machines Patricia Hoffman, PhD. June 3, 2010 Contents I Support Vector Machine Concepts 3 1 Review of Generalized Learning Algorithms 3 2 Intuition for Support Vector Machines 5 3 Support Vector Machines: Mathematical Derivation 7 ...

☆ Cited by 3 Related articles All 3 versions

## [PDF] Modeling Of Surface Roughness Using Mra And Ann Method

M Radovanović, M Madić - 2011 - imtuoradea.ro


... epochs). A complex ANN model having large number of hidden neurons or trained

# **Bias-Variance Decomposition and Trade-off**


# Bias-Variance Decomposition

- Decomposition of the loss into bias and variance help us understand learning algorithms, concepts are correlated to underfitting and overfitting
- Helps explain why ensemble methods (last lecture) might perform better than single models


# Bias-Variance Intuition




# Bias and Variance Intuition




# Bias and Variance Intuition



# Bias and Variance Intuition




# Bias and Variance Intuition






# Bias and Variance Intuition




(There are two points where the bias is zero)

# Bias and Variance Intuition



(here, I fit an unpruned decision tree)


# Bias and Variance Example




where  $f(x)$  is some true (target) function

suppose we have multiple training sets

# Bias and Variance Example



# Bias and Variance Example



What happens if we take the average?  
Does this remind you of something?

# Terminology

Point estimator  $\hat{\theta}$  of some parameter  $\theta$

(could also be a function, e.g., the hypothesis is an estimator of some target function)

# Terminology

Point estimator  $\hat{\theta}$  of some parameter  $\theta$

(could also be a function, e.g., the hypothesis is an estimator of some target function)

$$\mathbf{Bias} = E[\hat{\theta}] - \theta$$

# Bias-Variance Decomposition

General Definition:

$$\mathbf{Bias}(\hat{\theta}) = E[\hat{\theta}] - \theta$$

$$\mathbf{Var}(\hat{\theta}) = E[\hat{\theta}^2] - \left(E[\hat{\theta}]\right)^2$$

$$\mathbf{Var}(\hat{\theta}) = E[(E[\hat{\theta}] - \hat{\theta})^2]$$



# Bias-Variance Decomposition


General Definition:

$$\mathbf{Bias}(\hat{\theta}) = E[\hat{\theta}] - \theta$$

$$\mathbf{Var}(\hat{\theta}) = E[\hat{\theta}^2] - \left(E[\hat{\theta}]\right)^2$$

$$\mathbf{Var}(\hat{\theta}) = E[(E[\hat{\theta}] - \hat{\theta})^2]$$

Intuition:



# Bias-Variance Decomposition of Squared Error

General Definition:

$$\mathbf{Bias}(\hat{\theta}) = E[\hat{\theta}] - \theta$$

$$\mathbf{Var}(\hat{\theta}) = E[\hat{\theta}^2] - \left(E[\hat{\theta}]\right)^2$$

$$\mathbf{Var}(\hat{\theta}) = E[(E[\hat{\theta}] - \hat{\theta})^2]$$

Intuition:

Bias is the difference between the average estimator from different training samples and the true value. (The expectation is over the training sets.)

The variance provides an estimate of how much the estimate varies as we vary the training data (e.g., by resampling).

# Bias-Variance Decomposition

$$\text{Loss} = \text{Bias} + \text{Variance} + \text{Noise}$$

# Bias-Variance Decomposition of Squared Error

General Definition:

"ML notation" for the Squared Error Loss:

$$\mathbf{Bias}(\hat{\theta}) = E[\hat{\theta}] - \theta$$

$$\mathbf{Var}(\hat{\theta}) = E[\hat{\theta}^2] - \left(E[\hat{\theta}]\right)^2$$


$$\mathbf{Var}(\hat{\theta}) = E[(E[\hat{\theta}] - \hat{\theta})^2]$$

$$y = f(x) \quad (\text{target, target function})$$

$$\hat{y} = \hat{f}(x) = h(x)$$

$$S = (y - \hat{y})^2$$

(For the sake of simplicity, we ignore the noise term in this lecture)



(Next slides: the expectation is over the training data, i.e, the average estimator from different training samples)

# Bias-Variance Decomposition of Squared Error

"ML notation" for the Squared Error Loss:

$$y = f(x) \quad (\text{target, target function})$$

$$\hat{y} = \hat{f}(x) = h(x)$$

$$S = (y - \hat{y})^2$$

(x is a particular data point e.g., in the test set;  
the expectation is over training sets)

---

$$S = (y - \hat{y})^2$$

$$(y - \hat{y})^2 = (y - E[\hat{y}] + E[\hat{y}] - \hat{y})^2$$

$$= (y - E[\hat{y}])^2 + (E[\hat{y}] - \hat{y})^2 + 2(y - E[\hat{y}])(E[\hat{y}] - \hat{y})$$

# Bias-Variance Decomposition of Squared Error

$$S = (y - \hat{y})^2$$

$$\begin{aligned}(y - \hat{y})^2 &= (y - E[\hat{y}] + E[\hat{y}] - \hat{y})^2 \\ &= (y - E[\hat{y}])^2 + (E[\hat{y}] - \hat{y})^2 + 2(y - E[\hat{y}])(E[\hat{y}] - \hat{y})\end{aligned}$$

$$E[S] = E[(y - \hat{y})^2]$$

$$\begin{aligned}E[(y - \hat{y})^2] &= (y - E[\hat{y}])^2 + E[(E[\hat{y}] - \hat{y})^2] \\ &= \textbf{[Bias of the fit]}^2 + \textbf{Variance of the fit}\end{aligned}$$

(The expectation is over the training data, i.e, the average estimator from different training samples)

# Bias-Variance Decomposition of Squared Error

$$S = (y - \hat{y})^2$$

$$(y - \hat{y})^2 = (y - E[\hat{y}] + E[\hat{y}] - \hat{y})^2$$

$$= (y - E[\hat{y}])^2 + (E[\hat{y}] - \hat{y})^2 + 2(y - E[\hat{y}])(E[\hat{y}] - \hat{y})$$

???

$$E[S] = E[(y - \hat{y})^2]$$

$$E[(y - \hat{y})^2] = (y - E[\hat{y}])^2 + E[(E[\hat{y}] - \hat{y})^2]$$

$$= \mathbf{[Bias]^2 + Variance}$$

# Bias-Variance Decomposition of Squared Error

$$S = (y - \hat{y})^2$$


$$(y - \hat{y})^2 = (y - E[\hat{y}] + E[\hat{y}] - \hat{y})^2$$

$$= (y - E[\hat{y}])^2 + (E[\hat{y}] - y)^2 + 2(y - E[\hat{y}]) (E[\hat{y}] - \hat{y})$$

???

$$\begin{aligned} E[2(y - E[\hat{y}]) (E[\hat{y}] - \hat{y})] &= 2E[(y - E[\hat{y}]) (E[\hat{y}] - \hat{y})] \\ &= 2(y - E[\hat{y}]) E[(E[\hat{y}] - \hat{y})] \\ &= 2(y - E[\hat{y}]) (E[E[\hat{y}]] - E[\hat{y}]) \\ &= 2(y - E[\hat{y}]) (E[\hat{y}] - E[\hat{y}]) \\ &= 0 \end{aligned}$$





Domingos, P. (2000). A unified bias-variance decomposition.  
In *Proceedings of 17th International Conference on Machine Learning*  
(pp. 231-238).

"several authors have proposed bias-variance decompositions related to zero-one loss (Kong & Dietterich, 1995; Breiman, 1996b; Kohavi & Wolpert, 1996; Tibshirani, 1996; Friedman, 1997). However, each of these decompositions has significant shortcomings."

# Bias-Variance Decomposition of 0-1 Loss

Dietterich, T. G., & Kong, E. B. (1995). *Machine learning bias, statistical bias, and statistical variance of decision tree algorithms*. Technical report, Department of Computer Science, Oregon State University.

Domingos, P. (2000). A unified bias-variance decomposition. In *Proceedings of 17th International Conference on Machine Learning* (pp. 231-238).

## Squared Loss

$$(y - \hat{y})^2$$

$$E[(y - \hat{y})^2]$$

## Generalized Loss

$$L(y, \hat{y})$$

$$E[L(y, \hat{y})]$$

# Bias-Variance Decomposition of 0-1 Loss

Dietterich, T. G., & Kong, E. B. (1995). *Machine learning bias, statistical bias, and statistical variance of decision tree algorithms*. Technical report, Department of Computer Science, Oregon State University.

Domingos, P. (2000). A unified bias-variance decomposition. In *Proceedings of 17th International Conference on Machine Learning* (pp. 231-238).

## Squared Loss

$$(y - \hat{y})^2$$

$$E[(y - \hat{y})^2]$$

$$E[(y - \hat{y})^2] = \underbrace{(y - E[\hat{y}])^2}_{\text{Bias}^2} + \underbrace{E[(E[\hat{y}] - \hat{y})^2]}_{\text{Variance}}$$

## Generalized Loss

$$L(y, \hat{y})$$

$$E[L(y, \hat{y})]$$

# Bias-Variance Decomposition of 0-1 Loss

Dietterich, T. G., & Kong, E. B. (1995). *Machine learning bias, statistical bias, and statistical variance of decision tree algorithms*. Technical report, Department of Computer Science, Oregon State University.

Domingos, P. (2000). A unified bias-variance decomposition. In *Proceedings of 17th International Conference on Machine Learning* (pp. 231-238).

## Squared Loss

$$(y - \hat{y})^2$$

$$E[(y - \hat{y})^2]$$

$$E[(y - \hat{y})^2] = \underbrace{(y - E[\hat{y}])^2}_{\text{Bias}^2} + \underbrace{E[(E[\hat{y}] - \hat{y})^2]}_{\text{Variance}}$$

$$\text{Bias}^2: (y - E[\hat{y}])^2$$

$$\text{Variance: } E[(E[\hat{y}] - \hat{y})^2]$$

## Generalized Loss

$$L(y, \hat{y})$$

$$E[L(y, \hat{y})]$$

$$L(y, E[\hat{y}])$$

$$E[L(\hat{y}, E[\hat{y}])]$$

# Define "Main Prediction"

Dietterich, T. G., & Kong, E. B. (1995). *Machine learning bias, statistical bias, and statistical variance of decision tree algorithms*. Technical report, Department of Computer Science, Oregon State University.

Domingos, P. (2000). A unified bias-variance decomposition. In *Proceedings of 17th International Conference on Machine Learning* (pp. 231-238).

The main prediction is the prediction that minimizes the average loss

$$\bar{\hat{y}} = \operatorname{argmin}_{\hat{y}'} E[L(\hat{y}, \hat{y}')]$$

For squared loss -> Mean

For 0-1 loss -> Mode

# Bias-Variance Decomposition of 0-1 Loss

Dietterich, T. G., & Kong, E. B. (1995). *Machine learning bias, statistical bias, and statistical variance of decision tree algorithms*. Technical report, Department of Computer Science, Oregon State University.

Domingos, P. (2000). A unified bias-variance decomposition. In *Proceedings of 17th International Conference on Machine Learning* (pp. 231-238).

## Squared Loss

$$(y - \hat{y})^2$$

$$E[(y - \hat{y})^2]$$

$$E[(y - \hat{y})^2] = \underbrace{(y - E[\hat{y}])^2}_{\text{Bias}^2} + \underbrace{E[(E[\hat{y}] - \hat{y})^2]}_{\text{Variance}}$$

Main prediction -> Mean

$$\text{Bias}^2: (y - \boxed{E[\hat{y}]})^2$$

$$\text{Variance: } E[(E[\hat{y}] - \hat{y})^2]$$

## 0-1 Loss

$$L(y, \hat{y})$$

$$E[L(y, \hat{y})]$$

Main prediction -> Mode

$$L(y, \boxed{E[\hat{y}]})$$

$$E[L(\hat{y}, E[\hat{y}])]$$

# Bias-Variance Decomposition of 0-1 Loss

Dietterich, T. G., & Kong, E. B. (1995). *Machine learning bias, statistical bias, and statistical variance of decision tree algorithms*. Technical report, Department of Computer Science, Oregon State University.

Domingos, P. (2000). A unified bias-variance decomposition. In *Proceedings of 17th International Conference on Machine Learning* (pp. 231-238).

## Squared Loss

$$E[(y - \hat{y})^2]$$

Main prediction -> Mean

Bias<sup>2</sup>:  $(y - \boxed{E[\hat{y}]})^2$

Variance:  $E[(E[\hat{y}] - \hat{y})^2]$

## 0-1 Loss

$$E[L(y, \hat{y})]$$

$$P(y \neq \hat{y})$$

Main prediction -> Mode

$$L(y, \boxed{E[\hat{y}]})$$

$$Bias = \begin{cases} 1 & \text{if } y \neq \bar{y} \\ 0 & \text{otherwise} \end{cases}$$

$$E[L(\hat{y}, E[\hat{y}])]$$

$$Variance = P(\hat{y} \neq \bar{\hat{y}})$$



# Bias-Variance Decomposition of 0-1 Loss

Dietterich, T. G., & Kong, E. B. (1995). *Machine learning bias, statistical bias, and statistical variance of decision tree algorithms*. Technical report, Department of Computer Science, Oregon State University.

Domingos, P. (2000). A unified bias-variance decomposition. In *Proceedings of 17th International Conference on Machine Learning* (pp. 231-238).

0-1 Loss

$$\text{Loss} = \text{Bias} + \text{Variance} = P(\hat{y} \neq y)$$

$$\text{Bias} = \begin{cases} 1 & \text{if } y \neq \bar{y} \\ 0 & \text{otherwise} \end{cases}$$

$$\text{Loss} = \text{Variance} = P(\hat{y} \neq y)$$

$$\text{Variance} = P(\hat{y} \neq \hat{\bar{y}})$$

# Bias-Variance Decomposition of 0-1 Loss

Dietterich, T. G., & Kong, E. B. (1995). *Machine learning bias, statistical bias, and statistical variance of decision tree algorithms*. Technical report, Department of Computer Science, Oregon State University.

Domingos, P. (2000). A unified bias-variance decomposition. In *Proceedings of 17th International Conference on Machine Learning* (pp. 231-238).

**0-1 Loss**       $\text{Loss} = \text{Bias} + \text{Variance} = P(\hat{y} \neq y)$

$$\text{Bias} = \begin{cases} 1 & \text{if } y \neq \bar{y} \\ 0 & \text{otherwise} \end{cases}$$

$$\text{Loss} = \text{Variance} = P(\hat{y} \neq y)$$

$$\text{Variance} = P(\hat{y} \neq \hat{\bar{y}})$$

# Bias-Variance Decomposition of 0-1 Loss

Dietterich, T. G., & Kong, E. B. (1995). *Machine learning bias, statistical bias, and statistical variance of decision tree algorithms*. Technical report, Department of Computer Science, Oregon State University.

Domingos, P. (2000). A unified bias-variance decomposition. In *Proceedings of 17th International Conference on Machine Learning* (pp. 231-238).

0-1 Loss

$$\text{Loss} = P(\hat{y} \neq y)$$

$$\text{Bias} = \begin{cases} 1 & \text{if } y \neq \bar{y} \\ 0 & \text{otherwise} \end{cases}$$

$$\text{Loss} = P(\hat{y} \neq y) = 1 - P(\hat{y} = y)$$

# Bias-Variance Decomposition of 0-1 Loss

Dietterich, T. G., & Kong, E. B. (1995). *Machine learning bias, statistical bias, and statistical variance of decision tree algorithms*. Technical report, Department of Computer Science, Oregon State University.

Domingos, P. (2000). A unified bias-variance decomposition. In *Proceedings of 17th International Conference on Machine Learning* (pp. 231-238).

0-1 Loss

$$\text{Loss} = P(\hat{y} \neq y)$$

$$\text{Bias} = \begin{cases} 1 & \text{if } y \neq \bar{y} \\ 0 & \text{otherwise} \end{cases}$$

$$\text{Loss} = P(\hat{y} \neq y) = 1 - P(\hat{y} = y) = 1 - P(\hat{y} \neq \bar{y})$$

# Bias-Variance Decomposition of 0-1 Loss


Dietterich, T. G., & Kong, E. B. (1995). *Machine learning bias, statistical bias, and statistical variance of decision tree algorithms*. Technical report, Department of Computer Science, Oregon State University.

Domingos, P. (2000). A unified bias-variance decomposition. In *Proceedings of 17th International Conference on Machine Learning* (pp. 231-238).

0-1 Loss

$$\text{Loss} = P(\hat{y} \neq y)$$

$$\text{Bias} = \begin{cases} 1 & \text{if } y \neq \bar{y} \\ 0 & \text{otherwise} \end{cases}$$

$$\text{Loss} = P(\hat{y} \neq y) = 1 - P(\hat{y} = y) = 1 - P(\hat{y} \neq \bar{y})$$


# Bias-Variance Decomposition of 0-1 Loss


Dietterich, T. G., & Kong, E. B. (1995). *Machine learning bias, statistical bias, and statistical variance of decision tree algorithms*. Technical report, Department of Computer Science, Oregon State University.

Domingos, P. (2000). A unified bias-variance decomposition. In *Proceedings of 17th International Conference on Machine Learning* (pp. 231-238).

0-1 Loss

$$\text{Loss} = P(\hat{y} \neq y)$$

$$\text{Bias} = \begin{cases} 1 & \text{if } y \neq \bar{y} \\ 0 & \text{otherwise} \end{cases}$$

$$\text{Loss} = P(\hat{y} \neq y) = 1 - P(\hat{y} = y) = 1 - P(\hat{y} \neq \bar{y})$$


$$\text{Loss} = \text{Bias} - \text{Variance}$$

# Bias-Variance Decomposition of 0-1 Loss

Dietterich, T. G., & Kong, E. B. (1995). *Machine learning bias, statistical bias, and statistical variance of decision tree algorithms*. Technical report, Department of Computer Science, Oregon State University.

Domingos, P. (2000). A unified bias-variance decomposition. In *Proceedings of 17th International Conference on Machine Learning* (pp. 231-238).

## 0-1 Loss

$$\text{Loss} = P(\hat{y} \neq y)$$

$$\text{Bias} = \begin{cases} 1 & \text{if } y \neq \bar{y} \\ 0 & \text{otherwise} \end{cases}$$

Variance can improve loss!!  
Why is that so?

$$\text{Loss} = P(\hat{y} \neq y) = 1 - P(\hat{y} = y) = 1 - P(\hat{y} \neq \bar{y})$$

$$\text{Loss} = \text{Bias} - \text{Variance}$$

# Bias-Variance Simulation of C 4.5

Dietterich, T. G., & Kong, E. B. (1995). *Machine learning bias, statistical bias, and statistical variance of decision tree algorithms*. Technical report, Department of Computer Science, Oregon State University.

- simulation on 200 training sets with 200 examples each (0-1 labels)
  - 200 hypotheses
- test set: 22,801 examples (1 data point for each grid point)
- mean error rate is 536 errors (out of the 22,801 test examples)
  - 297 as a result of bias
  - 239 as a result of variance




Figure 1: A two-class problem with 200 training examples.




Figure 2: Bias errors of C4.5 on the problem from Figure 1.

(remember that trees use a "staircase" to approximate diagonal boundaries)




# Recommended Reading Resources for Bias-Decomposition

Dietterich, T. G., & Kong, E. B. (1995). *Machine learning bias, statistical bias, and statistical variance of decision tree algorithms*. Technical report, Department of Computer Science, Oregon State University.


0-1 loss

Domingos, P. (2000). A unified bias-variance decomposition. In *Proceedings of 17th International Conference on Machine Learning* (pp. 231-238).

includes noise  
and more general:  $\text{Loss} = \text{Bias} + c \text{ Variance}$




- Training set error is an optimistically biased estimator of the generalization error
- Test set error is an unbiased estimator of the generalization error (test sample and hypothesis chosen independently)
- (in practice, it is actually pessimistically biased; why?)



Often using the holdout method is not a good idea ...


# Often using the holdout method is not a good idea ...

- Pessimistically biased (not so bad)
- Does not account for variance in the training data (very bad)




# Holdout evaluation


1




2



3




4






# Holdout validation (hyperparam. tuning)




# Holdout validation (hyperparam. tuning)

1




2




# Holdout validation (hyperparam. tuning)

3




4




## Holdout validation (hyperparam. tuning)

5



6



# Cross-Validation is generally better

... but ...

Bengio, Y., & Grandvalet, Y. (2004). No unbiased estimator of the variance of k-fold cross-validation. *Journal of machine learning research*, 5(Sep), 1089-1105.

# Bias of Estimators Example

Normal Distribution:  $\mathcal{N}(\mu, \sigma^2)$

Probability density function:  $f(x^{[i]}; \mu, \sigma^2) = \frac{1}{\sqrt{2\pi\sigma^2}} \exp\left(-\frac{1}{2} \frac{(x^{[i]} - \mu)^2}{\sigma^2}\right)$

Is the sample mean an unbiased estimator of the mean of the Gaussian?

$$\hat{\mu} = \frac{1}{n} \sum_i x^{[i]}$$

# Bias of Estimators Example

Is the sample mean an unbiased estimator of the mean of the Gaussian?

$$\hat{\mu} = \frac{1}{n} \sum_i x^{[i]}$$

$$\begin{aligned} \text{Bias}(\hat{\mu}) &= E[\hat{\mu}] - \mu \\ &= E\left[\frac{1}{n} \sum_i x^{[i]}\right] - \mu \\ &= \frac{1}{n} \sum_i E[x^{[i]}] - \mu \\ &= \frac{1}{n} \sum_i \mu - \mu \\ &= \mu - \mu = 0 \end{aligned}$$

# Bias of Estimators Example

Is the sample variance an unbiased estimator of the mean of the Gaussian

$$\hat{\sigma}^2 = \frac{1}{n} \sum_i (x^{[i]} - \hat{\mu})^2$$

$$\begin{aligned} \text{Bias}(\hat{\sigma}^2) &= E[\hat{\sigma}^2] - \sigma^2 \\ &= E\left[\frac{1}{n} \sum_i (x^{[i]} - \hat{\mu})^2\right] - \sigma^2 \\ &= \dots \\ &= \frac{m-1}{m} \sigma^2 - \sigma^2 \end{aligned}$$



# Bias of Estimators Example

Is the sample variance an unbiased estimator of the mean of the Gaussian?

$$\hat{\sigma}^2 = \frac{1}{n} \sum_i (x^{[i]} - \hat{\mu})^2$$

$$\begin{aligned} \text{Bias}(\hat{\sigma}^2) &= E[\hat{\sigma}^2] - \sigma^2 \\ &= E\left[\frac{1}{n} \sum_i (x^{[i]} - \hat{\mu})^2\right] - \sigma^2 \\ &= \dots \\ &= \frac{n-1}{n} \sigma^2 - \sigma^2 \end{aligned}$$

The unbiased estimator is actually

$$\hat{\sigma}'^2 = \frac{1}{n-1} \sum_i (x^{[i]} - \hat{\mu})^2$$

