

Package ‘MetaboAnalystR’

April 20, 2018

Title An R Package for Comprehensive Analysis of Metabolomics Data

Version 1.0.0

BugReports <https://github.com/xia-lab/MetaboAnalystR/issues>

Description This package contains the R functions and libraries underlying the popular MetaboAnalyst web server, including 500 functions for data processing, normalization, statistical analysis, metabolite set enrichment analysis, metabolic pathway analysis, and biomarker analysis. The package is synchronized with the web server. After installing and loading the package, users will be able to reproduce the same results from their local computers using the corresponding R command history downloaded from MetaboAnalyst, to achieve maximum flexibility and reproducibility.

Depends R (>= 3.4.4), lattice, methods, pls

License GPL-3

Encoding UTF-8

LazyData true

RoxygenNote 6.0.1

Imports Rserve, ellipse, scatterplot3d, Cairo, randomForest, caTools, e1071, som, impute, pcaMethods, RJSONIO, ROCR, globaltest, GlobalAncova, Rgraphviz, preprocessCore, genefilter, pheatmap, SSPA, sva, Rcpp, pROC, data.table, limma, car, fitdistrplus, lars, Hmisc, magrittr, xtable, caret, igraph, gplots, KEGGgraph, reshape, RColorBrewer, tibble, RSQLite, spls, siggenes

Suggests knitr, rmarkdown, xcms, devtools

VignetteBuilder knitr

NeedsCompilation no

Author Jianguo Xia [aut],
Jasmine Chong [aut, cre]

Maintainer Jasmine Chong <jasmine.chong@mail.mcgill.ca>

R topics documented:

AddErrMsg	12
analyze.lipids	12
ANOVA.Anal	13
ANOVA2.Anal	13
aof	14
aov.between	14
aov.repeated	15
aov.within	15
ASCAfun.res	16
ASCAfun1	16
ASCAfun2	17
calculateConcISO	17
CalculateFeatureRanking	18
CalculateGlobalTestScore	18
CalculateHyperScore	19
CalculateImpVarCutoff	19
CalculateOraScore	20
CalculatePairwiseDiff	20
CalculateQeaScore	21
CalculateSSP	21
CheckMetaDataConsistency	22
CleanData	22
CleanDataMatrix	23
CleanNumber	23
ClearNegatives	24
ClearStrings	24
ClearUserDir	25
ComputeAverageCurve	25
computeConc	26
ComputeHighLow	26
ComputeMummichogSigPvals	27
CreateAnalNullMsg	27
CreateANOVAdoc	28
CreateAOV2doc	28
CreateASCAdoc	29
CreateBiomarkerInputDoc	29
CreateBiomarkerIntr	30
CreateBiomarkerOverview	30
CreateBiomarkerRatioOverview	30
CreateBiomarkerRnwReport	31
CreateCorrDoc	31
createCVset	32
CreateEBAMdoc	32
CreateEnrichAnalDoc	33
CreateEnrichInputDoc	33
CreateEnrichIntr	34

CreateEnrichORAdoc	34
CreateEnrichOverview	35
CreateEnrichProcessDoc	35
CreateEnrichQEAdoc	36
CreateEnrichRnwReport	36
CreateEnrichSSPdoc	37
CreateFooter	37
CreateGraph	38
CreateHCdoc	38
CreateHeader	39
CreateHeatmap2doc	39
CreateIntegPathwayAnalysisRnwReport	40
CreateIntegratedPathwayAnalInputDoc	40
CreateIntegratedPathwayAnalIntr	41
CreateIntegratedPathwayAnalOverview	41
CreateIntegratedPathwayDoc	42
CreateIntegratedPathwayGeneMapTable	42
CreateIntegratedPathwayNameMapTable	43
CreateIntegratedPathwayResultsTable	43
CreateiPCAdoc	44
CreateKMdoc	44
CreateLadder	45
CreateMappingResultTable	45
CreateMBdoc	46
CreateMetaAnalysisDEdoc	46
CreateMetaAnalysisInputDoc	47
CreateMetaAnalysisIntr	47
CreateMetaAnalysisNORMdoc	48
CreateMetaAnalysisOutput	48
CreateMetaAnalysisOverview	49
CreateMetaAnalysisRnwReport	49
CreateMetaTable	50
CreateModelBiomarkersDoc	50
CreateMultiBiomarkersDoc	51
CreateMummichogAnalTable	51
CreateMummichogAnalysisDoc	52
CreateMummichogInputDoc	52
CreateMummichogIntro	53
CreateMummichogOverview	53
CreateMummichogRnwReport	53
CreateNetworkExplorerDoc	54
CreateNetworkExplorerInputDoc	54
CreateNetworkExplorerIntr	55
CreateNetworkExplorerOverview	55
CreateNetworkExplorerRnwReport	56
CreateNetworkGeneMapTable	56
CreateNetworkNameMapTable	57
CreateOPLSDAdoc	57

CreatePathAnalDoc	58
CreatePathInputDoc	58
CreatePathIntr	59
CreatePathProcessDoc	59
CreatePathResultDoc	60
CreatePathRnwReport	60
CreatePCAdoc	61
CreatePDFReport	61
CreatePLSdoc	62
CreatePowerAnalDoc	62
CreatePowerInputDoc	63
CreatePowerIntr	63
CreatePowerOverview	64
CreatePowerParametersDoc	64
CreatePowerRnwReport	65
CreateRatioTable	65
CreateRFdoc	66
CreateRHistAppendix	66
CreateROCLabelsTable	67
CreateSAMdoc	67
CreateSemiTransColors	68
CreateSOMdoc	68
CreateSPLSDAdoc	69
CreateStatFooter	69
CreateStatIOdoc	70
CreateStatNORMdoc	70
CreateStatRnwReport	71
CreateSummaryTable	71
CreateSVMdoc	72
CreateTimeSeriesAnalNullMsg	72
CreateTimeSeriesIOdoc	72
CreateTimeSeriesRnwReport	73
CreateUnivarBiomarkersDoc	73
CreateUNIVdoc	74
CreateUnivROCTable	74
CreateVennMetaTable	75
CrossReferencing	75
CVTest.LRmodel	76
descendMin	76
doCompoundMapping	77
doEmblProtein2EntrezMapping	77
doGeneIDMapping	78
doKEGG2NameMapping	78
doKOFiltering	79
EBAM.A0.Init	79
EBAM.Cmpd.Init	80
FC.Anal.paired	80
FC.Anal.unpaired	81

FeatureCorrelation	81
FilterVariable	82
findEqualGreaterM	82
FisherLSD	83
genLogisticRegMdl	83
Get.asca.tss	84
Get.bwss	84
Get.ConcRef	85
Get.Leverage	85
Get.pAUC	86
Get.pred	86
Get.rpart.summary	87
Get.tss	87
Get.VIP	88
GetAbundanceLabel	88
GetAccuracyInfo	89
GetAllDataNames	89
GetAllKMClusterMembers	89
GetAllSOMClusterMembers	90
GetCandidateList	90
GetCircleInfo	91
GetCIs	91
GetCMD	92
GetConvertFullPath	92
getDataFromTextArea	93
GetExtendRange	93
GetFC	94
GetFeatureNumbers	94
GetFinalNameMap	95
GetFisherPvalue	95
GetHTMLMetSet	96
GetHTMLPathSet	96
GetImpFeatureMat	97
GetKEGGNodeInfo	97
GetKMClusterMembers	98
GetLassoFreqs	98
GetLimmaResTable	99
GetMapTable	99
GetMaxPCAComp	99
GetMeanROC	100
GetMetaResultMatrix	100
GetMetaSigHitsTable	101
GetMetSetName	101
GetMsetLibCheckMsg	102
GetMsetLibSearchResult	102
GetMsetNames	103
GetNetworkGeneMappingResultTable	103
GetNewSampleNames	104

GetORA.pathNames	104
GetORA.smpdbIDs	105
GetORATable	105
GetQEA.pathNames	105
GetQEATable	106
GetRCommandHistory	106
GetRFConf.Table	106
GetRFConfMat	107
GetRFOOB	107
GetRFSigMat	108
GetROC.coords	108
GetROCLassoFreq	109
GetROCTestP	109
GetSampleSizeLadder	110
GetSelectedDataNames	110
GetSelectedDataNumber	110
GetSigTable	111
GetSigTable.Anova	111
GetSigTable.Aov2	112
GetSigTable.ASCA	112
GetSigTable.Corr	113
GetSigTable.EBAM	113
GetSigTable.FC	113
GetSigTable.MB	114
GetSigTable.RF	114
GetSigTable.SAM	114
GetSigTable.SVM	115
GetSigTable.TT	115
GetSigTable.Volcano	115
GetSOMClusterMembers	116
GetSSPTable	116
GetSuggestedSAMDelta	117
GetSVMSigMat	117
GetTopInx	118
GetTrainTestSplitMat	118
GetTtestRes	119
GetTTSigMat	119
GetUnivReport	120
GetVariableLabel	120
GetVennGeneNames	121
GetXYCluster	121
GroupPeakList	122
heckbert	122
HMDBID2KEGGID	123
HMDBID2Name	123
ImputeVar	124
InitDataObjects	124
InitPowerAnal	125

InitStatAnalMode	125
InitTimeSeriesAnal	126
iPCA.Anal	126
isEmptyMatrix	127
IsSmallSmplSize	127
IsSpectraProcessingOK	128
KEGGID2HMDBID	128
KEGGID2Name	129
KEGGPATHID2SMPDBIDs	129
Kmeans.Anal	130
kwtest	130
LoadKEGGKO_lib	131
LoadKEGGLib	131
LoadMsetLib	132
LoadSmpLib	132
LogNorm	133
LSD.test	133
make_cpdlist	134
map	134
MapCmpd2KEGGNodes	135
MapKO2KEGGEges	135
Match.Pattern	136
MergeDatasets	136
MergeDuplicates	137
MetaboliteMappingExact	137
MSspec.fillPeaks	138
MSspec.rtCorrection	138
multi.stat	139
Normalization	139
OPLSR.Anal	140
parseFisher	140
parseTukey	141
PathMapping	141
PCA.Anal	142
PCA.Flip	142
PCA.GENES	143
Perform.ASCA	143
Perform.ASCA.permute	144
Perform.Permut	144
Perform.permutation	145
Perform.UnivROC	145
PerformApproxMatch	146
PerformBatchCorrection	146
PerformCV.explore	147
PerformCV.test	148
PerformDetailMatch	148
PerformEachDEAnal	149
PerformGeneAnnotation	149

PerformIndNormalization	150
PerformIntegCmpdMapping	150
PerformIntegGeneMapping	151
PerformIntegPathwayAnalysis	151
PerformKOEnrichAnalysis_KO01100	152
PerformKOEnrichAnalysis_List	152
PerformLimmaDE	153
PerformMapping	153
performMB	154
PerformMetaMerge	154
PerformMultiMatch	155
PerformMummichog	155
PerformMummichogPermutations	156
PerformPowerProfiling	156
PerformPvalCombination	157
PerformVoteCounting	157
Plot.Permutation	158
PlotAccuracy	158
PlotANOVA	159
PlotANOVA2	160
PlotASCA.Permutation	160
PlotAscaImpVar	161
PlotASCAModel	162
PlotCmpdSummary	162
PlotCmpdView	163
PlotConcRange	164
PlotCorr	164
PlotCorrHeatMap	165
PlotDetailROC	166
PlotEBAM.A0	167
PlotEBAM.Cmpd	167
PlotEnrichNet.Overview	168
PlotFC	169
PlotHCTree	169
PlotHeatMap	170
PlotHeatMap2	171
PlotImpVar	172
PlotImpVars	172
PlotInmexGraph	173
PlotInmexPath	174
PlotInteraction	174
PlotKEGGPath	175
PlotKmeans	175
PlotLoadingCmpd	176
PlotMBTimeProfile	177
PlotMetaVenn	177
PlotMetPath	178
PlotModelScree	178

PlotMS.RT	179
PlotMSEA.Overview	179
PlotNormSummary	180
PlotOPLS.MDL	180
PlotOPLS.Permutation	181
PlotOPLS.Splot	182
PlotOPLS2DScore	182
PlotORA	183
PlotPathSummary	184
PlotPCA.overview	184
PlotPCA2DScore	185
PlotPCA3DScore	186
PlotPCA3DScore_orig	186
PlotPCABiplot	187
PlotPCALoading	188
PlotPCAPairSummary	189
PlotPCAScree	189
PlotPLS.Classification	190
PlotPLS.Imp	191
PlotPLS.Permutation	191
PlotPLS2DScore	192
PlotPLS3DScore	193
PlotPLS3DScore_orig	194
PlotPLSLoading	195
PlotPLSPairSummary	196
PlotPowerEffectSize	196
PlotPowerProfile	197
PlotPowerStat	198
PlotProbView	198
PlotProbViewTest	199
plotProfile	200
PlotQEA.MetSet	200
PlotQEA.Overview	201
PlotRF.Classify	201
PlotRF.Outlier	202
PlotRF.VIP	203
PlotROC.LRmodel	203
PlotROCMulti	204
PlotROCTest	205
PlotRSVM.Classification	206
PlotRSVM.Cmpd	206
PlotSAM.Cmpd	207
PlotSAM.FDR	208
PlotSampleNormSummary	208
PlotSelectedFeature	209
PlotSigVar	210
PlotSOM	210
PlotSPLS2DScore	211

PlotSPLS3DScore	212
PlotSPLSDA.Classification	212
PlotSPLSLoading	213
PlotSPLSPairSummary	214
PlotSubHeatMap	214
PlotTestAccuracy	215
PlotTT	216
PlotVolcano	217
PLSDA.CV	217
PLSDA.Permut	218
PLSR.Anal	218
Predict.class	219
PrepareIntegData	219
PrepareNetworkData	220
PreparePermResult	220
PrepareQueryJson	221
PrepareROCDData	221
PrepareROCDetails	222
PrepareVennData	222
RankFeatures	223
Read.BatchCSVdata	223
Read.MSSpec	224
Read.PeakList	224
Read.PeakListData	225
Read.TextData	225
ReadIndData	226
ReadPairFile	226
RecordRCommand	227
rectUnique	227
RegisterData	228
RemoveCmpd	228
RemoveData	229
RemoveDuplicates	229
RemoveFile	230
RemoveFolder	230
RemoveGene	231
RemoveMissingPercent	231
ReplaceMin	232
RerenderKEGGGraph	232
RerenderMetPAGraph	233
ResetCustomCmpds	233
RF.Anal	234
ROCPredSamplesTable	234
RSVM	235
RSVM.Anal	235
SAM.Anal	236
SanityCheckData	236
SanityCheckIndData	237

SanityCheckMummichogData	237
saveNetworkInSIF	238
SaveTransformedData	238
SearchByCompound	239
SearchByName	239
SearchCompoundLib	240
SearchMsetLibraries	240
SearchNetDB	241
SelectMultiData	241
SetAnalysisMode	242
SetBarParams	242
SetCachexiaSetUsed	243
SetCandidate	243
SetCurrentGroups	244
SetCurrentMsetLib	244
SetCustomData	245
SetDesignType	245
SetEBAMSigMat	246
SetKEGG.PathLib	246
SetMass.PathLib	247
SetMetabolomeFilter	247
SetOrganism	248
SetPeakList.GroupValues	248
SetSAMSigMat	248
Setup.BiofluidType	249
Setup.ConcData	249
Setup.HMDBReferenceMetabolome	250
Setup.KEGGReferenceMetabolome	250
Setup.MapData	251
Setup.UserMsetLibData	251
SetupMSdataMatrix	252
SetupSMPDBLinks	252
SOM.Anal	253
sparse.mint.block_iteration	253
splsda	254
SPLSR.Anal	255
SumNorm	256
template.match	256
Ttests.Anal	257
UnzipUploadedFile	257
UpdateFeatureItems	258
UpdateGroupItems	258
UpdateIntegPathwayAnalysis	259
UpdateMummichogParameters	259
UpdateSampleItems	260
usr2png	261
Volcano.Anal	261
XSet2MSet	262

Index**263**

AddErrMsg	<i>Adds an error message</i>
-----------	------------------------------

Description

The error message will be printed in all cases. Used in higher functions.

Usage

```
AddErrMsg(msg)
```

Arguments

msg	Error message to print
-----	------------------------

analyze.lipids	<i>Lipid analysis pipeliner</i>
----------------	---------------------------------

Description

Lipid analysis pipeliner

Usage

```
analyze.lipids(inFile, iso = "y")
```

Arguments

inFile	Input the file to read in
iso	Default is set to "y"

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

ANOVA.Anal	<i>Perform ANOVA analysis</i>
------------	-------------------------------

Description

ANOVA analysis

Usage

```
ANOVA.Anal(mSetObj=NA, nonpar=F, thresh=0.05, post.hoc="fisher")
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
nonpar	Logical, use a non-parametric test (T) or not (F)
thresh	Numeric, from 0 to 1, indicate the p-value threshold
post.hoc	Input the name of the post-hoc test, "fisher" or "tukey"

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

ANOVA2.Anal	<i>Perform Two-way ANOVA</i>
-------------	------------------------------

Description

Perform Two-way ANOVA

Usage

```
ANOVA2.Anal(mSetObj=NA, thresh=0.05, p.cor="fdr", type="time0", aov.type=1, use.interact=1)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
thresh	Input the p-value threshold
p.cor	Select method for p-value correction, bonferroni, holm or fdr
type	Select b to perform between-subjects ANOVA, and w for within-subjects ANOVA
aov.type	Specify 1 for ANOVA type 1, or 3 for ANOVA type 3
use.interact	Numeric, whether to consider interaction in two-way repeated ANOVA (1) or not (0).

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

aof	<i>ANOVA</i>
-----	--------------

Description

Perform anova and only return p values and MSres (for Fisher's LSD)

Usage

```
aof(x, cls)
```

Arguments

x	Input the data to perform ANOVA
cls	Input class labels

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

aov.between	<i>Perform Two-way ANOVA</i>
-------------	------------------------------

Description

Perform Two-way ANOVA Perform between-subjects anova

Usage

```
aov.between(x)
```

Arguments

x	Input data to perform 2-way ANOVA
---	-----------------------------------

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

aov.repeated	<i>Perform Two-way ANOVA</i>
--------------	------------------------------

Description

Perform Two-way ANOVA Perform repeated measure one-way anova

Usage

```
aov.repeated(x, time.fac)
```

Arguments

x	Input the data
time.fac	Input the time factor

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

aov.within	<i>Perform Two-way ANOVA</i>
------------	------------------------------

Description

Perform Two-way ANOVA Perform within-subjects anova

Usage

```
aov.within(x, time.fac)
```

Arguments

x	Input the data
time.fac	Input the time factor

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

`ASCAfun.res`*Function to perform ASCA*

Description

Perform ASCA

Usage`ASCAfun.res(X, Fac)`**Arguments**`X` Input list of compounds`Fac` Numeric McGill University, Canada License: GNU GPL (≥ 2)**Author(s)**

Jeff Xia <jeff.xia@mcgill.ca>

`ASCAfun1`*Function to perform ASCA*

Description

Perform ASCA

Usage`ASCAfun1(X, Design, Fac)`**Arguments**`X` Numeric, number of compounds`Design` Number of levels in the factor`Fac` Numeric, the factor**Author(s)**Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (≥ 2)

ASCAfun2	<i>Function to perform ASCA</i>
----------	---------------------------------

Description

Perform ASCA

Usage

```
ASCAfun2(X, Desa, Desb, Fac)
```

Arguments

X	Numeric, number of compounds
Desa	Number of levels in the factor TIME
Desb	Number of levels in the other factor
Fac	Numeric, the factor

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

calculateConcISO	<i>Calculate Concentration ISO</i>
------------------	------------------------------------

Description

Assuming independent random distribution of FA, the most probable frequency will be the product of the each component. Note: the data is concentration, we need to get frequencies - percentage w.r.t the total nmol. the result is the saved as separate files for each lipid class data for each FA class, first col is sample name

Usage

```
calculateConcISO(dat, cls.name, cls.num, min.file, prob.file)
```

Arguments

dat	Input the data
cls.name	Input the class names
cls.num	Input the number of classes
min.file	Input the min file
prob.file	Input the prob file

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

`CalculateFeatureRanking`*Calculates feature importance*

Description

Perform calculation of feature importance (AUC, p value, fold change)

Usage

```
CalculateFeatureRanking(mSetObj=NA, clust.num=5)
```

Arguments

<code>mSetObj</code>	Input the name of the created mSetObj (see InitDataObjects)
<code>clust.num</code>	Numeric, input the number of clusters for cluster-analysis

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

`CalculateGlobalTestScore`*Quantitative enrichment analysis with globaltest*

Description

Various enrichment analysis algorithms

Usage

```
CalculateGlobalTestScore(mSetObj = NA)
```

Arguments

<code>mSetObj</code>	Input the name of the created mSetObj (see InitDataObjects)
----------------------	---

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

CalculateHyperScore *Over-representation analysis using hypergeometric tests*

Description

Over-representation analysis using hypergeometric tests The probability is calculated from obtaining equal or higher number of hits using 1-phyper. Since phyper is a cumulative probability, to get $P(X \geq \text{hit.num}) \Rightarrow P(X > (\text{hit.num} - 1))$

Usage

```
CalculateHyperScore(mSetObj = NA)
```

Arguments

mSetObj Input the name of the created mSetObj (see InitDataObjects)

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

CalculateImpVarCutoff *Perform OPLS-DA*

Description

Orthogonal PLS-DA (from ropls)

Usage

```
CalculateImpVarCutoff(mSetObj, spe.thresh, lev.thresh)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
spe.thresh	alpha threshold, less is better, default less than 5 percentile based chi-square note: spe and leverage are vectors, not a single value, but a list to store the result note: the last model is Model.res, no spe Calculate leverage cutoff based on permutation Calculate the reference distribution of leverages note: leverage.perm is a list with each member in a 3 column matrix
lev.thresh	leverage threshold, the higher better, default more than 95 percentile of permuted leverage

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

CalculateOraScore	<i>Calculate ORA score</i>
-------------------	----------------------------

Description

Calculate the over representation analysis score

Usage

```
CalculateOraScore(mSetObj=NA, nodeImp, method)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
nodeImp	Indicate the pathway topology analysis, "rbc" for relative-betweenness centrality, and "dgr" for out-degree centrality.
method	is "fisher" or "hyperg"

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

CalculatePairwiseDiff	<i>Calculate Pairwise Differences</i>
-----------------------	---------------------------------------

Description

Mat are log normalized, diff will be ratio. Used in higher functions.

Usage

```
CalculatePairwiseDiff(mat)
```

Arguments

mat	Input matrix of data to calculate pair-wise differences.
-----	--

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

CalculateQeaScore	<i>Calculate quantitative enrichment score</i>
-------------------	--

Description

Calculate quantitative enrichment score

Usage

```
CalculateQeaScore(mSetObj=NA, nodeImp, method)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
nodeImp	Indicate the pathway topology analysis, "rbc" for relative-betweenness centrality, and "dgr" for out-degree centrality.
method	Indicate the pathway enrichment analysis, global test is "gt" and global ancova is "ga".

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

CalculateSSP	<i>Single sample profiling to compare with</i>
--------------	--

Description

reference concentrations stored in the library

Usage

```
CalculateSSP(mSetObj = NA)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
---------	---

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

CheckMetaDataConsistency

Check if data are ready for meta-analysis

Description

This function determines if all annotated data are ready for meta-analysis

Usage

```
CheckMetaDataConsistency(mSetObj = NA, combat = TRUE)
```

Arguments

mSetObj	Input name of the created mSet Object
combat	Adjust for batch effects, logical variable: TRUE = adjust for batch effects using an empirical Bayes framework (R package sva), FALSE = no batch effect adjustment.

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

CleanData

Perform data cleaning

Description

Cleans data and removes -Inf, Inf, NA, negative and 0s.

Usage

```
CleanData(bdata, removeNA = T, removeNeg = T, removeConst = T)
```

Arguments

bdata	Input data to clean
removeNA	Logical, T to remove NAs, F to not.
removeNeg	Logical, T to remove negative numbers, F to not.
removeConst	Logical, T to remove samples/features with 0s, F to not.

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

CleanDataMatrix	<i>Clean the data matrix</i>
-----------------	------------------------------

Description

Function used in higher functinos to clean data matrix

Usage

```
CleanDataMatrix(ndata)
```

Arguments

ndata	Input the data to be cleaned
-------	------------------------------

CleanNumber	<i>Replace infinite numbers</i>
-------------	---------------------------------

Description

Replace -Inf, Inf to 99999 and -99999

Usage

```
CleanNumber(bdata)
```

Arguments

bdata	Input matrix to clean numbers
-------	-------------------------------

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

ClearNegatives

Data processing: Dealing with negative values

Description

Operates on dataSet\$procr after dealing with missing values

Usage

```
ClearNegatives(mSetObj = NA, method = "abs")
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
method	Input the method to clear negatives

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

ClearStrings*Remove spaces*

Description

Remove from, within, leading and trailing spaces

Usage

```
ClearStrings(query)
```

Arguments

query	Input the query to clear
-------	--------------------------

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

ClearUserDir	<i>Clear folder and memory</i>
--------------	--------------------------------

Description

Clear the current folder and objects in memory

Usage

```
ClearUserDir(mSetObj = NA)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
---------	---

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

ComputeAverageCurve	<i>Compute average ROC curve</i>
---------------------	----------------------------------

Description

Compute the average ROC curve

Usage

```
ComputeAverageCurve(perf, avg.method)
```

Arguments

perf	Input the average
avg.method	Input the name of the method to compute the average curve

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

computeConc

Lipid analysis

Description

The upper limit for each combination is considered to be the minimal of the fatty acid concentration (nmol fatty acid/gram of sample) X is the lopomics data obtained above the result is the saved as separate files for each lipid class

Usage

```
computeConc(X, iso = "y")
```

Arguments

X	Input the data
iso	Default is set to "y"

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

ComputeHighLow

Compute the 95 percent interval for threshold ROC

Description

Computes the 95 percent interval only for the y-axis. Utility function, called upon by higher functions

Usage

```
ComputeHighLow(perf)
```

Arguments

perf	Input the performance
------	-----------------------

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

`ComputeMummichogSigPvals`*Calculate p-values for the list of significant compounds*

Description

This function performs pathway enrichment by calculate p-values for each pathway in the reference organism from the list of significant compounds.

Usage

```
ComputeMummichogSigPvals(mSetObj=NA, enrichOpt, pvalOpt)
```

Arguments

<code>mSetObj</code>	Input the name of the created mSetObj (see InitDataObjects)
<code>enrichOpt</code>	Input method for enrichment analysis
<code>pvalOpt</code>	Calculate fisher or hypergeometric p-values

Author(s)

Jasmine Chong, Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL
(>= 2)

`CreateAnalNullMsg`*Create null message for analysis Creates a message for the Sweave report*

Description

Creates a message stating that no analyses were performed on your data.

Usage

```
CreateAnalNullMsg()
```

`CreateANOVAdoc`*Create report of analyses*

Description

Report generation using Sweave Create ANOVA document

Usage

```
CreateANOVAdoc(mSetObj = NA)
```

Arguments

`mSetObj` Input the name of the created `mSetObj` (see `InitDataObjects`)

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (≥ 2)

`CreateAOV2doc`*Create report of analyses*

Description

Report generation using Sweave ANOVA

Usage

```
CreateAOV2doc(mSetObj = NA)
```

Arguments

`mSetObj` Input the name of the created `mSetObj` (see `InitDataObjects`)

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (≥ 2)

CreateASCAdoc*Create report of analyses*

Description

Report generation using Sweave Random Forest ASCA

Usage

```
CreateASCAdoc(mSetObj = NA)
```

Arguments

mSetObj Input the name of the created mSetObj (see InitDataObjects)

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

CreateBiomarkerInputDoc*Create biomarker analysis report: Data Input*

Description

Report generation using Sweave Power analysis report, data input documentation.

Usage

```
CreateBiomarkerInputDoc(mSetObj = NA)
```

Arguments

mSetObj Input the name of the created mSetObj (see InitDataObjects)

Author(s)

Jasmine Chong McGill University, Canada License: GNU GPL (>= 2)

CreateBiomarkerIntr *Create biomarker analysis report: Introduction*

Description

Report generation using Sweave Biomarker analysis report introduction

Usage

CreateBiomarkerIntr()

Author(s)

Jasmine Chong McGill University, Canada License: GNU GPL (≥ 2)

CreateBiomarkerOverview
 Create biomarker analysis report: Overview

Description

Report generation using Sweave Power analysis report overview

Usage

CreateBiomarkerOverview()

Author(s)

Jasmine Chong McGill University, Canada License: GNU GPL (≥ 2)

CreateBiomarkerRatioOverview
 Create biomarker analysis report: Normalization, ratio

Description

Report generation using Sweave Biomarker analysis, ratio option

Usage

CreateBiomarkerRatioOverview(mSetObj = NA)

Arguments

mSetObj Input the name of the created mSetObj (see InitDataObjects)

Author(s)

Jasmine Chong McGill University, Canada License: GNU GPL (≥ 2)

CreateBiomarkerRnwReport

Create report of analyses (Biomarker)

Description

Report generation using Sweave Puts together the analysis report

Usage

CreateBiomarkerRnwReport(mSetObj, usrName)

Arguments

mSetObj Input the name of the created mSetObj (see InitDataObjects)

usrName Input the name of the user

Author(s)

Jasmine Chong McGill University, Canada License: GNU GPL (≥ 2)

CreateCorrDoc

Create report of analyses

Description

Report generation using Sweave Create correlation document

Usage

CreateCorrDoc(mSetObj = NA)

Arguments

mSetObj Input the name of the created mSetObj (see InitDataObjects)

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (≥ 2)

createCVset	<i>Separate data set using k-fold cross validation (CV)</i>
-------------	---

Description

Separate data set with k-fold CV, used in higher function

Usage

```
createCVset(groupN, kfold, rseed)
```

Arguments

groupN	Input the size of the group
kfold	Input the number of cross-validations
rseed	Input the random seed

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

CreateEBAMdoc	<i>Create report of analyses</i>
---------------	----------------------------------

Description

Report generation using Sweave Create EBAM document Note: the search for delta (SAM) and a0 (EBAM) will not be plotted it is only exploration, and may cause potential inconsistencies.

Usage

```
CreateEBAMdoc(mSetObj = NA)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
---------	---

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

CreateEnrichAnalDoc	<i>Create report of analyses (Met Enrichment)</i>
---------------------	---

Description

Report generation using Sweave Metabolite enrichment analysis report, analysis

Usage

```
CreateEnrichAnalDoc()
```

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

CreateEnrichInputDoc	<i>Create report of analyses (Met Enrichment)</i>
----------------------	---

Description

Report generation using Sweave Metabolite enrichment analysis report data input

Usage

```
CreateEnrichInputDoc(mSetObj = NA)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
---------	---

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

CreateEnrichIntr	<i>Create report of analyses (Met Enrichment)</i>
------------------	---

Description

Report generation using Sweave Metabolite enrichment analysis report introduction

Usage

```
CreateEnrichIntr()
```

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

CreateEnrichORAdoc	<i>Create report of analyses (Met Enrichment)</i>
--------------------	---

Description

Report generation using Sweave Metabolite enrichment analysis report, over representation analysis (ORA)

Usage

```
CreateEnrichORAdoc(mSetObj = NA)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
---------	---

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

CreateEnrichOverview *Create report of analyses (Met Enrichment)*

Description

Report generation using Sweave Metabolite enrichment analysis report overview

Usage

CreateEnrichOverview()

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

CreateEnrichProcessDoc
Create report of analyses (Met Enrichment)

Description

Report generation using Sweave Metabolite enrichment analysis report enrichment process

Usage

CreateEnrichProcessDoc(mSetObj = NA)

Arguments

mSetObj Input the name of the created mSetObj (see InitDataObjects)

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

CreateEnrichQEAdoc	Create report of analyses (Met Enrichment)
--------------------	--

Description

Report generation using Sweave Metabolite enrichment analysis report Quantitative enrichment analysis

Usage

```
CreateEnrichQEAdoc(mSetObj = NA)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
---------	---

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (≥ 2)

CreateEnrichRnwReport	Create report of analyses (Met Enrichment)
-----------------------	--

Description

Report generation using Sweave Metabolite enrichment analysis report

Usage

```
CreateEnrichRnwReport(mSetObj, usrName)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
usrName	Input the name of the user

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (≥ 2)

CreateEnrichSSPdoc	<i>Create report of analyses (Met Enrichment)</i>
--------------------	---

Description

Report generation using Sweave Metabolite enrichment analysis report Single sampling profiling

Usage

```
CreateEnrichSSPdoc(mSetObj = NA)
```

Arguments

mSetObj Input the name of the created mSetObj (see InitDataObjects)

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

CreateFooter	<i>Create report of analyses (Met Enrichment)</i>
--------------	---

Description

Report generation using Sweave Metabolite enrichment analysis report footer

Usage

```
CreateFooter()
```

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

CreateGraph	<i>Create igraph from the edgelist saved from graph DB and decompose into subnets</i>
-------------	---

Description

Function for the network explorer module, prepares user's data for network exploration.

Usage

```
CreateGraph(mSetObj = NA)
```

Arguments

mSetObj	Input name of the created mSet Object
---------	---------------------------------------

CreateHCdoc	<i>Create report of analyses</i>
-------------	----------------------------------

Description

Report generation using Sweave Create hierarchical clustering document

Usage

```
CreateHCdoc(mSetObj = NA)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
---------	---

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

CreateHeader	<i>Create report of analyses</i>
--------------	----------------------------------

Description

Report generation using Sweave Create header

Usage

```
CreateHeader(usrName)
```

Arguments

usrName	Input the name of the user
---------	----------------------------

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

CreateHeatmap2doc	<i>Create report of analyses</i>
-------------------	----------------------------------

Description

Report generation using Sweave 2-way heatmap

Usage

```
CreateHeatmap2doc(mSetObj = NA)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
---------	---

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

`CreateIntegPathwayAnalysisRnwReport`*Create report of analyses (IntegPathwayAnalysis)*

Description

Report generation using Sweave Puts together the analysis report

Usage

```
CreateIntegPathwayAnalysisRnwReport(mSetObj, usrName)
```

Arguments

<code>mSetObj</code>	Input the name of the created mSetObj (see InitDataObjects)
<code>usrName</code>	Input the name of the user

Author(s)

Jasmine Chong McGill University, Canada License: GNU GPL (≥ 2)

`CreateIntegratedPathwayAnalInputDoc`*Create integrated pathway report: Data Input*

Description

Report generation using Sweave integrated pathway report, data input documentation.

Usage

```
CreateIntegratedPathwayAnalInputDoc(mSetObj = NA)
```

Arguments

<code>mSetObj</code>	Input the name of the created mSetObj (see InitDataObjects)
----------------------	---

Author(s)

Jasmine Chong McGill University, viewingCanada License: GNU GPL (≥ 2)

CreateIntegratedPathwayAnalIntr

Create integrated pathway analysis report: Introduction

Description

Report generation using Sweave Integrated pathwayr analysis report introduction

Usage

CreateIntegratedPathwayAnalIntr()

Author(s)

Jasmine Chong McGill University, Canada License: GNU GPL (≥ 2)

CreateIntegratedPathwayAnalOverview

Create integrated pathway report: Overview

Description

Report generation using Sweave integrated pathway analysis report overview

Usage

CreateIntegratedPathwayAnalOverview()

Author(s)

Jasmine Chong McGill University, Canada License: GNU GPL (≥ 2)

`CreateIntegratedPathwayDoc`*Create integrated pathway analysis report*

Description

Report generation using Sweave Biomarker analysis report, ROC Curve Based Model Creation and Evaluation

Usage

```
CreateIntegratedPathwayDoc(mSetObj = NA)
```

Arguments

`mSetObj` Input the name of the created mSetObj (see InitDataObjects)

Author(s)

Jasmine Chong McGill University, Canada License: GNU GPL (≥ 2)

`CreateIntegratedPathwayGeneMapTable`*Create a x-table for gene name mapping*

Description

Report generation using Sweave Function to create a table for gene name mapping

Usage

```
CreateIntegratedPathwayGeneMapTable(mSetObj = NA)
```

Arguments

`mSetObj` Input the name of the created mSetObj (see InitDataObjects)

Author(s)

Jasmine Chong McGill University, Canada License: GNU GPL (≥ 2)

`CreateIntegratedPathwayNameMapTable`*Create a x-table for compound name mapping*

Description

Report generation using Sweave Function to create a table for compound name mapping

Usage

```
CreateIntegratedPathwayNameMapTable(mSetObj = NA)
```

Arguments

mSetObj Input the name of the created mSetObj (see InitDataObjects)

Author(s)

Jasmine Chong McGill University, Canada License: GNU GPL (≥ 2)

`CreateIntegratedPathwayResultsTable`*Create a x-table for pathway results*

Description

Report generation using Sweave Function to create a table for pathway results

Usage

```
CreateIntegratedPathwayResultsTable(mSetObj = NA)
```

Arguments

mSetObj Input the name of the created mSetObj (see InitDataObjects)

Author(s)

Jasmine Chong McGill University, Canada License: GNU GPL (≥ 2)

CreateiPCAdoc	<i>Create report of analyses</i>
---------------	----------------------------------

Description

Report generation using Sweave For Interactive PCA

Usage

```
CreateiPCAdoc(mSetObj = NA)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
---------	---

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

CreateKMdoc	<i>Create report of analyses</i>
-------------	----------------------------------

Description

Report generation using Sweave Create Kmeans partitional clustering document

Usage

```
CreateKMdoc(mSetObj = NA)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
---------	---

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

`CreateLadder`*R-code for R-SVM*

Description

use leave-one-out / Nfold or bootstrape to permute data for external CV build SVM model and use mean-balanced weight to sort genes on training set and recursive elimination of least important genes

Usage

```
CreateLadder(Ntotal, Nmin = 5)
```

Arguments

<code>Ntotal</code>	Total number
<code>Nmin</code>	Minimum number, default set to 5

Author(s)

Dr. Xin Lu, Research Scientist Biostatistics Department, Harvard School of Public Health create a decreasing ladder for recursive feature elimination

`CreateMappingResultTable`*Creates the mapping result table*

Description

Creates the mapping result table

Usage

```
CreateMappingResultTable(mSetObj = NA)
```

Arguments

<code>mSetObj</code>	Input the name of the created mSetObj (see InitDataObjects)
----------------------	---

CreateMBdoc

Create report of analyses

Description

Report generation using Sweave Multivariate Bayes

Usage

```
CreateMBdoc(mSetObj = NA)
```

Arguments

mSetObj Input the name of the created mSetObj (see InitDataObjects)

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

CreateMetaAnalysisDEdoc*Create MetaAnalysis analysis report: Data Normalization*

Description

Report generation using Sweave Meta-Analysis, data normalization documentation.

Usage

```
CreateMetaAnalysisDEdoc(mSetObj = NA)
```

Arguments

mSetObj Input the name of the created mSetObj (see InitDataObjects)

Author(s)

Jasmine Chong McGill University, Canada License: GNU GPL (>= 2)

`CreateMetaAnalysisInputDoc`*Create MetaAnalysis analysis report: Data Input*

Description

Report generation using Sweave Power analysis report, data input documentation.

Usage

```
CreateMetaAnalysisInputDoc(mSetObj = NA)
```

Arguments

`mSetObj` Input the name of the created mSetObj (see InitDataObjects)

Author(s)

Jasmine Chong McGill University, Canada License: GNU GPL (≥ 2)

`CreateMetaAnalysisIntr`*Create MetaAnalysis analysis report: Introduction*

Description

Report generation using Sweave MetaAnalysis analysis report introduction

Usage

```
CreateMetaAnalysisIntr()
```

Author(s)

Jasmine Chong McGill University, Canada License: GNU GPL (≥ 2)

`CreateMetaAnalysisNORMdoc`*Create MetaAnalysis analysis report: Data Normalization*

Description

Report generation using Sweave Meta-Analysis, data normalization documentation.

Usage

```
CreateMetaAnalysisNORMdoc(mSetObj = NA)
```

Arguments

`mSetObj` Input the name of the created `mSetObj` (see `InitDataObjects`)

Author(s)

Jasmine Chong McGill University, Canada License: GNU GPL (≥ 2)

`CreateMetaAnalysisOutput`*Create MetaAnalysis analysis report: Data Normalization*

Description

Report generation using Sweave MetaAnalysis analysis, data normalization documentation.

Usage

```
CreateMetaAnalysisOutput(mSetObj = NA)
```

Arguments

`mSetObj` Input the name of the created `mSetObj` (see `InitDataObjects`)

Author(s)

Jasmine Chong McGill University, Canada License: GNU GPL (≥ 2)

`CreateMetaAnalysisOverview`*Create MetaAnalysis analysis report: Overview*

Description

Report generation using Sweave Power analysis report overview

Usage

```
CreateMetaAnalysisOverview()
```

Author(s)

Jasmine Chong McGill University, Canada License: GNU GPL (≥ 2)

`CreateMetaAnalysisRnwReport`*Create report of analyses (Meta-Analysis)*

Description

Report generation using Sweave Puts together the analysis report

Usage

```
CreateMetaAnalysisRnwReport(mSetObj, usrName)
```

Arguments

<code>mSetObj</code>	Input the name of the created mSetObj (see InitDataObjects)
<code>usrName</code>	Input the name of the user

Author(s)

Jasmine Chong McGill University, Canada License: GNU GPL (≥ 2)

CreateMetaTable	<i>Create MetaAnalysis table of results</i>
-----------------	---

Description

Report generation using Sweave Function to create a table containing meta-analysis results.

Usage

```
CreateMetaTable(mSetObj = NA)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
---------	---

Author(s)

Jasmine Chong McGill University, Canada License: GNU GPL (≥ 2)

CreateModelBiomarkersDoc	<i>Create biomarker analysis report: ROC Curve Based Model Creation and Evaluation</i>
--------------------------	--

Description

Report generation using Sweave Biomarker analysis report, ROC Curve Based Model Creation and Evaluation

Usage

```
CreateModelBiomarkersDoc(mSetObj = NA)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
---------	---

Author(s)

Jasmine Chong McGill University, Canada License: GNU GPL (≥ 2)

`CreateMultiBiomarkersDoc`*Create biomarker analysis report: Multivariate Biomarker Analysis*

Description

Report generation using Sweave Biomarker analysis report, Multivariate Biomarker Analysis

Usage

```
CreateMultiBiomarkersDoc(mSetObj = NA)
```

Arguments

`mSetObj` Input the name of the created mSetObj (see InitDataObjects)

Author(s)

Jasmine Chong McGill University, Canada License: GNU GPL (≥ 2)

`CreateMummichogAnalTable`*Create Mummichog report of analyses*

Description

Report generation using Sweave Function to create a summary table of mummichog analysis

Usage

```
CreateMummichogAnalTable(mSetObj = NA)
```

Arguments

`mSetObj` Input the name of the created mSetObj (see InitDataObjects)

Author(s)

Jasmine Chong McGill University, Canada License: GNU GPL (≥ 2)

`CreateMummichogAnalysisDoc`*Create mummichog analysis report*

Description

Report generation using Sweave Mummichog analysis report

Usage

```
CreateMummichogAnalysisDoc(mSetObj = NA)
```

Arguments

`mSetObj` Input the name of the created `mSetObj` (see `InitDataObjects`)

Author(s)

Jasmine Chong McGill University, Canada License: GNU GPL (≥ 2)

`CreateMummichogInputDoc`*Create Mummichog analysis report: Data Input*

Description

Report generation using Sweave Mummichog analysis report, data input documentation.

Usage

```
CreateMummichogInputDoc(mSetObj = NA)
```

Arguments

`mSetObj` Input the name of the created `mSetObj` (see `InitDataObjects`)

Author(s)

Jasmine Chong McGill University, Canada License: GNU GPL (≥ 2)

CreateMummichogIntro *Create mummichog analysis report: Introduction*

Description

Report generation using Sweave Mummichog analysis report introduction

Usage

CreateMummichogIntro()

Author(s)

Jasmine Chong McGill University, Canada License: GNU GPL (≥ 2)

CreateMummichogOverview
Create Mummichog analysis report: Overview

Description

Report generation using Sweave Mummichog analysis report overview

Usage

CreateMummichogOverview()

Author(s)

Jasmine Chong McGill University, Canada License: GNU GPL (≥ 2)

CreateMummichogRnwReport
Create report of analyses (Biomarker)

Description

Report generation using Sweave Puts together the analysis report

Usage

CreateMummichogRnwReport(mSetObj, usrName)

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
usrName	Input the name of the user

Author(s)

Jasmine Chong McGill University, Canada License: GNU GPL (≥ 2)

CreateNetworkExplorerDoc

Create integrated pathway analysis report

Description

Report generation using Sweave Biomarker analysis report, ROC Curve Based Model Creation and Evaluation

Usage

CreateNetworkExplorerDoc(mSetObj = NA)

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
---------	---

Author(s)

Jasmine Chong McGill University, Canada License: GNU GPL (≥ 2)

CreateNetworkExplorerInputDoc

Create network explorer: Data Input

Description

Report generation using Sweave network explorer report, data input documentation.

Usage

CreateNetworkExplorerInputDoc(mSetObj = NA)

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
---------	---

Author(s)

Jasmine Chong McGill University, viewingCanada License: GNU GPL (≥ 2)

`CreateNetworkExplorerIntr`*Create integrated pathway analysis report: Introduction*

Description

Report generation using Sweave Network explorer report introduction

Usage`CreateNetworkExplorerIntr()`**Author(s)**

Jasmine Chong McGill University, Canada License: GNU GPL (≥ 2)

`CreateNetworkExplorerOverview`*Create network explorer report: Overview*

Description

Report generation using Sweave for the network explorer report overview

Usage`CreateNetworkExplorerOverview()`**Author(s)**

Jasmine Chong McGill University, Canada License: GNU GPL (≥ 2)

`CreateNetworkExplorerRnwReport`*Create report of analyses (Network Explorer)*

Description

Report generation using Sweave Puts together the analysis report

Usage

```
CreateNetworkExplorerRnwReport(mSetObj, usrName)
```

Arguments

<code>mSetObj</code>	Input the name of the created mSetObj (see InitDataObjects)
<code>usrName</code>	Input the name of the user

Author(s)

Jasmine Chong McGill University, Canada License: GNU GPL (≥ 2)

`CreateNetworkGeneMapTable`*Create a x-table for gene name mapping*

Description

Report generation using Sweave Function to create a table for gene name mapping

Usage

```
CreateNetworkGeneMapTable(mSetObj = NA)
```

Arguments

<code>mSetObj</code>	Input the name of the created mSetObj (see InitDataObjects)
----------------------	---

Author(s)

Jasmine Chong McGill University, Canada License: GNU GPL (≥ 2)

`CreateNetworkNameMapTable`*Create a x-table for compound name mapping*

Description

Report generation using Sweave Function to create a table for compound name mapping

Usage

```
CreateNetworkNameMapTable(mSetObj = NA)
```

Arguments

mSetObj Input the name of the created mSetObj (see InitDataObjects)

Author(s)

Jasmine Chong McGill University, Canada License: GNU GPL (≥ 2)

`CreateOPLSDAdoc`*Create report of analyses*

Description

Report generation using Sweave Create OPLSDA document

Usage

```
CreateOPLSDAdoc(mSetObj = NA)
```

Arguments

mSetObj Input the name of the created mSetObj (see InitDataObjects)

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (≥ 2)

CreatePathAnalDoc	Create report of analyses (Met Pathway)
-------------------	---

Description

Report generation using Sweave Metabolomic pathway analysis Create pathway analysis doc

Usage

```
CreatePathAnalDoc(mSetObj = NA)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
---------	---

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

CreatePathInputDoc	Create report of analyses (Met Pathway)
--------------------	---

Description

Report generation using Sweave Metabolomic pathway analysis Create data input doc

Usage

```
CreatePathInputDoc()
```

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

CreatePathIntr	<i>Create report of analyses (Met Pathway)</i>
----------------	--

Description

Report generation using Sweave Metabolomic pathway analysis Introduction

Usage

```
CreatePathIntr()
```

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

CreatePathProcessDoc	<i>Create report of analyses (Met Pathway)</i>
----------------------	--

Description

Report generation using Sweave Metabolomic pathway analysis Create MetPA process

Usage

```
CreatePathProcessDoc(mSetObj = NA)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
---------	---

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

CreatePathResultDoc	<i>Create report of analyses (Met Pathway)</i>
---------------------	--

Description

Report generation using Sweave Metabolomic pathway analysis Create MetPA results doc

Usage

```
CreatePathResultDoc(mSetObj = NA)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
---------	---

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

CreatePathRnwReport	<i>Create report of analyses (Met Pathway)</i>
---------------------	--

Description

Report generation using Sweave Metabolomic pathway analysis write .Rnw file template

Usage

```
CreatePathRnwReport(mSetObj, usrName)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
usrName	Input the name of the user

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

CreatePCAdoc	<i>Create report of analyses</i>
--------------	----------------------------------

Description

Report generation using Sweave Create PCA document

Usage

```
CreatePCAdoc(mSetObj = NA)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
---------	---

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

CreatePDFReport	<i>Create report of analyses</i>
-----------------	----------------------------------

Description

Report generation using Sweave Note: most analyses were already performed, only need to embed the results to the right place without rerunning the whole analysis through Sweave. Only some auxilliary info (i.e. time, version etc need to run in R through Sweave

Usage

```
CreatePDFReport(mSetObj = NA, usrName)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
usrName	Input the name of the user

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

CreatePLSdoc	<i>Create report of analyses</i>
--------------	----------------------------------

Description

Report generation using Sweave Create PLS document

Usage

```
CreatePLSdoc(mSetObj = NA)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
---------	---

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

CreatePowerAnalDoc	<i>Create power analysis report: Power Analysis</i>
--------------------	---

Description

Report generation using Sweave Power analysis report, analysis

Usage

```
CreatePowerAnalDoc(mSetObj)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
---------	---

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

CreatePowerInputDoc	<i>Create power analysis report: Data Input</i>
---------------------	---

Description

Report generation using Sweave Power analysis report, data input documentation.

Usage

```
CreatePowerInputDoc(mSetObj = NA)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
---------	---

Author(s)

Jasmine Chong McGill University, Canada License: GNU GPL (≥ 2)

CreatePowerIntr	<i>Create power analysis report: Introduction</i>
-----------------	---

Description

Report generation using Sweave Power analysis report introduction

Usage

```
CreatePowerIntr()
```

Author(s)

Jasmine Chong McGill University, Canada License: GNU GPL (≥ 2)

CreatePowerOverview	<i>Create power analysis report: Overview</i>
---------------------	---

Description

Report generation using Sweave Power analysis report overview

Usage

```
CreatePowerOverview()
```

Author(s)

Jasmine Chong McGill University, Canada License: GNU GPL (≥ 2)

CreatePowerParametersDoc	<i>Create power analysis report: Power Parameter Selection</i>
--------------------------	--

Description

Report generation using Sweave Power analysis report, parameter selection

Usage

```
CreatePowerParametersDoc(mSetObj = NA)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
---------	---

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (≥ 2)

CreatePowerRnwReport	<i>Create report of analyses (Power)</i>
----------------------	--

Description

Report generation using Sweave Put together the analysis report

Usage

```
CreatePowerRnwReport(mSetObj, usrName)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
usrName	Input the name of the user

Author(s)

Jasmine Chong McGill University, Canada License: GNU GPL (≥ 2)

CreateRatioTable	<i>Create report of analyses</i>
------------------	----------------------------------

Description

Report generation using Sweave Function to create a summary table for biomarker analysis: included metabolite ratios

Usage

```
CreateRatioTable(mSetObj = NA)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
---------	---

Author(s)

Jasmine Chong McGill University, Canada License: GNU GPL (≥ 2)

CreateRFdoc	<i>Create report of analyses</i>
-------------	----------------------------------

Description

Report generation using Sweave Create Random Forest document

Usage

```
CreateRFdoc(mSetObj = NA)
```

Arguments

mSetObj Input the name of the created mSetObj (see InitDataObjects)

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

CreateRHistAppendix	<i>Create report of analyses</i>
---------------------	----------------------------------

Description

Report generation using Sweave Create footer

Usage

```
CreateRHistAppendix()
```

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

CreateROCLabelsTable	<i>Create a x-table for newly classified samples</i>
----------------------	--

Description

Report generation using Sweave Function to create a table for newly classified samples

Usage

```
CreateROCLabelsTable(mSetObj = NA)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
---------	---

Author(s)

Jasmine Chong McGill University, Canada License: GNU GPL (≥ 2)

CreateSAMdoc	<i>Create report of analyses</i>
--------------	----------------------------------

Description

Report generation using Sweave Create SAM document

Usage

```
CreateSAMdoc(mSetObj = NA)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
---------	---

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (≥ 2)

CreateSemiTransColors *Create semitransparant colors*

Description

Create semitransparant colors for a given class label

Usage

```
CreateSemiTransColors(cls)
```

Arguments

cls	Input class labels
-----	--------------------

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

CreateSOMdoc *Create report of analyses*

Description

Report generation using Sweave Create SOM partitional clustering document

Usage

```
CreateSOMdoc(mSetObj = NA)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
---------	---

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

CreateSPLSDAdoc	<i>Create report of analyses</i>
-----------------	----------------------------------

Description

Report generation using Sweave Create sPLS-DA document

Usage

```
CreateSPLSDAdoc(mSetObj = NA)
```

Arguments

mSetObj Input the name of the created mSetObj (see InitDataObjects)

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

CreateStatFooter	<i>Create report of analyses</i>
------------------	----------------------------------

Description

Report generation using Sweave Create footer

Usage

```
CreateStatFooter()
```

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

CreateStatI0doc	<i>Create report of analyses</i>
-----------------	----------------------------------

Description

Report generation using Sweave Read and process raw data

Usage

```
CreateStatI0doc(mSetObj = NA)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
---------	---

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

CreateStatNORMdoc	<i>Create report of analyses</i>
-------------------	----------------------------------

Description

Report generation using Sweave Create normalization document

Usage

```
CreateStatNORMdoc(mSetObj = NA)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
---------	---

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

CreateStatRnwReport	<i>Create report of analyses</i>
---------------------	----------------------------------

Description

Report generation using Sweave Write .Rnw file template

Usage

```
CreateStatRnwReport(mSetObj, usrName)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
usrName	Input the name of the user

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

CreateSummaryTable	<i>Create report of analyses</i>
--------------------	----------------------------------

Description

Report generation using Sweave Create a summary table for each type of uploaded data csv table has 5 col: sampleID, feature #, zero, missing #

Usage

```
CreateSummaryTable(mSetObj = NA)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
---------	---

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

CreateSVMdoc	<i>Create report of analyses</i>
--------------	----------------------------------

Description

Report generation using Sweave Create R-SVM document

Usage

```
CreateSVMdoc(mSetObj = NA)
```

Arguments

mSetObj Input the name of the created mSetObj (see InitDataObjects)

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

CreateTimeSeriesAnalNullMsg	<i>Create null analysis message for time-series sweave report</i>
-----------------------------	---

Description

Creates empty time-series analysis message

Usage

```
CreateTimeSeriesAnalNullMsg()
```

CreateTimeSeriesIOdoc	<i>Create report of analyses (Met Pathway)</i>
-----------------------	--

Description

Report generation using Sweave Metabolomic pathway analysis, time-series Read and process the raw data

Usage

```
CreateTimeSeriesIOdoc(mSetObj = NA)
```


Arguments

mSetObj Input the name of the created mSetObj (see InitDataObjects)

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (≥ 2)

CreateTimeSeriesRnwReport

Create report of analyses (Met Pathway)

Description

Report generation using Sweave Metabolomic pathway analysis Create timeseries .Rnw file template

Usage

CreateTimeSeriesRnwReport(mSetObj, usrName)

Arguments

mSetObj Input the name of the created mSetObj (see InitDataObjects)
usrName Input the name of the user

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (≥ 2)

CreateUnivarBiomarkersDoc

Create power analysis report: Biomarker Univariate Analysis

Description

Report generation using Sweave Biomarker analysis report, Univariate Analysis

Usage

CreateUnivarBiomarkersDoc(mSetObj = NA)

Arguments

mSetObj Input the name of the created mSetObj (see InitDataObjects)

Author(s)

Jasmine Chong McGill University, Canada License: GNU GPL (≥ 2)

CreateUNIVdoc	<i>Create report of analyses</i>
---------------	----------------------------------

Description

Report generation using Sweave Create univariate analyses document

Usage

```
CreateUNIVdoc(mSetObj = NA)
```

Arguments

mSetObj Input the name of the created mSetObj (see InitDataObjects)

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

CreateUnivROCTable	<i>Create summary table for univariate ROC analysis</i>
--------------------	---

Description

Report generation using Sweave Function to create a summary table for univariate biomarker analysis

Usage

```
CreateUnivROCTable()
```

Author(s)

Jasmine Chong McGill University, Canada License: GNU GPL (>= 2)

CreateVennMetaTable	<i>Create MetaAnalysis table of results for Venn Diagram</i>
---------------------	--

Description

Report generation using Sweave Function to create a table containing meta-analysis results.

Usage

```
CreateVennMetaTable(mSetObj = NA)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
---------	---

Author(s)

Jasmine Chong McGill University, Canada License: GNU GPL (>= 2)

CrossReferencing	<i>Various functions for mapping b/w names & database identifiers Given a list of compound names or ids, find matched name or ids from selected databases</i>
------------------	---

Description

Given a list of compound names or ids find matched name or ids from selected databases

Usage

```
CrossReferencing(mSetObj = NA, q.type, hmdb = T, pubchem = T, chebi = F,  
kegg = T, metlin = F)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
q.type	Input the query type
hmdb	Logical, T to cross reference to HMDB, F to not
pubchem	Logical, T to cross reference to PubChem, F to not
chebi	Logical, T to cross reference to CheBI, F to not
kegg	Logical, T to cross reference to KEGG, F to not
metlin	Logical, T to cross reference to MetLin, F to not

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

CVTest.LRmodel	<i>Calculate ROC performance with CV</i>
----------------	--

Description

Calculate ROC performance with CV

Usage

```
CVTest.LRmodel(data.in, fmla.in, kfold = 10, run.stepwise = FALSE)
```

Arguments

data.in	Input matrix of data
fmla.in	Input for generalized linear model
kfold	Numeric
run.stepwise	Logical

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

descendMin	<i>Perform utilities for peak grouping</i>
------------	--

Description

Perform various utilities for peak grouping

Usage

```
descendMin(y, istart = which.max(y))
```

Arguments

y	Input peaks
istart	Performs which.max on y

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

doCompoundMapping	<i>Perform compound mapping</i>
-------------------	---------------------------------

Description

Perform compound mapping

Usage

```
doCompoundMapping(cmpd.vec, q.type)
```

Arguments

cmpd.vec	Input compound vector
q.type	Query type

doEmblProtein2EntrezMapping	<i>Utility function for PerformNetEnrichment</i>
-----------------------------	--

Description

Utility function for PerformNetEnrichment

Usage

```
doEmblProtein2EntrezMapping(emblprotein.vec)
```

Arguments

emblprotein.vec	Input the vector containing protein embl ids
-----------------	--

doGeneIDMapping	<i>Perform various annotation</i>
-----------------	-----------------------------------

Description

Gene ID mapping, gene annotation, compound mapping, KEGG mapping

Usage

```
doGeneIDMapping(q.vec, org, type)
```

Arguments

q.vec	Input the query
org	Input the organism type
type	Input the type of data to annotate

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (≥ 2)

doKEGG2NameMapping	<i>Perform KEGG to compound name mapping</i>
--------------------	--

Description

Perform KEGG to compound name mapping

Usage

```
doKEGG2NameMapping(kegg.vec)
```

Arguments

kegg.vec	Input vector of KEGG compounds
----------	--------------------------------

doKOFiltering	<i>Utility function</i>
---------------	-------------------------

Description

Returns matched KO in the same order (NA if no match)

Usage

```
doKOFiltering(ko.vec, type)
```

Arguments

ko.vec	Input the vector containing KOs
type	Input the type

EBAM.A0.Init	<i>For EBAM analysis</i>
--------------	--------------------------

Description

deteriming a0, only applicable for z.ebam (default)

Usage

```
EBAM.A0.Init(mSetObj = NA, isPaired, isVarEq)
```

Arguments

mSetObj	Input name of the created mSet Object
isPaired	Logical
isVarEq	Logical

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

EBAM.Cmpd.Init	<i>For EBAM analysis</i>
----------------	--------------------------

Description

note: if method is wilcoxon, the A0 and var equal will be ignored

Usage

```
EBAM.Cmpd.Init(mSetObj = NA, method = "z.ebam", A0 = 0,
  isPaired = FALSE, isVarEq = TRUE)
```

Arguments

mSetObj	Input name of the created mSet Object
method	Input the method for EBAM analysis
A0	Numeric
isPaired	Logical, FALSE by default
isVarEq	Logical, TRUE by default

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

FC.Anal.paired	<i>Fold change analysis, paired</i>
----------------	-------------------------------------

Description

Perform paired fold change analysis

Usage

```
FC.Anal.paired(mSetObj = NA, fc.thresh = 2, percent.thresh = 0.75,
  cmp.type = 0)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
fc.thresh	Fold-change threshold, numeric input
percent.thresh	Numeric input, from 0 to 1 to indicate the significant count threshold
cmp.type	Comparison type, 0 for group 1 minus group 2, and 1 for group

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

FC.Anal.unpaired	<i>Fold change analysis, unpaired</i>
------------------	---------------------------------------

Description

Perform fold change analysis, method can be mean or median

Usage

```
FC.Anal.unpaired(mSetObj, fc.thresh=2, cmp.type = 0)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
fc.thresh	Fold-change threshold, numeric input
cmp.type	Comparison type, 0 for group 1 minus group 2, and 1 for group 1 minus group 2

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

FeatureCorrelation	<i>Pattern hunter</i>
--------------------	-----------------------

Description

Calculate correlation of all other feature to a given feature name

Usage

```
FeatureCorrelation(mSetObj = NA, dist.name, varName)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
dist.name	Input the name of the distance measure
varName	Input the variable name

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

FilterVariable	<i>Methods for non-specific filtering of variables</i>
----------------	--

Description

This is a function that filters the dataset, dependent on the user-specified method for filtering. The function applies a filtering method, ranks the variables within the dataset, and removes variables based on its rank. The final dataset should contain no more than 5000 variables for effective computing.

Usage

```
FilterVariable(mSetObj=NA, filter, qcFilter, rsd)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
filter	Select the filter option, "rsd" which is the relative standard deviation, "nrstd" which is the non-parametric relative standard deviation, "mean" which is the mean, "sd" which is the standard deviation, "mad" which is the median absolute deviation, or "iqr" which is the interquantile range.
qcFilter	Filter the variables based on QC samples - True (T), or use non-QC based filtering - False (F).
rsd	Define the relative standard deviation cut-off. Variables with a RSD greater than this number will be removed from the dataset. It is only necessary to specify this argument if qcFilter is True (T). Otherwise, it will not be used in the function.

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

findEqualGreaterM	<i>Perform utilities for peak grouping</i>
-------------------	--

Description

Perform various utilities for peak grouping

Usage

```
findEqualGreaterM(x, values)
```

Arguments

x	Input the data
values	Input the values

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (≥ 2)

FisherLSD

Fisher for ANOVA

Description

Perform Fisher LSD for ANOVA, used in higher function

Usage

```
FisherLSD(aov.obj, thresh)
```

Arguments

aov.obj	Input the anova object
thresh	Numeric, input the alpha threshold

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (≥ 2)

genLogisticRegMdl

Develop a Logistic Regression Model with all of the combined k-fold CV subsets

Description

Develop a Logistic Regression Model with all of the combined k-fold CV subsets

Usage

```
genLogisticRegMdl(x.train, y.train, x.test, y.test)
```

Arguments

x.train	Input the X training set
y.train	Input the Y training set
x.test	Input the X test set
y.test	Input the Y test set

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (≥ 2)

Get.asca.tss	<i>Function for ASCA permutation</i>
--------------	--------------------------------------

Description

Dummy is used only for the purpose to maintain lapply API this is used for permutation on ANOVA partitions, not on the SCA/PCA part, so the number of selected components is not applicable in this step

Usage

```
Get.asca.tss(dummy, perm = T)
```

Arguments

dummy	Dummy variable
perm	Logical, TRUE by default

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

Get.bwss	<i>Compute within group and between group sum of squares (BSS/WSS) for each row of a matrix which may have NA</i>
----------	---

Description

Columns have labels, x is a numeric vector, cl is consecutive integers

Usage

```
Get.bwss(x, cl)
```

Arguments

x	Numeric vector
cl	Columns

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

Get.ConcRef	<i>Get the concentration reference</i>
-------------	--

Description

Get the concentration reference

Usage

```
Get.ConcRef(mSetObj = NA, compd.nm)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
compd.nm	Input the compound name

Get.Leverage	<i>Fast leverage calculation for permutation purpose</i>
--------------	--

Description

note, the leverage combines all components the importance feature is for the factor not per components

Usage

```
Get.Leverage(XKw, Fac)
```

Arguments

XKw	Features
Fac	Factor

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

`Get.pAUC`*Calculate partial area under ROC curve*

Description

Calculate partial area under ROC curve

Usage

```
Get.pAUC(x, y, focus, cutoff)
```

Arguments

x	Input X
y	Input Y
focus	Method
cutoff	Numeric

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

`Get.pred`*Get predicted class probability*

Description

Get predicted class probability, used in higher function

Usage

```
Get.pred(x.train, y.train, x.test, y.test, clsMethod = "pls")
```

Arguments

x.train	Training X
y.train	Training Y
x.test	Test X
y.test	Test Y
clsMethod	Method to predict class, by default it is PLS

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

Get.rpart.summary	<i>Get the text description of a recursive partitioning (rpart) result</i>
-------------------	--

Description

x must be an rpart object

Usage

```
Get.rpart.summary(x)
```

Arguments

x	An Rpart object
---	-----------------

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

Get.tss	<i>Compute sum of squares (SSQ) for each row of a matrix which may have NA</i>
---------	--

Description

Columns have labels cl=consecutive integers note: this is desgined for ASCA parition data in which Within group (WSS) is zero, so, we only need TSS

Usage

```
Get.tss(x, cl)
```

Arguments

x	Input X
cl	Input the columns

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

Get.VIP	<i>Calculate variable importance of projection (VIP) score for PLS object</i>
---------	---

Description

Users give a pls object ('oscorespls'=T), function calculates VIP score usually one VIP for each component, return is the average of all VIP

Usage

```
Get.VIP(pls.obj, comp = 2)
```

Arguments

pls.obj	Input the PLS object
comp	Numeric, input the number of components, by default it is 2

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

GetAbundanceLabel	<i>Determine value label for plotting</i>
-------------------	---

Description

Concentration or intensity data type

Usage

```
GetAbundanceLabel(data.type)
```

Arguments

data.type	Input concentration or intensity data
-----------	---------------------------------------

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

GetAccuracyInfo	<i>Export biomarker accuracy information</i>
-----------------	--

Description

Export biomarker accuracy information

Usage

```
GetAccuracyInfo(mSetObj = NA)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
---------	---

GetAllDataNames	<i>Get all meta-analysis name data</i>
-----------------	--

Description

Get all meta-analysis name data

Usage

```
GetAllDataNames()
```

GetAllKMClusterMembers	<i>K-means analysis - cluster</i>
------------------------	-----------------------------------

Description

K-means analysis - cluster

Usage

```
GetAllKMClusterMembers(mSetObj = NA)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
---------	---

GetAllSOMClusterMembers
SOM analysis

Description

Get members for given cluster index, return a character string

Usage

```
GetAllSOMClusterMembers(mSetObj = NA)
```

Arguments

mSetObj Input the name of the created mSetObj (see InitDataObjects)

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

GetCandidateList *Get all candidate compound names for a given index*

Description

Returns 3 coloumns - inx, name, score

Usage

```
GetCandidateList(mSetObj = NA)
```

Arguments

mSetObj Input the name of the created mSetObj (see InitDataObjects)

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

GetCircleInfo	<i>Export information about selected circle</i>
---------------	---

Description

Export information about selected circle

Usage

```
GetCircleInfo(mSetObj = NA)
```

Arguments

mSetObj	Input name of the created mSet Object
---------	---------------------------------------

GetCIs	<i>Get confidence intervals</i>
--------	---------------------------------

Description

For non-parametric tests, use quantiles, use normal (1.96*std.err) if parametric

Usage

```
GetCIs(data, param = F)
```

Arguments

data	Input data matrix
param	Logical, False by default

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

GetCMD	<i>Retrieve last command from the Rhistory.R file</i>
--------	---

Description

Fetches the last command from the Rhistory.R file

Usage

```
GetCMD(regex)
```

Arguments

regex	Retrieve last command from Rhistory file
-------	--

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

GetConvertFullPath	<i>Perform utilities for cropping images</i>
--------------------	--

Description

Obtain the full path to convert (from imagemagik) for cropping images

Usage

```
GetConvertFullPath()
```

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

getDataFromTextArea	<i>Transform 2 column text to data matrix</i>
---------------------	---

Description

Transform two column input text to data matrix (single column data frame)

Usage

```
getDataFromTextArea(txtInput, sep.type = "space")
```

Arguments

txtInput	Input text
sep.type	Indicate the separator type for input text. Default set to "space"

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

GetExtendRange	<i>Extend axis</i>
----------------	--------------------

Description

Extends the axis range to both ends vec is the values for that axis unit is the width to extend, 10 will increase by 1/10 of the range

Usage

```
GetExtendRange(vec, unit = 10)
```

Arguments

vec	Input the vector
unit	Numeric

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

`GetFC`*Used by higher functions to calculate fold change*

Description

Utility method to calculate FC, used in higher function

Usage

```
GetFC(mSetObj = NA, paired = FALSE, cmpType)
```

Arguments

<code>mSetObj</code>	Input the name of the created mSetObj (see InitDataObjects)
<code>paired</code>	Logical, true or false
<code>cmpType</code>	Numeric, 0 or 1

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

`GetFeatureNumbers`*Numbers for subset selection*

Description

Return a series of number for subsets selection

Usage

```
GetFeatureNumbers(feats.len)
```

Arguments

<code>feats.len</code>	Input the feature length
------------------------	--------------------------

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

GetFinalNameMap	<i>Return the final (after user selection) map as dataframe</i>
-----------------	---

Description

Returns three columns: original name, HMDB name and KEGG ID, for enrichment and pathway analysis, respectively

Usage

```
GetFinalNameMap(mSetObj = NA)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
---------	---

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

GetFisherPvalue	<i>Get fisher p-values</i>
-----------------	----------------------------

Description

Get fisher p-values

Usage

```
GetFisherPvalue(numSigMembers, numSigAll, numMembers, numAllMembers)
```

Arguments

numSigMembers	Number of significant members
numSigAll	Number of all significant features
numMembers	Number of members
numAllMembers	Number of all members

GetHTMLMetSet	<i>Given a metset inx, return hmtl highlighted metset cmpds and references</i>
---------------	--

Description

Given a metset inx, return hmtl highlighted metset cmpds and references

Usage

```
GetHTMLMetSet(mSetObj = NA, msetNm)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
msetNm	Input the name of the metabolite set

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

GetHTMLPathSet	<i>Given a metset inx, return hmtl highlighted pathway cmpds</i>
----------------	--

Description

Given a metset inx, return hmtl highlighted pathway cmpds

Usage

```
GetHTMLPathSet(mSetObj = NA, msetNm)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
msetNm	Input the name of the metabolite set

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

GetImpFeatureMat	<i>Get important feature matrix</i>
------------------	-------------------------------------

Description

feat.outp is a list that contains the ranked features in each cross validation (CV) and returns a two column matrix, col 1 = median ranking and col 2 = mean importance measure

Usage

```
GetImpFeatureMat(mSetObj = NA, feat.outp, bestFeatNum)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
feat.outp	Input the list that contains the ranked features in each cross validation (CV) and returns a two column matrix, col 1 = median ranking and col 2 = mean importance measure
bestFeatNum	Numeric

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

GetKEGGNodeInfo	<i>Retrieves KEGG node information</i>
-----------------	--

Description

Retrieves KEGG node information

Usage

```
GetKEGGNodeInfo(path.id, g, width, height, usr = par("usr"))
```

Arguments

path.id	Input the path ID
g	Input data
width	Input the width
height	Input the height
usr	Input the user

GetKMClusterMembers	<i>K-means analysis - cluster</i>
---------------------	-----------------------------------

Description

Get the cluster members for given index add HTML color to the names based on its group membership

Usage

```
GetKMClusterMembers(mSetObj = NA, i)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
i	Input the cluster index

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

GetLassoFreqs	<i>Compute lasso frequency</i>
---------------	--------------------------------

Description

Not part of default, need to perform function to compute lasso frequency msg: There are more than 500 variables and n<m You may wish to restart and set use.Gram=FALSE

Usage

```
GetLassoFreqs(mSetObj = NA)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
---------	---

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

GetLimmaResTable	<i>Get result table from eBayes fit object</i>
------------------	--

Description

Get result table from eBayes fit object

Usage

```
GetLimmaResTable(fit.obj)
```

Arguments

fit.obj	eBayes fit object to parse to a table
---------	---------------------------------------

GetMapTable	<i>Get mapping table</i>
-------------	--------------------------

Description

Return results from compound name mapping in a table

Usage

```
GetMapTable(mSetObj = NA)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
---------	---

GetMaxPCAComp	<i>For plotting PCA, selects max top 9 components</i>
---------------	---

Description

Rotate PCA analysis

Usage

```
GetMaxPCAComp(mSetObj = NA)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
---------	---

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

GetMeanROC

Compute data points on the ROC curve

Description

perf is the performance object from ROCR

Usage

```
GetMeanROC(perf)
```

Arguments

perf Performance object from ROCR

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

GetMetaResultMatrix

Single.type return logFC or p value for individual data analysis

Description

Single.type return logFC or p value for individual data analysis

Usage

```
GetMetaResultMatrix(mSetObj = NA, single.type = "fc")
```

Arguments

mSetObj Input name of the created mSet Object

single.type Default is "fc"

GetMetaSigHitsTable	<i>Export the significant hits from meta-analysis</i>
---------------------	---

Description

Export the significant hits from meta-analysis

Usage

```
GetMetaSigHitsTable(mSetObj = NA)
```

Arguments

mSetObj	Input name of the created mSet Object
---------	---------------------------------------

GetMetSetName	<i>Given a metset inx, give its name</i>
---------------	--

Description

Given a metset inx, give its name

Usage

```
GetMetSetName(mSetObj = NA, msetInx)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
msetInx	Input the index of the metabolite set

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

GetMsetLibCheckMsg	<i>Get the library check messages</i>
--------------------	---------------------------------------

Description

Get the library check messages

Usage

```
GetMsetLibCheckMsg(mSetObj = NA)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
---------	---

GetMsetLibSearchResult	<i>Return metset search results</i>
------------------------	-------------------------------------

Description

since String[][] is not supported, have to return as 1D vector, matrix can be directly convert to vector, note default will be column first

Usage

```
GetMsetLibSearchResult(mSetObj = NA)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
---------	---

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

GetMsetNames	<i>Return the selected metset library to java for display</i>
--------------	---

Description

Return the selected metset library to java for display

Usage

```
GetMsetNames(mSetObj = NA)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
---------	---

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

GetNetworkGeneMappingResultTable	<i>Exports Gene-Mapping result into a table</i>
----------------------------------	---

Description

Exports Gene-Mapping result into a table

Usage

```
GetNetworkGeneMappingResultTable(mSetObj = NA)
```

Arguments

mSetObj	Input name of the created mSet Object
---------	---------------------------------------

GetNewSampleNames	<i>Obtain sample names and their class labels</i>
-------------------	---

Description

Obtain sample names and their class labels

Usage

```
GetNewSampleNames(mSetObj = NA)
```

Arguments

mSetObj Input the name of the created mSetObj (see InitDataObjects)

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

GetORA.pathNames	<i>Export pathway names from ORA analysis</i>
------------------	---

Description

Export pathway names from ORA analysis

Usage

```
GetORA.pathNames(mSetObj = NA)
```

Arguments

mSetObj Input the name of the created mSetObj (see InitDataObjects)

GetORA.smpdbIDs	<i>Only for human pathways</i>
-----------------	--------------------------------

Description

Only for human pathways

Usage

```
GetORA.smpdbIDs(mSetObj = NA)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
---------	---

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

GetORATable	<i>Get ORA table</i>
-------------	----------------------

Description

Get ORA table

Usage

```
GetORATable(mSetObj = NA)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
---------	---

GetQEA.pathNames	<i>Export pathway names from QEA analysis</i>
------------------	---

Description

Export pathway names from QEA analysis

Usage

```
GetQEA.pathNames(mSetObj = NA)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
---------	---

GetQEATable	<i>QEA table</i>
-------------	------------------

Description

QEA table

Usage

GetQEATable(mSetObj = NA)

Arguments

mSetObj Input the name of the created mSetObj (see InitDataObjects)

GetRCommandHistory	<i>Export R Command History</i>
--------------------	---------------------------------

Description

Export R Command History

Usage

GetRCommandHistory(mSetObj = NA)

Arguments

mSetObj Input the name of the created mSetObj (see InitDataObjects)

GetRFConf.Table	<i>Classification performance table for random forest analysis</i>
-----------------	--

Description

Classification performance table for random forest analysis

Usage

GetRFConf.Table(mSetObj = NA)

Arguments

mSetObj Input the name of the created mSetObj (see InitDataObjects)

GetRFConfMat	<i>Random Forest Confusion Matrix</i>
--------------	---------------------------------------

Description

Return double confusion matrix

Usage

```
GetRFConfMat(mSetObj = NA)
```

Arguments

mSetObj Input the name of the created mSetObj (see InitDataObjects)

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

GetRF00B	<i>Random Forest OOB</i>
----------	--------------------------

Description

Get the OOB error for the last signif

Usage

```
GetRF00B(mSetObj = NA)
```

Arguments

mSetObj Input the name of the created mSetObj (see InitDataObjects)

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

GetRFSigMat

Random Forest Significance matrix

Description

Significance measure, double brackets

Usage

```
GetRFSigMat(mSetObj = NA)
```

Arguments

mSetObj Input the name of the created mSetObj (see InitDataObjects)

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

GetROC.coords

Return ROC corodinales with confidence intervals

Description

Return ROC corodinales with confidence intervals

Usage

```
GetROC.coords(mSetObj = NA, fld.nm, val, plot = TRUE, imgNm)
```

Arguments

mSetObj Input the name of the created mSetObj (see InitDataObjects)
fld.nm The kind of input coordinate
val The coordinates to look for
plot Logical, by default set to TRUE
imgNm Input the image name

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

GetROCLassoFreq	<i>Get p-values from lasso</i>
-----------------	--------------------------------

Description

Get p-values from lasso

Usage

```
GetROCLassoFreq(data, cls)
```

Arguments

data	Input data
cls	Input class labels

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (≥ 2)

GetROCTtestP	<i>Get p-values for ROC</i>
--------------	-----------------------------

Description

ROC p-values, used in higher function

Usage

```
GetROCTtestP(data, cls)
```

Arguments

data	Input data
cls	Input class labels

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (≥ 2)

GetSampleSizeLadder	<i>Retrieve sample size ladder</i>
---------------------	------------------------------------

Description

Return sample size ladder, used in higher functions

Usage

```
GetSampleSizeLadder(maxNum)
```

Arguments

maxNum	Numeric
--------	---------

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (≥ 2)

GetSelectedDataNames	<i>Retrieve data names</i>
----------------------	----------------------------

Description

Retrieve data names

Usage

```
GetSelectedDataNames(mSetObj = NA)
```

Arguments

mSetObj	Input name of the created mSet Object
---------	---------------------------------------

GetSelectedDataNumber	<i>Retrieve selected data numbers</i>
-----------------------	---------------------------------------

Description

Retrieve selected data numbers

Usage

```
GetSelectedDataNumber(mSetObj = NA)
```

Arguments

mSetObj	Input name of the created mSet Object
---------	---------------------------------------

GetSigTable	<i>Create Latex table</i>
-------------	---------------------------

Description

generate Latex table

Usage

```
GetSigTable(mat, method, data.type)
```

Arguments

mat	Input matrix
method	Input method to create table
data.type	Input the data type

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

GetSigTable.Anova	<i>Sig Table for Anova</i>
-------------------	----------------------------

Description

Sig Table for Anova

Usage

```
GetSigTable.Anova(mSetObj = NA)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
---------	---

GetSigTable.Aov2	<i>Sig table for AOV2</i>
------------------	---------------------------

Description

Sig table for AOV2

Usage

```
GetSigTable.Aov2(mSetObj = NA)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
---------	---

GetSigTable.ASCA	<i>Table of features well modelled by ASCA</i>
------------------	--

Description

Table of features well modelled by ASCA

Usage

```
GetSigTable.ASCA(mSetObj = NA, nm)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
nm	Input the name of the well modelled features

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

GetSigTable.Corr	<i>Sig table for Correlation Analysis</i>
------------------	---

Description

Sig table for Correlation Analysis

Usage

```
GetSigTable.Corr(mSetObj = NA)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
---------	---

GetSigTable.EBAM	<i>Sig table for EBAM</i>
------------------	---------------------------

Description

Sig table for EBAM

Usage

```
GetSigTable.EBAM(mSetObj = NA)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
---------	---

GetSigTable.FC	<i>Sig Table for Fold-Change Analysis</i>
----------------	---

Description

Sig Table for Fold-Change Analysis

Usage

```
GetSigTable.FC(mSetObj = NA)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
---------	---

GetSigTable.MB	<i>Sig table for MB analysis</i>
----------------	----------------------------------

Description

Sig table for MB analysis

Usage

```
GetSigTable.MB(mSetObj = NA)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
---------	---

GetSigTable.RF	<i>Sig table for random forest analysis</i>
----------------	---

Description

Sig table for random forest analysis

Usage

```
GetSigTable.RF(mSetObj = NA)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
---------	---

GetSigTable.SAM	<i>Sig table for SAM</i>
-----------------	--------------------------

Description

Sig table for SAM

Usage

```
GetSigTable.SAM(mSetObj = NA)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
---------	---

GetSigTable.SVM	<i>Sig table for SVM</i>
-----------------	--------------------------

Description

Sig table for SVM

Usage

```
GetSigTable.SVM(mSetObj = NA)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
---------	---

GetSigTable.TT	<i>Sig Table for T-test Analysis</i>
----------------	--------------------------------------

Description

Sig Table for T-test Analysis

Usage

```
GetSigTable.TT(mSetObj = NA)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
---------	---

GetSigTable.Volcano	<i>Sig table for Volcano Analysis</i>
---------------------	---------------------------------------

Description

Sig table for Volcano Analysis

Usage

```
GetSigTable.Volcano(mSetObj = NA)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
---------	---

GetSOMClusterMembers	<i>SOM analysis</i>
----------------------	---------------------

Description

Get members for given cluster index, return a character string

Usage

```
GetSOMClusterMembers(mSetObj = NA, i, j)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
i	Index of X
j	Index of Y

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

GetSSPTable	<i>Replace the last column of the ssp.mat with the final selection from users</i>
-------------	---

Description

Replace the last column of the ssp.mat with the final selection from users

Usage

```
GetSSPTable(mSetObj = NA)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
---------	---

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

GetSuggestedSAMDelta *For SAM analysis*

Description

obtain a default delta with reasonable number of sig features and decent FDR

Usage

```
GetSuggestedSAMDelta(mSetObj = NA)
```

Arguments

mSetObj Input the name of the created mSetObj (see InitDataObjects)

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

GetSVMSigMat *Recursive Support Vector Machine (R-SVM) Significance Measure*

Description

Return significance measure, double[][]

Usage

```
GetSVMSigMat(mSetObj = NA)
```

Arguments

mSetObj Input the name of the created mSetObj (see InitDataObjects)

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

`GetTopInx`*Volcano indices*

Description

Get indices of top n largest/smallest number

Usage

```
GetTopInx(vec, n, dec = T)
```

Arguments

<code>vec</code>	Vector containing volcano indices
<code>n</code>	Numeric
<code>dec</code>	Logical, default set to TRUE

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

`GetTrainTestSplitMat` *Make random partitions*

Description

Make random partitions, returns matrices indicating whether the observation is in train/test for each run note: try to get a balanced sampling for each group (classification) or each quantile (regression). This is very useful for unbalanced data

Usage

```
GetTrainTestSplitMat(y, propTraining = 2/3, nRuns = 30)
```

Arguments

<code>y</code>	Input the data
<code>propTraining</code>	By default set to 2/3
<code>nRuns</code>	By default set to 30

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

GetTtestRes	<i>Retrieve T-test p-values</i>
-------------	---------------------------------

Description

Utility method to get p values

Usage

```
GetTtestRes(mSetObj = NA, paired = FALSE, equal.var = TRUE, nonpar = F)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
paired	Default set to FALSE
equal.var	Default set to TRUE
nonpar	Use non-parametric tests, default is set to FALSE

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

GetTTSigMat	<i>T-test matrix</i>
-------------	----------------------

Description

Return a double matrix with 2 columns - p values and lod

Usage

```
GetTTSigMat(mSetObj = NA)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
---------	---

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

`GetUnivReport`*Utility method to perform the univariate analysis automatically*

Description

The approach is computationally expensive, and fails more often get around: make it lazy unless users request, otherwise the default t-test will also be affected

Usage

```
GetUnivReport(mSetObj = NA)
```

Arguments

`mSetObj` Input the name of the created `mSetObj` (see `InitDataObjects`)

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

`GetVariableLabel`*Determine variable label for plotting*

Description

Determine data type, binned spectra, nmr peak, or ms peak

Usage

```
GetVariableLabel(data.type)
```

Arguments

`data.type` Input the data type

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

GetVennGeneNames	<i>Get Venn names</i>
------------------	-----------------------

Description

Get Venn names

Usage

```
GetVennGeneNames(mSetObj = NA, areas)
```

Arguments

mSetObj	Input name of the created mSet Object
areas	Input areas to retrieve names

GetXYCluster	<i>Determine row/column number for plotting</i>
--------------	---

Description

Determine the number of rows and columns for a given total number of plots (used by Kmeans and SOM plots)

Usage

```
GetXYCluster(total)
```

Arguments

total	Input the total
-------	-----------------

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

GroupPeakList	<i>Group peak list</i>
---------------	------------------------

Description

Group peaks from the peak list based on position using the XCMS grouping algorithm (align peaks wrt, rt, and mz). For NMR peaks, need to change ppm -> mz and add dummy rt. If the data is 2-column MS, first need to add dummy rt. If the data is 3-column MS, the data can be used directly. The default mzwid for MS is 0.25 m/z, and for NMR is 0.03 ppm. The default bw is 30 for LCMS, and 5 for GCMS.

Usage

```
GroupPeakList(mSetObj=NA, mzwid, bw, minfrac, minsamp, max)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
mzwid,	define the width of overlapping m/z slices to use for creating peak density chromatograms and grouping peaks across samples
bw,	define the bandwidth (standard deviation or half width at half maximum) of gaussian smoothing kernel to apply to the peak density chromatogram
minfrac,	define the minimum fraction of samples necessary in at least one of the sample groups for it to be a valid group
minsamp,	define the minimum number of samples necessary in at least one of the sample groups for it to be a valid group
max,	define the maximum number of groups to identify in a single m/z slice

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

heckbert	<i>Heckbert algorithm</i>
----------	---------------------------

Description

function to calculate tick mark based on Heckbert algorithm available in the "labeling" package implemented by Justin Talbot adapted from the imagemap package Heckbert's labeling algorithm Heckbert, P. S. (1990) Nice numbers for graph labels, Graphics Gems I, Academic Press Professional, Inc.

Usage

```
heckbert(dmin, dmax, m)
```

Arguments

dmin	Heckbert
dmax	Heckbert
m	Heckbert

Author(s)

Justin Talbot <jtalbot@stanford.edu>

HMDBID2KEGGID

Given a vector of HMDBIDs, return a vector of KEGG IDs

Description

This function, when given a vector of HMDBIDs, returns a vector of KEGG ID. HMDB standing for the Human Metabolome Database.

Usage

```
HMDBID2KEGGID(ids)
```

Arguments

ids	Input the vector of HMDB Ids
-----	------------------------------

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

HMDBID2Name

Given a vector of HMDBIDs, return a vector of HMDB compound names

Description

This function, when given a vector of HMDBIDs, return a vector of HMDB compound names. HMDB standing for the Human Metabolome Database.

Usage

```
HMDBID2Name(ids)
```

Arguments

ids	Input the vector of HMDB Ids
-----	------------------------------

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

ImputeVar

Data processing: Replace missing variables

Description

Replace missing variables by min/mean/median/KNN/BPCA/PPCA/svdImpute.

Usage

```
ImputeVar(mSetObj, method)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
method	Select the option to replace missing variables, either replacement based on the minimum ("min"), the mean ("mean"), or the median ("median") value of each feature columns, or several options to impute the missing values, using k-nearest neighbour ("KNN"), probabilistic PCA ("PPCA"), Bayesian PCA ("BPCA") method, or Singular Value Decomposition ("svdImpute")

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

InitDataObjects

Constructs a dataSet object for storing data

Description

This functions handles the construction of a mSetObj object for storing data for further processing and analysis. It is necessary to utilize this function to specify to MetaboAnalystR the type of data and the type of analysis you will perform.

Usage

```
InitDataObjects(data.type, anal.type, paired=FALSE)
```

Arguments

data.type	The type of data, either list (Compound lists), conc (Compound concentration data), specbin (Binned spectra data), pktable (Peak intensity table), nmrpeak (NMR peak lists), mspeak (MS peak lists), or msspec (MS spectra data)
anal.type	Indicate the analysis module to be performed: stat, pathora, pathqea, msetora, msetssp, msetqea, ts, cmpdmap, smpmap, or pathinteg
paired	Indicate if the data is paired or not. Logical, default set to FALSE

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

InitPowerAnal	<i>Function for power analysis</i>
---------------	------------------------------------

Description

Perform power analysis, requires the SSPA R package.

Usage

```
InitPowerAnal(mSetObj, clsOpts)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
clsOpts	For data with >2 groups, specify the two classes on which to perform power analysis, otherwise for data with 2 groups, "NA" will automatically select the 2 groups.

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

InitStatAnalMode	<i>Introduction for statistical analysis module report Initialize Statistical Analysis Report</i>
------------------	---

Description

Introduction for statistical analysis module report Initialize Statistical Analysis Report

Usage

```
InitStatAnalMode()
```

InitTimeSeriesAnal	Create report of analyses (Met Pathway)
--------------------	---

Description

Report generation using Sweave Metabolomic pathway analysis, time-series analysis

Usage

```
InitTimeSeriesAnal()
```

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

iPCA.Anal	Perform PCA analysis, prepare file for interactive liveGraphics3D
-----------	---

Description

Perform PCA analysis, prepare file for interactive liveGraphics3D

Usage

```
iPCA.Anal(mSetObj, fileNm)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
fileNm	select a file name

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

isEmptyMatrix	<i>Sig table matrix is empty</i>
---------------	----------------------------------

Description

Test if a sig table matrix is empty

Usage

```
isEmptyMatrix(mat)
```

Arguments

mat	Matrix to test if empty
-----	-------------------------

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

IsSmallSmplSize	<i>Check if the sample size is small</i>
-----------------	--

Description

Returns whether or not the sanity check found that there were too many groups in the dataset containing too few samples. It will return a 0 if the data passes the check, or will return a 1 if the data does not.

Usage

```
IsSmallSmplSize(mSetObj=NA)
```

Arguments

mSetObj	Input name of the created mSet Object
---------	---------------------------------------

IsSpectraProcessingOK *Check if the spectra processing is ok*

Description

Check if the spectra processing is ok

Usage

IsSpectraProcessingOK(mSetObj = NA)

Arguments

mSetObj Input the name of the created mSetObj (see InitDataObjects).

KEGGID2HMDBID *Given a vector of KEGGIDs, return a vector of HMDB ID*

Description

This function, when given a vector of KEGGIDs, returns a vector of HMDB IDs. HMDB standing for the Human Metabolome Database.

Usage

KEGGID2HMDBID(ids)

Arguments

ids Vector of KEGG ids

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

KEGGID2Name	<i>Given a vector containing KEGGIDs, returns a vector of KEGG compound names</i>
-------------	---

Description

This function, given a vector containing KEGGIDs, returns a vector of KEGG compound names.

Usage

```
KEGGID2Name(ids)
```

Arguments

ids	Vector of KEGG ids
-----	--------------------

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

KEGGPATHID2SMPDBIDs	<i>Given a vector containing KEGG pathway IDs, return a vector containing SMPDB IDs (only for hsa)</i>
---------------------	--

Description

This function, when given a vector of KEGG pathway IDs, return a vector of SMPDB IDs (only for hsa). SMPDB standing for the Small Molecule Pathway Database, and hsa standing for human serum albumin.

Usage

```
KEGGPATHID2SMPDBIDs(ids)
```

Arguments

ids	Vector of KEGG pathway IDs
-----	----------------------------

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

`Kmeans.Anal`*K-means analysis*

Description

Perform K-means analysis

Usage

```
Kmeans.Anal(mSetObj = NA, clust.num)
```

Arguments

<code>mSetObj</code>	Input name of the created mSet Object
<code>clust.num</code>	Numeric, input the number of clusters for K-means analysis

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

`kwtest`*Kruskal-Wallis*

Description

Perform Kruskal-Wallis Test

Usage

```
kwtest(x, cls)
```

Arguments

<code>x</code>	Input data to perform Kruskal-Wallis
<code>cls</code>	Input class labels

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

LoadKEGGKO_lib	<i>Utility function for PerformKOEnrichAnalysis_KO01100</i>
----------------	---

Description

Utility function for PerformKOEnrichAnalysis_KO01100

Usage

```
LoadKEGGKO_lib(category)
```

Arguments

category	Module or pathway
----------	-------------------

LoadKEGGLib	<i>Load KEGG library</i>
-------------	--------------------------

Description

Load KEGG library

Usage

```
LoadKEGGLib(libOpt)
```

Arguments

libOpt	KEGG library option, "integ" for integrative, "genetic" for genetic, and "met" for metabolic
--------	--

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

LoadMsetLib	<i>Load metabolite set library</i>
-------------	------------------------------------

Description

Metabolite set library

Usage

```
LoadMsetLib(libname = "pathway")
```

Arguments

libname	Input the name of the metabolite set library to load. Default set to "pathway" library.
---------	---

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

LoadSmpLib	<i>Load pathway library</i>
------------	-----------------------------

Description

Load pathway library

Usage

```
LoadSmpLib(mSetObj = NA)
```

Arguments

mSetObj	Input name of the created mSet Object
---------	---------------------------------------

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

LogNorm	<i>Column-wise Normalization</i>
---------	----------------------------------

Description

Column-wise norm methods, when x is a column Options for log, zero mean and unit variance, and several zero mean and variance/SE

Usage

```
LogNorm(x, min.val)
```

Arguments

x	Input data
min.val	Input minimum value

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada

LSD.test	<i>Calculate Fisher's Least Significant Difference (LSD)</i>
----------	--

Description

Adapted from the 'agricolae' package

Usage

```
LSD.test(y, trt, alpha = 0.05)
```

Arguments

y	Input Y
trt	Input trt
alpha	Numeric, default is 0.05

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

`make_cpdlst`*Utility function to create compound lists for permutation analysis*

Description

From a vector of m/z features, this function outputs a vector of compounds.

Usage

```
make_cpdlst(mSetObj=NA, input_mzs)
```

Arguments

<code>mSetObj</code>	Input the name of the created mSetObj
<code>input_mzs</code>	The vector of randomly drawn m/z features.

Author(s)

Jasmine Chong, Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

`map`*sPLS-DA Map*

Description

map variable for (s)plsda

Usage

```
map(Y)
```

Arguments

<code>Y</code>	Input data
----------------	------------

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

MapCmpd2KEGGNodes	<i>Utility function for PrepareQueryJson</i>
-------------------	--

Description

Utility function for PrepareQueryJson

Usage

```
MapCmpd2KEGGNodes(cmpds, net = "ko01100")
```

Arguments

cmpds	Input the compounds
net	Input the network name

MapK02KEGGEEdges	<i>Utility function for PrepareQueryJson</i>
------------------	--

Description

Utility function for PrepareQueryJson

Usage

```
MapK02KEGGEEdges(kos, net = "ko01100")
```

Arguments

kos	Input the KOs
net	Input the name of the network

Match.Pattern	<i>Match pattern for correlation analysis</i>
---------------	---

Description

Match pattern for correlation analysis

Usage

```
Match.Pattern(mSetObj = NA, dist.name = "pearson", pattern = NULL)
```

Arguments

mSetObj	Input the name of the created mSetObj
dist.name	Input the distance method, default is set to pearson
pattern	Set the pattern, default is set to NULL

MergeDatasets	<i>Utility function for PrepareQueryJson</i>
---------------	--

Description

Utility function for PrepareQueryJson

Usage

```
MergeDatasets(dataSet1, dataSet2)
```

Arguments

dataSet1	Input the first dataset
dataSet2	Input the second dataset

MergeDuplicates	<i>Merge duplicated columns or rows by their mean</i>
-----------------	---

Description

dim 1 => row, dim 2 => column

Usage

```
MergeDuplicates(data, dim = 2)
```

Arguments

data	Input the data
dim	Numeric, input the dimensions, default is set to 2

MetaboliteMappingExact

Mapping from different metabolite IDs

Description

For compound names to other ids, can do exact or approximate matches For other IDs, except HMDB ID, all others may return multiple/non-unique hits Multiple hits or non-unique hits will allow users to manually select

Usage

```
MetaboliteMappingExact(mSetObj = NA, q.type)
```

Arguments

mSetObj	Input the name of the created mSetObj
q.type	Input the query-type

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

MSspec.fillPeaks	<i>Function to fill in missing peaks</i>
------------------	--

Description

For each sample in the processed MS spectra data, this function will fill in missing peaks using the fillPeaks function from the XCMS package. First, the function will identify any peak groups that are missing any peaks from the samples and will then fill in those peaks by rereading the raw data and integrating signals at those regions to create a new peak.

Usage

```
MSspec.fillPeaks(mSetObj=NA)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
---------	---

MSspec.rtCorrection	<i>Retention time correction for LC/GC-MS spectra</i>
---------------------	---

Description

Performs retention time correction for LC/GC-MS spectra using the XCMS package. Following retention time correction, the object dataSet will be regrouped.

Usage

```
MSspec.rtCorrection(mSetObj=NA, bw=30)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
bw	Numeric, define the bandwidth (standard deviation or half width at half maximum) of gaussian smoothing kernel to apply to the peak density chromatogram

multi.stat	<i>Get multiple category statistics</i>
------------	---

Description

Get multiple category statistics

Usage

```
multi.stat(pred, resp)
```

Arguments

pred	Input predictions
resp	Input responses

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (≥ 2)

Normalization	<i>Normalization</i>
---------------	----------------------

Description

This function performs row-wise normalization, transformation, and scaling of your metabolomic data.

Usage

```
Normalization(mSetObj, rowNorm, transNorm, scaleNorm, ref=NULL, ratio=FALSE, ratioNum=20)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
rowNorm	Select the option for row-wise normalization, "QuantileNorm" for Quantile Normalization, "ProbNormT" for Probabilistic Quotient Normalization without using a reference sample, "ProbNormF" for Probabilistic Quotient Normalization based on a reference sample, "CompNorm" for Normalization by a reference feature, "SumNorm" for Normalization to constant sum, "MedianNorm" for Normalization to sample median, and "SpecNorm" for Normalization by a sample-specific factor.
transNorm	Select option to transform the data, "LogNorm" for Log Normalization, and "CrNorm" for Cubic Root Transformation.

scaleNorm	Select option for scaling the data, "MeanCenter" for Mean Centering, "AutoNorm" for Autoscaling, "ParetoNorm" for Pareto Scaling, and "RangeNorm" for Range Scaling.
ref	Input the name of the reference sample or the reference feature, use " " around the name.
ratio	This option is only for biomarker analysis.
ratioNum	Relevant only for biomarker analysis.

Author(s)

Jeff Xia <jeff.xia@mcgill.ca>, Jasmine Chong McGill University, Canada

OPLSR.Anal	<i>Perform OPLS-DA</i>
------------	------------------------

Description

Orthogonal PLS-DA (from ropls) Add reg (regression i.e. if class order matters)

Usage

```
OPLSR.Anal(mSetObj = NA, reg = FALSE)
```

Arguments

mSetObj	Input name of the created mSet Object
reg	Logical

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

parseFisher	<i>Return only the significant comparison names</i>
-------------	---

Description

Return only the significant comparison names, used in higher function

Usage

```
parseFisher(fisher, cut.off)
```

Arguments

fisher	Input fisher object
cut.off	Numeric, set cut-off

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (≥ 2)

parseTukey	<i>Return only the significant comparison names</i>
------------	---

Description

Return only the significant comparison names, used in higher function

Usage

```
parseTukey(tukey, cut.off)
```

Arguments

tukey	Input tukey output
cut.off	Input numeric cut-off

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (≥ 2)

PathMapping	<i>Perform pathway mapping</i>
-------------	--------------------------------

Description

Perform pathway mapping of compounds

Usage

```
PathMapping(mSetObj = NA, qvec)
```

Arguments

mSetObj	Input name of the created mSet Object
qvec	Input the query vector

`PCA.Anal`*Perform PCA analysis*

Description

Perform PCA analysis, obtain variance explained, store item to PCA object

Usage

```
PCA.Anal(mSetObj = NA)
```

Arguments

<code>mSetObj</code>	Input name of the created mSet Object McGill University, Canada License: GNU GPL (≥ 2)
----------------------	---

Author(s)

Jeff Xia<jeff.xia@mcgill.ca>

`PCA.Flip`*Rotate PCA analysis*

Description

Rotate PCA analysis

Usage

```
PCA.Flip(mSetObj = NA, axisOpt)
```

Arguments

<code>mSetObj</code>	Input name of the created mSet Object
<code>axisOpt</code>	Input the axis option

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (≥ 2)

PCA.GENES

Obtain principal components into a matrix that has more variables than individuals

Description

X is a matrix that has as columns the compounds that were considered as variables in the PCA analysis. First we center the matrix by columns (Xoff) and then we obtain the eigenvalues and the eigenvectors of the matrix Xoff use the equivalences between the loadings and scores to obtain the solution

Usage

```
PCA.GENES(X)
```

Arguments

X	Input matrix that has as columns the compounds that were considered as variables in the PCA analysis
---	--

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

Perform.ASCA

Perform ASCA

Description

The ASCA algorithm was adapted from the ASCA-genes method (analysis of variance (ANOVA) simultaneous component analysis) by Maria Jose Nueda (mj.nueda@ua.es) and Ana Conesa (aconesa@ivia.es)

Usage

```
Perform.ASCA(mSetObj = NA, a = 1, b = 2, x = 2, res = 2)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
a	specify the number of components for facA
b	specify the number of components for facB
x	specify the number of components for interaction AB
res	specify the number of model residuals type is string, indicating the type of analysis "abc" separately "aab" facA joins with AB "bab" facB joins with AB

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (≥ 2)

Perform.ASCA.permute *Perform ASCA model validation by permutation*

Description

Perform ASCA model validation by permutation we use Manly's unrestricted permutation of observations which essentially permutes the data over all cells in the designed experiment, then calculates the score for each main factor or interaction components. This will get the null distribution for all effects in one go

Usage

```
Perform.ASCA.permute(mSetObj=NA, perm.num)
```

Arguments

mSetObj	Input name of the created mSet Object
perm.num	Select the number of permutations, default is 20

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (≥ 2)

Perform.Permut *Perform permutation tests only for ROC Tester*

Description

Perform permutation tests for the ROC Curve Based Model Creation and Evaluation module

Usage

```
Perform.Permut(mSetObj=NA, perf.measure, perm.num, propTraining = 2/3)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
perf.measure	Input the performance measure to rate the performance of the model, either the area under the ROC curve ("auroc") or the predictive accuracy ("accu")
perm.num	Input the number of permutations to perform
propTraining	Numeric, input the fraction of samples to set aside for training. Default is set to 2/3.

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (≥ 2)

Perform.permutation	<i>Permutation</i>
---------------------	--------------------

Description

Perform permutation, options to change number of cores used

Usage

```
Perform.permutation(perm.num, fun)
```

Arguments

perm.num	Numeric, input the number of permutations to perform
fun	Dummy function

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (≥ 2)

Perform.UnivROC	<i>Perform Classical Univariate ROC</i>
-----------------	---

Description

Perform Classical Univariate ROC

Usage

```
Perform.UnivROC(mSetObj=NA, feat.nm, imgName, format="png", dpi=72, isAUC, isOpt, optMethod, isPartial)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
feat.nm	Input the name of the feature to perform univariate ROC analysis
imgName	Input a name for the plot
format	Select the image format, png, of pdf.
dpi	Input the dpi. If the image format is pdf, users need not define the dpi. For png images, the default dpi is 72. It is suggested that for high-resolution images, select a dpi of 300.

isAUC	Logical, select T to compute the 95 percent confidence interval band and "F" to not
isOpt	Logical, show the optimal cutoff, T to show it and F to not
optMethod	Select the optimal cutoff by using either closest.topleft for closest to top-left corner or youden for farthest to the diagonal line (Youden)
isPartial	Logical, input T to calculate a partial ROC curve, and F to not
measure	Select the parameter to limit the calculation of the partial ROC curve, se for the X-axis (maximum false-positive rate) and sp for the Y-axis, representing the minimum true positive-rate
cutoff	Input the threshold to limit the calculation of the partial ROC curve, the number must be between 0 and 1.

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

PerformApproxMatch	<i>Perform approximate compound matches</i>
--------------------	---

Description

Given a query, perform approximate compound matching

Usage

```
PerformApproxMatch(mSetObj = NA, q)
```

Arguments

mSetObj	Input the name of the created mSetObj
q	Input the q vector

PerformBatchCorrection	<i>Set up two matrixes</i>
------------------------	----------------------------

Description

One is a batch containing summed concentrations of each sample the other contains the features aligned across all samples

Usage

```
PerformBatchCorrection(mSetObj = NA, imgName)
```

Arguments

mSetObj	Input name of the created mSet Object
imgName	Input the name of the plot to create

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

PerformCV.explore	<i>Perform Monte-Carlo Cross Validation (MCCV)</i>
-------------------	--

Description

Classification MCCV, aims to find the best feature subsets using default model parameters

Usage

```
PerformCV.explore(mSetObj, cls.method, rank.method="auroc", lvNum=2, propTraining=2/3)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
cls.method	Select the classification method, "rf" for random forest classification, "pls" for PLS-DA, and "svm" for support vector machine
rank.method	Select the ranking method, "rf" for random forest mean decrease accuracy, "fisher" for Fisher's univariate ranking based on area under the curve "auroc" for univariate ranking based on area under the curve, "tt" for T-test univariate ranking based on area under the curve, "pls" for partial least squares, and "svm" for support vector machine
lvNum	Input the number of latent variables to include in the analysis, only for PLS-DA classification
propTraining	Input the proportion of samples to use for training

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

PerformCV.test	<i>Perform MCCV for manually selected features</i>
----------------	--

Description

MCCV for manually selected features (no additional feature selection)

Usage

```
PerformCV.test(mSetObj, method, lvNum, propTraining=2/3, nRuns=100)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
method	Select the classification method, "rf" for random forest classification, "pls" for PLS-DA, and "svm" for support vector machine
lvNum	Input the number of latent variables to include in the analysis, only for PLS-DA classification
propTraining	Input the proportion of samples to use for training, by default it is 2/3
nRuns	Input the number of MCCV runs, by default it is 100

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

PerformDetailMatch	<i>Perform detailed name matche</i>
--------------------	-------------------------------------

Description

Given a query, perform compound matching

Usage

```
PerformDetailMatch(mSetObj = NA, q)
```

Arguments

mSetObj	Input name of the created mSet Object
q	Input the query

PerformEachDEAnal	<i>Performs differential expression analysis on individual data</i>
-------------------	---

Description

This function performs DE analysis on individual data using the common matrix, which will be used/compared in later steps of the analysis (according to the p-value). The DE for each feature may be adjusted using the p-value.

Usage

```
PerformEachDEAnal(mSetObj = NA)
```

Arguments

mSetObj	Input name of the created mSet Object
---------	---------------------------------------

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

PerformGeneAnnotation	<i>Perform gene annotation</i>
-----------------------	--------------------------------

Description

Perform gene annotation

Usage

```
PerformGeneAnnotation()
```

PerformIndNormalization

Perform normalization for individually-uploaded datasets for meta-analysis

Description

This function performs normalization of individually-uploaded datasets prior to meta-analysis.

Usage

```
PerformIndNormalization(mSetObj = NA, dataName, norm.opt, auto.opt)
```

Arguments

mSetObj	Input name of the created mSet Object
dataName	Input the name of the individual dataset for normalization.
norm.opt	Performs log2 normalization "log", or no normalization "none".
auto.opt	Performs auto-scaling of data (1), or no (0).

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

PerformIntegCmpdMapping

Perform compound mapping for integrative analysis methods

Description

Perform compound mapping

Usage

```
PerformIntegCmpdMapping(mSetObj = NA, cmpdIDs, org, idType)
```

Arguments

mSetObj	Input name of the created mSet Object
cmpdIDs	Input the list of compound IDs
org	Input the organism code
idType	Input the ID type

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

`PerformIntegGeneMapping`*Perform integrated gene mapping*

Description

Used for the pathinteg module

Usage

```
PerformIntegGeneMapping(mSetObj = NA, geneIDs, org, idType)
```

Arguments

<code>mSetObj</code>	Input name of the created mSet Object
<code>geneIDs</code>	Input the list of gene IDs
<code>org</code>	Input the organism code
<code>idType</code>	Input the ID type

`PerformIntegPathwayAnalysis`*Perform integrative pathway analysis*

Description

used for integrative analysis as well as general pathways analysis for meta-analysis results

Usage

```
PerformIntegPathwayAnalysis(mSetObj, topo="dc", enrich="hyper", libOpt="integ")
```

Arguments

<code>mSetObj</code>	Input name of the created mSet Object
<code>topo</code>	Select the mode for topology analysis: Degree Centrality ("dc") measures the number of links that connect to a node (representing either a gene or metabolite) within a pathway; Closeness Centrality ("cc") measures the overall distance from a given node to all other nodes in a pathway; Betweenness Centrality ("bc") measures the number of shortest paths from all nodes to all the others that pass through a given node within a pathway.
<code>enrich</code>	Method to perform over-representation analysis (ORA) based on either hypergeometrics analysis ("hyper") or Fisher's exact method ("fisher").

libOpt Select the different modes of pathways, either the gene-metabolite mode ("integ") which allows for joint-analysis and visualization of both significant genes and metabolites or the gene-centric ("genetic") and metabolite-centric mode ("metab") which allows users to identify enriched pathways driven by significant genes or metabolites, respectively.

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

PerformKOEnrichAnalysis_KO01100

Performs KO enrichment analysis based on the KO01100 map

Description

This function performs KO enrichment analysis based on the KO01100 map and saves the .JSON file

Usage

PerformKOEnrichAnalysis_KO01100(mSetObj = NA, category, file.nm)

Arguments

mSetObj	Input name of the created mSet Object
category	Input the option to perform enrichment analysis, "pathway"
file.nm	Input name of file to save

Author(s)

Othman Soufan, Jeff Xia <jeff.xia@mcgill.ca>, othman.soufan@mcgill.ca McGill University, Canada License: GNU GPL (>= 2)

PerformKOEnrichAnalysis_List

Utility function for PerformKOEnrichAnalysis_KO01100

Description

Please note: only return hits in map KO01100

Usage

PerformKOEnrichAnalysis_List(file.nm)

Arguments

file.nm Input the file name

PerformLimmaDE	<i>Perform differential expression analysis using Limma for individually-uploaded data.</i>
----------------	---

Description

This function performs DE analysis of individually-uploaded data prior to meta-analysis.

Usage

```
PerformLimmaDE(mSetObj = NA, dataName, p.lvl = 0.1, fc.lvl = 0)
```

Arguments

mSetObj Input name of the created mSet Object
 dataName Input the name of the individual dataset for normalization.
 p.lvl Numeric, input the p-value (FDR) cutoff.
 fc.lvl Numeric, input the fold-change (FC) cutoff.

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

PerformMapping	<i>Utility function for PrepareQueryJson geneIDs is text one string, need to make to vector</i>
----------------	---

Description

Utility function for PrepareQueryJson geneIDs is text one string, need to make to vector

Usage

```
PerformMapping(inputIDs, type)
```

Arguments

inputIDs Input list of IDs
 type Input the type of IDs

performMB

Timecourse analysis

Description

Adapted from the timecourse package by Yu Chuan Tai This method is only applicable for time-series, not for general case two/multiple factor analysis

Usage

```
performMB(mSetObj, topPerc)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
topPerc	select the cut-off, default is 10

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (≥ 2)

PerformMetaMerge

Meta-Analysis Method: Direct merging of datasets

Description

This function is one of three methods to perform meta-analysis. Direct merging of individual data into a mega-dataset results in an analysis of that mega-dataset as if the individual data were derived from the same experiment. This method thereby ignores any inherent bias and heterogeneity between the different data. Because of this, there exists several confounders such as different experimental protocols, technical platforms, and raw data processing procedures that can mask true underlying differences. It is therefore highly suggested that this approach be used only when individual data are very similar (i.e. from the same lab, same platform, without batch effects)."

Usage

```
PerformMetaMerge(mSetObj = NA, BHth = 0.05)
```

Arguments

mSetObj	Input name of the created mSet Object.
BHth	Numeric input to set the significance level. By default it is 0.05.

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (≥ 2)

PerformMultiMatch	<i>Perform multiple name matches</i>
-------------------	--------------------------------------

Description

Given a query, perform compound matching

Usage

```
PerformMultiMatch(mSetObj = NA, q)
```

Arguments

mSetObj	Input name of the created mSet Object
q	Input the query

PerformMummichog	<i>Main function to perform mummichog</i>
------------------	---

Description

This is the main function that performs the mummichog analysis.

Usage

```
PerformMummichog(mSetObj=NA, enrichOpt, pvalOpt, permNum = 100)
```

Arguments

mSetObj	Input the name of the created mSetObj object
enrichOpt	Input the method to perform enrichment analysis
pvalOpt	Input the method to calculate p-values
permNum	Numeric, the number of permutations to perform

Author(s)

Jasmine Chong, Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL
(>= 2)

`PerformMummichogPermutations`*Perform permutations and calculates p-values*

Description

This function performs permutations to create a background distribution of p-values for pathway enrichment analysis.

Usage

```
PerformMummichogPermutations(mSetObj=NA, permNum)
```

Arguments

<code>mSetObj</code>	Input the name of the created mSetObj.
<code>permNum</code>	Numeric, the number of permutations to perform

Author(s)

Jasmine Chong, Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

`PerformPowerProfiling` *Perform power profiling*

Description

Perform power profiling of data

Usage

```
PerformPowerProfiling(mSetObj=NA, fdr.lvl, smplSize)
```

Arguments

<code>mSetObj</code>	Input the name of the created mSetObj (see InitDataObjects)
<code>fdr.lvl</code>	Specify the false-discovery rate level.
<code>smplSize</code>	Specify the maximum sample size, the number must be between 60-1000.

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

`PerformPvalCombination`*Meta-Analysis Method: Combining p-values*

Description

This function is one of three methods to perform meta-analysis. Here, p-values are combined using either the Fisher's method or the Stouffer's method.

Usage

```
PerformPvalCombination(mSetObj = NA, method = "stouffer", BHth = 0.05)
```

Arguments

<code>mSetObj</code>	Input name of the created mSet Object.
<code>method</code>	Method of p-value combination. By default it is "stouffer", else it is "fisher".
<code>BHth</code>	Numeric input to set the significance level. By default it is 0.05.

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

`PerformVoteCounting`*Meta-Analysis Method: Vote Counting*

Description

This function is one of three methods to perform meta-analysis. Here, significant features are selected based on a selected criteria (i.e. an adjusted p-value <0.05 and the same direction of FC) for each dataset. The votes are then calculated for each feature by counting the total of number of times a feature is significant across all included datasets. However, this method is statistically inefficient and should be considered the last resort in situations where other methods to perform meta-analysis cannot be applied.

Usage

```
PerformVoteCounting(mSetObj = NA, BHth = 0.05, minVote)
```

Arguments

<code>mSetObj</code>	Input name of the created mSet Object.
<code>BHth</code>	Numeric input to set the significance level. By default it is 0.05.
<code>minVote</code>	Numeric input to set the minimum vote-count.

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

Plot.Permutation	<i>Plot results of permutation tests</i>
------------------	--

Description

Plot results of permutation tests

Usage

```
Plot.Permutation(mSetObj=NA, imgName, format="png", dpi=72)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
imgName	Input a name for the plot
format	elect the image format, "png", of "pdf".
dpi	Input the dpi. If the image format is "pdf", users need not define the dpi. For "png" images, the default dpi is 72. It is suggested that for high-resolution images, select a dpi of 300.

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

PlotAccuracy	<i>Plot classification performance using different features for Multi-Biomarker</i>
--------------	---

Description

Plot of the accuracy of classification with an increasing number of features.

Usage

```
PlotAccuracy(mSetObj=NA, imgName, format="png", dpi=72)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
imgName	Input a name for the plot
format	Select the image format, "png", or "pdf".
dpi	Input the dpi. If the image format is "pdf", users need not define the dpi. For "png" images, the default dpi is 72. It is suggested that for high-resolution images, select a dpi of 300.

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

PlotANOVA

Plot ANOVA

Description

Plot ANOVA

Usage

```
PlotANOVA(mSetObj=NA, imgName, format="png", dpi=72, width=NA)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
imgName	Input a name for the plot
format	Select the image format, "png", or "pdf".
dpi	Input the dpi. If the image format is "pdf", users need not define the dpi. For "png" images, the default dpi is 72. It is suggested that for high-resolution images, select a dpi of 300.
width	Input the width, there are 2 default widths, the first, width = NULL, is 10.5. The second default is width = 0, where the width is 7.2. Otherwise users can input their own width.

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

PlotANOVA2

Plot Venn diagram of ANOVA results

Description

Plot Venn diagram of ANOVA results

Usage

```
PlotANOVA2(mSetObj, imgName, format="png", dpi=72, width=NA)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
imgName	Input a name for the plot
format	Select the image format, "png", or "pdf".
dpi	Input the dpi. If the image format is "pdf", users need not define the dpi. For "png" images, the default dpi is 72. It is suggested that for high-resolution images, select a dpi of 300.
width	Input the width, there are 2 default widths, the first, width = NULL, is 10.5. The second default is width = 0, where the width is 7.2. Otherwise users can input their own width.

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

PlotASCA.Permutation

Plot ASCA permutation

Description

Plot plsda classification performance using different components

Usage

```
PlotASCA.Permutation(mSetObj=NA, imgName, format="png", dpi=72, width=NA)
```


Arguments

mSetObj	Input name of the created mSet Object
imgName	Input a name for the plot
format	Select the image format, "png", or "pdf".
dpi	Input the dpi. If the image format is "pdf", users need not define the dpi. For "png" images, the default dpi is 72. It is suggested that for high-resolution images, select a dpi of 300.
width	Input the width, there are 2 default widths, the first, width = NULL, is 10.5. The second default is width = 0, where the width is 7.2. Otherwise users can input their own width.

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

PlotAscaImpVar	<i>Plot the important variables for each factor</i>
----------------	---

Description

Plot the important variables for each factor

Usage

```
PlotAscaImpVar(mSetObj=NA, imgName, format, dpi, width=NA, type)
```

Arguments

mSetObj	Input name of the created mSet Object
imgName	Input a name for the plot
format	Select the image format, "png", or "pdf".
dpi	Input the dpi. If the image format is "pdf", users need not define the dpi. For "png" images, the default dpi is 72. It is suggested that for high-resolution images, select a dpi of 300.
width	Input the width, there are 2 default widths, the first, width = NULL, is 10.5. The second default is width = 0, where the width is 7.2. Otherwise users can input their own width.
type	select model a, b, or ab

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

PlotASCAModel	<i>Plot score plots of each ASCA model for component 1 against time</i>
---------------	---

Description

Plot score plots of each ASCA model for component 1 against time

Usage

```
PlotASCAModel(mSetObj=NA, imgName, format="png", dpi=72, width=NA, type, colorBW=FALSE)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
imgName	Input a name for the ASCA score plot
format	Select the image format, "png", or "pdf".
dpi	Input the dpi. If the image format is "pdf", users need not define the dpi. For "png" images, the default dpi is 72. It is suggested that for high-resolution images, select a dpi of 300
width	Input the width, there are 2 default widths, the first, width = NULL, is 10.5. The second default is width = 0, where the width is 7.2. Otherwise users can input their own width.
type	select model a or b
colorBW	Logical, use black/white coloring (T) or not (F)

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

PlotCmpdSummary	<i>Plot compound summary change to use dataSet\$procr instead of dataSet\$orig in case of too many NAs</i>
-----------------	--

Description

Plot compound summary change to use dataSet\$procr instead of dataSet\$orig in case of too many NAs

Usage

```
PlotCmpdSummary(mSetObj = NA, cmpdNm, format = "png", dpi = 72,
  width = NA)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
cmpdNm	Input the name of the compound to plot
format	Input the format of the image to create
dpi	Input the dpi of the image to create
width	Input the width of the image to create

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

PlotCmpdView	<i>Plot Compound View</i>
--------------	---------------------------

Description

Plots a bar-graph of selected compound over groups

Usage

```
PlotCmpdView(mSetObj=NA, cmpdNm, format="png", dpi=72, width=NA)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
cmpdNm	Input a name for the compound
format	Select the image format, "png", or "pdf".
dpi	Input the dpi. If the image format is "pdf", users need not define the dpi. For "png" images, the default dpi is 72. It is suggested that for high-resolution images, select a dpi of 300.
width	Input the width, there are 2 default widths, the first, width = NULL, is 10.5. The second default is width = 0, where the width is 7.2. Otherwise users can input their own width.

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

PlotConcRange	<i>Plot the compound concentration data compared to the reference concentration range</i>
---------------	---

Description

Plot the compound concentration data compared to the reference concentration range

Usage

```
PlotConcRange(mSetObj, nm, format="png", dpi=72, width=NA)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
nm	of the input compound
format	Select the image format, "png", or "pdf".
dpi	Input the dpi. If the image format is "pdf", users need not define the dpi. For "png" images, the default dpi is 72. It is suggested that for high-resolution images, select a dpi of 300.
width	Input the width, there are 2 default widths, the first, width = NULL, is 10.5. The second default is width = 0, where the width is 7.2. Otherwise users can input their own width.

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

PlotCorr	<i>Pattern hunter, correlation plot</i>
----------	---

Description

Plot correlation

Usage

```
PlotCorr(mSetObj = NA, imgName, format = "png", dpi = 72, width = NA)
```

Arguments

mSetObj	Input name of the created mSet Object
imgName	Input a name for the plot
format	Select the image format, "png", or "pdf".
dpi	Input the dpi. If the image format is "pdf", users need not define the dpi. For "png" images, the default dpi is 72. It is suggested that for high-resolution images, select a dpi of 300.
width	Input the width, there are 2 default widths, the first, width = NULL, is 10.5. The second default is width = 0, where the width is 7.2. Otherwise users can input their own width.

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

PlotCorrHeatMap	<i>Pattern hunter, corr heatmap</i>
-----------------	-------------------------------------

Description

Plot correlation heatmap

Usage

```
PlotCorrHeatMap(mSetObj = NA, imgName, format = "png", dpi = 72,
  width = NA, target, cor.method, colors, viewOpt, fix.col, no.clst, top,
  topNum)
```

Arguments

mSetObj	Input name of the created mSet Object.
imgName	Input the name of the image to create
format	Select the image format, "png", or "pdf".
dpi	Input the dpi. If the image format is "pdf", users need not define the dpi. For "png" images, the default dpi is 72. It is suggested that for high-resolution images, select a dpi of 300.
width	Input the width, there are 2 default widths, the first, width = NULL, is 10.5. The second default is width = 0, where the width is 7.2. Otherwise users can input their own width.
target	Input "row" to select features, or "col" to select samples.
cor.method	Indicate the correlation method, 'pearson', 'spearman', or 'kendall'.
colors	Indicate the colors for the heatmap, "bwm" for default, "gbr" for red/green, "heat" for heat colors, "topo" for topo colors, and "gray" for gray scale.

viewOpt	Indicate "overview" to get an overview of the heatmap, and "detail" to get a detailed view of the heatmap.
fix.col	Logical, fix colors (TRUE) or not (FALSE).
no.clst	Logical, indicate if the correlations should be clustered (TRUE) or not (FALSE).
top	View top
topNum	Numeric, view top McGill University, Canada License: GNU GPL (≥ 2)

Author(s)

Jeff Xia<jeff.xia@mcgill.ca>

PlotDetailROC	<i>Plot detailed ROC</i>
---------------	--------------------------

Description

Plot detailed ROC

Usage

```
PlotDetailROC(mSetObj = NA, imgName, thresh, sp, se, dpi = 72,
  format = "png")
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
imgName	Input a name for the plot
thresh	Input the threshold
sp	Specificity
se	Sensitivity
dpi	Input the dpi. If the image format is "pdf", users need not define the dpi. For "png" images, the default dpi is 72. It is suggested that for high-resolution images, select a dpi of 300.
format	Select the image format, "png", or "pdf".

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (≥ 2)

PlotEBAM.A0	<i>For EBAM analysis</i>
-------------	--------------------------

Description

plot ebam a0 plot also return the analSet\$ebam.a0 object so that the suggested a0 can be obtained

Usage

```
PlotEBAM.A0(mSetObj=NA, imgName, format="png", dpi=72, width=NA)
```

Arguments

mSetObj	Input name of the created mSet Object
imgName	Input a name for the plot
format	Select the image format, "png", or "pdf".
dpi	Input the dpi. If the image format is "pdf", users need not define the dpi. For "png" images, the default dpi is 72. It is suggested that for high-resolution images, select a dpi of 300.
width	Input the width, there are 2 default widths, the first, width = NULL, is 10.5. The second default is width = 0, where the width is 7.2. Otherwise users can input their own width.

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

PlotEBAM.Cmpd	<i>Plot EBAM</i>
---------------	------------------

Description

Plot EBAM

Usage

```
PlotEBAM.Cmpd(mSetObj=NA, imgName, format, dpi, width)
```

Arguments

mSetObj	Input name of the created mSet Object
imgName	Input a name for the plot
format	Select the image format, "png", or "pdf".
dpi	Input the dpi. If the image format is "pdf", users need not define the dpi. For "png" images, the default dpi is 72. It is suggested that for high-resolution images, select a dpi of 300.
width	Input the width, there are 2 default widths, the first, width = NULL, is 10.5. The second default is width = 0, where the width is 7.2. Otherwise users can input their own width.

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

PlotEnrichNet.Overview

Barplot height is enrichment fold change

Description

Used in higher functions, the color is based on p values

Usage

```
PlotEnrichNet.Overview(folds, pvals, layoutOpt = layout.fruchterman.reingold)
```

Arguments

folds	Input fold-change for bar plot
pvals	Input p-values for bar plot
layoutOpt	Input the layout option, default is set to layout.fruchterman.reingold

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

PlotFC	<i>Plot fold change</i>
--------	-------------------------

Description

Plot fold change analysis

Usage

```
PlotFC(mSetObj=NA, imgName, format="png", dpi=72, width=NA)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
imgName	Input a name for the plot
format	Select the image format, "png", or "pdf".
dpi	Input the dpi. If the image format is "pdf", users need not define the dpi. For "png" images, the default dpi is 72. It is suggested that for high-resolution images, select a dpi of 300.
width	Input the width, there are 2 default widths, the first, width = NULL, is 10.5. The second default is width = 0, where the width is 7.2. Otherwise users can input their own width.

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

PlotHCTree	<i>Plot Dendrogram</i>
------------	------------------------

Description

Dendrogram

Usage

```
PlotHCTree(mSetObj = NA, imgName, format = "png", dpi = 72, width = NA,
  smplDist, clstDist)
```

Arguments

mSetObj	Input name of the created mSet Object
imgName	Input a name for the plot
format	Select the image format, "png", or "pdf".
dpi	Input the dpi. If the image format is "pdf", users need not define the dpi. For "png" images, the default dpi is 72. It is suggested that for high-resolution images, select a dpi of 300.
width	Input the width, there are 2 default widths, the first, width = NULL, is 10.5. The second default is width = 0, where the width is 7.2. Otherwise users can input their own width.
smplDist	Method to calculate sample distance
clstDist	Method to calculate clustering distance

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

PlotHeatMap

Create Heat Map Plot

Description

Plot a heatmap based on results from t-tests/ANOVA, VIP or randomforest

Usage

```
PlotHeatMap(mSetObj = NA, imgName, format = "png", dpi = 72, width = NA,
  dataOpt, scaleOpt, smplDist, clstDist, palette, viewOpt = "detail",
  rowV = T, colV = T, var.inx = NA, border = T, grp.ave = F)
```

Arguments

mSetObj	Input name of the created mSet Object
imgName	Input a name for the plot
format	Select the image format, "png", or "pdf".
dpi	Input the dpi. If the image format is "pdf", users need not define the dpi. For "png" images, the default dpi is 72. It is suggested that for high-resolution images, select a dpi of 300.
width	Input the width, there are 2 default widths, the first, width = NULL, is 10.5. The second default is width = 0, where the width is 7.2. Otherwise users can input their own width.
dataOpt	Set data options
scaleOpt	Set the image scale

smplDist	Input the sample distance method
clstDist	Input the clustering distance method
palette	Input color palette choice
viewOpt	Set heatmap options, default is set to "detail"
rowV	Default is set to T
colV	Default is set to T
var.inx	Default is set to NA
border	Indicate whether or not to show cell-borders, default is set to T
grp.ave	Logical, default is set to F

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

PlotHeatMap2	<i>Plot heatmap visualization for time-series data</i>
--------------	--

Description

Plot heatmap visualization for time-series data

Usage

```
PlotHeatMap2(mSetObj=NA, imgName, format="png", dpi=72, width=NA, smplDist="pearson", clstDist="average")
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
imgName	Input a name for the plot
format	Select the image format, "png", or "pdf".
dpi	Input the dpi. If the image format is "pdf", users need not define the dpi. For "png" images, the default dpi is 72. It is suggested that for high-resolution images, select a dpi of 300.
width	Input the width, there are 2 default widths, the first, width = NULL, is 10.5. The second default is width = 0, where the width is 7.2. Otherwise users can input their own width.
smplDist	Select distance measure: euclidean, pearson, or minkowski
clstDist	Select clustering algorithm: ward, average, complete, single
colors	Select heatmap colors: bwm, gray
viewOpt	Select overview or detailed view: overview or detail
hiRes	Select high-resolution or not: logical, default set to F
sortInx	Sort by index
useSigFeature	Use significant features only: F or T (default false)
drawBorder	Show cell borders: F or T (default F)

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

PlotImpVar	<i>Plot PLS important variables,</i>
------------	--------------------------------------

Description

Plot PLS important variables, BHan: added bgcolor parameter for B/W color

Usage

```
PlotImpVar(mSetObj = NA, imp.vec, xlbl, feat.num = 15, color.BW = FALSE)
```

Arguments

mSetObj	Input name of the created mSet Object
imp.vec	Input the vector of important variables
xlabel	Input the x-label
feat.num	Numeric, set the feature numbers, default is set to 15
color.BW	Use black-white for plot (T) or colors (F)

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

PlotImpVars	<i>Plot selected compounds by their percentage frequency</i>
-------------	--

Description

Plot the important variables of single biomarker model ranked by order of importance

Usage

```
PlotImpVars(mSetObj=NA, imgName, format="png", dpi=72, mdl.inx, measure = "freq", feat.num = 15)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
imgName	Input a name for the plot
format	elect the image format, "png", of "pdf".
dpi	Input the dpi. If the image format is "pdf", users need not define the dpi. For "png" images, the default dpi is 72. It is suggested that for high-resolution images, select a dpi of 300.
mdl.inx	Model index, -1 selects the model with the best AUC, input 1-6 to view the important features of one of the top six models
measure	Choose to rank features by the frequency of being selected "freq", or the mean importance measure "mean"
feat.num	Input the number of features to include in the plot, by default it is 15.

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

PlotinmexGraph	<i>Plot an igrph object and return the node information (position and labels)</i>
----------------	---

Description

Plot an igrph object and return the node information (position and labels) Used in a higher function

Usage

```
PlotinmexGraph(mSetObj, path.id, g, width, height, bg.color = NULL,
  line.color = NULL)
```

Arguments

mSetObj	Input name of the created mSet Object
path.id	Input the pathway id
g	Input the graph
width	Input the width, there are 2 default widths, the first, width = NULL, is 10.5. The second default is width = 0, where the width is 7.2. Otherwise users can input their own width.
height	Input the height of the graph to create
bg.color	Set the background color, default is set to NULL
line.color	Set the line color, default is set to NULL

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

PlotInmexPath	<i>Plot integrated methods pathway analysis</i>
---------------	---

Description

Only update the background info for matched node

Usage

```
PlotInmexPath(mSetObj=NA, path.id, width, height)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
path.id	Input the ID of the pathway to plot.
width	Input the width, there are 2 default widths, the first, width = NULL, is 10.5. The second default is width = 0, where the width is 7.2. Otherwise users can input their own width.
height	Input the height of the image to create.

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

PlotInteraction	<i>Plot ASCA interaction plots</i>
-----------------	------------------------------------

Description

Plot ASCA interaction plots

Usage

```
PlotInteraction(mSetObj=NA, imgName, format="png", dpi=72, colorBW=FALSE, width=NA)
```

Arguments

mSetObj	Input name of the created mSet Object
imgName	Input a name for the plot
format	Select the image format, "png", or "pdf".
dpi	Input the dpi. If the image format is "pdf", users need not define the dpi. For "png" images, the default dpi is 72. It is suggested that for high-resolution images, select a dpi of 300.
colorBW	Logical, use black and white (TRUE) or colors (FALSE)
width	Input the width, there are 2 default widths, the first, width = NULL, is 10.5. The second default is width = 0, where the width is 7.2. Otherwise users can input their own width.

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

PlotKEGGPath	<i>Plot KEGG pathway</i>
--------------	--------------------------

Description

Orthogonal PLS-DA (from ropls)

Usage

```
PlotKEGGPath(mSetObj = NA, pathName, format = "png", width = NA,
             dpi = 72)
```

Arguments

mSetObj	Input name of the created mSet Object
pathName	Input the name of the selected KEGG pathway
format	Select the image format, "png", or "pdf".
width	Input the width, there are 2 default widths, the first, width = NULL, is 10.5. The second default is width = 0, where the width is 7.2. Otherwise users can input their own width.
dpi	Input the dpi. If the image format is "pdf", users need not define the dpi. For "png" images, the default dpi is 72. It is suggested that for high-resolution images, select a dpi of 300.

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

PlotKmeans	<i>Plot K-means analysis</i>
------------	------------------------------

Description

Plot K-means analysis

Usage

```
PlotKmeans(mSetObj = NA, imgName, format = "png", dpi = 72, width = NA)
```

Arguments

mSetObj	Input name of the created mSet Object
imgName	Input a name for the plot
format	Select the image format, "png", or "pdf".
dpi	Input the dpi. If the image format is "pdf", users need not define the dpi. For "png" images, the default dpi is 72. It is suggested that for high-resolution images, select a dpi of 300.
width	Input the width, there are 2 default widths, the first, width = NULL, is 10.5. The second default is width = 0, where the width is 7.2. Otherwise users can input their own width.

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

PlotLoadingCmpd

Plot loading compounds

Description

Plot loading compounds

Usage

```
PlotLoadingCmpd(mSetObj = NA, cmpdNm, format = "png", dpi = 72,  
  width = NA)
```

Arguments

mSetObj	Input name of the created mSet Object
cmpdNm	Input the name of the selected compound
format	Select the image format, "png", or "pdf".
dpi	Input the dpi. If the image format is "pdf", users need not define the dpi. For "png" images, the default dpi is 72. It is suggested that for high-resolution images, select a dpi of 300.
width	Input the width, there are 2 default widths, the first, width = NULL, is 10.5. The second default is width = 0, where the width is 7.2. Otherwise users can input their own width.

PlotMBTimeProfile	<i>Plot MB Time Profile</i>
-------------------	-----------------------------

Description

Plot MB Time Profile

Usage

```
PlotMBTimeProfile(mSetObj = NA, cmpdNm, format = "png", dpi = 72,  
width = NA)
```

Arguments

mSetObj	Input name of the created mSet Object
cmpdNm	Input the name of the compound
format	Select the image format, "png", or "pdf".
dpi	Input the dpi. If the image format is "pdf", users need not define the dpi. For "png" images, the default dpi is 72. It is suggested that for high-resolution images, select a dpi of 300.
width	Input the width, there are 2 default widths, the first, width = NULL, is 10.5. The second default is width = 0, where the width is 7.2. Otherwise users can input their own width.

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

PlotMetaVenn	<i>Meta-Analysis: Plot Venn Diagram</i>
--------------	---

Description

This function plots a venn diagram of the individual studies.

Usage

```
PlotMetaVenn(mSetObj = NA, imgNM = NA)
```

Arguments

mSetObj	Input name of the created mSet Object.
imgNM	Input the name of the created Venn Diagram

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

PlotMetPath	<i>Plot metabolome pathway</i>
-------------	--------------------------------

Description

Orthogonal PLS-DA (from ropls)

Usage

```
PlotMetPath(mSetObj = NA, pathName, width, height)
```

Arguments

mSetObj	Input name of the created mSet Object
pathName	Input the name of the selected pathway
width	Input the width, there are 2 default widths, the first, width = NULL, is 10.5. The second default is width = 0, where the width is 7.2. Otherwise users can input their own width.
height	Input the height of the created plot.

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

PlotModelScree	<i>Plot scree plots for each model in ASCA</i>
----------------	--

Description

Plot scree plots for each model in ASCA

Usage

```
PlotModelScree(mSetObj, imgName, format="png", dpi=72, width=NA)
```

Arguments

mSetObj	Input name of the created mSet Object.
imgName	Input a name for the plot
format	Select the image format, "png", or "pdf".
dpi	Input the dpi. If the image format is "pdf", users need not define the dpi. For "png" images, the default dpi is 72. It is suggested that for high-resolution images, select a dpi of 300.
width	Input the width, there are 2 default widths, the first, width = NULL, is 10.5. The second default is width = 0, where the width is 7.2. Otherwise users can input their own width.

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

PlotMS.RT

Plot retention time corrected spectra

Description

Plot the retention time corrected spectra

Usage

```
PlotMS.RT(mSetObj = NA, imgName, format = "png", dpi = 72, width = NA)
```

Arguments

mSetObj	Input name of the created mSet Object
imgName	Input the name for the created plot
format	Select the image format, "png", or "pdf".
dpi	Input the dpi. If the image format is "pdf", users need not define the dpi. For "png" images, the default dpi is 72. It is suggested that for high-resolution images, select a dpi of 300.
width	Input the width, there are 2 default widths, the first, width = NULL, is 10.5. The second default is width = 0, where the width is 7.2. Otherwise users can input their own width.

PlotMSEA.Overview

Plot MSEA overview

Description

Barplot height is enrichment fold change color is based on p values, used in higher functions

Usage

```
PlotMSEA.Overview(folds, pvals)
```

Arguments

folds	Input the fold-change values
pvals	Input the p-values

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

PlotNormSummary	<i>Two plot summary plot: Feature View of before and after normalization</i>
-----------------	--

Description

For each plot, the top is a box plot, bottom is a density plot

Usage

```
PlotNormSummary(mSetObj, imgName, format, dpi, width)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
imgName	Input a name for the plot
format	Select the image format, "png", or "pdf".
dpi	Input the dpi. If the image format is "pdf", users need not define the dpi. For "png" images, the default dpi is 72. It is suggested that for high-resolution images, select a dpi of 300.
width	Input the width, there are 2 default widths, the first, width = NULL, is 10.5. The second default is width = 0, where the width is 7.2. Otherwise users can input their own width.

Author(s)

Jeff Xia <jeff.xia@mcgill.ca>, Jasmine Chong McGill University, Canada

PlotOPLS.MDL	<i>Plot OPLS</i>
--------------	------------------

Description

Plot OPLS

Usage

```
PlotOPLS.MDL(mSetObj = NA, imgName, format = "png", dpi = 72,
  width = NA)
```

Arguments

mSetObj	Input name of the created mSet Object
imgName	Input a name for the plot
format	Select the image format, "png", or "pdf".
dpi	Input the dpi. If the image format is "pdf", users need not define the dpi. For "png" images, the default dpi is 72. It is suggested that for high-resolution images, select a dpi of 300.
width	Input the width, there are 2 default widths, the first, width = NULL, is 10.5. The second default is width = 0, where the width is 7.2. Otherwise users can input their own width.

PlotOPLS.Permutation *Perform OPLS-DA permutation*

Description

Orthogonal PLS-DA (from ropls) perform permutation, using training classification accuracy as indicator, for two or multi-groups

Usage

```
PlotOPLS.Permutation(mSetObj = NA, imgName, format = "png", dpi = 72,
  num = 100, width = NA)
```

Arguments

mSetObj	Input name of the created mSet Object
imgName	Input a name for the plot
format	Select the image format, "png", or "pdf".
dpi	Input the dpi. If the image format is "pdf", users need not define the dpi. For "png" images, the default dpi is 72. It is suggested that for high-resolution images, select a dpi of 300.
num	Input the number of permutations, default is set to 100.
width	Input the width, there are 2 default widths, the first, width = NULL, is 10.5. The second default is width = 0, where the width is 7.2. Otherwise users can input their own width.

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

PlotOPLS.Splot	<i>S-plot for OPLS-DA</i>
----------------	---------------------------

Description

Orthogonal PLS-DA (from roppls) S-plot for important features from OPLS-DA

Usage

```
PlotOPLS.Splot(mSetObj = NA, imgName, format = "png", dpi = 72,  
              width = NA, plotType)
```

Arguments

mSetObj	Input name of the created mSet Object
imgName	Input a name for the plot
format	Select the image format, "png", or "pdf".
dpi	Input the dpi. If the image format is "pdf", users need not define the dpi. For "png" images, the default dpi is 72. It is suggested that for high-resolution images, select a dpi of 300.
width	Input the width, there are 2 default widths, the first, width = NULL, is 10.5. The second default is width = 0, where the width is 7.2. Otherwise users can input their own width.
plotType	To create a plot of all compounds use "all", and to create a plot of custom compounds, use "custom"

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

PlotOPLS2DScore	<i>Create OPLS-DA score plot</i>
-----------------	----------------------------------

Description

Orthogonal PLS-DA (from roppls) score plot

Usage

```
PlotOPLS2DScore(mSetObj = NA, imgName, format = "png", dpi = 72,  
               width = NA, inx1, inx2, reg = 0.95, show = 1, grey.scale = 0)
```

Arguments

mSetObj	Input name of the created mSet Object
imgName	Input a name for the plot
format	Select the image format, "png", or "pdf".
dpi	Input the dpi. If the image format is "pdf", users need not define the dpi. For "png" images, the default dpi is 72. It is suggested that for high-resolution images, select a dpi of 300.
width	Input the width, there are 2 default widths, the first, width = NULL, is 10.5. The second default is width = 0, where the width is 7.2. Otherwise users can input their own width.
inx1	Numeric, indicate the number of the principal component for the x-axis of the loading plot.
inx2	Numeric, indicate the number of the principal component for the y-axis of the loading plot.
reg	Numeric
show	Show variable labels, 1 or 0
grey.scale	Numeric, indicate grey-scale, 0 for no, and 1 for yes

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

PlotORA

Plot over-representation analysis (ORA)

Description

Plot over-representation analysis (ORA)

Usage

```
PlotORA(mSetObj=NA, imgName, imgOpt, format="png", dpi=72, width=NA)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
imgName	Input a name for the plot
imgOpt	"net"
format	Select the image format, "png", or "pdf".
dpi	Input the dpi. If the image format is "pdf", users need not define the dpi. For "png" images, the default dpi is 72. It is suggested that for high-resolution images, select a dpi of 300.
width	Input the width, there are 2 default widths, the first, width = NULL, is 10.5. The second default is width = 0, where the width is 7.2. Otherwise users can input their own width.

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

PlotPathSummary

Plot a scatterplot (circle) overview of the matched pathways

Description

x axis is the pathway impact factor y axis is the p value (from ORA or globaltest) return the circle information

Usage

```
PlotPathSummary(mSetObj = NA, imgName, format = "png", dpi = 72,
  width = NA, x, y)
```

Arguments

mSetObj	Input name of the created mSet Object
imgName	Input a name for the plot
format	Select the image format, "png", or "pdf".
dpi	Input the dpi. If the image format is "pdf", users need not define the dpi. For "png" images, the default dpi is 72. It is suggested that for high-resolution images, select a dpi of 300.
width	Input the width, there are 2 default widths, the first, width = NULL, is 10.5.
x	Input the X
y	Input the Y

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

PlotPCA.overview

Scatter plot colored by different batches

Description

Scatter plot colored by different batches

Usage

```
PlotPCA.overview(mSetObj = NA, imgName, format = "png", dpi = 72,
  width = NA)
```


Arguments

mSetObj	Input name of the created mSet Object
imgName	Input a name for the plot
format	Select the image format, "png", or "pdf".
dpi	Input the dpi. If the image format is "pdf", users need not define the dpi. For "png" images, the default dpi is 72. It is suggested that for high-resolution images, select a dpi of 300.
width	Input the width, there are 2 default widths, the first, width = NULL, is 10.5. The second default is width = 0, where the width is 7.2. Otherwise users can input their own width.

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

PlotPCA2DScore	<i>Create 2D PCA score plot</i>
----------------	---------------------------------

Description

Rotate PCA analysis

Usage

```
PlotPCA2DScore(mSetObj=NA, imgName, format="png", dpi=72, width=NA, pcx, pcy, reg = 0.95, show=1, grey
```

Arguments

mSetObj	Input name of the created mSet Object
imgName	Input a name for the plot
format	Select the image format, "png", or "pdf".
dpi	Input the dpi. If the image format is "pdf", users need not define the dpi. For "png" images, the default dpi is 72. It is suggested that for high-resolution images, select a dpi of 300.
width	Input the width, there are 2 default widths, the first, width = NULL, is 10.5. The second default is width = 0, where the width is 7.2. Otherwise users can input their own width.
pcx	Specify the principal component on the x-axis
pcy	Specify the principal component on the y-axis
reg	Numeric, input a number between 0 and 1, 0.95 will display the 95 percent confidence regions, and 0 will not.
show	Display sample names, 1 = show names, 0 = do not show names.
grey.scale	Use grey-scale colors, 1 = grey-scale, 0 = not grey-scale.

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

PlotPCA3DScore	<i>Create 3D PCA score plot</i>
----------------	---------------------------------

Description

Rotate PCA analysis

Usage

```
PlotPCA3DScore(mSetObj=NA, imgName, format="json", inx1, inx2, inx3)
```

Arguments

mSetObj	Input name of the created mSet Object
imgName	Input a name for the plot
format	Select the image format, "png", or "pdf".
inx1	Numeric, indicate the number of the principal component for the x-axis of the loading plot.
inx2	Numeric, indicate the number of the principal component for the y-axis of the loading plot.
inx3	Numeric, indicate the number of the principal component for the z-axis of the loading plot.

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

PlotPCA3DScore_orig	<i>Create 3D PCA score plot</i>
---------------------	---------------------------------

Description

Rotate PCA analysis

Usage

```
PlotPCA3DScore_orig(mSetObj=NA, imgName, format="png", dpi=72, width=NA, inx1, inx2, inx3, angl)
```

Arguments

mSetObj	Input name of the created mSet Object
imgName	Input a name for the plot
format	Select the image format, "png", or "pdf".
dpi	Input the dpi. If the image format is "pdf", users need not define the dpi. For "png" images, the default dpi is 72. It is suggested that for high-resolution images, select a dpi of 300.
width	Input the width, there are 2 default widths, the first, width = NULL, is 10.5. The second default is width = 0, where the width is 7.2. Otherwise users can input their own width.
inx1	Numeric, indicate the number of the principal component for the x-axis of the loading plot.
inx2	Numeric, indicate the number of the principal component for the y-axis of the loading plot.
inx3	Numeric, indicate the number of the principal component for the z-axis of the loading plot.
ang1	Input the angle

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

PlotPCABiplot

Create PCA Biplot, set xpd = T to plot outside margin

Description

Rotate PCA analysis

Usage

```
PlotPCABiplot(mSetObj=NA, imgName, format="png", dpi=72, width=NA, inx1, inx2)
```

Arguments

mSetObj	Input name of the created mSet Object
imgName	Input a name for the plot
format	Select the image format, "png", or "pdf".
dpi	Input the dpi. If the image format is "pdf", users need not define the dpi. For "png" images, the default dpi is 72. It is suggested that for high-resolution images, select a dpi of 300.
width	Input the width, there are 2 default widths, the first, width = NULL, is 10.5. The second default is width = 0, where the width is 7.2. Otherwise users can input their own width.

inx1	Numeric, indicate the number of the principal component for the x-axis of the loading plot.
inx2	Numeric, indicate the number of the principal component for the y-axis of the loading plot.

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

PlotPCALoading	<i>Plot PCA loadings and also set up the matrix for display</i>
----------------	---

Description

Rotate PCA analysis

Usage

PlotPCALoading(mSetObj=NA, imgName, format="png", dpi=72, width=NA, inx1, inx2, plotType, lbl.feat=1)

Arguments

mSetObj	Input name of the created mSet Object
imgName	Input a name for the plot
format	Select the image format, "png", or "pdf".
dpi	Input the dpi. If the image format is "pdf", users need not define the dpi. For "png" images, the default dpi is 72. It is suggested that for high-resolution images, select a dpi of 300.
width	Input the width, there are 2 default widths, the first, width = NULL, is 10.5. The second default is width = 0, where the width is 7.2. Otherwise users can input their own width.
inx1	Numeric, indicate the number of the principal component for the x-axis of the loading plot.
inx2	Numeric, indicate the number of the principal component for the y-axis of the loading plot.
plotType	Indicate the plot type, "scatter" for a scatter plot, if blank it will create a barplot.
lbl.feat	Indicate 1 to show labeled features and 0 to not show labels.

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

PlotPCAPairSummary	<i>Plot PCA pair summary, format image in png, tiff, pdf, ps, svg</i>
--------------------	---

Description

Rotate PCA analysis

Usage

```
PlotPCAPairSummary(mSetObj=NA, imgName, format="png", dpi=72, width=NA, pc.num)
```

Arguments

mSetObj	Input name of the created mSet Object
imgName	Input a name for the plot
format	Select the image format, "png", or "pdf".
dpi	Input the dpi. If the image format is "pdf", users need not define the dpi. For "png" images, the default dpi is 72. It is suggested that for high-resolution images, select a dpi of 300.
width	Input the width, there are 2 default widths, the first, width = NULL, is 10.5. The second default is width = 0, where the width is 7.2. Otherwise users can input their own width.
pc.num	Numeric, input a number to indicate the number of principal components to display in the pairwise score plot.

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

PlotPCAScree	<i>Plot PCA scree plot</i>
--------------	----------------------------

Description

Rotate PCA analysis

Usage

```
PlotPCAScree(mSetObj=NA, imgName, format="png", dpi=72, width=NA, scree.num)
```

Arguments

mSetObj	Input name of the created mSet Object
imgName	Input a name for the plot
format	Select the image format, "png", or "pdf".
dpi	Input the dpi. If the image format is "pdf", users need not define the dpi. For "png" images, the default dpi is 72. It is suggested that for high-resolution images, select a dpi of 300.
width	Input the width, there are 2 default widths, the first, width = NULL, is 10.5. The second default is width = 0, where the width is 7.2. Otherwise users can input their own width.
scree.num	Numeric, input a number to indicate the number of principal components to display in the scree plot.

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

PlotPLS.Classification

Plot PLS-DA classification performance using different components

Description

Plot plsda classification performance using different components

Usage

```
PlotPLS.Classification(mSetObj = NA, imgName, format = "png", dpi = 72,
  width = NA)
```

Arguments

mSetObj	Input name of the created mSet Object
imgName	Input a name for the plot
format	Select the image format, "png", or "pdf".
dpi	Input the dpi. If the image format is "pdf", users need not define the dpi. For "png" images, the default dpi is 72. It is suggested that for high-resolution images, select a dpi of 300.
width	Input the width, there are 2 default widths, the first, width = NULL, is 10.5. The second default is width = 0, where the width is 7.2. Otherwise users can input their own width.

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

PlotPLS.Imp	<i>Plot PLS important features</i>
-------------	------------------------------------

Description

Plot PLS important features, BHan: added bgcolor parameter for B/W color

Usage

```
PlotPLS.Imp(mSetObj = NA, imgName, format = "png", dpi = 72, width = NA,
  type, feat.nm, feat.num, color.BW = FALSE)
```

Arguments

mSetObj	Input name of the created mSet Object
imgName	Input a name for the plot
format	Select the image format, "png", or "pdf".
dpi	Input the dpi. If the image format is "pdf", users need not define the dpi. For "png" images, the default dpi is 72. It is suggested that for high-resolution images, select a dpi of 300.
width	Input the width, there are 2 default widths, the first, width = NULL, is 10.5. The second default is width = 0, where the width is 7.2. Otherwise users can input their own width.
type	Indicate the type variables of importance to use, "vip" to use VIP scores, or "type" for coefficients
feat.nm	Feature name
feat.num	Feature numbers
color.BW	Logical, true to use black and white, or false to not

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

PlotPLS.Permutation	<i>Plot PLS-DA classification performance using different components, permutation</i>
---------------------	---

Description

Plot plsda classification performance using different components

Usage

```
PlotPLS.Permutation(mSetObj = NA, imgName, format = "png", dpi = 72,
  width = NA)
```

Arguments

mSetObj	Input name of the created mSet Object
imgName	Input a name for the plot
format	Select the image format, "png", or "pdf".
dpi	Input the dpi. If the image format is "pdf", users need not define the dpi. For "png" images, the default dpi is 72. It is suggested that for high-resolution images, select a dpi of 300.
width	Input the width, there are 2 default widths, the first, width = NULL, is 10.5. The second default is width = 0, where the width is 7.2. Otherwise users can input their own width.

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

PlotPLS2DScore	<i>Plot PLS score plot</i>
----------------	----------------------------

Description

Plot PLS score plot

Usage

```
PlotPLS2DScore(mSetObj = NA, imgName, format = "png", dpi = 72,
  width = NA, inx1, inx2, reg = 0.95, show = 1, grey.scale = 0,
  use.sparse = FALSE)
```

Arguments

mSetObj	Input name of the created mSet Object
imgName	Input a name for the plot
format	Select the image format, "png", or "pdf".
dpi	Input the dpi. If the image format is "pdf", users need not define the dpi. For "png" images, the default dpi is 72. It is suggested that for high-resolution images, select a dpi of 300.
width	Input the width, there are 2 default widths, the first, width = NULL, is 10.5. The second default is width = 0, where the width is 7.2. Otherwise users can input their own width.

inx1	Numeric, indicate the number of the principal component for the x-axis of the loading plot.
inx2	Numeric, indicate the number of the principal component for the y-axis of the loading plot.
reg	Numeric, default is 0.95
show	Show labels, 1 or 0
grey.scale	Numeric, use a grey scale (0) or not (1)
use.sparse	Logical, use a sparse algorithm (T) or not (F)

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

PlotPLS3DScore	<i>Plot PLS 3D score plot</i>
----------------	-------------------------------

Description

Plot PLS 3D score plot

Usage

```
PlotPLS3DScore(mSetObj = NA, imgName, format = "json", inx1, inx2, inx3)
```

Arguments

mSetObj	Input name of the created mSet Object
imgName	Input a name for the plot
format	Select the image format, "png", or "pdf".
inx1	Numeric, indicate the number of the principal component for the x-axis of the loading plot.
inx2	Numeric, indicate the number of the principal component for the y-axis of the loading plot.
inx3	Numeric, indicate the number of the principal component for the z-axis of the loading plot.

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

PlotPLS3DScore_orig	<i>Plot PLS 3D score plot</i>
---------------------	-------------------------------

Description

Plot PLS 3D score plot

Usage

```
PlotPLS3DScore_orig(mSetObj = NA, imgName, format = "png", dpi = 72,  
  width = NA, inx1, inx2, inx3, angl)
```

Arguments

mSetObj	Input name of the created mSet Object
imgName	Input a name for the plot
format	Select the image format, "png", or "pdf".
dpi	Input the dpi. If the image format is "pdf", users need not define the dpi. For "png" images, the default dpi is 72. It is suggested that for high-resolution images, select a dpi of 300.
width	Input the width, there are 2 default widths, the first, width = NULL, is 10.5. The second default is width = 0, where the width is 7.2. Otherwise users can input their own width.
inx1	Numeric, indicate the number of the principal component for the x-axis of the loading plot.
inx2	Numeric, indicate the number of the principal component for the y-axis of the loading plot.
inx3	Numeric, indicate the number of the principal component for the z-axis of the loading plot.
angl	Input the angle

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

PlotPLSLoading	<i>Plot PLS loading plot, also set the loading matrix for display</i>
----------------	---

Description

Plot PLS loading plot, also set the loading matrix for display

Usage

```
PlotPLSLoading(mSetObj = NA, imgName, format = "png", dpi = 72,  
               width = NA, inx1, inx2, plotType, lbl.feats = 1)
```

Arguments

mSetObj	Input name of the created mSet Object
imgName	Input a name for the plot
format	Select the image format, "png", or "pdf".
dpi	Input the dpi. If the image format is "pdf", users need not define the dpi. For "png" images, the default dpi is 72. It is suggested that for high-resolution images, select a dpi of 300.
width	Input the width, there are 2 default widths, the first, width = NULL, is 10.5. The second default is width = 0, where the width is 7.2. Otherwise users can input their own width.
inx1	Numeric, indicate the number of the principal component for the x-axis of the loading plot.
inx2	Numeric, indicate the number of the principal component for the y-axis of the loading plot.
plotType	Two options, "scatter" or "barplot"
lbl.feats	1 or 0

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

PlotPLSPairSummary	<i>Plot PLS pairwise summary</i>
--------------------	----------------------------------

Description

Plot PLS pairwise summary

Usage

```
PlotPLSPairSummary(mSetObj = NA, imgName, format = "png", dpi = 72,
  width = NA, pc.num)
```

Arguments

mSetObj	Input name of the created mSet Object
imgName	Input a name for the plot
format	Select the image format, "png", or "pdf".
dpi	Input the dpi. If the image format is "pdf", users need not define the dpi. For "png" images, the default dpi is 72. It is suggested that for high-resolution images, select a dpi of 300.
width	Input the width, there are 2 default widths, the first, width = NULL, is 10.5. The second default is width = 0, where the width is 7.2. Otherwise users can input their own width.
pc.num	Numeric, indicate the number of principal components

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

PlotPowerEffectSize	<i>Plot power effect size</i>
---------------------	-------------------------------

Description

Create power effect size plot

Usage

```
PlotPowerEffectSize(mSetObj, imgName, format, dpi, width)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
imgName	Specify the name to save the image as.
format	Specify the format of the image to save it as, either "png" or "pdf"
dpi	Specify the dots-per-inch (dpi). By default it is 72, for publications the recommended dpi is 300.
width	Specify the width of the image. NA specifies a width of 9, 0 specifies a width of 8, otherwise input a chosen width.

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

PlotPowerProfile	<i>Plot power profile</i>
------------------	---------------------------

Description

Plot power profile, specifying FDR level and sample size. It will return the image as well as the predicted power at various sample sizes.

Usage

```
PlotPowerProfile(mSetObj=NA, fdr.lvl, smplSize, imgName, format, dpi, width)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
fdr.lvl	Specify the false-discovery rate level.
smplSize	Specify the maximum sample size, the number must be between 60-1000.
imgName	Specify the name to save the image as.
format	Specify the format of the image to save it as, either "png" or "pdf".
dpi	Specify the dots-per-inch (dpi). By default it is 72, for publications the recommended dpi is 300.
width	Specify the width of the image. NA specifies a width of 9, 0 specifies a width of 7, otherwise input a chosen width.

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

PlotPowerStat	<i>Plot power statistics</i>
---------------	------------------------------

Description

Create plot for power statistics

Usage

```
PlotPowerStat(mSetObj, imgName, format="png", dpi=72, width=NA)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
imgName	Specify the name to save the image as.
format	Specify the format of the image to save it as, either "png" or "pdf"
dpi	Specify the dots-per-inch (dpi). By default it is 72, for publications the recommended dpi is 300.
width	Specify the width of the image. NA or 0 specifies a width of 10, otherwise input a chosen width.

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

PlotProbView	<i>Plot a summary view of the classification result</i>
--------------	---

Description

Plot of predicted class probabilities. On the x-axis is the probability, and the y-axis is the index of each predicted sample based on the probability. The samples are turned into separations at the x-axis. This plot can be created for multivariate ROC curve analysis using SVM, PLS, and RandomForest. Please note that sometimes, not all samples will be tested, instead they will be plotted at the 0.5 neutral line.

Usage

```
PlotProbView(mSetObj=NA, imgName, format="png", dpi=72, mdl.inx, show, showPred)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
imgName	Input a name for the plot
format	Select the image format, "png", of "pdf".
dpi	Input the dpi. If the image format is "pdf", users need not define the dpi. For "png" images, the default dpi is 72. It is suggested that for high-resolution images, select a dpi of 300.
mdl.inx	Model index, 0 means to compare all models, -1 means to use the best model, input 1-6 to plot a ROC curve for one of the top six models
show	1 or 0, if 1, label samples classified to the wrong groups
showPred	Show predicted samples

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

PlotProbViewTest	<i>Plot a summary view of the classification result for ROC Curve Based Model Creation and Evaluation</i>
------------------	---

Description

Plot of predicted class probabilities for ROC Curve Based Model Creation and Evaluation. On the x-axis is the probability, and the y-axis is the index of each predicted sample based on the probability. The samples are turned into separations at the x-axis. This plot can be created for multivariate ROC curve analysis using SVM, PLS, and RandomForest. Please note that sometimes, not all samples will be tested, instead they will be plotted at the 0.5 neutral line.

Usage

```
PlotProbViewTest(mSetObj=NA, imgName, format="png", dpi=72, mdl.inx, show, showPred)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
imgName	Input a name for the plot
format	Select the image format, "png", of "pdf".
dpi	Input the dpi. If the image format is "pdf", users need not define the dpi. For "png" images, the default dpi is 72. It is suggested that for high-resolution images, select a dpi of 300.
mdl.inx	Model index, 0 means to compare all models, -1 means to use the best model, input 1-6 to plot a ROC curve for one of the top six models
show	1 or 0, if 1, label samples classified to the wrong groups
showPred	Show predicted samples

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

plotProfile	<i>Plot the variable across time points (x)</i>
-------------	---

Description

Colored by experimental conditions, used in higher function

Usage

```
plotProfile(mSetObj = NA, varName)
```

Arguments

mSetObj	Input name of the created mSet Object
varName	Input the name of the variable

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

PlotQEA.MetSet	<i>View individual compounds related to a given metabolite set</i>
----------------	--

Description

View individual compounds related to a given metabolite set Functions for various plots for enrichment analysis

Usage

```
PlotQEA.MetSet(mSetObj=NA, setNM, format="png", dpi=72, width=NA)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
setNM	Input the name of the metabolite set
format	Select the image format, "png", or "pdf".
dpi	Input the dpi. If the image format is "pdf", users need not define the dpi. For "png" images, the default dpi is 72. It is suggested that for high-resolution images, select a dpi of 300.
width	Input the width, there are 2 default widths, the first, width = NULL, is 10.5. The second default is width = 0, where the width is 7.2. Otherwise users can input their own width.

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

PlotQEA.Overview

Plot QEA overview

Description

Plot QEA overview

Usage

```
PlotQEA.Overview(mSetObj=NA, imgName, imgOpt, format="png", dpi=72, width=NA)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
imgName	Input a name for the plot
imgOpt	"net"
format	Select the image format, "png", or "pdf".
dpi	Input the dpi. If the image format is "pdf", users need not define the dpi. For "png" images, the default dpi is 72. It is suggested that for high-resolution images, select a dpi of 300.
width	Input the width, there are 2 default widths, the first, width = NULL, is 10.5. The second default is width = 0, where the width is 7.2. Otherwise users can input their own width.

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

PlotRF.Classify

Plot Random Forest

Description

Random Forest plot

Usage

```
PlotRF.Classify(mSetObj, imgName, format, dpi, width)
```

Arguments

mSetObj	Input name of the created mSet Object
imgName	Input a name for the plot
format	Select the image format, "png", or "pdf".
dpi	Input the dpi. If the image format is "pdf", users need not define the dpi. For "png" images, the default dpi is 72. It is suggested that for high-resolution images, select a dpi of 300.
width	Input the width, there are 2 default widths, the first, width = NULL, is 10.5. The second default is width = 0, where the width is 7.2. Otherwise users can input their own width.

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

PlotRF.Outlier

Plot Random Forest outliers

Description

Random Forest plot of outliers

Usage

```
PlotRF.Outlier(mSetObj=NA, imgName, format="png", dpi=72, width=NA)
```

Arguments

mSetObj	Input name of the created mSet Object
imgName	Input a name for the plot
format	Select the image format, "png", or "pdf".
dpi	Input the dpi. If the image format is "pdf", users need not define the dpi. For "png" images, the default dpi is 72. It is suggested that for high-resolution images, select a dpi of 300.
width	Input the width, there are 2 default widths, the first, width = NULL, is 10.5. The second default is width = 0, where the width is 7.2. Otherwise users can input their own width.

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

PlotRF.VIP

Plot Random Forest variable importance

Description

Random Forest plot of variable importance ranked by MeanDecreaseAccuracy

Usage

```
PlotRF.VIP(mSetObj=NA, imgName, format, dpi, width)
```

Arguments

mSetObj	Input name of the created mSet Object
imgName	Input a name for the plot
format	Select the image format, "png", or "pdf".
dpi	Input the dpi. If the image format is "pdf", users need not define the dpi. For "png" images, the default dpi is 72. It is suggested that for high-resolution images, select a dpi of 300.
width	Input the width, there are 2 default widths, the first, width = NULL, is 10.5. The second default is width = 0, where the width is 7.2. Otherwise users can input their own width.

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

PlotROC.LRmodel

Plot ROC for the logistic regression model

Description

Plot ROC for the logistic regression model

Usage

```
PlotROC.LRmodel(mSetObj = NA, imgName, format = "png", dpi = 72,
  show.conf = FALSE, sp.bin = 0.01)
```

Arguments

mSetObj	Input name of the created mSet Object
imgName	Input a name for the plot
format	Select the image format, "png", or "pdf".
dpi	Input the dpi. If the image format is "pdf", users need not define the dpi. For "png" images, the default dpi is 72. It is suggested that for high-resolution images, select a dpi of 300.
show.conf	Logical, show confidence intervals
sp.bin	Numeric, default is set to 0.01.

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

PlotROCMulti

Plot ROC

Description

Pred and auroc are lists containing predictions and labels from different cross-validations

Usage

```
PlotROCMulti(mSetObj=NA, imgName, format="png", dpi=72, mdl.inx, avg.method, show.conf, show.holdout,
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
imgName	Input a name for the plot
format	Select the image format, "png", or "pdf".
dpi	Input the dpi. If the image format is "pdf", users need not define the dpi. For "png" images, the default dpi is 72. It is suggested that for high-resolution images, select a dpi of 300.
mdl.inx	Model index, 0 means to compare all models, input 1-6 to plot a ROC curve for one of the top six models
avg.method	Input the method to compute the average ROC curve, either "threshold", "vertical" or "horizontal"
show.conf	Logical, if 1, show confidence interval, if 0 do not show
show.holdout	Logical, if 1, show the ROC curve for hold-out validation, if 0 do not show
focus	"fpr"
cutoff	Input the threshold to limit the calculation of the ROC curve, the number must be between 0 and 1.

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

PlotROCTest	<i>Plot ROC for the ROC Curve Based Model Creation and Evaluation module</i>
-------------	--

Description

Plot the ROC curve of the biomarker model created using a user-selected subset of features. Pred and auroc are lists containing predictions and labels from different cross-validations.

Usage

```
PlotROCTest(mSetObj=NA, imgName, format="png", dpi=72, mdl.inx, avg.method, show.conf, show.holdout,
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
imgName	Input a name for the plot
format	Select the image format, "png", or "pdf".
dpi	Input the dpi. If the image format is "pdf", users need not define the dpi. For "png" images, the default dpi is 72. It is suggested that for high-resolution images, select a dpi of 300.
mdl.inx	Model index, 0 means to compare all models, input 1-6 to plot a ROC curve for one of the top six models
avg.method	Input the method to compute the average ROC curve, either "threshold", "vertical" or "horizontal"
show.conf	Logical, if 1, show confidence interval, if 0 do not show
show.holdout	Logical, if 1, show the ROC curve for hold-out validation, if 0 do not show
focus	"fpr"
cutoff	Input the threshold to limit the calculation of the ROC curve, the number must be between 0 and 1.

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

PlotRSVM.Classification

Recursive Support Vector Machine (R-SVM) plot

Description

Plot recursive SVM classification

Usage

```
PlotRSVM.Classification(mSetObj, imgName, format, dpi, width)
```

Arguments

mSetObj	Input name of the created mSet Object
imgName	Input a name for the plot
format	Select the image format, "png", or "pdf".
dpi	Input the dpi. If the image format is "pdf", users need not define the dpi. For "png" images, the default dpi is 72. It is suggested that for high-resolution images, select a dpi of 300.
width	Input the width, there are 2 default widths, the first, width = NULL, is 10.5. The second default is width = 0, where the width is 7.2. Otherwise users can input their own width.

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

PlotRSVM.Cmpd

Recursive Support Vector Machine (R-SVM) plot of important variables

Description

Plot recursive SVM variables of importance if too many, plot top 15

Usage

```
PlotRSVM.Cmpd(mSetObj=NA, imgName, format="png", dpi=72, width=NA)
```

Arguments

mSetObj	Input name of the created mSet Object
imgName	Input a name for the plot
format	Select the image format, "png", or "pdf".
dpi	Input the dpi. If the image format is "pdf", users need not define the dpi. For "png" images, the default dpi is 72. It is suggested that for high-resolution images, select a dpi of 300.
width	Input the width, there are 2 default widths, the first, width = NULL, is 10.5. The second default is width = 0, where the width is 7.2. Otherwise users can input their own width.

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

PlotSAM.Cmpd

Plot SAM

Description

Plot SAM with positive and negative metabolite sets

Usage

```
PlotSAM.Cmpd(mSetObj = NA, imgName, format = "png", dpi = 72,
  width = NA)
```

Arguments

mSetObj	Input name of the created mSet Object
imgName	Input a name for the plot
format	Select the image format, "png", or "pdf".
dpi	Input the dpi. If the image format is "pdf", users need not define the dpi. For "png" images, the default dpi is 72. It is suggested that for high-resolution images, select a dpi of 300.
width	Input the width, there are 2 default widths, the first, width = NULL, is 10.5. The second default is width = 0, where the width is 7.2. Otherwise users can input their own width.

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

PlotSAM.FDR

Plot SAM Delta Plot

Description

Plot SAM Delta Plot (FDR)

Usage

```
PlotSAM.FDR(mSetObj = NA, delta, imgName, format = "png", dpi = 72,
            width = NA)
```

Arguments

mSetObj	Input name of the created mSet Object
delta	Input the delta
imgName	Input a name for the plot
format	Select the image format, "png", or "pdf".
dpi	Input the dpi. If the image format is "pdf", users need not define the dpi. For "png" images, the default dpi is 72. It is suggested that for high-resolution images, select a dpi of 300.
width	Input the width, there are 2 default widths, the first, width = NULL, is 10.5. The second default is width = 0, where the width is 7.2. Otherwise users can input their own width.

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

PlotSampleNormSummary *Two plot summary plot: Sample View of before and after normalization*

Description

For each plot, the top is a density plot and the bottom is a box plot.

Usage

```
PlotSampleNormSummary(mSetObj=NA, imgName, format="png", dpi=72, width=NA)
```


Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
imgName	Input a name for the plot
format	Select the image format, "png", of "pdf".
dpi	Input the dpi. If the image format is "pdf", users need not define the dpi. For "png" images, the default dpi is 72. It is suggested that for high-resolution images, select a dpi of 300.
width	Input the width, there are 2 default widths, the first, width = NULL, is 10.5. The second default is width = 0, where the width is 7.2. Otherwise users can input their own width.

Author(s)

Jeff Xia <jeff.xia@mcgill.ca>, Jasmine Chong McGill University, Canada

PlotSelectedFeature	<i>Create a box-plot of a feature's expression pattern across the different datasets</i>
---------------------	--

Description

This function plots a box-plot of the expression pattern of a user-selected feature across the different datasets included in meta-analysis.

Usage

```
PlotSelectedFeature(mSetObj = NA, gene.id)
```

Arguments

mSetObj	Input name of the created mSet Object.
gene.id	Input the name of the selected feature.

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

PlotSigVar	<i>Supporting function for plotting important variables for each factor</i>
------------	---

Description

Supporting function for plotting important variables for each factor note, by control xpd to plot legend outside the plotting area without using layout

Usage

```
PlotSigVar(x, y, xline, yline, title)
```

Arguments

x	Input the X variable
y	Input the Y variable
xline	Input the xline
yline	Input the yline
title	Input the title

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

PlotSOM	<i>SOM Plot</i>
---------	-----------------

Description

Plot SOM map for less than 20 clusters

Usage

```
PlotSOM(mSetObj = NA, imgName, format = "png", dpi = 72, width = NA)
```

Arguments

mSetObj	Input name of the created mSet Object
imgName	Input a name for the plot
format	Select the image format, "png", or "pdf".
dpi	Input the dpi. If the image format is "pdf", users need not define the dpi. For "png" images, the default dpi is 72. It is suggested that for high-resolution images, select a dpi of 300.
width	Input the width, there are 2 default widths, the first, width = NULL, is 10.5. The second default is width = 0, where the width is 7.2. Otherwise users can input their own width.

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

PlotSPLS2DScore

Score Plot SPLS-DA

Description

Sparse PLS-DA (from mixOmics) score plot

Usage

```
PlotSPLS2DScore(mSetObj = NA, imgName, format = "png", dpi = 72,
  width = NA, inx1, inx2, reg = 0.95, show = 1, grey.scale = 0)
```

Arguments

mSetObj	Input name of the created mSet Object
imgName	Input a name for the plot
format	Select the image format, "png", or "pdf".
dpi	Input the dpi. If the image format is "pdf", users need not define the dpi. For "png" images, the default dpi is 72. It is suggested that for high-resolution images, select a dpi of 300.
width	Input the width, there are 2 default widths, the first, width = NULL, is 10.5. The second default is width = 0, where the width is 7.2. Otherwise users can input their own width.
inx1	Numeric, indicate the number of the principal component for the x-axis of the loading plot.
inx2	Numeric, indicate the number of the principal component for the y-axis of the loading plot.
reg	Numeric, between 1 and 0
show	Numeric, 1 or 0
grey.scale	Numeric, use grey-scale, 0 for no, and 1 for yes.

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

PlotSPLS3DScore	<i>3D SPLS-DA score plot</i>
-----------------	------------------------------

Description

Sparse PLS-DA (from mixOmics) 3D score plot

Usage

```
PlotSPLS3DScore(mSetObj = NA, imgName, format = "json", inx1 = 1,  
  inx2 = 2, inx3 = 3)
```

Arguments

mSetObj	Input name of the created mSet Object
imgName	Input a name for the plot
format	Select the image format, "png", or "pdf".
inx1	Numeric, indicate the number of the principal component for the x-axis of the loading plot.
inx2	Numeric, indicate the number of the principal component for the y-axis of the loading plot.
inx3	Numeric, indicate the number of the principal component for the z-axis of the loading plot.

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

PlotSPLSDA.Classification	<i>Create SPLS-DA classification plot</i>
---------------------------	---

Description

Sparse PLS-DA (from mixOmics) plot of classification performance using different components

Usage

```
PlotSPLSDA.Classification(mSetObj = NA, imgName, validOpt = "Mfold",  
  format = "png", dpi = 72, width = NA)
```

Arguments

mSetObj	Input name of the created mSet Object
imgName	Input a name for the plot
validOpt	"Mfold"
format	Select the image format, "png", or "pdf".
dpi	Input the dpi. If the image format is "pdf", users need not define the dpi. For "png" images, the default dpi is 72. It is suggested that for high-resolution images, select a dpi of 300.
width	Input the width, there are 2 default widths, the first, width = NULL, is 10.5. The second default is width = 0, where the width is 7.2. Otherwise users can input their own width.

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

PlotSPLSLoading	<i>Create SPLS-DA loading plot</i>
-----------------	------------------------------------

Description

Sparse PLS-DA (from mixOmics) loading plot

Usage

```
PlotSPLSLoading(mSetObj = NA, imgName, format = "png", dpi = 72,
  width = NA, inx, viewOpt = "detail")
```

Arguments

mSetObj	Input name of the created mSet Object
imgName	Input a name for the plot
format	Select the image format, "png", or "pdf".
dpi	Input the dpi. If the image format is "pdf", users need not define the dpi. For "png" images, the default dpi is 72. It is suggested that for high-resolution images, select a dpi of 300.
width	Input the width, there are 2 default widths, the first, width = NULL, is 10.5. The second default is width = 0, where the width is 7.2. Otherwise users can input their own width.
inx	Input the model index
viewOpt	Detailed view "detail"

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

PlotSPLSPairSummary *Plot SPLS-DA*

Description

Sparse PLS-DA (from mixOmics) pairwise summary plot

Usage

```
PlotSPLSPairSummary(mSetObj = NA, imgName, format = "png", dpi = 72,
  width = NA, pc.num)
```

Arguments

mSetObj	Input name of the created mSet Object
imgName	Input a name for the plot
format	Select the image format, "png", or "pdf".
dpi	Input the dpi. If the image format is "pdf", users need not define the dpi. For "png" images, the default dpi is 72. It is suggested that for high-resolution images, select a dpi of 300.
width	Input the width, there are 2 default widths, the first, width = NULL, is 10.5. The second default is width = 0, where the width is 7.2. Otherwise users can input their own width.
pc.num	Numeric, indicate the number of principle components

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

PlotSubHeatMap *Create Sub Heat Map Plot*

Description

Plot a sub heatmap based on results from t-tests/ANOVA, VIP or randomforest

Usage

```
PlotSubHeatMap(mSetObj = NA, imgName, format = "png", dpi = 72,
  width = NA, dataOpt, scaleOpt, smplDist, clstDist, palette, method.nm,
  top.num, viewOpt, rowV = T, colV = T, border = T, grp.ave = F)
```

Arguments

mSetObj	Input name of the created mSet Object
imgName	Input a name for the plot
format	Select the image format, "png", or "pdf".
dpi	Input the dpi. If the image format is "pdf", users need not define the dpi. For "png" images, the default dpi is 72. It is suggested that for high-resolution images, select a dpi of 300.
width	Input the width, there are 2 default widths, the first, width = NULL, is 10.5. The second default is width = 0, where the width is 7.2. Otherwise users can input their own width.
dataOpt	Set data options
scaleOpt	Set the image scale
smplDist	Input the sample distance method
clstDist	Input the clustering distance method
palette	Input color palette choice
method.nm	Input the method for sub-heat map
top.num	Input the top number
viewOpt	Set heatmap options, default is set to "detail"
rowV	Default is set to T
colV	Default is set to T
border	Indicate whether or not to show cell-borders, default is set to T
grp.ave	Logical, default is set to F

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

PlotTestAccuracy	<i>Plot classification performance using different features for Biomarker Tester</i>
------------------	--

Description

Plot of the accuracy of classification with an increasing number of features.

Usage

```
PlotTestAccuracy(mSetObj=NA, imgName, format="png", dpi=72)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
imgName	Input a name for the plot
format	Select the image format, "png", or "pdf".
dpi	Input the dpi. If the image format is "pdf", users need not define the dpi. For "png" images, the default dpi is 72. It is suggested that for high-resolution images, select a dpi of 300.

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

PlotTT

Plot t-test

Description

Plot t-test

Usage

```
PlotTT(mSetObj=NA, imgName, format="png", dpi=72, width=NA)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
imgName	Input a name for the plot
format	Select the image format, "png", or "pdf".
dpi	Input the dpi. If the image format is "pdf", users need not define the dpi. For "png" images, the default dpi is 72. It is suggested that for high-resolution images, select a dpi of 300.
width	Input the width, there are 2 default widths, the first, width = NULL, is 10.5. The second default is width = 0, where the width is 7.2. Otherwise users can input their own width.

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

PlotVolcano	<i>Create volcano plot</i>
-------------	----------------------------

Description

For labelling interesting points, it is defined by the following rules: need to be significant (sig.inx) and or 2. top 5 p, or 2. top 5 left, or 3. top 5 right.

Usage

```
PlotVolcano(mSetObj=NA, imgName, format="png", dpi=72, width=NA)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
imgName	Input a name for the plot
format	Select the image format, "png", or "pdf".
dpi	Input the dpi. If the image format is "pdf", users need not define the dpi. For "png" images, the default dpi is 72. It is suggested that for high-resolution images, select a dpi of 300.
width	Input the width, there are 2 default widths, the first, width = NULL, is 10.5. The second default is width = 0, where the width is 7.2. Otherwise users can input their own width.

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

PLSDA.CV	<i>PLS-DA classification and feature selection</i>
----------	--

Description

PLS-DA classification and feature selection

Usage

```
PLSDA.CV(mSetObj = NA, methodName = "T", compNum = GetDefaultPLSCVComp(),  
choice = "Q2")
```

Arguments

mSetObj	Input name of the created mSet Object
methodName	Logical, by default set to TRUE
compNum	GetDefaultPLSCVComp()
choice	Input the choice, by default it is Q2

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

PLSDA.Permut

Perform PLS-DA permutation

Description

Perform PLS-DA permutation using training classification accuracy as indicator, for two or multi-groups

Usage

```
PLSDA.Permut(mSetObj = NA, num = 100, type = "accu")
```

Arguments

mSetObj	Input name of the created mSet Object
num	Numeric, input the number of permutations
type	Type of accuracy, if "accu" indicate prediction accuracy, else "sep" is separation distance

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

PLSR.Anal

PLS analysis using oscorespls (Orthogonal scores algorithm) so that VIP can be calculated note: the VIP is calculated only after PLSDA-CV is performed to determine the best # of comp. used for VIP

Description

PLS analysis using oscorespls

Usage

```
PLSR.Anal(mSetObj = NA, reg = FALSE)
```

Arguments

mSetObj	Input name of the created mSet Object
reg	Logical

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

Predict.class	<i>Get predicted class probability</i>
---------------	--

Description

Get predicted class probability

Usage

```
Predict.class(x.train, y.train, x.test, clsMethod = "pls", lvNum,  
             imp.out = F)
```

Arguments

x.train	Input the x training samples
y.train	Input the y training samples
x.test	Input the x testing samples
clsMethod	Se the classification method, default is set to pls
lvNum	Input the number of levels
imp.out	Logical, set to F by default

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

PrepareIntegData	<i>Prepare integrated data</i>
------------------	--------------------------------

Description

Used for the pathinteg module.

Usage

```
PrepareIntegData(mSetObj = NA)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
---------	---

PrepareNetworkData	<i>Prepare data for network exploration</i>
--------------------	---

Description

Function for the network explorer module, prepares user's data for network exploration.

Usage

```
PrepareNetworkData(mSetObj = NA)
```

Arguments

mSetObj	Input name of the created mSet Object
---------	---------------------------------------

PreparePermResult	<i>Prepare report for permutation tests</i>
-------------------	---

Description

Function to prepare a report for permutation tests, used in higher functions

Usage

```
PreparePermResult(perm.vec)
```

Arguments

perm.vec	Input permutation vector
----------	--------------------------

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

PrepareQueryJson	<i>Prepare user's query for mapping KEGG Global Metabolic Network</i>
------------------	---

Description

This function prepares the user's data for the KEGG Global Metabolic Network

Usage

```
PrepareQueryJson(mSetObj = NA)
```

Arguments

mSetObj	Input name of the created mSet Object
---------	---------------------------------------

Author(s)

Othman Soufan, Jeff Xia <jeff.xia@mcgill.ca>, othman.soufan@mcgill.ca McGill University, Canada License: GNU GPL (≥ 2)

PrepareROCData	<i>Prepare data for ROC analysis</i>
----------------	--------------------------------------

Description

Prepare data for ROC analysis

Usage

```
PrepareROCData(mSetObj = NA)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
---------	---

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (≥ 2)

PrepareROCDetails	<i>ROC with CI for AUC</i>
-------------------	----------------------------

Description

ROC with CI for AUC

Usage

```
PrepareROCDetails(mSetObj = NA, feat.nm)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
feat.nm	Input the feature name

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

PrepareVennData	<i>Prepare data for Venn diagram</i>
-----------------	--------------------------------------

Description

Prepare data for Venn diagram

Usage

```
PrepareVennData(mSetObj = NA)
```

Arguments

mSetObj	Input name of the created mSet Object
---------	---------------------------------------

RankFeatures	<i>Rank features based on different importance measures</i>
--------------	---

Description

Ranks features based on various importance measures, return `imp.vec` which contains the importance measures of unordered features

Usage

```
RankFeatures(x.in, y.in, method, lvNum)
```

Arguments

<code>x.in</code>	Input the X features
<code>y.in</code>	Input the Y features
<code>method</code>	Input the method
<code>lvNum</code>	Input the number of levels

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

Read.BatchCSVdata	<i>Data I/O for batch effect checking</i>
-------------------	---

Description

Read multiple user uploaded CSV data one by one format: row, col

Usage

```
Read.BatchCSVdata(mSetObj = NA, filePath, format, label)
```

Arguments

<code>mSetObj</code>	Input name of the created mSet Object
<code>filePath</code>	Input the path to the batch files
<code>format</code>	Input the format of the batch files
<code>label</code>	Input the label-type of the files

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

Read.MSspec	<i>Read LC/GC-MS spectra (.netCDF, .mzXML, mzData)</i>
-------------	--

Description

This function handles reading in LC/GC-MS spectra files and fills in the dataSet object. It uses functions from the XCMS package to perform peak detection and alignment (grouping).

Usage

```
Read.MSspec(mSetObj, folderName, profmethod, fwhm, bw)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
folderName	the name of the folder containing the MS spectra
profmethod	specify the method to use for profile generation, supports "bin", "binlin", "binlinbase" and "intlin"
fwhm	specify the full width at half maximum of the matched filtration gaussian model peak
bw	define the bandwidth (standard deviation of the smoothing kernel) to be used

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

Read.PeakList	<i>Read peak list files</i>
---------------	-----------------------------

Description

This function reads peak list files and fills the data into a dataSet object. For NMR peak lists, the input should be formatted as two-columns containing numeric values (ppm, int). Further, this function will change ppm to mz, and add a dummy 'rt'. For MS peak data, the lists can be formatted as two-columns (mz, int), in which case the function will add a dummy 'rt', or the lists can be formatted as three-columns (mz, rt, int).

Usage

```
Read.PeakList(mSetObj=NA, foldername)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
foldername	name of the folder containing the NMR or MS peak list files to read

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (≥ 2)

Read.PeakListData	<i>Constructor to read uploaded user files into the mummichog object</i>
-------------------	--

Description

This function handles reading in CSV or TXT files and filling in the mSet object for mummichog analysis. It makes sure that all necessary columns are present.

Usage

```
Read.PeakListData(mSetObj=NA, filename = NA)
```

Arguments

mSetObj	Input the name of the created mSetObj.
filename	Input the path name for the CSV/TXT files to read.

Author(s)

Jasmine Chong, Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (≥ 2)

Read.TextData	<i>Constructor to read uploaded CSV or TXT files into the dataSet object</i>
---------------	--

Description

This function handles reading in CSV or TXT files and filling in the dataSet object created using "InitDataObjects".

Usage

```
Read.TextData(mSetObj=NA, filePath, format, lbl.type)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects).
filePath	Input the path name for the CSV/TXT files to read.
format	Specify if samples are paired and in rows (rowp), unpaired and in rows (rowu), in columns and paired (colp), or in columns and unpaired (colu).
lbl.type	Specify the data label type, either discrete (disc) or continuous (cont).

Author(s)

Jeff Xia <jeff.xia@mcgill.ca>, Jasmine Chong McGill University, Canada License: GNU GPL
(>= 2)

ReadIndData

Read in individual data

Description

This function determines reads in user's individual data for meta-analysis.

Usage

```
ReadIndData(mSetObj = NA, dataName, format = "colu")
```

Arguments

mSetObj	Input name of the created mSet Object
dataName	Name of inputted dataset.
format	Specify if samples are paired and in rows (rowp), unpaired and in rows (rowu), in columns and paired (colp), or in columns and unpaired (colu).

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

ReadPairFile

Read paired peak or spectra files

Description

This function reads paired peak lists or spectra files. The pair information is stored in a file where each line is a pair and names are separated by ":".

Usage

```
ReadPairFile(filePath = "pairs.txt")
```

Arguments

filePath	Set file path
----------	---------------

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

RecordRCommand	<i>Record R Commands</i>
----------------	--------------------------

Description

Record R Commands

Usage

```
RecordRCommand(mSetObj = NA, cmd)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
cmd	Commands

rectUnique	<i>Perform utilities for peak grouping</i>
------------	--

Description

Perform various utilities for peak grouping

Usage

```
rectUnique(m, order = seq(length = nrow(m)), xdiff = 0, ydiff = 0)
```

Arguments

m	Peaks
order	Performs seq(length = nrow(m))
xdiff	Default set to 0
ydiff	Default set to 0

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

RegisterData*Register data in R*

Description

When there are multiple datasets, record their name and save the inputted data as a .RDS file to save memory. Note, the memory will only contain one mSetObj\$dataSet object. By default the last one will be the most recent/current dataSet object. Users can switch which data to load into memory.

Usage

```
RegisterData(mSetObj = NA, dataSet)
```

Arguments

mSetObj	Input name of the created mSet Object
dataSet	Input dataset to be registered in R.

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

RemoveCmpd*Remove selected compounds*

Description

Remove compounds

Usage

```
RemoveCmpd(mSetObj = NA, inx)
```

Arguments

mSetObj	Input name of the created mSet Object
inx	Input the index of compound to remove

RemoveData	<i>Remove data object, the current dataSet will be the last one by default</i>
------------	--

Description

Remove data object, the current dataSet will be the last one by default

Usage

```
RemoveData(dataName)
```

Arguments

dataName	Input name of data to remove
----------	------------------------------

RemoveDuplicates	<i>Given a data with duplicates, remove duplicates</i>
------------------	--

Description

Dups is the one with duplicates

Usage

```
RemoveDuplicates(data, lvlOpt = "mean", quiet = T)
```

Arguments

data	Input data to remove duplicates
lvlOpt	Set options, default is mean
quiet	Set to quiet, logical, default is T

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

`RemoveFile`*Remove file*

Description

Remove file

Usage

`RemoveFile(fileName)`

Arguments

`fileName` Input name of file to remove

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

`RemoveFolder`*Remove folder*

Description

Remove folder

Usage

`RemoveFolder(folderName)`

Arguments

`folderName` Input name of folder to remove

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

RemoveGene	<i>Remove selected genes</i>
------------	------------------------------

Description

Remove selected genes based on an index

Usage

```
RemoveGene(mSetObj = NA, inx)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
inx	Input compound index

RemoveMissingPercent	<i>Data processing: remove variables with missing values</i>
----------------------	--

Description

Remove variables containing a user-defined percentage cut-off of missing values.

Usage

```
RemoveMissingPercent(mSetObj, percent)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
percent	Input the percentage cut-off you wish to use. For instance, 50 percent is represented by percent=0.5.

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

ReplaceMin	<i>Replace missing or zero values</i>
------------	---------------------------------------

Description

This function will replace zero/missing values by half of the smallest positive value in the original dataset. This method will be called after all missing value imputations are conducted. Also, it directly modifies the mSet\$dataSet\$procr if executed after normalization, or the mSet\$dataSet\$norm if before normalization.

Usage

```
ReplaceMin(mSetObj=NA)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
---------	---

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

RerenderKEGGGraph	<i>Redraw current graph for zooming or clipping then return a value</i>
-------------------	---

Description

Redraw current graph for zooming or clipping then return a value

Usage

```
RerenderKEGGGraph(mSetObj, imgName, width, height, zoom.factor)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
imgName	Input a name for the plot
width	Input the width, there are 2 default widths, the first, width = NULL, is 10.5. The second default is width = 0, where the width is 7.2. Otherwise users can input their own width.
height	Input the heights
zoom.factor	Input the zoom factor

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

RerenderMetPAGraph	<i>Redraw current graph for zooming or clipping then return a value</i>
--------------------	---

Description

Redraw current graph for zooming or clipping then return a value

Usage

```
RerenderMetPAGraph(mSetObj = NA, imgName, width, height)
```

Arguments

mSetObj	Input name of the created mSet Object
imgName	Input the name of the plot
width	Input the width, there are 2 default widths, the first, width = NULL, is 10.5. The second default is width = 0, where the width is 7.2. Otherwise users can input their own width.
height	Input the height of the created plot.

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

ResetCustomCmpds	<i>Reset custom compounds</i>
------------------	-------------------------------

Description

Reset custom compounds

Usage

```
ResetCustomCmpds(mSetObj = NA)
```

Arguments

mSetObj	Input name of the created mSet Object
---------	---------------------------------------

RF.Anal	<i>Perform Random Forest Analysis</i>
---------	---------------------------------------

Description

Perform Random Forest

Usage

```
RF.Anal(mSetObj = NA, treeNum = 500, tryNum = 7, randomOn = 1)
```

Arguments

mSetObj	Input name of the created mSet Object
treeNum	Input the number of trees to create, default is set to 500
tryNum	Set number of tries, default is 7
randomOn	Set random, default is 1

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

ROCPredSamplesTable	<i>Create a table of newly classified samples</i>
---------------------	---

Description

Function to create the table of newly classified samples

Usage

```
ROCPredSamplesTable(mSetObj = NA)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects) Function to create the table of newly classified samples
---------	--

RSVM

R-SVM core code

Description

Core code to perform R-SVM

Usage

```
RSVM(x, y, ladder, CVtype, CVnum = 0)
```

Arguments

x	Row matrix of data
y	Class label: 1 / -1 for 2 classes
ladder	Input the ladder
CVtype	Integer (N fold CV), "LOO" leave-one-out CV, "bootstrape" bootstrape CV
CVnum	Number of CVs, LOO: defined as sample size, Nfold and bootstrape: user defined, default as sample size outputs a named list Error: a vector of CV error on each level SelfFreq: a matrix for the frequency of each gene being selected in each level with each column corresponds to a level of selection and each row for a gene The top important gene in each level are those high-frequent ones

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

RSVM.Anal

Recursive Support Vector Machine (R-SVM)

Description

recursive SVM for feature selection and classification

Usage

```
RSVM.Anal(mSetObj = NA, cvType)
```

Arguments

mSetObj	Input name of the created mSet Object
cvType	Cross-validation type

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

SAM.Anal

Perform Significance Analysis of Microarrays (SAM) analysis

Description

Perform SAM

Usage

```
SAM.Anal(mSetObj = NA, method = "d.stat", paired = FALSE,
         varequal = TRUE)
```

Arguments

mSetObj	Input name of the created mSet Object
method	Method for SAM analysis, default is set to "d.stat", alternative is "wilc.stat"
paired	Logical, indicates if samples are paired or not. Default is set to FALSE
varequal	Logical, indicates if variance is equal. Default is set to TRUE

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

SanityCheckData

Sanity Check Data

Description

SanityCheckData is used for data processing, and performs a basic sanity check of the uploaded content, ensuring that the data is suitable for further analysis. The function will return a 1 if the data is suitable, or a 0 if unsuitable. The function will perform the check directly onto the mSet\$dataset object, and must be performed immediately after reading in data.

Usage

```
SanityCheckData(mSetObj=NA)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
---------	---

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

SanityCheckIndData	<i>Sanity check of individual datasets for meta-analysis</i>
--------------------	--

Description

Performs a sanity check on each-uploaded dataset for meta-analysis. Briefly, this function will exclude empty rows, check class labels, ensure only 2 groups are being compared within the dataset, ensure sample names are unique, remove low quality samples/features, and replace missing values.

Usage

```
SanityCheckIndData(mSetObj = NA, dataName)
```

Arguments

mSetObj	Input name of the created mSet Object
dataName	Input name of the dataset to perform the sanity check.

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

SanityCheckMummichogData	<i>Sanity Check Data</i>
--------------------------	--------------------------

Description

SanityCheckData is used for data processing, and performs a basic sanity check of the uploaded data, ensuring that the data is suitable for further analysis. The function ensure that all parameters are properly set based on updated parameters.

Usage

```
SanityCheckMummichogData(mSetObj=NA)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects).
---------	--

Author(s)

Jasmine Chong, Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

saveNetworkInSIF	<i>Network functions</i>
------------------	--------------------------

Description

Adapted from BioNet

Usage

```
saveNetworkInSIF(network, name)
```

Arguments

network	Input network
name	Input file name

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

SaveTransformedData	<i>Save the processed data with class names</i>
---------------------	---

Description

This function saves the processed data with class names as CSV files. Several files may be generated, the original data, processed data, peak normalized, and/or normalized data.

Usage

```
SaveTransformedData(mSetObj = NA)
```

Arguments

mSetObj	Input name of the created mSet Object
---------	---------------------------------------

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

SearchByCompound	<i>Search for compound from all member compounds of metabolite set</i>
------------------	--

Description

Search for compound from all member compounds of metabolite set

Usage

```
SearchByCompound(mSetObj = NA, query)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
query	Input the query to search

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

SearchByName	<i>Given a metabolite set name, search its index</i>
--------------	--

Description

Given a metabolite set name, search its index

Usage

```
SearchByName(mSetObj = NA, query)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
query	Input the query to search

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

SearchCompoundLib	<i>Merges user-input files with library files</i>
-------------------	---

Description

This function matches user-uploaded files to library files specific to the selected organism. It also creates a list of compounds IDs from the user-uploaded list of significant m/z features.

Usage

```
SearchCompoundLib(mSetObj=NA)
```

Arguments

mSetObj	Input the name of the created mSetObj object
---------	--

Author(s)

Jasmine Chong, Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

SearchMsetLibraries	<i>Search metabolite set libraries</i>
---------------------	--

Description

Search metabolite set libraries

Usage

```
SearchMsetLibraries(mSetObj = NA, query, type)
```

Arguments

mSetObj	Input name of the created mSet Object
query	Input the query to search
type	Input the data type (name or compound)

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

SearchNetDB*Perform mapping of user's data to interaction network*

Description

This function performs mapping of user's data to the internal network to create a network from the seed nodes

Usage

```
SearchNetDB(mSetObj = NA, db.type, table.nm, require.exp = TRUE,  
            min.score = 900)
```

Arguments

mSetObj	Input name of the created mSet Object
db.type	Input the database type
table.nm	Input the organism code for the sqlite table (ppi). For chemical type, the table.nm is drugbank of ctd
require.exp	Logical, only used for the STRING database
min.score	Input the minimal score, only used for the STRING database

Author(s)

Othman Soufan, Jeff Xia <jeff.xia@mcgill.ca>, othman.soufan@mcgill.ca McGill University, Canada License: GNU GPL (>= 2)

SelectMultiData*Select one or more datasets for meta-analysis*

Description

This function selects one or more datasets to be used for meta-analysis. 1 is used to indicate that a dataset is selected and by default, all datasets will be selected for meta-analysis.

Usage

```
SelectMultiData(mSetObj = NA)
```

Arguments

mSetObj	Input name of the created mSet Object
---------	---------------------------------------

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

SetAnalysisMode	<i>Set biomarker analysis mode</i>
-----------------	------------------------------------

Description

ROC utilities

Usage

```
SetAnalysisMode(mSetObj, mode)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)s
mode	Input the selected mode for biomarker analysis, "univ" for univariate ROC curve analysis, "explore" for multivariate ROC curve analysis, and "test" for ROC curve based model creation and evaluation. McGill University, Canada License: GNU GPL (>= 2)

Author(s)

Jeff Xia <jeff.xia@mcgill.ca>

SetBarParams	<i>Plot a scatterplot bubble chart overview of the matched pathways</i>
--------------	---

Description

x axis is the pathway impact factor y axis is the p value (from ORA) return the circle information

Usage

```
SetBarParams(mSetObj = NA)
```

Arguments

mSetObj	Input name of the created mSet Object
---------	---------------------------------------

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

SetCachexiaSetUsed	<i>Set the cachexia set used</i>
--------------------	----------------------------------

Description

Set cachexia set used

Usage

```
SetCachexiaSetUsed(mSetObj = NA, used)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
used	Set data to be used

SetCandidate	<i>Set matched name based on user selection from all potential hits</i>
--------------	---

Description

Note: to change object in the enclosing enviroment, use "<-"

Usage

```
SetCandidate(mSetObj = NA, query_nm, can_nm)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
query_nm	Input the query name
can_nm	Input the candidate name

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

SetCurrentGroups	<i>To choose from two groups</i>
------------------	----------------------------------

Description

Choose two groups (when more than two groups uploaded)

Usage

```
SetCurrentGroups(mSetObj = NA, grps)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
grps	Input the groups

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

SetCurrentMsetLib	<i>Set current user selected metaset library for search</i>
-------------------	---

Description

if enrichment analysis, also prepare lib by creating a list of metabolite sets

Usage

```
SetCurrentMsetLib(mSetObj=NA, lib.type, excludeNum)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
lib.type	Input user selected name of library, "self", "pathway", "blood", "urine", "csf", "snp", "predicted", "location", "drug"
excludeNum	Users input the minimum number compounds within selected metabolite sets (metabolitesets < excludeNum)

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

SetCustomData	<i>Set custom data</i>
---------------	------------------------

Description

The "selected.cmpds" should be for extraction

Usage

```
SetCustomData(mSetObj = NA, selected.cmpds, selected.smpIs)
```

Arguments

mSetObj Input the name of the created mSetObj (see InitDataObjects)
selected.cmpds Input the vector containing the compounds
selected.smpIs Input the vector containing the samples

SetDesignType	<i>For two factor time series only</i>
---------------	--

Description

For two factor time series only

Usage

```
SetDesignType(mSetObj = NA, design)
```

Arguments

mSetObj Input the name of the created mSetObj (see InitDataObjects)
design Input the design type

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

`SetEBAMSigMat`*For EBAM analysis*

Description

return double matrix with 3 columns - z.value, posterior, local.fdr

Usage

```
SetEBAMSigMat(mSetObj = NA, delta)
```

Arguments

<code>mSetObj</code>	Input name of the created mSet Object
<code>delta</code>	Input the delta for EBAM analysis

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

`SetKEGG.PathLib`*Set KEGG pathway library*

Description

note, this process can be long, need to return a value to force Java to wait

Usage

```
SetKEGG.PathLib(mSetObj = NA, kegg.rda)
```

Arguments

<code>mSetObj</code>	Input the name of the created mSetObj (see InitDataObjects)
<code>kegg.rda</code>	Input the name of the KEGG library

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

SetMass.PathLib*Load the selected metabolic pathway database*

Description

SetMass.PathLib is used to load in the user selected metabolic pathway database. If the user's input is just a list of significant features (anal.type = "siglist"), this function will also provide a list of reference features.

Usage

```
SetMass.PathLib(mSetObj=NA, lib)
```

Arguments

mSetObj Input the name of the created mSetObj (see InitDataObjects)

lib Input the name of organism library

Author(s)

Jasmine Chong, Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL
(>= 2)

SetMetabolomeFilter*Set metabolome filter*

Description

Set metabolome filter

Usage

```
SetMetabolomeFilter(mSetObj = NA, TorF)
```

Arguments

mSetObj Input the name of the created mSetObj (see InitDataObjects)

TorF Input metabolome filter

SetOrganism	<i>Set organism for further analysis</i>
-------------	--

Description

Set organism for further analysis

Usage

```
SetOrganism(mSetObj = NA, org)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
org	Set organism ID

SetPeakList.GroupValues	<i>Set peak list group values</i>
-------------------------	-----------------------------------

Description

Set peak list group values

Usage

```
SetPeakList.GroupValues(mSetObj = NA)
```

Arguments

mSetObj	Input name of mSetObj, the data used is the nmr.xcmsSet object
---------	--

SetSAMSigMat	<i>Set Significance Analysis of Microarrays (SAM) analysis matrix</i>
--------------	---

Description

Create SAM matrix

Usage

```
SetSAMSigMat(mSetObj = NA, delta)
```

Arguments

mSetObj	Input name of the created mSet Object
delta	Input the delta for SAM analysis

Setup.BiofluidType	<i>Save biofluid type for SSP</i>
--------------------	-----------------------------------

Description

Save biofluid type for SSP

Usage

```
Setup.BiofluidType(mSetObj = NA, type)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
type	Input the biofluid type

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

Setup.ConcData	<i>Save concentration data</i>
----------------	--------------------------------

Description

Save concentration data

Usage

```
Setup.ConcData(mSetObj = NA, conc)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
conc	Input the concentration data

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

Setup.HMDBReferenceMetabolome

Read user uploaded metabolome as a list of HMDB compound names

Description

Read user uploaded metabolome as a list of HMDB compound names

Usage

Setup.HMDBReferenceMetabolome(mSetObj = NA, filePath)

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
filePath	Input the path to the user's list of HMDB compound names

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

Setup.KEGGReferenceMetabolome

Read user uploaded metabolome as a list of KEGG pathway ids

Description

Read user uploaded metabolome as a list of KEGG pathway ids

Usage

Setup.KEGGReferenceMetabolome(mSetObj = NA, filePath)

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
filePath	Input the path to the user's list of KEGG pathway ids

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

Setup.MapData	<i>Save compound name for mapping</i>
---------------	---------------------------------------

Description

Save compound name for mapping

Usage

```
Setup.MapData(mSetObj = NA, qvec)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
qvec	Input the vector to query

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

Setup.UserMsetLibData	<i>Read user upload metabolite set library file</i>
-----------------------	---

Description

Return two col csv file, first name, second cmpd list

Usage

```
Setup.UserMsetLibData(mSetObj = NA, filePath)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
filePath	Input the path to the user's uploaded metabolite set library

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

SetupMSdataMatrix	<i>Create a MS spectra data matrix of peak values for each group</i>
-------------------	--

Description

This function sets up a MS spectra data matrix using the 'groupval' function from XCMS. This generates a usable matrix of peak values for analysis where columns represent peak groups and rows represent samples. Collisions where more than one peak from a single sample are in the same group get resolved utilizing "medret", which uses the peak closest to the median retention time.

Usage

```
SetupMSdataMatrix(mSetObj, intvalue)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
intvalue	name of peak column to enter into the returned matrix, if intvalue = 'into', use integrated area of original (raw) peak intensities, if intvalue = 'intf', use integrated area of filtered peak intensities, if intvalue = 'intb', use baseline corrected integrated peak intensities, if intvalue = 'maxo', use the maximum intensity of original (raw) peaks, or if intvalue = 'maxf' use the maximum intensity of filtered peaks

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

SetupSMPDBLinks	<i>Only works for human (hsa.rda) data</i>
-----------------	--

Description

Only works for human (hsa.rda) data

Usage

```
SetupSMPDBLinks(kegg.ids)
```

Arguments

kegg.ids	Input the list of KEGG ids to add SMPDB links
----------	---

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

SOM.Anal

*SOM analysis***Description**

SOM analysis

Usage

```
SOM.Anal(mSetObj = NA, x.dim, y.dim, initMethod, neighb = "gaussian")
```

Arguments

mSetObj	Input name of the created mSet Object
x.dim	Input X dimension for SOM analysis
y.dim	Input Y dimension for SOM analysis
initMethod	Input the method
neighb	Default is set to 'gaussian'

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

sparse.mint.block_iteration

*Perform Sparse Generalized Canonical Correlation (sgccak)***Description**

Runs sgccak() modified from RGCCA

Usage

```
sparse.mint.block_iteration(A, design, study = NULL,
  keepA.constraint = NULL, keepA = NULL, scheme = "horst", init = "svd",
  max.iter = 100, tol = 1e-06, verbose = TRUE, bias = FALSE,
  penalty = NULL)
```

Arguments

A	Data
design	Set design
study	Default set to NULL
keepA.constraint	Default set to NULL
keepA	Default set to NULL
scheme	Scheme, default set to "horst"
init	Init mode, default set to "svd"
max.iter	Max number of iterations, numeric, default set to 100
tol	Tolerance, numeric, default set to 1e-06
verbose	Default set to TRUE
bias	Default set to FALSE
penalty	Default set to NULL

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

splsda

Perform sPLS-DA

Description

Sparse PLS functions (adapted from mixOmics package for web-based usage) this function is a particular setting of internal_mint.block the formatting of the input is checked in internal_wrapper.mint

Usage

```
splsda(X, Y, ncomp = 2, mode = c("regression", "canonical", "invariant",
  "classic"), keepX, keepX.constraint = NULL, scale = TRUE, tol = 1e-06,
  max.iter = 100, near.zero.var = FALSE, logratio = "none",
  multilevel = NULL)
```

Arguments

X	numeric matrix of predictors
Y	a factor or a class vector for the discrete outcome
ncomp	the number of components to include in the model. Default to 2.
mode	Default set to c("regression", "canonical", "invariant", "classic")
keepX	Number of X variables kept in the model on the last components (once all keepX.constraint[[i]] are used).

keepX.constraint	A list containing which variables of X are to be kept on each of the first PLS-components.
scale	Boolean. If scale = TRUE, each block is standardized to zero means and unit variances (default: TRUE).
tol	Convergence stopping value.
max.iter	integer, the maximum number of iterations.
near.zero.var	boolean, see the internal nearZeroVar function (should be set to TRUE in particular for data with many zero values). Setting this argument to FALSE (when appropriate) will speed up the computations
logratio	"None" by default, or "CLR"
multilevel	Designate multilevel design, "NULL" by default

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

SPLSR.Anal

Perform SPLS-DA

Description

Sparse PLS-DA (from mixOmics)

Usage

```
SPLSR.Anal(mSetObj = NA, comp.num, var.num, compVarOpt)
```

Arguments

mSetObj	Input name of the created mSet Object
comp.num	Input the number of computations to run
var.num	Input the number of variables
compVarOpt	Input the option to perform SPLS-DA

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

SumNorm

Row-wise Normalization

Description

Row-wise norm methods, when x is a row. Normalize by a sum of each sample, assume constant sum (1000). Options for normalize by sum median, reference sample, reference reference (compound), or quantile normalization

Usage

```
SumNorm(x)
```

Arguments

x	Input data to normalize
---	-------------------------

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada

template.match

Pattern hunter

Description

Run template on all the high region effect genes

Usage

```
template.match(x, template, dist.name)
```

Arguments

x	Input data
template	Input template
dist.name	Input distance method

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

Ttests.Anal	<i>Perform t-test analysis</i>
-------------	--------------------------------

Description

This function is used to perform t-test analysis.

Usage

```
Ttests.Anal(mSetObj = NA, nonpar = F, threshp = 0.05, paired = FALSE,  
            equal.var = TRUE)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
nonpar	Logical, use a non-parametric test, T or F. False is default.
threshp	Numeric, enter the adjusted p-value (FDR) cutoff
paired	Logical, is data paired (T) or not (F).
equal.var	Logical, evaluates if the group variance is equal (T) or not (F).

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

UnzipUploadedFile	<i>Unzip .zip files</i>
-------------------	-------------------------

Description

Unzips uploaded .zip files, removes the uploaded file, checks for success

Usage

```
UnzipUploadedFile(inPath, outPath, rmFile = T)
```

Arguments

inPath	Input the path of the zipped files
outPath	Input the path to directory where the unzipped files will be deposited
rmFile	Logical, input whether or not to remove files. Default set to T

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

UpdateFeatureItems	<i>Remove feature items</i>
--------------------	-----------------------------

Description

This function removes user-selected features from the data set. This must be performed following data processing and filtering. If the data was normalized prior to removal, you must re-normalize the data.

Usage

```
UpdateFeatureItems(mSetObj=NA, feature.nm.vec)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
feature.nm.vec	Input the name of the feature to remove from the data in quotation marks. The name must be identical to the feature names found in the data set.

Author(s)

Jeff Xia <jeff.xia@mcgill.ca>, Jasmine Chong McGill University, Canada

UpdateGroupItems	<i>Remove a group from the data</i>
------------------	-------------------------------------

Description

This function removes a user-specified group from the data set. This must be performed following data processing and filtering. If the data was normalized prior to removal, you must re-normalize the data.

Usage

```
UpdateGroupItems(mSetObj=NA, grp.nm.vec)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
grp.nm.vec	Input the name of the group you would like to remove from the data set in quotation marks (ex: "Disease B") The name must be identical to a class label.

Author(s)

Jeff Xia <jeff.xia@mcgill.ca>, Jasmine Chong McGill University, Canada

UpdateIntegPathwayAnalysis

Update integrative pathway analysis for new input list

Description

used for integrative analysis as well as general pathways analysis for meta-analysis results

Usage

```
UpdateIntegPathwayAnalysis(mSetObj=NA, qids, file.nm, topo="dc", enrich="hyper", libOpt="integ")
```

Arguments

mSetObj	Input name of the created mSet Object
qids	Input the query IDs
file.nm	Input the name of the file
topo	Select the mode for topology analysis: Degree Centrality ("dc") measures the number of links that connect to a node (representing either a gene or metabolite) within a pathway; Closeness Centrality ("cc") measures the overall distance from a given node to all other nodes in a pathway; Betweenness Centrality ("bc") measures the number of shortest paths from all nodes to all the others that pass through a given node within a pathway.
enrich	Method to perform over-representation analysis (ORA) based on either hypergenometrics analysis ("hyper") or Fisher's exact method ("fisher").
libOpt	Select the different modes of pathways, either the gene-metabolite mode ("integ") which allows for joint-analysis and visualization of both significant genes and metabolites or the gene-centric ("genetic") and metabolite-centric mode ("metab") which allows users to identify enriched pathways driven by significant genes or metabolites, respectively.

Author(s)

Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

UpdateMummichogParameters

Upates the mSetObj with user-selected parameters

Description

This functions handles updating the mSet object for mummichog analysis. It is necessary to utilize this function to specify to the organism's pathways to use (libOpt), the mass-spec mode (msModeOpt), mass-spec instrument (instrumentOpt), the p-value cutoff (pvalCutoff), and the number of permutations (permNum).

Usage

```
UpdateMummichogParameters(mSetObj=NA, instrumentOpt, msModeOpt, pvalCutoff)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects).
instrumentOpt	Define the mass-spec instrument used to perform untargeted metabolomics.
msModeOpt	Define the mass-spec mode of the instrument used to perform untargeted metabolomics.
pvalCutoff	Numeric, specify the p-value cutoff to define significant m/z features from reference m/z features.

Author(s)

Jasmine Chong, Jeff Xia <jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

UpdateSampleItems	<i>Remove samples from user's data</i>
-------------------	--

Description

This function removes samples from the data set. This must be performed following data processing and filtering. If the data was normalized prior to removal, you must re-normalize the data.

Usage

```
UpdateSampleItems(mSetObj=NA, smp1.nm.vec)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
smp1.nm.vec	Input the name of the sample to remove from the data in quotation marks. The name must be identical to the sample names found in the data set.

Author(s)

Jeff Xia <jeff.xia@mcgill.ca>, Jasmine Chong McGill University, Canada

usr2png

*Perform utilities for MetPa***Description**

Convert user coords (as used in current plot) to pixels in a png adapted from the imagemap package

Usage

```
usr2png(xy, im)
```

Arguments

xy	Input coordinates
im	Input coordinates

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

Volcano.Anal

*Perform Volcano Analysis***Description**

Perform volcano analysis

Usage

```
Volcano.Anal(mSetObj=NA, paired=FALSE, fcthresh, cmpType, percent.thresh, nonpar=F, threshp, equal.var)
```

Arguments

mSetObj	Input the name of the created mSetObj (see InitDataObjects)
paired	Logical, T if data is paired, F if data is not.
fcthresh	Numeric, input the fold change threshold
cmpType	Comparison type, 1 indicates group 1 vs group 2, and 2 indicates group 2 vs group 1
percent.thresh	Only for paired data, numeric, indicate the significant count threshold
nonpar	Logical, indicate if a non-parametric test should be used (T or F)
threshp	Numeric, indicate the p-value threshold
equal.var	Logical, indicates if the group variance is equal (T) or unequal (F)
pval.type	To indicate raw p-values, use "raw". To indicate FDR-adjusted p-values, use "fdr".

Author(s)

Jeff Xia<jeff.xia@mcgill.ca> McGill University, Canada License: GNU GPL (>= 2)

XSet2MSet

Converts xset object from XCMS to mSet object for MetaboAnalyst

Description

This function converts processed raw LC/MS data from XCMS to a usable data object (mSet) for MetaboAnalyst. The immediate next step following using this function is to perform a SanityCheck, and then further data processing and analysis can continue.

Usage

```
XSet2MSet(xset, dataType, analType, paired = F, format, lbl.type)
```

Arguments

xset	The name of the xcmsSet object created.
dataType	The type of data, either list (Compound lists), conc (Compound concentration data), specbin (Binned spectra data), pktable (Peak intensity table), nmrpeak (NMR peak lists), mspeak (MS peak lists), or msspec (MS spectra data).
analType	Indicate the analysis module to be performed: stat, pathora, pathqea, msetora, msetssp, msetqea, ts, cmpdmap, smpmap, or pathinteg.
paired	Logical, is data paired (T) or not (F).
format	Specify if samples are paired and in rows (rowp), unpaired and in rows (rowu), in columns and paired (colp), or in columns and unpaired (colu).
lbl.type	Specify the data label type, either discrete (disc) or continuous (cont).

Index

AddErrMsg, [12](#)
analyze.lipids, [12](#)
ANOVA.Anal, [13](#)
ANOVA2.Anal, [13](#)
aof, [14](#)
aov.between, [14](#)
aov.repeated, [15](#)
aov.within, [15](#)
ASCAfun.res, [16](#)
ASCAfun1, [16](#)
ASCAfun2, [17](#)

calculateConcISO, [17](#)
CalculateFeatureRanking, [18](#)
CalculateGlobalTestScore, [18](#)
CalculateHyperScore, [19](#)
CalculateImpVarCutoff, [19](#)
CalculateOraScore, [20](#)
CalculatePairwiseDiff, [20](#)
CalculateQeaScore, [21](#)
CalculateSSP, [21](#)
CheckMetaDataConsistency, [22](#)
CleanData, [22](#)
CleanDataMatrix, [23](#)
CleanNumber, [23](#)
ClearNegatives, [24](#)
ClearStrings, [24](#)
ClearUserDir, [25](#)
ComputeAverageCurve, [25](#)
computeConc, [26](#)
ComputeHighLow, [26](#)
ComputeMummichogSigPvals, [27](#)
CreateAnalNullMsg, [27](#)
CreateANOVAdoc, [28](#)
CreateAOV2doc, [28](#)
CreateASCAdoc, [29](#)
CreateBiomarkerInputDoc, [29](#)
CreateBiomarkerIntr, [30](#)
CreateBiomarkerOverview, [30](#)
CreateBiomarkerRatioOverview, [30](#)

CreateBiomarkerRnwReport, [31](#)
CreateCorrDoc, [31](#)
createCVset, [32](#)
CreateEBAMdoc, [32](#)
CreateEnrichAnalDoc, [33](#)
CreateEnrichInputDoc, [33](#)
CreateEnrichIntr, [34](#)
CreateEnrichORAdoc, [34](#)
CreateEnrichOverview, [35](#)
CreateEnrichProcessDoc, [35](#)
CreateEnrichQEAdoc, [36](#)
CreateEnrichRnwReport, [36](#)
CreateEnrichSSPdoc, [37](#)
CreateFooter, [37](#)
CreateGraph, [38](#)
CreateHCdoc, [38](#)
CreateHeader, [39](#)
CreateHeatmap2doc, [39](#)
CreateIntegPathwayAnalysisRnwReport, [40](#)
CreateIntegratedPathwayAnalInputDoc, [40](#)
CreateIntegratedPathwayAnalIntr, [41](#)
CreateIntegratedPathwayAnalOverview, [41](#)
CreateIntegratedPathwayDoc, [42](#)
CreateIntegratedPathwayGeneMapTable, [42](#)
CreateIntegratedPathwayNameMapTable, [43](#)
CreateIntegratedPathwayResultsTable, [43](#)
CreateiPCAdoc, [44](#)
CreateKMdoc, [44](#)
CreateLadder, [45](#)
CreateMappingResultTable, [45](#)
CreateMBdoc, [46](#)
CreateMetaAnalysisDEdoc, [46](#)
CreateMetaAnalysisInputDoc, [47](#)

- CreateMetaAnalysisIntr, [47](#)
- CreateMetaAnalysisNORMdoc, [48](#)
- CreateMetaAnalysisOutput, [48](#)
- CreateMetaAnalysisOverview, [49](#)
- CreateMetaAnalysisRnwReport, [49](#)
- CreateMetaTable, [50](#)
- CreateModelBiomarkersDoc, [50](#)
- CreateMultiBiomarkersDoc, [51](#)
- CreateMummichogAnalTable, [51](#)
- CreateMummichogAnalysisDoc, [52](#)
- CreateMummichogInputDoc, [52](#)
- CreateMummichogIntro, [53](#)
- CreateMummichogOverview, [53](#)
- CreateMummichogRnwReport, [53](#)
- CreateNetworkExplorerDoc, [54](#)
- CreateNetworkExplorerInputDoc, [54](#)
- CreateNetworkExplorerIntr, [55](#)
- CreateNetworkExplorerOverview, [55](#)
- CreateNetworkExplorerRnwReport, [56](#)
- CreateNetworkGeneMapTable, [56](#)
- CreateNetworkNameMapTable, [57](#)
- CreateOPLSDAdoc, [57](#)
- CreatePathAnalDoc, [58](#)
- CreatePathInputDoc, [58](#)
- CreatePathIntr, [59](#)
- CreatePathProcessDoc, [59](#)
- CreatePathResultDoc, [60](#)
- CreatePathRnwReport, [60](#)
- CreatePCAdoc, [61](#)
- CreatePDFReport, [61](#)
- CreatePLSdoc, [62](#)
- CreatePowerAnalDoc, [62](#)
- CreatePowerInputDoc, [63](#)
- CreatePowerIntr, [63](#)
- CreatePowerOverview, [64](#)
- CreatePowerParametersDoc, [64](#)
- CreatePowerRnwReport, [65](#)
- CreateRatioTable, [65](#)
- CreateRFdoc, [66](#)
- CreateRHistAppendix, [66](#)
- CreateROCLabelsTable, [67](#)
- CreateSAMdoc, [67](#)
- CreateSemiTransColors, [68](#)
- CreateSOMdoc, [68](#)
- CreateSPLSDAdoc, [69](#)
- CreateStatFooter, [69](#)
- CreateStatIOdoc, [70](#)
- CreateStatNORMdoc, [70](#)
- CreateStatRnwReport, [71](#)
- CreateSummaryTable, [71](#)
- CreateSVMdoc, [72](#)
- CreateTimeSeriesAnalNullMsg, [72](#)
- CreateTimeSeriesIOdoc, [72](#)
- CreateTimeSeriesRnwReport, [73](#)
- CreateUnivarBiomarkersDoc, [73](#)
- CreateUNIVdoc, [74](#)
- CreateUnivROCTable, [74](#)
- CreateVennMetaTable, [75](#)
- CrossReferencing, [75](#)
- CVTest.LRmodel, [76](#)
- descendMin, [76](#)
- doCompoundMapping, [77](#)
- doEmblProtein2EntrezMapping, [77](#)
- doGeneIDMapping, [78](#)
- doKEGG2NameMapping, [78](#)
- doK0Filtering, [79](#)
- EBAM.A0.Init, [79](#)
- EBAM.Cmpd.Init, [80](#)
- FC.Anal.paired, [80](#)
- FC.Anal.unpaired, [81](#)
- FeatureCorrelation, [81](#)
- FilterVariable, [82](#)
- findEqualGreaterM, [82](#)
- FisherLSD, [83](#)
- genLogisticRegMdl, [83](#)
- Get.asca.tss, [84](#)
- Get.bwss, [84](#)
- Get.ConcRef, [85](#)
- Get.Leverage, [85](#)
- Get.pAUC, [86](#)
- Get.pred, [86](#)
- Get.rpart.summary, [87](#)
- Get.tss, [87](#)
- Get.VIP, [88](#)
- GetAbundanceLabel, [88](#)
- GetAccuracyInfo, [89](#)
- GetAllDataNames, [89](#)
- GetAllKMClusterMembers, [89](#)
- GetAllSOMClusterMembers, [90](#)
- GetCandidateList, [90](#)
- GetCircleInfo, [91](#)
- GetCIs, [91](#)
- GetCMD, [92](#)

GetConvertFullPath, 92
getDataFromTextArea, 93
GetExtendRange, 93
GetFC, 94
GetFeatureNumbers, 94
GetFinalNameMap, 95
GetFisherPvalue, 95
GetHTMLMetSet, 96
GetHTMLPathSet, 96
GetImpFeatureMat, 97
GetKEGGNodeInfo, 97
GetKMClusterMembers, 98
GetLassoFreqs, 98
GetLimmaResTable, 99
GetMapTable, 99
GetMaxPCAComp, 99
GetMeanROC, 100
GetMetaResultMatrix, 100
GetMetaSigHitsTable, 101
GetMetSetName, 101
GetMsetLibCheckMsg, 102
GetMsetLibSearchResult, 102
GetMsetNames, 103
GetNetworkGeneMappingResultTable, 103
GetNewSampleNames, 104
GetORA.pathNames, 104
GetORA.smpdbIDs, 105
GetORATable, 105
GetQEA.pathNames, 105
GetQEATable, 106
GetRCommandHistory, 106
GetRFConf.Table, 106
GetRFConfMat, 107
GetRFOOB, 107
GetRFSigMat, 108
GetROC.coords, 108
GetROCLassoFreq, 109
GetROCTtestP, 109
GetSampleSizeLadder, 110
GetSelectedDataNames, 110
GetSelectedDataNumber, 110
GetSigTable, 111
GetSigTable.Anova, 111
GetSigTable.Aov2, 112
GetSigTable.ASCA, 112
GetSigTable.Corr, 113
GetSigTable.EBAM, 113
GetSigTable.FC, 113
GetSigTable.MB, 114
GetSigTable.RF, 114
GetSigTable.SAM, 114
GetSigTable.SVM, 115
GetSigTable.TT, 115
GetSigTable.Volcano, 115
GetSOMClusterMembers, 116
GetSSPTable, 116
GetSuggestedSAMDelta, 117
GetSVMSigMat, 117
GetTopInx, 118
GetTrainTestSplitMat, 118
GetTtestRes, 119
GetTTSigMat, 119
GetUnivReport, 120
GetVariableLabel, 120
GetVennGeneNames, 121
GetXYCluster, 121
GroupPeakList, 122

heckbert, 122
HMDBID2KEGGID, 123
HMDBID2Name, 123

ImputeVar, 124
InitDataObjects, 124
InitPowerAnal, 125
InitStatAnalMode, 125
InitTimeSeriesAnal, 126
iPCA.Anal, 126
isEmptyMatrix, 127
IsSmallSmpSize, 127
IsSpectraProcessingOK, 128

KEGGID2HMDBID, 128
KEGGID2Name, 129
KEGGPATHID2SMPDBIDs, 129
Kmeans.Anal, 130
kwtest, 130

LoadKEGGKO_lib, 131
LoadKEGGLib, 131
LoadMsetLib, 132
LoadSmpLib, 132
LogNorm, 133
LSD.test, 133

make_cpdlist, 134
map, 134

- MapCmpd2KEGGNodes, 135
- MapK02KEGGEEdges, 135
- Match.Pattern, 136
- MergeDatasets, 136
- MergeDuplicates, 137
- MetaboliteMappingExact, 137
- MSspec.fillPeaks, 138
- MSspec.rtCorrection, 138
- multi.stat, 139

- nearZeroVar, 255
- Normalization, 139

- OPLSR.Anal, 140

- parseFisher, 140
- parseTukey, 141
- PathMapping, 141
- PCA.Anal, 142
- PCA.Flip, 142
- PCA.GENES, 143
- Perform.ASCA, 143
- Perform.ASCA.permute, 144
- Perform.Permut, 144
- Perform.permutation, 145
- Perform.UnivROC, 145
- PerformApproxMatch, 146
- PerformBatchCorrection, 146
- PerformCV.explore, 147
- PerformCV.test, 148
- PerformDetailMatch, 148
- PerformEachDEAnal, 149
- PerformGeneAnnotation, 149
- PerformIndNormalization, 150
- PerformIntegCmpdMapping, 150
- PerformIntegGeneMapping, 151
- PerformIntegPathwayAnalysis, 151
- PerformK0EnrichAnalysis_K001100, 152
- PerformK0EnrichAnalysis_List, 152
- PerformLimmaDE, 153
- PerformMapping, 153
- performMB, 154
- PerformMetaMerge, 154
- PerformMultiMatch, 155
- PerformMummichog, 155
- PerformMummichogPermutations, 156
- PerformPowerProfiling, 156
- PerformPvalCombination, 157
- PerformVoteCounting, 157

- Plot.Permutation, 158
- PlotAccuracy, 158
- PlotANOVA, 159
- PlotANOVA2, 160
- PlotASCA.Permutation, 160
- PlotAscaImpVar, 161
- PlotASCAModel, 162
- PlotCmpdSummary, 162
- PlotCmpdView, 163
- PlotConcRange, 164
- PlotCorr, 164
- PlotCorrHeatMap, 165
- PlotDetailROC, 166
- PlotEBAM.A0, 167
- PlotEBAM.Cmpd, 167
- PlotEnrichNet.Overview, 168
- PlotFC, 169
- PlotHCTree, 169
- PlotHeatMap, 170
- PlotHeatMap2, 171
- PlotImpVar, 172
- PlotImpVars, 172
- PlotInmexGraph, 173
- PlotInmexPath, 174
- PlotInteraction, 174
- PlotKEGGPath, 175
- PlotKmeans, 175
- PlotLoadingCmpd, 176
- PlotMBTimeProfile, 177
- PlotMetaVenn, 177
- PlotMetPath, 178
- PlotModelScree, 178
- PlotMS.RT, 179
- PlotMSEA.Overview, 179
- PlotNormSummary, 180
- PlotOPLS.MDL, 180
- PlotOPLS.Permutation, 181
- PlotOPLS.Splot, 182
- PlotOPLS2DScore, 182
- PlotORA, 183
- PlotPathSummary, 184
- PlotPCA.overview, 184
- PlotPCA2DScore, 185
- PlotPCA3DScore, 186
- PlotPCA3DScore_orig, 186
- PlotPCABiplot, 187
- PlotPCALoading, 188
- PlotPCAPairSummary, 189

- PlotPCAScree, [189](#)
- PlotPLS.Classification, [190](#)
- PlotPLS.Imp, [191](#)
- PlotPLS.Permutation, [191](#)
- PlotPLS2DScore, [192](#)
- PlotPLS3DScore, [193](#)
- PlotPLS3DScore_orig, [194](#)
- PlotPLSLoading, [195](#)
- PlotPLSPairSummary, [196](#)
- PlotPowerEffectSize, [196](#)
- PlotPowerProfile, [197](#)
- PlotPowerStat, [198](#)
- PlotProbView, [198](#)
- PlotProbViewTest, [199](#)
- plotProfile, [200](#)
- PlotQEA.MetSet, [200](#)
- PlotQEA.Overview, [201](#)
- PlotRF.Classify, [201](#)
- PlotRF.Outlier, [202](#)
- PlotRF.VIP, [203](#)
- PlotROC.LRmodel, [203](#)
- PlotROCMulti, [204](#)
- PlotROCTest, [205](#)
- PlotRSVM.Classification, [206](#)
- PlotRSVM.Cmpd, [206](#)
- PlotSAM.Cmpd, [207](#)
- PlotSAM.FDR, [208](#)
- PlotSampleNormSummary, [208](#)
- PlotSelectedFeature, [209](#)
- PlotSigVar, [210](#)
- PlotSOM, [210](#)
- PlotSPLS2DScore, [211](#)
- PlotSPLS3DScore, [212](#)
- PlotSPLSDA.Classification, [212](#)
- PlotSPLSLoading, [213](#)
- PlotSPLSPairSummary, [214](#)
- PlotSubHeatMap, [214](#)
- PlotTestAccuracy, [215](#)
- PlotTT, [216](#)
- PlotVolcano, [217](#)
- PLSDA.CV, [217](#)
- PLSDA.Permut, [218](#)
- PLSR.Anal, [218](#)
- Predict.class, [219](#)
- PrepareIntegData, [219](#)
- PrepareNetworkData, [220](#)
- PreparePermResult, [220](#)
- PrepareQueryJson, [221](#)
- PrepareROCData, [221](#)
- PrepareROCDetails, [222](#)
- PrepareVennData, [222](#)
- RankFeatures, [223](#)
- Read.BatchCSVdata, [223](#)
- Read.MSspec, [224](#)
- Read.PeakList, [224](#)
- Read.PeakListData, [225](#)
- Read.TextData, [225](#)
- ReadIndData, [226](#)
- ReadPairFile, [226](#)
- RecordRCommand, [227](#)
- rectUnique, [227](#)
- RegisterData, [228](#)
- RemoveCmpd, [228](#)
- RemoveData, [229](#)
- RemoveDuplicates, [229](#)
- RemoveFile, [230](#)
- RemoveFolder, [230](#)
- RemoveGene, [231](#)
- RemoveMissingPercent, [231](#)
- ReplaceMin, [232](#)
- RerenderKEGGGraph, [232](#)
- RerenderMetPAGraph, [233](#)
- ResetCustomCmpds, [233](#)
- RF.Anal, [234](#)
- ROCPredSamplesTable, [234](#)
- RSVM, [235](#)
- RSVM.Anal, [235](#)
- SAM.Anal, [236](#)
- SanityCheckData, [236](#)
- SanityCheckIndData, [237](#)
- SanityCheckMummichogData, [237](#)
- saveNetworkInSIF, [238](#)
- SaveTransformedData, [238](#)
- SearchByCompound, [239](#)
- SearchByName, [239](#)
- SearchCompoundLib, [240](#)
- SearchMsetLibraries, [240](#)
- SearchNetDB, [241](#)
- SelectMultiData, [241](#)
- SetAnalysisMode, [242](#)
- SetBarParams, [242](#)
- SetCachexiaSetUsed, [243](#)
- SetCandidate, [243](#)
- SetCurrentGroups, [244](#)
- SetCurrentMsetLib, [244](#)

SetCustomData, [245](#)
SetDesignType, [245](#)
SetEBAMSigMat, [246](#)
SetKEGG.PathLib, [246](#)
SetMass.PathLib, [247](#)
SetMetabolomeFilter, [247](#)
SetOrganism, [248](#)
SetPeakList.GroupValues, [248](#)
SetSAMSigMat, [248](#)
Setup.BiofluidType, [249](#)
Setup.ConcData, [249](#)
Setup.HMDBReferenceMetabolome, [250](#)
Setup.KEGGReferenceMetabolome, [250](#)
Setup.MapData, [251](#)
Setup.UserMsetLibData, [251](#)
SetupMSdataMatrix, [252](#)
SetupSMPDBLinks, [252](#)
SOM.Anal, [253](#)
sparse.mint.block_iteration, [253](#)
spllda, [254](#)
SPLSR.Anal, [255](#)
SumNorm, [256](#)

template.match, [256](#)
Ttests.Anal, [257](#)

UnzipUploadedFile, [257](#)
UpdateFeatureItems, [258](#)
UpdateGroupItems, [258](#)
UpdateIntegPathwayAnalysis, [259](#)
UpdateMummichogParameters, [259](#)
UpdateSampleItems, [260](#)
usr2png, [261](#)

Volcano.Anal, [261](#)

XSet2MSet, [262](#)