

Chapter 7: Computations lifted to a functor context II. Monads

Part 2: Laws and structure of semimonads

Sergei Winitzki

Academy by the Bay

2018-03-11

Semimonad laws I: The intuitions

What properties of functor block programs do we expect to have?

- In $x \leftarrow c$, the value of x will *go over items* held in container c
- Manipulating items in container is followed by a generator:

$x \leftarrow \text{cont1}$	$y \leftarrow \text{cont1}$
$y = f(x)$	$\quad .\text{map}(x \Rightarrow f(x))$
$z \leftarrow \text{cont2}(y)$	$z \leftarrow \text{cont2}(y)$

$\text{cont1.flatMap}(x \Rightarrow \text{cont2}(f(x))) = \text{cont1.map}(f).\text{flatMap}(y \Rightarrow \text{cont2}(y))$

- Manipulating items in container is preceded by a generator:

$x \leftarrow \text{cont1}$	$x \leftarrow \text{cont1}$
$y \leftarrow \text{cont2}(x)$	$z \leftarrow \text{cont2}(x)$
$z = f(y)$	$\quad .\text{map}(f)$

$\text{cont1.flatMap}(\text{cont2}).\text{map}(f) = \text{cont1.flatMap}(x \Rightarrow \text{cont2}(x).\text{map}(f))$

- After $x \leftarrow \text{cont}$, further computations will use *all those* x

$x \leftarrow \text{cont}$	$y \leftarrow \text{for } \{ x \leftarrow \text{cont}$
$y \leftarrow p(x)$	$\quad yy \leftarrow p(x) \} \text{ yield } yy$
$z \leftarrow \text{cont2}(y)$	$z \leftarrow \text{cont2}(y)$

$\text{cont.flatMap}(x \Rightarrow p(x).\text{flatMap}(\text{cont2})) = \text{cont.flatMap}(p).\text{flatMap}(\text{cont2})$

Semimonad laws II: The laws for `flatMap`

To get a more concise notation, use `flm` instead of `flatMap`

A **semimonad** S^A has $\text{flm}^{[S, A, B]} : (A \Rightarrow S^B) \Rightarrow S^A \Rightarrow S^B$ with 3 laws:

❶ $\text{flm} (f^{A \Rightarrow B} \circ g^{B \Rightarrow S^C}) = \text{fmap } f \circ \text{flm } g$ (naturality in A)

$$\begin{array}{ccc} & S^B & \\ \text{fmap } f^{A \Rightarrow B} \nearrow & & \searrow \text{flm } g^{B \Rightarrow S^C} \\ S^A & \xRightarrow{\text{flm } (f^{A \Rightarrow B} \circ g^{B \Rightarrow S^C})} & S^C \end{array}$$

❷ $\text{flm} (f^{A \Rightarrow S^B} \circ \text{fmap } g^{B \Rightarrow C}) = \text{flm } f \circ \text{fmap } g$ (naturality in B)

$$\begin{array}{ccc} & S^B & \\ \text{flm } f^{A \Rightarrow S^B} \nearrow & & \searrow \text{fmap } g^{B \Rightarrow C} \\ S^A & \xRightarrow{\text{flm } (f^{A \Rightarrow S^B} \circ \text{fmap } g^{B \Rightarrow C})} & S^C \end{array}$$

❸ $\text{flm} (f^{A \Rightarrow S^B} \circ \text{flm } g^{B \Rightarrow S^C}) = \text{flm } f \circ \text{flm } g$ (associativity)

$$\begin{array}{ccc} & S^B & \\ \text{flm } f^{A \Rightarrow S^B} \nearrow & & \searrow \text{flm } g^{B \Rightarrow S^C} \\ S^A & \xRightarrow{\text{flm } (f^{A \Rightarrow S^B} \circ \text{flm } g^{B \Rightarrow S^C})} & S^C \end{array}$$

Is there a shorter formulation of the laws?

Semimonad laws III: The laws for `flatten`

The methods `flatten` (denoted by `ftn`) and `flatMap` are equivalent:

$$\text{ftn}^{[S,A]} : S^{S^A} \Rightarrow S^A = \text{flm}^{[S,S^A,A]}(m^{S^A} \Rightarrow m)$$

$$\text{flm}(f^{A \Rightarrow S^B}) = \text{fmap } f \circ \text{ftn}$$

A commutative triangle diagram. The top-left node is S^A , the top-right node is S^{S^B} , and the bottom-right node is S^B . An arrow labeled $\text{fmap } f^{A \Rightarrow S^B}$ points from S^A to S^{S^B} . An arrow labeled ftn points from S^{S^B} to S^B . A bottom arrow labeled $\text{flm}(f^{A \Rightarrow S^B})$ points from S^A to S^B .

It turns out that `flatten` has only 2 laws:

- ❶ $\text{fmap}(\text{fmap } f^{A \Rightarrow B}) \circ \text{ftn}^{[S,B]} = \text{ftn}^{[S,A]} \circ \text{fmap } f$ (naturality)

A commutative diagram with four nodes. The top-left node is S^{S^A} , the top-right node is S^{S^B} , the bottom-left node is S^A , and the bottom-right node is S^B . An arrow labeled $\text{fmap}(\text{fmap } f^{A \Rightarrow B})$ points from S^{S^A} to S^{S^B} . An arrow labeled $\text{ftn}^{[S,B]}$ points from S^{S^B} to S^B . An arrow labeled $\text{ftn}^{[S,A]}$ points from S^{S^A} to S^A . An arrow labeled $\text{fmap } f^{A \Rightarrow B}$ points from S^A to S^B .

- ❷ $\text{fmap}(\text{ftn}^{[S,A]}) \circ \text{ftn}^{[S,S^A]} = \text{ftn}^{[S,S^A]} \circ \text{ftn}^{[S,A]}$ (associativity)

A commutative diagram with four nodes. The top-left node is $S^{S^{S^A}}$, the top-right node is S^{S^A} , the bottom-left node is S^{S^A} , and the bottom-right node is S^A . An arrow labeled $\text{fmap}(\text{ftn}^{[S,A]})$ points from $S^{S^{S^A}}$ to S^{S^A} . An arrow labeled $\text{ftn}^{[S,A]}$ points from S^{S^A} to S^A . An arrow labeled $\text{ftn}^{[S,S^A]}$ points from $S^{S^{S^A}}$ to S^{S^A} . An arrow labeled $\text{ftn}^{[S,A]}$ points from S^{S^A} to S^A .

Equivalence of a natural transformation and a “lifting”

- Equivalence of flm and ftn : $\text{ftn} = \text{flm}(\text{id})$; $\text{flm } f = \text{fmap } f \circ \text{ftn}$
- We saw this before: $\text{deflate} = \text{fmapOpt}(\text{id})$; $\text{fmapOpt } f = \text{fmap } f \circ \text{deflate}$
 - ▶ Is there a general pattern where two such functions are equivalent?
- Let $\text{tr} : F^{G^A} \Rightarrow F^A$ be a natural transformation (F and G are functors)
- Define $\text{ftr} : (A \Rightarrow G^B) \Rightarrow F^A \Rightarrow F^B$ by $\text{ftr } f = \text{fmap } f \circ \text{tr}$
- It follows that $\text{tr} = \text{ftr}(\text{id})$, and we have equivalence between tr and ftr :

$$\text{tr} : F^{G^A} \Rightarrow F^A = \text{ftr}(m^{G^A} \Rightarrow m)$$

$$\text{ftr}(f^{A \Rightarrow G^B}) = \text{fmap } f \circ \text{tr}$$

A commutative triangle diagram illustrating the relationship between functors F and G . The top vertex is F^{G^B} . The bottom-left vertex is F^A . The bottom-right vertex is F^B . An arrow labeled $\text{fmap } f^{A \Rightarrow G^B}$ points from F^A to F^{G^B} . An arrow labeled tr points from F^{G^B} to F^B . A long arrow labeled $\text{ftr}(f^{A \Rightarrow G^B})$ points directly from F^A to F^B , representing the composition of the other two arrows.

- An automatic law for ftr (“naturality in A ”) follows from the definition:
 $\text{fmap } g \circ \text{ftr } f = \text{fmap } g \circ \text{fmap } f \circ \text{tr} = \text{fmap}(g \circ f) \circ \text{tr} = \text{ftr}(g \circ f)$
 - ▶ This is why tr has *one law fewer* than ftr
- To demonstrate equivalence in the direction $\text{ftr} \rightarrow \text{tr}$: start with an arbitrary ftr satisfying “naturality in A ”, then obtain $\text{tr} = \text{ftr}(\text{id})$ from it, then verify $\text{ftr } f = \text{fmap } f \circ \text{tr}$ with that tr : $\text{fmap } f \circ \text{ftr}(\text{id}) = \text{ftr}(f \circ \text{id}) = \text{ftr } f$

Semimonad laws IV: Deriving the laws for `flatten`

Denote for brevity $q^\uparrow \equiv \text{fmap}^{[S]} q$ for any function q

Express $\text{flm } f = f^\uparrow \circ \text{ftn}$ and substitute that into flm 's 3 laws:

- ❶ $\text{flm } (f \circ g) = f^\uparrow \circ \text{flm } g$ gives $(f \circ g)^\uparrow \circ \text{ftn} = f^\uparrow \circ g^\uparrow \circ \text{ftn}$
– this law holds automatically due to functor composition law
 - ❷ $\text{flm } (f \circ g^\uparrow) = \text{flm } f \circ g^\uparrow$ gives $(f \circ h)^\uparrow \circ \text{ftn} = f^\uparrow \circ \text{ftn} \circ h$;
using the functor composition law, we reduce this to $h^\uparrow \circ \text{ftn} = \text{ftn} \circ h$ – this is the naturality law
 - ❸ $\text{flm } (f \circ \text{flm } g) = \text{flm } f \circ \text{flm } g$ with functor composition law gives $f^\uparrow \circ g^{\uparrow\uparrow} \circ \text{ftn}^\uparrow \circ \text{ftn} = f^\uparrow \circ \text{ftn} \circ g^\uparrow \circ \text{ftn}$; using ftn 's naturality and omitting the common factor $f^\uparrow \circ g^{\uparrow\uparrow}$, we get $\text{ftn}^\uparrow \circ \text{ftn} = \text{ftn} \circ \text{ftn}$ – associativity law
- `flatten` has the simplest type signature *and* the fewest laws
 - It is usually easy to check naturality!
 - ▶ **Parametricity theorem:** Any *pure, fully parametric* code for a function of type $F^A \Rightarrow G^A$ will implement a natural transformation
 - Checking `flatten`'s associativity needs *a lot* more work!

The `cats` library has a `FlatMap` type class, defining `flatten` via `flatMap`

Checking the associativity law for standard monads

- Implement `flatten` for these functors and check the laws (see code):
 - ▶ `Option` monad: $F^A \equiv 1 + A$; $\text{ftn} : 1 + (1 + A) \Rightarrow 1 + A$
 - ▶ `Either` monad: $F^A \equiv Z + A$; $\text{ftn} : Z + (Z + A) \Rightarrow Z + A$
 - ▶ `List` monad: $F^A \equiv \text{List}^A$; $\text{ftn} : \text{List}^{\text{List}^A} \Rightarrow \text{List}^A$
 - ▶ `Writer` monad: $F^A \equiv A \times W$; $\text{ftn} : (A \times W) \times W \Rightarrow A \times W$
 - ▶ `Reader` monad: $F^A \equiv R \Rightarrow A$; $\text{ftn} : (R \Rightarrow (R \Rightarrow A)) \Rightarrow R \Rightarrow A$
 - ▶ `State`: $F^A \equiv S \Rightarrow A \times S$; $\text{ftn} : (S \Rightarrow (S \Rightarrow A \times S)) \times S \Rightarrow S \Rightarrow A \times S$
 - ▶ `Continuation` monad: $F^A \equiv (A \Rightarrow R) \Rightarrow R$;
 $\text{ftn} : (((A \Rightarrow R) \Rightarrow R) \Rightarrow R) \Rightarrow (A \Rightarrow R) \Rightarrow R$
- Code implementing these `flatten` functions is *fully parametric* in A
 - ▶ Naturality of these functions follows from parametricity theorem
 - ▶ Associativity needs to be checked for each monad!
- Example of a useful semimonad that is *not* a full monad:
 - ▶ $F^A \equiv A \times V \times W$; $\text{ftn}((a \times v_1 \times w_1) \times v_2 \times w_2) = a \times v_1 \times w_2$
- Examples of *non-associative* (i.e. wrong) implementations of `flatten`:
 - ▶ $F^A \equiv A \times W \times W$; $\text{ftn}((a \times v_1 \times v_2) \times w_1 \times w_2) = a \times w_2 \times w_1$
 - ▶ $F^A \equiv \text{List}^A$, but `flatten` concatenates the nested lists in reverse order

Motivation for monads

- Monads represent values with a “special computational context”
- Specific monads will have methods to create various contexts
- Monadic composition will “combine” the contexts associatively
- It is generally useful to have an “empty context” available

$$\text{pure} : A \Rightarrow M^A$$

- Combining empty context with another context works as a no-op
- Empty context is followed by a generator:

`y ← pure(x)`

`y = x`

`z ← cont(y)`

`z ← cont(y)`

`pure(x).flatMap(y ⇒ cont(y)) = cont(x)`

`pure ∘ flm f = f` – left identity

- Empty context is preceded by a generator:

`x ← cont`

`x ← cont`

`y ← pure(x)`


`y = x`

`cont.flatMap(x ⇒ pure(x)) = cont`


`flm (pure) = id` – right identity

The monad laws formulated in terms of `pure` and `flatten`


- Naturality law for `pure`: $f \circ \text{pure} = \text{pure} \circ f^\uparrow$



- Left identity: $\text{pure} \circ \text{flm } f = \text{pure} \circ f^\uparrow \circ \text{ftn} = f \circ \text{pure} \circ \text{ftn} = f$ requires that $\text{pure} \circ \text{ftn} = \text{id}$ (both sides applied to S^A)



- Right identity: $\text{flm}(\text{pure}) = \text{pure}^\uparrow \circ \text{ftn} = \text{id}$



Formulating laws via Kleisli functions

- Recall: we formulated the laws of filterables via `fmapOpt`
 - $\text{fmapOpt} : (A \Rightarrow 1 + B) \Rightarrow S^A \Rightarrow S^B$
- And then we had to compose functions of types $A \Rightarrow 1 + B$ with \diamond_{Opt}
- Here we have $\text{flm} : (A \Rightarrow S^B) \Rightarrow S^A \Rightarrow S^B$ instead of `fmapOpt`
- Can we compose **Kleisli functions** with “twisted” types $A \Rightarrow S^B$?
- Use flm to define **Kleisli composition**: $f^{A \Rightarrow S^B} \diamond g^{B \Rightarrow S^C} \equiv f \circ \text{flm } g$
- Define **Kleisli identity** id_\diamond of type $A \Rightarrow S^A$ as $\text{id}_\diamond \equiv \text{pure}$
- Composition law: $\text{flm}(f \diamond g) = \text{flm } f \circ \text{flm } g$ (same as for `fmapOpt`)
 - Shows that `flatMap` is a “lifting” of $A \Rightarrow S^B$ to $S^A \Rightarrow S^B$
- These laws are similar to functor “lifting” laws...
 - except that \diamond is used for composing Kleisli functions
- What are the properties of \diamond ?
 - Exactly similar to the properties of function composition $f \circ g$

Reformulate flm ’s laws in terms of the \diamond operation:

- flm ’s left and right identity laws: $\text{pure} \diamond f = f$ and $f \diamond \text{pure} = f$
- Associativity law: $(f \diamond g) \diamond h = f \diamond (g \diamond h)$
 - Follows from the flm law: $f \circ \text{flm}(g \circ \text{flm } h) = f \circ \text{flm } g \circ \text{flm } h$

From Kleisli back to `flatMap`

Compare different “liftings” seen so far:

Category	Function type	Identity	Composition
plain functions	$A \Rightarrow B$	$\text{id} : A \Rightarrow A$	$f^{A \Rightarrow B} \circ g^{B \Rightarrow C}$
lifted to F	$F^A \Rightarrow F^B$	$\text{id} : F^A \Rightarrow F^A$	$f^{F^A \Rightarrow F^B} \circ g^{F^B \Rightarrow F^C}$
Kleisli over F	$A \Rightarrow F^B$	$\text{pure} : A \Rightarrow F^A$	$f^{A \Rightarrow F^B} \diamond g^{B \Rightarrow F^C}$

Category axioms: identity and associativity for composition

General **functor**: a “lifting” maps functions from one category to another

- Functor laws: “lifting” must preserve identity and composition

Reformulate `map` and `flatMap` in terms of the \diamond operation:

- Define `flatMap` through Kleisli composition: $\text{flm } f^{A \Rightarrow S^B} \equiv \text{id}^{S^A \Rightarrow S^A} \diamond f$
- Define `flatten` through Kleisli: $\text{ftn} \equiv \text{id}^{S^{S^A} \Rightarrow S^{S^A}} \diamond \text{id}^{S^A \Rightarrow S^A}$
- Express `fmap` through Kleisli: $\text{fmap } f \equiv (\text{fmap id}) \diamond (f \circ \text{pure})$
- Need two additional laws to connect \diamond and \circ :
 - ▶ Left naturality: $f^{A \Rightarrow B} \circ g^{B \Rightarrow S^C} = (f \circ \text{pure}) \diamond g$
 - ▶ Right naturality: $f^{A \Rightarrow B} \circ \text{fmap } g^{B \Rightarrow S^C} = f \diamond (g \circ \text{pure})$

★ With these laws, monad laws follow from category axioms for Kleisli

Structure of semigroups and monoids

- Semimonad contexts are combined associatively, as in a semigroup
- A full monad includes an “empty” context, i.e. the identity element
- Semigroup with an identity element is a monoid

Some constructions of semigroups and monoids:

- 1 Any type Z is a semigroup with operation $z_1 \circledast z_2 = z_1$ (or z_2)
- 2 $1 + S$ is a monoid if S is (at least) a semigroup
- 3 List^A is a monoid (for any type A), also Seq^A etc.
- 4 The function type $A \Rightarrow A$ is a monoid (for any type A)
 - ▶ The operation $f \circledast g$ is either $f \circ g$ or $g \circ f$
- 5 Any totally ordered type is a monoid, with \circledast defined as max or min
- 6 $S_1 \times S_2$ is a semigroup (monoid) if S_1, S_2 are semigroups (monoids)
- 7 $S \times P$ is a semigroup (monoid) if S is a semigroup (monoid) such that S acts on P . (“Twisted product.”) Example: $(A \Rightarrow A) \times A$
 - ▶ The “action” is $a : S \Rightarrow P \Rightarrow P$ such that $a(s_1) \circ a(s_2) = a(s_1 \circledast s_2)$.
- 8 $Z \Rightarrow S$ is a semigroup/monoid, for any Z , if S is a semigroup/monoid
 - There are other examples: Int , String , Set^A , Akka routes, ...
 - Non-examples: trees; $S_1 + S_2$ where $S_{1,2}$ are different monoids

Structure of (semi)monads

How to recognize a (semi)monad by its type? Open question!

Intuition from `flatten`: reshuffle data in F^{F^A} to fit into F^A

Some constructions of exponential-polynomial semimonads:

- ① $F^A \equiv Z$ (constant functor) for a fixed type Z
 - ▶ For a full monad, need to choose $Z = 1$
- ② $F^A \equiv A \times G^A$ for any functor G^A (a full monad only if $G^A \equiv 1$)
- ③ $F^A \equiv Z + A \times W$ for a fixed type Z and a semigroup W
 - ▶ For a full monad, need W to be a monoid
- ④ $F^A \equiv G^{Z+A \times W}$ if $Z + A \times W$ is a (semi)monad
- ⑤ $F^A \equiv G^A \times H^A$ for any (semi)monads G^A and H^A
- ⑥ $F^A \equiv A + G^A$ for any semimonad G^A
- ⑦ $F^A \equiv A + G^{F^A}$ (recursive) for any functor G^A (**free monad** over G)
- ⑧ $F^A \equiv G^A + G^{F^A}$ (recursive) for any functor G^A (semimonad only!)
- ⑨ $F^A \equiv R \rightarrow G^A$ for any (semi)monad G^A
- ⑩ $F^A \equiv H^A \Rightarrow A \times G^A$ for any contrafunctor H^A and functor G^A
 - ▶ For a full monad, need to set $G^A \equiv 1$

Worked examples II: Constructions of filterable functors I

z

Exercises II

- 1 For an arbitrary monad M^A , show that the functor $F^A \equiv \text{Boolean} \times M^A$ can be defined as a semimonad but not a monad.
- 2 If W and R are arbitrary fixed types, which of the functors can be made into a semimonad: $F^A \equiv W \times (R \Rightarrow A)$, $G^A \equiv R \Rightarrow (W \times A)$?
- 3 Suppose a functor F^A has a natural transformation $\text{ex}^{[A]} : F^A \Rightarrow A$ that “extracts the value” from F^A . Would F^A be a semimonad if we defined `flatten` as `ftn = ex[FA]` or `ftn = fmap ex`?
- 4 A programmer implemented the `fmap` method for the type constructor $F^A \equiv A \times (A \Rightarrow Z)$ as

```
def fmap[A,B](f: A⇒B): ((A, A⇒Z)) ⇒ (B, B⇒Z) =  
  { case(a, az) ⇒ (f(a), (_: B) ⇒ az(a)) }
```

Show that this implementation fails to satisfy the functor laws.

- 5 Implement the `flatten` and `pure` methods for the type constructor $F^A \equiv 1 + A \times A$ (`type F[A] = Option[(A, A)]`) in at least two different ways, and show that the monad laws always fail.
- 6 Implement the monad methods for $F^A \equiv (Z \Rightarrow 1 + A) \times \text{List}^A$ using the known monad constructions.

(continued from the previous slide)

- 7 Check the identity laws for monad construction 6, $F^A \equiv A + G^A$, when pure_F is defined as $\text{id}^{[A]} + 0$ (given that G^A is a monad). Show that the identity laws fail if pure_F is defined as $0 + \text{pure}_G$.
- 8 Show that $F^A = (P \Rightarrow A) + (Q \Rightarrow A)$ is not a semimonad when P and Q are arbitrary, different types.