

Alponix WhatsApp Platform API

Unified Master Reference Manual & System Integration Guide

Welcome to the official unified developer documentation for the **Alponix WhatsApp Platform API**. This comprehensive technical blueprint outlines layout specifications, structural configurations, response matrices, payload schemas, security exceptions, and inbound webhook structures managed across the gateway infrastructure.

Global Configuration

Configuration Attribute	Value / Target Settings
Base Gateway URL	https://whatsapp-backend.alponix.com
Content-Type Header	application/json
Authentication Type	Custom Secure API Token Header Key

Global Request Headers

```
x-api-key: ovhRGfBdDwK68NQCBpPYeVu7SWuLLpAM7xobtNfW0qooTypSU4wPagWW1GJRqn9I
Content-Type: application/json
```

1. Authentication Templates

POST /api/v1/api-management/message-template

Handles high-priority, quick-delivery structural strings such as One-Time Passwords (OTPs) or transaction authorization pins. These requests contain structural variables only and do not support dynamic media headers.

Request Body Schema

Parameter	Type	Required	Functional Description
<code>send_to</code>	string	Yes	Recipient mobile path with country prefix code. Exclude spaces, leading zeros, or <code>+</code> signs. (e.g., <code>"447123456789"</code>).
<code>template_name</code>	string	Yes	The exact template string registered and approved within your Facebook Meta Developer Business Suite.
<code>variables</code>	object	Yes	Key-value positional parameter dictionary mapping directly to template string positions.
<code>variables."1"</code>	string	Yes	The dynamic token value to inject into placeholder string block <code>{{1}}</code> .

Payload Blueprint Example

```
{
  "send_to": "447123456789",
  "template_name": "otp_verification_1001",
  "variables": {
    "1": "756894"
  }
}
```

cURL Execution Target

```
curl -X POST 'https://whatsapp-backend.alponix.com/api/v1/api-management/message-template' --
header 'x-api-key: ovhRGfBdDwK68NQCbpPYeVu7SWuLLpAM7xobtNfw0qooTypSU4wPagWW1GJRqn9I' --header
'Content-Type: application/json' --data '{
  "send_to": "447123456789",
  "template_name": "otp_verification_1001",
  "variables": {
    "1": "756894"
  }
}'
```

2. Marketing & Utility Templates

POST /api/v1/api-management/message-template

Manages broad outbound customer journeys, promotional coupon drops, transactional invoice delivery, and delivery status milestones. The underlying execution engine processes structured array conversions sequentially (sorting variable maps numerically before passing payloads to Meta).

Header Struct Validation Environments

Depending on the designated template header requirements, supply one of the exact configurations highlighted below inside the parent `"header"` object blocks:

Case A: Dynamic IMAGE Header Configurations

The asset parameter requires a live cloud storage link inside the `url` key terminating strictly with: `png` , `jpg` , or `jpeg` .

```
{
  "send_to": "447123456789",
  "template_name": "festive_wishes_banner",
  "header": {
    "type": "IMAGE",
    "url": "https://whatsapp-alponix.s3.ap-south-1.amazonaws.com/media/banner.jpg"
  },
  "variables": {
    "1": "Alex",
    "2": "Alponix Team"
  }
}
```

Case B: Dynamic VIDEO Header Configurations

The video streaming structure strictly evaluates links provided in the `url` key to confirm a valid container suffix: `.mp4` , `.mov` , `.avi` , `.wmv` , or `.mkv` .

```
{
  "send_to": "447123456789",
  "template_name": "wishes_and_offer",
  "header": {
    "type": "VIDEO",
    "url": "https://whatsapp-alponix.s3.ap-south-1.amazonaws.com/
bb2be59d0f344b4ebc9a3553406a1ff1.mp4"
  },
  "variables": {
    "1": "Shivam",
    "2": "Alponix Corporation",
    "3": "exciting discounts"
  }
}
```

Case C: Dynamic TEXT Header Title Configurations

For standard alphanumeric dynamic titles, inject string values exclusively using the `text` parameter block.

```
{
  "send_to": "447123456789",
  "template_name": "order_delivery_status",
  "header": {
    "type": "TEXT",
    "text": "Your Order Has Shipped!"
  },
  "variables": {
    "1": "Customer Name",
    "2": "TRACK-ID-99201"
  }
}
```



3. Fetch WhatsApp Template Dropdown List

GET /api/v1/api-management/whatsapp-template-dropdown

Retrieves an index dictionary array representing all currently approved Meta templates stored in your account database layout. This utility endpoint populates application dashboard selector inputs or interface dropdown blocks.

Success Response Structure (HTTP 200 OK)

```
[
  {
    "name": "template_identifier_name",
    "category": "TEMPLATE_CATEGORY"
  }
]
```



4. Get Message Template Preview

POST /api/v1/api-management/message-template-preview

Extracts functional fields, layout formats, and placeholder parameters associated with a registered scheme design.

Note: Each template response contains a maximum of one HEADER segment inside the data array.

Request Body Schema

Parameter	Type	Required	Functional Description
template_name	string	Yes	The unique name token of the targeted template blueprint to inspect.

Isolated Template Preview Response Schemas (Documented Separately)

Type A: Rich Media (Image) Marketing Structure

```
{
  "success": "1",
  "message": "Successfully fetched template preview",
  "data": [
    {
      "type": "HEADER",
      "format": "IMAGE",
      "url": "https://storage-provider-bucket.amazonaws.com/media_resource_hash.jpg"
    },
    {
      "type": "BODY",
      "text": "Core content narrative layout string featuring dynamic body variables like {{1}}
and {{2}}",
      "placeholders": {
        "1": "sample_body_placeholder_1",
        "2": "sample_body_placeholder_2"
      }
    },
    {
      "type": "BUTTONS",
      "buttons": [
        {
          "type": "URL",
          "text": "Call to Action Label String",
          "url": "https://external-resource-link.com/path/"
        }
      ]
    }
  ]
}
```

Type B: Text Header Utility / Transactional Structure

```
{
  "success": "1",
  "message": "Successfully fetched template preview",
  "data": [
    {
      "type": "HEADER",
      "format": "TEXT",
      "text": "Header display template string featuring prefix/suffix variables like {{1}}",
      "placeholder": {
        "1": "sample_header_placeholder"
      }
    },
    {
      "type": "BODY",
      "text": "Thank you! Your order {{1}} is confirmed. We will let you know once your package is on its way.",
      "placeholders": {
        "1": "sample_order_id"
      }
    },
    {
      "type": "BUTTONS",
      "buttons": [
        {
          "type": "URL",
          "text": "Track Your Order",
          "url": "https://external-resource-link.com/order/"
        }
      ]
    }
  ]
}
```

Type C: Secure Authentication (OTP) Layout Structure

```
{
  "success": "1",
  "message": "Successfully fetched template preview",
  "data": [
    {
      "type": "BODY",
      "text": "*{{1}}* is your verification code.",
      "placeholders": {
        "1": "sample_numeric_otp"
      }
    },
    {
      "type": "BUTTONS",
      "buttons": [
        {
          "type": "URL",
          "text": "Copy code",
          "url": "https://www.whatsapp.com/otp/code/?otp_type=COPY_CODE&code=otp{{1}}",
          "example": [
            "https://www.whatsapp.com/otp/code/?otp_type=COPY_CODE&code=otp_sample"
          ]
        }
      ]
    }
  ]
}
```


5. Send Direct Text Message (Non-Template)

POST /api/v1/api-management/whatsapp-message

Dispatches unstructured, standard custom text string messages directly into an active target customer timeline sequence.

Response Definitions (Success & Server-Level Exceptions)

Success Response Structure (HTTP 201 Created)

```
{
  "success": "1",
  "message": "Message sent"
}
```

Error Response: Unauthorized / Bad Security Token (HTTP 403 Forbidden)

```
{
  "success": "-1",
  "message": "Incorrect api key"
}
```

Error Response: Expired or Non-Existent Subscription Plan (HTTP 400 Bad Request)

```
{
  "success": "-1",
  "message": "User don't have platform plans"
}
```

Error Response: Conversational Window Expired / No Customer Interaction (HTTP 400 Bad Request)

```
{
  "success": "-1",
  "message": "No active session found for this number."
}
```

Error Response: Meta Graph API Gateway Pipeline Failure (HTTP 400 Bad Request)

```
{
  "success": "-1",
  "message": "Can not send text message",
  "data": {
    "error": {
      "message": "(#131030) Wireless carrier network transmission failed.",
      "type": "OAuthException",
      "code": 131030,
      "fbtrace_id": "AMzGKh1E8_ExampleTraceID"
    }
  }
}
```

6. Inbound Webhook Notifications (Event Receiver)

The Alponix system fires an asynchronous `POST` request to your registered webhook URL whenever an inbound event occurs from an active contact stream.

System Constraints: A project account profile is strictly permitted to register a **maximum of two active webhook endpoints** simultaneously within the gateway management layer.

Isolated Webhook Payload Event Profiles (Sanitized Parameters)

Profile A: Inbound Document Attachment Event

```
{
  "name": "REDACTED_SENDER_NAME",
  "phone_number": "REDACTED_PHONE_NUMBER",
  "timestamp": "2026-05-18 08:10:34.538657+00:00",
  "message_type": "document",
  "message": "https://whatsapp-backend.alponix.com/media/chat_attachments/
JavaScriptNotesForProfessionals2_TwtF3TP.pdf"
}
```

Profile B: Inbound Raw Text Thread Event

```
{
  "name": "REDACTED_SENDER_NAME",
  "phone_number": "REDACTED_PHONE_NUMBER",
  "timestamp": "2026-05-18 08:11:45.924647+00:00",
  "message_type": "text",
  "message": "hello"
}
```

Profile C: Inbound Media Image Event

```
{
  "name": "REDACTED_SENDER_NAME",
  "phone_number": "REDACTED_PHONE_NUMBER",
  "timestamp": "2026-05-18 07:56:29.750744+00:00",
  "message_type": "image",
  "message": "https://whatsapp-backend.alponix.com/media/chat_attachments/
media_20260518_132629.jpg"
}
```



7. Engine Gateway Response & Error Validation Matrix

Success System Response (HTTP 200 OK)

Returned when core constraints are cleared, messaging system history records are committed, log tables updated, and execution dispatches safely through the Meta API cloud edge.

```
{
  "success": "1",
  "message": "Template Successfully sent.",
  "status": 200
}
```

Exception & Rejection Fault Codes (HTTP 400 Bad Request)

When payload attributes collide with validation constraints, the application processing block drops transmission and outputs descriptive dictionaries matching your backend code routines:

System Context Condition	JSON Response Data Output	Developer Resolution Guide
Missing Asset Reference URL	<pre>{"success": "-1", "message": "Provide url for the header", "status": 400}</pre>	Fired when image or video configurations are missing a live string in the "url" property.
Image Verification Failure	<pre>{"success": "-1", "message": "Provide image url for the type image.", "status": 400}</pre>	The file extension inside the target link does not match png, jpg, or jpeg.
Video Validation Failure	<pre>{"success": "-1", "message": "Provide the video url for type video", "status": 400}</pre>	The target filename payload string fails to resolve against .mp4, .mov, .avi, .wmv, or .mkv patterns.
Text Header String Blank	<pre>{"success": "-1", "message": "Provide only one value for the header for selected template.", "status": 400}</pre>	Fired when a TEXT header model is targeted but the value key remains undefined.
Meta Cloud Connection Rejection	<pre>{"success": "-1", "message": "Can't Send template Error from meta.", "status": 400}</pre>	A component structurally cleared local parameters but Facebook's remote server threw an internal deployment or billing error.
Malformed Schema Payload	<pre>{"success": "-1", "message": "Data is invalid", "status": 400}</pre>	Fallback exception triggered if incoming request properties fail overall mapping standards.