

# Review

---

王昊翔: [hxwang@scut.edu.cn](mailto:hxwang@scut.edu.cn)

School of Computer Science & Engineering ,SCUT

# Chapter 1 Introduction

---

- ☐ What is computer network?
- ☐ Network category
- ☐ Reference model
  - TCP/IP VS. OSI
  - Benefits of layered structure
  - PDU names
- ☐ Service VS. Protocol

# Chapter 2 Physical Layer

## □ Bandwidth – Fourier Series

■ Hz and bps

## □ Nyquist theorem

$$MaxDataRate = 2H \log_2 V \text{ bits / sec}$$

## □ Shannon theory

$$SNR_{dB} = 10 \log_{10} \left( \frac{S}{N} \right) \text{ dB}$$

$$MaxDataRate = H \log_2 \left( 1 + \frac{S}{N} \right) \text{ bits / sec}$$



# Chapter 2 Physical Layer(cont'd)

---

- UTP
- Copper wires and Optical fiber
- Understand modem
  - Amplitude modulation(AM)
  - Frequency modulation(FM)
  - Quadrature Phase shift keying (QPSK)

# Chapter 2 Physical Layer(cont'd)

---

- Master trunk multiplex technology
  - Frequency Division Multiplexing
  - Time Division Multiplexing
- Master **circuit-switching** ,message switching and **packet switching**
- understand mobile-phone system
  - Code division multiple Access (CDMA)

# Chapter 3 data link layer

---

## □ Master framing

- Character count(字符计数法)
- Flag bytes with byte stuffing(带字符填充的首尾界符法)
- Starting and ending flags, with bit stuffing(带位填充的首尾标志法)
- Physical layer coding violations(物理层编码违例法)

# Chapter 3 data link layer(cont'd)

---

## ❑ Master error detection and correction

### ■ Hamming distance (definition)

### ■ Error correction: hamming code

❑ Correct one bit error:  $m + r + 1 \leq 2^r$

### ■ Error detection: CRC

## ❑ The error-detecting and error-correcting properties of a code depend on its Hamming distance.

■ In order to *detect* **d** errors, we need a distance of **d+1**.

■ In order to *correct* **d** errors, we need a distance of **2d+1**

# Error correcting and detecting

---

- ❑ Hamming code
- ❑ CRC



# Chapter 3 data link layer(cont'd)

---

## □ Master 6 dll's basic protocol

- Utopia
- Stop and wait
- PAR (positive acknowledgement with retransmission ) or ARQ (automatic repeat request)
- One-bit sliding window
- Go back n
- Selective repeat
- Max window sizes!

# Chapter 4 MAC sublayer(cont'd)

---

## ☐ Multiple Access Protocols

### ■ ALOHA

#### ☐ Pure ALOHA

#### ☐ Slotted ALOHA

### ■ Carrier Sense Multiple Access Protocols

#### ☐ 1-persistent CSMA

#### ☐ Non-persistent CSMA

#### ☐ p-persistent CSMA

#### ☐ CSMA/CD (CSMA with Collision Detection)(“先听后发、边发边听”)


### ■ Ethernet and IEEE802.3

### ■ Min frame length

# Chapter 4 MAC sublayer(cont'd)


## □ Bit stream encoding methods

- Manchester Encoding
- Differential Manchester Encoding
- Question - Bit stream is **1001101001**, sketch three waves:



# The MAC address

## MAC Address Format



# Working principle of swithing

---

- ☐ Flooding
- ☐ Backward learning

# Chapter 5 network layer

---

## ☐ Routing Protocol

### ■ IGP

#### ☐ DV:RIP

#### ☐ LS:OSPF

## ☐ Routed Protocol

### ■ IPv4

### ■ IPv6

## ☐ BGP

# Routing algorithm

---

## ☐ Routing algorithm

### ■ Static routing algorithm

- ☐ **Dijkstra**

- ☐ flooding

### ■ Dynamic routing algorithm

- ☐ **DV**

- ☐ **LS**

# IPv4

---

- Main function of router
- Learn IP
  - IP packet format
  - IP address and it's classification
- Reserved IPv4 address



# Other protocol and technology

---

- Subnet and subnetting
- The idea of **CIDR**
- The principle of **NAT/PAT**

# Sup. :IPv6

---

- Advantage of IPv6
- Differences with IPv4

# Chapter 6 transport layer

---

- ☐ UDP (segment)
- ☐ TCP (segment)
- ☐ Pseudo header
- ☐ Socket



**Comparation**

# Chapter 7 Application layer

---

## □ DNS

---

□ THANKS!

□ [hxwang@scut.edu.cn](mailto:hxwang@scut.edu.cn)