

The NCAlgebra Suite

John W. Helton

Mauricio C. de Oliveira

September, 2016

Contents

I	User Guide	9
1	Changes in Version 5.0	11
2	Introduction	13
2.1	Running NCAIgebra	13
2.2	Now what?	13
2.3	Testing	14
3	Most Basic Commands	15
3.1	To Commute Or Not To Commute?	15
3.2	Transposes and Adjointes	16
3.3	Inverses	16
3.4	Expand and Collect	17
3.5	Replace	17
3.6	Rationals and Simplification	17
3.7	Calculus	18
3.8	Matrices	18
4	Things you can do with NCAIgebra and NCGB	19
4.1	Noncommutative Inequalities	19
4.2	Linear Systems and Control	19
4.3	Semidefinite Programming	19
4.4	NonCommutative Groebner Bases	19
4.5	Groups	20
4.6	NCGBX	20
II	Reference Manual	21
5	Introduction	23
6	NonCommutativeMultiply	25
6.1	aj	25
6.2	co	25
6.3	Id	26
6.4	inv	26
6.5	rt	26
6.6	tp	26
6.7	CommutativeQ	26
6.8	NonCommutativeQ	26
6.9	SetCommutative	26
6.10	SetNonCommutative	26

6.11	Commutative	27
6.12	CommuteEverything	27
6.13	BeginCommuteEverything	27
6.14	EndCommuteEverything	27
6.15	ExpandNonCommutativeMultiply	27
7	NCCollect	29
7.1	NCCollect	29
7.1.1	Notes	29
7.2	NCCollectSelfAdjoint	30
7.3	NCCollectSymmetric	30
7.4	NCStrongCollect	30
7.5	NCStrongCollectSelfAdjoint	30
7.6	NCStrongCollectSymmetric	30
7.7	NCCompose	31
7.8	NCDecompose	31
7.9	NCTermsOfDegree	31
8	NCSimplifyRational	33
8.1	NCNormalizeInverse	34
8.2	NCSimplifyRational	34
8.3	NCSimplifyRationalSinglePass	34
8.4	NCPreSimplifyRational	34
8.5	NCPreSimplifyRationalSinglePass	35
9	NCDiff	37
9.1	NCDirectionalD	37
9.2	NCGrad	37
9.3	NCHessian	38
9.4	DirectionalD	39
9.5	NCIntegrate	39
10	NCReplace	41
10.1	NCReplace	41
10.2	NCReplaceAll	41
10.3	NCReplaceList	42
10.4	NCReplaceRepeated	42
10.5	NCMakeRuleSymmetric	42
10.6	NCMakeRuleSelfAdjoint	42
11	NCSelfAdjoint	43
11.1	NCSymmetricQ	43
11.2	NCSymmetricTest	43
11.3	NCSymmetricPart	44
11.4	NCSelfAdjointQ	44
11.5	NCSelfAdjointTest	44
12	NCOutput	47
12.1	NCOutputFunction	47
12.2	NCSetOutput	47
13	NCPolynomial	49
13.1	NCPolynomial	49
13.2	NCToNCPolynomial	50
13.3	NCPolynomialToNC	50

13.4	NCRationalToNCPolynomial	50
13.5	NCPCoefficients	51
13.6	NCPTermsOfDegree	51
13.7	NCPTermsOfTotalDegree	52
13.8	NCPTermsToNC	52
13.9	NCPPlus	52
13.10	NCPSort	52
13.11	NCPDecompose	53
13.12	NCPDegree	53
13.13	NCPMonomialDegree	53
13.14	NCPLinearQ	53
13.15	NCPQuadraticQ	53
13.16	NCPCompatibleQ	54
13.17	NCPSameVariablesQ	54
13.18	NCPMatrixQ	54
13.19	NCPNormalize	54
14	NCSylvester	55
14.1	NCPolynomialToNCSylvester	55
14.2	NCSylvesterToNCPolynomial	55
15	NCQuadratic	57
15.1	NCQuadratic	57
15.2	NCQuadraticMakeSymmetric	58
15.3	NCMatrixOfQuadratic	58
15.4	NCQuadraticToNCPolynomial	58
16	NCRational	59
16.1	NCRational	60
16.2	NCToNCRational	60
16.3	NCRationalToNC	60
16.4	NCRationalToCanonical	60
16.5	CanonicalToNCRational	60
16.6	NCROrder	60
16.7	NCRLinearQ	60
16.8	NCRStrictlyProperQ	60
16.9	NCRPlus	60
16.10	NCRTimes	60
16.11	NCRTranspose	61
16.12	NCRInverse	61
16.13	NCRControllableRealization	61
16.14	NCRControllableSubspace	61
16.15	NCRObservableRealization	61
16.16	NCRMinimalRealization	61
17	NCConvexity	63
17.1	NCIndependent	63
17.2	NCConvexityRegion	63
18	NCRealization	65
18.1	NCDescriptorRealization	65
18.2	NCDeterminantalRepresentationReciprocal	66
18.3	NCMatrixDescriptorRealization	66
18.4	NCMinimalDescriptorRealization	66
18.5	NCSymmetricDescriptorRealization	66

18.6	NCSymmetricDeterminantalRepresentationDirect	66
18.7	NCSymmetricDeterminantalRepresentationReciprocal	66
18.8	NCSymmetrizeMinimalDescriptorRealization	66
18.9	NonCommutativeLift	67
18.10	SignatureOfAffineTerm	67
18.11	TestDescriptorRealization	67
18.12	PinnedQ	67
18.13	PinningSpace	67
19	NCMatMult	69
19.1	tpMat	69
19.2	ajMat	69
19.3	coMat	69
19.4	MatMult	69
19.4.1	Notes	70
19.5	NCInverse	70
19.6	NCMatrixExpand	70
20	NCMatrixDecompositions	71
20.1	NCLDLDecomposition	72
20.2	NCLeftDivide	72
20.3	NCLowerTriangularSolve	72
20.4	NCLUCompletePivoting	72
20.5	NCLUDecompositionWithCompletePivoting	72
20.6	NCLUDecompositionWithPartialPivoting	72
20.7	NCLUIInverse	72
20.8	NCLUPartialPivoting	72
20.9	NCMatrixDecompositions	72
20.10	NCRightDivide	72
20.11	NCUpperTriangularSolve	72
21	MatrixDecompositions	73
21.1	LUDecompositionWithPartialPivoting	73
21.2	LUDecompositionWithCompletePivoting	74
21.3	LDLDecomposition	74
21.4	UpperTriangularSolve	75
21.5	LowerTriangularSolve	75
21.6	LUInverse	75
21.7	GetLUMatrices	76
21.8	GetLDUMatrices	76
21.9	GetDiagonal	76
21.10	LUPartialPivoting	76
21.11	LUCompletePivoting	77
22	NCUtil	79
22.1	NCConsistentQ	79
22.2	NCGrabFunctions	79
22.3	NCGrabSymbols	80
22.4	NCGrabIndeterminants	80
22.5	NCConsolidateList	80
22.6	NCLeafCount	80
22.7	NCReplaceData	81
22.8	NCToExpression	81
23	NCSDP	83

23.1	NCSDP	84
23.2	NCSDPForm	84
23.3	NCSDPDual	85
23.4	NCSDPDualForm	85
24	SDP	87
24.1	SDPMatrices	89
24.2	SDPSolve	89
24.3	SDPEval	89
24.4	SDPInner	89
24.5	SDPCheckDimensions	89
24.6	SDPDualEval	89
24.7	SDPFunctions	89
24.8	SDPPrimalEval	89
24.9	SDPScale	89
24.10	SDPSylvesterDiagonalEval	89
24.11	SDPSylvesterEval	89
25	NCPoly	91
25.1	NCPoly	92
25.2	NCPolyMonomial	92
25.3	NCPolyConstant	93
25.4	NCPolyMonomialQ	93
25.5	NCPolyDegree	93
25.6	NCPolyNumberOfVariables	93
25.7	NCPolyCoefficient	93
25.8	NCPolyGetCoefficients	94
25.9	NCPolyGetDigits	94
25.10	NCPolyGetIntegers	94
25.11	NCPolyLeadingMonomial	95
25.12	NCPolyLeadingTerm	95
25.13	NCPolyOrderType	95
25.14	NCPolyToRule	95
25.15	NCPolyDisplayOrder	96
25.16	NCPolyDisplay	96
25.17	NCPolyDivideDigits	96
25.18	NCPolyDivideLeading	96
25.19	NCPolyFullReduce	96
25.20	NCPolyNormalize	96
25.21	NCPolyProduct	96
25.22	NCPolyQuotientExpand	96
25.23	NCPolyReduce	97
25.24	NCPolySum	97
25.25	NCFromDigits	97
25.26	NCIntegerDigits	97
25.27	NCPadAndMatch	98
26	NCTest	99
26.1	NCTest	99
26.2	NCTestRun	99
26.3	NCTestSummarize	99

Part I

User Guide

Chapter 1

Changes in Version 5.0

1. Completely rewritten core handling of noncommutative expressions with significant speed gains.
2. Commands `Transform`, `Substitute`, `SubstituteSymmetric`, etc, have been replaced by the much more reliable commands in the new package `NCReplace`.
3. Modified behavior of `CommuteEverything` (see important notes in `CommuteEverything`).
4. Improvements and consolidation of NC calculus in the package `NCDiff`.
5. Added a complete set of linear algebra solvers in the new package `MatrixDecomposition` and their noncommutative versions in the new package `NCMatrixDecomposition`.
6. New algorithms for representing and operating with NC polynomials (`NCPolynomial`) and NC linear polynomials (`NCSylvester`).
7. General improvements on the Semidefinite Programming package `NCSDP`.
8. New algorithms for simplification of noncommutative rationals (`NCSimplifyRational`).

Chapter 2

Introduction

This *User Guide* attempts to document the many improvements introduced in **NCAIgebra** Version 5.0. Please be patient, as we move to incorporate the many recent changes into this document.

See Reference Manual for a detailed description of the available commands.

2.1 Running NCAIgebra

In *Mathematica* (notebook or text interface), type

```
<< NC`
```

If this step fails, your installation has problems (check out installation instructions on the main page). If your installation is succesful you will see a message like:

You are using the version of NCAIgebra which is found in:

```
/your_home_directory/NC.
```

You can now use "<< NCAIgebra`" to load NCAIgebra or "<< NCGB`" to load NCGB.

Just type

```
<< NCAIgebra`
```

to load NCAIgebra, or

```
<< NCGB`
```

to load NCAIgebra *and* NCGB.

2.2 Now what?

Basic documentation is found in the project wiki:

<https://github.com/NCAIgebra/NC/wiki>

Extensive documentation is found in the directory **DOCUMENTATION**.

You may want to try some of the several demo files in the directory **DEMOS** after installing NCAIgebra.

You can also run some tests to see if things are working fine.

2.3 Testing

Type

```
<< NCTEST
```

to test NCAgebra. Type

```
<< NCGBTEST
```

to test NCGB.

We recommend that you restart the kernel before and after running tests. Each test takes a few minutes to run.

Chapter 3

Most Basic Commands

First you must load in NCAIgebra with the following command

```
In[1] := <<NC`  
In[2] := <<NCAIgebra`
```

3.1 To Commute Or Not To Commute?

In NCAIgebra, the operator `**` denotes *noncommutative multiplication*.

At present, single-letter lower case variables are non-commutative by default and all others are commutative by default.

We consider non-commutative lower case variables in the following examples:

```
In[3] := a**b-b**a  
Out[3] = a**b-b**a  
In[4] := A**B-B**A  
Out[4] = 0  
In[5] := A**b-b**A  
Out[5] = 0
```

`CommuteEverything` temporarily makes all noncommutative symbols appearing in a given expression to behave as if they were commutative and returns the resulting commutative expression:

```
In[6] := CommuteEverything[a**b-b**a]  
Out[6] = 0  
In[7] := EndCommuteEverything[]  
In[8] := a**b-b**a  
Out[8] = a**b-b**a
```

`EndCommuteEverything` restores the original noncommutative behavior.

`SetNonCommutative` makes symbols behave permanently as noncommutative:

```
In[9] := SetNonCommutative[A,B]  
In[10] := A**B-B**A  
Out[10] = A**B-B**A  
In[11] := SetNonCommutative[A]; SetCommutative[B];  
In[12] := A**B-B**A  
Out[12] = 0
```

SNC is an alias for `SetNonCommutative`. So, SNC can be typed rather than the longer `SetNonCommutative`.

```
In[13] := SNC[A];
In[14] := A**a-a**A
Out[14] = -a**A+A**a
```

`SetCommutative` makes symbols permanently behave as commutative:

```
In[15] := SetCommutative[v];
In[16] := v**b
Out[16] = b v
```

3.2 Transposes and Adjoints

`tp[x]` denotes the transpose of symbol `x`

`aj[x]` denotes the adjoint of symbol `x`

The properties of transposes and adjoints that everyone uses constantly are built-in:

```
In[17] := tp[a**b]
Out[17] = tp[b]**tp[a]
In[18] := tp[5]
Out[18] = 5
In[19] := tp[2+3I]    (* I is the imaginary unit *)
Out[19] = 2+3 I
In[20] := tp[a]
Out[20] = tp[a]
In[21] := tp[a+b]
Out[21] = tp[a]+tp[b]
In[22] := tp[6x]
Out[22] = 6 tp[x]
In[23] := tp[tp[a]]
Out[23] = a
In[24] := aj[5]
Out[24] = 5
In[25] := aj[2+3I]
Out[25] = 2-3 I
In[26] := aj[a]
Out[26] = aj[a]
In[27] := aj[a+b]
Out[27] = aj[a]+aj[b]
In[28] := aj[6x]
Out[28] = 6 aj[x]
In[29] := aj[aj[a]]
Out[29] = a
```

3.3 Inverses

The multiplicative identity is denoted `Id` in the program. At the present time, `Id` is set to 1.

A symbol `a` may have an inverse, which will be denoted by `inv[a]`.

```
In[30] := Id
Out[30] = 1
```



```

In[31]:= inv[a**b]
Out[31]= inv[a**b]
In[32]:= inv[a]**a
Out[32]= 1
In[33]:= a**inv[a]
Out[33]= 1
In[34]:= a**b**inv[b]
Out[34]= a

```

3.4 Expand and Collect

One can collect noncommutative terms involving same powers of a symbol using `NCCollect`. `NCEExpand` expand noncommutative products.

```

In[35]:= NCEExpand[(a+b)**x]
Out[35]= a**x+b**x
In[36]:= NCCollect[a**x+b**x,x]
Out[36]= (a+b)**x
In[37]:= NCCollect[tp[x]**a**x+tp[x]**b**x+z,{x,tp[x]}]
Out[37]= z+tp[x]**(a+b)**x

```

3.5 Replace

The Mathematica substitute commands, e.g. `Replace`, `ReplaceAll (/.)` and `ReplaceRepeated (//.)`, are not reliable in `NCAgebra`, so you must use our NC versions of these commands:

```

In[38]:= NCReplace[x**a**b,a**b->c]
Out[38]= x**a**b
In[39]:= NCReplaceAll[tp[b**a]+b**a,b**a->p]
Out[39]= p+tp[a]**tp[b]

```

Use `NCMakeRuleSymmetric` and `NCMakeRuleSelfAdjoint` to automatically create symmetric and self adjoint versions of your rules:

```

In[40]:= NCReplaceAll[tp[a**b]+w+a**b,a**b->c]
Out[40]= c+w+tp[b]**tp[a]
In[41]:= NCReplaceAll[tp[a**b]+w+a**b,NCMakeRuleSymmetric[a**b->c]]
Out[41]= c+w+tp[c]

```

3.6 Rationals and Simplification

`NCSimplifyRational` attempts to simplify noncommutative rationals.

```

In[42]:= f1=1+inv[d]**c**inv[S-a]**b-inv[d]**c**inv[S-a+b**inv[d]**c]**b\
        -inv[d]**c**inv[S-a+b**inv[d]**c]**b**inv[d]**c**inv[S-a]**b
Out[42]= 1+inv[d]**c**inv[-a+S]**b-inv[d]**c**inv[-a+S+b**inv[d]**c]**b\
        -inv[d]**c**inv[-a+S+b**inv[d]**c]**b**inv[d]**c**inv[-a+S]**b
In[43]:= NCSimplifyRational[f1]
Out[43]= 1
In[44]:= f2=2inv[1+2a]**a;
In[45]:= NCSimplifyRational[f2]
Out[45]= 1-inv[1+2 a]

```

NCSR is the alias for NCSimplifyRational.

```
In[46] := f3=a**inv[1-a];
In[47] := NCSR[f3]
Out[47]= -1+inv[1-a]
In[48] := f4=inv[1-b**a]**inv[a];
In[49] := NCSR[f4]
Out[49]= inv[a]+b**inv[1-b**a]
```

3.7 Calculus

One can calculate directional derivatives with `DirectionalD` and noncommutative gradients with `NCGrad`.

```
In[50] := DirectionalD[x**x,x,h]
Out[50]= h**x+x**h
In[51] := NCGrad[tp[x]**x+tp[x]**A**x+m**x,x]
Out[51]= m+tp[x]**A+tp[x]**tp[A]+2 tp[x]
```

3.8 Matrices

NCAlgebra has many algorithms that handle matrices with noncommutative entries.

```
In[52] := m1={{a,b},{c,d}}
Out[52]= {{a,b},{c,d}}
In[53] := m2={{d,2},{e,3}}
Out[53]= {{d,2},{e,3}}
In[54] := MatMult[m1,m2]
Out[54]= {{a**d+b**e,2 a+3 b},{c**d+d**e,2 c+3 d}}
```

Chapter 4

Things you can do with NCAgebra and NCGB

In this page you will find some things that you can do with NCAgebra and NCGB.

4.1 Noncommutative Inequalities

Is a given noncommutative function *convex*? You type in a function of noncommutative variables; the command `NCConvexityRegion[Function, ListOfVariables]` tells you where the (symbolic) `Function` is *convex* in the `Variables`. This corresponds to papers of *Camino, Helton and Skelton*.

4.2 Linear Systems and Control

NCAgebra integrates with *Mathematica*'s control toolbox (version 8.0 and above) to work on noncommutative block systems, just as a human would do...

Look for `NCControl.nb` in the `NC/DEMOS` subdirectory.

4.3 Semidefinite Programming

NCAgebra now comes with a numerical solver that can compute the solution to semidefinite programs, aka linear matrix inequalities.

Look for demos in the `NC/NCSDP/DEMOS` subdirectory.

You can also find examples of systems and control linear matrix inequalities problems being manipulated and numerically solved by NCAgebra on the UCSD course webpage.

Look for the `.nb` files, starting with the file `sat5.nb` at Lecture 8.

4.4 NonCommutative Groebner Bases

NCGB Computes NonCommutative Groebner Bases and has extensive sorting and display features and algorithms for automatically discarding *redundant* polynomials, as well as *kludgy* methods for suggesting

changes of variables (which work better than one would expect).

NCGB runs in conjunction with NCAlgebra.

4.5 Groups

You can compute a complete list of rewrite rules for Groups using NCGB. See demos at <http://math.ucsd.edu/~ncalg>.

4.6 NCGBX

NCGBX is a 100% Mathematica version of our NC Groebner Basis Algorithm and does not require C/C++ code compilation.

Look for demos in the NC/NCPoly/DEMOS subdirectory of the most current distributions.

IMPORTANT: Do not load NCGB and NCGBX simultaneously.

Part II

Reference Manual

Chapter 5

Introduction

Each following chapter describes a **Package** inside *NCAIgebra*.

Packages are automatically loaded unless otherwise noted.

Chapter 6

NonCommutativeMultiply

NonCommutativeMultiply is the main package that provides noncommutative functionality to Mathematica's native `NonCommutativeMultiply` bound to the operator `**`.

Members are:

- `aj`
- `co`
- `Id`
- `inv`
- `tp`
- `rt`
- `CommutativeQ`
- `NonCommutativeQ`
- `SetCommutative`
- `SetNonCommutative`
- `Commutative`
- `CommuteEverything`
- `BeginCommuteEverything`
- `EndCommuteEverything`
- `ExpandNonCommutativeMultiply`

6.1 `aj`

`aj[expr]` is the adjoint of expression `expr`. It is a conjugate linear involution.

See also: `tp`, `co`.

6.2 `co`

`co[expr]` is the conjugate of expression `expr`. It is a linear involution.

See also: `aj`.

6.3 Id

Id is noncommutative multiplicative identity. Actually Id is now set equal 1.

6.4 inv

inv[expr] is the 2-sided inverse of expression `expr`.

6.5 rt

rt[expr] is the root of expression `expr`.

6.6 tp

tp[expr] is the tranpose of expression `expr`. It is a linear involution.

See also: aj, co.

6.7 CommutativeQ

CommutativeQ[expr] is *True* if expression `expr` is commutative (the default), and *False* if `expr` is noncommutative.

See also: SetCommutative, SetNonCommutative.

6.8 NonCommutativeQ

NonCommutativeQ[expr] is equal to Not[CommutativeQ[expr]].

See also: CommutativeQ.

6.9 SetCommutative

SetCommutative[a,b,c,...] sets all the *Symbols* a, b, c, ... to be commutative.

See also: SetNonCommutative, CommutativeQ, NonCommutativeQ.

6.10 SetNonCommutative

SetNonCommutative[a,b,c,...] sets all the *Symbols* a, b, c, ... to be noncommutative.

See also: SetCommutative, CommutativeQ, NonCommutativeQ.

6.11 Commutative

`Commutative[symbol]` is commutative even if `symbol` is noncommutative.

See also: `CommuteEverything`, `CommutativeQ`, `SetCommutative`, `SetNonCommutative`.

6.12 CommuteEverything

`CommuteEverything[expr]` is an alias for `BeginCommuteEverything`.

See also: `BeginCommuteEverything`, `Commutative`.

6.13 BeginCommuteEverything

`BeginCommuteEverything[expr]` sets all symbols appearing in `expr` as commutative so that the resulting expression contains only commutative products or inverses. It issues messages warning about which symbols have been affected.

`EndCommuteEverything[]` restores the symbols noncommutative behaviour.

`BeginCommuteEverything` answers the question *what does it sound like?*

See also: `EndCommuteEverything`, `Commutative`.

6.14 EndCommuteEverything

`EndCommuteEverything[expr]` restores noncommutative behaviour to symbols affected by `BeginCommuteEverything`.

See also: `BeginCommuteEverything`, `Commutative`.

6.15 ExpandNonCommutativeMultiply

`ExpandNonCommutativeMultiply[expr]` expands out `**`s in `expr`.

For example

```
ExpandNonCommutativeMultiply[a**(b+c)]
```

returns

```
a**b+a**c.
```

Its aliases are `NCE`, and `NCEExpand`.

Chapter 7

NCCollect

Members are:

- NCCollect
- NCCollectSelfAdjoint
- NCCollectSymmetric
- NCStrongCollect
- NCStrongCollectSelfAdjoint
- NCStrongCollectSymmetric
- NCCompose
- NCDecompose
- NCTermsOfDegree

7.1 NCCollect

`NCCollect[expr, vars]` collects terms of nc expression `expr` according to the elements of `vars` and attempts to combine them. It is weaker than `NCStrongCollect` in that only same order terms are collected together. It basically is `NCCompose[NCStrongCollect[NCDecompose]]`.

If `expr` is a rational nc expression then degree correspond to the degree of the polynomial obtained using `NCRationalToNCPolynomial`.

`NCCollect` also works with nc expressions instead of *Symbols* in `vars`. In this case nc expressions are replaced by new variables and `NCCollect` is called using the resulting expression and the newly created *Symbols*.

This command internally converts nc expressions into the special `NCPolynomial` format.

7.1.1 Notes

While `NCCollect[expr, vars]` always returns mathematically correct expressions, it may not collect `vars` from as many terms as one might think it should.

See also: `NCStrongCollect`, `NCCollectSymmetric`, `NCCollectSelfAdjoint`, `NCStrongCollectSymmetric`, `NCStrongCollectSelfAdjoint`, `NCRationalToNCPolynomial`.

7.2 NCCollectSelfAdjoint

`NCCollectSelfAdjoint[expr,vars]` allows one to collect terms of nc expression `expr` on the variables `vars` and their adjoints without writing out the adjoints.

This command internally converts nc expressions into the special `NCPolynomial` format.

See also: `NCCollect`, `NCStrongCollect`, `NCCollectSymmetric`, `NCStrongCollectSymmetric`, `NCStrongCollectSelfAdjoint`.

7.3 NCCollectSymmetric

`NCCollectSymmetric[expr,vars]` allows one to collect terms of nc expression `expr` on the variables `vars` and their transposes without writing out the transposes.

This command internally converts nc expressions into the special `NCPolynomial` format.

See also: `NCCollect`, `NCStrongCollect`, `NCCollectSelfAdjoint`, `NCStrongCollectSymmetric`, `NCStrongCollectSelfAdjoint`.

7.4 NCStrongCollect

`NCStrongCollect[expr,vars]` collects terms of expression `expr` according to the elements of `vars` and attempts to combine by association.

In the noncommutative case the Taylor expansion and so the collect function is not uniquely specified. The function `NCStrongCollect` often collects too much and while correct it may be stronger than you want.

For example, a symbol `x` will factor out of terms where it appears both linearly and quadratically thus mixing orders.

This command internally converts nc expressions into the special `NCPolynomial` format.

See also: `NCCollect`, `NCCollectSymmetric`, `NCCollectSelfAdjoint`, `NCStrongCollectSymmetric`, `NCStrongCollectSelfAdjoint`.

7.5 NCStrongCollectSelfAdjoint

`NCStrongCollectSymmetric[expr,vars]` allows one to collect terms of nc expression `expr` on the variables `vars` and their transposes without writing out the transposes.

This command internally converts nc expressions into the special `NCPolynomial` format.

See also: `NCCollect`, `NCStrongCollect`, `NCCollectSymmetric`, `NCCollectSelfAdjoint`, `NCStrongCollectSymmetric`.

7.6 NCStrongCollectSymmetric

`NCStrongCollectSymmetric[expr,vars]` allows one to collect terms of nc expression `expr` on the variables `vars` and their transposes without writing out the transposes.

This command internally converts nc expressions into the special `NCPolynomial` format.

See also: `NCCollect`, `NCStrongCollect`, `NCCollectSymmetric`, `NCCollectSelfAdjoint`, `NCStrongCollectSelfAdjoint`.

7.7 NCCompose

`NCCompose[dec]` will reassemble the terms in `dec` which were decomposed by `NCDecompose`.

`NCCompose[dec, degree]` will reassemble only the terms of degree `degree`.

The expression `NCCompose[NCDecompose[p,vars]]` will reproduce the polynomial `p`.

The expression `NCCompose[NCDecompose[p,vars], degree]` will reproduce only the terms of degree `degree`.

This command internally converts nc expressions into the special `NCPolynomial` format.

See also: `NCDecompose`, `NCPDecompose`.

7.8 NCDecompose

`NCDecompose[p,vars]` gives an association of elements of the nc polynomial `p` in variables `vars` in which elements of the same order are collected together.

`NCDecompose[p]` treats all nc letters in `p` as variables.

This command internally converts nc expressions into the special `NCPolynomial` format.

Internally `NCDecompose` uses `NCPDecompose`.

See also: `NCCompose`, `NCPDecompose`.

7.9 NCTermsOfDegree

`NCTermsOfDegree[expr,vars,indices]` returns an expression such that each term has the right number of factors of the variables in `vars`.

For example,

```
NCTermsOfDegree[x**y**x + x**w,{x,y},{2,1}]
```

returns `x**y**x` and

```
NCTermsOfDegree[x**y**x + x**w,{x,y},{1,0}]
```

return `x**w`. It returns 0 otherwise.

This command internally converts nc expressions into the special `NCPolynomial` format.

See also: `NCDecompose`, `NCPDecompose`.

Chapter 8

NCSimplifyRational

NCSimplifyRational is a package with function that simplifies noncommutative expressions and certain functions of their inverses.

NCSimplifyRational simplifies rational noncommutative expressions by repeatedly applying a set of reduction rules to the expression. **NCSimplifyRationalSinglePass** does only a single pass.

Rational expressions of the form

`inv[A + terms]`

are first normalized to

`inv[1 + terms/A]/A`

using **NCNormalizeInverse**.

For each `inv` found in expression, a custom set of rules is constructed based on its associated NC Groebner basis.

For example, if

`inv[mon1 + ... + K lead]`

where `lead` is the leading monomial with the highest degree then the following rules are generated:

Original	Transformed
<code>inv[mon1 + ... + K lead] lead</code>	<code>(1 - inv[mon1 + ... + K lead] (mon1 + ...))/K</code>
<code>lead inv[mon1 + ... + K lead]</code>	<code>(1 - (mon1 + ...) inv[mon1 + ... + K lead])/K</code>

Finally the following pattern based rules are applied:

Original	Transformed
<code>inv[a] inv[1 + K a b]</code>	<code>inv[a] - K b inv[1 + K a b]</code>
<code>inv[a] inv[1 + K a]</code>	<code>inv[a] - K inv[1 + K a]</code>
<code>inv[1 + K a b] inv[b]</code>	<code>inv[b] - K inv[1 + K a b] a</code>
<code>inv[1 + K a] inv[a]</code>	<code>inv[a] - K inv[1 + K a]</code>
<code>inv[1 + K a b] a</code>	<code>a inv[1 + K b a]</code>
<code>inv[A inv[a] + B b] inv[a]</code>	<code>(1/A) inv[1 + (B/A) a b]</code>
<code>inv[a] inv[A inv[a] + K b]</code>	<code>(1/A) inv[1 + (B/A) b a]</code>

`NCPreSimplifyRational` only applies pattern based rules from the second table above. In addition, the following two rules are applied:

Original	Transformed
$\text{inv}[1 + K a b] a b$	$(1 - \text{inv}[1 + K a b])/K$
$\text{inv}[1 + K a] a$	$(1 - \text{inv}[1 + K a])/K$
$a b \text{inv}[1 + K a b]$	$(1 - \text{inv}[1 + K a b])/K$
$a \text{inv}[1 + K a]$	$(1 - \text{inv}[1 + K a])/K$

Rules in `NCSimplifyRational` and `NCPreSimplifyRational` are applied repeatedly.

Rules in `NCSimplifyRationalSinglePass` and `NCPreSimplifyRationalSinglePass` are applied only once.

The particular ordering of monomials used by `NCSimplifyRational` is the one implied by the `NCPolynomial` format. This ordering is a variant of the deg-lex ordering where the lexical ordering is Mathematica's natural ordering.

Members are:

- `NCNormalizeInverse`
- `NCSimplifyRational`
- `NCSimplifyRationalSinglePass`
- `NCPreSimplifyRational`
- `NCPreSimplifyRationalSinglePass`

8.1 NCNormalizeInverse

`NCNormalizeInverse[expr]` transforms all rational NC expressions of the form $\text{inv}[K + b]$ into $\text{inv}[1 + (1/K) b]/K$ if A is commutative.

See also: `NCSimplifyRational`, `NCSimplifyRationalSinglePass`.

8.2 NCSimplifyRational

`NCSimplifyRational[expr]` repeatedly applies `NCSimplifyRationalSinglePass` in an attempt to simplify the rational NC expression `expr`.

See also: `NCNormalizeInverse`, `NCSimplifyRationalSinglePass`.

8.3 NCSimplifyRationalSinglePass

`NCSimplifyRationalSinglePass[expr]` applies a series of custom rules only once in an attempt to simplify the rational NC expression `expr`.

See also: `NCNormalizeInverse`, `NCSimplifyRational`.

8.4 NCPreSimplifyRational

`NCPreSimplifyRational[expr]` repeatedly applies `NCPreSimplifyRationalSinglePass` in an attempt to simplify the rational NC expression `expr`.

See also: `NCNormalizeInverse`, `NCPreSimplifyRationalSinglePass`.

8.5 `NCPreSimplifyRationalSinglePass`

`NCPreSimplifyRationalSinglePass[expr]` applies a series of custom rules only once in an attempt to simplify the rational NC expression `expr`.

See also: `NCNormalizeInverse`, `NCPreSimplifyRational`.

Chapter 9

NCDiff

NCDiff is a package containing several functions that are used in noncommutative differentiation of functions and polynomials.

Members are:

- `NCDirectionalD`
- `NCGrad`
- `NCHessian`
- `NCIntegrate`

Members being deprecated:

- `DirectionalD`

9.1 NCDirectionalD

`NCDirectionalD[expr, {var1, h1}, ...]` takes the directional derivative of expression `expr` with respect to variables `var1, var2, ...` successively in the directions `h1, h2, ...`.

For example, if:

```
expr = a**inv[1+x]**b + x**c**x
```

then

```
NCDirectionalD[expr, {x,h}]
```

returns

```
h**c**x + x**c**h - a**inv[1+x]**h**inv[1+x]**b
```

In the case of more than one variables `NCDirectionalD[expr, {x,h}, {y,k}]` takes the directional derivative of `expr` with respect to `x` in the direction `h` and with respect to `y` in the direction `k`.

See also: `NCGrad`, `NCHessian`.

9.2 NCGrad

`NCGrad[expr, var1, ...]` gives the nc gradient of the expression `expr` with respect to variables `var1, var2, ...`. If there is more than one variable then `NCGrad` returns the gradient in a list.

The transpose of the gradient of the nc expression `expr` is the derivative with respect to the direction `h` of the trace of the directional derivative of `expr` in the direction `h`.

For example, if:

```
expr = x**a**x**b + x**c**x**d
```

then its directional derivative in the direction `h` is

```
NCDirectionalD[expr, {x,h}]
```

which returns

```
h**a**x**b + x**a**h**b + h**c**x**d + x**c**h**d
```

and

```
NCGrad[expr, x]
```

returns the nc gradient

```
a**x**b + b**x**a + c**x**d + d**x**c
```

For example, if:

```
expr = x**a**x**b + x**c**y**d
```

is a function on variables `x` and `y` then

```
NCGrad[expr, x, y]
```

returns the nc gradient list

```
{a**x**b + b**x**a + c**y**d, d**x**c}
```

IMPORTANT: The expression returned by `NCGrad` is the transpose or the adjoint of the standard gradient. This is done so that no assumption on the symbols are needed. The calculated expression is correct even if symbols are self-adjoint or symmetric.

See also: `NCDirectionalD`.

9.3 NCHessian

`NCHessian[expr, {var1, h1}, ...]` takes the second directional derivative of nc expression `expr` with respect to variables `var1`, `var2`, ... successively in the directions `h1`, `h2`, ...

For example, if:

```
expr = y**inv[x]**y + x**a**x
```

then

```
NCHessian[expr, {x,h}, {y,s}]
```

returns

```
2 h**a**h + 2 s**inv[x]**s - 2 s**inv[x]**h**inv[x]**y -
2 y**inv[x]**h**inv[x]**s + 2 y**inv[x]**h**inv[x]**h**inv[x]**y
```

In the case of more than one variables `NCHessian[expr, {x,h}, {y,k}]` takes the second directional derivative of `expr` with respect to `x` in the direction `h` and with respect to `y` in the direction `k`.

See also: `NCDirectionalD`, `NCGrad`.

9.4 DirectionalD

`DirectionalD[expr,var,h]` takes the directional derivative of nc expression `expr` with respect to the single variable `var` in direction `h`.

DEPRECATION NOTICE: This syntax is limited to one variable and is being deprecated in favor of the more general syntax in `NCDirectionalD`.

See also: `NCDirectionalD`.

9.5 NCIntegrate

`NCIntegrate[expr,{var1,h1},...]` attempts to calculate the nc antiderivative of nc expression `expr` with respect to the single variable `var` in direction `h`.

For example:

```
NCIntegrate[x**h+h**x, {x,h}]
```

returns

```
x**x
```

See also: `NCDirectionalD`.

Chapter 10

NCRReplace

NCRReplace is a package containing several functions that are useful in making replacements in noncommutative expressions. It offers replacements to Mathematica's **Replace**, **ReplaceAll**, **ReplaceRepeated**, and **ReplaceList** functions.

Commands in this package replace the old **Substitute** and **Transform** family of command which are been deprecated. The new commands are much more reliable and work faster than the old commands. From the beginning, substitution was always problematic and certain patterns would be missed. We reassure that the call expression that are returned are mathematically correct but some opportunities for substitution may have been missed.

Members are:

- **NCRReplace**
- **NCRReplaceAll**
- **NCRReplaceList**
- **NCRReplaceRepeated**
- **NCMakeRuleSymmetric**
- **NCMakeRuleSelfAdjoint**

10.1 NCRReplace

NCRReplace[*expr*,*rules*] applies a rule or list of rules *rules* in an attempt to transform the entire nc expression *expr*.

NCRReplace[*expr*,*rules*,*levelspec*] applies *rules* to parts of *expr* specified by *levelspec*.

See also: **NCRReplaceAll**, **NCRReplaceList**, **NCRReplaceRepeated**.

10.2 NCRReplaceAll

NCRReplaceAll[*expr*,*rules*] applies a rule or list of rules *rules* in an attempt to transform each part of the nc expression *expr*.

See also: **NCRReplace**, **NCRReplaceList**, **NCRReplaceRepeated**.

10.3 NCReplaceList

`NCReplace[expr,rules]` attempts to transform the entire nc expression `expr` by applying a rule or list of rules `rules` in all possible ways, and returns a list of the results obtained.

`ReplaceList[expr,rules,n]` gives a list of at most `n` results.

See also: `NCReplace`, `NCReplaceAll`, `NCReplaceRepeated`.

10.4 NCReplaceRepeated

`NCReplaceRepeated[expr,rules]` repeatedly performs replacements using rule or list of rules `rules` until `expr` no longer changes.

See also: `NCReplace`, `NCReplaceAll`, `NCReplaceList`.

10.5 NCMakeRuleSymmetric

`NCMakeRuleSymmetric[rules]` add rules to transform the transpose of the left-hand side of `rules` into the transpose of the right-hand side of `rules`.

See also: `NCMakeRuleSelfAdjoint`, `NCReplace`, `NCReplaceAll`, `NCReplaceList`, `NCReplaceRepeated`.

10.6 NCMakeRuleSelfAdjoint

`NCMakeRuleSelfAdjoint[rules]` add rules to transform the adjoint of the left-hand side of `rules` into the adjoint of the right-hand side of `rules`.

See also: `NCMakeRuleSymmetric`, `NCReplace`, `NCReplaceAll`, `NCReplaceList`, `NCReplaceRepeated`.

Chapter 11

NCSelfAdjoint

Members are:

- NCSymmetricQ
- NCSymmetricTest
- NCSymmetricPart
- NCSelfAdjointQ
- NCSelfAdjointTest

11.1 NCSymmetricQ

`NCSymmetricQ[expr]` returns *True* if `expr` is symmetric, i.e. if `tp[exp] == exp`.

`NCSymmetricQ` attempts to detect symmetric variables using `NCSymmetricTest`.

See also: `NCSelfAdjointQ`, `NCSymmetricTest`.

11.2 NCSymmetricTest

`NCSymmetricTest[expr]` attempts to establish symmetry of `expr` by assuming symmetry of its variables.

`NCSymmetricTest[exp,options]` uses `options`.

`NCSymmetricTest` returns a list of two elements:

- the first element is *True* or *False* if it succeeded to prove `expr` symmetric.
- the second element is a list of the variables that were made symmetric.

The following options can be given:

- **SymmetricVariables**: list of variables that should be considered symmetric; use `All` to make all variables symmetric;
- **ExcludeVariables**: list of variables that should not be considered symmetric; use `All` to exclude all variables;
- **Strict**: treats as non-symmetric any variable that appears inside `tp`.

See also: `NCSymmetricQ`, `NCNCSelfAdjointTest`.

11.3 NCSymmetricPart

`NCSymmetricPart[expr]` returns the *symmetric part* of `expr`.

`NCSymmetricPart[exp,options]` uses `options`.

`NCSymmetricPart[expr]` returns a list of two elements:

- the first element is the *symmetric part* of `expr`;
- the second element is a list of the variables that were made symmetric.

`NCSymmetricPart[expr]` returns `{Failed, {}}` if `expr` is not symmetric.

For example:

```
{answer, symVars} = NCSymmetricPart[a ** x + x ** tp[a] + 1];
```

returns

```
answer = 2 a ** x + 1
symVars = {x}
```

The following options can be given:

- **SymmetricVariables**: list of variables that should be considered symmetric; use `All` to make all variables symmetric;
- **ExcludeVariables**: list of variables that should not be considered symmetric; use `All` to exclude all variables.
- **Strict**: treats as non-symmetric any variable that appears inside `tp`.

See also: `NCSymmetricTest`.

11.4 NCSelfAdjointQ

`NCSelfAdjointQ[expr]` returns true if `expr` is self-adjoint, i.e. if `aj[exp] == exp`.

See also: `NCSymmetricQ`, `NCSelfAdjointTest`.

11.5 NCSelfAdjointTest

`NCSelfAdjointTest[expr]` attempts to establish whether `expr` is self-adjoint by assuming that some of its variables are self-adjoint or symmetric. `NCSelfAdjointTest[expr,options]` uses `options`.

`NCSelfAdjointTest` returns a list of three elements:

- the first element is *True* or *False* if it succeeded to prove `expr` self-adjoint.
- the second element is a list of variables that were made self-adjoint.
- the third element is a list of variables that were made symmetric.

The following options can be given:

- **SelfAdjointVariables**: list of variables that should be considered self-adjoint; use `All` to make all variables self-adjoint;
- **SymmetricVariables**: list of variables that should be considered symmetric; use `All` to make all variables symmetric;
- **ExcludeVariables**: list of variables that should not be considered symmetric; use `All` to exclude all variables.
- **Strict**: treats as non-self-adjoint any variable that appears inside `aj`.

See also: `NCSelfAdjointQ`.

Chapter 12

NCOOutput

NCOOutput is a package that can be used to beautify the display of noncommutative expressions. **NCOOutput** does not alter the internal representation of NC expressions, just the way they are displayed on the screen.

Members are:

- **NCSetOutput**
- **NCOOutputFunction**

12.1 NCOOutputFunction

NCOOutputFunction[expr] returns a formatted version of the expression **expr** which will be displayed to the screen.

See also: **NCSetOutput**.

12.2 NCSetOutput

NCSetOutput[options] controls the display of expressions in a special format without affecting the internal representation of the expression.

The following **options** can be given:

- **Dot**: If *True* **x**y** is displayed as **x.y**;
- **tp**: If *True* **tp[x]** is displayed as **x** with a superscript ‘T’;
- **inv**: If *True* **inv[x]** is displayed as **x** with a superscript ‘-1’;
- **aj**: If *True* **aj[x]** is displayed as **x** with a superscript ‘*’;
- **rt**: If *True* **rt[x]** is displayed as **x** with a superscript ‘1/2’;
- **Array**: If *True* matrices are displayed using **MatrixForm**;
- **All**: Set all available options to *True* or *False*.

See also: **NCOOutputFunction**.

Chapter 13

NCPolynomial

This package contains functionality to convert an nc polynomial expression into an expanded efficient representation that can have commutative or noncommutative coefficients.

For example the polynomial

```
exp = a**x**b - 2 x**y**c**x + a**c
```

in variables x and y can be converted into an NCPolynomial using

```
p = NCToNCPolynomial[exp, {x,y}]
```

which returns

```
p = NCPolynomial[a**c, <|{x}->{{1,a,b}},{x**y,x}->{{2,1,c,1}}|>, {x,y}]
```

Members are:

- NCPolynomial
- NCToNCPolynomial
- NCPolynomialToNC
- NCRationalToNCPolynomial
- NCPCoefficients
- NCPTermsOfDegree
- NCPTermsOfTotalDegree
- NCPTermsToNC
- NCPSort
- NCPDecompose
- NCPDegree
- NCPMonomialDegree
- NCPCompatibleQ
- NCPSameVariablesQ
- NCPMatrixQ
- NCPLinearQ
- NCPQuadraticQ
- NCPNormalize

13.1 NCPolynomial

`NCPolynomial[indep, rules, vars]` is an expanded efficient representation for an nc polynomial in `vars` which can have commutative or noncommutative coefficients.

The nc expression `indep` collects all terms that are independent of the letters in `vars`.

The *Association* rules stores terms in the following format:

`{mon1, ..., monN} -> {scalar, term1, ..., termN+1}`

where:

- `mon1, ..., monN`: are nc monomials in `vars`;
- `scalar`: contains all commutative coefficients; and
- `term1, ..., termN+1`: are nc expressions on letters other than the ones in `vars` which are typically the noncommutative coefficients of the polynomial.

`vars` is a list of *Symbols*.

For example the polynomial

`a**x**b - 2 x**y**c**x + a**c`

in variables `x` and `y` is stored as:

`NCPolynomial[a**c, <|{x}->{{1,a,b}},{x**y,x}->{{2,1,c,1}}|>, {x,y}]`

NCPolynomial specific functions are prefixed with NCP, e.g. NCPDegree.

See also: NCToNCPolynomial, NCPolynomialToNC, NCTermsToNC.

13.2 NCToNCPolynomial

NCToNCPolynomial[`p`, `vars`] generates a representation of the noncommutative polynomial `p` in `vars` which can have commutative or noncommutative coefficients.

NCToNCPolynomial[`p`] generates an NCPolynomial in all nc variables appearing in `p`.

Example:

`exp = a**x**b - 2 x**y**c**x + a**c`

`p = NCToNCPolynomial[exp, {x,y}]`

returns

`NCPolynomial[a**c, <|{x}->{{1,a,b}},{x**y,x}->{{2,1,c,1}}|>, {x,y}]`

See also: NCPolynomial, NCPolynomialToNC.

13.3 NCPolynomialToNC

NCPolynomialToNC[`p`] converts the NCPolynomial `p` back into a regular nc polynomial.

See also: NCPolynomial, NCToNCPolynomial.

13.4 NCRationalToNCPolynomial

NCRationalToNCPolynomial[`r`, `vars`] generates a representation of the noncommutative rational expression `r` in `vars` which can have commutative or noncommutative coefficients.

NCRationalToNCPolynomial[`r`] generates an NCPolynomial in all nc variables appearing in `r`.

`NCRationalToNCPolynomial` creates one variable for each `inv` expression in `vars` appearing in the rational expression `r`. It returns a list of three elements:

- the first element is the `NCPolynomial`;
- the second element is the list of new variables created to replace `invs`;
- the third element is a list of rules that can be used to recover the original rational expression.

For example:

```
exp = a**inv[x]**y**b - 2 x**y**c**x + a**c
{p,rvars,rules} = NCRationalToNCPolynomial[exp, {x,y}]

returns

p = NCPolynomial[a**c, <|{rat1**y}->{{1,a,b}},{x**y,x}->{{2,1,c,1}}|>, {x,y,rat1}]
rvars = {rat1}
rules = {rat1->inv[x]}
```

See also: `NCToNCPolynomial`, `NCPolynomialToNC`.

13.5 NCP Coefficients

`NCPCoefficients[p, m]` gives all coefficients of the `NCPolynomial` `p` in the monomial `m`.

For example:

```
exp = a ** x ** b - 2 x ** y ** c ** x + a ** c + d ** x
p = NCToNCPolynomial[exp, {x, y}]
NCPCoefficients[p, {x}]
```

returns

```
{{1, d, 1}, {1, a, b}}
```

and

```
NCPCoefficients[p, {x ** y, x}]
```

returns

```
{{-2, 1, c, 1}}
```

See also: `NCPTermsToNC`.

13.6 NCP TermsOfDegree

`NCPTermsOfDegree[p, deg]` gives all terms of the `NCPolynomial` `p` of degree `deg`.

The degree `deg` is a list with the degree of each symbol.

For example:

```
p = NCPolynomial[0, <|{x,y}->{{2,a,b,c}},
                  {x,x}->{{1,a,b,c}},
                  {x**x}->{{-1,a,b}}|>, {x,y}]
NCPTermsOfDegree[p, {1,1}]
```

returns

```
<|{x,y}->{{2,a,b,c}}|>
```

and

```
NCPTermsOfDegree[p, {2,0}]
```

returns

```
<|{x,x}->{{1,a,b,c}}, {x**x}->{{-1,a,b}}|>
```

See also: NCPTermsOfTotalDegree, NCPTermsToNC.

13.7 NCPTermsOfTotalDegree

NCPTermsOfDegree[p,deg] gives all terms of the NCPolynomial p of total degree deg.

The degree deg is the total degree.

For example:

```
p = NCPolynomial[0, <|{x,y}->{{2,a,b,c}},
                    {x,x}->{{1,a,b,c}},
                    {x**x}->{{-1,a,b}}|>, {x,y}]
```

```
NCPTermsOfDegree[p, 2]
```

returns

```
<|{x,y}->{{2,a,b,c}}, {x,x}->{{1,a,b,c}}, {x**x}->{{-1,a,b}}|>
```

See also: NCPTermsOfDegree, NCPTermsToNC.

13.8 NCPTermsToNC

NCPTermsToNC gives a nc expression corresponding to terms produced by NCPTermsOfDegree or NCPTermsOfTotalDegree.

For example:

```
terms = <|{x,x}->{{1,a,b,c}}, {x**x}->{{-1,a,b}}|>
```

```
NCPTermsToNC[terms]
```

returns

```
a**x**b**c-a**x**b
```

See also: NCPTermsOfDegree, NCPTermsOfTotalDegree.

13.9 NCPPlus

NCPPlus[p1,p2,...] gives the sum of the nc polynomials p1,p2,... .

13.10 NCPSort

NCPSort[p] gives a list of elements of the NCPolynomial p in which monomials are sorted first according to their degree then by Mathematica's implicit ordering.

For example

```
NCPSort[NCPolynomial[c + x**x - 2 y, {x,y}]]
```

will produce the list

```
{c, -2 y, x**x}
```

See also: NCPDecompose, NCDecompose, NCCompose.

13.11 NCPDecompose

`NCPDecompose[p]` gives an association of elements of the `NCPolynomial p` in which elements of the same order are collected together.

For example

```
NCPDecompose[NCPolynomial[a**x**b+c+d**x**e+a**x**e**x**b+a**x**y, {x,y}]]
```

will produce the Association

```
<|{1,0}->a**x**b + d**x**e, {1,1}->a**x**y, {2,0}->a**x**e**x**b, {0,0}->c|>
```

See also: NCPSort, NCDecompose, NCCompose.

13.12 NCPDegree

`NCPDegree[p]` gives the degree of the `NCPolynomial p`.

See also: NCPMonomialDegree.

13.13 NCPMonomialDegree

`NCPDegree[p]` gives the degree of each monomial in the `NCPolynomial p`.

See also: NCDegree.

13.14 NCPLinearQ

`NCPLinearQ[p]` gives True if the `NCPolynomial p` is linear.

See also: NCPQuadraticQ.

13.15 NCPQuadraticQ

`NCPQuadraticQ[p]` gives True if the `NCPolynomial p` is quadratic.

See also: NCPLinearQ.

13.16 NCPCompatibleQ

`NCPCompatibleQ[p1,p2,...]` returns *True* if the polynomials `p1,p2,...` have the same variables and dimensions.

See also: `NCPSameVariablesQ`, `NCPMatrixQ`.

13.17 NCPSameVariablesQ

`NCPSameVariablesQ[p1,p2,...]` returns *True* if the polynomials `p1,p2,...` have the same variables.

See also: `NCPCompatibleQ`, `NCPMatrixQ`.

13.18 NCPMatrixQ

`NCPMatrixQ[p]` returns *True* if the polynomial `p` is a matrix polynomial.

See also: `NCPCompatibleQ`.

13.19 NCPNormalize

`NCPNormalizes[p]` gives a normalized version of `NCPolynomial p` where all factors that have free commutative products are collected in the scalar.

This function is intended to be used mostly by developers.

See also: `NCPolynomial`

Chapter 14

NCSylvester

NCSylvester is a package that provides functionality to handle linear polynomials in NC variables.

Members are:

- `NCPolynomialToNCSylvester`
- `NCSylvesterToNCPolynomial`

14.1 NCPolynomialToNCSylvester

`NCPolynomialToNCSylvester[p]` gives an expanded representation for the linear `NCPolynomial` `p`.

`NCPolynomialToNCSylvester` returns a list with two elements:

- the first is a the independent term;
- the second is an association where each key is one of the variables and each value is a list with three elements:
 - the first element is a list of left NC symbols;
 - the second element is a list of right NC symbols;
 - the third element is a numeric `SparseArray`.

Example:

```
p = NCToNCPolynomial[2 + a**x**b + c**x**d + y, {x,y}];
{p0,sylv} = NCPolynomialToNCSylvester[p,x]
```

produces

```
p0 = 2
sylv = <|x->{{a,c},{b,d},SparseArray[{{1,0},{0,1}}]},
      y->{{1},{1},SparseArray[{{1}}]}|>
```

See also: `NCSylvesterToNCPolynomial`, `NCPolynomial`.

14.2 NCSylvesterToNCPolynomial

`NCSylvesterToNCPolynomial[rep]` takes the list `rep` produced by `NCPolynomialToNCSylvester` and converts it back to an `NCPolynomial`.

`NCSylvesterToNCPolynomial[rep,options]` uses `options`.

The following `options` can be given: * `Collect (True)`: controls whether the coefficients of the resulting `NCPolynomial` are collected to produce the minimal possible number of terms.

See also: `NCPolynomialToNCSylvester`, `NCPolynomial`.

Chapter 15

NCQuadratic

NCQuadratic is a package that provides functionality to handle quadratic polynomials in NC variables.

Members are:

- NCQuadraticMakeSymmetric
- NCMatrixOfQuadratic
- NCQuadratic
- NCQuadraticToNCPolynomial

15.1 NCQuadratic

NCQuadratic[p] gives an expanded representation for the quadratic **NCPolynomial** p.

NCQuadratic returns a list with four elements:

- the first element is the independent term;
- the second represents the linear part as in **NCSylvester**;
- the third element is a list of left NC symbols;
- the fourth element is a numeric **SparseArray**;
- the fifth element is a list of right NC symbols.

Example:

```
exp = d + x + x**x + x**a**x + x**e**x + x**b**y**d + d**y**c**y**d;  
vars = {x,y};  
p = NCToNCPolynomial[exp, vars];  
{p0,sylv,left,middle,right} = NCQuadratic[p];
```

produces

```
p0 = d  
sylv = <|x->{{1},{1},SparseArray[{{1}}]}, y->{{},{},{}}|>  
left = {x,d**y}  
middle = SparseArray[{{1+a+e,b},{0,c}}]  
right = {x,y**d}
```

See also: **NCSylvester**, **NCQuadraticToNCPolynomial**, **NCPolynomial**.

15.2 NCQuadraticMakeSymmetric

`NCQuadraticMakeSymmetric[{p0, sylv, left, middle, right}]` takes the output of `NCQuadratic` and produces, if possible, an equivalent symmetric representation in which `Map[tp, left] = right` and `middle` is a symmetric matrix.

See also: `NCQuadratic`.

15.3 NCMatrixOfQuadratic

`NCMatrixOfQuadratic[p, vars]` gives a factorization of the symmetric quadratic function `p` in noncommutative variables `vars` and their transposes.

`NCMatrixOfQuadratic` checks for symmetry and automatically sets variables to be symmetric if possible.

Internally it uses `NCQuadratic` and `NCQuadraticMakeSymmetric`.

It returns a list of three elements:

- the first is the left border row vector;
- the second is the middle matrix;
- the third is the right border column vector.

For example:

```
expr = x**y**x + z**x**x**z;
{left,middle,right}=NCMatrixOfQuadratics[expr, {x}];
```

returns:

```
left={x, z**x}
middle=SparseArray[{{y,0},{0,1}}]
right={x,x**z}
```

The answer from `NCMatrixOfQuadratics` always satisfies `p = MatMult[left,middle,right]`.

See also: `NCQuadratic`, `NCQuadraticMakeSymmetric`.

15.4 NCQuadraticToNCPolynomial

`NCQuadraticToNCPolynomial[rep]` takes the list `rep` produced by `NCQuadratic` and converts it back to an `NCPolynomial`.

`NCQuadraticToNCPolynomial[rep,options]` uses options.

The following options can be given:

- `Collect (True)`: controls whether the coefficients of the resulting `NCPolynomial` are collected to produce the minimal possible number of terms.

See also: `NCQuadratic`, `NCPolynomial`.

Chapter 16

NCRational

This package contains functionality to convert an nc rational expression into a descriptor representation.

For example the rational

```
exp = 1 + inv[1 + x]
```

in variables x and y can be converted into an NCPolynomial using

```
p = NCToNCPolynomial[exp, {x,y}]
```

which returns

```
p = NCPolynomial[a**c, <|{x}->{{1,a,b}},{x**y,x}->{{2,1,c,1}}|>, {x,y}]
```

Members are:

- NCRational
- NCToNCRational
- NCRationalToNC
- NCRationalToCanonical
- CanonicalToNCRational
- NCROrder
- NCRLinearQ
- NCRStrictlyProperQ
- NCRPlus
- NCRTimes
- NCRTranspose
- NCRInverse
- NCRControllableSubspace
- NCRControllableRealization
- NCRObservableRealization
- NCRMinimalRealization

16.1 NCRational

NCRational::usage

16.2 NCToNCRational

NCToNCRational::usage

16.3 NCRationalToNC

NCRationalToNC::usage

16.4 NCRationalToCanonical

NCRationalToCanonical::usage

16.5 CanonicalToNCRational

CanonicalToNCRational::usage

16.6 NCROrder

NCROrder::usage

16.7 NCRLinearQ

NCRLinearQ::usage

16.8 NCRStrictlyProperQ

NCRStrictlyProperQ::usage

16.9 NCRPlus

NCRPlus::usage

16.10 NCRTimes

NCRTimes::usage

16.11 NCRTranspose

NCRTranspose::usage

16.12 NCRInverse

NCRInverse::usage

16.13 NCRControllableRealization

NCRControllableRealization::usage

16.14 NCRControllableSubspace

NCRControllableSubspace::usage

16.15 NCRObservableRealization

NCRObservableRealization::usage

16.16 NCRMinimalRealization

NCRMinimalRealization::usage

Chapter 17

NCConvexity

NCConvexity is a package that provides functionality to determine whether a rational or polynomial noncommutative function is convex.

Members are:

- NCIndependent
- NCConvexityRegion

17.1 NCIndependent

`NCIndependent[list]` attempts to determine whether the nc entries of `list` are independent.

Entries of `NCIndependent` can be nc polynomials or nc rationals.

For example:

```
NCIndependent[{x,y,z}]
return True while
NCIndependent[{x,0,z}]
NCIndependent[{x,y,x}]
NCIndependent[{x,y,x+y}]
NCIndependent[{x,y,A x + B y}]
NCIndependent[{inv[1+x]**inv[x], inv[x], inv[1+x]}]
all return False.
```

See also: `NCConvexity`.

17.2 NCConvexityRegion

`NCConvexityRegion[expr,vars]` is a function which can be used to determine whether the nc rational `expr` is convex in `vars` or not.

For example:

```
d = NCConvexityRegion[x**x**x, {x}];
returns
```

```
d = {2 x, -2 inv[x]}
```

from which we conclude that $x**x**x$ is not convex in x because $x \succ 0$ and $-x^{-1} \succ 0$ cannot simultaneously hold.

`NCConvexityRegion` works by factoring the `NCHessian`, essentially calling:

```
hes = NCHessian[expr, {x, h}];
```

then

```
{lt, mq, rt} = NCMatrixOfQuadratic[hes, {h}]
```

to decompose the Hessian into a product of a left row vector, `lt`, times a middle matrix, `mq`, times a right column vector, `rt`. The middle matrix, `mq`, is factored using the `NCLDLDecomposition`:

```
{ldl, p, s, rank} = NCLDLDecomposition[mq];
```

```
{lf, d, rt} = GetLDUMatrices[ldl, s];
```

from which the output of `NCConvexityRegion` is the a list with the block-diagonal entries of the matrix `d`.

See also: `NCHessian`, `NCMatrixOfQuadratic`, `NCLDLDecomposition`.

Chapter 18

NCRealization

The package **NCRealization** implements an algorithm due to N. Slingend for producing minimal realizations of nc rational functions in many nc variables. See “Toward Making LMIs Automatically”.

It actually computes formulas similar to those used in the paper “Noncommutative Convexity Arises From Linear Matrix Inequalities” by J William Helton, Scott A. McCullough, and Victor Vinnikov. In particular, there are functions for calculating (symmetric) minimal descriptor realizations of nc (symmetric) rational functions, and determinantal representations of polynomials.

Members are:

- Drivers:
 - NCDescriptorRealization
 - NCMatrixDescriptorRealization
 - NCMinimalDescriptorRealization
 - NCDeterminantalRepresentationReciprocal
 - NCSymmetrizeMinimalDescriptorRealization
 - NCSymmetricDescriptorRealization
 - NCSymmetricDeterminantalRepresentationDirect
 - NCSymmetricDeterminantalRepresentationReciprocal
 - NonCommutativeLift
- Auxiliary:
 - PinnedQ
 - PinningSpace
 - TestDescriptorRealization
 - SignatureOfAffineTerm

18.1 NCDescriptorRealization

`NCDescriptorRealization[RationalExpression,UnknownVariables]` returns a list of 3 matrices $\{C,G,B\}$ such that $CG^{-1}B$ is the given `RationalExpression`. i.e. `MatMult[C,NCInverse[G],B] == RationalExpression`.

`C` and `B` do not contain any `UnknownsVariables` and `G` has linear entries in the `UnknownVariables`.

18.2 NCDeterminantalRepresentationReciprocal

`NCDeterminantalRepresentationReciprocal[Polynomial,Unknowns]` returns a linear pencil matrix whose determinant equals `Constant * CommuteEverything[Polynomial]`. This uses the reciprocal algorithm: find a minimal descriptor realization of `inv[Polynomial]`, so `Polynomial` must be nonzero at the origin.

18.3 NCMatrixDescriptorRealization

`NCMatrixDescriptorRealization[RationalMatrix,UnknownVariables]` is similar to `NCDescriptorRealization` except it takes a *Matrix* with rational function entries and returns a matrix of lists of the vectors/matrix `{C,G,B}`. A different `{C,G,B}` for each entry.

18.4 NCMinimalDescriptorRealization

`NCMinimalDescriptorRealization[RationalFunction,UnknownVariables]` returns `{C,G,B}` where `MatMult[C,NCInverse[G],B] == RationalFunction`, `G` is linear in the `UnknownVariables`, and the realization is minimal (may be pinned).

18.5 NCSymmetricDescriptorRealization

`NCSymmetricDescriptorRealization[RationalSymmetricFunction,Unknowns]` combines two steps: `NCSymmetrizeMinimalDescriptorRealization[NCMinimalDescriptorRealization[RationalSymmetricFunction,Unknowns]]`.

18.6 NCSymmetricDeterminantalRepresentationDirect

`NCSymmetricDeterminantalRepresentationDirect[SymmetricPolynomial,Unknowns]` returns a linear pencil matrix whose determinant equals `Constant * CommuteEverything[SymmetricPolynomial]`. This uses the direct algorithm: Find a realization of `1 - NCSymmetricPolynomial`,...

18.7 NCSymmetricDeterminantalRepresentationReciprocal

`NCSymmetricDeterminantalRepresentationReciprocal[SymmetricPolynomial,Unknowns]` returns a linear pencil matrix whose determinant equals `Constant * CommuteEverything[NCSymmetricPolynomial]`. This uses the reciprocal algorithm: find a symmetric minimal descriptor realization of `inv[NCSymmetricPolynomial]`, so `NCSymmetricPolynomial` must be nonzero at the origin.

18.8 NCSymmetrizeMinimalDescriptorRealization

`NCSymmetrizeMinimalDescriptorRealization[{C,G,B},Unknowns]` symmetrizes the minimal realization `{C,G,B}` (such as output from `NCMinimalRealization`) and outputs `{Ctilde,Gtilde}` corresponding to the realization `{Ctilde, Gtilde,Transpose[Ctilde]}`.

WARNING: May produces errors if the realization doesn't correspond to a symmetric rational function.

18.9 NonCommutativeLift

`NonCommutativeLift[Rational]` returns a noncommutative symmetric lift of `Rational`.

18.10 SignatureOfAffineTerm

`SignatureOfAffineTerm[Pencil,Unknowns]` returns a list of the number of positive, negative and zero eigenvalues in the affine part of `Pencil`.

18.11 TestDescriptorRealization

`TestDescriptorRealization[Rat,{C,G,B},Unknowns]` checks if `Rat` equals $CG^{-1}B$ by substituting random 2-by-2 matrices in for the unknowns. `TestDescriptorRealization[Rat,{C,G,B},Unknowns,NumberOfTests]` can be used to specify the `NumberOfTests`, the default being 5.

18.12 PinnedQ

`PinnedQ[Pencil_,Unknowns_]` is `True` or `False`.

18.13 PinningSpace

`PinningSpace[Pencil_,Unknowns_]` returns a matrix whose columns span the pinning space of `Pencil`. Generally, either an empty matrix or a d-by-1 matrix (vector).

Chapter 19

NCMatMult

Members are:

- `tpMat`
- `ajMat`
- `coMat`
- `MatMult`
- `NCInverse`
- `NCMatrixExpand`

19.1 `tpMat`

`tpMat[mat]` gives the transpose of matrix `mat` using `tp`.

See also: `ajMat`, `coMat`, `MatMult`.

19.2 `ajMat`

`ajMat[mat]` gives the adjoint transpose of matrix `mat` using `aj` instead of `ConjugateTranspose`.

See also: `tpMat`, `coMat`, `MatMult`.

19.3 `coMat`

`coMat[mat]` gives the conjugate of matrix `mat` using `co` instead of `Conjugate`.

See also: `tpMat`, `ajMat`, `MatMult`.

19.4 `MatMult`

`MatMult[mat1, mat2, ...]` gives the matrix multiplication of `mat1, mat2, ...` using `NonCommutativeMultiply` rather than `Times`.

See also: `tpMat`, `ajMat`, `coMat`.

19.4.1 Notes

The experienced matrix analyst should always remember that the Mathematica convention for handling vectors is tricky.

- $\{\{1,2,4\}\}$ is a 1×3 *matrix* or a *row vector*;
- $\{\{1\},\{2\},\{4\}\}$ is a 3×1 *matrix* or a *column vector*;
- $\{1,2,4\}$ is a *vector* but **not** a *matrix*. Indeed whether it is a row or column vector depends on the context. We advise not to use *vectors*.

19.5 NCInverse

`NCInverse[mat]` gives the nc inverse of the square matrix `mat`. `NCInverse` uses partial pivoting to find a nonzero pivot.

`NCInverse` is primarily used symbolically. Usually the elements of the inverse matrix are huge expressions. We recommend using `NCSimplifyRational` to improve the results.

See also: `tpMat`, `ajMat`, `coMat`.

19.6 NCMatrixExpand

`NCMatrixExpand[expr]` expands `inv` and `**` of matrices appearing in nc expression `expr`. It effectively substitutes `inv` for `NCInverse` and `**` by `MatMult`.

See also: `NCInverse`, `MatMult`.

Chapter 20

NCMatrixDecompositions

Members are:

- Decompositions
 - NCLUDecompositionWithPartialPivoting
 - NCLUDecompositionWithCompletePivoting
 - NCLDLDecomposition
- Solvers
 - NCLowerTriangularSolve
 - NCUpperTriangularSolve
 - NCLUInverse
- Utilities
 - NCLUCompletePivoting
 - NCLUPartialPivoting
 - NCLeftDivide
 - NCRightDivide

20.1 NCLDLDecomposition

20.2 NCLeftDivide

20.3 NCLowerTriangularSolve

20.4 NCLUCompletePivoting

20.5 NCLUDecompositionWithCompletePivoting

20.6 NCLUDecompositionWithPartialPivoting

20.7 NCLUInverse

20.8 NCLUPartialPivoting

20.9 NCMatrixDecompositions

20.10 NCRightDivide

20.11 NCUpperTriangularSolve

Chapter 21

MatrixDecompositions

MatrixDecompositions is a package that implements various linear algebra algorithms, such as *LU Decomposition* with *partial* and *complete pivoting*, and *LDL Decomposition*. The algorithms have been written with correctness and easy of customization rather than efficiency as the main goals. They were originally developed to serve as the core of the noncommutative linear algebra algorithms for NCAAlgebra. See NCMatrixDecompositions.

Members are:

- Decompositions
 - LUDecompositionWithPartialPivoting
 - LUDecompositionWithCompletePivoting
 - LDLDecomposition
- Solvers
 - LowerTriangularSolve
 - UpperTriangularSolve
 - LUInverse
- Utilities
 - GetLUMatrices
 - GetLDUMatrices
 - GetDiagonal
 - LUPartialPivoting
 - LUCompletePivoting
 - LUNoPartialPivoting
 - LUNoCompletePivoting

21.1 LUDecompositionWithPartialPivoting

`LUDecompositionWithPartialPivoting[m]` generates a representation of the LU decomposition of the rectangular matrix `m`.

`LUDecompositionWithPartialPivoting[m, options]` uses `options`.

`LUDecompositionWithPartialPivoting` returns a list of two elements:

- the first element is a combination of upper- and lower-triangular matrices;
- the second element is a vector specifying rows used for pivoting.

`LUDecompositionWithPartialPivoting` is similar in functionality with the built-in `LUDecomposition`. It implements a *partial pivoting* strategy in which the sorting can be configured using the options listed below.

It also applies to general rectangular matrices as well as square matrices.

The triangular factors are recovered using `GetLUMatrices`.

The following options can be given:

- `ZeroTest` (`PossibleZeroQ`): function used to decide if a pivot is zero;
- `RightDivide` (`RightDivide`): function used to divide a vector by an entry;
- `Dot` (`Dot`): function used to multiply vectors and matrices;
- `Pivoting` (`LUPartialPivoting`): function used to sort rows for pivoting;
- `SuppressPivoting` (`False`): whether to perform pivoting or not.

See also: `LUdecompositionWithPartialPivoting`, `LUdecompositionWithCompletePivoting`, `GetLUMatrices`, `LUPartialPivoting`.

21.2 LUdecompositionWithCompletePivoting

`LUdecompositionWithCompletePivoting[m]` generates a representation of the LU decomposition of the rectangular matrix `m`.

`LUdecompositionWithCompletePivoting[m, options]` uses options.

`LUdecompositionWithCompletePivoting` returns a list of four elements:

- the first element is a combination of upper- and lower-triangular matrices;
- the second element is a vector specifying rows used for pivoting;
- the third element is a vector specifying columns used for pivoting;
- the fourth element is the rank of the matrix.

`LUdecompositionWithCompletePivoting` implements a *complete pivoting* strategy in which the sorting can be configured using the options listed below. It also applies to general rectangular matrices as well as square matrices.

The triangular factors are recovered using `GetLUMatrices`.

The following options can be given:

- `ZeroTest` (`PossibleZeroQ`): function used to decide if a pivot is zero;
- `Divide` (`Divide`): function used to divide a vector by an entry;
- `Dot` (`Dot`): function used to multiply vectors and matrices;
- `Pivoting` (`LUCompletePivoting`): function used to sort rows for pivoting;

See also: `LUdecomposition`, `GetLUMatrices`, `LUCompletePivoting`, `LUdecompositionWithPartialPivoting`.

21.3 LDLdecomposition

`LDLdecomposition[m]` generates a representation of the LDL decomposition of the symmetric or self-adjoint matrix `m`.

`LDLdecomposition[m, options]` uses options.

`LDLdecomposition` returns a list of four elements:

- the first element is a combination of upper- and lower-triangular matrices;
- the second element is a vector specifying rows and columns used for pivoting;
- the third element is a vector specifying the size of the diagonal blocks; it can be 1 or 2;
- the fourth element is the rank of the matrix.

`LUdecompositionWithCompletePivoting` implements a *Bunch-Parlett pivoting* strategy in which the sorting can be configured using the options listed below. It applies only to square symmetric or self-adjoint matrices.

The triangular factors are recovered using `GetLDUMatrices`.

The following options can be given:

- `ZeroTest` (`PossibleZeroQ`): function used to decide if a pivot is zero;
- `RightDivide` (`RightDivide`): function used to divide a vector by an entry on the right;
- `LeftDivide` (`LeftDivide`): function used to divide a vector by an entry on the left;
- `Dot` (`Dot`): function used to multiply vectors and matrices;
- `CompletePivoting` (`LUCompletePivoting`): function used to sort rows for complete pivoting;
- `PartialPivoting` (`LUPartialPivoting`): function used to sort matrices for complete pivoting;
- `Inverse` (`Inverse`): function used to invert 2x2 diagonal blocks;
- `SelfAdjointQ` (`SelfAdjointMatrixQ`): function to test if matrix is self-adjoint;
- `SuppressPivoting` (`False`): whether to perform pivoting or not.

See also: `LUdecompositionWithPartialPivoting`, `LUdecompositionWithCompletePivoting`, `GetLUMatrices`, `LUCompletePivoting`, `LUPartialPivoting`.

21.4 UpperTriangularSolve

`UpperTriangularSolve[u, b]` solves the upper-triangular system of equations $ux = b$ using back-substitution.

For example:

```
x = UpperTriangularSolve[u, b];
```

returns the solution `x`.

See also: `LUdecompositionWithPartialPivoting`, `LUdecompositionWithCompletePivoting`, `LDLdecomposition`.

21.5 LowerTriangularSolve

`LowerTriangularSolve[l, b]` solves the lower-triangular system of equations $lx = b$ using forward-substitution.

For example:

```
x = LowerTriangularSolve[l, b];
```

returns the solution `x`.

See also: `LUdecompositionWithPartialPivoting`, `LUdecompositionWithCompletePivoting`, `LDLdecomposition`.

21.6 LUInverse

`LUInverse[a]` calculates the inverse of matrix `a`.

`LUInverse` uses the `LUdecompositionWithPartialPivoting` and the triangular solvers `LowerTriangularSolve` and `UpperTriangularSolve`.

See also: `LUdecompositionWithPartialPivoting`.

21.7 GetLUMatrices

`GetLUMatrices[m]` extracts lower- and upper-triangular blocks produced by `LDUdecompositionWithPartialPivoting` and `LDUdecompositionWithCompletePivoting`.

For example:

```
{lu, p} = LDUdecompositionWithPartialPivoting[A];
{l, u} = GetLUMatrices[lu];
```

returns the lower-triangular factor `l` and upper-triangular factor `u`.

See also: `LDUdecompositionWithPartialPivoting`, `LDUdecompositionWithCompletePivoting`.

21.8 GetLDUMatrices

`GetLDUMatrices[m,s]` extracts lower-, upper-triangular and diagonal blocks produced by `LDLdecomposition`.

For example:

```
{ldl, p, s, rank} = LDLdecomposition[A];
{l,d,u} = GetLDUMatrices[ldl,s];
```

returns the lower-triangular factor `l`, the upper-triangular factor `u`, and the block-diagonal factor `d`.

See also: `LDLdecomposition`.

21.9 GetDiagonal

`GetDiagonal[m]` extracts the diagonal entries of matrix `m`.

`GetDiagonal[m, s]` extracts the block-diagonal entries of matrix `m` with block size `s`.

For example:

```
d = GetDiagonal[{{1,-1,0},{-1,2,0},{0,0,3}}];
```

returns

```
d = {1,2,3}
```

and

```
d = GetDiagonal[{{1,-1,0},{-1,2,0},{0,0,3}}, {2,1}];
```

returns

```
d = {{{1,-1},{-1,2}},3}
```

See also: `LDLdecomposition`.

21.10 LUPartialPivoting

`LUPartialPivoting[v]` returns the index of the element with largest absolute value in the vector `v`. If `v` is a matrix, it returns the index of the element with largest absolute value in the first column.

`LUPartialPivoting[v, f]` sorts with respect to the function `f` instead of the absolute value.

See also: `LDUdecompositionWithPartialPivoting`, `LUCompletePivoting`.

21.11 LUCompletePivoting

`LUCompletePivoting[m]` returns the row and column index of the element with largest absolute value in the matrix `m`.

`LUCompletePivoting[v, f]` sorts with respect to the function `f` instead of the absolute value.

See also: `LUdecompositionWithCompletePivoting`, `LUPartialPivoting`.

Chapter 22

NCUtil

NCUtil is a package with a collection of utilities used throughout **NCAgebra**.

Members are:

- **NCConsistentQ**
- **NCGrabFunctions**
- **NCGrabSymbols**
- **NCGrabIndeterminants**
- **NCConsolidateList**
- **NCLeafCount**
- **NCReplaceData**
- **NCToExpression**

22.1 NCConsistentQ

NCConsistentQ[expr] returns *True* if **expr** contains no commutative products or inverses involving noncommutative variables.

22.2 NCGrabFunctions

NCGrabFunctions[expr] returns a list with all fragments containing function of **expr**.

NCGrabFunctions[expr,f] returns a list with all fragments of **expr** containing the function **f**.

For example:

```
NCGrabFunctions[inv[x] + tp[y]**inv[1+inv[1+tp[x]**y]], inv]
```

returns

```
{inv[1+inv[1+tp[x]**y]], inv[1+tp[x]**y], inv[x]}
```

and

```
NCGrabFunctions[inv[x] + tp[y]**inv[1+inv[1+tp[x]**y]]]
```

returns

```
{inv[1+inv[1+tp[x]**y]], inv[1+tp[x]**y], inv[x], tp[x], tp[y]}
```

See also: **NCGrabSymbols**.

22.3 NCGrabSymbols

NCGrabSymbols[expr] returns a list with all *Symbols* appearing in **expr**.

NCGrabSymbols[expr,f] returns a list with all *Symbols* appearing in **expr** as the single argument of function **f**.

For example:

```
NCGrabSymbols[inv[x] + y**inv[1+inv[1+x**y]]]
```

returns {x,y} and

```
NCGrabSymbols[inv[x] + y**inv[1+inv[1+x**y]], inv]
```

returns {inv[x]}.

See also: NCGrabFunctions.

22.4 NCGrabIndeterminants

NCGrabIndeterminants[expr] returns a list with first level symbols and nc expressions involved in sums and nc products in **expr**.

For example:

```
NCGrabIndeterminants[y - inv[x] + tp[y]**inv[1+inv[1+tp[x]**y]]]
```

returns

```
{y, inv[x], inv[1 + inv[1 + tp[x] ** y]], tp[y]}
```

See also: NCGrabFunctions, NCGrabSymbols.

22.5 NCConsolidateList

NCConsolidateList[list] produces two lists:

- The first list contains a version of **list** where repeated entries have been suppressed;
- The second list contains the indices of the elements in the first list that recover the original **list**.

For example:

```
{list,index} = NCConsolidateList[{z,t,s,f,d,f,z}];
```

results in:

```
list = {z,t,s,f,d};
```

```
index = {1,2,3,4,5,4,1};
```

See also: Union

22.6 NCLeafCount

NCLeafCount[expr] returns an number associated with the complexity of an expression:

- If PossibleZeroQ[expr] == True then NCLeafCount[expr] is -Infinity;
- If NumberQ[expr] == True then NCLeafCount[expr] is Abs[expr];

- Otherwise `NCLearCount[expr]` is `-LeafCount[expr]`;

`NCLearCount` is `Listable`.

See also: `LeafCount`.

22.7 NCRReplaceData

`NCRReplaceData[expr, rules]` applies `rules` to `expr` and convert resulting expression to standard Mathematica, for example replacing `**` by `..`.

`NCRReplaceData` does not attempt to resize entries in expressions involving matrices. Use `NCToExpression` for that.

See also: `NCToExpression`.

22.8 NCToExpression

`NCToExpression[expr, rules]` applies `rules` to `expr` and convert resulting expression to standard Mathematica.

`NCToExpression` attempts to resize entries in expressions involving matrices.

See also: `NCRReplaceData`.

Chapter 23

NCSDP

NCSDP is a package that allows the symbolic manipulation and numeric solution of semidefinite programs.

Problems consist of symbolic noncommutative expressions representing inequalities and a list of rules for data replacement. For example the semidefinite program:

$$\begin{aligned} \min_Y \quad & \langle I, Y \rangle \\ \text{s.t.} \quad & AY + YA^T + I \preceq 0 \\ & Y \succeq 0 \end{aligned}$$

can be solved by defining the noncommutative expressions

```
<< NCSDP`
SNC[a, y];
obj = {-1};
ineqs = {a ** y + y ** tp[a] + 1, -y};
```

The inequalities are stored in the list `ineqs` in the form of noncommutative linear polynomials in the variable `y` and the objective function contains the symbolic coefficients of the inner product, in this case `-1`. The reason for the negative signs in the objective as well as in the second inequality is that semidefinite programs are expected to be cast in the following *canonical form*:

$$\begin{aligned} \max_y \quad & \langle b, y \rangle \\ \text{s.t.} \quad & f(y) \preceq 0 \end{aligned}$$

or, equivalently:

$$\begin{aligned} \max_y \quad & \langle b, y \rangle \\ \text{s.t.} \quad & f(y) + s = 0, \quad s \succeq 0 \end{aligned}$$

Semidefinite programs can be visualized using `NCSDPForm` as in:

```
vars = {y};
NCSDPForm[ineqs, vars, obj]
```

In order to obtaining a numerical solution to an instance of the above semidefinite program one must provide a list of rules for data substitution. For example:

```
A = {{0, 1}, {-1, -2}};
data = {a -> A};
```

Equipped with a list of rules one can invoke `NCSDP` to produce an instance of `SDPSylvester`:

```
<< SDPSylvester`
{abc, rules} = NCSDP[F, vars, obj, data];
```

It is the resulting `abc` and `rules` objects that are used for calculating the numerical solution using `SDPSolve`:

```
{Y, X, S, flags} = SDPSolve[abc, rules];
```

The variables `Y` and `S` are the *primal* solutions and `X` is the *dual* solution.

An explicit symbolic dual problem can be calculated easily using `NCSDPDual`:

```
{dIneqs, dVars, dObj} = NCSDPDual[ineqs, vars, obj];
```

The corresponding dual program is expressed in the *canonical form*:

$$\begin{aligned} \max_x \quad & \langle c, x \rangle \\ \text{s.t.} \quad & f^*(x) + b = 0, \quad x \succeq 0 \end{aligned}$$

In the case of the above problem the dual program is

$$\begin{aligned} \max_{X_1, X_2} \quad & \langle I, X_1 \rangle \\ \text{s.t.} \quad & A^T X_1 + X_1 A - X_2 - I = 0 \\ & X_1 \succeq 0, \\ & X_2 \succeq 0 \end{aligned}$$

Dual semidefinite programs can be visualized using `NCSDPDualForm` as in:

```
NCSDPDualForm[dIneqs, dVars, dObj]
```

Members are:

- NCSDP
- NCSDPForm
- NCSDPDual
- NCSDPDualForm

23.1 NCSDP

`NCSDP[inequalities, vars, obj, data]` converts the list of NC polynomials and NC matrices of polynomials `inequalities` that are linear in the unknowns listed in `vars` into the semidefinite program with linear objective `obj`. The semidefinite program (SDP) should be given in the following canonical form:

```
max <obj, vars> s.t. inequalities <= 0.
```

`NCSDP` uses the user supplied rules in `data` to set up the problem data.

`NCSDP[constraints, vars, data]` converts problem into a feasibility semidefinite program.

See also: `NCSDPForm`, `NCSDPDual`.

23.2 NCSDPForm

`NCSDPForm[[inequalities, vars, obj]]` prints out a pretty formatted version of the SDP expressed by the list of NC polynomials and NC matrices of polynomials `inequalities` that are linear in the unknowns listed in `vars`.

See also: `NCSDP`, `NCSDPDualForm`.

23.3 NCSDPDual

`{dInequalities, dVars, dObj} = NCSDPDual[inequalities, vars, obj]` calculates the symbolic dual of the SDP expressed by the list of NC polynomials and NC matrices of polynomials `inequalities` that are linear in the unknowns listed in `vars` with linear objective `obj` into a dual semidefinite in the following canonical form:

`max <dObj, dVars> s.t. dInequalities == 0, dVars >= 0.`

See also: `NCSDPDualForm`, `NCSDP`.

23.4 NCSDPDualForm

`NCSDPForm[[dInequalities, dVars, dObj]` prints out a pretty formatted version of the dual SDP expressed by the list of NC polynomials and NC matrices of polynomials `dInequalities` that are linear in the unknowns listed in `dVars` with linear objective `dObj`.

See also: `NCSDPDual`, `NCSDPForm`.

Chapter 24

SDP

The package **SDP** provides a crude and highly inefficient way to define and solve semidefinite programs in standard form, that is vectorized. You do not need to load **NCAIgebra** if you just want to use the semidefinite program solver. But you still need to load **NC** as in:

```
<< NC`  
<< SDP`
```

Semidefinite programs are optimization problems of the form:

$$\begin{aligned} \min_{y,S} \quad & b^T y \\ \text{s.t.} \quad & Ay + c = S \\ & S \succeq 0 \end{aligned}$$

where S is a symmetric positive semidefinite matrix.

For convenience, problems can be stated as:

$$\begin{aligned} \min_y \quad & \text{obj}(y), \\ \text{s.t.} \quad & \text{ineqs}(y) \succeq 0 \end{aligned}$$

where $\text{obj}(y)$ and $\text{ineqs}(y)$ are affine functions of the vector variable y .

Here is a simple example:

```
ineqs = {y0 - 2, {{y1, y0}, {y0, 1}}, {{y2, y1}, {y1, 1}}};  
obj = y2;  
y = {y0, y1, y2};
```

The list of constraints in **ineqs** are to be interpreted as:

$$\begin{aligned} y_0 - 2 &\geq 0, \\ \begin{bmatrix} y_1 & y_0 \\ y_0 & 1 \end{bmatrix} &\succeq 0, \\ \begin{bmatrix} y_2 & y_1 \\ y_1 & 1 \end{bmatrix} &\succeq 0. \end{aligned}$$

The function **SDPMatrices** convert the above symbolic problem into numerical data that can be used to solve an SDP.

```
abc = SDPMatrices[by, ineqs, y]
```

All required data, that is A , b , and c , is stored in the variable `abc` as Mathematica's sparse matrices. Their contents can be revealed using the Mathematica command `Normal`.

```
Normal[abc]
```

The resulting SDP is solved using `SDPSolve`:

```
{Y, X, S, flags} = SDPSolve[abc];
```

The variables `Y` and `S` are the *primal* solutions and `X` is the *dual* solution. Detailed information on the computed solution is found in the variable `flags`.

The package **SDP** is built so as to be easily overloaded with more efficient or more structure functions. See for example `SDPFlat` and `SDPSylvester`.

Members are:

- `SDPMatrices`
- `SDPSolve`
- `SDPEval`
- `SDPInner`

The following members are not supposed to be called directly by users:

- `SDPCheckDimensions`
- `SDPScale`
- `SDPFunctions`
- `SDPPrimalEval`
- `SDPDualEval`
- `SDPSylvesterEval`
- `SDPSylvesterDiagonalEval`

24.1 SDPMatrices

24.2 SDPSolve

24.3 SDPEval

24.4 SDPInner

24.5 SDPCheckDimensions

24.6 SDPDualEval

24.7 SDPFunctions

24.8 SDPPrimalEval

24.9 SDPScale

24.10 SDPSylvesterDiagonalEval

24.11 SDPSylvesterEval

Chapter 25

NCPoly

Members are:

- Constructors
 - NCPoly
 - NCPolyMonomial
 - NCPolyConstant
- Access
 - NCPolyMonomialQ
 - NCPolyDegree
 - NCPolyNumberOfVariables
 - NCPolyCoefficient
 - NCPolyGetCoefficients
 - NCPolyGetDigits
 - NCPolyGetIntegers
 - NCPolyLeadingMonomial
 - NCPolyLeadingTerm
 - NCPolyOrderType
 - NCPolyToRule
- Formatting
 - NCPolyDisplay
 - NCPolyDisplayOrder
- Arithmetic
 - NCPolyDivideDigits
 - NCPolyDivideLeading
 - NCPolyFullReduce
 - NCPolyNormalize
 - NCPolyProduct
 - NCPolyQuotientExpand
 - NCPolyReduce
 - NCPolySum
- Auxiliary
 - NCFromDigits
 - NCIntegerDigits
 - NCPadAndMatch

25.1 NCPoly

`NCPoly[coeff, monomials, vars]` constructs a noncommutative polynomial object in variables `vars` where the monomials have coefficient `coeff`.

Monomials are specified in terms of the symbols in the list `vars` as in `NCPolyMonomial`.

For example:

```
vars = {x,y,z};
poly = NCPoly[{-1, 2}, {{x,y,x}, {z}}, vars];
```

constructs an object associated with the noncommutative polynomial $2z - xyx$ in variables `x`, `y` and `z`.

The internal representation varies with the implementation but it is so that the terms are sorted according to a degree-lexicographic order in `vars`. In the above example, $x < y < z$.

The construction:

```
vars = {{x},{y,z}};
poly = NCPoly[{-1, 2}, {{x,y,x}, {z}}, vars];
```

represents the same polyomial in a graded degree-lexicographic order in `vars`, in this example, $x \ll y < z$.

See also: `NCPolyMonomial`, `NCIntegerDigits`, `NCFromDigits`.

25.2 NCPolyMonomial

`NCPolyMonomial[monomial, vars]` constructs a noncommutative monomial object in variables `vars`.

Monic monomials are specified in terms of the symbols in the list `vars`, for example:

```
vars = {x,y,z};
mon = NCPolyMonomial[{x,y,x},vars];
```

returns an `NCPoly` object encoding the monomial xyx in noncommutative variables `x`, `y`, and `z`. The actual representation of `mon` varies with the implementation.

Monomials can also be specified implicitly using indices, for example:

```
mon = NCPolyMonomial[{0,1,0}, 3];
```

also returns an `NCPoly` object encoding the monomial xyx in noncommutative variables `x`, `y`, and `z`.

If graded ordering is supported then

```
vars = {{x},{y,z}};
mon = NCPolyMonomial[{x,y,x},vars];
```

or

```
mon = NCPolyMonomial[{0,1,0}, {1,2}];
```

construct the same monomial xyx in noncommutative variables `x`, `y`, and `z` this time using a graded order in which $x \ll y < z$.

There is also an alternative syntax for `NCPolyMonomial` that allows users to input the monomial along with a coefficient using rules and the output of `NCFromDigits`. For example:

```
mon = NCPolyMonomial[{3, 3} -> -2, 3];
```

or

```
mon = NCPolyMonomial[NCFromDigits[{0,1,0}, 3] -> -2, 3];
```

represent the monomial $-2xyx$ with has coefficient -2 .

See also: `NCPoly`, `NCIntegerDigits`, `NCFromDigits`.

25.3 NCPolyConstant

`NCPolyConstant[value, vars]` constructs a noncommutative monomial object in variables `vars` representing the constant `value`.

For example:

```
NCPolyConstant[3, {x, y, z}]
```

constructs an object associated with the constant 3 in variables `x`, `y` and `z`.

See also: `NCPoly`, `NCPolyMonomial`.

25.4 NCPolyMonomialQ

`NCPolyMonomialQ[p]` returns `True` if `p` is a `NCPoly` monomial.

See also: `NCPoly`, `NCPolyMonomial`.

25.5 NCPolyDegree

`NCPolyDegree[poly]` returns the degree of the nc polynomial `poly`.

25.6 NCPolyNumberOfVariables

`NCPolyNumberOfVariables[poly]` returns the number of variables of the nc polynomial `poly`.

25.7 NCPolyCoefficient

`NCPolyCoefficient[poly, mon]` returns the coefficient of the monomial `mon` in the nc polynomial `poly`.

For example, in:

```
coeff = {1, 2, 3, -1, -2, -3, 1/2};
mon = {{}, {x}, {z}, {x, y}, {x, y, x, x}, {z, x}, {z, z, z, z}};
vars = {x,y,z};
poly = NCPoly[coeff, mon, vars];
```

```
c = NCPolyCoefficient[poly, NCPolyMonomial[{x,y},vars]];
```

returns

```
c = -1
```

See also: `NCPoly`, `NCPolyMonomial`.

25.8 NCPolyGetCoefficients

`NCPolyGetCoefficients[poly]` returns a list with the coefficients of the monomials in the nc polynomial `poly`.

For example:

```
vars = {x,y,z};
poly = NCPoly[{-1, 2}, {{x,y,x}, {z}}, vars];
coeffs = NCPolyGetCoefficients[poly];
```

returns

```
coeffs = {2,-1}
```

The coefficients are returned according to the current graded degree-lexicographic ordering, in this example $x < y < z$.

See also: `NCPolyGetDigits`, `NCPolyCoefficient`, `NCPoly`.

25.9 NCPolyGetDigits

`NCPolyGetDigits[poly]` returns a list with the digits that encode the monomials in the nc polynomial `poly` as produced by `NCIntegerDigits`.

For example:

```
vars = {x,y,z};
poly = NCPoly[{-1, 2}, {{x,y,x}, {z}}, vars];
digits = NCPolyGetDigits[poly];
```

returns

```
digits = {{2}, {0,1,0}}
```

The digits are returned according to the current ordering, in this example $x < y < z$.

See also: `NCPolyGetCoefficients`, `NCPoly`.

25.10 NCPolyGetIntegers

`NCPolyGetIntegers[poly]` returns a list with the digits that encode the monomials in the nc polynomial `poly` as produced by `NCFromDigits`.

For example:

```
vars = {x,y,z};
poly = NCPoly[{-1, 2}, {{x,y,x}, {z}}, vars];
digits = NCPolyGetIntegers[poly];
```

returns

```
digits = {{1,2}, {3,3}}
```

The digits are returned according to the current ordering, in this example $x < y < z$.

See also: `NCPolyGetCoefficients`, `NCPoly`.

25.11 NCPolyLeadingMonomial

`NCPolyLeadingMonomial[poly]` returns an `NCPoly` representing the leading term of the nc polynomial `poly`.

For example:

```
vars = {x,y,z};
poly = NCPoly[{-1, 2}, {{x,y,x}, {z}}, vars];
lead = NCPolyLeadingMonomial[poly];
```

returns an `NCPoly` representing the monomial xyx . The leading monomial is computed according to the current ordering, in this example $x < y < z$. The actual representation of `lead` varies with the implementation.

See also: `NCPolyLeadingTerm`, `NCPolyMonomial`, `NCPoly`.

25.12 NCPolyLeadingTerm

`NCPolyLeadingTerm[poly]` returns a rule associated with the leading term of the nc polynomial `poly` as understood by `NCPolyMonomial`.

For example:

```
vars = {x,y,z};
poly = NCPoly[{-1, 2}, {{x,y,x}, {z}}, vars];
lead = NCPolyLeadingTerm[poly];
```

returns

```
lead = {3,3} -> -1
```

representing the monomial $-xyx$. The leading monomial is computed according to the current ordering, in this example $x < y < z$.

See also: `NCPolyLeadingMonomial`, `NCPolyMonomial`, `NCPoly`.

25.13 NCPolyOrderType

`NCPolyOrderType[poly]` returns the type of monomial order in which the nc polynomial `poly` is stored. Order can be `NCPolyGradedDegLex` or `NCPolyDegLex`.

See also: `NCPoly`,

25.14 NCPolyToRule

`NCPolyToRule[poly]` returns a `Rule` associated with polynomial `poly`. If `poly = lead + rest`, where `lead` is the leading term in the current order, then `NCPolyToRule[poly]` returns the rule `lead -> -rest` where the coefficient of the leading term has been normalized to 1.

For example:

```
vars = {x, y, z};
poly = NCPoly[{-1, 2, 3}, {{x, y, x}, {z}, {x, y}}, vars];
rule = NCPolyToRule[poly]
```

returns the rule `lead -> rest` where `lead` represents is the nc monomial xyz and `rest` is the nc polynomial $2z + 3xy$

See also: `NCPolyLeadingTerm`, `NCPolyLeadingMonomial`, `NCPoly`.

25.15 NCPolyDisplayOrder

`NCPolyDisplayOrder[vars]` prints the order implied by the list of variables `vars`.

25.16 NCPolyDisplay

`NCPolyDisplay[p]` prints the noncommutative polynomial `p` using symbols x_1, \dots, x_n . `NCPolyDisplay[p, vars]` uses the symbols in the list `vars`.

25.17 NCPolyDivideDigits

`NCPolyDivideDigits[F,G]` returns the result of the division of the leading digits `lf` and `lg`.

25.18 NCPolyDivideLeading

`NCPolyDivideLeading[lF,lG,base]` returns the result of the division of the leading Rules `lf` and `lg` as returned by `NCGetLeadingTerm`.

25.19 NCPolyFullReduce

`NCPolyFullReduce[f,g]` applies `NCPolyReduce` successively until the remainder does not change. See also `NCPolyReduce` and `NCPolyQuotientExpand`.

25.20 NCPolyNormalize

`NCPolyNormalize[p]` makes the coefficient of the leading term of `p` to unit. It also works when `p` is a list.

25.21 NCPolyProduct

`NCPolyProduct[f,g]` returns a `NCPoly` that is the product of the `NCPoly`'s `f` and `g`.

25.22 NCPolyQuotientExpand

`NCPolyQuotientExpand[q,g]` returns a `NCPoly` that is the left-right product of the quotient as returned by `NCPolyReduce` by the `NCPoly` `g`. It also works when `g` is a list.

25.23 NCPolyReduce

25.24 NCPolySum

`NCPolySum[f,g]` returns a `NCPoly` that is the sum of the `NCPoly`'s `f` and `g`.

25.25 NCFromDigits

`NCFromDigits[list, b]` constructs a representation of a monomial in `b` encoded by the elements of `list` where the digits are in base `b`.

`NCFromDigits[{list1,list2}, b]` applies `NCFromDigits` to each `list1, list2, ...`.

List of integers are used to codify monomials. For example the list `{0,1}` represents a monomial xy and the list `{1,0}` represents the monomial yx . The call

```
NCFromDigits[{0,0,0,1}, 2]
```

returns

```
{4,1}
```

in which 4 is the degree of the monomial $xxxx$ and 1 is 0001 in base 2. Likewise

```
NCFromDigits[{0,2,1,1}, 3]
```

returns

```
{4,22}
```

in which 4 is the degree of the monomial $xzyy$ and 22 is 0211 in base 3.

If `b` is a list, then degree is also a list with the partial degrees of each letters appearing in the monomial. For example:

```
NCFromDigits[{0,2,1,1}, {1,2}]
```

returns

```
{3, 1, 22}
```

in which 3 is the partial degree of the monomial $xzyy$ with respect to letters `y` and `z`, 1 is the partial degree with respect to letter `x` and 22 is 0211 in base $3 = 1 + 2$.

This construction is used to represent graded degree-lexicographic orderings.

See also: `NCIntegerDigits`.

25.26 NCIntegerDigits

`NCIntegerDigits[n,b]` is the inverse of the `NCFromDigits`.

`NCIntegerDigits[{list1,list2}, b]` applies `NCIntegerDigits` to each `list1, list2, ...`.

For example:

```
NCIntegerDigits[{4,1}, 2]
```

returns

```
{0,0,0,1}
```

in which 4 is the degree of the monomial $x**x**x**y$ and 1 is 0001 in base 2. Likewise

```
NCIntegerDigits[{4,22}, 3]
```

returns

```
{0,2,1,1}
```

in which 4 is the degree of the monomial $x**z**y**y$ and 22 is 0211 in base 3.

If **b** is a list, then degree is also a list with the partial degrees of each letters appearing in the monomial. For example:

```
NCIntegerDigits[{3, 1, 22}, {1,2}]
```

returns

```
{0,2,1,1}
```

in which 3 is the partial degree of the monomial $x**z**y**y$ with respect to letters **y** and **z**, 1 is the partial degree with respect to letter **x** and 22 is 0211 in base 3 = 1 + 2.

See also: NCFromDigits.

25.27 NCPadAndMatch

When list **a** is longer than list **b**, NCPadAndMatch[**a**,**b**] returns the minimum number of elements from list **a** that should be added to the left and right of list **b** so that **a** = 1 **b** **r**. When list **b** is longer than list **a**, return the opposite match.

NCPadAndMatch returns all possible matches with the minimum number of elements.

Chapter 26

NCTest

Members are:

- `NCTest`
- `NCTestRun`
- `NCTestSummarize`

26.1 NCTest

`NCTest[expr,answer]` asserts whether `expr` is equal to `answer`. The result of the test is collected when `NCTest` is run from `NCTestRun`.

See also: `#NCTestRun`, `#NCTestSummarize`

26.2 NCTestRun

`NCTest[list]` runs the test files listed in `list` after appending the `‘.NCTest’` suffix and return the results.

For example:

```
results = NCTestRun[{"NCCollect", "NCSylvester"}]
```

will run the test files `“NCCollect.NCTest”` and `“NCSylvester.NCTest”` and return the results in `results`.

See also: `#NCTest`, `#NCTestSummarize`

26.3 NCTestSummarize

`NCTestSummarize[results]` will print a summary of the results in `results` as produced by `NCTestRun`.

See also: `#NCTestRun`