12,349,778 members (27,629 online)

jash.liao 🔻 898 Sign out 🔀



articles

Q&A

forums

lounge

Search for articles, questions, tips



Curve Fitting using Lagrange Interpolation





Fady Aladdin, 12 Sep 2008



Rate:




*** 4.55 (21 votes)

Fitting a set of points P to a curve using Lagrange Interpolation Polynomial.



Is your email address OK? You are signed up for our newsletters but your email address is either unconfirmed, or has not been reconfirmed in a long time. Please click here to have a confirmation email sent so we can confirm your email address and start sending you newsletters again. Alternatively, you can update your subscriptions.

Download source code - 20.9 KB



Introduction

In this article, I will explain curve fitting using the Lagrange interpolation polynomial. Curve fitting is used in a wide spectrum in engineering applications such as cars and air crafts surface design. The main problem is, given a set of points in the plan, we want to fit them in a smooth curve that passes through these points. The order of the curve f(x) depends on the number of points given. For example, if we have two points, the function will be of the first order, and the curve will be the line that passes through these two points, while if you have three points, the function will be of the second order $f(x) = x^2$. Let's first explain the Lagrange polynomial, then we will proceed to the algorithm and the implementation. In this article, I am using C# for coding.

Background

Lagrange Polynomial

An interpolation on two points, (x0, y0) and (x1, y1), results in a linear equation or a straight line. The standard form of a linear equation is given by y = mx + c, where m is the gradient of the line and c is the y-intercept.

Hide Copy Code

```
m = y1 - y0 / x1 - x0

c = y0 - mx0
```

which results in:

Hide Copy Code

```
y = (y1 - y0 / x1 - x0) * x + (x1 y0 - x0 y1 )/ (x1 - x0)
```

The linear equation is rewritten so that the two interpolated points, (x0, y0) and (x1, y1), are directly represented.

With this in mind, the linear equation is rewritten as:

Hide Copy Code

```
P1(x) = a0(x - x1) + a1(x - x0)
```

where a0 and a1 are constants. The points x0 and x1 in the factors of the above equation are called the *centers*. Applying the equation at (x0, y0), we obtain:

Hide Copy Code

```
y\theta = a\theta(x\theta - x1) + a1(x\theta - x0)

or

a\theta = y\theta/x\theta - x1
```

At (x1, y1), we get:

Hide Copy Code

```
y1 = a0(x1 - x1) + a1(x1 - x0), or a1 = y1/x1-x0
```

Therefore, the linear equation becomes:

Hide Copy Code

```
P1(x) = y0 (x-x1) / (x0 - x1) + y1 (x-x0) / (x1 - x0)
```

The quadratic form of the Lagrange polynomial interpolates three points, (x0, y0), (x1, y1), and (x2, y2). The polynomial has the form:

Hide Copy Code

```
P2(x) = a0(x-x1)(x-x2) + a1(x-x0)(x-x2) + a2(x-x0)(x-x1)
```

with centers at x0, x1, and x2. At (x0, y0):

Hide Copy Code

```
y\theta = a\theta(x\theta - x1)(x\theta - x2) + a1(x\theta - x\theta)(x\theta - x2) + a2(x\theta - x\theta)(x\theta - x1),
or
a\theta = y\theta/(x\theta - x1)(x\theta - x2)
a1 = y1 / (x1 - x\theta)(x1 - x2)
a2 = y2/(x2 - x\theta)(x2 - x1)
P2(x) = y\theta (x - x1)(x - x2) / (x\theta - x1)(x\theta - x2) + y1 (x - x\theta)(x - x2)/
(x1 - x\theta)(x1 - x2) + y2 (x - x\theta)(x - x1)/(x2 - x\theta)(x2 - x1)
```

In general, a Lagrange polynomial of degree n is a polynomial that is produced from an interpolation over a set of points, (xi, yi) for

i = 0, 1, ..., n, as follows:

Hide Copy Code

```
Pn(x) = y0L0(x) + y1L1(x) + \cdots + ynLn(x)
```

Using the Code

The Algorithm

Hide Copy Code

```
Given the interpolating points (xi , yi ) for i =0, 1, . . . ,n;

for i = 0 to n
   //the cumulative multiplication from k = 1 (and k not equal i) to n
   Evaluate Li (x) = ∏nk=1,k != i (x-xk ) / (xi-xk );
endfor

Evaluate Pn(x) = y0L0(x) + y1L1(x) + ··· + ynLn(x);
```

Download the source code from the top of this page to view the code.

Points of Interest

Numerical computing is a very interesting field in software development. This article is related to that field ... And, I will post more articles soon about Computational Geometry ...such as Convex Hull algorithm and Triangulation.

License

This article, along with any associated source code and files, is licensed under The Code Project Open License (CPOL)

Share

EMAIL

About the Author



Fady Aladdin_{No Biography} provided Software Developer Egypt

You may also be interested in...

Interpolation from Polynomial to Natural Splines #COBOLrocks TechCasts: New tricks for COBOL

devs


CCurveDlg - Curve Interpolation ES6 Arrow functions - The new fat and concise

syntax in JavaScript

C# Cubic Spline Interpolation

Strong Authentication and the Road to FIDO

Comments and Discussions





http://www.codeproject.com/Articles/28948/Curve-Fitting-using-Lagrange-Interpolation