

	Date	SYM	REVISION RECORD	AUTH	DR.	CK.
	10/22/05	Α	ADDED "ROHS COMPLIANT"	T.B.	B.S.	
	5/02/08	В	ADDED NOTE	T.B.	B.S.	
	7/11/14	С	UPDATED TO ROHS 2 COMPLIANT	T.B.	B.S.	
1				_		

NOTE:

ORIENTATION OF SNAPS AND WIRES VARIES AND IS SHOWN FOR REFERENCE ONLY. RED WIRE TO POSITIVE CONTACT. BLACK WIRE TO NEGATIVE CONTACT.

ROHS 2 COMPLIANT

N0.	PART NAME MATERIAL		QTY.	Tolerance	■ MPD Mem	ory Prote	Protection Devices, Inc		
1	COVER	PVC COVER OVER FIBERBOARD	1	(Except as noted)	200 Broad Hollow Road, Farmingdale, New York 11735				
2	BLACK WIRE(-)	24 AWG OR 26 AWG, UL-1007, CSA TR-64, 300V, 80°C	1	decimal	<u> </u>		Scale	Drawn By B.S.	
3	RED WIRE (+)	24 AWG OR 26 AWG, UL-1007, CSA TR-64, 300V, 80°C	1	(000)				·	
4	FEMALE SNAP	BRASS, NICKLE PLATED	1	±.5 (.020)				Approved By T.B.	
5	MALE SNAP	BRASS NICKLE PLATED	1	Fractional	Title				
	,		± .8 (.030)	9 VOLT BATTERY SNAP-I STYLE-6" WIRE LEADS					
			Angular	Date	Drawing Number				
				± 3°	7/11/14	BS6I			