



Business To Manufacturing Markup Language

Batch Markup Language

Version 0500 – February 15, 2012

Errata #5



IMPORTANT: While the information, data, and standards provided in this publication were developed and are presented in good faith in accordance with a reasonable process that was subject to intellectual property and antitrust policies to benefit the industry as a whole, the publication is provided “as is” for information and guidance only, and there is no representation or warranty of any type or kind, including but not limited to warranties of merchantability or fitness for a particular purpose, and no warranty that use of the information, data, or standards will not infringe patent, copyright, trademark, trade secret, or other intellectual property rights of any party.

1	Errata #1 - B2MML-V05-Common.xsd.....	5
2	Errata #2 - BatchML-V05-BatchInformation.xsd	6
3	Errata #3 - B2MML-V0500-OperationsDefinition.xsd.....	7
4	Errata #4 and #5 – Multiple Items	8
4.1	B2MML-V0500-Common.xsd	8
4.2	B2MML-V0500-OperationsPerformanceTypes.xsd.....	9
4.3	B2MML-V0500-OperationsPerformanceTypes.xsd.....	10
4.4	B2MML-V0500-OperationsSchedule.xsd	11

Change History:

Change	Date	Person	Description
#1	20 Apr 2011	Dennis Brandl	The group definition ProductProductionRuleIDGroup has an incorrect type for the ProductProductionRuleID element.
#2	19 May 2011	Dennis Brandl	The extension element in the FromIDType (line 682) is incorrect.
#3	7 Aug 2011	Dennis Brandl	The OperationsMaterialBillType has a wrong definition for the OperationsMaterialBillItem. The maxOccurs="unbounded" is missing in the element definition
#4	24 Jan 2012	Dennis Brandl	<ol style="list-style-type: none">1. The "TimingFactor" element in a SegmentDerpendancy is a ValueType but did not get the update to make it maxOccurs=unbounded2. SegmentData has the <i>Description</i> element defined after the <i>Value</i> element. Every other message has it directly after the <i>ID</i> element. To simplify processing of all message types, the <i>Description</i> element should be moved to after the <i>ID</i> element3. MaterialActualProperty is not recursive like MaterialDefinitionProperty. This means the results in the performance message cannot reflect the structure of the definition in the material master.4. MaterialRequirementProperty is not recursive like MaterialDefinitionProperty. This means the requirements in the schedule message cannot reflect the structure of the definition in the material master.
#5	15 Feb 2012	Dennis Brandl	<ol style="list-style-type: none">1. The "name" attribute in the new definitions of Errata #4 was wrong in (4.3) and (4.4). It should not contain the string "type" or the spaces after the first quote.2. In 4.3, the MaterialActualProperty should come after Quantity and before RequiredByRequestedSegmentResponse.3. The heading of 4.4 was incorrect, it should be B2MML-V0500-OperationsSchedule.xsd

			<p>4. In 4.1 the “TimingFactor” element in a SegmentDerpendancy is a ValueType but did not get the update to make it maxOccurs=unbounded</p> <p>5. In 4.2 the Description element in OPSegmentDataType has been moved to be consistent with other types.</p>
--	--	--	--

Applying the changes:

This errata document includes all the patches in previous V0500 errata documents. You should make the identified changes to the schemas in your local copies to correct the problems. The changes should be made in the order listed below.

1 Errata #1 - B2MML-V05-Common.xsd

The following problem has been identified in the schemas.

The group definition ProductProductionRuleIDGroup has an incorrect type for the ProductProductionRuleID element.

It is defined as:

```
<xsd:group name="ProductProductionRuleIDGroup">
  <xsd:sequence>
    <xsd:element name="ProductProductionRuleID"
      type="ProductionRequestIDType" minOccurs="0"/>
    <xsd:element name="Version"
      type="VersionType" minOccurs="0"/>
  </xsd:sequence>
</xsd:group>
```

It should be defined as:

```
<xsd:group name="ProductProductionRuleIDGroup">
  <xsd:sequence>
    <xsd:element name="ProductProductionRuleID"
      type=" ProductProductionRuleIDType" minOccurs="0" />
    <xsd:element name="Version"
      type="VersionType" minOccurs="0"/>
  </xsd:sequence>
</xsd:group>
```

2 Errata #2 - BatchML-V05-BatchInformation.xsd

The following problem has been identified in the schemas.

The extension element in the FromIDType (line 682) is incorrect.

It is defined as:

```
<!-- Complex Type with Extension -->
<xsd:complexType name = "FromIDType">
  <xsd:sequence>
    <xsd:element name = "FromIDValue"           type = "xsd:string" />
    <xsd:element name = "FromType"              type = "FromTypeType" />
    <xsd:element name = "IDScope"               type = "IDScopeType" />
    <xsd:group   ref = "Extended:FromEquipmentID"
                                                         minOccurs="0" maxOccurs="1"/>
  </xsd:sequence>
</xsd:complexType>
```

It should be defined as:

```
<!-- Complex Type with Extension -->
<xsd:complexType name = "FromIDType">
  <xsd:sequence>
    <xsd:element name = "FromIDValue"           type = "xsd:string" />
    <xsd:element name = "FromType"              type = "FromTypeType" />
    <xsd:element name = "IDScope"               type = "IDScopeType" />
    <xsd:group   ref = "Extended:FromID"
                                                         minOccurs="0" maxOccurs="1"/>
  </xsd:sequence>
</xsd:complexType>
```

3 Errata #3 - B2MML-V0500-OperationsDefinition.xsd

The following problem has been identified in the schemas.

The OperationsMaterialBillType has a wrong definition for the OperationsMaterialBillItem. The maxOccurs="unbounded" is missing in the element definition.

It is defined as:

```
<xsd:complexType name="OperationsMaterialBillType">
  <xsd:sequence>
    <xsd:element name="ID" type="IdentifierType"/>
    <xsd:element name="Description" type="DescriptionType" minOccurs="0"/>
    <xsd:element name="OperationsMaterialBillItem"
      type="OperationsMaterialBillItemType"
      minOccurs="0"/>
    <xsd:group ref="Extended:OperationsMaterialBill" minOccurs="0"/>
  </xsd:sequence>
</xsd:complexType>
```

It should be defined as:

```
<xsd:complexType name="OperationsMaterialBillType">
  <xsd:sequence>
    <xsd:element name="ID" type="IdentifierType"/>
    <xsd:element name="Description" type="DescriptionType" minOccurs="0"/>
    <xsd:element name="OperationsMaterialBillItem"
      type="OperationsMaterialBillItemType"
      minOccurs="0" maxOccurs="unbounded"/>
    <xsd:group ref="Extended:OperationsMaterialBill" minOccurs="0"/>
  </xsd:sequence>
</xsd:complexType>
```

4 Errata #4 and #5 – Multiple Items

Errata #4 and #5 consist of 4 patches. Errata #5 consists of corrections to Errata #4, these are indicated by underlining in the schema patches.

4.1 B2MML-V0500-Common.xsd

The “TimingFactor” element in a SegmentDerpendancy is a ValueType but did not get the update to make it maxOccurs=unbounded.

It is defined as:

```
<xsd:complexType name = "SegmentDependencyType">
  <xsd:sequence>
    <xsd:element name = "ID" type="IdentifierType"/>
    <xsd:element name = "Description" type="DescriptionType"
      minOccurs="0" maxOccurs="unbounded"/>
    <xsd:element name = "Dependency" type="DependencyType"/>
    <xsd:element name = "TimingFactor" type="ValueType"
      minOccurs="0"/>
    <xsd:choice minOccurs="0" maxOccurs="unbounded">
      <xsd:element name = "ProductSegmentID" type="ProductSegmentIDType"/>
      <xsd:element name = "ProcessSegmentID" type="ProcessSegmentIDType"/>
      <xsd:element name = "SegmentID" type="IdentifierType"/>
    </xsd:choice>
    <xsd:group ref = "Extended:SegmentDependency"
      minOccurs="0" maxOccurs="1"/>
  </xsd:sequence>
</xsd:complexType>
```

It should be defined as:

```
xsd:complexType name = "SegmentDependencyType">
  <xsd:sequence>
    <xsd:element name = "ID" type="IdentifierType"/>
    <xsd:element name = "Description" type="DescriptionType"
      minOccurs="0" maxOccurs="unbounded"/>
    <xsd:element name = "Dependency" type="DependencyType"/>
    <xsd:element name = "TimingFactor" type="ValueType"
      minOccurs="0" maxOccurs="unbounded"/>
    <xsd:choice minOccurs="0" maxOccurs="unbounded">
      <xsd:element name = "ProductSegmentID" type="ProductSegmentIDType"/>
      <xsd:element name = "ProcessSegmentID" type="ProcessSegmentIDType"/>
      <xsd:element name = "SegmentID" type="IdentifierType"/>
    </xsd:choice>
    <xsd:group ref = "Extended:SegmentDependency"
      minOccurs="0" maxOccurs="1"/>
  </xsd:sequence>
</xsd:complexType>
```


4.2 B2MML-V0500-OperationsPerformanceTypes.xsd

SegmentData has the *Description* element defined after the *Value* element. Every other message has it directly after the *ID* element. To simplify processing of all message types, the *Description* element should be moved to after the *ID* element. You should make the identified changes to the schemas in your local copies to correct the problems:

It is defined as:

```
<xsd:complexType name = "OpSegmentDataType">
  <xsd:sequence>
    <xsd:element name = "ID"          type="IdentifierType"/>
    <xsd:element name = "Value"       type="ValueType"
      minOccurs="0" maxOccurs="unbounded"/>
    <xsd:element name = "Description" type="DescriptionType"
      minOccurs="0" maxOccurs="unbounded"/>
    <xsd:element name = "SegmentData" type="OpSegmentDataType"
      minOccurs="0" maxOccurs="unbounded"/>
    <xsd:element name = "RequiredByRequestedSegmentResponse"
      type = "RequiredByRequestedSegmentResponseType"
      minOccurs = "0"/>
    <xsd:group ref = "Extended:OpSegmentData"
      minOccurs="0" maxOccurs="1"/>
  </xsd:sequence>
</xsd:complexType>
```

It should be defined as:

```
<xsd:complexType name = "OpSegmentDataType">
  <xsd:sequence>
    <xsd:element name = "ID"          type="IdentifierType"/>
    <xsd:element name = "Description" type="DescriptionType"
      minOccurs="0" maxOccurs="unbounded"/>
    <xsd:element name = "Value"       type="ValueType"
      minOccurs="0" maxOccurs="unbounded"/>
    <xsd:element name = "SegmentData" type="OpSegmentDataType"
      minOccurs="0" maxOccurs="unbounded"/>
    <xsd:element name = "RequiredByRequestedSegmentResponse"
      type = "RequiredByRequestedSegmentResponseType"
      minOccurs = "0"/>
    <xsd:group ref = "Extended:OpSegmentData"
      minOccurs="0" maxOccurs="1"/>
  </xsd:sequence>
</xsd:complexType>
```

4.3 B2MML-V0500-OperationsPerformanceTypes.xsd

MaterialActualProperty is not recursive like MaterialDefinitionProperty. This means the results in the performance message cannot reflect the structure of the definition in the material master. You should make the identified changes to the schemas in your local copies to correct the problems:

It is defined as:

```
<xsd:complexType name = "OpMaterialActualPropertyType">
  <xsd:sequence>
    <xsd:element name = "ID" type = "IdentifierType" />
    <xsd:element name = "Description" type = "DescriptionType"
      minOccurs = "0" maxOccurs = "unbounded"/>
    <xsd:element name = "Value" type = "ValueType"
      minOccurs = "0" maxOccurs = "unbounded"/>
    <xsd:element name = "Quantity" type = "QuantityValueType"
      minOccurs = "0" maxOccurs = "unbounded"/>
    <xsd:element name = "RequiredByRequestedSegmentResponse"
      type = "RequiredByRequestedSegmentResponseType"
      minOccurs = "0"/>
    <xsd:group ref = "Extended:OpMaterialActualProperty"
      minOccurs = "0" maxOccurs = "1"/>
  </xsd:sequence>
</xsd:complexType>
```

It should be defined as:

```
xsd:complexType name = "OpMaterialActualPropertyType">
  <xsd:sequence>
    <xsd:element name = "ID" type = "IdentifierType" />
    <xsd:element name = "Description" type = "DescriptionType"
      minOccurs = "0" maxOccurs = "unbounded"/>
    <xsd:element name = "Value" type = "ValueType"
      minOccurs = "0" maxOccurs = "unbounded"/>
    <xsd:element name = "Quantity" type = "QuantityValueType"
      minOccurs = "0" maxOccurs = "unbounded"/>
    <xsd:element name = "MaterialActualProperty"
type = "OpMaterialActualPropertyType"
minOccurs = "0" maxOccurs = "unbounded"/>
    <xsd:element name = "RequiredByRequestedSegmentResponse"
      type = "RequiredByRequestedSegmentResponseType"
      minOccurs = "0"/>
    <xsd:group ref = "Extended:OpMaterialActualProperty"
      minOccurs = "0" maxOccurs = "1"/>
  </xsd:sequence>
</xsd:complexType>
```

4.4 B2MML-V0500-OperationsSchedule.xsd

MaterialRequirementProperty is not recursive like MaterialDefinitionProperty. This means the requirements in the schedule message cannot reflect the structure of the definition in the material master. You should make the identified changes to the schemas in your local copies to correct the problems:

It is defined as:

```
<xsd:complexType name = "OpMaterialRequirementPropertyType">
  <xsd:sequence>
    <xsd:element name = "ID"          type = "IdentifierType"
                  minOccurs = "0"/>
    <xsd:element name = "Description" type = "DescriptionType"
                  minOccurs = "0" maxOccurs = "unbounded"/>
    <xsd:element name = "Value"       type = "ValueType"
                  minOccurs = "0" maxOccurs = "unbounded"/>
    <xsd:element name = "Quantity" type = "QuantityValueType"
                  minOccurs = "0" maxOccurs = "unbounded"/>
    <xsd:group ref = "Extended:OpMaterialRequirementProperty"
               minOccurs = "0" maxOccurs = "1"/>
  </xsd:sequence>
</xsd:complexType>
```

It should be defined as:

```
<xsd:complexType name = "OpMaterialRequirementPropertyType">
  <xsd:sequence>
    <xsd:element name = "ID"          type = "IdentifierType"
                  minOccurs = "0"/>
    <xsd:element name = "Description" type = "DescriptionType"
                  minOccurs = "0" maxOccurs = "unbounded"/>
    <xsd:element name = "Value"       type = "ValueType"
                  minOccurs = "0" maxOccurs = "unbounded"/>
    <xsd:element name = "Quantity" type = "QuantityValueType"
                  minOccurs = "0" maxOccurs = "unbounded"/>
    <xsd:element name = "MaterialRequirementProperty"
    type = "OpMaterialRequirementPropertyType"
    minOccurs = "0" maxOccurs = "unbounded"/>
    <xsd:group ref = "Extended:OpMaterialRequirementProperty"
               minOccurs = "0" maxOccurs = "1"/>
  </xsd:sequence>
</xsd:complexType>
```