

4.058 Combined Bearing

Family: Standard



4.058

Combined roller bearing

Configuration illustration - not to scale

Standard combined bearing in the 88.4 mm outside-diameter class with multiple common cross-references.

Typical application: Forklift masts, heavy warehouse equipment, steel profiles and industrial lifting systems.

Common references: MR0025 / MR0025G88.4 / JD88.4-57 / 400-0058 / TR090.0200

Catalog dimensions and ratings

Parameter	Catalog value	Parameter	Catalog value
d	45 mm	D	88.4 mm
H	57 mm	h	44 mm
B	30 mm	S	26 mm
A	3.5 mm	r	3 mm
T	59 mm	FR	22.4 kN
FA	7 kN	Cr	68 kN
C0r	72 kN	Ca	23 kN
C0a	23 kN	nG	750 rpm
Mass	1.62 kg		

Quotation verification

- Confirm the complete designation, suffix and marking photographs.
- Verify d, D, H, h, B, S, T and every mounting interface on the controlled drawing.
- Check radial and axial load, speed, shock, duty cycle, profile and lubrication.
- Agree inspection records, marking and packing scope before order.

Identification reference only. This sheet is not a controlled manufacturing drawing, interchange approval or batch inspection certificate. Final supply is governed by the confirmed quotation and controlled drawing.