

4.059 Combined Bearing

Family: Standard



4.059

Combined roller bearing

Configuration illustration - not to scale

Standard combined bearing with 101.2 mm outside diameter, available alone or with a galvanized mounting plate.

Typical application: Forklift masts, welded plate assemblies, lifting equipment and logistics guide systems.

Common references: JD101.2-46 / 400-0059 / HYV30201

Catalog dimensions and ratings

Parameter	Catalog value	Parameter	Catalog value
d	50 mm	D	101.2 mm
H	46 mm	h	33 mm
B	28 mm	S	30 mm
A	3 mm	r	3 mm
T	67 mm	FR	22 kN
FA	7 kN	Cr	73 kN
C0r	82 kN	Ca	25 kN
C0a	27 kN	nG	700 rpm
Mass	1.74 kg		

Quotation verification

- Confirm the complete designation, suffix and marking photographs.
- Verify d, D, H, h, B, S, T and every mounting interface on the controlled drawing.
- Check radial and axial load, speed, shock, duty cycle, profile and lubrication.
- Agree inspection records, marking and packing scope before order.

Identification reference only. This sheet is not a controlled manufacturing drawing, interchange approval or batch inspection certificate. Final supply is governed by the confirmed quotation and controlled drawing.