

MR.142 / MR.146-MR.154 High-Load Axial-Support Bearings

High-load combined bearings with hardened axial support and washer adjustment.

Model	d mm	D mm	C mm	H / range mm	Cr kN	C0r kN	Ca kN	C0a kN	Speed rpm	Mass kg
MR.146	30	62	20	43	39	65	10	14	900	0.60
MR.147	35	70.1	23	48	56	93	10	14	900	0.90
MR.148	40	77.7	23	50.5	58	101.5	14	22	800	1.05
MR.149	40	78.3	23	45	58	101.5	14	22	800	0.95
MR.150	45	88.9	30	61	84	133	14	22	700	1.70
MR.151	50	101.9	28	50.5	91	153	18	22	700	1.85
MR.142 / 4.0784	60	107.7	31	69	94	162	39	57	650	2.40
MR.152 / 4.078	55	108.55	31	58.5	94	162	39	57	650	2.80
MR.153	60	123	37	75.8	132	242	39	57	500	4.10
MR.154	60	149	43	89	179	353	83	131	400	6.80

Verification notes

- Adapter washers: 0.3, 0.5 and 1.0 mm.
- MR.142 cross-references 4.0784; MR.152 cross-references 4.078.
- Confirm tapered or cylindrical outer-ring execution.

Before ordering, confirm the current controlled drawing, suffix, mounting geometry, load case, lubrication, temperature and inspection scope.