

# MR.961-MR.968 Screw-Adjustable Combined Bearings

Factory catalog dimensions and ratings. Axial adjustment uses a UNI 5929 / DIN 916 screw.

| Model  | d mm | D mm  | C mm | H / range mm | Cr kN | C0r kN | Ca kN | C0a kN | Speed rpm | Mass kg |
|--------|------|-------|------|--------------|-------|--------|-------|--------|-----------|---------|
| MR.961 | 30   | 62    | 20   | 37.5-39.5    | 39    | 65     | -     | -      | 900       | 0.52    |
| MR.962 | 35   | 70.1  | 23   | 38.5-40.5    | 56    | 93     | -     | -      | 900       | 0.60    |
| MR.963 | 40   | 77.7  | 23   | 40.7-42.7    | 58    | 101.5  | -     | -      | 800       | 0.82    |
| MR.964 | 45   | 88.9  | 30   | 48.5-51      | 84    | 133    | 15    | 22     | 700       | 1.43    |
| MR.965 | 50   | 101.9 | 28   | 46-48.5      | 91    | 153    | 18    | 22     | 700       | 1.70    |
| MR.966 | 55   | 107.7 | 31   | 53.5-56.5    | 94    | 162    | 31    | 40     | 650       | 2.45    |
| MR.967 | 60   | 123   | 33   | 61.5-64.5    | 132   | 242    | 31    | 40     | 500       | 3.50    |
| MR.968 | 60   | 149   | 43   | 75.5-79      | 179   | 353    | 68    | 71     | 400       | 6.50    |

## Verification notes

- DIN 620 P0 tolerance and clearance basis.
- ISO 76 and ISO 281 load-rating basis.
- Outer ring 16NiCr4; inner ring and rolling elements 100Cr6.

Before ordering, confirm the current controlled drawing, suffix, mounting geometry, load case, lubrication, temperature and inspection scope.