

# COSC 304

## Introduction to Database Systems

### Database Web Programming

**Dr. Ramon Lawrence**  
**University of British Columbia Okanagan**  
 ramon.lawrence@ubc.ca

## Database Web Programming Overview

Web applications consist of a client interface and a server component.

The client interface does not access the database directly. The server code accesses the database and provides the data as needed to the client.

- ◆ The server code may be JSP/Servlets, PHP, Python, etc.
- ◆ The client code is HTML/JavaScript.

HTTP is a stateless protocol which requires special handling to remember client state.

Page 2

## Static versus Dynamic Content

**Static** content: the HTML is created once and is always the same (although it may include client-side scripts (JavaScript)).

**Dynamic** content: the HTML is produced when requested. Requires the web server to dynamically generate the output.

Page 3

## Dynamic HTML and JDBC


Dynamic HTML involves constructing HTML output dynamically on the server then sending it to the client.

By building the content dynamically, it can have different content for each user. Typically, this dynamic content is retrieved from databases and then inserted into the HTML.

The two standard ways for generating dynamic content using Java are **Java Server Pages (JSPs)** and **Servlets**. Since both use Java, they can use JDBC to retrieve dynamic, database content.

Page 4

## Dynamic Web Server Architecture



Page 5

## JSP/Servlet Question

**Question: True or False:** Java JSP/Servlet code runs in the browser.

- A) true
- B) false

Page 6

## JSP/Servlet Question #2

**Question: True or False:** JavaScript running in the browser can connect to a database directly using JDBC.

A) true

B) false

Page 7

## Java Server Pages (JSPs)

**Java Server Pages (JSPs)** provide a layer above `Servlets` that allow you to mix HTML and calls to Java code.

JSPs are converted into `Servlets`, and are easier to work with for those familiar with HTML.

Page 8

## Java Server Pages (JSPs) (2)

How to create JSPs:

◆1) Create a file with a `.jsp` extension that contains HTML.

◆2) Include JSP Scripting Elements in the file such as:

- ⇒ Expressions    `<%= expression %>`
  - Note that an expression returns a string into the HTML.
- ⇒ Scriptlets     `<% code %>`
- ⇒ Declarations `<%! Code %>`
- ⇒ Directives    `<%@ variable directive %>`
- ⇒ Comments     `<!-- JSP Comment -->`

◆3) Can use pre-defined variables:

- ⇒ `request`       `HttpServletRequest`
- ⇒ `response`      `HttpServletResponse`
- ⇒ `session`       `HttpSession`
- ⇒ `out`            `PrintWriter`
  - Prints to HTML document.

Page 9

## JSP "Hello World!"

```
<html>
<head>
<title>Hello World in JSP</title>
</head>
<body>
```

```
<% out.println("Hello World!"); %>
```

```
</body>
</html>
```

← Java code embedded in HTML file.

Page 10

## Useful JSP Code

Include another file:

```
<%@ include file="commontop.html" %>
```

Import from the Java library:

```
<%@ page import="java.util.*" %>
```

Declare and use a variable:

```
<%! private int accessCount = 0 %>
<h2>Accesses to page since server reboot:
<%= ++accessCount %></h2>
```

Access session and request information:

```
<h2>Current time: <%= new java.util.Date() %></h2>
<h2>Remote Host: <%= request.getRemoteHost() %></h2>
<h2>Session ID: <%= session.getID() %></h2>
```

Page 11

## JSP and JDBC

```
<%@ page import="java.sql.*" %>
```

```
<html>
<head><title>Query Results Using JSP</title></head><body>
```

```
<%
    Connection con = null;
    try
    { // Note: Need to define url, uid, pw
      con = DriverManager.getConnection(url, uid, pw);
      Statement stmt = con.createStatement();
      ResultSet rst = stmt.executeQuery("SELECT ename,salary
                                         FROM Emp");
```

Page 12

## JSP and JDBC (2)

```

out.print("<table><tr><th>Name</th>");
out.println("<th>Salary</th></tr>");
while (rst.next())
{   out.println("<tr><td>"+rst.getString(1)+"</td>"
    + "<td>"+rst.getDouble(2)+"</td></tr>");
}
out.println("</table>");
con.close();
}
catch (SQLException ex)      { out.println(ex); }
finally
{   if (con != null)
    try
    {   con.close(); }
    catch (SQLException ex) { out.println(ex); }
}
%>
</body>
</html>

```

Page 13

## Answering Queries using HTML Forms

One of the common uses of dynamic web pages is to construct answers to user queries expressed using HTML forms.

The HTML code will contain a `FORM` and the `FORM ACTION` will indicate the server code to call to process the request.

In our example, the JSP or Servlet gets the HTML request (and parameters in the URL), queries the database, and returns the answers in a table.

Page 14

## HTTP GET and POST Methods

`GET` and `POST` are two ways a HTTP client can communicate with a web server. `GET` is used for getting data from the server, and `POST` is used for sending data there.

- ◆ `GET` appends the form data (called a query string) to an URL, in the form of key/value pairs, for example, `name=John`.
  - ⇒ In the query string, key/value pairs are separated by `&` characters, spaces are converted to `+` characters, and special characters are converted to their hexadecimal equivalents.
  - ⇒ Since the query string is in the URL, the page can be bookmarked. The query string is usually limited to a relatively small amount of data.
- ◆ `POST` passes data of unlimited length as an HTTP request body to the server. The user working in the client Web browser cannot see the data that is being sent, so `POST` requests are ideal for sending confidential or large amounts of data to the server.

Page 15

## GET vs. POST Question

**Question:** Select a **true** statement.

- A) Data sent using `POST` is passed as part of the URL.
- B) A `GET` request with all parameters cannot be bookmarked.
- C) Your servlet can do the same action for both `GET` and `POST` requests.
- D) A `GET` request is used to send a large amount of data.

Page 16

## HTML Form

```

<html>
<head>
<title>Querying Using JSP/Servlets and Forms</title>
</head>
<body>

<h1>Enter the name and/or department to search for:</h1>

<form method="get"
    action="http://cosc304.ok.ubc.ca/tomcat/EmpQuery.jsp">
Name:<input type="text" name="empname" size="25">
Dept:<input type="text" name="deptnum" size="5">
<input type="submit" value="Submit">
<input type="reset" value="Reset">
</form>

</body>
</html>

```

↑  
FORM action  
and type

↑  
FORM buttons and  
input fields

Page 17

## Reading Parameters

Parameters passed into the JSP are accessible using the request object:

```

String empName = request.getParameter("empname");
String deptNum = request.getParameter("deptnum");

```

Page 18

## Reading Parameters

### Badly Building a Query – SQL Injection!

```
String empName = request.getParameter("empname");
String deptNum = request.getParameter("deptnum");
try
{
    con = DriverManager.getConnection(url, uid, pw);
    Statement stmt = con.createStatement();
    String SQLSt = "SELECT ename, salary, dno FROM Emp "
        + "WHERE 1=1 ";

    if (empName != null && !empName.equals(""))
        SQLSt = SQLSt + " and ename LIKE '%" + empName + "%'";

    if (deptNum != null && !deptNum.equals(""))
        SQLSt = SQLSt + " and dno = '" + deptNum + "'";

    ResultSet rst = stmt.executeQuery(SQLSt);
    ...
}
```

Page 19

## Building a Query using a PreparedStatement

```
String empName = request.getParameter("empname");
String deptNum = request.getParameter("deptnum");
try
{
    con = DriverManager.getConnection(url, uid, pw);
    String sql = "SELECT ename, salary, dno FROM Emp";
    boolean hasEmp = empName != null && !empName.equals("");
    boolean hasDept = deptNum != null && !deptNum.equals("");

    PreparedStatement pstmt=null;
    ResultSet rst = null;

    if (!hasEmp && !hasDept)
    {
        pstmt = con.prepareStatement(sql);
        rst = pstmt.executeQuery();
    }
}
```

Page 20

## Building a Query using a PreparedStatement

```
else if (hasEmp)
{
    empName = "%" + empName + "%";
    sql += " WHERE ename LIKE ?";
    if (hasDept)
        sql += " AND dno = ?";
    pstmt = con.prepareStatement(sql);
    pstmt.setString(1, empName);
    if (hasDept)
        pstmt.setString(2, deptNum);
    rst = pstmt.executeQuery();
}
else if (hasDept)
{
    sql += " WHERE dno = ?";
    pstmt = con.prepareStatement(sql);
    pstmt.setString(1, deptNum);
    rst = pstmt.executeQuery();
}
...
}
```

Page 21

## JSP Examples

### Implementing Login and Security

How do you password protect files in your web site?

The basic idea is to:

- ◆ Create a login page like login.jsp.
- ◆ Create a page to validate the user login (often by connecting to the database to determine if given valid user id/password).
- ◆ Create a file containing JSP code that is included in every one of your protected pages. This code:
  - ⇒ Examines if a session variable flag is set indicating if logged in.
  - ⇒ If user is logged in, show page. Otherwise redirect to login page.

Page 22

## Implementing Login and Security

### login.jsp

```
<html>
<head><title>Login Screen</title></head>
<body>
<center>
<h3>Please Login to System</h3>

<%
// Print prior error login message if present
if (session.getAttribute("loginMessage") != null)
    out.println("<p>" +
        session.getAttribute("loginMessage").toString() + "</p>");
%>

<br>
```

Page 23

## Implementing Login and Security

### login.jsp (2)

```
<form name="MyForm" method=post action="validateLogin.jsp">
<table width="40%" border="0" cellspacing="0" cellpadding="0">
<tr>
<td><div align="right">Username:</div></td>
<td><input type="text" name="username" size=8 maxlength=8></td>
</tr>
<tr>
<td><div align="right">Password:</div></td>
<td><input type="password" name="password" size=8
        maxlength=8></td>
</tr>
</table>
<input class="submit" type="submit" name="Sub" value="Log In">
</form>
<br/>
</center>
</body>
</html>
```

Page 24

## Implementing Login and Security

### validateLogin.jsp

```
<%@ page language="java" import="java.io.*" %>
<%
    String authenticatedUser = null;
    session = request.getSession(true); // May create new session
    try
    {
        authenticatedUser = validateLogin(out,request,session);
    }
    catch(IOException e)
    {
        System.err.println(e);
    }

    if(authenticatedUser != null)
        response.sendRedirect("protectedPage.jsp"); // Success
    else
        response.sendRedirect("login.jsp"); // Failed login
        // Redirect back to login page with a message
%>
```

Page 25

## Implementing Login and Security

### validateLogin.jsp (2)

```
<%!
String validateLogin(JspWriter out,HttpServletRequest request,
                    HttpSession session) throws IOException
{
    String username = request.getParameter("username");
    String password = request.getParameter("password");
    String retStr = null;

    if(username == null || password == null)
        return null;
    if((username.length() == 0) || (password.length() == 0))
        return null;

    // Should make a database connection here and check password
    // Here just hard-coding password
    if (username.equals("test") && password.equals("test"))
        retStr = username;
}
```

Page 26

## Implementing Login and Security

### validateLogin.jsp (3)

```
try { // Login using database version
    // Make database connection -- Sample query:
    String query = "SELECT pswd FROM User WHERE userID =
        BINARY '"+username+"' AND pswd = BINARY '"+password+"'";
    ResultSet rst = executeQuery(con,query);
    if (!rst.next()) // Such a record does not exist
        retStr = "";

}
catch(SQLException e) { System.err.println(ex); }
finally { // Close database connection }

if(retStr != null)
{
    session.removeAttribute("loginMessage");
    session.setAttribute("authenticatedUser",username);
}
else
    session.setAttribute("loginMessage","Failed login.");
return retStr;
} %>
```

Page 27

## Implementing Login and Security

### protectedPage.jsp

```
<html>
<head><title>Password Protected Page</title></head>
<body>

<%@ include file="auth.jsp"%>

<%
String user = (String)session.getAttribute("authenticatedUser");
out.println("<h1>You have access to this page: "+user+"</h1>");
%>

</body>
</html>
```

Page 28

## Implementing Login and Security

### auth.jsp

```
<%
Object authUser = session.getAttribute("authenticatedUser");
boolean authenticated = authUser == null ? false : true;

if (!authenticated)
{
    String loginMessage = "You have not been authorized to "+
        " access the URL "+request.getRequestURL().toString();
    session.setAttribute("loginMessage",loginMessage);
    response.sendRedirect("login.jsp");
    return;
}
%>
```

Page 29

## JSP Examples

### Passing Objects Between Pages

How do you pass information between pages?

One way is to encode that information in the URL as parameters. These parameters can be extracted from the request object.

If you have a lot of information, it is better to use the `session` object. The session object allows you to store any number of objects that are later looked up by name. Since they remain on the server, performance/security is improved.

Page 30

## Passing Objects Between Pages

### sendingPage.jsp

```
<%@ page import="java.util.ArrayList,java.util.Random" %>
<html>
<head><title>Sending Data Page</title></head>
<body>

<%
    // Generate and print array
    ArrayList ar = new ArrayList(20);
    Random generator = new Random();
    out.println("<h2>Created the following array:</h2>");
    for (int i = 0; i < 20; i++)
    {   ar.add(new Integer(generator.nextInt(10)));
        out.println(ar.get(i)+"<BR>");
    }
    // Store arraylist in a session variable
    session.setAttribute("arraydata",ar);
%>
</body>
</html>
```

Page 31

## Passing Objects Between Pages

### receivingPage.jsp

```
<%@ page import="java.util.ArrayList" %>
<html>
<head><title>Receiving Data Page</title> </head>
<body>

<%
    ArrayList ar = (ArrayList)session.getAttribute("arraydata");
    if (ar == null)
        out.println("<h2>No data sent to page.</h2>");
    else
    {   out.println("<h2>Received the following array:</h2>");
        for (int i = 0; i < 20; i++)
            out.println(ar.get(i)+"<BR>");
    }
%>
</body>
</html>
```

Page 32

## Session Question

**Question: True or False:** Data associated with a session remains on the server.

A) true

B) false

Page 33

## Servlets

Servlets are Java programs that run inside a web server that can perform server-side processing such as interacting with a database or another application. Servlets can generate dynamic html and return this to the client.

How to create a Servlet:

- ◆1) create an HTML file that invokes a Servlet (usually through the FORM ACTION=...).
- ◆2) create a Java program that does the following:
  - ⇒import javax.servlet.\*;
  - ⇒import javax.servlet.http.\*;
  - ⇒inherit from HttpServlet
  - ⇒override the doGet and doPost methods
  - ⇒write the response HTML file using java.io.PrintWriter

Page 34

## Servlets Notes

There is one instance of Servlet for each Servlet name, and the same instance serves all requests to that name.

Instance members persist across all requests to that name.

Local variables in doPost and doGet are unique to each request.

Page 35

## Servlets "Hello World!"

```
import javax.servlet.*;
import javax.servlet.http.*; ← Import Servlet API

public class HelloServlet extends HttpServlet {
    public void init(ServletConfig cfg) throws ServletException {
        super.init(cfg); // First time Servlet is invoked
    }

    public void doGet(HttpServletRequest request, HttpServletResponse response)
        throws ServletException, java.io.IOException {
        doHello(request, response);
    }

    public void doPost(HttpServletRequest request, HttpServletResponse response)
        throws ServletException, java.io.IOException {
        doHello(request, response);
    }

    private void doHello(HttpServletRequest request, HttpServletResponse response)
        throws ServletException, java.io.IOException {
        response.setContentType("text/html");
        java.io.PrintWriter out = response.getWriter();
        out.println("<html><head><title>Hello World</title></head>");
        out.println("<body><h1>Hello World</h1></body></html>");
        out.close();
    }
}
```

Get & Post

Write out HTML file for client

Page 36

## Servlets and JDBC

```
import javax.servlet.*;
import javax.servlet.http.*;
import java.sql.*;

public class JdbcServlet extends HttpServlet {

    private Connection con;

    public void init(ServletConfig cfg) throws ServletException {
        super.init(cfg);

        String url = "<fill-in>";
        con = null;
        try
        {
            con = DriverManager.getConnection(url);
        }
        catch (SQLException e)
        {
            throw new ServletException("SQLException: " + e);
        }
    }
}
```

Page 37

## Servlets and JDBC (2)

```
public void destroy()
{
    try {
        if (con != null)
            con.close();
    }
    catch (SQLException e)
    {
        System.err.println("SQLException: " + e);
    }
}

public void doGet(HttpServletRequest request, HttpServletResponse response)
    throws ServletException, java.io.IOException
{
    doTable(request, response);
}

public void doPost(HttpServletRequest request, HttpServletResponse response)
    throws ServletException, java.io.IOException
{
    doTable(request, response);
}
}
```

Page 38

## Servlets and JDBC (3)

```
private void doTable(HttpServletRequest request, HttpServletResponse response)
    throws ServletException, java.io.IOException {
    response.setContentType("text/html");
    java.io.PrintWriter out = response.getWriter();
    out.println("<html><head><title></title></head>");

    if (con == null)
        out.println("<body><H1>Unable to connect to DB</H1></body></html>");
    else
    {
        try {
            Statement stmt = con.createStatement();
            ResultSet rst = stmt.executeQuery("SELECT ename,salary FROM Emp");

            out.print("<table><tr><th>Name</th><th>Salary</th></tr>");
            while (rst.next())
            {
                out.println("<tr><td>" + rst.getString(1) + "</td>"
                    + "<td>" + rst.getDouble(2) + "</td></tr>");
            }
            out.println("</table></body></html>");
            out.close();
        } catch (SQLException ex) { System.err.println(ex); }
    }
}
```

Page 39

## JSP and Servlets Discussion

Java Server Pages (JSPs) are HTML files with embedded Java code. They are easier to produce because the HTML file is the main product and the Java code is secondary.

When a JSP file is actually used, it is converted to a Servlet and run. Apache Tomcat handles the conversion and execution of the Servlet.

The advantage of JSP over Servlets is that the HTML page can be edited by users not familiar with the Java language using standard HTML editors and the Java code added separately by programmers.

Page 40

## JavaScript

JavaScript is a *scripting* language used primarily for web pages.

- ◆ JavaScript was developed in 1995 and released in the Netscape web browser (since renamed to Mozilla Firefox).

Despite the name, JavaScript is not related to Java, although its syntax is similar to other languages like C, C++, and Java.

- ◆ There are some major differences between JavaScript and Java.

From the database perspective, JavaScript is used to make HTML forms more interactive and to validate input client-side before sending it to the server.

Page 41

## Hello World Example - JavaScript Code

helloWorld.html

```
<html>
<head>
<title>HelloWorld using JavaScript</title>
</head>

<body>

<h1>

    <script type="text/javascript">
        document.write("Hello, world!");
    </script>
</h1>

</body>
</html>
```

Page 42

## JavaScript and JSP

Your JSP code can either include JavaScript code:

- ◆1) Directly in the HTML code
- ◆2) By outputting it using `out.println()`
  - ⇒ With servlets, you only have option #2.

Remember, the JSP/Servlet code is run on the server, and the JavaScript code is run on the client.

- ◆The JavaScript code cannot access the database directly.
- ◆The JSP/Servlet code cannot interact with the user (unless you use AJAX or some other method to send server requests).

## Hello World written by JSP Code

helloWorld\_JS.jsp

```
<html>
<head>
<title>HelloWorld using JavaScript</title>
</head>

<body>

<h1>
  <%
    out.println("<script language=\"javascript\">");
    out.println("document.write(\"Hello, world!\");");
    out.println("</script>");
  %>
</h1>

</body>
</html>
```

## JavaScript for Data Validation

JavaScript is commonly used to validate form input on the client-side without sending it to the server. This reduces the load on the server, and more importantly, improves the browsing experience for the user.

## JavaScript Data Validation Example

validateNum.html

```
<html><head><title>Number Field Validation</title></head>
<body>

<script type="text/javascript">
function validate(num){
  if (parseInt(num))
    alert("You entered number: " + parseInt(num));
  else
    alert("Invalid number entered: " + num);
}
</script>

Enter a number:
<form name="input">
  <input type="text" name="numField"
    onchange="validate(this.value)">
</form>

</body>
</html>
```

Validation code

Validate when field is changed. Can also use:  
 - `onblur` – triggered when field loses focus  
 - `onsubmit` – triggered when form is submitted

## AJAX

AJAX allows client-side JavaScript to request and receive data from the server without refreshing the page.

**AJAX** (Asynchronous JavaScript+XML) was named by Jesse Garret in 2005. However, XML is not required for data communication between client and server (JSON is more common).

AJAX uses the `XMLHttpRequest` Object to communicate requests and receive results from the server.

Communication can either be synchronous or asynchronous.

## AJAX Validate Form Fields Example

validateUserEmail.html

```
<html><head><title>Validate User Name and Email</title></head>
<body>
<script type="text/javascript">
function checkUserName(){
  var name = document.getElementById("username").value;
  var xmlhttp = new XMLHttpRequest();
  xmlhttp.open("GET","validateUserEmail.jsp?name="+name,false);
  xmlhttp.send(null); // Synchronous version, no additional payload
  if (xmlhttp.responseText != "VALID")
    alert(xmlhttp.responseText);
}
function checkEmail(){
  var email = document.getElementById("email").value;
  var xmlhttp = new XMLHttpRequest();
  xmlhttp.open("GET","validateUserEmail.jsp?email="+email,false);
  xmlhttp.send(null); // Synchronous version, no additional payload
  if (xmlhttp.responseText != "VALID")
    alert(xmlhttp.responseText);
}
</script>
<form name="input">
  Name: <input type="text" id="username">
  <a href="javascript: checkUserName()">Check</a> <br>
  Email: <input type="text" id="email">
  <a href="javascript: checkEmail()">Check</a>
</form></body></html>
```



## AJAX Validate Form Fields Example

### validateUserEmail.jsp

```
<%
String name = request.getParameter("name");
if (name != null)
{
    // This is simple validation code.
    if (name.length() < 4)
        out.println("Name too short. Must be at least 4
                        characters.");
    else
        out.println("VALID");
}
else
{
    String email = request.getParameter("email");
    if (email != null)
    {
        if (!email.contains("@"))
            out.println("INVALID");
        else
            out.println("VALID");
    }
    else
        out.println("INVALID INPUT");
}
}%>
```

Page 49

## AJAX Example - Province/State

### provinceState.html

#### Canada Version

Country:

Province:

#### US Version

Country:

State:

```
<html>
<head><title>Province/State</title></head>

<body bgcolor="white">

<form name="input">
    Country: <select id="country" onchange="changeCountry()">
        <option value="CA">Canada</option>
        <option value="US">United States</option>
    </select><br>
    <p id="stateText">State: </p><select id="state"></select>
</form>

<script type="text/javascript">
```

Page 50

## Province/State for Canada/US

### provinceState.html (2)

```
var xmlhttp = new XMLHttpRequest();

function changeCountry_callBack()
{
    if (xmlhttp.readyState == 4 && xmlhttp.status == 200)
    {
        var text = xmlhttp.responseText;
        if (text != "INVALID")
        {
            var stateList = document.getElementById("state");

            // Remove all current items in list
            for (var i = stateList.length-1; i >= 0; i--)
                stateList.remove(i);

            // Add elements to list
            var values = text.split(',');
            for (var i=0; i < values.length; i++)
            {
                var stateCode = values[i];
                var newOpt = document.createElement('option');
                newOpt.text = stateCode;
                newOpt.value = stateCode;

                stateList.add(newOpt, null);
            }
        }
    }
}
```

Page 51

## Province/State for Canada/US

### provinceState.html (3)

```
function changeCountry(){
    var countryList = document.getElementById("country");
    var stateText = document.getElementById("stateText");

    if (countryList.selectedIndex == 1)
        stateText.innerHTML = "State: ";
    else
        stateText.innerHTML = "Province: ";

    xmlhttp.open("GET", "provinceState.jsp?country="+
                    countryList.value, true);
    xmlhttp.onreadystatechange = changeCountry_callBack;
    xmlhttp.send(null); // Asynchronous version
}

changeCountry(); // Initialize list with default as Canada
</script>
</body>
</html>
```

Page 52

## Province/State for Canada/US – JSP

### provinceState.jsp

```
<%@ page import="java.sql.*" %> <%
String country = request.getParameter("country");
if (country == null)
    out.println("INVALID");
else
{
    Connection con = null;
    try {
        con = DriverManager.getConnection(url,uid,pw);
        String sql = "select stateCode from states where countrycode=?";
        PreparedStatement pstmt = con.prepareStatement(sql);
        pstmt.setString(1, country);
        ResultSet rst = pstmt.executeQuery();
        StringBuffer buf = new StringBuffer();
        while (rst.next())
        {
            buf.append(rst.getString(1));
            buf.append(',');
        }
        if (buf.length() > 0)
            buf.setLength(buf.length()-1);
        out.println(buf.toString());
    }
    catch (SQLException ex){ out.println("INVALID"); }
    finally
    {
        if (con != null)
        {
            try { con.close(); } catch (SQLException ex) {}
        }
    }
}%>
```

Page 53

## Connection Pools

A **connection pool** is a group of database connections managed by a (web) server.

- ◆ All connections in the pool are open. Clients request a connection from the pool and return it when done.
- ◆ This results in improved performance as connections are shared across clients and do not pay an open/close penalty every time a connection is used.

Using a connection pool in Tomcat with JNDI:

```
Context root = new InitialContext(); // Get root of JNDI tree
String path = "java:comp/env/jdbc/workson"; // Name key
DataSource ds = (DataSource) root.lookup(path); // JNDI lookup
con = ds.getConnection(); // Get connection from pool
...
con.close(); // Return connection to pool
```

Page 54

## Connection Pools Configuration

Modify `conf/context.xml` file to add the resource:

```
<Context>
  <Resource name="jdbc/workson" type="javax.sql.DataSource"
    driverClassName="com.mysql.jdbc.Driver"
    url="jdbc:mysql://cs-suse-4.ok.ubc.ca/workson"
    username="rlawrenc" password="pw"
    maxActive="100" maxIdle="30" maxWait="10000"
    auth="Container"/>
</Context>

⇒ name - following standard convention to add "jdbc" but not necessary.
  Prefix "java:comp/env" added by web server (by convention).
⇒ type – class/interface of resource
⇒ driverClassName – class name of JDBC driver for database
⇒ url – connection string for the driver
⇒ maxActive, maxIdle, maxWait – maximum # of connections, idle
  connection, and time in milliseconds a client will wait before rollback resp.
⇒ auth – indicates if resource managed by web server or web app.
```

Page 55

## Connection Pools Question

**Question: True or False:** A connection pool will speed up the execution time of a query (not considering connection time).

A) true

B) false

Page 56

## Configuring your Web Application

Each web application (*webapp*) has its own directory that stores HTML/JSP files and has a subdirectory `WEB-INF` that contains:

- ◆ `classes` directory – stores all Java class files
- ◆ `lib` directory – store all jars used by your Servlets
- ◆ `web.xml` – is a **deployment descriptor** that provides mapping from URL path to Servlet class name. Example:

```
<web-app>
  <servlet>
    <servlet-name>HelloServlet</servlet-name>
    <servlet-class>HelloServlet</servlet-class>
  </servlet>
  <servlet-mapping>
    <servlet-name>HelloServlet</servlet-name>
    <url-pattern>/servlet/HelloServlet</url-pattern>
  </servlet-mapping>
</web-app>
```

Internal name used in mapping (you decide)

Servlet Java class name

Internal name (same as line #1)

URL to get to Servlet (from user's perspective)

Page 57

## PHP

**PHP** ([www.php.net](http://www.php.net)) is a general-purpose scripting language used extensively in web development.

PHP supports several different ways of connecting to databases including a custom MySQL connector as well as support for ODBC and PHP Data Objects (PDO).

Unlike JDBC, each database has its own database extension which has different features and methods.

Page 58

## PHP MySQLi Example Procedural Version

```
<?php
// Connecting, selecting database
$mysqli = mysqli_connect("cosc304.ok.ubc.ca", "rlawrenc",
    "pw", "db_rlawrenc")
    or die("Could not connect: " . mysqli_error());

// Performing SQL query
$query = "SELECT * FROM Emp";
$result = mysqli_query($mysqli, $query);
if (mysqli_connect_errno($mysqli))
    echo "Failed to connect to MySQL: " . mysqli_connect_error();
```

Page 59

## PHP MySQLi Example Procedural Version (2)

```
// Printing results in HTML
echo "<table>\n";
while ($line = mysqli_fetch_assoc($result)) {
    echo "\t<tr>\n";
    foreach ($line as $col_value) {
        echo "\t\t<td>$col_value</td>\n";
    }
    echo "\t</tr>\n";
}
echo "</table>\n";

// Free resultset
mysqli_free_result($result);

// Closing connection
mysqli_close($mysqli);

?>
```

Page 60

## PHP MySQLi Example Object-Oriented Version

```
<?php
$mysqli = new mysqli("cosc304.ok.ubc.ca", "rlawrenc", "<pw>",
                    "db_rlawrenc");
if ($mysqli->connect_errno)
    echo "Failed to connect to MySQL: " . $mysqli->connect_error;

$result = $mysqli->query($query);
echo "<table>\n";
while ($line = $result->fetch_assoc()) {
    echo "\t<tr>\n";
    foreach ($line as $col_value) {
        echo "\t\t<td>$col_value</td>\n";
    }
    echo "\t</tr>\n";
}
echo "</table>\n";
$result->free();
$mysqli->close();
?>
```

Page 61

## Conclusion

JSP and `Servlets` can use JDBC for constructing dynamic web content and answering user queries via HTML.

JSP and `Servlets` are used with HTML forms to allow users to enter queries or information to the database.

- ◆ JSP/ `Servlets` can be run using Apache Tomcat which supports connection pooling.

JavaScript is used for browser-based validation and interactivity. AJAX supports requests to server for data.

Connecting and querying a database with PHP (and other languages) is very similar to using Java/JDBC.

Page 62

## Objectives

- ◆ Write a simple JSP page that uses JDBC.
- ◆ Explain the relationship between JSP and `Servlets` and how dynamic web pages are created.
- ◆ Be able to create client-side code in JavaScript for data validation.
- ◆ Explain the general idea with AJAX.
- ◆ Explain what a connection pool is and why it is beneficial.
- ◆ Be able to write database access code using PHP.

Page 63