一、读程序写结果

```
1 • include <stdio.h>
                                                                2 -
                                                                          main()
          main()
                                                                          \{ \text{ int } x=4, y=0, z; \}
                                                                             x*=3+2:
            \{ \text{ int } a = -1, b = 4, k; \}
               k=(a++<=0)&&(!(b--<=0));
                                                                              printf("%d",x);
               printf("%d,%d,%d\n",k,a,b);
                                                                             x*=(y==(z=4));
                                                                              printf("%d",x);
               }
                                                                            }
3 •
         main()
                                                                4 •
                                                                           main()
          { int x,y,z;
                                                                            \{ int x=1,y=1,z=10; 
            x=3; y=z=4;
                                                                               if(z<0)
            printf("\%d",(x>=z>=x)?1:0);
                                                                                 if(y>0) x=3;
            printf("%d",z>=y && y>=x);
                                                                                 else x=5;
                                                                              printf("%d\t",x);
          }
                                                                              if(z=y<0) x=3;
                                                                              else if(y==0) x=5;
                                                                              else x=7;
                                                                              printf("%d\t",x);
                                                                              printf("%d\t",z);
                                                                              }
5 •
                                                                6 •
           main()
                                                                           main()
           { char x='B';
                                                                           \{ int x=1,y=0,a=0,b=0; 
             switch(x)
                                                                              switch(x)
                { case 'A': printf("It is A.");
                                                                              { case 1: switch(y)
                   case 'B': printf("It is B.");
                                                                                       { case 0: a++;break;
                   case 'C': printf("It is C.");
                                                                                          case 1: b++;break;
                   default: printf("other.");
                }
                                                                                case 2: a++;b++;break;
               }
                                                                                case 3: a++;b++;
                                                                               }
                                                                               printf("a=\%d,b=\%d\n",a,b);
                                                                            }
```

二、 输入一个数,判断它能否被 3 或者被 5 整除,如至少能被这两个数中的一个整除则将此数打印出来,否则不打印,编出程序。

参考答案 读程序写结果

- 1 1,0,3
- 2 200
- 3 01
- 4 1 7 0
- 5 It is B. It is C. other.
- 6 a=2,b=1