# The Coq Reference Manual

Release 8.11.2

The Coq Development Team

## **CONTENTS**

1	Introduction 1					
	1.1	How to read this book				
	1.2	List of additional documentation				
	1.3	License				
2	Early history of Coq					
	2.1	Historical roots				
	2.2	Versions 1 to 5				
	2.3	Versions 6				
	2.4	Versions 7				
3	Recent changes 25					
	3.1	Version 8.11				
	3.2	Version 8.10				
	3.3	Version 8.9				
	3.4	Version 8.8				
	3.5	Version 8.7				
	3.6	Version 8.6				
	3.7	Version 8.5				
	3.8	Version 8.4				
	3.9	Version 8.3				
	3.10	Version 8.2				
	3.11	Version 8.1				
	3.12	Version 8.0				
4	The language 124					
	4.1	The Gallina specification language				
	4.2	Extensions of Gallina				
	4.3	The Coq library				
	4.4	Calculus of Inductive Constructions				
	4.5	The Module System				
5	The	proof engine 236				
	5.1	Vernacular commands				
	5.2	Proof handling				
	5.3	Tactics				
	5.4	Ltac				
	5.5	Ltac2				
	5.6	Detailed examples of tactics				
	5.7	The SSReflect proof language				

6	User 6.1 6.2	extensions Syntax extensions and interpretation scopes Proof schemes			
7	Prac 7.1 7.2 7.3	tical tools The Coq commands	532		
8	Adde 8.1 8.2 8.3 8.4 8.5 8.6 8.7 8.8 8.9 8.10 8.11 8.12 8.13 8.14 8.15	Extended pattern matching Implicit Coercions Canonical Structures Typeclasses Omega: a solver for quantifier-free problems in Presburger Arithmetic Micromega: tactics for solving arithmetic goals over ordered rings Extraction of programs in OCaml and Haskell Program The ring and field tactic families Nsatz: tactics for proving equalities in integral domains Generalized rewriting Asynchronous and Parallel Proof Processing Miscellaneous extensions Polymorphic Universes SProp (proof irrelevant propositions)	563 571 581 589 592 595 605 610 620 621 632 636 637		
Bibliography					
Command Index					
Tactic Index					
$\mathbf{Fl}$	Flags, options and Tables Index				
Errors and Warnings Index					
Index					

## INTRODUCTION

This document is the Reference Manual of the Coq proof assistant. To start using Coq, it is advised to first read a tutorial. Links to several tutorials can be found at https://coq.inria.fr/documentation and https://github.com/coq/coq/wiki#coq-tutorials

The Coq system is designed to develop mathematical proofs, and especially to write formal specifications, programs and to verify that programs are correct with respect to their specifications. It provides a specification language named Gallina. Terms of Gallina can represent programs as well as properties of these programs and proofs of these properties. Using the so-called *Curry-Howard isomorphism*, programs, properties and proofs are formalized in the same language called *Calculus of Inductive Constructions*, that is a  $\lambda$ -calculus with a rich type system. All logical judgments in Coq are typing judgments. The very heart of the Coq system is the type checking algorithm that checks the correctness of proofs, in other words that checks that a program complies to its specification. Coq also provides an interactive proof assistant to build proofs using specific programs called *tactics*.

All services of the Coq proof assistant are accessible by interpretation of a command language called *the* vernacular.

Coq has an interactive mode in which commands are interpreted as the user types them in from the keyboard and a compiled mode where commands are processed from a file.

- In interactive mode, users can develop their theories and proofs step by step, and query the system for available theorems and definitions. The interactive mode is generally run with the help of an IDE, such as CoqIDE, documented in *Coq Integrated Development Environment*, Emacs with Proof-General [Asp00]<sup>4</sup>, or jsCoq to run Coq in your browser (see https://github.com/ejgallego/jscoq). The coqtop read-eval-print-loop can also be used directly, for debugging purposes.
- The compiled mode acts as a proof checker taking a file containing a whole development in order to ensure its correctness. Moreover, Coq's compiler provides an output file containing a compact representation of its input. The compiled mode is run with the coqc command.

## See also:

The Coq commands.

## 1.1 How to read this book

This is a Reference Manual, so it is not intended for continuous reading. We recommend using the various indexes to quickly locate the documentation you are looking for. There is a global index, and a number of specific indexes for tactics, vernacular commands, and error messages and warnings. Nonetheless, the manual has some structure that is explained below.

<sup>&</sup>lt;sup>4</sup> Proof-General is available at https://proofgeneral.github.io/. Optionally, you can enhance it with the minor mode Company-Coq [PCC16] (see https://github.com/cpitclaudel/company-coq).

- The first part describes the specification language, Gallina. Chapters *The Gallina specification language* and *Extensions of Gallina* describe the concrete syntax as well as the meaning of programs, theorems and proofs in the Calculus of Inductive Constructions. Chapter *The Coq library* describes the standard library of Coq. Chapter *Calculus of Inductive Constructions* is a mathematical description of the formalism. Chapter *The Module System* describes the module system.
- The second part describes the proof engine. It is divided into several chapters. Chapter Vernacular commands presents all commands (we call them vernacular commands) that are not directly related to interactive proving: requests to the environment, complete or partial evaluation, loading and compiling files. How to start and stop proofs, do multiple proofs in parallel is explained in Chapter Proof handling. In Chapter Tactics, all commands that realize one or more steps of the proof are presented: we call them tactics. The legacy language to combine these tactics into complex proof strategies is given in Chapter Ltac. The currently experimental language that will eventually replace Ltac is presented in Chapter Ltac2. Examples of tactics are described in Chapter Detailed examples of tactics. Finally, the SSReflect proof language is presented in Chapter The SSReflect proof language.
- The third part describes how to extend the syntax of Coq in Chapter Syntax extensions and interpretation scopes and how to define new induction principles in Chapter Proof schemes.
- In the fourth part more practical tools are documented. First in Chapter *The Coq commands*, the usage of coqc (batch mode) and coqtop (interactive mode) with their options is described. Then, in Chapter *Utilities*, various utilities that come with the Coq distribution are presented. Finally, Chapter *Coq Integrated Development Environment* describes CoqIDE.
- The fifth part documents a number of advanced features, including coercions, canonical structures, typeclasses, program extraction, and specialized solvers and tactics. See the table of contents for a complete list.

## 1.2 List of additional documentation

This manual does not contain all the documentation the user may need about Coq. Various informations can be found in the following documents:

**Installation** A text file INSTALL that comes with the sources explains how to install Coq.

The Coq standard library A commented version of sources of the Coq standard library (including only the specifications, the proofs are removed) is available at https://coq.inria.fr/stdlib/.

## 1.3 License

This material (the Coq Reference Manual) may be distributed only subject to the terms and conditions set forth in the Open Publication License, v1.0 or later (the latest version is presently available at http://www.opencontent.org/openpub). Options A and B are not elected.

## EARLY HISTORY OF COQ

## 2.1 Historical roots

Coq is a proof assistant for higher-order logic, allowing the development of computer programs consistent with their formal specification. It is the result of about ten years<sup>5</sup> of research of the Coq project. We shall briefly survey here three main aspects: the *logical language* in which we write our axiomatizations and specifications, the *proof assistant* which allows the development of verified mathematical proofs, and the *program extractor* which synthesizes computer programs obeying their formal specifications, written as logical assertions in the language.

The logical language used by Coq is a variety of type theory, called the Calculus of Inductive Constructions. Without going back to Leibniz and Boole, we can date the creation of what is now called mathematical logic to the work of Frege and Peano at the turn of the century. The discovery of antinomies in the free use of predicates or comprehension principles prompted Russell to restrict predicate calculus with a stratification of types. This effort culminated with Principia Mathematica, the first systematic attempt at a formal foundation of mathematics. A simplification of this system along the lines of simply typed  $\lambda$ -calculus occurred with Church's Simple Theory of Types. The  $\lambda$ -calculus notation, originally used for expressing functionality, could also be used as an encoding of natural deduction proofs. This Curry-Howard isomorphism was used by N. de Bruijn in the Automath project, the first full-scale attempt to develop and mechanically verify mathematical proofs. This effort culminated with Jutting's verification of Landau's Grundlagen in the 1970's. Exploiting this Curry-Howard isomorphism, notable achievements in proof theory saw the emergence of two typetheoretic frameworks; the first one, Martin-Löf's Intuitionistic Theory of Types, attempts a new foundation of mathematics on constructive principles. The second one, Girard's polymorphic  $\lambda$ -calculus  $F_{\omega}$ , is a very strong functional system in which we may represent higher-order logic proof structures. Combining both systems in a higher-order extension of the Automath language, T. Coquand presented in 1985 the first version of the Calculus of Constructions, CoC. This strong logical system allowed powerful axiomatizations, but direct inductive definitions were not possible, and inductive notions had to be defined indirectly through functional encodings, which introduced inefficiencies and awkwardness. The formalism was extended in 1989 by T. Coquand and C. Paulin with primitive inductive definitions, leading to the current Calculus of Inductive Constructions. This extended formalism is not rigorously defined here. Rather, numerous concrete examples are discussed. We refer the interested reader to relevant research papers for more information about the formalism, its meta-theoretic properties, and semantics. However, it should not be necessary to understand this theoretical material in order to write specifications. It is possible to understand the Calculus of Inductive Constructions at a higher level, as a mixture of predicate calculus, inductive predicate definitions presented as typed PROLOG, and recursive function definitions close to the language ML.

Automated theorem-proving was pioneered in the 1960's by Davis and Putnam in propositional calculus. A complete mechanization (in the sense of a semidecision procedure) of classical first-order logic was proposed in 1965 by J.A. Robinson, with a single uniform inference rule called *resolution*. Resolution relies on solving equations in free algebras (i.e. term structures), using the *unification algorithm*. Many refinements of resolution were studied in the 1970's, but few convincing implementations were realized, except of course

<sup>&</sup>lt;sup>5</sup> At the time of writing, i.e. 1995.

that PROLOG is in some sense issued from this effort. A less ambitious approach to proof development is computer-aided proof-checking. The most notable proof-checkers developed in the 1970's were LCF, designed by R. Milner and his colleagues at U. Edinburgh, specialized in proving properties about denotational semantics recursion equations, and the Boyer and Moore theorem-prover, an automation of primitive recursion over inductive data types. While the Boyer-Moore theorem-prover attempted to synthesize proofs by a combination of automated methods, LCF constructed its proofs through the programming of *tactics*, written in a high-level functional meta-language, ML.

The salient feature which clearly distinguishes our proof assistant from say LCF or Boyer and Moore's, is its possibility to extract programs from the constructive contents of proofs. This computational interpretation of proof objects, in the tradition of Bishop's constructive mathematics, is based on a realizability interpretation, in the sense of Kleene, due to C. Paulin. The user must just mark his intention by separating in the logical statements the assertions stating the existence of a computational object from the logical assertions which specify its properties, but which may be considered as just comments in the corresponding program. Given this information, the system automatically extracts a functional term from a consistency proof of its specifications. This functional term may be in turn compiled into an actual computer program. This methodology of extracting programs from proofs is a revolutionary paradigm for software engineering. Program synthesis has long been a theme of research in artificial intelligence, pioneered by R. Waldinger. The Tablog system of Z. Manna and R. Waldinger allows the deductive synthesis of functional programs from proofs in tableau form of their specifications, written in a variety of first-order logic. Development of a systematic programming logic, based on extensions of Martin-Löf's type theory, was undertaken at Cornell U. by the Nuprl team, headed by R. Constable. The first actual program extractor, PX, was designed and implemented around 1985 by S. Hayashi from Kyoto University. It allows the extraction of a LISP program from a proof in a logical system inspired by the logical formalisms of S. Feferman. Interest in this methodology is growing in the theoretical computer science community. We can foresee the day when actual computer systems used in applications will contain certified modules, automatically generated from a consistency proof of their formal specifications. We are however still far from being able to use this methodology in a smooth interaction with the standard tools from software engineering, i.e. compilers, linkers, run-time systems taking advantage of special hardware, debuggers, and the like. We hope that Coq can be of use to researchers interested in experimenting with this new methodology.

## 2.2 Versions 1 to 5

**Note:** This summary was written in 1995 together with the previous section and formed the initial version of the Credits chapter.

A more comprehensive description of these early versions is available in the following subsections, which come from a document written in September 2015 by Gérard Huet, Thierry Coquand and Christine Paulin.

A first implementation of CoC was started in 1984 by G. Huet and T. Coquand. Its implementation language was CAML, a functional programming language from the ML family designed at INRIA in Rocquencourt. The core of this system was a proof-checker for CoC seen as a typed  $\lambda$ -calculus, called the *Constructive Engine*. This engine was operated through a high-level notation permitting the declaration of axioms and parameters, the definition of mathematical types and objects, and the explicit construction of proof objects encoded as  $\lambda$ -terms. A section mechanism, designed and implemented by G. Dowek, allowed hierarchical developments of mathematical theories. This high-level language was called the *Mathematical Vernacular*. Furthermore, an interactive *Theorem Prover* permitted the incremental construction of proof trees in a top-down manner, subgoaling recursively and backtracking from dead-ends. The theorem prover executed tactics written in CAML, in the LCF fashion. A basic set of tactics was predefined, which the user could extend by his own specific tactics. This system (Version 4.10) was released in 1989. Then, the system was extended to deal with the new calculus with inductive types by C. Paulin, with corresponding new tactics for proofs by induction. A new standard set of tactics was streamlined, and the vernacular extended for tactics execution.

A package to compile programs extracted from proofs to actual computer programs in CAML or some other functional language was designed and implemented by B. Werner. A new user-interface, relying on a CAML-X interface by D. de Rauglaudre, was designed and implemented by A. Felty. It allowed operation of the theorem-prover through the manipulation of windows, menus, mouse-sensitive buttons, and other widgets. This system (Version 5.6) was released in 1991.

Coq was ported to the new implementation Caml-light of X. Leroy and D. Doligez by D. de Rauglaudre (Version 5.7) in 1992. A new version of Coq was then coordinated by C. Murthy, with new tools designed by C. Parent to prove properties of ML programs (this methodology is dual to program extraction) and a new user-interaction loop. This system (Version 5.8) was released in May 1993. A Centaur interface CTCoq was then developed by Y. Bertot from the Croap project from INRIA-Sophia-Antipolis.

In parallel, G. Dowek and H. Herbelin developed a new proof engine, allowing the general manipulation of existential variables consistently with dependent types in an experimental version of Coq (V5.9).

The version V5.10 of Coq is based on a generic system for manipulating terms with binding operators due to Chet Murthy. A new proof engine allows the parallel development of partial proofs for independent subgoals. The structure of these proof trees is a mixed representation of derivation trees for the Calculus of Inductive Constructions with abstract syntax trees for the tactics scripts, allowing the navigation in a proof at various levels of details. The proof engine allows generic environment items managed in an object-oriented way. This new architecture, due to C. Murthy, supports several new facilities which make the system easier to extend and to scale up:

- User-programmable tactics are allowed
- It is possible to separately verify development modules, and to load their compiled images without verifying them again a quick relocation process allows their fast loading
- A generic parsing scheme allows user-definable notations, with a symmetric table-driven pretty-printer
- Syntactic definitions allow convenient abbreviations
- A limited facility of meta-variables allows the automatic synthesis of certain type expressions, allowing generic notations for e.g. equality, pairing, and existential quantification.

In the Fall of 1994, C. Paulin-Mohring replaced the structure of inductively defined types and families by a new structure, allowing the mutually recursive definitions. P. Manoury implemented a translation of recursive definitions into the primitive recursive style imposed by the internal recursion operators, in the style of the ProPre system. C. Muñoz implemented a decision procedure for intuitionistic propositional logic, based on results of R. Dyckhoff. J.C. Filliâtre implemented a decision procedure for first-order logic without contraction, based on results of J. Ketonen and R. Weyhrauch. Finally C. Murthy implemented a library of inversion tactics, relieving the user from tedious definitions of "inversion predicates".

Rocquencourt, Feb. 1st 1995 Gérard Huet

## 2.2.1 Version 1

This software is a prototype type-checker for a higher-order logical formalism known as the Theory of Constructions, presented in his PhD thesis by Thierry Coquand, with influences from Girard's system F and de Bruijn's Automath. The metamathematical analysis of the system is the PhD work of Thierry Coquand. The software is mostly the work of Gérard Huet. Most of the mathematical examples verified with the software are due to Thierry Coquand.

2.2. Versions 1 to 5

The programming language of the CONSTR software (as it was called at the time) was a version of ML adapted from the Edinburgh LCF system and running on a LISP backend. The main improvements from the original LCF ML were that ML was compiled rather than interpreted (Gérard Huet building on the original translator by Lockwood Morris), and that it was enriched by recursively defined types (work of Guy Cousineau). This ancestor of CAML was used and improved by Larry Paulson for his implementation of Cambridge LCF.

Software developments of this prototype occurred from late 1983 to early 1985.

Version 1.10 was frozen on December 22nd 1984. It is the version used for the examples in Thierry Coquand's thesis, defended on January 31st 1985. There was a unique binding operator, used both for universal quantification (dependent product) at the level of types and functional abstraction ( $\lambda$ ) at the level of terms/proofs, in the manner of Automath. Substitution ( $\lambda$ -reduction) was implemented using de Bruijn's indexes.

Version 1.11 was frozen on February 19th, 1985. It is the version used for the examples in the paper: T. Coquand, G. Huet. Constructions: A Higher Order Proof System for Mechanizing Mathematics [CH85].

Christine Paulin joined the team at this point, for her DEA research internship. In her DEA memoir (August 1985) she presents developments for the lambo function – lambo(f)(n) computes the minimal m such that f(m) is greater than n, for f an increasing integer function, a challenge for constructive mathematics. She also encoded the majority voting algorithm of Boyer and Moore.

#### 2.2.2 **Version 2**

The formal system, now renamed as the *Calculus of Constructions*, was presented with a proof of consistency and comparisons with proof systems of Per Martin Löf, Girard, and the Automath family of N. de Bruijn, in the paper: T. Coquand and G. Huet. *The Calculus of Constructions [CH86b]*.

An abstraction of the software design, in the form of an abstract machine for proof checking, and a fuller sequence of mathematical developments was presented in: T. Coquand, G. Huet. *Concepts Mathématiques et Informatiques Formalisés dans le Calcul des Constructions [CH86a]*.

Version 2.8 was frozen on December 16th, 1985, and served for developing the examples in the above papers.

This calculus was then enriched in version 2.9 with a cumulative hierarchy of universes. Universe levels were initially explicit natural numbers. Another improvement was the possibility of automatic synthesis of implicit type arguments, relieving the user of tedious redundant declarations.

Christine Paulin wrote an article Algorithm development in the Calculus of Constructions [Moh86]. Besides lambo and majority, she presents quicksort and a text formatting algorithm.

Version 2.13 of the Calculus of Constructions with universes was frozen on June 25th, 1986.

A synthetic presentation of type theory along constructive lines with ML algorithms was given by Gérard Huet in his May 1986 CMU course notes Formal Structures for Computation and Deduction. Its chapter Induction and Recursion in the Theory of Constructions was presented as an invited paper at the Joint Conference on Theory and Practice of Software Development TAPSOFT'87 at Pise in March 1987, and published as Induction Principles Formalized in the Calculus of Constructions [Hue88].

## 2.2.3 **Version 3**

This version saw the beginning of proof automation, with a search algorithm inspired from PROLOG and the applicative logic programming programs of the course notes *Formal structures for computation and deduction*. The search algorithm was implemented in ML by Thierry Coquand. The proof system could thus be used in two modes: proof verification and proof synthesis, with tactics such as AUTO.

The implementation language was now called CAML, for Categorical Abstract Machine Language. It used as backend the LLM3 virtual machine of Le Lisp by Jérôme Chailloux. The main developers of CAML were Michel Mauny, Ascander Suarez and Pierre Weis.

V3.1 was started in the summer of 1986, V3.2 was frozen at the end of November 1986. V3.4 was developed in the first half of 1987.

Thierry Coquand held a post-doctoral position in Cambridge University in 1986-87, where he developed a variant implementation in SML, with which he wrote some developments on fixpoints in Scott's domains.

#### 2.2.4 Version 4

This version saw the beginning of program extraction from proofs, with two varieties of the type Prop of propositions, indicating constructive intent. The proof extraction algorithms were implemented by Christine Paulin-Mohring.

V4.1 was frozen on July 24th, 1987. It had a first identified library of mathematical developments (directory exemples), with libraries Logic (containing impredicative encodings of intuitionistic logic and algebraic primitives for booleans, natural numbers and list), Peano developing second-order Peano arithmetic, Arith defining addition, multiplication, euclidean division and factorial. Typical developments were the Knaster-Tarski theorem and Newman's lemma from rewriting theory.

V4.2 was a joint development of a team consisting of Thierry Coquand, Gérard Huet and Christine Paulin-Mohring. A file V4.2 log records the log of changes. It was frozen on September 1987 as the last version implemented in CAML 2.3, and V4.3 followed on CAML 2.5, a more stable development system.

V4.3 saw the first top-level of the system. Instead of evaluating explicit quotations, the user could develop his mathematics in a high-level language called the mathematical vernacular (following Automath terminology). The user could develop files in the vernacular notation (with .v extension) which were now separate from the m1 sources of the implementation. Gilles Dowek joined the team to develop the vernacular language as his DEA internship research.

A notion of sticky constant was introduced, in order to keep names of lemmas when local hypotheses of proofs were discharged. This gave a notion of global mathematical environment with local sections.

Another significant practical change was that the system, originally developed on the VAX central computer of our lab, was transferred on SUN personal workstations, allowing a level of distributed development. The extraction algorithm was modified, with three annotations Pos, Null and Typ decorating the sorts Prop and Type.

Version 4.3 was frozen at the end of November 1987, and was distributed to an early community of users (among those were Hugo Herbelin and Loic Colson).

V4.4 saw the first version of (encoded) inductive types. Now natural numbers could be defined as:

```
[source, coq]
Inductive NAT : Prop = 0 : NAT | Succ : NAT->NAT.
```

These inductive types were encoded impredicatively in the calculus, using a subsystem *rec* due to Christine Paulin. V4.4 was frozen on March 6th 1988.

Version 4.5 was the first one to support inductive types and program extraction. Its banner was *Calcul des Constructions avec Réalisations et Synthèse*. The vernacular language was enriched to accommodate extraction commands.

The verification engine design was presented as: G. Huet. *The Constructive Engine*. Version 4.5. Invited Conference, 2nd European Symposium on Programming, Nancy, March 88. The final paper, describing the V4.9 implementation, appeared in: A perspective in Theoretical Computer Science, Commemorative Volume in memory of Gift Siromoney, Ed. R. Narasimhan, World Scientific Publishing, 1989.

2.2. Versions 1 to 5

Version 4.5 was demonstrated in June 1988 at the YoP Institute on Logical Foundations of Functional Programming organized by Gérard Huet at Austin, Texas.

Version 4.6 was started during the summer of 1988. Its main improvement was the complete rehaul of the proof synthesis engine by Thierry Coquand, with a tree structure of goals.

Its source code was communicated to Randy Pollack on September 2nd 1988. It evolved progressively into LEGO, proof system for Luo's formalism of Extended Calculus of Constructions.

The discharge tactic was modified by Gérard Huet to allow for inter-dependencies in discharged lemmas. Christine Paulin improved the inductive definition scheme in order to accommodate predicates of any arity.

Version 4.7 was started on September 6th, 1988.

This version starts exploiting the CAML notion of module in order to improve the modularity of the implementation. Now the term verifier is identified as a proper module Machine, which the structure of its internal data structures being hidden and thus accessible only through the legitimate operations. This machine (the constructive engine) was the trusted core of the implementation. The proof synthesis mechanism was a separate proof term generator. Once a complete proof term was synthesized with the help of tactics, it was entirely re-checked by the engine. Thus there was no need to certify the tactics, and the system took advantage of this fact by having tactics ignore the universe levels, universe consistency check being relegated to the final type-checking pass. This induced a certain puzzlement in early users who saw, after a successful proof search, their QED followed by silence, followed by a failure message due to a universe inconsistency...

The set of examples comprise set theory experiments by Hugo Herbelin, and notably the Schroeder-Bernstein theorem.

Version 4.8, started on October 8th, 1988, saw a major re-implementation of the abstract syntax type constr, separating variables of the formalism and metavariables denoting incomplete terms managed by the search mechanism. A notion of level (with three values TYPE, OBJECT and PROOF) is made explicit and a type judgement clarifies the constructions, whose implementation is now fully explicit. Structural equality is speeded up by using pointer equality, yielding spectacular improvements. Thierry Coquand adapts the proof synthesis to the new representation, and simplifies pattern matching to first-order predicate calculus matching, with important performance gain.

A new representation of the universe hierarchy is then defined by Gérard Huet. Universe levels are now implemented implicitly, through a hidden graph of abstract levels constrained with an order relation. Checking acyclicity of the graph insures well-foundedness of the ordering, and thus consistency. This was documented in a memo Adding Type: Type to the Calculus of Constructions which was never published.

The development version is released as a stable 4.8 at the end of 1988.

Version 4.9 is released on March 1st 1989, with the new "elastic" universe hierarchy.

The spring of 1989 saw the first attempt at documenting the system usage, with a number of papers describing the formalism:

- Metamathematical Investigations of a Calculus of Constructions, by Thierry Coquand [Coq89],
- Inductive definitions in the Calculus of Constructions, by Christine Paulin-Mohrin,
- Extracting  $F\omega$ 's programs from proofs in the Calculus of Constructions, by Christine Paulin-Mohring\* [PM89],
- The Constructive Engine, by Gérard Huet [Hue89],

as well as a number of user guides:

- A short user's guide for the Constructions, Version 4.10, by Gérard Huet
- A Vernacular Syllabus, by Gilles Dowek.
- The Tactics Theorem Prover, User's quide, Version 4.10, by Thierry Coquand.

Stable V4.10, released on May 1st, 1989, was then a mature system, distributed with CAML V2.6.

In the mean time, Thierry Coquand and Christine Paulin-Mohring had been investigating how to add native inductive types to the Calculus of Constructions, in the manner of Per Martin-Löf's Intuitionistic Type Theory. The impredicative encoding had already been presented in: F. Pfenning and C. Paulin-Mohring. Inductively defined types in the Calculus of Constructions [PPM89]. An extension of the calculus with primitive inductive types appeared in: T. Coquand and C. Paulin-Mohring. Inductively defined types [CP90].

This led to the Calculus of Inductive Constructions, logical formalism implemented in Versions 5 upward of the system, and documented in: C. Paulin-Mohring. *Inductive Definitions in the System Coq - Rules and Properties* [PM93b].

The last version of CONSTR is Version 4.11, which was last distributed in the spring of 1990. It was demonstrated at the first workshop of the European Basic Research Action Logical Frameworks In Sophia Antipolis in May 1990.

#### 2.2.5 Version 5

At the end of 1989, Version 5.1 was started, and renamed as the system Coq for the Calculus of Inductive Constructions. It was then ported to the new stand-alone implementation of ML called Caml-light.

In 1990 many changes occurred. Thierry Coquand left for Chalmers University in Göteborg. Christine Paulin-Mohring took a CNRS researcher position at the LIP laboratory of École Normale Supérieure de Lyon. Project Formel was terminated, and gave rise to two teams: Cristal at INRIA-Roquencourt, that continued developments in functional programming with Caml-light then OCaml, and Coq, continuing the type theory research, with a joint team headed by Gérard Huet at INRIA-Rocquencourt and Christine Paulin-Mohring at the LIP laboratory of CNRS-ENS Lyon.

Chetan Murthy joined the team in 1991 and became the main software architect of Version 5. He completely rehauled the implementation for efficiency. Versions 5.6 and 5.8 were major distributed versions, with complete documentation and a library of users' developments. The use of the RCS revision control system, and systematic ChangeLog files, allow a more precise tracking of the software developments.

September 2015 +

Thierry Coquand, Gérard Huet and Christine Paulin-Mohring.

## 2.3 Versions 6

## 2.3.1 Version 6.1

The present version 6.1 of Coq is based on the V5.10 architecture. It was ported to the new language Objective Caml by Bruno Barras. The underlying framework has slightly changed and allows more conversions between sorts.

The new version provides powerful tools for easier developments.

Cristina Cornes designed an extension of the Coq syntax to allow definition of terms using a powerful pattern matching analysis in the style of ML programs.

Amokrane Saïbi wrote a mechanism to simulate inheritance between types families extending a proposal by Peter Aczel. He also developed a mechanism to automatically compute which arguments of a constant may be inferred by the system and consequently do not need to be explicitly written.

2.3. Versions 6 9

Yann Coscoy designed a command which explains a proof term using natural language. Pierre Crégut built a new tactic which solves problems in quantifier-free Presburger Arithmetic. Both functionalities have been integrated to the Coq system by Hugo Herbelin.

Samuel Boutin designed a tactic for simplification of commutative rings using a canonical set of rewriting rules and equality modulo associativity and commutativity.

Finally the organisation of the Coq distribution has been supervised by Jean-Christophe Filliâtre with the help of Judicaël Courant and Bruno Barras.

Lyon, Nov. 18th 1996 Christine Paulin

## 2.3.2 Version 6.2

In version 6.2 of Coq, the parsing is done using camlp4, a preprocessor and pretty-printer for CAML designed by Daniel de Rauglaudre at INRIA. Daniel de Rauglaudre made the first adaptation of Coq for camlp4, this work was continued by Bruno Barras who also changed the structure of Coq abstract syntax trees and the primitives to manipulate them. The result of these changes is a faster parsing procedure with greatly improved syntax-error messages. The user-interface to introduce grammar or pretty-printing rules has also changed.

Eduardo Giménez redesigned the internal tactic libraries, giving uniform names to Caml functions corresponding to Coq tactic names.

Bruno Barras wrote new, more efficient reduction functions.

Hugo Herbelin introduced more uniform notations in the Coq specification language: the definitions by fixpoints and pattern matching have a more readable syntax. Patrick Loiseleur introduced user-friendly notations for arithmetic expressions.

New tactics were introduced: Eduardo Giménez improved the mechanism to introduce macros for tactics, and designed special tactics for (co)inductive definitions; Patrick Loiseleur designed a tactic to simplify polynomial expressions in an arbitrary commutative ring which generalizes the previous tactic implemented by Samuel Boutin. Jean-Christophe Filliâtre introduced a tactic for refining a goal, using a proof term with holes as a proof scheme.

David Delahaye designed the tool to search an object in the library given its type (up to isomorphism).

Henri Laulhère produced the Coq distribution for the Windows environment.

Finally, Hugo Herbelin was the main coordinator of the Coq documentation with principal contributions by Bruno Barras, David Delahaye, Jean-Christophe Filliâtre, Eduardo Giménez, Hugo Herbelin and Patrick Loiseleur.

Orsay, May 4th 1998 Christine Paulin

## 2.3.3 Version 6.3

The main changes in version V6.3 were the introduction of a few new tactics and the extension of the guard condition for fixpoint definitions.

- B. Barras extended the unification algorithm to complete partial terms and fixed various tricky bugs related to universes.
- D. Delahaye developed the AutoRewrite tactic. He also designed the new behavior of Intro and provided the tacticals First and Solve.
- J.-C. Filliâtre developed the Correctness tactic.
- E. Giménez extended the guard condition in fixpoints.
- H. Herbelin designed the new syntax for definitions and extended the Induction tactic.
- P. Loiseleur developed the Quote tactic and the new design of the Auto tactic, he also introduced the index of errors in the documentation.
- C. Paulin wrote the Focus command and introduced the reduction functions in definitions, this last feature was proposed by J.-F. Monin from CNET Lannion.

Orsay, Dec. 1999 Christine Paulin

## 2.4 Versions 7

## 2.4.1 Summary of changes

The version V7 is a new implementation started in September 1999 by Jean-Christophe Filliâtre. This is a major revision with respect to the internal architecture of the system. The Coq version 7.0 was distributed in March 2001, version 7.1 in September 2001, version 7.2 in January 2002, version 7.3 in May 2002 and version 7.4 in February 2003.

Jean-Christophe Filliâtre designed the architecture of the new system. He introduced a new representation for environments and wrote a new kernel for type checking terms. His approach was to use functional data-structures in order to get more sharing, to prepare the addition of modules and also to get closer to a certified kernel.

Hugo Herbelin introduced a new structure of terms with local definitions. He introduced "qualified" names, wrote a new pattern matching compilation algorithm and designed a more compact algorithm for checking the logical consistency of universes. He contributed to the simplification of Coq internal structures and the optimisation of the system. He added basic tactics for forward reasoning and coercions in patterns.

David Delahaye introduced a new language for tactics. General tactics using pattern matching on goals and context can directly be written from the Coq toplevel. He also provided primitives for the design of user-defined tactics in Caml.

Micaela Mayero contributed the library on real numbers. Olivier Desmettre extended this library with axiomatic trigonometric functions, square, square roots, finite sums, Chasles property and basic plane geometry.

Jean-Christophe Filliâtre and Pierre Letouzey redesigned a new extraction procedure from Coq terms to Caml or Haskell programs. This new extraction procedure, unlike the one implemented in previous version

of Coq is able to handle all terms in the Calculus of Inductive Constructions, even involving universes and strong elimination. P. Letouzey adapted user contributions to extract ML programs when it was sensible. Jean-Christophe Filliâtre wrote cogdoc, a documentation tool for Coq libraries usable from version 7.2.

Bruno Barras improved the efficiency of the reduction algorithm and the confidence level in the correctness of Coq critical type checking algorithm.

Yves Bertot designed the SearchPattern and SearchRewrite tools and the support for the pcoq interface (http://www-sop.inria.fr/lemme/pcoq/).

Micaela Mayero and David Delahaye introduced Field, a decision tactic for commutative fields.

Christine Paulin changed the elimination rules for empty and singleton propositional inductive types.

Loïc Pottier developed Fourier, a tactic solving linear inequalities on real numbers.

Pierre Crégut developed a new, reflection-based version of the Omega decision procedure.

Claudio Sacerdoti Coen designed an XML output for the Coq modules to be used in the Hypertextual Electronic Library of Mathematics (HELM cf http://www.cs.unibo.it/helm).

A library for efficient representation of finite maps using binary trees contributed by Jean Goubault was integrated in the basic theories.

Pierre Courtieu developed a command and a tactic to reason on the inductive structure of recursively defined functions.

Jacek Chrząszcz designed and implemented the module system of Coq whose foundations are in Judicaël Courant's PhD thesis.

The development was coordinated by C. Paulin.

Many discussions within the Démons team and the LogiCal project influenced significantly the design of Coq especially with J. Courant, J. Duprat, J. Goubault, A. Miquel, C. Marché, B. Monate and B. Werner.

Intensive users suggested improvements of the system : Y. Bertot, L. Pottier, L. Théry, P. Zimmerman from INRIA, C. Alvarado, P. Crégut, J.-F. Monin from France Telecom R & D.

Orsay, May. 2002 Hugo Herbelin & Christine Paulin

## 2.4.2 Details of changes in 7.0 and 7.1

## Notes:

- items followed by (\*\*) are important sources of incompatibilities
- items followed by (\*) may exceptionally be sources of incompatibilities
- items followed by (+) have been introduced in version 7.0

#### Main novelties

References are to Coq 7.1 reference manual

- New primitive let-in construct (see sections 1.2.8 and )
- Long names (see sections 2.6 and 2.7)

- New high-level tactic language (see chapter 10)
- Improved search facilities (see section 5.2)
- New extraction algorithm managing the Type level (see chapter 17)
- New rewriting tactic for arbitrary equalities (see chapter 19)
- New tactic Field to decide equalities on commutative fields (see 7.11)
- New tactic Fourier to solve linear inequalities on reals numbers (see 7.11)
- New tactics for induction/case analysis in "natural" style (see 7.7)
- Deep restructuration of the code (safer, simpler and more efficient)
- Export of theories to XML for publishing and rendering purposes (see http://www.cs.unibo.it/helm)

#### **Details of changes**

## Language: new "let-in" construction

- New construction for local definitions (let-in) with syntax [x:=u]t (\*)(+)
- Local definitions allowed in Record (a.k.a. record à la Randy Pollack)

#### Language: long names

- Each construction has a unique absolute names built from a base name, the name of the module in which they are defined (Top if in coqtop), and possibly an arbitrary long sequence of directory (e.g. "Coq.Lists.PolyList.flat\_map" where "Coq" means that "flat\_map" is part of Coq standard library, "Lists" means it is defined in the Lists library and "PolyList" means it is in the file Polylist) (+)
- Constructions can be referred by their base name, or, in case of conflict, by a "qualified" name, where the base name is prefixed by the module name (and possibly by a directory name, and so on). A fully qualified name is an absolute name which always refer to the construction it denotes (to preserve the visibility of all constructions, no conflict is allowed for an absolute name) (+)
- Long names are available for modules with the possibility of using the directory name as a component of the module full name (with option -R to coqtop and coqc, or command Add LoadPath) (+)
- Improved conflict resolution strategy (the Unix PATH model), allowing more constructions to be referred just by their base name

## Language: miscellaneous

- The names of variables for Record projections \_and\_ for induction principles (e.g. sum\_ind) is now based on the first letter of their type (main source of incompatibility) (\*\*)(+)
- Most typing errors have now a precise location in the source (+)
- Slightly different mechanism to solve "?" (\*)(+)
- More arguments may be considered implicit at section closing (\*)(+)
- Bug with identifiers ended by a number greater than 2^30 fixed (+)

• New visibility discipline for Remark, Fact and Local: Remark's and Fact's now survive at the end of section, but are only accessible using a qualified names as soon as their strength expires; Local's disappear and are moved into local definitions for each construction persistent at section closing

#### Language: Cases

- Cases no longer considers aliases inferable from dependencies in types (\*)(+)
- A redundant clause in Cases is now an error (\*)

#### Reduction

- New reduction flags "Zeta" and "Evar" in Eval Compute, for inlining of local definitions and instantiation of existential variables
- Delta reduction flag does not perform Zeta and Evar reduction any more (\*)
- Constants declared as opaque (using Qed) can no longer become transparent (a constant intended to be alternatively opaque and transparent must be declared as transparent (using Defined)); a risk exists (until next Coq version) that Simpl and Hnf reduces opaque constants (\*)

#### **New tactics**

- New set of tactics to deal with types equipped with specific equalities (a.k.a. Setoids, e.g. nat equipped with eq\_nat) [by C. Renard]
- New tactic Assert, similar to Cut but expected to be more user-friendly
- New tactic NewDestruct and NewInduction intended to replace Elim and Induction, Case and Destruct in a more user-friendly way (see restrictions in the reference manual)
- New tactic ROmega: an experimental alternative (based on reflexion) to Omega [by P. Crégut]
- New tactic language Ltac (see reference manual) (+)
- New versions of Tauto and Intuition, fully rewritten in the new Ltac language; they run faster and produce more compact proofs; Tauto is fully compatible but, in exchange of a better uniformity, Intuition is slightly weaker (then use Tauto instead) (\*\*)(+)
- New tactic Field to decide equalities on commutative fields (as a special case, it works on real numbers)
   (+)
- New tactic Fourier to solve linear inequalities on reals numbers [by L. Pottier] (+)
- New tactics dedicated to real numbers: DiscrR, SplitRmult, SplitAbsolu (+)

#### Changes in existing tactics

- Reduction tactics in local definitions apply only to the body
- New syntax of the form "Compute in Type of H." to require a reduction on the types of local definitions
- Inversion, Injection, Discriminate, ... apply also on the quantified premises of a goal (using the "Intros until" syntax)
- Decompose has been fixed but hypotheses may get different names (\*)(+)

- Tauto now manages uniformly hypotheses and conclusions of the form t=t which all are considered equivalent to True. Especially, Tauto now solves goals of the form H: ~ t = t |- A.
- The "Let" tactic has been renamed "LetTac" and is now based on the primitive "let-in" (+)
- Elim can no longer be used with an elimination schema different from the one defined at definition time of the inductive type. To overload an elimination schema, use "Elim <hyp> using <name of the new schema>" (\*)(+)
- Simpl no longer unfolds the recursive calls of a mutually defined fixpoint (\*)(+)
- Intro now fails if the hypothesis name already exists (\*)(+)
- "Require Prolog" is no longer needed (i.e. it is available by default) (\*)(+)
- Unfold now fails on a non unfoldable identifier (\*)(+)
- Unfold also applies on definitions of the local context
- AutoRewrite now deals only with the main goal and it is the purpose of Hint Rewrite to deal with generated subgoals (+)
- Redundant or incompatible instantiations in Apply ... with ... are now correctly managed (+)

## **Efficiency**

- Excessive memory uses specific to V7.0 fixed
- Sizes of .vo files vary a lot compared to V6.3 (from -30% to +300% depending on the developments)
- An improved reduction strategy for lazy evaluation
- A more economical mechanism to ensure logical consistency at the Type level; warning: this is experimental and may produce "universes" anomalies (please report)

#### Concrete syntax of constructions

- Only identifiers starting with "\_" or a letter, and followed by letters, digits, "\_" or "'" are allowed (e.g. "\$" and "@" are no longer allowed) (\*)
- A multiple binder like  $(a:A)(a,b:(P\ a))(Q\ a)$  is no longer parsed as  $(a:A)(a0:(P\ a))(b:(P\ a))(Q\ a0)$  but as  $(a:A)(a0:(P\ a))(b:(P\ a0))(Q\ a0)$  (\*)(+)
- A dedicated syntax has been introduced for Reals (e.g 3+1/x) (+)
- Pretty-printing of Infix notations fixed. (+)

#### Parsing and grammar extension

- More constraints when writing ast
  - "{...}" and the macros \$LIST, \$VAR, etc. now expect a metavariable (an identifier starting with \$) (\*)
  - identifiers should starts with a letter or "\_" and be followed by letters, digits, "\_" or "'" (other characters are still supported but it is not advised to use them) (\*)(+)
- Entry "command" in "Grammar" and quotations (<<...>> stuff) is renamed "constr" as in "Syntax" (+)

- New syntax "[" sentence\_1 ... sentence\_n"]." to group sentences (useful for Time and to write grammar rules abbreviating several commands) (+)
- The default parser for actions in the grammar rules (and for patterns in the pretty-printing rules) is now the one associated to the grammar (i.e. vernac, tactic or constr); no need then for quotations as in <:vernac:<...>>; to return an "ast", the grammar must be explicitly typed with tag ": ast" or ": ast list", or if a syntax rule, by using <<...>> in the patterns (expression inside these angle brackets are parsed as "ast"); for grammars other than vernac, tactic or constr, you may explicitly type the action with tags ": constr", ": tactic", or ":vernac" (\*\*)(+)
- Interpretation of names in Grammar rule is now based on long names, which allows to avoid problems (or sometimes tricks;) related to overloaded names (+)

#### **New commands**

- New commands "Print XML All", "Show XML Proof", ... to show or export theories to XML to be used with Helm's publishing and rendering tools (see http://www.cs.unibo.it/helm) (by Claudio Sacerdoti Coen) (+)
- New commands to manually set implicit arguments (+)
  - "Implicits ident." to activate the implicit arguments mode just for ident
  - "Implicits ident [num1 num2 ...]." to explicitly give which arguments have to be considered as implicit
- New SearchPattern/SearchRewrite (by Yves Bertot) (+)
- New commands "Debug on"/"Debug off" to activate/deactivate the tactic language debugger (+)
- New commands to map physical paths to logical paths (+) Add LoadPath physical\_dir as logical\_dir
   Add Rec LoadPath physical\_dir as logical\_dir

#### Changes in existing commands

- Generalization of the usage of qualified identifiers in tactics and commands about globals, e.g. Decompose, Eval Delta; Hints Unfold, Transparent, Require
- Require synchronous with Reset; Require's scope stops at Section ending (\*)
- For a module indirectly loaded by a "Require" but not exported, the command "Import module" turns the constructions defined in the module accessible by their short name, and activates the Grammar, Syntax, Hint, ... declared in the module (+)
- The scope of the "Search" command can be restricted to some modules (+)
- Final dot in command (full stop/period) must be followed by a blank (newline, tabulation or whitespace) (+)
- Slight restriction of the syntax for Cbv Delta: if present, option [-myconst] must immediately follow the Delta keyword (\*)(+)
- SearchIsos currently not supported
- Add ML Path is now implied by Add LoadPath (+)
- New names for the following commands (+)
  - AddPath -> Add LoadPath Print LoadPath -> Print LoadPath DelPath -> Remove LoadPath AddRecPath -> Add Rec LoadPath Print Path -> Print Coercion Paths

Implicit Arguments On -> Set Implicit Arguments Implicit Arguments Off -> Unset Implicit Arguments

Begin Silent -> Set Silent End Silent -> Unset Silent.

#### **Tools**

- cogtop (+)
  - Two executables: coqtop.byte and coqtop.opt (if supported by the platform)
  - coqtop is a link to the more efficient executable (coqtop.opt if present)
  - option -full is obsolete (+)
- do Makefile renamed into coq makefile (+)
- New option -R to coqtop and coqc to map a physical directory to a logical one (+)
- coqc no longer needs to create a temporary file
- No more warning if no initialization file .coqrc exists

#### **Extraction**

• New algorithm for extraction able to deal with "Type" (+) (by J.-C. Filliâtre and P. Letouzey)

## Standard library

- New library on maps on integers (IntMap, contributed by Jean Goubault)
- New lemmas about integer numbers [ZArith]
- New lemmas and a "natural" syntax for reals [Reals] (+)
- Exc/Error/Value renamed into Option/Some/None (\*)

#### New user contributions

- Constructive complex analysis and the Fundamental Theorem of Algebra [FTA] (Herman Geuvers, Freek Wiedijk, Jan Zwanenburg, Randy Pollack, Henk Barendregt, Nijmegen)
- A new axiomatization of ZFC set theory [Functions in ZFC] (C. Simpson, Sophia-Antipolis)
- Basic notions of graph theory [GRAPHS-BASICS] (Jean Duprat, Lyon)
- A library for floating-point numbers [Float] (Laurent Théry, Sylvie Boldo, Sophia-Antipolis)
- Formalisation of CTL and TCTL temporal logic [CtlTctl] (Carlos Daniel Luna, Montevideo)
- Specification and verification of the Railroad Crossing Problem in CTL and TCTL [RailroadCrossing] (Carlos Daniel Luna, Montevideo)
- P-automaton and the ABR algorithm [PAutomata] (Christine Paulin, Emmanuel Freund, Orsay)
- Semantics of a subset of the C language [MiniC] (Eduardo Giménez, Emmanuel Ledinot, Suresnes)
- Correctness proofs of the following imperative algorithms: Bresenham line drawing algorithm [Bresenham], Marché's minimal edition distance algorithm [Diff] (Jean-Christophe Filliâtre, Orsay)

- Correctness proofs of Buchberger's algorithm [Buchberger] and RSA cryptographic algorithm [Rsa] (Laurent Théry, Sophia-Antipolis)
- Correctness proof of Stalmarck tautology checker algorithm [Stalmarck] (Laurent Théry, Pierre Letouzey, Sophia-Antipolis)

## 2.4.3 Details of changes in 7.2

#### Language

- Automatic insertion of patterns for local definitions in the type of the constructors of an inductive types (for compatibility with V6.3 let-in style)
- Coercions allowed in Cases patterns
- New declaration "Canonical Structure id = t : I" to help resolution of equations of the form (proj ?)=a; if proj(e)=a then a is canonically equipped with the remaining fields in e, i.e. ? is instantiated by e

#### Tactics

- New tactic "ClearBody H" to clear the body of definitions in local context
- New tactic "Assert H := c" for forward reasoning
- Slight improvement in naming strategy for NewInduction/NewDestruct
- Intuition/Tauto do not perform useless unfolding and work up to conversion

Extraction (details in plugins/extraction/CHANGES or documentation)

- Syntax changes: there are no more options inside the extraction commands. New commands for customization and options have been introduced instead.
- More optimizations on extracted code.
- Extraction tests are now embedded in 14 user contributions.

#### Standard library

- In [Relations], Rstar.v and Newman.v now axiom-free.
- In [Sets], Integers.v now based on nat
- In [Arith], more lemmas in Min.v, new file Max.v, tail-recursive plus and mult added to Plus.v and Mult.v respectively
- New directory [Sorting] with a proof of heapsort (dragged from 6.3.1 lib)
- In [Reals], more lemmas in Rbase.v, new lemmas on square, square root and trigonometric functions (R\_sqr.v Rtrigo.v); a complementary approach and new theorems about continuity and derivability in Ranalysis.v; some properties in plane geometry such as translation, rotation or similarity in Rgeom.v; finite sums and Chasles property in Rsigma.v

## Bugs

- Confusion between implicit args of locals and globals of same base name fixed
- Various incompatibilities wrt inference of "?" in V6.3.1 fixed
- Implicits in infix section variables bug fixed
- Known coercions bugs fixed
- Apply "universe anomaly" bug fixed

- NatRing now working
- "Discriminate 1", "Injection 1", "Simplify\_eq 1" now working
- NewInduction bugs with let-in and recursively dependent hypotheses fixed
- Syntax [x:=t:T]u now allowed as mentioned in documentation
- Bug with recursive inductive types involving let-in fixed
- Known pattern-matching bugs fixed
- Known Cases elimination predicate bugs fixed
- Improved errors messages for pattern-matching and projections
- Better error messages for ill-typed Cases expressions

#### Incompatibilities

- New naming strategy for NewInduction/NewDestruct may affect 7.1 compatibility
- Extra parentheses may exceptionally be needed in tactic definitions.
- Coq extensions written in Ocaml need to be updated (see dev/changements.txt for a description of the main changes in the interface files of V7.2)
- New behaviour of Intuition/Tauto may exceptionally lead to incompatibilities

## 2.4.4 Details of changes in 7.3

#### Language

- Slightly improved compilation of pattern-matching (slight source of incompatibilities)
- Record's now accept anonymous fields "\_" which does not build projections
- Changes in the allowed elimination sorts for certain class of inductive definitions: an inductive definition without constructors of Sort Prop can be eliminated on sorts Set and Type A "singleton" inductive definition (one constructor with arguments in the sort Prop like conjunction of two propositions or equality) can be eliminated directly on sort Type (In V7.2, only the sorts Prop and Set were allowed)

#### Tactics

- New tactic "Rename x into y" for renaming hypotheses
- New tactics "Pose x:=u" and "Pose u" to add definitions to local context
- Pattern now working on partially applied subterms
- Ring no longer applies irreversible congruence laws of mult but better applies congruence laws of plus (slight source of incompatibilities).
- Field now accepts terms to be simplified as arguments (as for Ring). This extension has been also implemented using the toplevel tactic language.
- Intuition does no longer unfold constants except "<->" and "~". It can be parameterized by a tactic. It also can introduce dependent product if needed (source of incompatibilities)
- "Match Context" now matching more recent hypotheses first and failing only on user errors and Fail tactic (possible source of incompatibilities)
- Tactic Definition's without arguments now allowed in Coq states
- Better simplification and discrimination made by Inversion (source of incompatibilities)

#### Bugs

- "Intros H" now working like "Intro H" trying first to reduce if not a product
- Forward dependencies in Cases now taken into account
- Known bugs related to Inversion and let-in's fixed
- Bug unexpected Delta with let-in now fixed

Extraction (details in plugins/extraction/CHANGES or documentation)

- Signatures of extracted terms are now mostly expunged from dummy arguments.
- Haskell extraction is now operational (tested & debugged).

## Standard library

- Some additions in [ZArith]: three files (Zcomplements.v, Zpower.v and Zlogarithms.v) moved from plugins/omega in order to be more visible, one Zsgn function, more induction principles (Wf\_Z.v and tail of Zcomplements.v), one more general Euclid theorem
- Peano\_dec.v and Compare\_dec.v now part of Arith.v

#### Tools

• new option -dump-glob to coqtop to dump globalizations (to be used by the new documentation tool coqdoc; see  $http://www.lri.fr/\sim filliatr/coqdoc$ )

#### User Contributions

- CongruenceClosure (congruence closure decision procedure) [Pierre Corbineau, ENS Cachan]
- MapleMode (an interface to embed Maple simplification procedures over rational fractions in Coq) [David Delahaye, Micaela Mayero, Chalmers University]
- Presburger: A formalization of Presburger's algorithm [Laurent Thery, INRIA Sophia Antipolis]
- Chinese has been rewritten using Z from ZArith as datatype ZChinese is the new version, Chinese the obsolete one [Pierre Letouzey, LRI Orsay]

#### Incompatibilities

- Ring: exceptional incompatibilities (1 above 650 in submitted user contribs, leading to a simplification)
- Intuition: does not unfold any definition except "<->" and " $\sim$ "
- Cases: removal of some extra Cases in configurations of the form "Cases ... of C \_ => ... | \_ D => ..." (effects on 2 definitions of submitted user contributions necessitating the removal of now superfluous proof steps in 3 different proofs)
- Match Context, in case of incompatibilities because of a now non trapped error (e.g. Not\_found or Failure), use instead tactic Fail to force Match Context trying the next clause
- Inversion: better simplification and discrimination may occasionally lead to less subgoals and/or hypotheses and different naming of hypotheses
- Unification done by Apply/Elim has been changed and may exceptionally lead to incompatible instantiations
- Peano\_dec.v and Compare\_dec.v parts of Arith.v make Auto more powerful if these files were not already required (1 occurrence of this in submitted user contribs)

## Changes in 7.3.1

#### Bug fixes

- Corrupted Field tactic and Match Context tactic construction fixed
- Checking of names already existing in Assert added (#1386)
- Invalid argument bug in Exact tactic solved (#1387)
- Colliding bound names bug fixed (#1412)
- Wrong non-recursivity test for Record fixed (#1394)
- Out of memory/seg fault bug related to parametric inductive fixed (#1404)
- Setoid\_replace/Setoid\_rewrite bug wrt "==" fixed

#### Misc

- Ocaml version >= 3.06 is needed to compile Coq from sources
- Simplification of fresh names creation strategy for Assert, Pose and LetTac (#1402)

## 2.4.5 Details of changes in 7.4

#### Symbolic notations

- Introduction of a notion of scope gathering notations in a consistent set; a notation sets has been developed for nat, Z and R (undocumented)
- New command "Notation" for declaring notations simultaneously for parsing and printing (see chap 10 of the reference manual)
- Declarations with only implicit arguments now handled (e.g. the argument of nil can be set implicit; use !nil to refer to nil without arguments)
- "Print Scope sc" and "Locate ntn" allows to know to what expression a notation is bound
- New defensive strategy for printing or not implicit arguments to ensure re-type-checkability of the printed term
- In Grammar command, the only predefined non-terminal entries are ident, global, constr and pattern (e.g. nvar, numarg disappears); the only allowed grammar types are constr and pattern; ast and ast list are no longer supported; some incompatibilities in Grammar: when a syntax is a initial segment of an other one, Grammar does not work, use Notation

## Library

- Lemmas in Set from Compare\_dec.v (le\_lt\_dec, ...) and Wf\_nat.v (lt\_wf\_rec, ...) are now transparent. This may be source of incompatibilities.
- Syntactic Definitions Fst, Snd, Ex, All, Ex2, AllT, ExT, ExT2, ProjS1, ProjS2, Error, Value and Except are turned to notations. They now must be applied (incompatibilities only in unrealistic cases).
- More efficient versions of Zmult and times (30% faster)
- Reals: the library is now divided in 6 parts (Rbase, Rfunctions, SeqSeries, Rtrigo, Ranalysis, Integration). New tactics: Sup and RCompute. See Reals.v for details.

#### Modules

• Beta version, see doc chap 2.5 for commands and chap 5 for theory

#### Language

- Inductive definitions now accept ">" in constructor types to declare the corresponding constructor as
  a coercion.
- Idem for assumptions declarations and constants when the type is mentioned.
- The "Coercion" and "Canonical Structure" keywords now accept the same syntax as "Definition", i.e. "hyps :=c (:t)?" or "hyps :t".
- Theorem-like declaration now accepts the syntax "Theorem thm [x:t;...] : u".
- Remark's and Fact's now definitively behave as Theorem and Lemma: when sections are closed, the full name of a Remark or a Fact has no longer a section part (source of incompatibilities)
- Opaque Local's (i.e. built by tactics and ended by Qed), do not survive section closing any longer; as a side-effect, Opaque Local's now appear in the local context of proofs; their body is hidden though (source of incompatibilities); use one of Remark/Fact/Lemma/Theorem instead to simulate the old behaviour of Local (the section part of the name is not kept though)

#### ML tactic and vernacular commands

- "Grammar tactic" and "Grammar vernac" of type "ast" are no longer supported (only "Grammar tactic simple\_tactic" of type "tactic" remains available).
- Concrete syntax for ML written vernacular commands and tactics is now declared at ML level using camlp4 macros TACTIC EXTEND et VERNAC COMMAND EXTEND.
- "Check n c" now "n:Check c", "Eval n ..." now "n:Eval ..."
- Proof with T (no documentation)
- SearchAbout id prints all theorems which contain id in their type

#### Tactic definitions

- Static globalisation of identifiers and global references (source of incompatibilities, especially, Recursive keyword is required for mutually recursive definitions).
- New evaluation semantics: no more partial evaluation at definition time; evaluation of all Tactic/Meta Definition, even producing terms, expect a proof context to be evaluated (especially "()" is no longer needed).
- Debugger now shows the nesting level and the reasons of failure

## Tactics

- Equality tactics (Rewrite, Reflexivity, Symmetry, Transitivity) now understand JM equality
- Simpl and Change now apply to subterms also
- "Simpl f" reduces subterms whose head constant is f
- Double Induction now referring to hypotheses like "Intros until"
- "Inversion" now applies also on quantified hypotheses (naming as for Intros until)
- NewDestruct now accepts terms with missing hypotheses
- NewDestruct and NewInduction now accept user-provided elimination scheme
- NewDestruct and NewInduction now accept user-provided introduction names
- Omega could solve goals such as ~x<y |- x>=y but failed when the hypothesis was unfolded to x < y -> False. This is fixed. In addition, it can also recognize 'False' in the hypothesis and use it to solve the goal.
- Coercions now handled in "with" bindings

- "Subst x" replaces all occurrences of x by t in the goal and hypotheses when an hypothesis x=t or x:=t or t=x exists
- Fresh names for Assert and Pose now based on collision-avoiding Intro naming strategy (exceptional source of incompatibilities)
- LinearIntuition (no documentation)
- Unfold expects a correct evaluable argument
- Clear expects existing hypotheses

Extraction (See details in plugins/extraction/CHANGES and README):

- An experimental Scheme extraction is provided.
- Concerning Ocaml, extracted code is now ensured to always type-check, thanks to automatic inserting of Obj.magic.
- Experimental extraction of Coq new modules to Ocaml modules.

#### Proof rendering in natural language

• Export of theories to XML for publishing and rendering purposes now includes proof-trees (see http://www.cs.unibo.it/helm)

#### Miscellaneous

- Printing Coercion now used through the standard keywords Set/Add, Test, Print
- "Print Term id" is an alias for "Print id"
- New switch "Unset/Set Printing Symbols" to control printing of symbolic notations
- Two new variants of implicit arguments are available
  - Unset/Set Contextual Implicits tells to consider implicit also the arguments inferable from the context (e.g. for nil or refl\_eq)
  - Unset/Set Strict Implicits tells to consider implicit only the arguments that are inferable in any case (i.e. arguments that occurs as argument of rigid constants in the type of the remaining arguments; e.g. the witness of an existential is not strict since it can vanish when applied to a predicate which does not use its argument)

## Incompatibilities

- "Grammar tactic ... : ast" and "Grammar vernac ... : ast" are no longer supported, use TACTIC EXTEND and VERNAC COMMAND EXTEND on the ML-side instead
- Transparency of le\_lt\_dec and co (leads to some simplification in proofs; in some cases, incompatibilities is solved by declaring locally opaque the relevant constant)
- Opaque Local do not now survive section closing (rename them into Remark/Lemma/... to get them still surviving the sections; this renaming allows also to solve incompatibilites related to now forbidden calls to the tactic Clear)
- Remark and Fact have no longer (very) long names (use Local instead in case of name conflict)

#### Bugs

- Improved localisation of errors in Syntactic Definitions
- Induction principle creation failure in presence of let-in fixed (#1459)
- Inversion bugs fixed (#1427 and #1437)
- Omega bug related to Set fixed (#1384)

- Type-checking in efficiency of nested destructuring let-in fixed (#1435)
- Improved handling of let-in during holes resolution phase (#1460)

## Efficiency

• Implementation of a memory sharing strategy reducing memory requirements by an average ratio of 3.

## RECENT CHANGES

## 3.1 Version 8.11

## 3.1.1 Summary of changes

The main changes brought by Coq version 8.11 are:

- Ltac2, a new tactic language for writing more robust larger scale tactics, with built-in support for datatypes and the multi-goal tactic monad.
- *Primitive floats* are integrated in terms and follow the binary64 format of the IEEE 754 standard, as specified in the Coq.Float.Floats library.
- *Cleanups* of the section mechanism, delayed proofs and further restrictions of template polymorphism to fix soundness issues related to universes.
- New *unsafe flags* to disable locally guard, positivity and universe checking. Reliance on these flags is always printed by Print Assumptions.
- Fixed bugs of Export and Import that can have a significant impact on user developments (common source of incompatibility!).
- New interactive development method based on **vos** *interface files*, allowing to work on a file without recompiling the proof parts of their dependencies.
- New Arguments annotation for *bidirectional type inference* configuration for reference (e.g. constants, inductive) applications.
- New refine attribute for Instance can be used instead of the removed Refine Instance Mode.
- Generalization of the under and over tactics of SSReflect to arbitrary relations.
- Revision of the Coq.Reals library, its axiomatisation and instances of the constructive and classical real numbers.

Additionally, while the *omega* tactic is not yet deprecated in this version of Coq, it should soon be the case and we already recommend users to switch to *lia* in new proof scripts (see also the warning message in the *corresponding chapter*).

The dev/doc/critical-bugs file documents the known critical bugs of Coq and affected releases. See the *Changes in 8.11+beta1* section and following sections for the detailed list of changes, including potentially breaking changes marked with **Changed**.

Coq's documentation is available at https://coq.github.io/doc/v8.11/api (documentation of the ML API), https://coq.github.io/doc/v8.11/refman (reference manual), and https://coq.github.io/doc/v8.11/stdlib (documentation of the standard library).

Maxime Dénès, Emilio Jesús Gallego Arias, Gaëtan Gilbert, Michael Soegtrop and Théo Zimmermann worked on maintaining and improving the continuous integration system and package building infrastructure.

The OPAM repository for Coq packages has been maintained by Guillaume Claret, Karl Palmskog, Matthieu Sozeau and Enrico Tassi with contributions from many users. A list of packages is available at https://coq.inria.fr/opam/www/.

The 61 contributors to this version are Michael D. Adams, Guillaume Allais, Helge Bahmann, Langston Barrett, Guillaume Bertholon, Frédéric Besson, Simon Boulier, Michael Caci, Tej Chajed, Arthur Charguéraud, Cyril Cohen, Frédéric Dabrowski, Arthur Azevedo de Amorim, Maxime Dénès, Nikita Eshkeev, Jim Fehrle, Emilio Jesús Gallego Arias, Paolo G. Giarrusso, Gaëtan Gilbert, Georges Gonthier, Jason Gross, Samuel Gruetter, Armaël Guéneau, Hugo Herbelin, Florent Hivert, Jasper Hugunin, Shachar Itzhaky, Jan-Oliver Kaiser, Robbert Krebbers, Vincent Laporte, Olivier Laurent, Samuel Lelièvre, Nicholas Lewycky, Yishuai Li, Jose Fernando Lopez Fernandez, Andreas Lynge, Kenji Maillard, Erik Martin-Dorel, Guillaume Melquiond, Alexandre Moine, Oliver Nash, Wojciech Nawrocki, Antonio Nikishaev, Pierre-Marie Pédrot, Clément Pit-Claudel, Lars Rasmusson, Robert Rand, Talia Ringer, JP Rodi, Pierre Roux, Kazuhiko Sakaguchi, Vincent Semeria, Michael Soegtrop, Matthieu Sozeau, spanjel, Claude Stolze, Enrico Tassi, Laurent Théry, James R. Wilcox, Xia Li-yao, Théo Zimmermann

Many power users helped to improve the design of the new features via the issue and pull request system, the Coq development mailing list, the coq-club@inria.fr mailing list or the Discourse forum<sup>6</sup>. It would be impossible to mention exhaustively the names of everybody who to some extent influenced the development.

Version 8.11 is the sixth release of Coq developed on a time-based development cycle. Its development spanned 3 months from the release of Coq 8.10. Pierre-Marie Pédrot is the release manager and maintainer of this release, assisted by Matthieu Sozeau. This release is the result of 2000+ commits and 300+ PRs merged, closing 75+ issues.

Paris, November 2019, Matthieu Sozeau for the Coq development team

## 3.1.2 Changes in 8.11+beta1

## Kernel

- Added: A built-in support of floating-point arithmetic, allowing one to devise efficient reflection tactics involving numerical computation. Primitive floats are added in the language of terms, following the binary64 format of the IEEE 754 standard, and the related operations are implemented for the different reduction engines of Coq by using the corresponding processor operators in rounding-to-nearest-even. The properties of these operators are axiomatized in the theory Coq.Floats.FloatAxioms which is part of the library Coq.Floats.Floats. See Section Primitive Floats (#9867<sup>7</sup>, closes #8276<sup>8</sup>, by Guillaume Bertholon, Erik Martin-Dorel, Pierre Roux).
- Changed: Internal definitions generated by *abstract*-like tactics are now inlined inside universe *Qed*-terminated polymorphic definitions, similarly to what happens for their monomorphic counterparts, (#10439<sup>9</sup>, by Pierre-Marie Pédrot).

<sup>&</sup>lt;sup>6</sup> https://coq.discourse.group/

<sup>&</sup>lt;sup>7</sup> https://github.com/coq/coq/pull/9867

<sup>8</sup> https://github.com/coq/coq/issues/8276

<sup>9</sup> https://github.com/coq/coq/pull/10439

- **Fixed:** Section data is now part of the kernel. Solves a soundness issue in interactive mode where global monomorphic universe constraints would be dropped when forcing a delayed opaque proof inside a polymorphic section. Also relaxes the nesting criterion for sections, as polymorphic sections can now appear inside a monomorphic one (#10664, <sup>10</sup> by Pierre-Marie Pédrot).
- Changed: Using SProp is now allowed by default, without needing to pass -allow-sprop or use Allow StrictProp (#10811<sup>11</sup>, by Gaëtan Gilbert).

## Specification language, type inference

- Added: Annotation in Arguments for bidirectionality hints: it is now possible to tell type inference to use type information from the context once the n first arguments of an application are known. The syntax is: Arguments foo x y & z. See Arguments (bidirectionality hints) (#10049<sup>12</sup>, by Maxime Dénès with help from Enrico Tassi).
- Added: Record fields can be annotated to prevent them from being used as canonical projections; see *Canonical Structures* for details (#10076<sup>13</sup>, by Vincent Laporte).
- Changed: Require parentheses around nested disjunctive patterns, so that pattern and term syntax are consistent; match branch patterns no longer require parentheses for notation at level 100 or more.

## Warning: Incompatibilities

- In match p with  $(_, (0|1)) \Rightarrow \dots$  parentheses may no longer be omitted around 0|1.
- Notation (p | q) now potentially clashes with core pattern syntax, and should be avoided.
   w disj-pattern-notation flags such Notation.

See Extended pattern matching for details (#10167<sup>14</sup>, by Georges Gonthier).

- Changed: Function always opens a proof when used with a measure or wf annotation, see Advanced recursive functions for the updated documentation (#10215<sup>15</sup>, by Enrico Tassi).
- Changed: The legacy command Add Morphism always opens a proof and cannot be used inside a module type. In order to declare a module type parameter that happens to be a morphism, use Declare Morphism. See Deprecated syntax and backward incompatibilities for the updated documentation (#10215<sup>16</sup>, by Enrico Tassi).
- Changed: The universe polymorphism setting now applies from the opening of a section. In particular, it is not possible anymore to mix polymorphic and monomorphic definitions in a section when there are no variables nor universe constraints defined in this section. This makes the behaviour consistent with the documentation. (#10441<sup>17</sup>, by Pierre-Marie Pédrot)
- Added: The Section vernacular command now accepts the "universes" attribute. In addition to setting the section universe polymorphism, it also locally sets the universe polymorphic option inside the section. (#10441<sup>18</sup>, by Pierre-Marie Pédrot)

3.1. Version 8.11 27

 $<sup>^{10}</sup>$  https://github.com/coq/coq/pull/10664

<sup>&</sup>lt;sup>11</sup> https://github.com/coq/coq/pull/10811

<sup>12</sup> https://github.com/coq/coq/pull/10049

<sup>13</sup> https://github.com/coq/coq/pull/10076

<sup>14</sup> https://github.com/coq/coq/pull/10167

<sup>15</sup> https://github.com/coq/coq/pull/10215

https://github.com/coq/coq/pull/10215 https://github.com/coq/coq/pull/10215

 $<sup>^{17}~\</sup>mathrm{https://github.com/coq/coq/pull/10441}$ 

 $<sup>^{18}</sup>$  https://github.com/coq/coq/pull/10441

- Fixed: Program Fixpoint now uses ex and sig to make telescopes involving Prop types (#10758<sup>19</sup>, by Gaëtan Gilbert, fixing #10757<sup>20</sup> reported by Xavier Leroy).
- Changed: Output of the *Print* and *About* commands. Arguments meta-data is now displayed as the corresponding *Arguments* command instead of the human-targeted prose used in previous Coq versions. (#10985<sup>21</sup>, by Gaëtan Gilbert).
- Added: #[refine] attribute for *Instance*, a more predictable version of the old Refine Instance Mode which unconditionally opens a proof (#10996<sup>22</sup>, by Gaëtan Gilbert).
- Changed: The unsupported attribute error is now an error-by-default warning, meaning it can be disabled (#10997<sup>23</sup>, by Gaëtan Gilbert).
- **Fixed:** Bugs sometimes preventing to define valid (co)fixpoints with implicit arguments in the presence of local definitions, see #3282<sup>24</sup> (#11132<sup>25</sup>, by Hugo Herbelin).

#### Example

The following features an implicit argument after a local definition. It was wrongly rejected.

```
Definition f := fix f (o := true) \{n : nat\} m \{struct m\} := match m with <math>0 => 0 \mid S m' => f (n := n+1) m' end.
```

#### **Notations**

- Added: Numeral Notations now support sorts in the input to printing functions (e.g., numeral notations can be defined for terms containing things like @cons Set nat nil). (#9883<sup>26</sup>, by Jason Gross).
- Added: The Notation and Infix commands now support the deprecated attribute (#10180<sup>27</sup>, by Maxime Dénès).
- **Deprecated:** The former compat annotation for notations is deprecated, and its semantics changed. It is now made equivalent to using a deprecated attribute, and is no longer connected with the -compat command-line flag (#10180<sup>28</sup>, by Maxime Dénès).
- Changed: A simplification of parsing rules could cause a slight change of parsing precedences for the very rare users who defined notations with constr at level strictly between 100 and 200 and used these notations on the right-hand side of a cast operator (:, :>, :>>) (#10963<sup>29</sup>, by Théo Zimmermann, simplification initially noticed by Jim Fehrle).

## Tactics

• Added: Syntax injection term as [= intropattern] as an alternative to injection term as simple\_intropattern using the standard injection\_intropattern syntax (#9288<sup>30</sup>, by Hugo Herbelin).

```
19 https://github.com/coq/coq/pull/10758
20 https://github.com/coq/coq/issues/10757
21 https://github.com/coq/coq/pull/10985
22 https://github.com/coq/coq/pull/10996
23 https://github.com/coq/coq/pull/10997
24 https://github.com/coq/coq/issues/3282
25 https://github.com/coq/coq/pull/11132
26 https://github.com/coq/coq/pull/9883
27 https://github.com/coq/coq/pull/10180
28 https://github.com/coq/coq/pull/10180
```

 $<sup>^{29}</sup>$  https://github.com/coq/coq/pull/10963  $^{30}$  https://github.com/coq/coq/pull/9288

- Changed: Reimplementation of the zify tactic. The tactic is more efficient and copes with dependent hypotheses. It can also be extended by redefining the tactic zify\_post\_hook. (#9856<sup>31</sup>, fixes #8898<sup>32</sup>, #7886<sup>33</sup>, #9848<sup>34</sup> and #5155<sup>35</sup>, by Frédéric Besson).
- Changed: The goal selector tactical only now checks that the goal range it is given is valid instead of ignoring goals out of the focus range (#10318<sup>36</sup>, by Gaëtan Gilbert).
- Added: Flags Lia Cache, Nia Cache and Nra Cache. (#10765<sup>37</sup>, by Frédéric Besson, see #10772<sup>38</sup> for use case).
- Added: The zify tactic is now aware of Z.to\_N. (#10774<sup>39</sup>, grants #9162<sup>40</sup>, by Kazuhiko Sakaguchi).
- Changed: The assert\_succeeds and assert\_fails tactics now only run their tactic argument once, even if it has multiple successes. This prevents blow-up and looping from using multisuccess tactics with assert\_succeeds. (#10966<sup>41</sup> fixes #10965<sup>42</sup>, by Jason Gross).
- **Fixed:** The assert\_succeeds and assert\_fails tactics now behave correctly when their tactic fully solves the goal. (#10966<sup>43</sup> fixes #9114<sup>44</sup>, by Jason Gross).

## Tactic language

- Added: Ltac2, a new version of the tactic language Ltac, that doesn't preserve backward compatibility, has been integrated in the main Coq distribution. It is still experimental, but we already recommend users of advanced Ltac to start using it and report bugs or request enhancements. See its documentation in the dedicated chapter (#10002<sup>45</sup>, plugin authored by Pierre-Marie Pédrot, with contributions by various users, integration by Maxime Dénès, help on integrating / improving the documentation by Théo Zimmermann and Jim Fehrle).
- Added: Ltac2 tactic notations with "constr" arguments can specify the interpretation scope for these arguments; see *Notations* for details (#10289<sup>46</sup>, by Vincent Laporte).
- Changed: White spaces are forbidden in the &ident syntax for ltac2 references that are described in Built-in quotations (#10324<sup>47</sup>, fixes #10088<sup>48</sup>, authored by Pierre-Marie Pédrot).

#### **SSReflect**

• Added: Generalize tactics under and over for any registered relation. More precisely, assume the given context lemma has type forall f1 f2, ... -> (forall i, R1 (f1 i) (f2 i)) -> R2 f1 f2. The first step performed by under (since Coq 8.10) amounts to calling the tactic rewrite, which itself relies on setoid\_rewrite if need be. So this step was already compatible with a double implication or setoid equality for the conclusion head symbol R2. But a further step consists in tagging the generated

```
33 https://github.com/coq/coq/issues/7886
34 https://github.com/coq/coq/issues/9848
35 https://github.com/coq/coq/issues/5155
36 https://github.com/coq/coq/pull/10318
37 https://github.com/coq/coq/pull/10765
38 https://github.com/coq/coq/issues/10772
39 https://github.com/coq/coq/pull/10774
40 https://github.com/coq/coq/issues/9162
41 https://github.com/coq/coq/pull/10966
```

 $^{31}$  https://github.com/coq/coq/pull/9856  $^{32}$  https://github.com/coq/coq/issues/8898

- https://github.com/coq/coq/jun/10900 42 https://github.com/coq/coq/issues/10965
- 43 https://github.com/coq/coq/pull/10966
- $^{44}~\rm https://github.com/coq/coq/issues/9114$
- 45 https://github.com/coq/coq/pull/10002
- 46 https://github.com/coq/coq/pull/10289
- 47 https://github.com/coq/coq/pull/10324
- 48 https://github.com/coq/coq/issues/10088

3.1. Version 8.11 29

subgoal R1 (f1 i) (?f2 i) to protect it from unwanted evar instantiation, and get Under\_rel \_ R1 (f1 i) (?f2 i) that is displayed as 'Under[ f1 i ]. In Coq 8.10, this second (convenience) step was only performed when R1 was Leibniz' eq or iff. Now, it is also performed for any relation R1 which has a RewriteRelation instance (a RelationClasses.Reflexive instance being also needed so over can discharge the 'Under[ \_ ] goal by instantiating the hidden evar.) This feature generalizing support for setoid-like relations is enabled as soon as we do both Require Import ssreflect. and Require Setoid. Finally, a rewrite rule UnderE has been added if one wants to "unprotect" the evar, and instantiate it manually with another rule than reflexivity (i.e., without using the over tactic nor the over rewrite rule). See also Section Rewriting under binders (#1002249, by Erik Martin-Dorel, with suggestions and review by Enrico Tassi and Cyril Cohen).

- Added: A void notation for the standard library empty type (Empty\_set) (#10932<sup>50</sup>, by Arthur Azevedo de Amorim).
- Added: Lemma inj\_compr to ssr.ssrfun (#11136<sup>51</sup>, by Cyril Cohen).

## Commands and options

- Removed: Deprecated flag Refine Instance Mode (#9530<sup>52</sup>, fixes #3632<sup>53</sup>, #3890<sup>54</sup> and #4638<sup>55</sup> by Maxime Dénès, review by Gaëtan Gilbert).
- Changed: Fail does not catch critical errors (including "stack overflow") anymore (#10173<sup>56</sup>, by Gaëtan Gilbert).
- Removed: Undocumented Instance : ! type syntax (#10185<sup>57</sup>, by Gaëtan Gilbert).
- Removed: Deprecated Show Script command (#10277<sup>58</sup>, by Gaëtan Gilbert).
- Added: Unsafe commands to enable/disable guard checking, positivity checking and universes checking (providing a local -type-in-type). See Controlling Typing Flags (#10291<sup>59</sup> by Simon Boulier).
- **Fixed:** Two bugs in *Export*. This can have an impact on the behavior of the *Import* command on libraries. Import A when A imports B which exports C was importing C, whereas *Import* is not transitive. Also, after Import A B, the import of B was sometimes incomplete (#10476<sup>60</sup>, by Maxime Dénès).

Warning: This is a common source of incompatibilities in projects migrating to Coq 8.11.

- Changed: Output generated by *Printing Dependent Evars Line* flag used by the Prooftree tool in Proof General. (#10489<sup>61</sup>, closes #4504<sup>62</sup>, #10399<sup>63</sup> and #10400<sup>64</sup>, by Jim Fehrle).
- Added: Optionally highlight the differences between successive proof steps in the *Show Proof* command. Experimental; only available in coqtop and Proof General for now, may be supported in other

 $<sup>^{49}~\</sup>mathrm{https://github.com/coq/coq/pull/} 10022$ 

<sup>&</sup>lt;sup>50</sup> https://github.com/coq/coq/pull/10932

 $<sup>^{51}</sup>$ https://github.com/coq/coq/pull/11136

<sup>&</sup>lt;sup>52</sup> https://github.com/coq/coq/pull/9530

<sup>&</sup>lt;sup>53</sup> https://github.com/coq/coq/issues/3632

<sup>&</sup>lt;sup>54</sup> https://github.com/coq/coq/issues/3890

 $<sup>^{55}~\</sup>rm https://github.com/coq/coq/issues/4638$ 

<sup>56</sup> https://github.com/coq/coq/pull/10173

<sup>&</sup>lt;sup>57</sup> https://github.com/coq/coq/pull/10185

 $<sup>^{58}</sup>$  https://github.com/coq/coq/pull/10277

 $<sup>^{59}~\</sup>rm https://github.com/coq/coq/pull/10291$ 

<sup>60</sup> https://github.com/coq/coq/pull/10476

 $<sup>^{61}~\</sup>rm https://github.com/coq/coq/pull/10489$ 

 $<sup>^{62}</sup>$  https://github.com/coq/coq/issues/4504

<sup>63</sup> https://github.com/coq/coq/issues/10399

 $<sup>^{64}</sup>$  https://github.com/coq/coq/issues/10400

IDEs in the future. ( $\#10494^{65}$ , by Jim Fehrle).

• Removed: Legacy commands AddPath, AddRecPath, and DelPath which were undocumented, broken variants of Add LoadPath, Add Rec LoadPath, and Remove LoadPath (#11187<sup>66</sup>, by Maxime Dénès and Théo Zimmermann).

#### Tools

- Added: coqc now provides the ability to generate compiled interfaces. Use coqc -vos foo.v to skip all opaque proofs during the compilation of foo.v, and output a file called foo.vos. This feature is experimental. It enables working on a Coq file without the need to first compile the proofs contained in its dependencies (#8642<sup>67</sup> by Arthur Charguéraud, review by Maxime Dénès and Emilio Gallego).
- Added: Command-line options -require-import, -require-export, -require-import-from and -require-export-from, as well as their shorthand, -ri, -re, -refrom and -rifrom. Deprecate confusing command line option -require (#10245<sup>68</sup> by Hugo Herbelin, review by Emilio Gallego).
- Changed: Renamed VDFILE from .coqdeps.d to .<CoqMakefile>.d in the coq\_makefile utility, where <CoqMakefile> is the name of the output file given by the -o option. In this way two generated makefiles can coexist in the same directory. (#10947<sup>69</sup>, by Kazuhiko Sakaguchi).
- Fixed: coq\_makefile now supports environment variable COQBIN with no ending / character (#11068<sup>70</sup>, by Gaëtan Gilbert).

#### Standard library

- Changed: Moved the *auto* hints of the OrderedType module into a new ordered\_type database (#9772<sup>71</sup>, by Vincent Laporte).
- Removed: Deprecated modules Coq.ZArith.Zlogarithm and Coq.ZArith.Zsqrt\_compat (#9881<sup>72</sup>, by Vincent Laporte).
- Added: Module Reals.ConstructiveCauchyReals defines constructive real numbers by Cauchy sequences of rational numbers (#10445<sup>73</sup>, by Vincent Semeria, with the help and review of Guillaume Melquiond and Bas Spitters).
- Added: New module Reals.ClassicalDedekindReals defines Dedekind real numbers as boolean-valued functions along with 3 logical axioms: limited principle of omniscience, excluded middle of negations, and functional extensionality. The exposed type R in module Reals.Rdefinitions now corresponds to these Dedekind reals, hidden behind an opaque module, which significantly reduces the number of axioms needed (see Reals.Rdefinitions and Reals.Raxioms), while preserving backward compatibility. Classical Dedekind reals are a quotient of constructive reals, which allows to transport many constructive proofs to the classical case (#10827<sup>74</sup>, by Vincent Semeria, based on discussions with Guillaume Melquiond, Bas Spitters and Hugo Herbelin, code review by Hugo Herbelin).
- Added: New lemmas on combine, filter, nodup, nth, and nth\_error functions on lists (#10651<sup>75</sup>, and #10731<sup>76</sup>, by Oliver Nash).

3.1. Version 8.11 31

<sup>65</sup> https://github.com/coq/coq/pull/10494

<sup>66</sup> https://github.com/coq/coq/pull/11187

 $<sup>^{67}~\</sup>rm https://github.com/coq/coq/pull/8642$ 

<sup>68</sup> https://github.com/coq/coq/pull/10245

<sup>69</sup> https://github.com/coq/coq/pull/10947

<sup>70</sup> https://github.com/coq/coq/pull/11068

 $<sup>^{71}</sup>$  https://github.com/coq/coq/pull/9772

<sup>&</sup>lt;sup>72</sup> https://github.com/coq/coq/pull/9811

 $<sup>^{73}</sup>$  https://github.com/coq/coq/pull/10445

<sup>&</sup>lt;sup>74</sup> https://github.com/coq/coq/pull/10827

<sup>&</sup>lt;sup>75</sup> https://github.com/coq/coq/pull/10651

 $<sup>^{76}</sup>$ https://github.com/coq/coq/pull/10731

- Changed: The lemma filter app was moved to the List module (#10651<sup>77</sup>, by Oliver Nash).
- Added: Standard equivalence between weak excluded-middle and the classical instance of De Morgan's law, in module ClassicalFacts (#10895<sup>78</sup>, by Hugo Herbelin).

#### Infrastructure and dependencies

• Changed: Coq now officially supports OCaml 4.08. See INSTALL file for details (#10471<sup>79</sup>, by Emilio Jesús Gallego Arias).

## 3.1.3 Changes in 8.11.0

#### Kernel

- Changed: the native compilation (native\_compute) now creates a directory to contain temporary files instead of putting them in the root of the system temporary directory (#11081<sup>80</sup>, by Gaëtan Gilbert).
- Fixed: #11360<sup>81</sup>. Broken section closing when a template polymorphic inductive type depends on a section variable through its parameters (#11361<sup>82</sup>, by Gaëtan Gilbert).
- Fixed: The type of Set+1 would be computed to be itself, leading to a proof of False (#1142283, by Gaëtan Gilbert).

## Specification language, type inference

- Changed: Heuristics for universe minimization to Set: only minimize flexible universes (#10657<sup>84</sup>, by Gaëtan Gilbert with help from Maxime Dénès and Matthieu Sozeau).
- Fixed: A dependency was missing when looking for default clauses in the algorithm for printing pattern matching clauses (#11233<sup>85</sup>, by Hugo Herbelin, fixing #11231<sup>86</sup>, reported by Barry Jay).

#### **Notations**

- Fixed: Print Visibility was failing in the presence of only-printing notations (#1127687, by Hugo Herbelin, fixing  $\#10750^{88}$ ).
- Fixed: Recursive notations with custom entries were incorrectly parsing constr instead of custom grammars (#1131189 by Maxime Dénès, fixes  $\#9532^{90}$ ,  $\#9490^{91}$ ).

#### **Tactics**

• Changed: The tactics eapply, refine and variants no longer allow shelved goals to be solved by typeclass resolution (#10762<sup>92</sup>, by Matthieu Sozeau).

<sup>&</sup>lt;sup>77</sup> https://github.com/coq/coq/pull/10651

 $<sup>^{78}</sup>$ https://github.com/coq/coq/pull/10895

<sup>&</sup>lt;sup>79</sup> https://github.com/coq/coq/pull/10471

<sup>80</sup> https://github.com/coq/coq/pull/11081

 $<sup>^{81}</sup>$  https://github.com/issues/11360

<sup>82</sup> https://github.com/coq/coq/pull/11361

<sup>83</sup> https://github.com/coq/coq/pull/11422

 $<sup>^{84}</sup>$  https://github.com/coq/coq/pull/10657

 $<sup>^{85}</sup>$ https://github.com/coq/coq/pull/11233

<sup>86</sup> https://github.com/coq/coq/pull/11231

 $<sup>^{87}</sup>$ https://github.com/coq/coq/pull/11276

 $<sup>^{88}</sup>$  https://github.com/coq/coq/pull/10750

<sup>89</sup> https://github.com/coq/coq/pull/11311

 $<sup>^{90}</sup>$ https://github.com/coq/coq/pull/9532

<sup>91</sup> https://github.com/coq/coq/pull/9490

<sup>92</sup> https://github.com/coq/coq/pull/10762

- **Fixed:** The optional string argument to *time* is now properly quoted under *Print Ltac* (#11203<sup>93</sup>, fixes #10971<sup>94</sup>, by Jason Gross)
- **Fixed:** Efficiency regression of *lia* introduced in 8.10 by PR #9725<sup>95</sup> (#11263<sup>96</sup>, fixes #11063<sup>97</sup>, and #11242<sup>98</sup>, and #11270<sup>99</sup>, by Frédéric Besson).
- **Deprecated:** The undocumented omega with tactic variant has been deprecated. Using *lia* is the recommended replacement, though the old semantics of omega with \* can be recovered with zify; omega (#11337<sup>100</sup>, by Emilio Jesus Gallego Arias).
- **Fixed** For compatibility reasons, in 8.11, *zify* does not support Z.pow\_pos by default. It can be enabled by explicitly loading the module ZifyPow (#11430<sup>101</sup> by Frédéric Besson fixes #11191<sup>102</sup>).

#### Tactic language

• Fixed: Syntax of tactic cofix ... with ... was broken since Coq 8.10 (#11241<sup>103</sup>, by Hugo Herbelin).

## Commands and options

• **Deprecated:** The -load-ml-source and -load-ml-object command line options have been deprecated; their use was very limited, you can achieve the same by adding object files in the linking step or by using a plugin (#11428<sup>104</sup>, by Emilio Jesus Gallego Arias).

#### Tools

- Fixed: coqtop --version was broken when called in the middle of an installation process (#11255 $^{105}$ , by Hugo Herbelin, fixing #11254 $^{106}$ ).
- **Deprecated:** The -quick command is renamed to -vio, for consistency with the new -vos and -vok flags. Usage of -quick is now deprecated (#11280<sup>107</sup>, by Arthur Charguéraud).
- Fixed: coq\_makefile does not break when using the CAMLPKGS variable together with an unpacked (mllib) plugin (#11357<sup>108</sup>, by Gaëtan Gilbert).
- Fixed: coqdoc with option -g (Gallina only) now correctly prints commands with attributes  $(\#11394^{109}, \text{ fixes } \#11353^{110}, \text{ by Karl Palmskog}).$

#### CoqIDE

• Changed: CoqIDE now uses the GtkSourceView native implementation of the autocomplete mechanism (#11400<sup>111</sup>, by Pierre-Marie Pédrot).

## Standard library

93 https://github.com/coq/coq/pull/11203 94 https://github.com/coq/coq/issues/10971  $^{95}$  https://github.com/coq/coq/pull/9725 96 https://github.com/coq/coq/pull/11263 97 https://github.com/coq/coq/issues/11063 98 https://github.com/coq/coq/issues/11242 99 https://github.com/coq/coq/issues/11270 100 https://github.com/coq/coq/pull/11337  $^{101}$  https://github.com/coq/coq/pull/11430  $^{102}$  https://github.com/coq/coq/issues/11191  $^{103}~\rm https://github.com/coq/coq/pull/11241$ 104 https://github.com/coq/coq/pull/11428  $^{105}~\mathrm{https://github.com/coq/coq/pull/11255}$ 106 https://github.com/coq/coq/pull/11254 107 https://github.com/coq/coq/pull/11280  $^{108}$ https://github.com/coq/coq/pull/11357 109 https://github.com/coq/coq/pull/11394 110 https://github.com/coq/coq/issues/11353 111 https://github.com/coq/coq/pull/11400

3.1. Version 8.11 33

• Removed: Export of module RList in Ranalysis and Ranalysis\_reg. Module RList is still there but must be imported explicitly where required (#11396<sup>112</sup>, by Michael Soegtrop).

## Infrastructure and dependencies

• Added: Build date can now be overridden by setting the SOURCE\_DATE\_EPOCH environment variable (#11227<sup>113</sup>, by Bernhard M. Wiedemann).

# 3.1.4 Changes in 8.11.1

## Kernel

• Fixed: Allow more inductive types in Unset Positivity Checking mode (#11811<sup>114</sup>, by Simon-Boulier).

## Notations

- **Fixed:** Bugs in dealing with precedences of notations in custom entries (#11530<sup>115</sup>, by Hugo Herbelin, fixing in particular #9517<sup>116</sup>, #9519<sup>117</sup>, #9521<sup>118</sup>, #11331<sup>119</sup>).
- Added: In primitive floats, print a warning when parsing a decimal value that is not exactly a binary64 floating-point number. For instance, parsing 0.1 will print a warning whereas parsing 0.5 won't. (#11859<sup>120</sup>, by Pierre Roux).

# CoqIDE

• Fixed: Compiling file paths containing spaces (#10008<sup>121</sup>, by snyke7, fixing #11595<sup>122</sup>).

## Infrastructure and dependencies

• Added: Bump official OCaml support and CI testing to 4.10.0 (#11131<sup>123</sup>, #11123<sup>124</sup>, #11102<sup>125</sup>, by Emilio Jesus Gallego Arias, Jacques-Henri Jourdan, Guillaume Melquiond, and Guillaume Munch-Maccagnoni).

## Miscellaneous

• **Fixed:** Extraction Implicit on the constructor of a record was leading to an anomaly (#11329<sup>126</sup>, by Hugo Herbelin, fixes #11114<sup>127</sup>).

# 3.1.5 Changes in 8.11.2

#### Kernel

```
112 https://github.com/coq/coq/pull/11396
113 https://github.com/coq/coq/pull/11227
114 https://github.com/coq/coq/pull/11811
115 https://github.com/coq/coq/pull/11530
116 https://github.com/coq/coq/pull/9517
117 https://github.com/coq/coq/pull/9519
118 https://github.com/coq/coq/pull/9521
119 https://github.com/coq/coq/pull/11331
120 https://github.com/coq/coq/pull/11859
^{121} https://github.com/coq/coq/pull/10008
122 https://github.com/coq/coq/pull/11595
123 https://github.com/coq/coq/pull/11131
^{124}~\rm{https://github.com/coq/coq/pull/11123}
125 https://github.com/coq/coq/pull/11123
126 https://github.com/coq/coq/pull/11329
127 https://github.com/coq/coq/pull/11114
```

• **Fixed:** Using *Require* inside a section caused an anomaly when closing the section. (#11972<sup>128</sup>, by Gaëtan Gilbert, fixing #11783<sup>129</sup>, reported by Attila Boros).

#### **Tactics**

- **Fixed:** Anomaly with induction schemes whose conclusion is not normalized (#12116<sup>130</sup>, by Hugo Herbelin; fixes  $#12045^{131}$ )
- **Fixed:** Loss of location of some tactic errors (#12223<sup>132</sup>, by Hugo Herbelin; fixes #12152<sup>133</sup> and #12255<sup>134</sup>).

# Commands and options

• Changed: Ignore -native-compiler option when built without native compute support. (#12070<sup>135</sup>, by Pierre Roux).

## CoqIDE

- **Changed:** CoqIDE now uses native window frames by default on Windows. The GTK window frames can be restored by setting the GTK\_CSD environment variable to 1 (#12060<sup>136</sup>, fixes #11080<sup>137</sup>, by Attila Gáspár).
- **Fixed:** New patch presumably fixing the random Coq 8.11 segfault issue with CoqIDE completion (#12068<sup>138</sup>, by Hugo Herbelin, presumably fixing #11943<sup>139</sup>).
- **Fixed:** Highlighting style consistently applied to all three buffers of CoqIDE (#12106<sup>140</sup>, by Hugo Herbelin; fixes #11506<sup>141</sup>).

# 3.2 Version 8.10

# 3.2.1 Summary of changes

Coq version 8.10 contains two major new features: support for a native fixed-precision integer type and a new sort SProp of strict propositions. It is also the result of refinements and stabilization of previous features, deprecations or removals of deprecated features, cleanups of the internals of the system and API, and many documentation improvements. This release includes many user-visible changes, including deprecations that are documented in the next subsection, and new features that are documented in the reference manual. Here are the most important user-visible changes:

- Kernel:
  - A notion of primitive object was added to the calculus. Its first instance is primitive cyclic unsigned integers, axiomatized in module UInt63. See Section *Primitive Integers*. The Coq. Numbers.Cyclic.Int31 library is deprecated (#6914<sup>142</sup>, by Maxime Dénès, Benjamin Grégoire and Vincent Laporte, with help and reviews from many others).

 128
 https://github.com/coq/coq/pull/11972

 129
 https://github.com/coq/coq/issues/11783

 130
 https://github.com/coq/coq/pull/12116

 131
 https://github.com/coq/coq/pull/12045

 132
 https://github.com/coq/coq/pull/12223

 133
 https://github.com/coq/coq/pull/12152

 134
 https://github.com/coq/coq/pull/12070

 136
 https://github.com/coq/coq/pull/12060

 137
 https://github.com/coq/coq/jull/12068

 138
 https://github.com/coq/coq/pull/11943

 140
 https://github.com/coq/coq/pull/12106

 141
 https://github.com/coq/coq/pull/1506

 142
 https://github.com/coq/coq/pull/1506

 143
 https://github.com/coq/coq/pull/1506

 144
 https://github.com/coq/coq/pull/1506

 145
 https://github.com/coq/coq/pull/1506

3.2. Version 8.10 35

- The SProp sort of definitionally proof-irrelevant propositions was introduced. SProp allows to mark proof terms as irrelevant for conversion, and is treated like Prop during extraction. It is enabled using the -allow-sprop command-line flag or the Allow StrictProp flag. See Chapter SProp (proof irrelevant propositions) (#8817<sup>143</sup>, by Gaëtan Gilbert).
- The unfolding heuristic in termination checking was made more complete, allowing more constants to be unfolded to discover valid recursive calls. Performance regression may occur in Fixpoint declarations without an explicit {struct} annotation, since guessing the decreasing argument can now be more expensive (#9602<sup>144</sup>, by Enrico Tassi).

### • Universes:

- Added Print Universes Subgraph variant of Print Universes. Try for instance Print Universes Subgraph(sigT2.u1 sigT\_of\_sigT2.u1 projT3\_eq.u1). (#8451<sup>145</sup>, by Gaëtan Gilbert).
- Added private universes for opaque polymorphic constants, see the documentation for the Private
  Polymorphic Universes flag, and unset it to get the previous behaviour (#8850<sup>146</sup>, by Gaëtan
  Gilbert).

#### • Notations:

- New command String Notation to register string syntax for custom inductive types (#8965<sup>147</sup>, by Jason Gross).
- Experimental: *Numeral Notations* now parse decimal constants such as 1.02e+01 or 10.2. Parsers added for Q and R. In the rare case when such numeral notations were used in a development along with Q or R, they may have to be removed or disambiguated through explicit scope annotations (#8764<sup>148</sup>, by Pierre Roux).
- Ltac backtraces can be turned on using the *Ltac Backtrace* flag, which is off by default (#9142<sup>149</sup>, fixes #7769<sup>150</sup> and #7385<sup>151</sup>, by Pierre-Marie Pédrot).
- The tactics lia, nia, lra, nra are now using a novel Simplex-based proof engine. In case of regression, unset Simplex to get the venerable Fourier-based engine (#8457<sup>152</sup>, by Fréderic Besson).
- SSReflect:
  - New intro patterns:
    - \* temporary introduction: => +
    - \* block introduction: => [^ prefix ] [^~ suffix ]
    - \* fast introduction:  $\Rightarrow$
    - \* tactics as views: => /ltac:mytac
    - \* replace hypothesis: => {}H

See Section Introduction in the context ( $\#6705^{153}$ , by Enrico Tassi, with help from Maxime Dénès, ideas coming from various users).

```
143 https://github.com/coq/coq/pull/8817
144 https://github.com/coq/coq/pull/9602
145 https://github.com/coq/coq/pull/8451
146 https://github.com/coq/coq/pull/8850
147 https://github.com/coq/coq/pull/8965
148 https://github.com/coq/coq/pull/8764
149 https://github.com/coq/coq/pull/9142
150 https://github.com/coq/coq/issues/7769
151 https://github.com/coq/coq/issues/7385
152 https://github.com/coq/coq/pull/8457
```

153 https://github.com/coq/coq/pull/6705

- New tactic *under* to rewrite under binders, given an extensionality lemma:
  - \* interactive mode: under term, associated terminator: over
  - \* one-liner mode: under term do [tactic | ...]

It can take occurrence switches, contextual patterns, and intro patterns: under {2}[in RHS]eq\_big => [i|i ?] (#9651<sup>154</sup>, by Erik Martin-Dorel and Enrico Tassi).

- Combined Scheme now works when inductive schemes are generated in sort Type. It used to be limited to sort Prop (#7634<sup>155</sup>, by Théo Winterhalter).
- A new registration mechanism for reference from ML code to Coq constructs has been added (#186<sup>156</sup>, by Emilio Jesús Gallego Arias, Maxime Dénès and Vincent Laporte).
- CoqIDE:
  - CoqIDE now depends on gtk+3 and lablgtk3 instead of gtk+2 and lablgtk2. The INSTALL file available in the Coq sources has been updated to list the new dependencies (#9279<sup>157</sup>, by Hugo Herbelin, with help from Jacques Garrigue, Emilio Jesús Gallego Arias, Michael Sogetrop and Vincent Laporte).
  - Smart input for Unicode characters. For example, typing \alpha then Shift+Space will insert the greek letter alpha. A larger number of default bindings are provided, following the latex naming convention. Bindings can be customized, either globally, or on a per-project basis. See Section Bindings for input of Unicode symbols for details (#8560<sup>158</sup>, by Arthur Charguéraud).
- Infrastructure and dependencies:
  - Coq 8.10 requires OCaml >= 4.05.0, bumped from 4.02.3 See the INSTALL file for more information on dependencies (# $7522^{159}$ , by Emilio Jesús Gallego Arías).
  - Coq 8.10 doesn't need Camlp5 to build anymore. It now includes a fork of the core parsing library that Coq uses, which is a small subset of the whole Camlp5 distribution. In particular, this subset doesn't depend on the OCaml AST, allowing easier compilation and testing on experimental OCaml versions. Coq also ships a new parser coqpp that plugin authors must switch to (#7902<sup>160</sup>, #7979<sup>161</sup>, #8161<sup>162</sup>, #8667<sup>163</sup>, and #8945<sup>164</sup>, by Pierre-Marie Pédrot and Emilio Jesús Gallego Arias).

The Coq developers would like to thank Daniel de Rauglaudre for many years of continued support.

- Coq now supports building with Dune, in addition to the traditional Makefile which is scheduled for deprecation ( $\#6857^{165}$ , by Emilio Jesús Gallego Arias, with help from Rudi Grinberg).

Experimental support for building Coq projects has been integrated in Dune at the same time, providing an improved experience<sup>166</sup> for plugin developers. We thank the Dune team for their work supporting Coq.

```
https://github.com/coq/coq/pull/9651
https://github.com/coq/coq/pull/7634
https://github.com/coq/coq/pull/186
https://github.com/coq/coq/pull/9279
https://github.com/coq/coq/pull/8560
https://github.com/coq/coq/pull/7522
https://github.com/coq/coq/pull/7902
https://github.com/coq/coq/pull/7979
https://github.com/coq/coq/pull/8161
https://github.com/coq/coq/pull/8667
https://github.com/coq/coq/pull/8945
https://github.com/coq/coq/pull/6857
https://coq.discourse.group/t/a-guide-to-building-your-coq-libraries-and-plugins-with-dune/
```

3.2. Version 8.10 37

Version 8.10 also comes with a bunch of smaller-scale changes and improvements regarding the different components of the system, including many additions to the standard library (see the next subsection for details).

On the implementation side, the dev/doc/changes.md file documents the numerous changes to the implementation and improvements of interfaces. The file provides guidelines on porting a plugin to the new version and a plugin development tutorial originally made by Yves Bertot is now in doc/plugin\_tutorial. The dev/doc/critical-bugs file documents the known critical bugs of Coq and affected releases.

The efficiency of the whole system has seen improvements thanks to contributions from Gaëtan Gilbert, Pierre-Marie Pédrot, and Maxime Dénès.

Maxime Dénès, Emilio Jesús Gallego Arias, Gaëtan Gilbert, Michael Soegtrop, Théo Zimmermann worked on maintaining and improving the continuous integration system and package building infrastructure. Coq is now continuously tested against OCaml trunk, in addition to the oldest supported and latest OCaml releases.

Coq's documentation for the development branch is now deployed continuously at https://coq.github.io/doc/master/api (documentation of the ML API), https://coq.github.io/doc/master/refman (reference manual), and https://coq.github.io/doc/master/stdlib (documentation of the standard library). Similar links exist for the v8.10 branch.

The OPAM repository for Coq packages has been maintained by Guillaume Melquiond, Matthieu Sozeau, Enrico Tassi (who migrated it to opam 2) with contributions from many users. A list of packages is available at https://coq.inria.fr/opam/www/.

The 61 contributors to this version are Tanaka Akira, Benjamin Barenblat, Yves Bertot, Frédéric Besson, Lasse Blaauwbroek, Martin Bodin, Joachim Breitner, Tej Chajed, Frédéric Chapoton, Arthur Charguéraud, Cyril Cohen, Lukasz Czajka, David A. Dalrymple, Christian Doczkal, Maxime Dénès, Andres Erbsen, Jim Fehrle, Emilio Jesus Gallego Arias, Gaëtan Gilbert, Matěj Grabovský, Simon Gregersen, Jason Gross, Samuel Gruetter, Hugo Herbelin, Jasper Hugunin, Mirai Ikebuchi, Chantal Keller, Matej Košík, Sam Pablo Kuper, Vincent Laporte, Olivier Laurent, Larry Darryl Lee Jr, Nick Lewycky, Yao Li, Yishuai Li, Assia Mahboubi, Simon Marechal, Erik Martin-Dorel, Thierry Martinez, Guillaume Melquiond, Kayla Ngan, Karl Palmskog, Pierre-Marie Pédrot, Clément Pit-Claudel, Pierre Roux, Kazuhiko Sakaguchi, Ryan Scott, Vincent Semeria, Gan Shen, Michael Soegtrop, Matthieu Sozeau, Enrico Tassi, Laurent Théry, Kamil Trzciński, whitequark, Théo Winterhalter, Xia Li-yao, Beta Ziliani and Théo Zimmermann.

Many power users helped to improve the design of the new features via the issue and pull request system, the Coq development mailing list, the coq-club@inria.fr mailing list or the new Discourse forum. It would be impossible to mention exhaustively the names of everybody who to some extent influenced the development.

Version 8.10 is the fifth release of Coq developed on a time-based development cycle. Its development spanned 6 months from the release of Coq 8.9. Vincent Laporte is the release manager and maintainer of this release. This release is the result of  $\sim$ 2500 commits and  $\sim$ 650 PRs merged, closing 150+ issues.

Santiago de Chile, April 2019, Matthieu Sozeau for the Coq development team

# 3.2.2 Other changes in 8.10+beta1

- Command-line tools and options:
  - The use of coqtop as a compiler has been deprecated, in favor of coqc. Consequently option -compile will stop to be accepted in the next release. coqtop is now reserved to interactive use

 $(#9095^{167}, \text{ by Emilio Jesús Gallego Arias}).$ 

- New option -topfile filename, which will set the current module name (à la -top) based on the filename passed, taking into account the proper -R/-Q options. For example, given -R Foo foolib using -topfile foolib/bar.v will set the module name to Foo.Bar. CoqIDE now properly sets the module name for a given file based on its path (#8991<sup>168</sup>, closes #8989<sup>169</sup>, by Gaëtan Gilbert).
- Experimental: Coq flags and options can now be set on the command-line, e.g. -set "Universe Polymorphism=true" ( $\#9876^{170}$ , by Gaëtan Gilbert).
- The -native-compiler flag of coqc and coqtop now takes an argument which can have three values:
  - \* no disables native\_compute
  - \* yes enables native compute and precompiles .v files to native code
  - \* ondemand enables native\_compute but compiles code only when native\_compute is called

The default value is ondemand. Note that this flag now has priority over the configure flag of the same name

A new -bytecode-compiler flag for coqc and coqtop controls whether conversion can use the VM. The default value is yes.

```
(\#8870^{171}, \text{ by Maxime Dénès})
```

- The pretty timing diff scripts (flag TIMING=1 to a coq\_makefile-made Makefile, also tools/make-both-single-timing-files.py, tools/make-both-time-files.py, and tools/make-one-time-file.py) now correctly support non-UTF-8 characters in the output of coqc / make as well as printing to stdout, on both python2 and python3 (#9872<sup>172</sup>, closes #9767<sup>173</sup> and #9705<sup>174</sup>, by Jason Gross)
- coq\_makefile's install target now errors if any file to install is missing (#9906<sup>175</sup>, by Gaëtan Gilbert).
- Preferences from coqide.keys are no longer overridden by modifiers preferences in coqiderc (#10014<sup>176</sup>, by Hugo Herbelin).
- Specification language, type inference:
  - Fixing a missing check in interpreting instances of existential variables that are bound to local definitions. Might exceptionally induce an overhead if the cost of checking the conversion of the corresponding definitions is additionally high ( $\#8217^{177}$ , closes  $\#8215^{178}$ , by Hugo Herbelin).
  - A few improvements in inference of the return clause of match that can exceptionally introduce incompatibilities. This can be solved by writing an explicit return clause, sometimes even simply an explicit return \_ clause (#262<sup>179</sup>, by Hugo Herbelin).

```
https://github.com/coq/coq/pull/9095
https://github.com/coq/coq/pull/8991
https://github.com/coq/coq/issues/8989
https://github.com/coq/coq/pull/9876
https://github.com/coq/coq/pull/8870
https://github.com/coq/coq/pull/9872
https://github.com/coq/coq/issues/9767
https://github.com/coq/coq/issues/9765
https://github.com/coq/coq/pull/9906
https://github.com/coq/coq/pull/10014
https://github.com/coq/coq/pull/8217
https://github.com/coq/coq/issues/8215
https://github.com/coq/coq/pull/262
```

3.2. Version 8.10

- Using non-projection values with the projection syntax is not allowed. For instance 0.(S) is not a valid way to write S 0. Projections from non-primitive (emulated) records are allowed with warning "nonprimitive-projection-syntax" (#8829<sup>180</sup>, by Gaëtan Gilbert).
- An option and attributes to control the automatic decision to declare an inductive type as template polymorphic were added. Warning "auto-template" (off by default) can trigger when an inductive is automatically declared template polymorphic without the attribute.

Inductive types declared by Funind will never be template polymorphic.

```
(\#8488^{181}, \text{ by Gaëtan Gilbert})
```

### • Notations:

- New command *Declare Scope* to explicitly declare a scope name before any use of it. Implicit declaration of a scope at the time of *Bind Scope*, *Delimit Scope*, *Undelimit Scope*, or *Notation* is deprecated (#7135<sup>182</sup>, by Hugo Herbelin).
- Various bugs have been fixed (e.g. #9214<sup>183</sup> on removing spurious parentheses on abbreviations shortening a strict prefix of an application, by Hugo Herbelin).
- Numeral Notation now support inductive types in the input to printing functions (e.g., numeral notations can be defined for terms containing things like @cons nat 0 0), and parsing functions now fully normalize terms including parameters of constructors (so that, e.g., a numeral notation whose parsing function outputs a proof of Nat.gcd x y = 1 will no longer fail to parse due to containing the constant Nat.gcd in the parameter-argument of eq\_refl) (#9874<sup>184</sup>, closes #9840<sup>185</sup> and #9844<sup>186</sup>, by Jason Gross).
- Deprecated compatibility notations have actually been removed. Uses of these notations are generally easy to fix thanks to the hint contained in the deprecation warning emitted by Coq 8.8 and 8.9. For projects that require more than a handful of such fixes, there is a script<sup>187</sup> that will do it automatically, using the output of coqc (#8638<sup>188</sup>, by Jason Gross).
- Allow inspecting custom grammar entries by *Print Custom Grammar* (#10061<sup>189</sup>, fixes #9681<sup>190</sup>, by Jasper Hugunin, review by Pierre-Marie Pédrot and Hugo Herbelin).
- The quote plugin<sup>191</sup> was removed. If some users are interested in maintaining this plugin externally, the Coq development team can provide assistance for extracting the plugin and setting up a new repository (#7894<sup>192</sup>, by Maxime Dénès).

## • Ltac:

- Tactic names are no longer allowed to clash, even if they are not defined in the same section. For example, the following is no longer accepted: Ltac foo := idtac. Section S. Ltac foo := fail. End S. (#8555<sup>193</sup>, by Maxime Dénès).
- Names of existential variables occurring in Ltac functions (e.g. ?[n] or ?n in terms not in patterns) are now interpreted the same way as other variable names occurring in Ltac functions

```
180 https://github.com/coq/coq/pull/8829
181 https://github.com/coq/coq/pull/8488
182 https://github.com/coq/coq/pull/7135
183 https://github.com/coq/coq/pull/9214
184 https://github.com/coq/coq/pull/9840
185 https://github.com/coq/coq/issues/9840
186 https://github.com/coq/coq/issues/9844
187 https://gist.github.com/JasonGross/9770653967de3679d131c59d42de6d17#file-replace-notations-py
188 https://github.com/coq/coq/pull/8638
189 https://github.com/coq/coq/pull/10061
190 http://github.com/coq/coq/pull/9681
191 https://coq.inria.fr/distrib/V8.9.0/refman/proof-engine/detailed-tactic-examples.html#quote
192 https://github.com/coq/coq/pull/7894
193 https://github.com/coq/coq/pull/8555
```

```
(\#7309^{194}, \text{ by Hugo Herbelin}).
```

## • Tactics:

- Removed the deprecated romega tactic (#8419<sup>195</sup>, by Maxime Dénès and Vincent Laporte).
- Hint declaration and removal should now specify a database (e.g. Hint Resolve foo: database). When the database name is omitted, the hint is added to the core database (as previously), but a deprecation warning is emitted (#8987<sup>196</sup>, by Maxime Dénès).
- There are now tactics in PreOmega.v called Z.div\_mod\_to\_equations, Z.quot\_rem\_to\_equations, and Z.to\_euclidean\_division\_equations (which combines the div\_mod and quot\_rem variants) which allow *lia*, *nia*, etc to support Z.div and Z.modulo (Z.quot and Z.rem, respectively), by posing the specifying equation for Z.div and Z.modulo before replacing them with atoms (#8062<sup>197</sup>, by Jason Gross).
- The syntax of the *autoapply* tactic was fixed to conform with preexisting documentation: it now takes a with clause instead of a using clause (#9524<sup>198</sup>, closes #7632<sup>199</sup>, by Théo Zimmermann).
- Modes are now taken into account by typeclasses eauto for local hypotheses (#9996<sup>200</sup>, fixes #5752<sup>201</sup>, by Maxime Dénès, review by Pierre-Marie Pédrot).
- New variant <code>change\_no\_check</code> of <code>change</code>, usable as a documented replacement of <code>convert\_concl\_no\_check</code> (#10012<sup>202</sup>, #10017<sup>203</sup>, #10053<sup>204</sup>, and #10059<sup>205</sup>, by Hugo Herbelin and Paolo G. Giarrusso).
- The simplified value returned by field\_simplify is not always a fraction anymore. When the denominator is 1, it returns x while previously it was returning x/1. This change could break codes that were post-processing application of field\_simplify to get rid of these x/1 (#9854<sup>206</sup>, by Laurent Théry, with help from Michael Soegtrop, Maxime Dénès, and Vincent Laporte).

### • SSReflect:

- Clear discipline made consistent across the entire proof language. Whenever a clear switch {x..} comes immediately before an existing proof context entry (used as a view, as a rewrite rule or as name for a new context entry) then such entry is cleared too.

E.g. The following sentences are elaborated as follows (when H is an existing proof context entry):

```
* => {x..} H-> => {x..H} H

* => {x..} /H-> => /v {x..H}

* rewrite {x..} H-> rewrite E {x..H}
(#9341<sup>207</sup>, by Enrico Tassi).
```

- inE now expands y in r x when r is a simpl\_rel. New {pred T} notation for a pred T alias in the pred\_sort coercion class, simplified predType interface: pred\_class and mkPredType deprecated, {pred T} and PredType should be used instead. if c return t then ... now

```
https://github.com/coq/coq/pull/7309
https://github.com/coq/coq/pull/8419
https://github.com/coq/coq/pull/8987
https://github.com/coq/coq/pull/8062
https://github.com/coq/coq/pull/9524
https://github.com/coq/coq/susues/7632
https://github.com/coq/coq/pull/9996
https://github.com/coq/coq/pull/9996
https://github.com/coq/coq/pull/10012
https://github.com/coq/coq/pull/10017
https://github.com/coq/coq/pull/10053
https://github.com/coq/coq/pull/10059
https://github.com/coq/coq/pull/9854
https://github.com/coq/coq/pull/9341
```

3.2. Version 8.10 41

expects c to be a variable bound in t. New nonPropType interface matching types that do \_not\_ have sort Prop. New relpre R f definition for the preimage of a relation R under f (#9995<sup>208</sup>, by Georges Gonthier).

### • Vernacular commands:

- Binders for an *Instance* now act more like binders for a *Theorem*. Names may not be repeated, and may not overlap with section variable names (#8820<sup>209</sup>, closes #8791<sup>210</sup>, by Jasper Hugunin).
- Removed the deprecated Implicit Tactic family of commands (#8779<sup>211</sup>, by Pierre-Marie Pédrot).
- The Automatic Introduction option has been removed and is now the default (#9001<sup>212</sup>, by Emilio Jesús Gallego Arias).
- Arguments now accepts names for arguments provided with extra\_scopes (#9117<sup>213</sup>, by Maxime Dénès).
- The naming scheme for anonymous binders in a **Theorem** has changed to avoid conflicts with explicitly named binders ( $\#9160^{214}$ , closes  $\#8819^{215}$ , by Jasper Hugunin).
- Computation of implicit arguments now properly handles local definitions in the binders for an Instance, and can be mixed with implicit binders {x : T} (#9307<sup>216</sup>, closes #9300<sup>217</sup>, by Jasper Hugunin).
- Declare Instance now requires an instance name.

The flag Refine Instance Mode has been turned off by default, meaning that *Instance* no longer opens a proof when a body is provided. The flag has been deprecated and will be removed in the next version.

```
(#9270^{218}, \text{ and } #9825^{219}, \text{ by Maxime Dénès})
```

- Command *Instance*, when no body is provided, now always opens a proof. This is a breaking change, as instance of Instance  $ident_1: ident_2$ . where  $ident_2$  is a trivial class will have to be changed into Instance  $ident_1: ident_2:=\{\}$ . or Instance  $ident_1: ident_2$ . Proof. Qed. (#9274<sup>220</sup>, by Maxime Dénès).
- The flag Program Mode now means that the Program attribute is enabled for all commands that support it. In particular, it does not have any effect on tactics anymore. May cause some incompatibilities (#9410<sup>221</sup>, by Maxime Dénès).
- The algorithm computing implicit arguments now behaves uniformly for primitive projection and application nodes ( $\#9509^{222}$ , closes  $\#9508^{223}$ , by Pierre-Marie Pédrot).

```
208 https://github.com/coq/coq/pull/9995
209 https://github.com/coq/coq/pull/8820
210 https://github.com/coq/coq/issues/8791
211 https://github.com/coq/coq/pull/8779
212 https://github.com/coq/coq/pull/9001
213 https://github.com/coq/coq/pull/9117
214 https://github.com/coq/coq/pull/9160
215 https://github.com/coq/coq/jull/9307
216 https://github.com/coq/coq/pull/9307
217 https://github.com/coq/coq/jull/9307
218 https://github.com/coq/coq/jull/9270
219 https://github.com/coq/coq/pull/9270
210 https://github.com/coq/coq/pull/9274
221 https://github.com/coq/coq/pull/9410
222 https://github.com/coq/coq/pull/9509
```

223 https://github.com/coq/coq/issues/9508

- Hypotheses and Variables can now take implicit binders inside sections (#9364<sup>224</sup>, closes #9363<sup>225</sup>, by Jasper Hugunin).
- Removed deprecated option Automatic Coercions Import (#8094<sup>226</sup>, by Maxime Dénès).
- The Show Script command has been deprecated (#9829<sup>227</sup>, by Vincent Laporte).
- Coercion does not warn ambiguous paths which are obviously convertible with existing ones. The ambiguous paths messages have been turned to warnings, thus now they could appear in the output of coqc. The convertibility checking procedure for coercion paths is complete for paths consisting of coercions satisfying the uniform inheritance condition, but some coercion paths could be reported as ambiguous even if they are convertible with existing ones when they have coercions that don't satisfy the uniform inheritance condition (#9743<sup>228</sup>, closes #3219<sup>229</sup>, by Kazuhiko Sakaguchi).
- A new flag Fast Name Printing has been introduced. It changes the algorithm used for allocating bound variable names for a faster but less clever one (#9078<sup>230</sup>, by Pierre-Marie Pédrot).
- Option Typeclasses Axioms Are Instances (compatibility option introduced in the previous version) is deprecated. Use *Declare Instance* for axioms which should be instances (#8920<sup>231</sup>, by Gaëtan Gilbert).
- Removed option Printing Primitive Projection Compatibility (#9306<sup>232</sup>, by Gaëtan Gilbert).

## • Standard Library:

- Added Bvector.BVeq that decides whether two Bvectors are equal. Added notations for BVxor, BVand, BVor, BVeq and BVneg (#8171<sup>233</sup>, by Yishuai Li).
- Added ByteVector type that can convert to and from string (#8365<sup>234</sup>, by Yishuai Li).
- Added lemmas about monotonicity of N.double and N.succ\_double, and about the upper bound of number represented by a vector. Allowed implicit vector length argument in Ndigits.Bv2N (#8815<sup>235</sup>, by Yishuai Li).
- The prelude used to be automatically Exported and is now only Imported. This should be relevant only when importing files which don't use -noinit into files which do (#9013<sup>236</sup>, by Gaëtan Gilbert).
- Added Coq.Structures.OrderedTypeEx.String\_as\_OT to make strings an ordered type, using lexical order ( $\#7221^{237}$ , by Li Yao).
- Added lemmas about Z.testbit, Z.ones, and Z.modulo (#9425<sup>238</sup>, by Andres Erbsen).
- Moved the auto hints of the FSet library into a new fset database (#9725<sup>239</sup>, by Frédéric Besson).

 $^{224}$ https://github.com/coq/coq/pull/9364 <sup>225</sup> https://github.com/coq/coq/issues/9363 <sup>226</sup> https://github.com/coq/coq/pull/8094  $^{227}$ https://github.com/coq/coq/pull/9829  $^{228}$ https://github.com/coq/coq/pull/9743 <sup>229</sup> https://github.com/coq/coq/issues/3219 <sup>230</sup> https://github.com/coq/coq/pull/9078 <sup>231</sup> https://github.com/coq/coq/pull/8920 <sup>232</sup> https://github.com/coq/coq/pull/9306  $^{233}$  https://github.com/coq/coq/pull/8171 <sup>234</sup> https://github.com/coq/coq/pull/8365 <sup>235</sup> https://github.com/coq/coq/pull/8815 <sup>236</sup> https://github.com/coq/coq/pull/9013 <sup>237</sup> https://github.com/coq/coq/pull/7221 <sup>238</sup> https://github.com/coq/coq/pull/9425 <sup>239</sup> https://github.com/coq/coq/pull/9725

3.2. Version 8.10 43

- Added Coq.Structures.EqualitiesFacts.PairUsualDecidableTypeFull (#9984<sup>240</sup>, by Jean-Christophe Léchenet and Oliver Nash).
- Some error messages that show problems with a pair of non-matching values will now highlight the differences (#8669<sup>241</sup>, by Jim Fehrle).
- Changelog has been moved from a specific file CHANGES.md to the reference manual; former Credits chapter of the reference manual has been split in two parts: a History chapter which was enriched with additional historical information about Coq versions 1 to 5, and a Changes chapter which was enriched with the content formerly in CHANGES.md and COMPATIBILITY (#9133<sup>242</sup>, #9668<sup>243</sup>, #9939<sup>244</sup>, #9964<sup>245</sup>, and #10085<sup>246</sup>, by Théo Zimmermann, with help and ideas from Emilio Jesús Gallego Arias, Gaëtan Gilbert, Clément Pit-Claudel, Matthieu Sozeau, and Enrico Tassi).

# 3.2.3 Changes in 8.10+beta2

Many bug fixes and documentation improvements, in particular:

### **Tactics**

• Make the discriminate tactic work together with Universe Polymorphism and equality in Type. This, in particular, makes discriminate compatible with the HoTT library https://github.com/HoTT/HoTT (#10205<sup>247</sup>, by Andreas Lynge, review by Pierre-Marie Pédrot and Matthieu Sozeau).

## **SSReflect**

- Make the case E: t tactic work together with *Universe Polymorphism* and equality in Type. This makes case compatible with the HoTT library https://github.com/HoTT/HoTT (#10302<sup>248</sup>, fixes #10301<sup>249</sup>, by Andreas Lynge, review by Enrico Tassi)
- Make the rewrite /t tactic work together with *Universe Polymorphism*. This makes rewrite compatible with the HoTT library https://github.com/HoTT/HoTT (#10305<sup>250</sup>, fixes #9336<sup>251</sup>, by Andreas Lynge, review by Enrico Tassi)

## CoqIDE

• Fix CoqIDE instability on Windows after the update to gtk3 (#10360<sup>252</sup>, by Michael Soegtrop, closes #9885<sup>253</sup>).

### Miscellaneous

• Proof General can now display Coq-generated diffs between proof steps in color (# $10019^{254}$  and (in Proof General) # $421^{255}$ , by Jim Fehrle).

```
<sup>240</sup> https://github.com/coq/coq/pull/9984
<sup>241</sup> https://github.com/coq/coq/pull/8669
242 https://github.com/coq/coq/pull/9133
^{243}https://github.com/coq/coq/pull/9668
<sup>244</sup> https://github.com/coq/coq/pull/9939
<sup>245</sup> https://github.com/coq/coq/pull/9964
^{246} https://github.com/coq/coq/pull/10085
^{247} https://github.com/coq/coq/pull/10205
<sup>248</sup> https://github.com/coq/coq/pull/10302
<sup>249</sup> https://github.com/coq/coq/issues/10301
^{250} https://github.com/coq/coq/pull/10305
<sup>251</sup> https://github.com/coq/coq/issues/9336
<sup>252</sup> https://github.com/coq/coq/pull/10360
^{253} https://github.com/coq/coq/issues/9885
<sup>254</sup> https://github.com/coq/coq/pull/10019
<sup>255</sup> https://github.com/ProofGeneral/PG/pull/421
```

# 3.2.4 Changes in 8.10+beta3

#### Kernel

• Fix soundness issue with template polymorphism ( $\#9294^{256}$ ).

Declarations of template-polymorphic inductive types ignored the provenance of the universes they were abstracting on and did not detect if they should be greater or equal to Set in general. Previous universes and universes introduced by the inductive definition could have constraints that prevented their instantiation with e.g. Prop, resulting in unsound instantiations later. The implemented fix only allows abstraction over universes introduced by the inductive declaration, and properly records all their constraints by making them by default only >= Prop. It is also checked that a template polymorphic inductive actually is polymorphic on at least one universe.

This prevents inductive declarations in sections to be universe polymorphic over section parameters. For a backward compatible fix, simply hoist the inductive definition out of the section. An alternative is to declare the inductive as universe-polymorphic and cumulative in a universe-polymorphic section: all universes and constraints will be properly gathered in this case. See *Template polymorphism* for a detailed exposition of the rules governing template-polymorphic types.

To help users incrementally fix this issue, a command line option -no-template-check and a global flag *Template Check* are available to selectively disable the new check. Use at your own risk.

(#9918<sup>257</sup>, by Matthieu Sozeau and Maxime Dénès).

## User messages

• Improve the ambiguous paths warning to indicate which path is ambiguous with new one (#10336<sup>258</sup>, closes #3219<sup>259</sup>, by Kazuhiko Sakaguchi).

### Extraction

- Fix extraction to OCaml of primitive machine integers; see *Primitive Integers* (#10430<sup>260</sup>, fixes #10361<sup>261</sup>, by Vincent Laporte).
- Fix a printing bug of OCaml extraction on dependent record projections, which produced improper assert false. This change makes the OCaml extractor internally inline record projections by default; thus the monolithic OCaml extraction (*Extraction* and *Recursive Extraction*) does not produce record projection constants anymore except for record projections explicitly instructed to extract, and records declared in opaque modules (#10577<sup>262</sup>, fixes #7348<sup>263</sup>, by Kazuhiko Sakaguchi).

## Standard library

• Added splitat function and lemmas about splitat and uncons (#9379<sup>264</sup>, by Yishuai Li, with help of Konstantinos Kallas, follow-up of #8365<sup>265</sup>, which added uncons in 8.10+beta1).

```
https://github.com/coq/coq/issues/9294
https://github.com/coq/coq/pull/9918
https://github.com/coq/coq/pull/10336
https://github.com/coq/coq/issues/3219
https://github.com/coq/coq/pull/10430
https://github.com/coq/coq/issues/10361
https://github.com/coq/coq/issues/10361
https://github.com/coq/coq/pull/10577
https://github.com/coq/coq/issues/7348
https://github.com/coq/coq/pull/9379
https://github.com/coq/coq/pull/8365
```

3.2. Version 8.10 45

# 3.2.5 Changes in 8.10.0

• Micromega tactics (*lia*, *nia*, etc) are no longer confused by primitive projections (#10806<sup>266</sup>, fixes #9512<sup>267</sup> by Vincent Laporte).

# 3.2.6 Changes in 8.10.1

A few bug fixes and documentation improvements, in particular:

### Kernel

• Fix proof of False when using SProp (incorrect De Bruijn handling when inferring the relevance mark of a function) (#10904<sup>268</sup>, by Pierre-Marie Pédrot).

#### **Tactics**

• Fix an anomaly when unsolved evar in Add Ring (#10891<sup>269</sup>, fixes #9851<sup>270</sup>, by Gaëtan Gilbert).

## Tactic language

• Fix Ltac regression in binding free names in uconstr (#10899<sup>271</sup>, fixes #10894<sup>272</sup>, by Hugo Herbelin).

## CoqIDE

• Fix handling of unicode input before space (#10852<sup>273</sup>, fixes #10842<sup>274</sup>, by Arthur Charguéraud).

### Extraction

• Fix custom extraction of inductives to JSON (#10897<sup>275</sup>, fixes #4741<sup>276</sup>, by Helge Bahmann).

# 3.2.7 Changes in 8.10.2

### Kernel

- Fixed a critical bug of template polymorphism and nonlinear universes (#11128<sup>277</sup>, fixes #11039<sup>278</sup>, by Gaëtan Gilbert).
- Fixed an anomaly "Uncaught exception Constr.DestKO" on Inductive (#11052<sup>279</sup>, fixes #11048<sup>280</sup>, by Gaëtan Gilbert).
- Fixed an anomaly "not enough abstractions in fix body" ( $\#11014^{281}$ , fixes  $\#8459^{282}$ , by Gaëtan Gilbert).

# Notations

```
<sup>266</sup> https://github.com/coq/coq/pull/10806
https://github.com/coq/coq/issues/9512
<sup>268</sup> https://github.com/coq/coq/pull/10904
^{269}https://github.com/coq/coq/pull/10891
<sup>270</sup> https://github.com/coq/coq/issues/9851
<sup>271</sup> https://github.com/coq/coq/pull/10899
<sup>272</sup> https://github.com/coq/coq/issues/10894
^{273} https://github.com/coq/coq/pull/10852
https://github.com/coq/coq/issues/10842
<sup>275</sup> https://github.com/coq/coq/pull/10897
^{276}~\mathrm{https://github.com/coq/coq/issues}/4741
277 https://github.com/coq/coq/pull/11128
<sup>278</sup> https://github.com/coq/coq/issues/11039
^{279} https://github.com/coq/coq/pull/11052
<sup>280</sup> https://github.com/coq/coq/issues/11048
281 https://github.com/coq/coq/pull/11014
<sup>282</sup> https://github.com/coq/coq/issues/8459
```

• Fixed an 8.10 regression related to the printing of coercions associated to notations (#11090<sup>283</sup>, fixes #11033<sup>284</sup>, by Hugo Herbelin).

## CoqIDE

- Fixed uneven dimensions of CoqIDE panels when window has been resized (#11070<sup>285</sup>, fixes 8.10-regression #10956<sup>286</sup>, by Guillaume Melquiond).
- Do not include final stops in queries (#11069<sup>287</sup>, fixes 8.10-regression #11058<sup>288</sup>, by Guillaume Melquiond).

# Infrastructure and dependencies

• Enable building of executables when they are running (#11000<sup>289</sup>, fixes 8.9-regression #10728<sup>290</sup>, by Gaëtan Gilbert).

# 3.3 Version 8.9

# 3.3.1 Summary of changes

Coq version 8.9 contains the result of refinements and stabilization of features and deprecations or removals of deprecated features, cleanups of the internals of the system and API along with a few new features. This release includes many user-visible changes, including deprecations that are documented in the next subsection and new features that are documented in the reference manual. Here are the most important changes:

- Kernel: mutually recursive records are now supported, by Pierre-Marie Pédrot.
- Notations:
  - Support for autonomous grammars of terms called "custom entries", by Hugo Herbelin (see Section *Custom entries* of the reference manual).
  - Deprecated notations of the standard library will be removed in the next version of Coq, see the next subsection for a script to ease porting, by Jason Gross and Jean-Christophe Léchenet.
  - Added the Numeral Notation command for registering decimal numeral notations for custom types, by Daniel de Rauglaudre, Pierre Letouzey and Jason Gross.
- Tactics: Introduction tactics <code>intro/intros</code> on a goal that is an existential variable now force a refinement of the goal into a dependent product rather than failing, by Hugo Herbelin.
- Decision procedures: deprecation of tactic romega in favor of *lia* and removal of fourier, replaced by *lra* which subsumes it, by Frédéric Besson, Maxime Dénès, Vincent Laporte and Laurent Théry.
- Proof language: focusing bracket { now supports named *goals*, e.g. [x]: { will focus on a goal (existential variable) named x, by Théo Zimmermann.
- SSReflect: the implementation of delayed clear was simplified by Enrico Tassi: the variables are always renamed using inaccessible names when the clear switch is processed and finally cleared at the end of the intro pattern. In addition to that, the use-and-discard flag {} typical of rewrite rules can now be also applied to views, e.g. => {}/v applies v and then clears v. See Section Introduction in the context.

3.3. Version 8.9 47

<sup>283</sup> https://github.com/coq/coq/pull/11090

<sup>&</sup>lt;sup>284</sup> https://github.com/coq/coq/issues/11033

 $<sup>^{285}~\</sup>rm{https://github.com/coq/coq/pull/11070}$ 

 $<sup>^{286}</sup>$  https://github.com/coq/coq/issues/10956

<sup>&</sup>lt;sup>287</sup> https://github.com/coq/coq/pull/11069

<sup>&</sup>lt;sup>288</sup> https://github.com/coq/coq/issues/11058

 $<sup>^{289}</sup>$  https://github.com/coq/coq/pull/11000

 $<sup>^{290}</sup>$  https://github.com/coq/coq/issues/10728

### • Vernacular:

- Experimental support for attributes on commands, by Vincent Laporte, as in #[local] Lemma
  foo: bar. Tactics and tactic notations now support the deprecated attribute.
- Removed deprecated commands Arguments Scope and Implicit Arguments in favor of Arguments (scopes) and Arguments (implicits), with the help of Jasper Hugunin.
- New flag Uniform Inductive Parameters by Jasper Hugunin to avoid repeating uniform parameters in constructor declarations.
- New commands Hint Variables and Hint Constants, by Matthieu Sozeau, for controlling the
  opacity status of variables and constants in hint databases. It is recommended to always use these
  commands after creating a hint database with Create HintDb.
- Multiple sections with the same name are now allowed, by Jasper Hugunin.
- Library: additions and changes in the VectorDef, Ascii, and String libraries. Syntax notations are now available only when using Import of libraries and not merely Require, by various contributors (source of incompatibility, see the next subsection for details).
- Toplevels: coqtop and coqide can now display diffs between proof steps in color, using the *Diffs* option, by Jim Fehrle.
- Documentation: we integrated a large number of fixes to the new Sphinx documentation by various contributors, coordinated by Clément Pit-Claudel and Théo Zimmermann.
- Tools: removed the gallina utility and the homebrewed Emacs mode.
- Packaging: as in Coq 8.8.2, the Windows installer now includes many more external packages that can be individually selected for installation, by Michael Soegtrop.

Version 8.9 also comes with a bunch of smaller-scale changes and improvements regarding the different components of the system. Most important ones are documented in the next subsection file.

On the implementation side, the <code>dev/doc/changes.md</code> file documents the numerous changes to the implementation and improvements of interfaces. The file provides guidelines on porting a plugin to the new version and a plugin development tutorial kept in sync with Coq was introduced by Yves Bertot <a href="http://github.com/ybertot/plugin\_tutorials">http://github.com/ybertot/plugin\_tutorials</a>. The new <code>dev/doc/critical-bugs</code> file documents the known critical bugs of Coq and affected releases.

The efficiency of the whole system has seen improvements thanks to contributions from Gaëtan Gilbert, Pierre-Marie Pédrot, and Maxime Dénès.

Maxime Dénès, Emilio Jesús Gallego Arias, Gaëtan Gilbert, Michael Soegtrop, Théo Zimmermann worked on maintaining and improving the continuous integration system.

The OPAM repository for Coq packages has been maintained by Guillaume Melquiond, Matthieu Sozeau, Enrico Tassi with contributions from many users. A list of packages is available at https://coq.inria.fr/opam/www/.

The 54 contributors for this version are Léo Andrès, Rin Arakaki, Benjamin Barenblat, Langston Barrett, Siddharth Bhat, Martin Bodin, Simon Boulier, Timothy Bourke, Joachim Breitner, Tej Chajed, Arthur Charguéraud, Pierre Courtieu, Maxime Dénès, Andres Erbsen, Jim Fehrle, Julien Forest, Emilio Jesus Gallego Arias, Gaëtan Gilbert, Matěj Grabovský, Jason Gross, Samuel Gruetter, Armaël Guéneau, Hugo Herbelin, Jasper Hugunin, Ralf Jung, Sam Pablo Kuper, Ambroise Lafont, Leonidas Lampropoulos, Vincent Laporte, Peter LeFanu Lumsdaine, Pierre Letouzey, Jean-Christophe Léchenet, Nick Lewycky, Yishuai Li, Sven M. Hallberg, Assia Mahboubi, Cyprien Mangin, Guillaume Melquiond, Perry E. Metzger, Clément Pit-Claudel, Pierre-Marie Pédrot, Daniel R. Grayson, Kazuhiko Sakaguchi, Michael Soegtrop, Matthieu Sozeau, Paul Steckler, Enrico Tassi, Laurent Théry, Anton Trunov, whitequark, Théo Winterhalter, Zeimer, Beta Ziliani, Théo Zimmermann.

Many power users helped to improve the design of the new features via the issue and pull request system, the Coq development mailing list or the coq-club@inria.fr mailing list. It would be impossible to mention exhaustively the names of everybody who to some extent influenced the development.

Version 8.9 is the fourth release of Coq developed on a time-based development cycle. Its development spanned 7 months from the release of Coq 8.8. The development moved to a decentralized merging process during this cycle. Guillaume Melquiond was in charge of the release process and is the maintainer of this release. This release is the result of  $\sim 2,000$  commits and  $\sim 500$  PRs merged, closing 75+ issues.

The Coq development team welcomed Vincent Laporte, a new Coq engineer working with Maxime Dénès in the Coq consortium.

Paris, November 2018, Matthieu Sozeau for the Coq development team

# 3.3.2 Details of changes in 8.9+beta1

#### Kernel

• Mutually defined records are now supported.

### Notations

- New support for autonomous grammars of terms, called "custom entries" (see chapter "Syntax extensions" of the reference manual).
- Deprecated compatibility notations will actually be removed in the next version of Coq. Uses of these notations are generally easy to fix thanks to the hint contained in the deprecation warnings. For projects that require more than a handful of such fixes, there is a script<sup>291</sup> that will do it automatically, using the output of coqc. The script contains documentation on its usage in a comment at the top.

### Tactics

- Added toplevel goal selector ! which expects a single focused goal. Use with Set Default Goal Selector to force focusing before tactics are called.
- The undocumented "nameless" forms fix N, cofix that were deprecated in 8.8 have been removed from Ltac's syntax; please use fix ident N/cofix ident to explicitly name the (co)fixpoint hypothesis to be introduced.
- Introduction tactics intro/intros on a goal that is an existential variable now force a refinement of the goal into a dependent product rather than failing.
- Support for fix/cofix added in Ltac match and lazymatch.
- Ltac backtraces now include trace information about tactics called by OCaml-defined tactics.
- Option Ltac Debug now applies also to terms built using Ltac functions.
- Deprecated the Implicit Tactic family of commands.
- The default program obligation tactic uses a bounded proof search instead of an unbounded and potentially non-terminating one now (source of incompatibility).
- The simple apply tactic now respects the Opaque flag when called from Ltac (auto still does not respect it).

3.3. Version 8.9 49

 $<sup>^{291}\</sup> https://gist.github.com/JasonGross/9770653967de3679d131c59d42de6d17\#file-replace-notations-pylonger-polynometric and the properties of the propert$ 

- Tactic constr\_eq now adds universe constraints needed for the identity to the context (it used to ignore them). New tactic constr\_eq\_strict checks that the required constraints already hold without adding new ones. Preexisting tactic constr\_eq\_nounivs can still be used if you really want to ignore universe constraints.
- Tactics and tactic notations now understand the deprecated attribute.
- The fourier tactic has been removed. Please now use lra instead. You may need to add Require
  Import Lra to your developments. For compatibility, we now define fourier as a deprecated alias of
  lra.
- The romega tactics have been deprecated; please use lia instead.

### Focusing

• Focusing bracket { now supports named goal selectors, e.g. [x]: { will focus on a goal (existential variable) named x. As usual, unfocus with } once the sub-goal is fully solved.

## Specification language

• A fix to unification (which was sensitive to the ascii name of variables) may occasionally change type inference in incompatible ways, especially regarding the inference of the return clause of match.

## Standard Library

- Added Ascii.eqb and String.eqb and the =? notation for them, and proved some lemmas about them. Note that this might cause incompatibilities if you have, e.g., string\_scope and Z\_scope both open with string\_scope on top, and expect =? to refer to Z.eqb. Solution: wrap \_ =? \_ in (\_ =? \_)%Z (or whichever scope you want).
- Added Ndigits. N2Bv sized, and proved some lemmas about it. Deprecated Ndigits. N2Bv gen.
- The scopes int\_scope and uint\_scope have been renamed to dec\_int\_scope and dec\_uint\_scope, to clash less with ssreflect and other packages. They are still delimited by %int and %uint.
- Syntax notations for string, ascii, Z, positive, N, R, and int31 are no longer available merely by <code>Require</code>ing the files that define the inductives. You must <code>Import</code> Coq.Strings. String.StringSyntax (after Require Coq.Strings.String), Coq.Strings.Ascii.AsciiSyntax (after Require Coq.Strings.Ascii), Coq.ZArith.BinIntDef, Coq.PArith.BinPosDef, Coq.NArith. BinNatDef, Coq.Reals.Rdefinitions, and Coq.Numbers.Cyclic.Int31.Int31, respectively, to be able to use these notations. Note that passing -compat 8.8 or issuing Require Import Coq.Compat. Coq88 will make these notations available. Users wishing to port their developments automatically may download fix.py from https://gist.github.com/JasonGross/5d4558edf8f5c2c548a3d96c17820169 and run a command like while true; do make -Okj 2>&1 | /path/to/fix.py; done and get a cup of coffee. (This command must be manually interrupted once the build finishes all the way though. Note also that this method is not fail-proof; you may have to adjust some scopes if you were relying on string notations not being available even when string\_scope was open.)
- Numeral syntax for nat is no longer available without loading the entire prelude (Require Import Coq.Init.Prelude). This only impacts users running Coq without the init library (-nois or -noinit) and also issuing Require Import Coq.Init.Datatypes.

### Tools

- Coq\_makefile lets one override or extend the following variables from the command line: COQFLAGS, COQCHKFLAGS, COQCHAGS. COQFLAGS is now entirely separate from COQLIBS, so in custom Makefiles \$(COQFLAGS) should be replaced by \$(COQFLAGS) \$(COQLIBS).
- Removed the gallina utility (extracts specification from Coq vernacular files). If you would like to maintain this tool externally, please contact us.

• Removed the Emacs modes distributed with Coq. You are advised to use Proof-General<sup>292</sup> (and optionally Company-Coq<sup>293</sup>) instead. If your use case is not covered by these alternative Emacs modes, please open an issue. We can help set up external maintenance as part of Proof-General, or independently as part of coq-community.

## Vernacular Commands

- Removed deprecated commands Arguments Scope and Implicit Arguments (not the option). Use the Arguments command instead.
- Nested proofs may be enabled through the option Nested Proofs Allowed. By default, they are disabled and produce an error. The deprecation warning which used to occur when using nested proofs has been removed.
- Added option Uniform Inductive Parameters which abstracts over parameters before typechecking constructors, allowing to write for example Inductive list (A : Type) := nil : list | cons : A -> list -> list.
- New Set Hint Variables/Constants Opaque/Transparent commands for setting globally the opacity flag of variables and constants in hint databases, overwriting the opacity set of the hint database.
- Added generic syntax for "attributes", as in: #[local] Lemma foo: bar.
- Added the Numeral Notation command for registering decimal numeral notations for custom types
- The Set SsrHave NoTCResolution command no longer has special global scope. If you want the previous behavior, use Global Set SsrHave NoTCResolution.
- Multiple sections with the same name are allowed.

## Coq binaries and process model

• Before 8.9, Coq distributed a single coqtop binary and a set of dynamically loadable plugins that used to take over the main loop for tasks such as IDE language server or parallel proof checking.

These plugins have been turned into full-fledged binaries so each different process has associated a particular binary now, in particular coqidetop is the CoqIDE language server, and coq{proof,tactic,query}worker are in charge of task-specific and parallel proof checking.

## **SSReflect**

- The implementation of delayed clear switches in intro patterns is now simpler to explain:
  - 1. The immediate effect of a clear switch like  $\{x\}$  is to rename the variable x to  $_x_ (i.e. a reserved identifier that cannot be mentioned explicitly)$
  - 2. The delayed effect of  $\{x\}$  is that  $_x_i$  is cleared at the end of the intro pattern
  - 3. A clear switch immediately before a view application like  $\{x\}/v$  is translated to  $\{v\}$ .

In particular, the third rule lets one write  $\{x\}/v$  even if v uses the variable x: indeed the view is executed before the renaming.

• An empty clear switch is now accepted in intro patterns before a view application whenever the view is a variable. One can now write  $\{\}/v$  to mean  $\{v\}/v$ . Remark that  $\{\}/x$  is very similar to the idiom  $\{\}e$  for the rewrite tactic (the equation e is used for rewriting and then discarded).

### Standard Library

• There are now conversions between string and positive, Z, nat, and N in binary, octal, and hex.

Display diffs between proof steps

3.3. Version 8.9 51

<sup>&</sup>lt;sup>292</sup> https://proofgeneral.github.io/

<sup>&</sup>lt;sup>293</sup> https://github.com/cpitclaudel/company-coq

• coqtop and coqide can now highlight the differences between proof steps in color. This can be enabled from the command line or the Set Diffs "on"/"off"/"removed" command. Please see the documentation for details. Showing diffs in Proof General requires small changes to PG (under discussion).

## Notations

• Added ++ infix for VectorDef.append. Note that this might cause incompatibilities if you have, e.g., list\_scope and vector\_scope both open with vector\_scope on top, and expect ++ to refer to app. Solution: wrap \_ ++ \_ in (\_ ++ \_)%list (or whichever scope you want).

# 3.3.3 Changes in 8.8.0

Various bug fixes.

# 3.3.4 Changes in 8.8.1

- Some quality-of-life fixes.
- Numerous improvements to the documentation.
- Fix a critical bug related to primitive projections and native compute.
- Ship several additional Coq libraries with the Windows installer.

# 3.4 Version 8.8

## 3.4.1 Summary of changes

Coq version 8.8 contains the result of refinements and stabilization of features and deprecations, cleanups of the internals of the system along with a few new features. The main user visible changes are:

- Kernel: fix a subject reduction failure due to allowing fixpoints on non-recursive values, by Matthieu Sozeau. Handling of evars in the VM (the kernel still does not accept evars) by Pierre-Marie Pédrot.
- Notations: many improvements on recursive notations and support for destructuring patterns in the syntax of notations by Hugo Herbelin.
- Proof language: tacticals for profiling, timing and checking success or failure of tactics by Jason Gross. The focusing bracket { supports single-numbered goal selectors, e.g. 2:{, by Théo Zimmermann.
- Vernacular: deprecation of commands and more uniform handling of the Local flag, by Vincent Laporte and Maxime Dénès, part of a larger attribute system overhaul. Experimental Show Extraction command by Pierre Letouzey. Coercion now accepts Prop or Type as a source by Arthur Charguéraud. Export modifier for options allowing to export the option to modules that Import and not only Require a module, by Pierre-Marie Pédrot.
- Universes: many user-level and API level enhancements: qualified naming and printing, variance annotations for cumulative inductive types, more general constraints and enhancements of the minimization heuristics, interaction with modules by Gaëtan Gilbert, Pierre-Marie Pédrot and Matthieu Sozeau.
- Library: Decimal Numbers library by Pierre Letouzey and various small improvements.
- Documentation: a large community effort resulted in the migration of the reference manual to the Sphinx documentation tool. The result is this manual. The new documentation infrastructure (based on Sphinx) is by Clément Pit-Claudel. The migration was coordinated by Maxime Dénès and Paul

Steckler, with some help of Théo Zimmermann during the final integration phase. The 14 people who ported the manual are Calvin Beck, Heiko Becker, Yves Bertot, Maxime Dénès, Richard Ford, Pierre Letouzey, Assia Mahboubi, Clément Pit-Claudel, Laurence Rideau, Matthieu Sozeau, Paul Steckler, Enrico Tassi, Laurent Théry, Nikita Zyuzin.

• Tools: experimental -mangle-names option to coqtop/coqc for linting proof scripts, by Jasper Hugunin.

On the implementation side, the dev/doc/changes.md file documents the numerous changes to the implementation and improvements of interfaces. The file provides guidelines on porting a plugin to the new version.

Version 8.8 also comes with a bunch of smaller-scale changes and improvements regarding the different components of the system. Most important ones are documented in the next subsection file.

The efficiency of the whole system has seen improvements thanks to contributions from Gaëtan Gilbert, Pierre-Marie Pédrot, Maxime Dénès and Matthieu Sozeau and performance issue tracking by Jason Gross and Paul Steckler.

The official wiki and the bugtracker of Coq migrated to the GitHub platform, thanks to the work of Pierre Letouzey and Théo Zimmermann. Gaëtan Gilbert, Emilio Jesús Gallego Arias worked on maintaining and improving the continuous integration system.

The OPAM repository for Coq packages has been maintained by Guillaume Melquiond, Matthieu Sozeau, Enrico Tassi with contributions from many users. A list of packages is available at https://coq.inria.fr/opam/www/.

The 44 contributors for this version are Yves Bertot, Joachim Breitner, Tej Chajed, Arthur Charguéraud, Jacques-Pascal Deplaix, Maxime Dénès, Jim Fehrle, Julien Forest, Yannick Forster, Gaëtan Gilbert, Jason Gross, Samuel Gruetter, Thomas Hebb, Hugo Herbelin, Jasper Hugunin, Emilio Jesus Gallego Arias, Ralf Jung, Johannes Kloos, Matej Košík, Robbert Krebbers, Tony Beta Lambda, Vincent Laporte, Peter LeFanu Lumsdaine, Pierre Letouzey, Farzon Lotfi, Cyprien Mangin, Guillaume Melquiond, Raphaël Monat, Carl Patenaude Poulin, Pierre-Marie Pédrot, Clément Pit-Claudel, Matthew Ryan, Matt Quinn, Sigurd Schneider, Bernhard Schommer, Michael Soegtrop, Matthieu Sozeau, Arnaud Spiwack, Paul Steckler, Enrico Tassi, Anton Trunov, Martin Vassor, Vadim Zaliva and Théo Zimmermann.

Version 8.8 is the third release of Coq developed on a time-based development cycle. Its development spanned 6 months from the release of Coq 8.7 and was based on a public roadmap. The development process was coordinated by Matthieu Sozeau. Maxime Dénès was in charge of the release process. Théo Zimmermann is the maintainer of this release.

Many power users helped to improve the design of the new features via the bug tracker, the pull request system, the Coq development mailing list or the coq-club@inria.fr mailing list. Special thanks to the users who contributed patches and intensive brain-storming and code reviews, starting with Jason Gross, Ralf Jung, Robbert Krebbers and Amin Timany. It would however be impossible to mention exhaustively the names of everybody who to some extent influenced the development.

The Coq consortium, an organization directed towards users and supporters of the system, is now running and employs Maxime Dénès. The contacts of the Coq Consortium are Yves Bertot and Maxime Dénès.

Santiago de Chile, March 2018, Matthieu Sozeau for the Coq development team

3.4. Version 8.8 53

# 3.4.2 Details of changes in 8.8+beta1

#### Kernel

- Support for template polymorphism for definitions was removed. May trigger more "universe inconsistency" errors in rare occasions.
- Fixpoints are no longer allowed on non-recursive inductive types.

#### Notations

- Recursive notations with the recursive pattern repeating on the right (e.g. "(x; ..; y; z)") now supported.
- Notations with a specific level for the leftmost nonterminal, when printing-only, are supported.
- Notations can now refer to the syntactic category of patterns (as in "fun 'pat =>" or "match p with pat => ... end"). Two variants are available, depending on whether a single variable is considered as a pattern or not.
- Recursive notations now support ".." patterns with several occurrences of the recursive term or binder, possibly mixing terms and binders, possibly in reverse left-to-right order.
- "Locate" now working also on notations of the form "x + y" (rather than "\_ + \_").

## Specification language

• When printing clauses of a "match", clauses with same right-hand side are factorized and the last most factorized clause with no variables, if it exists, is turned into a default clause. Use "Unset Printing Allow Default Clause" do deactivate printing of a default clause. Use "Unset Printing Factorizable Match Patterns" to deactivate factorization of clauses with same right-hand side.

## Tactics

- On Linux, "native\_compute" calls can be profiled using the "perf" utility. The command "Set NativeCompute Profiling" enables profiling, and "Set NativeCompute Profile Filename" customizes the profile filename.
- The tactic "omega" is now aware of the bodies of context variables such as "x := 5: Z" (see #1362). This could be disabled via Unset Omega UseLocalDefs.
- The tactic "romega" is also aware now of the bodies of context variables.
- The tactic "zify" resp. "omega with N" is now aware of N.pred.
- Tactic "decide equality" now able to manage constructors which contain proofs.
- Added tactics reset ltac profile, show ltac profile (and variants)
- Added tactics restart\_timer, finish\_timing, and time\_constr as an experimental way of timing Ltac's evaluation phase
- Added tactic optimize\_heap, analogous to the Vernacular Optimize Heap, which performs a major garbage collection and heap compaction in the OCaml run-time system.
- The tactics "dtauto", "dintuition", "firstorder" now handle inductive types with let bindings in the parameters.
- The tactic dtauto now handles some inductives such as @sigT A (fun \_ => B) as non-dependent conjunctions.
- A bug fixed in rewrite H in \* and rewrite H in \* |- may cause a few rare incompatibilities (it was unintendedly recursively rewriting in the side conditions generated by H).

- Added tactics "assert\_succeeds tac" and "assert\_fails tac" to ensure properties of the execution of a tactic without keeping the effect of the execution.
- vm\_compute now supports existential variables.
- Calls to shelve and give\_up within calls to tactic refine now working.
- Deprecated tactic appronext was removed.

## Focusing

• Focusing bracket { now supports single-numbered goal selector, e.g. 2: { will focus on the second subgoal. As usual, unfocus with } once the sub-goal is fully solved. The Focus and Unfocus commands are now deprecated.

#### Vernacular Commands

- Proofs ending in "Qed exporting ident, .., ident" are not supported anymore. Constants generated during abstract are kept private to the local environment.
- The deprecated Coercion Local, Open Local Scope, Notation Local syntax was removed. Use Local as a prefix instead.
- For the Extraction Language command, "OCaml" is spelled correctly. The older "Ocaml" is still accepted, but deprecated.
- Using "Require" inside a section is deprecated.
- An experimental command "Show Extraction" allows to extract the content of the current ongoing proof (grant wish #4129).
- Coercion now accepts the type of its argument to be "Prop" or "Type".
- The "Export" modifier can now be used when setting and unsetting options, and will result in performing the same change when the module corresponding the command is imported.
- The Axiom command does not automatically declare axioms as instances when their type is a class. Previous behavior can be restored using Set Typeclasses Axioms Are Instances.

### Universes

- Qualified naming of global universes now works like other namespaced objects (e.g. constants), with a separate namespace, inside and across module and library boundaries. Global universe names introduced in an inductive / constant / Let declaration get qualified with the name of the declaration.
- Universe cumulativity for inductive types is now specified as a variance for each polymorphic universe. See the reference manual for more information.
- Inference of universe constraints with cumulative inductive types produces more general constraints. Unsetting new option Cumulativity Weak Constraints produces even more general constraints (but may produce too many universes to be practical).
- Fix #5726: Notations that start with Type now support universe instances with Q{u}.
- with Definition now understands universe declarations (like O(u | Set < u)).

### Tools

- Coq can now be run with the option -mangle-names to change the auto-generated name scheme. This is intended to function as a linter for developments that want to be robust to changes in auto-generated names. This feature is experimental, and may change or disappear without warning.
- GeoProof support was removed.

### Checker

3.4. Version 8.8 55

• The checker now accepts filenames in addition to logical paths.

## CoqIDE

• Find and Replace All report the number of occurrences found; Find indicates when it wraps.

## coqdep

• Learned to read -I, -Q, -R and filenames from \_CoqProject files. This is used by coq\_makefile when generating dependencies for .v files (but not other files).

### Documentation

- The Coq FAQ, formerly located at https://coq.inria.fr/faq, has been moved to the GitHub wiki section of this repository; the main entry page is https://github.com/coq/coq/wiki/The-Coq-FAQ.
- Documentation: a large community effort resulted in the migration of the reference manual to the Sphinx documentation tool. The result is partially integrated in this version.

## Standard Library

- New libraries Coq.Init.Decimal, Coq.Numbers.DecimalFacts, Coq.Numbers.DecimalNat, Coq.Numbers.DecimalPos, Coq.Numbers.DecimalN, Coq.Numbers.DecimalZ, Coq.Numbers.DecimalString providing a type of decimal numbers, some facts about them, and conversions between decimal numbers and nat, positive, N, Z, and string.
- Added [Coq.Strings.String.concat] to concatenate a list of strings inserting a separator between each item
- Notation ' for Zpos in QArith was removed.
- Some deprecated aliases are now emitting warnings when used.

## Compatibility support

• Support for compatibility with versions before 8.6 was dropped.

## Options

- The following deprecated options have been removed:
  - Refolding Reduction
  - Standard Proposition Elimination
  - Dependent Propositions Elimination
  - Discriminate Introduction
  - Shrink Abstract
  - Tactic Pattern Unification
  - Intuition Iff Unfolding
  - Injection L2R Pattern Order
  - Record Elimination Schemes
  - Match Strict
  - Tactic Compat Context
  - Typeclasses Legacy Resolution
  - Typeclasses Module Eta
  - Typeclass Resolution After Apply

# 3.4.3 Details of changes in 8.8.0

#### Tools

• Asynchronous proof delegation policy was fixed. Since version 8.7 Coq was ignoring previous runs and the -async-proofs-delegation-threshold option did not have the expected behavior.

## Tactic language

• The undocumented "nameless" forms fix N, cofix have been deprecated; please use fix ident N /cofix ident to explicitly name the (co)fixpoint hypothesis to be introduced.

## Documentation

• The reference manual is now fully ported to Sphinx.

Other small deprecations and bug fixes.

# 3.4.4 Details of changes in 8.8.1

#### Kernel

- Fix a critical bug with cofixpoints and vm\_compute/native\_compute (#7333).
- Fix a critical bug with modules and algebraic universes (#7695)
- Fix a critical bug with inlining of polymorphic constants (#7615).
- Fix a critical bug with universe polymorphism and vm\_compute (#7723). Was present since 8.5.

#### Notations

• Fixed unexpected collision between only-parsing and only-printing notations (issue #7462).

#### Windows installer

• The Windows installer now includes external packages Ltac2 and Equations (it included the Bignums package since 8.8+beta1).

Many other bug fixes, documentation improvements (including fixes of regressions due to the Sphinx migration), and user message improvements (for details, see the 8.8.1 milestone at https://github.com/coq/coq/milestone/13?closed=1).

## 3.4.5 Details of changes in 8.8.2

## Documentation

• A PDF version of the reference manual is available once again.

## Tools

• The coq-makefile targets print-pretty-timed, print-pretty-timed-diff, and print-pretty-single-time-diff now correctly label the "before" and "after" columns, rather than swapping them.

#### Kernel

• The kernel does not tolerate capture of global universes by polymorphic universe binders, fixing a soundness break (triggered only through custom plugins)

Windows installer

3.4. Version 8.8 57

• The Windows installer now includes many more external packages that can be individually selected for installation.

Many other bug fixes and lots of documentation improvements (for details, see the 8.8.2 milestone at https://github.com/coq/coq/milestone/15?closed=1).

# 3.5 Version 8.7

# 3.5.1 Summary of changes

Coq version 8.7 contains the result of refinements, stabilization of features and cleanups of the internals of the system along with a few new features. The main user visible changes are:

- New tactics: variants of tactics supporting existential variables *eassert*, *eenough*, etc... by Hugo Herbelin. Tactics extensionality in H and *inversion\_sigma* by Jason Gross, specialize with ... accepting partial bindings by Pierre Courtieu.
- Cumulative Polymorphic Inductive types, allowing cumulativity of universes to go through applied inductive types, by Amin Timany and Matthieu Sozeau.
- Integration of the SSReflect plugin and its documentation in the reference manual, by Enrico Tassi, Assia Mahboubi and Maxime Dénès.
- The coq\_makefile tool was completely redesigned to improve its maintainability and the extensibility of generated Makefiles, and to make CoqProject files more palatable to IDEs by Enrico Tassi.

Coq 8.7 involved a large amount of work on cleaning and speeding up the code base, notably the work of Pierre-Marie Pédrot on making the tactic-level system insensitive to existential variable expansion, providing a safer API to plugin writers and making the code more robust. The dev/doc/changes.txt file documents the numerous changes to the implementation and improvements of interfaces. An effort to provide an official, streamlined API to plugin writers is in progress, thanks to the work of Matej Košík.

Version 8.7 also comes with a bunch of smaller-scale changes and improvements regarding the different components of the system. We shall only list a few of them.

The efficiency of the whole system has been significantly improved thanks to contributions from Pierre-Marie Pédrot, Maxime Dénès and Matthieu Sozeau and performance issue tracking by Jason Gross and Paul Steckler.

Thomas Sibut-Pinote and Hugo Herbelin added support for side effect hooks in cbv, cbn and simpl. The side effects are provided via a plugin available at https://github.com/herbelin/reduction-effects/.

The BigN, BigZ, BigQ libraries are no longer part of the Coq standard library, they are now provided by a separate repository https://github.com/coq/bignums, maintained by Pierre Letouzey.

In the Reals library, IZR has been changed to produce a compact representation of integers and real constants are now represented using IZR (work by Guillaume Melquiond).

Standard library additions and improvements by Jason Gross, Pierre Letouzey and others, documented in the next subsection file.

The mathematical proof language/declarative mode plugin was removed from the archive.

The OPAM repository for Coq packages has been maintained by Guillaume Melquiond, Matthieu Sozeau, Enrico Tassi with contributions from many users. A list of packages is available at https://coq.inria.fr/opam/www/.

Packaging tools and software development kits were prepared by Michael Soegtrop with the help of Maxime Dénès and Enrico Tassi for Windows, and Maxime Dénès for MacOS X. Packages are regularly built on the Travis continuous integration server.

The contributors for this version are Abhishek Anand, C.J. Bell, Yves Bertot, Frédéric Besson, Tej Chajed, Pierre Courtieu, Maxime Dénès, Julien Forest, Gaëtan Gilbert, Jason Gross, Hugo Herbelin, Emilio Jesús Gallego Arias, Ralf Jung, Matej Košík, Xavier Leroy, Pierre Letouzey, Assia Mahboubi, Cyprien Mangin, Erik Martin-Dorel, Olivier Marty, Guillaume Melquiond, Sam Pablo Kuper, Benjamin Pierce, Pierre-Marie Pédrot, Lars Rasmusson, Lionel Rieg, Valentin Robert, Yann Régis-Gianas, Thomas Sibut-Pinote, Michael Soegtrop, Matthieu Sozeau, Arnaud Spiwack, Paul Steckler, George Stelle, Pierre-Yves Strub, Enrico Tassi, Hendrik Tews, Amin Timany, Laurent Théry, Vadim Zaliva and Théo Zimmermann.

The development process was coordinated by Matthieu Sozeau with the help of Maxime Dénès, who was also in charge of the release process. Théo Zimmermann is the maintainer of this release.

Many power users helped to improve the design of the new features via the bug tracker, the pull request system, the Coq development mailing list or the Coq-Club mailing list. Special thanks to the users who contributed patches and intensive brain-storming and code reviews, starting with Jason Gross, Ralf Jung, Robbert Krebbers, Xavier Leroy, Clément Pit-Claudel and Gabriel Scherer. It would however be impossible to mention exhaustively the names of everybody who to some extent influenced the development.

Version 8.7 is the second release of Coq developed on a time-based development cycle. Its development spanned 9 months from the release of Coq 8.6 and was based on a public road-map. It attracted many external contributions. Code reviews and continuous integration testing were systematically used before integration of new features, with an important focus given to compatibility and performance issues, resulting in a hopefully more robust release than Coq 8.6 while maintaining compatibility.

Coq Enhancement Proposals (CEPs for short) and open pull request discussions were used to discuss publicly the new features.

The Coq consortium, an organization directed towards users and supporters of the system, is now upcoming and will rely on Inria's newly created Foundation.

Paris, August 2017, Matthieu Sozeau and the Coq development team

## 3.5.2 Potential compatibility issues

• Extra superfluous names in introduction patterns may now raise an error rather than a warning when the superfluous name is already in use. The easy fix is to remove the superfluous name.

# 3.5.3 Details of changes in 8.7+beta1

## Tactics

- New tactic "extensionality in H" which applies (possibly dependent) functional extensionality in H supposed to be a quantified equality until giving a bare equality.
- New tactic inversion\_sigma which turns equalities of dependent pairs (e.g., existT P x p = existT P y q, frequently left over by inversion on a dependent type family) into pairs of equalities (e.g., a hypothesis H : x = y and a hypothesis of type rew H in p = q); these hypotheses can subsequently be simplified using subst, without ever invoking any kind of axiom asserting uniqueness of identity proofs. If you want to explicitly specify the hypothesis to be inverted, or name the generated hypotheses,

3.5. Version 8.7 59

- you can invoke induction H as [H1 H2] using eq\_sigT\_rect. The tactic also works for sig, sigT2, and sig2, and there are similar eq\_sig\*\_rect induction lemmas.
- Tactic "specialize with ..." now accepts any partial bindings. Missing bindings are either solved by unification or left quantified in the hypothesis.
- New representation of terms that statically ensure stability by evar-expansion. This has several consequences.
  - In terms of performance, this adds a cost to every term destructuration, but at the same time most eager evar normalizations were removed, which couterbalances this drawback and even sometimes outperforms the old implementation. For instance, many operations that would require O(n) normalization of the term are now O(1) in tactics. YMMV.
  - This triggers small changes in unification, which was not evar-insensitive. Most notably, the new implementation recognizes Miller patterns that were missed before because of a missing normalization step. Hopefully this should be fairly uncommon.
- Tactic "auto with real" can now discharge comparisons of literals.
- The types of variables in patterns of "match" are now beta-iota-reduced after type-checking. This has an impact on the type of the variables that the tactic "refine" introduces in the context, producing types a priori closer to the expectations.
- In "Tactic Notation" or "TACTIC EXTEND", entry "constr\_with\_bindings" now uses type classes and rejects terms with unresolved holes, like entry "constr" does. To get the former behavior use "open\_constr\_with\_bindings" (possible source of incompatibility).
- New e-variants eassert, eenough, epose proof, eset, eremember, epose which behave like the corresponding variants with no "e" but turn unresolved implicit arguments into existential variables, on the shelf, rather than failing.
- Tactic injection has become more powerful (closes bug #4890) and its documentation has been updated.
- New variants of the first and solve tacticals that do not rely on parsing rules, meant to define tactic notations.
- Added support for side effects hooks in cbv, cbn and simpl. The side effects are provided via a plugin: https://github.com/herbelin/reduction-effects/
- It is now possible to take hint database names as parameters in a Ltac definition or a Tactic Notation.
- New option Set Ltac Batch Debug on top of Set Ltac Debug for non-interactive Ltac debug output.

#### Gallina

• Now supporting all kinds of binders, including 'pat, in syntax of record fields.

### Vernacular Commands

- Goals context can be printed in a more compact way when Set Printing Compact Contexts is activated.
- Unfocused goals can be printed with the Set Printing Unfocused option.
- Print now shows the types of let-bindings.
- The compatibility options for printing primitive projections (Set Printing Primitive Projection Parameters and Set Printing Primitive Projection Compatibility) are now off by default.
- Possibility to unset the printing of notations in a more fine grained fashion than Unset Printing Notations is provided without any user-syntax. The goal is that someone creates a plugin to experiment such a user-syntax, to be later integrated in Coq when stabilized.
- About now tells if a reference is a coercion.

- The deprecated Save vernacular and its form Save Theorem id to close proofs have been removed from the syntax. Please use Qed.
- Search now sorts results by relevance (the relevance metric is a weighted sum of number of distinct symbols and size of the term).

## Standard Library

- New file PropExtensionality.v to explicitly work in the axiomatic context of propositional extensionality.
- New file SetoidChoice.v axiomatically providing choice over setoids, and, consequently, choice of representatives in equivalence classes. Various proof-theoretic characterizations of choice over setoids in file ChoiceFacts.v.
- New lemmas about iff and about orders on positive and Z.
- New lemmas on powerRZ.
- Strengthened statement of JMeq\_eq\_dep (closes bug #4912).
- The BigN, BigZ, BigZ libraries are no longer part of the Coq standard library, they are now provided by a separate repository https://github.com/coq/bignums The split has been done just after the Int31 library.
- IZR (Reals) has been changed to produce a compact representation of integers. As a consequence, IZR is no longer convertible to INR and lemmas such as INR\_IZR\_INZ should be used instead.
- Real constants are now represented using IZR rather than R0 and R1; this might cause rewriting rules to fail to apply to constants.
- Added new notation {x & P} for sigT (without a type for x)

## Plugins

- The Ssreflect plugin is now distributed with Coq. Its documentation has been integrated as a chapter of the reference manual. This chapter is work in progress so feedback is welcome.
- The mathematical proof language (also known as declarative mode) was removed.
- A new command Extraction TestCompile has been introduced, not meant for the general user but instead for Coq's test-suite.
- The extraction plugin is no longer loaded by default. It must be explicitly loaded with [Require Extraction], which is backwards compatible.
- The functional induction plugin (which provides the [Function] vernacular) is no longer loaded by default. It must be explicitly loaded with [Require FunInd], which is backwards compatible.

## Dependencies

• Support for camlp4 has been removed.

### Tools

- coq\_makefile was completely redesigned to improve its maintainability and the extensibility of generated Makefiles, and to make \_CoqProject files more palatable to IDEs. Overview:
  - \_CoqProject files contain only Coq specific data (i.e. the list of files, -R options, ...)
  - coq\_makefile translates \_CoqProject to Makefile.conf and copies in the desired location a standard Makefile (that reads Makefile.conf)
  - Makefile extensions can be implemented in a Makefile.local file (read by the main Makefile) by installing a hook in the extension points provided by the standard Makefile

3.5. Version 8.7 61

The current version contains code for retro compatibility that prints warnings when a deprecated feature is used. Please upgrade your \_CoqProject accordingly.

- Additionally, coq\_makefile-made Makefiles now support experimental timing targets pretty-timed, pretty-timed-before, pretty-timed-after, print-pretty-timed-diff, print-pretty-single-time-diff, all.timing.diff, and the variable TIMING=1 (or TIMING=before or TIMING=after); see the documentation for more details.

#### Build Infrastructure

• Note that 'make world' does not build the bytecode binaries anymore. For that, you can use 'make byte' (and 'make install-byte' afterwards). Warning: native and byte compilations should *not* be mixed in the same instance of 'make -j', otherwise both ocamlc and ocamlopt might race for access to the same .cmi files. In short, use "make -j && make -j byte" instead of "make -j world byte".

### Universes

- Cumulative inductive types. see prefixes "Cumulative", "NonCumulative" for inductive definitions and the option "Set Polymorphic Inductive Cumulativity" in the reference manual.
- New syntax foo@{\_} to instantiate a polymorphic definition with anonymous universes (can also be used with Type).

XML Protocol and internal changes

See dev/doc/changes.txt

Many bugfixes including #1859, #2884, #3613, #3943, #3994, #4250, #4709, #4720, #4824, #4844, #4911, #5026, #5233, #5275, #5315, #5336, #5360, #5390, #5414, #5417, #5420, #5439, #5449, #5475, #5476, #5482, #5501, #5507, #5520, #5523, #5524, #5553, #5577, #5578, #5589, #5597, #5598, #5607, #5618, #5619, #5620, #5641, #5648, #5651, #5671.

Many bugfixes on OS X and Windows (now the test-suite passes on these platforms too).

Many optimizations.

Many documentation improvements.

## 3.5.4 Details of changes in 8.7+beta2

Tools

• In CoqIDE, the "Compile Buffer" command takes account of flags in \_CoqProject or other project file. Improvements around some error messages.

Many bug fixes including two important ones:

- Bug #5730: CoqIDE becomes unresponsive on file open.
- coq\_makefile: make sure compile flags for Coq and coq\_makefile are in sync (in particular, make sure the -safe-string option is used to compile plugins).

# 3.5.5 Details of changes in 8.7.0

## **OCaml**

 Users can pass specific flags to the OCaml optimizing compiler by -using the flambda-opts configuretime option.

Beware that compiling Coq with a flambda-enabled compiler is experimental and may require large amounts of RAM and CPU, see INSTALL for more details.

# 3.5.6 Details of changes in 8.7.1

Compatibility with OCaml 4.06.0.

Many bug fixes, documentation improvements, and user message improvements (for details see the 8.7.1 milestone at https://github.com/coq/coq/milestone/10?closed=1).

# 3.5.7 Details of changes in 8.7.2

Fixed a critical bug in the VM handling of universes (#6677). This bug affected all releases since 8.5.

Improved support for building with OCaml 4.06.0 and external num package.

Many other bug fixes, documentation improvements, and user message improvements (for details, see the 8.7.2 milestone at https://github.com/coq/coq/milestone/11?closed=1).

# 3.6 Version 8.6

# 3.6.1 Summary of changes

Coq version 8.6 contains the result of refinements, stabilization of 8.5's features and cleanups of the internals of the system. Over the year of (now time-based) development, about 450 bugs were resolved and over 100 contributions integrated. The main user visible changes are:

- A new, faster state-of-the-art universe constraint checker, by Jacques-Henri Jourdan.
- In CoqIDE and other asynchronous interfaces, more fine-grained asynchronous processing and error reporting by Enrico Tassi, making Coq capable of recovering from errors and continue processing the document.
- More access to the proof engine features from Ltac: goal management primitives, range selectors and a typeclasses eauto engine handling multiple goals and multiple successes, by Cyprien Mangin, Matthieu Sozeau and Arnaud Spiwack.
- Tactic behavior uniformization and specification, generalization of intro-patterns by Hugo Herbelin and others.
- A brand new warning system allowing to control warnings, turn them into errors or ignore them selectively by Maxime Dénès, Guillaume Melquiond, Pierre-Marie Pédrot and others.
- Irrefutable patterns in abstractions, by Daniel de Rauglaudre.
- The ssreflect subterm selection algorithm by Georges Gonthier and Enrico Tassi is now accessible to tactic writers through the ssrmatching plugin.
- Integration of LtacProf, a profiler for Ltac by Jason Gross, Paul Steckler, Enrico Tassi and Tobias Tebbi.

Coq 8.6 also comes with a bunch of smaller-scale changes and improvements regarding the different components of the system. We shall only list a few of them.

The iota reduction flag is now a shorthand for match, fix and cofix flags controlling the corresponding reduction rules (by Hugo Herbelin and Maxime Dénès).

Maxime Dénès maintained the native compilation machinery.

Pierre-Marie Pédrot separated the Ltac code from general purpose tactics, and generalized and rationalized the handling of generic arguments, allowing to create new versions of Ltac more easily in the future.

3.6. Version 8.6 63

In patterns and terms, @, abbreviations and notations are now interpreted the same way, by Hugo Herbelin.

Name handling for universes has been improved by Pierre-Marie Pédrot and Matthieu Sozeau. The minimization algorithm has been improved by Matthieu Sozeau.

The unifier has been improved by Hugo Herbelin and Matthieu Sozeau, fixing some incompatibilities introduced in Coq 8.5. Unification constraints can now be left floating around and be seen by the user thanks to a new option. The Keyed Unification mode has been improved by Matthieu Sozeau.

The typeclass resolution engine and associated proof-search tactic have been reimplemented on top of the proof-engine monad, providing better integration in tactics, and new options have been introduced to control it, by Matthieu Sozeau with help from Théo Zimmermann.

The efficiency of the whole system has been significantly improved thanks to contributions from Pierre-Marie Pédrot, Maxime Dénès and Matthieu Sozeau and performance issue tracking by Jason Gross and Paul Steckler.

Standard library improvements by Jason Gross, Sébastien Hinderer, Pierre Letouzey and others.

Emilio Jesús Gallego Arias contributed many cleanups and refactorings of the pretty-printing and user interface communication components.

Frédéric Besson maintained the micromega tactic.

The OPAM repository for Coq packages has been maintained by Guillaume Claret, Guillaume Melquiond, Matthieu Sozeau, Enrico Tassi and others. A list of packages is now available at https://coq.inria.fr/opam/www/.

Packaging tools and software development kits were prepared by Michael Soegtrop with the help of Maxime Dénès and Enrico Tassi for Windows, and Maxime Dénès and Matthieu Sozeau for MacOS X. Packages are now regularly built on the continuous integration server. Coq now comes with a META file usable with ocamlfind, contributed by Emilio Jesús Gallego Arias, Gregory Malecha, and Matthieu Sozeau.

Matej Košík maintained and greatly improved the continuous integration setup and the testing of Coq contributions. He also contributed many API improvements and code cleanups throughout the system.

The contributors for this version are Bruno Barras, C.J. Bell, Yves Bertot, Frédéric Besson, Pierre Boutillier, Tej Chajed, Guillaume Claret, Xavier Clerc, Pierre Corbineau, Pierre Courtieu, Maxime Dénès, Ricky Elrod, Emilio Jesús Gallego Arias, Jason Gross, Hugo Herbelin, Sébastien Hinderer, Jacques-Henri Jourdan, Matej Košík, Xavier Leroy, Pierre Letouzey, Gregory Malecha, Cyprien Mangin, Erik Martin-Dorel, Guillaume Melquiond, Clément Pit-Claudel, Pierre-Marie Pédrot, Daniel de Rauglaudre, Lionel Rieg, Gabriel Scherer, Thomas Sibut-Pinote, Matthieu Sozeau, Arnaud Spiwack, Paul Steckler, Enrico Tassi, Laurent Théry, Nickolai Zeldovich and Théo Zimmermann. The development process was coordinated by Hugo Herbelin and Matthieu Sozeau with the help of Maxime Dénès, who was also in charge of the release process.

Many power users helped to improve the design of the new features via the bug tracker, the pull request system, the Coq development mailing list or the Coq-Club mailing list. Special thanks to the users who contributed patches and intensive brain-storming and code reviews, starting with Cyril Cohen, Jason Gross, Robbert Krebbers, Jonathan Leivent, Xavier Leroy, Gregory Malecha, Clément Pit-Claudel, Gabriel Scherer and Beta Ziliani. It would however be impossible to mention exhaustively the names of everybody who to some extent influenced the development.

Version 8.6 is the first release of Coq developed on a time-based development cycle. Its development spanned 10 months from the release of Coq 8.5 and was based on a public roadmap. To date, it contains more external contributions than any previous Coq system. Code reviews were systematically done before integration of new features, with an important focus given to compatibility and performance issues, resulting in a hopefully more robust release than Coq 8.5.

Coq Enhancement Proposals (CEPs for short) were introduced by Enrico Tassi to provide more visibility and a discussion period on new features, they are publicly available https://github.com/coq/ceps.

Started during this period, an effort is led by Yves Bertot and Maxime Dénès to put together a Coq consortium.

Paris, November 2016, Matthieu Sozeau and the Coq development team

# 3.6.2 Potential sources of incompatibilities

• Symptom: An obligation generated by Program or an abstracted subproof has different arguments.

Cause: Set Shrink Abstract and Set Shrink Obligations are on by default and the subproof does not use the argument.

## Remedy:

- Adapt the script.
- Write an explicit lemma to prove the obligation/subproof and use it instead (compatible with 8.4).
- Unset the option for the program/proof the obligation/subproof originates from.
- Symptom: In a goal, order of hypotheses, or absence of an equality of the form "x = t" or "t = x", or no unfolding of a local definition.

Cause: This might be connected to a number of fixes in the tactic "subst". The former behavior can be reactivated by issuing "Unset Regular Subst Tactic".

# 3.6.3 Details of changes in 8.6beta1

## Kernel

• A new, faster state-of-the-art universe constraint checker.

# Specification language

- Giving implicit arguments explicitly to a constant with multiple choices of implicit arguments does not break any more insertion of further maximal implicit arguments.
- Ability to put any pattern in binders, prefixed by quote, e.g. "fun '(a,b) => ...", " $\lambda$  '(a,(b,c)), ...", "Definition foo '(x,y) := ...". It expands into a "let 'pattern := ..."

## Tactics

- Flag "Bracketing Last Introduction Pattern" is now on by default.
- Flag "Regular Subst Tactic" is now on by default: it respects the initial order of hypothesis, it contracts cycles, it unfolds no local definitions (common source of incompatibilities, fixable by "Unset Regular Subst Tactic").
- New flag "Refolding Reduction", now disabled by default, which turns on refolding of constants/fixpoints (as in cbn) during the reductions done during type inference and tactic retyping. Can be extremely expensive. When set off, this recovers the 8.4 behaviour of unification and type inference. Potential source of incompatibility with 8.5 developments (the option is set on in Compat/Coq85.v).
- New flag "Shrink Abstract" that minimalizes proofs generated by the abstract tactical w.r.t. variables appearing in the body of the proof. On by default and deprecated. Minor source of incompatibility for code relying on the precise arguments of abstracted proofs.

3.6. Version 8.6 65

- Serious bugs are fixed in tactic "double induction" (source of incompatibilities as soon as the inductive types have dependencies in the type of their constructors; "double induction" remains however deprecated).
- In introduction patterns of the form (pat1,...,patn), n should match the exact number of hypotheses introduced (except for local definitions for which pattern can be omitted, as in regular pattern-matching).
- Tactic scopes in Ltac like constr: and ltac: now require parentheses around their argument.
- Every generic argument type declares a tactic scope of the form "name:(...)" where name is the name of the argument. This generalizes the constr: and ltac: instances.
- When in strict mode (i.e. in a Ltac definition), if the "intro" tactic is given a free identifier, it is not bound in subsequent tactics anymore. In order to introduce a binding, use e.g. the "fresh" primitive instead (potential source of incompatibilities).
- New tactics is ind, is const, is proj, is constructor for use in Ltac.
- New goal selectors. Sets of goals can be selected by listing integers ranges. Example: "1,4-7,24: tac" focuses "tac" on goals 1,4,5,6,7,24.
- For uniformity with "destruct"/"induction" and for a more natural behavior, "injection" can now work in place by activating option "Structural Injection". In this case, hypotheses are also put in the context in the natural left-to-right order and the hypothesis on which injection applies is cleared.
- Tactic "contradiction" (hence "easy") now also solve goals with hypotheses of the form "~True" or "t<>t" (possible source of incompatibilities because of more successes in automation, but generally a more intuitive strategy).
- Option "Injection On Proofs" was renamed "Keep Proof Equalities". When enabled, injection and inversion do not drop equalities between objects in Prop. Still disabled by default.
- New tactics "notypeclasses refine" and "simple notypeclasses refine" that disallow typeclass resolution when typechecking their argument, for use in typeclass hints.
- Integration of LtacProf, a profiler for Ltac.
- Reduction tactics now accept more fine-grained flags: iota is now a shorthand for the new flags match, fix and cofix.
- The ssreflect subterm selection algorithm is now accessible to tactic writers through the ssrmatching plugin.
- When used as an argument of an ltac function, "auto" without "with" nor "using" clause now correctly uses only the core hint database by default.

#### Hints

- Revised the syntax of [Hint Cut] to follow standard notation for regexps.
- Hint Mode now accepts "!" which means that the mode matches only if the argument's head is not an evar (it goes under applications, casts, and scrutinees of matches and projections).
- Hints can now take an optional user-given pattern, used only by [typeclasses eauto] with the [Filtered Unification] option on.

# Typeclasses

Many new options and new engine based on the proof monad. The [typeclasses eauto] tactic is now a
multi-goal, multi-success tactic. See reference manual for more information. It is planned to replace
auto and eauto in the following version. The 8.5 resolution engine is still available to help solve
compatibility issues.

# Program

- The "Shrink Obligations" flag now applies to all obligations, not only those solved by the automatic tactic.
- "Shrink Obligations" is on by default and deprecated. Minor source of incompatibility for code relying on the precise arguments of obligations.

### Notations

• "Bind Scope" can once again bind "Funclass" and "Sortclass".

#### General infrastructure

- New configurable warning system which can be controlled with the vernacular command "Set Warnings", or, under coqc/coqtop, with the flag "-w". In particular, the default is now that warnings are printed by coqc.
- In asynchronous mode, Coq is now capable of recovering from errors and continue processing the document.

### Tools

- cogc accepts a -o option to specify the output file name
- coqtop accepts –print-version to print Coq and OCaml versions in easy to parse format
- Setting [Printing Dependent Evars Line] can be unset to disable the computation associated with printing the "dependent evars: " line in -emacs mode
- Removed the -verbose-compat-notations flag and the corresponding Set Verbose Compat vernacular, since these warnings can now be silenced or turned into errors using "-w".

## XML protocol

• message format has changed, see dev/doc/changes.txt for more details.

Many bug fixes, minor changes and documentation improvements are not mentioned here.

# 3.6.4 Details of changes in 8.6

## Kernel

• Fixed critical bug #5248 in VM long multiplication on 32-bit architectures. Was there only since 8.6beta1, so no stable release impacted.

Other bug fixes in universes, type class shelving,...

# 3.6.5 Details of changes in 8.6.1

- Fix #5380: Default colors for CoqIDE are actually applied.
- Fix plugin warnings
- Document named evars (including Show ident)
- Fix Bug #5574, document function scope
- Adding a test case as requested in bug 5205.
- Fix Bug #5568, no dup notation warnings on repeated module imports
- Fix documentation of Typeclasses eauto :=
- Refactor documentation of records.

3.6. Version 8.6 67

- Protecting from warnings while compiling 8.6
- Fixing an inconsistency between configure and configure.ml
- Add test-suite checks for coqchk with constraints
- Fix bug #5019 (looping zify on dependent types)
- Fix bug 5550: "typeclasses eauto with" does not work with section variables.
- Bug 5546, qualify datatype constructors when needed in Show Match
- Bug #5535, test for Show with -emacs
- Fix bug #5486, don't reverse ids in tuples
- Fixing #5522 (anomaly with free vars of pat)
- Fix bug #5526, don't check for nonlinearity in notation if printing only
- Fix bug #5255
- Fix bug #3659: -time should understand multibyte encodings.
- FIx bug #5300: Anomaly: Uncaught exception Not\_found" in "Print Assumptions".
- Fix outdated description in RefMan.
- Repairing Set Rewriting Schemes
- Fixing #5487 (v8.5 regression on ltac-matching expressions with evars).
- Fix description of command-line arguments for Add (Rec) LoadPath
- Fix bug #5377: @? patterns broken.
- add XML protocol doc
- Fix anomaly when doing [all:Check \_.] during a proof.
- Correction of bug #4306
- Fix #5435: [Eval native compute in] raises anomaly.
- Instances should obey universe binders even when defined by tactics.
- Intern names bound in match patterns
- funind: Ignore missing info for current function
- Do not typecheck twice the type of opaque constants.
- show unused intro pattern warning
- [future] Be eager when "chaining" already resolved future values.
- Opaque side effects
- Fix #5132: coq\_makefile generates incorrect install goal
- Run non-tactic comands without resilient command
- Univs: fix bug #5365, generation of u+k <= v constraints
- make emit tail recursive
- Don't require printing-only notation to be productive
- Fix the way setoid rewrite handles bindings.
- Fix for bug 5244 set printing width ignored when given enough space

• Fix bug 4969, autoapply was not tagging shelved subgoals correctly

# 3.7 Version 8.5

# 3.7.1 Summary of changes

Coq version 8.5 contains the result of five specific long-term projects:

- A new asynchronous evaluation and compilation mode by Enrico Tassi with help from Bruno Barras and Carst Tankink.
- Full integration of the new proof engine by Arnaud Spiwack helped by Pierre-Marie Pédrot,
- Addition of conversion and reduction based on native compilation by Maxime Dénès and Benjamin Grégoire.
- Full universe polymorphism for definitions and inductive types by Matthieu Sozeau.
- An implementation of primitive projections with  $\eta$ -conversion bringing significant performance improvements when using records by Matthieu Sozeau.

The full integration of the proof engine, by Arnaud Spiwack and Pierre-Marie Pédrot, brings to primitive tactics and the user level Ltac language dependent subgoals, deep backtracking and multiple goal handling, along with miscellaneous features and an improved potential for future modifications. Dependent subgoals allow statements in a goal to mention the proof of another. Proofs of unsolved subgoals appear as existential variables. Primitive backtracking makes it possible to write a tactic with several possible outcomes which are tried successively when subsequent tactics fail. Primitives are also available to control the backtracking behavior of tactics. Multiple goal handling paves the way for smarter automation tactics. It is currently used for simple goal manipulation such as goal reordering.

The way Coq processes a document in batch and interactive mode has been redesigned by Enrico Tassi with help from Bruno Barras. Opaque proofs, the text between Proof and Qed, can be processed asynchronously, decoupling the checking of definitions and statements from the checking of proofs. It improves the responsiveness of interactive development, since proofs can be processed in the background. Similarly, compilation of a file can be split into two phases: the first one checking only definitions and statements and the second one checking proofs. A file resulting from the first phase – with the .vio extension – can be already Required. All .vio files can be turned into complete .vo files in parallel. The same infrastructure also allows terminating tactics to be run in parallel on a set of goals via the par: goal selector.

CoqIDE was modified to cope with asynchronous checking of the document. Its source code was also made separate from that of Coq, so that CoqIDE no longer has a special status among user interfaces, paving the way for decoupling its release cycle from that of Coq in the future.

Carst Tankink developed a Coq back-end for user interfaces built on Makarius Wenzel's Prover IDE framework (PIDE), like PIDE/jEdit (with help from Makarius Wenzel) or PIDE/Coqoon (with help from Alexander Faithfull and Jesper Bengtson). The development of such features was funded by the Paral-ITP French ANR project.

The full universe polymorphism extension was designed by Matthieu Sozeau. It conservatively extends the universes system and core calculus with definitions and inductive declarations parameterized by universes and constraints. It is based on a modification of the kernel architecture to handle constraint checking only, leaving the generation of constraints to the refinement/type inference engine. Accordingly, tactics are now fully universe aware, resulting in more localized error messages in case of inconsistencies and allowing higher-level algorithms like unification to be entirely type safe. The internal representation of universes has been modified but this is invisible to the user.

3.7. Version 8.5

The underlying logic has been extended with  $\eta$ -conversion for records defined with primitive projections by Matthieu Sozeau. This additional form of  $\eta$ -conversion is justified using the same principle than the previously added  $\eta$ -conversion for function types, based on formulations of the Calculus of Inductive Constructions with typed equality. Primitive projections, which do not carry the parameters of the record and are rigid names (not defined as a pattern matching construct), make working with nested records more manageable in terms of time and space consumption. This extension and universe polymorphism were carried out partly while Matthieu Sozeau was working at the IAS in Princeton.

The guard condition has been made compliant with extensional equality principles such as propositional extensionality and univalence, thanks to Maxime Dénès and Bruno Barras. To ensure compatibility with the univalence axiom, a new flag -indices-matter has been implemented, taking into account the universe levels of indices when computing the levels of inductive types. This supports using Coq as a tool to explore the relations between homotopy theory and type theory.

Maxime Dénès and Benjamin Grégoire developed an implementation of conversion test and normal form computation using the OCaml native compiler. It complements the virtual machine conversion offering much faster computation for expensive functions.

Coq 8.5 also comes with a bunch of many various smaller-scale changes and improvements regarding the different components of the system. We shall only list a few of them.

Pierre Boutillier developed an improved tactic for simplification of expressions called cbn.

Maxime Dénès maintained the bytecode-based reduction machine. Pierre Letouzey maintained the extraction mechanism.

Pierre-Marie Pédrot has extended the syntax of terms to, experimentally, allow holes in terms to be solved by a locally specified tactic.

Existential variables are referred to by identifiers rather than mere numbers, thanks to Hugo Herbelin who also improved the tactic language here and there.

Error messages for universe inconsistencies have been improved by Matthieu Sozeau. Error messages for unification and type inference failures have been improved by Hugo Herbelin, Pierre-Marie Pédrot and Arnaud Spiwack.

Pierre Courtieu contributed new features for using Coq through Proof General and for better interactive experience (bullets, Search, etc).

The efficiency of the whole system has been significantly improved thanks to contributions from Pierre-Marie Pédrot.

A distribution channel for Coq packages using the OPAM tool has been initiated by Thomas Braibant and developed by Guillaume Claret, with contributions by Enrico Tassi and feedback from Hugo Herbelin.

Packaging tools were provided by Pierre Letouzey and Enrico Tassi (Windows), Pierre Boutillier, Matthieu Sozeau and Maxime Dénès (MacOS X). Maxime Dénès improved significantly the testing and benchmarking support.

Many power users helped to improve the design of the new features via the bug tracker, the coq development mailing list or the Coq-Club mailing list. Special thanks are going to the users who contributed patches and intensive brain-storming, starting with Jason Gross, Jonathan Leivent, Greg Malecha, Clément Pit-Claudel, Marc Lasson, Lionel Rieg. It would however be impossible to mention with precision all names of people who to some extent influenced the development.

Version 8.5 is one of the most important releases of Coq. Its development spanned over about 3 years and a half with about one year of beta-testing. General maintenance during part or whole of this period has been done by Pierre Boutillier, Pierre Courtieu, Maxime Dénès, Hugo Herbelin, Pierre Letouzey, Guillaume Melquiond, Pierre-Marie Pédrot, Matthieu Sozeau, Arnaud Spiwack, Enrico Tassi as well as Bruno Barras, Yves Bertot, Frédéric Besson, Xavier Clerc, Pierre Corbineau, Jean-Christophe Filliâtre, Julien Forest,

Sébastien Hinderer, Assia Mahboubi, Jean-Marc Notin, Yann Régis-Gianas, François Ripault, Carst Tankink. Maxime Dénès coordinated the release process.

Paris, January 2015, revised December 2015, Hugo Herbelin, Matthieu Sozeau and the Coq development team

# 3.7.2 Potential sources of incompatibilities

List of typical changes to be done to adapt files from Coq 8.4 to Coq 8.5 when not using compatibility option -compat 8.4.

• Symptom: "The reference omega was not found in the current environment".

Cause: "Require Omega" does not import the tactic "omega" any more

Possible solutions:

- use "Require Import OmegaTactic" (not compatible with 8.4)
- use "Require Import Omega" (compatible with 8.4)
- add definition "Ltac omega: Coq.omega.Omega.omega."
- Symptom: "intuition" cannot solve a goal (not working anymore on non standard connective)

Cause: "intuition" had an accidental non uniform behavior fixed on non standard connectives

Possible solutions:

- use "dintuition" instead; it is stronger than "intuition" and works uniformly on non standard connectives, such as n-ary conjunctions or disjunctions (not compatible with 8.4)
- do the script differently
- Symptom: The constructor foo (in type bar) expects n arguments.

Cause: parameters must now be given in patterns

Possible solutions:

- use option "Set Asymmetric Patterns" (compatible with 8.4)
- add "\_" for the parameters (not compatible with 8.4)
- turn the parameters into implicit arguments (compatible with 8.4)
- Symptom: "NPeano.Nat.foo" not existing anymore

Possible solutions:

- use "Nat.foo" instead

Symptom: typing problems with proj1 sig or similar

Cause: coercion from sig to sigT and similar coercions have been removed so as to make the initial state easier to understand for beginners

Solution: change proj1\_sig into projT1 and similarly (compatible with 8.4)

Other detailed changes

• options for *coq* compilation (see below for ocaml).

3.7. Version 8.5

- [-I foo] is now deprecated and will not add directory foo to the coq load path (only for ocaml, see below). Just replace [-I foo] by [-Q foo ""] in your project file and re-generate makefile. Or perform the same operation directly in your makefile if you edit it by hand.
- Option -R Foo bar is the same in v8.5 than in v8.4 concerning coq load path.
- Option [-I foo -as bar] is unchanged but discouraged unless you compile ocaml code. Use -Q foo bar instead.

for more details: see section "Customization at launch time" of the reference manual.

- Command line options for ocaml Compilation of ocaml code (plugins)
  - [-I foo] is *not* deprecated to add foo to the ocaml load path.
  - [-I foo -as bar] adds foo to the ocaml load path and adds foo to the coq load path with logical name bar (shortcut for -I foo -Q foo bar).

for more details: section "Customization at launch time" of the reference manual.

- Universe Polymorphism.
- Refinement, unification and tactics are now aware of universes, resulting in more localized errors. Universe inconsistencies should no more get raised at Qed time but during the proof. Unification always produces well-typed substitutions, hence some rare cases of unifications that succeeded while producing ill-typed terms before will now fail.
- The [change p with c] tactic semantics changed, now typechecking [c] at each matching occurrence [t] of the pattern [p], and converting [t] with [c].
- Template polymorphic inductive types: the partial application of a template polymorphic type (e.g. list) is not polymorphic. An explicit parameter application (e.g [fun A => list A]) or [apply (list \_)] will result in a polymorphic instance.
- The type inference algorithm now takes opacity of constants into account. This may have effects on tactics using type inference (e.g. induction). Extra "Transparent" might have to be added to revert opacity of constants.

## Type classes.

• When writing an Instance foo: Class A := {| proj := t |} (note the vertical bars), support for typechecking the projections using the type information and switching to proof mode is no longer available. Use { } (without the vertical bars) instead.

### Tactic abstract.

• Auxiliary lemmas generated by the abstract tactic are removed from the global environment and inlined in the proof term when a proof is ended with Qed. The behavior of 8.4 can be obtained by ending proofs with "Qed exporting" or "Qed exporting ident, ..., ident".

# 3.7.3 Details of changes in 8.5beta1

# Logic

• Primitive projections for records allow for a compact representation of projections, without parameters and avoid the behavior of defined projections that can unfold to a case expression. To turn the use of native projections on, use [Set Primitive Projections]. Record, Class and Structure types defined while this option is set will be defined with primitive projections instead of the usual encoding as a case expression. For compatibility, when p is a primitive projection, @p can be used to refer to the projection with explicit parameters, i.e. [@p] is definitionally equal to [λ params r. r.(p)]. Records with primitive projections have eta-conversion, the canonical form being [mkR pars (p1 t) ... (pn t)].

- New universe polymorphism (see reference manual)
- New option -type-in-type to collapse the universe hierarchy (this makes the logic inconsistent).
- The guard condition for fixpoints is now a bit stricter. Propagation of subterm value through pattern matching is restricted according to the return predicate. Restores compatibility of Coq's logic with the propositional extensionality axiom. May create incompatibilities in recursive programs heavily using dependent types.
- Trivial inductive types are no longer defined in Type but in Prop, which leads to a non-dependent induction principle being generated in place of the dependent one. To recover the old behavior, explicitly define your inductive types in Set.

## Vernacular commands

- A command "Variant" allows to define non-recursive variant types.
- The command "Record foo ..." does not generate induction principles (foo\_rect, foo\_rec, foo\_ind) anymore by default (feature wish #2693). The command "Variant foo ..." does not either. A flag "Set/Unset Nonrecursive Elimination Schemes" allows changing this. The tactic "induction" on a "Record" or a "Variant" is now actually doing "destruct".
- The "Open Scope" command can now be given also a delimiter (e.g. Z).
- The "Definition" command now allows the "Local" modifier, allowing for non-importable definitions. The same goes for "Axiom" and "Parameter".
- Section-specific commands such as "Let" (resp. "Variable", "Hypothesis") used out of a section now behave like the corresponding "Local" command, i.e. "Local Definition" (resp. "Local Parameter", "Local Axiom"). (potential source of rare incompatibilities).
- The "Let" command can now define local (co)fixpoints.
- Command "Search" has been renamed into "SearchHead". The command name "Search" now behaves like former "SearchAbout". The latter name is deprecated.
- "Search", "About", "SearchHead", "SearchRewrite" and "SearchPattern" now search for hypothesis (of the current goal by default) first. They now also support the goal selector prefix to specify another goal to search: e.g. "n:Search id". This is also true for SearchAbout although it is deprecated.
- The coq/user-contrib directory and the XDG directories are no longer recursively added to the load path, so files from installed libraries now need to be fully qualified for the "Require" command to find them. The tools/update-require script can be used to convert a development.
- A new Print Strategies command allows visualizing the opacity status of the whole engine.
- The "Locate" command now searches through all sorts of qualified namespaces of Coq: terms, modules, tactics, etc. The old behavior of the command can be retrieved using the "Locate Term" command.
- New "Derive" command to help writing program by derivation.
- New "Refine Instance Mode" option that allows to deactivate the generation of obligations in incomplete typeclass instances, raising an error instead.
- "Collection" command to name sets of section hypotheses. Named collections can be used in the syntax of "Proof using" to assert which section variables are used in a proof.
- The "Optimize Proof" command can be placed in the middle of a proof to force the compaction of the data structure used to represent the ongoing proof (evar map). This may result in a lower memory footprint and speed up the execution of the following tactics.
- "Optimize Heap" command to tell the OCaml runtime to perform a major garbage collection step and heap compaction.

3.7. Version 8.5 73

• Instance no longer treats the {|...|} syntax specially; it handles it in the same way as other commands, e.g. "Definition". Use the {...} syntax (no pipe symbols) to recover the old behavior.

## Specification Language

- Slight changes in unification error messages.
- Added a syntax \$(...)\$ that allows putting tactics in terms (may break user notations using "\$(", fixable by inserting a space or rewriting the notation).
- Constructors in pattern-matching patterns now respect the same rules regarding implicit arguments as in applicative position. The old behavior can be recovered by the command "Set Asymmetric Patterns". As a side effect, notations for constructors explicitly mentioning non-implicit parameters can now be used in patterns. Considering that the pattern language is already rich enough, binding local definitions is however now forbidden in patterns (source of incompatibilities for local definitions that delta-reduce to a constructor).
- Type inference algorithm now granting opacity of constants. This might also affect behavior of tactics (source of incompatibilities, solvable by re-declaring transparent constants which were set opaque).
- Existential variables are now referred to by an identifier and the relevant part of their instance is displayed by default. They can be reparsed. The naming policy is yet unstable and subject to changes in future releases.

## Tactics

- New tactic engine allowing dependent subgoals, fully backtracking (also known as multiple success) tactics, as well as tactics which can consider multiple goals together. In the new tactic engine, instantiation information of existential variables is always propagated to tactics, removing the need to manually use the "instantiate" tactics to mark propagation points.
  - New tactical (a+b) inserts a backtracking point. When (a+b);c fails during the execution of c, it can backtrack and try b instead of a.
  - New tactical (once a) removes all the backtracking points from a (i.e. it selects the first success of a).
  - Tactic "constructor" is now fully backtracking. In case of incompatibilities (e.g. combinatoric explosion), the former behavior of "constructor" can be retrieved by using instead "[> once constructor ..]". Thanks to backtracking, undocumented "constructor <tac>" syntax is now equivalent to "[> once (constructor; tac) ..]".
  - New "multimatch" variant of "match" tactic which backtracks to new branches in case of a later failure. The "match" tactic is equivalent to "once multimatch".
  - New selector "all:" such that "all:tac" applies tactic "tac" to all the focused goals, instead of just the first one as is the default.
  - A corresponding new option Set Default Goal Selector "all" makes the tactics in scripts be applied to all the focused goal by default
  - New selector "par:" such that "par:tac" applies the (terminating) tactic "tac" to all the focused goal in parallel. The number of worker can be selected with -async-proofs-tac-j and also limited using the coqworkmgr utility.
  - New tactics "revgoals", "cycle" and "swap" to reorder goals.
  - The semantics of recursive tactics (introduced with "Ltac t := ..." or "let rec t := ... in ...") changed slightly as t is now applied to every goal, not each goal independently. In particular it may be applied when no goals are left. This may cause tactics such as "let rec t := constructor;t" to loop indefinitely. The simple fix is to rewrite the recursive calls as follows: "let rec t := constructor;[t..]" which recovers the earlier behavior (source of rare incompatibilities).

- New tactic language feature "numgoals" to count number of goals. It is accompanied by a "guard" tactic which fails if a Boolean test over integers does not pass.
- New tactical "[> ... ]" to apply tactics to individual goals.
- New tactic "gfail" which works like "fail" except it will also fail if every goal has been solved.
- The refine tactic is changed not to use an ad hoc typing algorithm to generate subgoals. It also uses the dependent subgoal feature to generate goals to materialize every existential variable which is introduced by the refinement (source of incompatibilities).
- A tactic shelve is introduced to manage the subgoals which may be solved by unification: shelve removes every goal it is applied to from focus. These goals can later be called back into focus by the Unshelve command.
- A variant shelve\_unifiable only removes those goals which appear as existential variables in other goals. To emulate the old refine, use "refine c;shelve\_unifiable". This can still cause incompatibilities in rare occasions.
- New "give\_up" tactic to skip over a goal. A proof containing given up goals cannot be closed with "Qed", but only with "Admitted".
- The implementation of the admit tactic has changed: no axiom is generated for the admitted sub proof. "admit" is now an alias for "give\_up". Code relying on this specific behavior of "admit" can be made to work by:
  - Adding an "Axiom" for each admitted subproof.
  - Adding a single "Axiom proof\_admitted : False." and the Ltac definition "Ltac admit := case proof admitted.".
- Matching using "lazymatch" was fundamentally modified. It now behaves like "match" (immediate execution of the matching branch) but without the backtracking mechanism in case of failure.
- New "tryif t then u else v" tactical which executes "u" in case of success of "t" and "v" in case of failure.
- New conversion tactic "native\_compute": evaluates the goal (or an hypothesis) with a call-by-value strategy, using the OCaml native compiler. Useful on very intensive computations.
- New "cbn" tactic, a well-behaved simpl.
- Repeated identical calls to omega should now produce identical proof terms.
- Tactics btauto, a reflexive Boolean tautology solver.
- Tactic "tauto" was exceptionally able to destruct other connectives than the binary connectives "and", "or", "prod", "sum", "iff". This non-uniform behavior has been fixed (bug #2680) and tauto is slightly weaker (possible source of incompatibilities). On the opposite side, new tactic "dtauto" is able to destruct any record-like inductive types, superseding the old version of "tauto".
- Similarly, "intuition" has been made more uniform and, where it now fails, "dintuition" can be used (possible source of incompatibilities).
- New option "Unset Intuition Negation Unfolding" for deactivating automatic unfolding of "not" in intuition.
- Tactic notations can now be defined locally to a module (use "Local" prefix).
- Tactic "red" now reduces head beta-iota redexes (potential source of rare incompatibilities).
- Tactic "hnf" now reduces inner beta-iota redexes (potential source of rare incompatibilities).
- Tactic "intro H" now reduces beta-iota redexes if these hide a product (potential source of rare incompatibilities).

3.7. Version 8.5 75

- In Ltac matching on patterns of the form "\_ pat1 ... patn" now behaves like if matching on "?X pat1 ... patn", i.e. accepting "\_" to be instantiated by an applicative term (experimental at this stage, potential source of incompatibilities).
- In Ltac matching on goal, types of hypotheses are now interpreted in the %type scope (possible source of incompatibilities).
- "change ... in ..." and "simpl ... in ..." now properly consider nested occurrences (possible source of incompatibilities since this alters the numbering of occurrences), but do not support nested occurrences.
- Tactics simpl, vm\_compute and native\_compute can be given a notation string to a constant as argument.
- When given a reference as argument, simpl, vm\_compute and native\_compute now strictly interpret it as the head of a pattern starting with this reference.
- The "change p with c" tactic semantics changed, now type-checking "c" at each matching occurrence "t" of the pattern "p", and converting "t" with "c".
- Now "approntext" and "context" behave the same. The old buggy behavior of "context" can be retrieved at parse time by setting the "Tactic Compat Context" flag (possible source of incompatibilities).
- New introduction pattern p/c which applies lemma c on the fly on the hypothesis under consideration before continuing with introduction pattern p.
- New introduction pattern [= x1 .. xn] applies "injection as [x1 .. xn]" on the fly if injection is applicable to the hypothesis under consideration (idea borrowed from Georges Gonthier). Introduction pattern [=] applies "discriminate" if a discriminable equality.
- New introduction patterns \* and \*\* to respectively introduce all forthcoming dependent variables and all variables/hypotheses dependent or not.
- Tactic "injection c as ipats" now clears c if c refers to an hypothesis and moves the resulting equations in the hypotheses independently of the number of ipats, which has itself to be less than the number of new hypotheses (possible source of incompatibilities; former behavior obtainable by "Unset Injection L2R Pattern Order").
- Tactic "injection" now automatically simplifies subgoals "existT n p = existT n p" into "p = p" when "n" is in an inductive type for which a decidable equality scheme has been generated with "Scheme Equality" (possible source of incompatibilities).
- New tactic "rewrite\_strat" for generalized rewriting with user-defined strategies, subsuming autorewrite.
- Injection can now also deduce equality of arguments of sort Prop, by using the option "Set Injection On Proofs" (disabled by default). Also improved the error messages.
- Tactic "subst id" now supports id occurring in dependent local definitions.
- Bugs fixed about intro-pattern "\*" might lead to some rare incompatibilities.
- New tactical "time" to display time spent executing its argument.
- Tactics referring or using a constant dependent in a section variable which has been cleared or renamed in the current goal context now fail (possible source of incompatibilities solvable by avoiding clearing the relevant hypotheses).
- New construct "uconstr:c" and "type term c" to build untyped terms.
- Binders in terms defined in Ltac (either "constr" or "uconstr") can now take their names from identifiers defined in Ltac. As a consequence, a name cannot be used in a binder "constr:(fun x => ...)" if an Ltac variable of that name already exists and does not contain an identifier. Source of occasional incompatibilities.

- The "refine" tactic now accepts untyped terms built with "uconstr" so that terms with holes can be constructed piecewise in Ltac.
- New bullets -, ++, , —, +++, \*, ... made available.
- More informative messages when wrong bullet is used.
- Bullet suggestion when a subgoal is solved.
- New tactic "enough", symmetric to "assert", but with subgoals swapped, as a more friendly replacement
  of "cut".
- In destruct/induction, experimental modifier "!" prefixing the hypothesis name to tell not erasing the hypothesis.
- Bug fixes in "inversion as" may occasionally lead to incompatibilities.
- Behavior of introduction patterns -> and <- made more uniform (hypothesis is cleared, rewrite in hypotheses and conclusion and erasing the variable when rewriting a variable).
- New experimental option "Set Standard Proposition Elimination Names" so that case analysis or induction on schemes in Type containing propositions now produces "H"-based names.
- Tactics from plugins are now active only when the corresponding module is imported (source of incompatibilities, solvable by adding an "Import"; in the particular case of Omega, use "Require Import OmegaTactic").
- Semantics of destruct/induction has been made more regular in some edge cases, possibly leading to incompatibilities:
  - new goals are now opened when the term does not match a subterm of the goal and has unresolved holes, while in 8.4 these holes were turned into existential variables
  - when no "at" option is given, the historical semantics which selects all subterms syntactically
    identical to the first subterm matching the given pattern is used
  - non-dependent destruct/induction on an hypothesis with premises in an inductive type with indices is fixed
  - residual local definitions are now correctly removed.
- The rename tactic may now replace variables in parallel.
- A new "Info" command replaces the "info" tactical discontinued in v8.4. It still gives informative results in many cases.
- The "info\_auto" tactic is known to be broken and does not print a trace anymore. Use "Info 1 auto" instead. The same goes for "info\_trivial". On the other hand "info\_eauto" still works fine, while "Info 1 eauto" prints a trivial trace.
- When using a lemma of the prototypical form "forall A, {a:A & P a}", "apply" and "apply in" do not instantiate anymore "A" with the current goal and use "a" as the proof, as they were sometimes doing, now considering that it is a too powerful decision.

# Program

- "Solve Obligations using" changed to "Solve Obligations with", consistent with "Proof with".
- Program Lemma, Definition now respect automatic introduction.
- Program Lemma, Definition, etc.. now interpret "->" like Lemma and Definition as a non-dependent arrow (potential source of incompatibility).
- Add/document "Set Hide Obligations" (to hide obligations in the final term inside an implicit argument) and "Set Shrink Obligations" (to minimize dependencies of obligations defined by tactics).

3.7. Version 8.5

# Notations

- The syntax "x -> y" is now declared at level 99. In particular, it has now a lower priority than "<->": "A -> B <-> C" is now "A -> (B <-> C)" (possible source of incompatibilities)
- Notations accept term-providing tactics using the \$(...)\$ syntax.
- "Bind Scope" can no longer bind "Funclass" and "Sortclass".
- A notation can be given a (compat "8.x") annotation, making it behave like a "only parsing" notation, but the annotation may lead to eventually issue warnings or errors in further versions when this notation is used.
- More systematic insertion of spaces as a default for printing notations ("format" still available to override the default).
- In notations, a level modifier referring to a non-existent variable is now considered an error rather than silently ignored.

### Tools

- Option -I now only adds directories to the ml path.
- Option -Q behaves as -R, except that the logical path of any loaded file has to be fully qualified.
- Option -R no longer adds recursively to the ml path; only the root directory is added. (Behavior with respect to the load path is unchanged.)
- Option -nois prevents coq/theories and coq/plugins to be recursively added to the load path. (Same behavior as with coq/user-contrib.)
- coqdep accepts a -dumpgraph option generating a dot file.
- Makefiles generated through coq\_makefile have three new targets "quick" "checkproofs" and "vio2vo", allowing respectively to asynchronously compile the files without playing the proof scripts, asynchronously checking that the quickly generated proofs are correct and generating the object files from the quickly generated proofs.
- The XML plugin was discontinued and removed from the source.
- A new utility called coqworkmgr can be used to limit the number of concurrent workers started by independent processes, like make and CoqIDE. This is of interest for users of the par: goal selector.

## Interfaces

- CoqIDE supports asynchronous edition of the document, ongoing tasks and errors are reported in the bottom right window. The number of workers taking care of processing proofs can be selected with -async-proofs-j.
- CoqIDE highlights in yellow "unsafe" commands such as axiom declarations, and tactics like "give up".
- CoqIDE supports Proof General like key bindings; to activate the PG mode go to Edit -> Preferences -> Editor. For the documentation see Help -> Help for PG mode.
- CoqIDE automatically retracts the locked area when one edits the locked text.
- CoqIDE search and replace got regular expressions power. See the documentation of OCaml's Str module for the supported syntax.
- Many CoqIDE windows, including the query one, are now detachable to improve usability on multi screen work stations.
- Coqtop/coqc outputs highlighted syntax. Colors can be configured thanks to the COQ\_COLORS environment variable, and their current state can be displayed with the -list-tags command line option.

• Third party user interfaces can install their main loop in \$COQLIB/toploop and call coqtop with the -toploop flag to select it.

#### Internal Infrastructure

- Many reorganizations in the ocaml source files. For instance, many internal a.s.t. of Coq are now placed in mli files in a new directory intf/, for instance constrexpr.mli or glob\_term.mli. More details in dev/doc/changes.
- The file states/initial.coq does not exist anymore. Instead, coqtop initially does a "Require" of Prelude.vo (or nothing when given the options -noinit or -nois).
- The format of vo files has slightly changed: cf final comments in checker/cic.mli.
- The build system does not produce anymore programs named coqtop.opt and a symbolic link to coqtop. Instead, coqtop is now directly an executable compiled with the best OCaml compiler available. The bytecode program coqtop.byte is still produced. Same for other utilities.
- Some options of the ./configure script slightly changed:
  - The -coqrumbyteflags and its blank-separated argument is replaced by option -vmbyteflags which expects a comma-separated argument.
  - The -coqtoolsbyteflags option is discontinued, see -no-custom instead.

## Miscellaneous

• ML plugins now require a "DECLARE PLUGIN "foo" statement. The "foo" name must be exactly the name of the ML module that will be loaded through a "Declare ML "foo" command.

# 3.7.4 Details of changes in 8.5beta2

## Logic

The VM now supports inductive types with up to 8388851 non-constant constructors and up to 8388607 constant ones.

## Specification language

• Syntax "\$(tactic)\$" changed to "ltac: tactic".

## Tactics

- A script using the admit tactic can no longer be concluded by either Qed or Defined. In the first case, Admitted can be used instead. In the second case, a subproof should be used.
- The easy tactic and the now tactical now have a more predictable behavior, but they might now discharge some previously unsolved goals.

### Extraction

- Definitions extracted to Haskell GHC should no longer randomly segfault when some Coq types cannot be represented by Haskell types.
- Definitions can now be extracted to Json for post-processing.

# Tools

- Option -I -as has been removed, and option -R -as has been deprecated. In both cases, option -R can be used instead.
- coq makefile now generates double-colon rules for rules such as clean.

## API

3.7. Version 8.5

• The interface of [change] has changed to take a [change\_arg], which can be built from a [constr] using [make\_change\_arg].

# 3.7.5 Details of changes in 8.5beta3

## Vernacular commands

- New command "Redirect" to redirect the output of a command to a file.
- New command "Undelimit Scope" to remove the delimiter of a scope.
- New option "Strict Universe Declaration", set by default. It enforces the declaration of all polymorphic universes appearing in a definition when introducing it.
- New command "Show id" to show goal named id.
- Option "Virtual Machine" removed.

## Tactics

- New flag "Regular Subst Tactic" which fixes "subst" in situations where it failed to substitute all substitutable equations or failed to simplify cycles, or accidentally unfolded local definitions (flag is off by default).
- New flag "Loose Hint Behavior" to handle hints loaded but not imported in a special way. It accepts three distinct flags: \* "Lax", which is the default one, sets the old behavior, i.e. a non-imported hint behaves the same as an imported one. \* "Warn" outputs a warning when a non-imported hint is used. Note that this is an over-approximation, because a hint may be triggered by an eauto run that will eventually fail and backtrack. \* "Strict" changes the behavior of an unloaded hint to the one of the fail tactic, allowing to emulate the hopefully future import-scoped hint mechanism.
- New compatibility flag "Universal Lemma Under Conjunction" which let tactics working under conjunctions apply sublemmas of the form "forall A, ... -> A".
- New compatibility flag "Bracketing Last Introduction Pattern" which can be set so that the last disjunctive-conjunctive introduction pattern given to "intros" automatically complete the introduction of its subcomponents, as the disjunctive-conjunctive introduction patterns in non-terminal position already do.
- New flag "Shrink Abstract" that minimalizes proofs generated by the abstract tactical w.r.t. variables appearing in the body of the proof.

### Program

- The "Shrink Obligations" flag now applies to all obligations, not only those solved by the automatic tactic.
- Importing Program no longer overrides the "exists" tactic (potential source of incompatibilities).
- Hints costs are now correctly taken into account (potential source of incompatibilities).
- Documented the Hint Cut command that allows control of the proof-search during typeclass resolution (see reference manual).

## API

- Some functions from pretyping/typing.ml and their derivatives were potential source of evarmap leaks, as they dropped their resulting evarmap. The situation was clarified by renaming them according to a unsafe\_\* scheme. Their sound variant is likewise renamed to their old name. The following renamings were made.
  - Typing.type\_of -> unsafe\_type\_of

- Typing.e\_type\_of -> type\_of
- A new e\_type\_of function that matches the e\_ prefix policy
- Tacmach.pf\_type\_of -> pf\_unsafe\_type\_of
- A new safe pf\_type\_of function.

All uses of unsafe\_\* functions should be eventually eliminated.

#### Tools

- Added an option -w to control the output of coqtop warnings.
- Configure now takes an optional -native-compiler (yes|no) flag replacing -no-native-compiler. The new flag is set to no by default under Windows.
- Flag -no-native-compiler was removed and became the default for coqc. If precompilation of files for native conversion test is desired, use -native-compiler.
- The -compile command-line option now takes the full path of the considered file, including the ".v" extension, and outputs a warning if such an extension is lacking.
- The -require and -load-vernac-object command-line options now take a logical path of a given library rather than a physical path, thus they behave like Require [Import] path.
- The -vm command-line option has been removed.

## Standard Library

• There is now a Coq.Compat.Coq84 library, which sets the various compatibility options and does a few redefinitions to make Coq behave more like Coq v8.4. The standard way of putting Coq in v8.4 compatibility mode is to pass the command line flags "-require Coq.Compat.Coq84 -compat 8.4".

# 3.7.6 Details of changes in 8.5

# Tools

• Flag "-compat 8.4" now loads Coq.Compat.Coq84. The standard way of putting Coq in v8.4 compatibility mode is to pass the command line flag "-compat 8.4". It can be followed by "-require Coq.Compat.AdmitAxiom" if the 8.4 behavior of admit is needed, in which case it uses an axiom.

### Specification language

• Syntax "\$(tactic)\$" changed to "ltac:(tactic)".

## Tactics

- Syntax "destruct !hyp" changed to "destruct (hyp)", and similarly for induction (rare source of incompatibilities easily solvable by removing parentheses around "hyp" when not for the purpose of keeping the hypothesis).
- Syntax "p/c" for on-the-fly application of a lemma c before introducing along pattern p changed to p%c1..%cn. The feature and syntax are in experimental stage.
- "Proof using" does not clear unused section variables.
- Tactic "refine" has been changed back to the 8.4 behavior of shelving subgoals that occur in other subgoals. The "refine" tactic of 8.5beta3 has been renamed "simple refine"; it does not shelve any subgoal.
- New tactical "unshelve tac" which grab existential variables put on the tactic shelve by the execution of "tac".

3.7. Version 8.5

# 3.7.7 Details of changes in 8.5pl1

## Critical bugfix

• The subterm relation for the guard condition was incorrectly defined on primitive projections (#4588)

## Plugin development tools

• add a .merlin target to the makefile

Various performance improvements (time, space used by .vo files)

## Other bugfixes

- Fix order of arguments to Big.compare case in ExtrOcamlZBigInt.v
- Added compatibility coercions from Specif.v which were present in Coq 8.4.
- Fixing a source of inefficiency and an artificial dependency in the printer in the congruence tactic.
- Allow to unset the refinement mode of Instance in ML
- Fixing an incorrect use of prod\_apprect on a term which was not a product in setoid\_rewrite.
- Add -compat 8.4 econstructor tactics, and tests
- Add compatibility Nonrecursive Elimination Schemes
- Fixing the "No applicable tactic" non informative error message regression on apply.
- Univs: fix get\_current\_context (bug #4603, part I)
- Fix a bug in Program coercion code
- Fix handling of arity of definitional classes.
- #4630: Some tactics are 20x slower in 8.5 than 8.4.
- #4627: records with no declared arity can be template polymorphic.
- #4623: set tactic too weak with universes (regression)
- Fix incorrect behavior of CS resolution
- #4591: Uncaught exception in directory browsing.
- CogIDE is more resilient to initialization errors.
- #4614: "Fully check the document" is uninterruptible.
- Try eta-expansion of records only on non-recursive ones
- Fix bug when a sort is ascribed to a Record
- Primitive projections: protect kernel from erroneous definitions.
- Fixed bug #4533 with previous Keyed Unification commit
- Win: kill unreliable hence do not waitpid after kill -9 (Close #4369)
- Fix strategy of Keyed Unification
- #4608: Anomaly "output value: abstract value (outside heap)".
- #4607: do not read native code files if native compiler was disabled.
- #4105: poor escaping in the protocol between CoqIDE and coqtop.
- #4596: [rewrite] broke in the past few weeks.
- #4533 (partial): respect declared global transparency of projections in unification.ml

- #4544: Backtrack on using full betaiota reduction during keyed unification.
- #4540: CoqIDE bottom progress bar does not update.
- Fix regression from 8.4 in reflexivity
- #4580: [Set Refine Instance Mode] also used for Program Instance.
- #4582: cannot override notation [x]. MAY CREATE INCOMPATIBILITIES, see #4683.
- STM: Print/Extraction have to be skipped if -quick
- #4542: CoqIDE: STOP button also stops workers
- STM: classify some variants of Instance as regular "Fork nodes.
- #4574: Anomaly: Uncaught exception Invalid\_argument("splay\_arity").
- Do not give a name to anonymous evars anymore. See bug #4547.
- STM: always stock in vio files the first node (state) of a proof
- STM: not delegate proofs that contain Vernac(Module|Require|Import), #4530
- Don't fail fatally if PATH is not set.
- #4537: Coq 8.5 is slower in typeclass resolution.
- #4522: Incorrect "Warning..." on windows.
- #4373: cogdep does not know about .vio files.
- #3826: "Incompatible module types" is uninformative.
- #4495: Failed assertion in metasyntax.ml.
- #4511: evar tactic can create non-typed evars.
- #4503: mixing universe polymorphic and monomorphic variables and definitions in sections is unsupported.
- #4519: oops, global shadowed local universe level bindings.
- #4506: Anomaly: File "pretyping/indrec.ml", line 169, characters 14-20: Assertion failed.
- #4548: Coqide crashes when going back one command

# 3.7.8 Details of changes in 8.5pl2

# Critical bugfix

- Checksums of .vo files dependencies were not correctly checked.
- Unicode-to-ASCII translation was not injective, leading in a soundness bug in the native compiler.

## Other bugfixes

- #4097: more efficient occur-check in presence of primitive projections
- #4398: type scope used consistently in "match goal".
- #4450: eauto does not work with polymorphic lemmas
- #4677: fix alpha-conversion in notations needing eta-expansion.
- Fully preserve initial order of hypotheses in "Regular Subst Tactic" mode.
- #4644: a regression in unification.

3.7. Version 8.5

- #4725: Function (Error: Conversion test raised an anomaly) and Program (Error: Cannot infer this placeholder of type)
- #4747: Problem building Coq 8.5pl1 with OCaml 4.03.0: Fatal warnings
- #4752: CoqIDE crash on files not ended by ".v".
- #4777: printing inefficiency with implicit arguments
- #4818: "Admitted" fails due to undefined universe anomaly after calling "destruct"
- #4823: remote counter: avoid thread race on sockets
- #4841: -verbose flag changed semantics in 8.5, is much harder to use
- #4851: [nsatz] cannot handle duplicated hypotheses
- #4858: Anomaly: Uncaught exception Failure("hd"). Please report. in variant of nsatz
- #4880: [nsatz\_compute] generates invalid certificates if given redundant hypotheses
- #4881: synchronizing "Declare Implicit Tactic" with backtrack.
- #4882: anomaly with Declare Implicit Tactic on hole of type with evars
- Fix use of "Declare Implicit Tactic" in refine. triggered by CoqIDE
- #4069, #4718: congruence fails when universes are involved.

### Universes

- Disallow silently dropping universe instances applied to variables (forward compatible)
- Allow explicit universe instances on notations, when they can apply to the head reference of their expansion.

# Build infrastructure

• New update on how to find camlp5 binary and library at configure time.

# 3.7.9 Details of changes in 8.5pl3

### Critical bugfix

• #4876: Guard checker incompleteness when using primitive projections

### Other bugfixes

- #4780: Induction with universe polymorphism on was creating ill-typed terms.
- #4673: regression in setoid\_rewrite, unfolding let-ins for type unification.
- #4754: Regression in setoid\_rewrite, allow postponed unification problems to remain.
- #4769: Anomaly with universe polymorphic schemes defined inside sections.
- #3886: Program: duplicate obligations of mutual fixpoints.
- #4994: Documentation typo.
- #5008: Use the "md5" command on OpenBSD.
- #5007: Do not assume the "TERM" environment variable is always set.
- #4606: Output a break before a list only if there was an empty line.
- #5001: metas not cleaned properly in clenv\_refine\_in.
- #2336: incorrect glob data for module symbols (bug #2336).

- #4832: Remove extraneous dot in error message.
- Anomaly in printing a unification error message.
- #4947: Options which take string arguments are not backwards compatible.
- #4156: micromega cache files are now hidden files.
- #4871: interrupting par:abstract kills coqtop.
- #5043: [Admitted] lemmas pick up section variables.
- Fix name of internal refine ("simple refine").
- #5062: probably a typo in Strict Proofs mode.
- #5065: Anomaly: Not a proof by induction.
- Restore native compiler optimizations, they were disabled since 8.5!
- #5077: failure on typing a fixpoint with evars in its type.
- Fix recursive notation bug.
- #5095: non relevant too strict test in let-in abstraction.
- Ensuring that the evar name is preserved by "rename".
- #4887: confusion between using and with in documentation of firstorder.
- Bug in subst with let-ins.
- #4762: eauto weaker than auto.
- Remove if\_then\_else (was buggy). Use tryif instead.
- #4970: confusion between special "{" and non special "{{" in notations.
- #4529: primitive projections unfolding.
- #4416: Incorrect "Error: Incorrect number of goals".
- #4863: abstract in typeclass hint fails.
- #5123: unshelve can impact typeclass resolution
- Fix a collision about the meta-variable ".." in recursive notations.
- Fix printing of info auto.
- #3209: Not\_found due to an occur-check cycle.
- #5097: status of evars refined by "clear" in ltac: closed wrt evars.
- #5150: Missing dependency of the test-suite subsystems in prerequisite.
- Fix a bug in error printing of unif constraints
- #3941: Do not stop propagation of signals when Coq is busy.
- #4822: Incorrect assertion in cbn.
- #3479 parsing of "{" and "}" when a keyword starts with "{" or "}".
- #5127: Memory corruption with the VM.
- #5102: bullets parsing broken by calls to parse\_entry.

Various documentation improvements

3.7. Version 8.5

# 3.8 Version 8.4

# 3.8.1 Summary of changes

Coq version 8.4 contains the result of three long-term projects: a new modular library of arithmetic by Pierre Letouzey, a new proof engine by Arnaud Spiwack and a new communication protocol for CoqIDE by Vincent Gross.

The new modular library of arithmetic extends, generalizes and unifies the existing libraries on Peano arithmetic (types nat, N and BigN), positive arithmetic (type positive), integer arithmetic (Z and BigZ) and machine word arithmetic (type Int31). It provides with unified notations (e.g. systematic use of add and mul for denoting the addition and multiplication operators), systematic and generic development of operators and properties of these operators for all the types mentioned above, including gcd, pcm, power, square root, base 2 logarithm, division, modulo, bitwise operations, logical shifts, comparisons, iterators, ...

The most visible feature of the new proof engine is the support for structured scripts (bullets and proof brackets) but, even if yet not user-available, the new engine also provides the basis for refining existential variables using tactics, for applying tactics to several goals simultaneously, for reordering goals, all features which are planned for the next release. The new proof engine forced Pierre Letouzey to reimplement info and Show Script differently.

Before version 8.4, CoqIDE was linked to Coq with the graphical interface living in a separate thread. From version 8.4, CoqIDE is a separate process communicating with Coq through a textual channel. This allows for a more robust interfacing, the ability to interrupt Coq without interrupting the interface, and the ability to manage several sessions in parallel. Relying on the infrastructure work made by Vincent Gross, Pierre Letouzey, Pierre Boutillier and Pierre-Marie Pédrot contributed many various refinements of CoqIDE.

Coq 8.4 also comes with a bunch of various smaller-scale changes and improvements regarding the different components of the system.

The underlying logic has been extended with  $\eta$ -conversion thanks to Hugo Herbelin, Stéphane Glondu and Benjamin Grégoire. The addition of  $\eta$ -conversion is justified by the confidence that the formulation of the Calculus of Inductive Constructions based on typed equality (such as the one considered in Lee and Werner to build a set-theoretic model of CIC /LW11/) is applicable to the concrete implementation of Coq.

The underlying logic benefited also from a refinement of the guard condition for fixpoints by Pierre Boutillier, the point being that it is safe to propagate the information about structurally smaller arguments through  $\beta$ -redexes that are blocked by the "match" construction (blocked commutative cuts).

Relying on the added permissiveness of the guard condition, Hugo Herbelin could extend the pattern matching compilation algorithm so that matching over a sequence of terms involving dependencies of a term or of the indices of the type of a term in the type of other terms is systematically supported.

Regarding the high-level specification language, Pierre Boutillier introduced the ability to give implicit arguments to anonymous functions, Hugo Herbelin introduced the ability to define notations with several binders (e.g. exists x y z, P), Matthieu Sozeau made the typeclass inference mechanism more robust and predictable, Enrico Tassi introduced a command Arguments that generalizes Implicit Arguments and Arguments Scope for assigning various properties to arguments of constants. Various improvements in the type inference algorithm were provided by Matthieu Sozeau and Hugo Herbelin with contributions from Enrico Tassi.

Regarding tactics, Hugo Herbelin introduced support for referring to expressions occurring in the goal by pattern in tactics such as set or destruct. Hugo Herbelin also relied on ideas from Chung-Kil Hur's Heq plugin to introduce automatic computation of occurrences to generalize when using destruct and induction on types with indices. Stéphane Glondu introduced new tactics  $constr_eq$ ,  $is_evar$ , and  $has_evar$ , to be used when writing complex tactics. Enrico Tassi added support to fine-tuning the behavior of simpl. Enrico Tassi added the ability to specify over which variables of a section a lemma has to be exactly generalized.

Pierre Letouzey added a tactic timeout and the interruptibility of  $vm_compute$ . Bug fixes and miscellaneous improvements of the tactic language came from Hugo Herbelin, Pierre Letouzey and Matthieu Sozeau.

Regarding decision tactics, Loïc Pottier maintained nsatz, moving in particular to a typeclass based reification of goals while Frédéric Besson maintained Micromega, adding in particular support for division.

Regarding vernacular commands, Stéphane Glondu provided new commands to analyze the structure of type universes.

Regarding libraries, a new library about lists of a given length (called vectors) has been provided by Pierre Boutillier. A new instance of finite sets based on Red-Black trees and provided by Andrew Appel has been adapted for the standard library by Pierre Letouzey. In the library of real analysis, Yves Bertot changed the definition of  $\pi$  and provided a proof of the long-standing fact yet remaining unproved in this library, namely that  $\sin \frac{\pi}{2} = 1$ .

Pierre Corbineau maintained the Mathematical Proof Language (C-zar).

Bruno Barras and Benjamin Grégoire maintained the call-by-value reduction machines.

The extraction mechanism benefited from several improvements provided by Pierre Letouzey.

Pierre Letouzey maintained the module system, with contributions from Élie Soubiran.

Julien Forest maintained the Function command.

Matthieu Sozeau maintained the setoid rewriting mechanism.

Coq related tools have been upgraded too. In particular, coq\_makefile has been largely revised by Pierre Boutillier. Also, patches from Adam Chlipala for coqdoc have been integrated by Pierre Boutillier.

Bruno Barras and Pierre Letouzey maintained the coqchk checker.

Pierre Courtieu and Arnaud Spiwack contributed new features for using Coq through Proof General.

The Dp plugin has been removed. Use the plugin provided with Why 3 instead (http://why3.lri.fr/).

Under the hood, the Coq architecture benefited from improvements in terms of efficiency and robustness, especially regarding universes management and existential variables management, thanks to Pierre Letouzey and Yann Régis-Gianas with contributions from Stéphane Glondu and Matthias Puech. The build system is maintained by Pierre Letouzey with contributions from Stéphane Glondu and Pierre Boutillier.

A new backtracking mechanism simplifying the task of external interfaces has been designed by Pierre Letouzey.

The general maintenance was done by Pierre Letouzey, Hugo Herbelin, Pierre Boutillier, Matthieu Sozeau and Stéphane Glondu with also specific contributions from Guillaume Melquiond, Julien Narboux and Pierre-Marie Pédrot.

Packaging tools were provided by Pierre Letouzey (Windows), Pierre Boutillier (MacOS), Stéphane Glondu (Debian). Releasing, testing and benchmarking support was provided by Jean-Marc Notin.

Many suggestions for improvements were motivated by feedback from users, on either the bug tracker or the Coq-Club mailing list. Special thanks are going to the users who contributed patches, starting with Tom Prince. Other patch contributors include Cédric Auger, David Baelde, Dan Grayson, Paolo Herms, Robbert Krebbers, Marc Lasson, Hendrik Tews and Eelis van der Weegen.

Paris, December 2011 Hugo Herbelin

3.8. Version 8.4 87

# 3.8.2 Potential sources of incompatibilities

The main known incompatibilities between 8.3 and 8.4 are consequences of the following changes:

• The reorganization of the library of numbers:

Several definitions have new names or are defined in modules of different names, but a special care has been taken to have this renaming transparent for the user thanks to compatibility notations.

However some definitions have changed, what might require some adaptations. The most noticeable examples are:

- The "?=" notation which now bind to Pos.compare rather than former Pcompare (now Pos.compare cont).
- Changes in names may induce different automatically generated names in proof scripts (e.g. when issuing "destruct Z\_le\_gt\_dec").
- Z.add has a new definition, hence, applying "simpl" on subterms of its body might give different results than before.
- BigN.shiftl and BigN.shiftr have reversed arguments order, the power function in BigN now takes two BigN.
- Other changes in libraries:
  - The definition of functions over "vectors" (list of fixed length) have changed.
  - TheoryList.v has been removed.
- Slight changes in tactics:
  - Less unfolding of fixpoints when applying destruct or inversion on a fixpoint hiding an inductive type (add an extra call to simpl to preserve compatibility).
  - Less unexpected local definitions when applying "destruct" (incompatibilities solvable by adapting name hypotheses).
  - Tactic "apply" might succeed more often, e.g. by now solving pattern-matching of the form ?f x y = g(x,y) (compatibility ensured by using "Unset Tactic Pattern Unification"), but also because it supports (full) betaiota (using "simple apply" might then help).
  - Tactic autorewrite does no longer instantiate pre-existing existential variables.
  - Tactic "info" is now available only for auto, eauto and trivial.
- Miscellaneous changes:
  - The command "Load" is now atomic for backtracking (use "Unset Atomic Load" for compatibility).

# 3.8.3 Details of changes in 8.4beta

Logic

- Standard eta-conversion now supported (dependent product only).
- Guard condition improvement: subterm property is propagated through beta-redex blocked by pattern-matching, as in "(match v with C .. => fun x => u end) x"; this allows for instance to use "rewrite ... in ..." without breaking the guard condition.

Specification language and notations

- Maximal implicit arguments can now be set locally by { }. The registration traverses fixpoints and lambdas. Because there is conversion in types, maximal implicit arguments are not taken into account in partial applications (use eta expanded form with explicit { } instead).
- Added support for recursive notations with binders (allows for instance to write "exists x y z, P").
- Structure/Record printing can be disable by "Unset Printing Records". In addition, it can be controlled on type by type basis using "Add Printing Record" or "Add Printing Constructor".
- Pattern-matching compilation algorithm: in "match x, y with ... end", possible dependencies of x (or of the indices of its type) in the type of y are now taken into account.

### Tactics

- New proof engine.
- Scripts can now be structured thanks to bullets \* + and to subgoal delimitation via { }. Note: for use with Proof General, a cvs version of Proof General no older than mid-July 2011 is currently required.
- Support for tactical "info" is suspended.
- Support for command "Show Script" is suspended.
- New tactics constr\_eq, is\_evar and has\_evar for use in Ltac (DOC TODO).
- Removed the two-argument variant of "decide equality".
- New experimental tactical "timeout < n > < tac >". Since < n > is a time in second for the moment, this feature should rather be avoided in scripts meant to be machine-independent.
- Fix in "destruct": removal of unexpected local definitions in context might result in some rare incompatibilities (solvable by adapting name hypotheses).
- Introduction pattern "\_" made more robust.
- Tactic (and Eval command) vm\_compute can now be interrupted via Ctrl-C.
- Unification in "apply" supports unification of patterns of the form ?f x y = g(x,y) (compatibility ensured by using "Unset Tactic Pattern Unification"). It also supports (full) betaiota.
- Tactic autorewrite does no longer instantiate pre-existing existential variables (theoretical source of possible incompatibilities).
- Tactic "dependent rewrite" now supports equality in "sig".
- Tactic omega now understands Zpred (wish #1912) and can prove any goal from a context containing an arithmetical contradiction (wish #2236).
- Using "auto with nocore" disables the use of the "core" database (wish #2188). This pseudo-database "nocore" can also be used with trivial and eauto.
- Tactics "set", "destruct" and "induction" accepts incomplete terms and use the goal to complete the pattern assuming it is non ambiguous.
- When used on arguments with a dependent type, tactics such as "destruct", "induction", "case", "elim", etc. now try to abstract automatically the dependencies over the arguments of the types (based on initial ideas from Chung-Kil Hur, extension to nested dependencies suggested by Dan Grayson)
- Tactic "injection" now failing on an equality showing no constructors while it was formerly generalizing again the goal over the given equality.
- In Ltac, the "context [...]" syntax has now a variant "appropriate [...]" allowing to match partial applications in larger applications.

3.8. Version 8.4 89

- When applying destruct or inversion on a fixpoint hiding an inductive type, recursive calls to the fixpoint now remain folded by default (rare source of incompatibility generally solvable by adding a call to simpl).
- In an ltac pattern containing a "match", a final "| \_ => \_" branch could be used now instead of enumerating all remaining constructors. Moreover, the pattern "match \_ with \_ => \_ end" now allows to match any "match". A "in" annotation can also be added to restrict to a precise inductive type.
- The behavior of "simpl" can be tuned using the "Arguments" vernacular. In particular constants can be marked so that they are always/never unfolded by "simpl", or unfolded only when a set of arguments evaluates to a constructor. Last one can mark a constant so that it is unfolded only if the simplified term does not expose a match in head position.

#### Vernacular commands

- It is now mandatory to have a space (or tabulation or newline or end-of-file) after a "." ending a sentence.
- In SearchAbout, the [ ] delimiters are now optional.
- New command "Add/Remove Search Blacklist <substring> ...": a Search or SearchAbout or similar query will never mention lemmas whose qualified names contain any of the declared substrings. The default blacklisted substrings are \_subproof, Private\_.
- When the output file of "Print Universes" ends in ".dot" or ".gv", the universe graph is printed in the DOT language, and can be processed by Graphviz tools.
- New command "Print Sorted Universes".
- The undocumented and obsolete option "Set/Unset Boxed Definitions" has been removed, as well as syntaxes like "Boxed Fixpoint foo".
- A new option "Set Default Timeout n / Unset Default Timeout".
- Qed now uses information from the reduction tactics used in proof script to avoid conversion at Qed time to go into a very long computation.
- New command "Show Goal ident" to display the statement of a goal, even a closed one (available from Proof General).
- Command "Proof" accept a new modifier "using" to force generalization over a given list of section variables at section ending (DOC TODO).
- New command "Arguments" generalizing "Implicit Arguments" and "Arguments Scope" and that also allows to rename the parameters of a definition and to tune the behavior of the tactic "simpl".

### Module System

- During subtyping checks, an opaque constant in a module type could now be implemented by anything of the right type, even if bodies differ. Said otherwise, with respect to subtyping, an opaque constant behaves just as a parameter. Coqchk was already implementing this, but not coqtop.
- The inlining done during application of functors can now be controlled more precisely, by the annotations (no inline) or (inline at level XX). With the latter annotation, only functor parameters whose levels are lower or equal than XX will be inlined. The level of a parameter can be fixed by "Parameter Inline(30) foo". When levels aren't given, the default value is 100. One can also use the flag "Set Inline Level ..." to set a level (DOC TODO).
- Print Assumptions should now handle correctly opaque modules (#2168).
- Print Module (Type) now tries to print more details, such as types and bodies of the module elements. Note that Print Module Type could be used on a module to display only its interface. The option "Set

Short Module Printing" could be used to switch back to the earlier behavior were only field names were displayed.

#### Libraries

- Extension of the abstract part of Numbers, which now provide axiomatizations and results about many more integer functions, such as pow, gcd, lcm, sqrt, log2 and bitwise functions. These functions are implemented for nat, N, BigN, Z, BigZ. See in particular file NPeano for new functions about nat.
- The definition of types positive, N, Z is now in file BinNums.v
- Major reorganization of ZArith. The initial file ZArith/BinInt.v now contains an internal module Z implementing the Numbers interface for integers. This module Z regroups:
  - all functions over type Z : Z.add, Z.mul, ...
  - the minimal proofs of specifications for these functions: Z.add 0 l, ...
  - an instantiation of all derived properties proved generically in Numbers : Z.add\_comm, Z.add assoc, ...

A large part of ZArith is now simply compatibility notations, for instance Zplus\_comm is an alias for Z.add\_comm. The direct use of module Z is now recommended instead of relying on these compatibility notations.

- Similar major reorganization of NArith, via a module N in NArith/BinNat.v
- Concerning the positive datatype, BinPos.v is now in a specific directory PArith, and contains an internal submodule Pos. We regroup there functions such as Pos.add Pos.mul etc as well as many results about them. These results are here proved directly (no Number interface for strictly positive numbers).
- Note that in spite of the compatibility layers, all these reorganizations may induce some marginal incompatibilies in scripts. In particular:
  - the "?=" notation for positive now refers to a binary function Pos.compare, instead of the infamous ternary Pcompare (now Pos.compare cont).
  - some hypothesis names generated by the system may changed (typically for a "destruct Z\_le\_gt\_dec") since naming is done after the short name of the head predicate (here now "le" in module Z instead of "Zle", etc).
  - the internals of Z.add has changed, now relying of Z.pos\_sub.
- Also note these new notations:
  - "<?" "<=?" "=?" for boolean tests such as Z.ltb Z.leb Z.egb.
  - "÷" for the alternative integer division Z.quot implementing the Truncate convention (former ZOdiv), while the notation for the Coq usual division Z.div implementing the Flooring convention remains "/". Their corresponding modulo functions are Z.rem (no notations) for Z.quot and Z.modulo (infix "mod" notation) for Z.div.
- Lemmas about conversions between these datatypes are also organized in modules, see for instance modules Z2Nat, N2Z, etc.
- When creating BigN, the macro-generated part NMake\_gen is much smaller. The generic part NMake has been reworked and improved. Some changes may introduce incompatibilities. In particular, the order of the arguments for BigN.shiftl and BigN.shiftr is now reversed: the number to shift now comes first. By default, the power function now takes two BigN.
- Creation of Vector, an independent library for lists indexed by their length. Vectors' names overwrite lists' one so you should not "Import" the library. All old names changed: function names follow

3.8. Version 8.4 91

the ocaml ones and, for example, Vcons becomes Vector.cons. You can get [..;..;..]-style notations by importing Vector.VectorNotations.

- Removal of TheoryList. Requiring List instead should work most of the time.
- New syntax "rew Heq in H" and "rew <- Heq in H" for eq\_rect and eq\_rect\_r (available by importing module EqNotations).
- Wf.iter\_nat is now Peano.nat\_iter (with an implicit type argument).

#### Internal infrastructure

- Opaque proofs are now loaded lazily by default. This allows to be almost as fast as -dont-load-proofs, while being safer (no creation of axioms) and avoiding feature restrictions (Print and Print Assumptions work ok).
- Revised hash-consing code allowing more sharing of memory
- Experimental support added for camlp4 (the one provided alongside ocaml), simply pass option usecamlp4 to ./configure. By default camlp5 is used.
- Revised build system: no more stages in Makefile thanks to some recursive aspect of recent gnu make, use of vo.itarget files containing .v to compile for both make and ocambuild, etc.
- Support of cross-compilation via mingw from unix toward Windows, contact P. Letouzey for more informations.
- New Makefile rules mli-doc to make html of mli in dev/doc/html and full-stdlib to get a (huge) pdf reflecting the whole standard library.

#### Extraction

- By default, opaque terms are now truly considered opaque by extraction: instead of accessing their body, they are now considered as axioms. The previous behaviour can be reactivated via the option "Set Extraction AccessOpaque".
- The pretty-printer for Haskell now produces layout-independent code
- A new command "Separate Extraction cst1 cst2 ..." that mixes a minimal extracted environment a la "Recursive Extraction" and the production of several files (one per coq source) a la "Extraction Library" (DOC TODO).
- New option "Set/Unset Extraction KeepSingleton" for preventing the extraction to optimize singleton container types (DOC TODO).
- The extraction now identifies and properly rejects a particular case of universe polymorphism it cannot handle yet (the pair (I,I) being Prop).
- Support of anonymous fields in record (#2555).

## CoqIDE

- Coqide now runs coqtop as separated process, making it more robust: coqtop subprocess can be interrupted, or even killed and relaunched (cf button "Restart Coq", ex-"Go to Start"). For allowing such interrupts, the Windows version of coqide now requires Windows >= XP SP1.
- The communication between CoqIDE and Coqtop is now done via a dialect of XML (DOC TODO).
- The backtrack engine of CoqIDE has been reworked, it now uses the "Backtrack" command similarly to Proof General.
- The Coqide parsing of sentences has be reworked and now supports tactic delimitation via { }.
- Cogide now accepts the Abort command (wish #2357).

- Coqide can read coq\_makefile files as "project file" and use it to set automatically options to send to coqtop.
- Preference files have moved to \$XDG\_CONFIG\_HOME/coq and accelerators are not stored as a list anymore.

### Tools

- Coq now searches directories specified in COQPATH, \$XDG\_DATA\_HOME/coq, \$XDG\_DATA\_DIRS/coq, and user-contribs before the standard library.
- Coq rc file has moved to \$XDG\_CONFIG\_HOME/coq.
- Major changes to coq makefile:
  - mli/mlpack/mllib taken into account, ml not preprocessed anymore, ml4 work;
  - mlihtml generates doc of mli, install-doc install the html doc in DOCDIR with the same policy as vo in COQLIB;
  - More variables are given by coqtop -config, others are defined only if the users doesn't have defined them elsewhere. Consequently, generated makefile should work directly on any architecture;
  - Packagers can take advantage of \$(DSTROOT) introduction. Installation can be made in \$XDG\_DATA\_HOME/coq;
  - - arg option allows to send option as argument to coqc.

# 3.8.4 Details of changes in 8.4beta2

### Vernacular commands

- Commands "Back" and "BackTo" are now handling the proof states. They may perform some extra steps of backtrack to avoid states where the proof state is unavailable (typically a closed proof).
- The commands "Suspend" and "Resume" have been removed.
- A basic Show Script has been reintroduced (no indentation).
- New command "Set Parsing Explicit" for deactivating parsing (and printing) of implicit arguments (useful for teaching).
- New command "Grab Existential Variables" to transform the unresolved evars at the end of a proof
  into goals.

## Tactics

- Still no general "info" tactical, but new specific tactics info\_auto, info\_eauto, info\_trivial which provides information on the proofs found by auto/eauto/trivial. Display of these details could also be activated by "Set Info Auto"/"Set Info Eauto"/"Set Info Trivial".
- Details on everything tried by auto/eauto/trivial during a proof search could be obtained by "debug auto", "debug eauto", "debug trivial" or by a global "Set Debug Auto"/"Set Debug Eauto"/"Set Debug Trivial".
- New command "r string" in Ltac debugger that interprets "idtac string" in Ltac code as a breakpoint
  and jumps to its next use.
- Tactics from the Dp plugin (simplify, ergo, yices, cvc3, z3, cvcl, harvey, zenon, gwhy) have been removed, since Why2 has not been maintained for the last few years. The Why3 plugin should be a suitable replacement in most cases.

## Libraries

3.8. Version 8.4 93

- MSetRBT: a new implementation of MSets via Red-Black trees (initial contribution by Andrew Appel).
- MSetAVL: for maximal sharing with the new MSetRBT, the argument order of Node has changed (this should be transparent to regular MSets users).

## Module System

• The names of modules (and module types) are now in a fully separated namespace from ordinary definitions: "Definition E:=0. Module E. End E." is now accepted.

### CoqIDE

• Coqide now supports the "Restart" command, and "Undo" (with a warning). Better support for "Abort".

# 3.8.5 Details of changes in 8.4

#### Vernacular commands

- The "Reset" command is now supported again in files given to coqc or Load.
- "Show Script" now indents again the displayed scripts. It can also work correctly across Load'ed files if the option "Unset Atomic Load" is used.
- "Open Scope" can now be given the delimiter (e.g. Z) instead of the full scope name (e.g. Z\_scope).

### Notations

- Most compatibility notations of the standard library are now tagged as (compat xyz), where xyz is a former Coq version, for instance "8.3". These notations behave as (only parsing) notations, except that they may triggers warnings (or errors) when used while Coq is not in a corresponding -compat mode.
- To activate these compatibility warnings, use "Set Verbose Compat Notations" or the command-line flag -verbose-compat-notations.
- For a strict mode without these compatibility notations, use "Unset Compat Notations" or the command-line flag -no-compat-notations.

## Tactics

- An annotation "eqn:H" or "eqn:?" can be added to a "destruct" or "induction" to make it generate equations in the spirit of "case\_eq". The former syntax "\_eqn" is discontinued.
- The name of the hypothesis introduced by tactic "remember" can be set via the new syntax "remember t as x eqn:H" (wish #2489).

## Libraries

- Reals: changed definition of PI, no more axiom about  $\sin(\text{PI}/2)$ .
- SetoidPermutation: a notion of permutation for lists modulo a setoid equality.
- BigN: fixed the ocaml code doing the parsing/printing of big numbers.
- List: a couple of lemmas added especially about no-duplication, partitions.
- Init: Removal of the coercions between variants of sigma-types and subset types (possible source of incompatibility).

# 3.9 Version 8.3

# 3.9.1 Summary of changes

Coq version 8.3 is before all a transition version with refinements or extensions of the existing features and libraries and a new tactic nsatz based on Hilbert's Nullstellensatz for deciding systems of equations over rings.

With respect to libraries, the main evolutions are due to Pierre Letouzey with a rewriting of the library of finite sets FSets and a new round of evolutions in the modular development of arithmetic (library Numbers). The reason for making FSets evolve is that the computational and logical contents were quite intertwined in the original implementation, leading in some cases to longer computations than expected and this problem is solved in the new MSets implementation. As for the modular arithmetic library, it was only dealing with the basic arithmetic operators in the former version and its current extension adds the standard theory of the division, min and max functions, all made available for free to any implementation of  $\mathbb{N}$ ,  $\mathbb{Z}$  or  $\mathbb{Z}/n\mathbb{Z}$ .

The main other evolutions of the library are due to Hugo Herbelin who made a revision of the sorting library (including a certified merge-sort) and to Guillaume Melquiond who slightly revised and cleaned up the library of reals.

The module system evolved significantly. Besides the resolution of some efficiency issues and a more flexible construction of module types, Élie Soubiran brought a new model of name equivalence, the  $\Delta$ -equivalence, which respects as much as possible the names given by the users. He also designed with Pierre Letouzey a new, convenient operator <+ for nesting functor application that provides a light notation for inheriting the properties of cascading modules.

The new tactic nsatz is due to Loïc Pottier. It works by computing Gröbner bases. Regarding the existing tactics, various improvements have been done by Matthieu Sozeau, Hugo Herbelin and Pierre Letouzey.

Matthieu Sozeau extended and refined the typeclasses and Program features (the Russell language). Pierre Letouzey maintained and improved the extraction mechanism. Bruno Barras and Élie Soubiran maintained the Coq checker, Julien Forest maintained the Function mechanism for reasoning over recursively defined functions. Matthieu Sozeau, Hugo Herbelin and Jean-Marc Notin maintained coqdoc. Frédéric Besson maintained the Micromega platform for deciding systems of inequalities. Pierre Courtieu maintained the support for the Proof General Emacs interface. Claude Marché maintained the plugin for calling external provers (dp). Yves Bertot made some improvements to the libraries of lists and integers. Matthias Puech improved the search functions. Guillaume Melquiond usefully contributed here and there. Yann Régis-Gianas grounded the support for Unicode on a more standard and more robust basis.

Though invisible from outside, Arnaud Spiwack improved the general process of management of existential variables. Pierre Letouzey and Stéphane Glondu improved the compilation scheme of the Coq archive. Vincent Gross provided support to CoqIDE. Jean-Marc Notin provided support for benchmarking and archiving.

Many users helped by reporting problems, providing patches, suggesting improvements or making useful comments, either on the bug tracker or on the Coq-Club mailing list. This includes but not exhaustively Cédric Auger, Arthur Charguéraud, François Garillot, Georges Gonthier, Robin Green, Stéphane Lescuyer, Eelis van der Weegen, ...

Though not directly related to the implementation, special thanks are going to Yves Bertot, Pierre Castéran, Adam Chlipala, and Benjamin Pierce for the excellent teaching materials they provided.

Paris, April 2010 Hugo Herbelin

3.9. Version 8.3 95

# 3.9.2 Details of changes

## Rewriting tactics

- Tactic "rewrite" now supports rewriting on ad hoc equalities such as eq\_true.
- "Hint Rewrite" now checks that the lemma looks like an equation.
- New tactic "etransitivity".
- Support for heterogeneous equality (JMeq) in "injection" and "discriminate".
- Tactic "subst" now supports heterogeneous equality and equality proofs that are dependent (use "simple subst" for preserving compatibility).
- Added support for Leibniz-rewriting of dependent hypotheses.
- Renamed "Morphism" into "Proper" and "respect" into "proper\_prf" (possible source of incompatibility). A partial fix is to define "Notation Morphism R f := (Proper (R%signature) f)."
- New tactic variants "rewrite\* by" and "autorewrite\*" that rewrite respectively the first and all matches whose side-conditions are solved.
- "Require Import Setoid" does not export all of "Morphisms" and "RelationClasses" anymore (possible source of incompatibility, fixed by importing "Morphisms" too).
- Support added for using Chung-Kil Hur's Heq library for rewriting over heterogeneous equality (courtesy of the library's author).
- Tactic "replace" supports matching terms with holes.

### Automation tactics

- Tactic intuition now preserves inner iff and not (exceptional source of incompatibilities solvable by redefining intuition as unfold iff, not in \*; intuition, or, for iff only, by using Set Intuition Iff Unfolding.)
- Tactic tauto now proves classical tautologies as soon as classical logic (i.e. library Classical\_Prop or Classical) is loaded.
- Tactic gappa has been removed from the Dp plugin.
- Tactic firstorder now supports the combination of its using and with options.
- New Hint Resolve -> (or <-) for declaring iff's as oriented hints (wish #2104).
- An inductive type as argument of the using option of auto / eauto / firstorder is interpreted as using the collection of its constructors.
- New decision tactic "nsatz" to prove polynomial equations by computation of Groebner bases.

### Other tactics

- Tactic "discriminate" now performs intros before trying to discriminate an hypothesis of the goal (previously it applied intro only if the goal had the form t1<>t2) (exceptional source of incompatibilities former behavior can be obtained by "Unset Discriminate Introduction").
- Tactic "quote" now supports quotation of arbitrary terms (not just the goal).
- Tactic "idtac" now displays its "list" arguments.
- New introduction patterns "\*" for introducing the next block of dependent variables and "\*\*" for introducing all quantified variables and hypotheses.
- Pattern Unification for existential variables activated in tactics and new option "Unset Tactic Evars Pattern Unification" to deactivate it.

- Resolution of canonical structure is now part of the tactic's unification algorithm.
- New tactic "decide lemma with hyp" for rewriting decidability lemmas when one knows which side is true.
- Improved support of dependent goals over objects in dependent types for "destruct" (rare source of incompatibility that can be avoided by unsetting option "Dependent Propositions Elimination").
- Tactic "exists", "eexists", "destruct" and "edestruct" supports iteration using comma-separated arguments
- Tactic names "case" and "elim" now support clauses "as" and "in" and become then synonymous of "destruct" and "induction" respectively.
- A new tactic name "exfalso" for the use of 'ex-falso quodlibet' principle. This tactic is simply a shortcut for "elimtype False".
- Made quantified hypotheses get the name they would have if introduced in the context (possible but rare source of incompatibilities).
- When applying a component of a conjunctive lemma, "apply in" (and sequences of "apply in") now leave the side conditions of the lemmas uniformly after the main goal (possible source of rare incompatibilities).
- In "simpl c" and "change c with d", c can be a pattern.
- Tactic "revert" now preserves let-in's making it the exact inverse of "intro".
- New tactics "clear dependent H" and "revert dependent H" that clears (resp. reverts) H and all the hypotheses that depend on H.
- Ltac's pattern-matching now supports matching metavariables that depend on variables bound upwards in the pattern.

# Tactic definitions

- Ltac definitions support Local option for non-export outside modules.
- Support for parsing non-empty lists with separators in tactic notations.
- New command "Locate Ltac" to get the full name of an Ltac definition.

## Notations

- Record syntax  $\{|x=...; y=...|\}$  now works inside patterns too.
- Abbreviations from non-imported module now invisible at printing time.
- Abbreviations now use implicit arguments and arguments scopes for printing.
- Abbreviations to pure names now strictly behave like the name they refer to (make redirections of qualified names easier).
- Abbreviations for applied constant now propagate the implicit arguments and arguments scope of the underlying reference (possible source of incompatibilities generally solvable by changing such abbreviations from e.g. Notation foo' := (foo x) to Notation foo' y := (foo x (y:=y))).
- The "where" clause now supports multiple notations per defined object.
- Recursive notations automatically expand one step on the left for better factorization; recursion notations inner separators now ensured being tokens.
- Added "Reserved Infix" as a specific shortcut of the corresponding "Reserved Notation".
- Open/Close Scope command supports Global option in sections.

### Specification language

3.9. Version 8.3 97

- New support for local binders in the syntax of Record/Structure fields.
- Fixpoint/CoFixpoint now support building part or all of bodies using tactics.
- Binders given before ":" in lemmas and in definitions built by tactics are now automatically introduced (possible source of incompatibility that can be resolved by invoking "Unset Automatic Introduction").
- New support for multiple implicit arguments signatures per reference.

## Module system

- Include Type is now deprecated since Include now accept both modules and module types.
- Declare ML Module supports Local option.
- The sharing between non-logical object and the management of the name-space has been improved by the new "Delta-equivalence" on qualified name.
- The include operator has been extended to high-order structures
- Sequences of Include can be abbreviated via new syntax "<+".
- A module (or module type) can be given several "<:" signatures.
- Interactive proofs are now permitted in module type. Functors can hence be declared as Module Type and be used later to type themselves.
- A functor application can be prefixed by a "!" to make it ignore any "Inline" annotation in the type of its argument(s) (for examples of use of the new features, see libraries Structures and Numbers).
- Coercions are now active only when modules are imported (use "Set Automatic Coercions Import" to get the behavior of the previous versions of Coq).

## Extraction

- When using (Recursive) Extraction Library, the filenames are directly the Coq ones with new appropriate extensions: we do not force anymore uncapital first letters for Ocaml and capital ones for Haskell.
- The extraction now tries harder to avoid code transformations that can be dangerous for the complexity. In particular many eta-expansions at the top of functions body are now avoided, clever partial applications will likely be preserved, let-ins are almost always kept, etc.
- In the same spirit, auto-inlining is now disabled by default, except for induction principles, since this feature was producing more frequently weird code than clear gain. The previous behavior can be restored via "Set Extraction AutoInline".
- Unicode characters in identifiers are now transformed into ascii strings that are legal in Ocaml and other languages.
- Harsh support of module extraction to Haskell and Scheme: module hierarchy is flattened, module abbreviations and functor applications are expanded, module types and unapplied functors are discarded.
- Less unsupported situations when extracting modules to Ocaml. In particular module parameters might be alpha-renamed if a name clash is detected.
- Extract Inductive is now possible toward non-inductive types (e.g. nat => int)
- Extraction Implicit: this new experimental command allows to mark some arguments of a function or constructor for removed during extraction, even if these arguments don't fit the usual elimination principles of extraction, for instance the length n of a vector.
- Files ExtrOcaml\*.v in plugins/extraction try to provide a library of common extraction commands: mapping of basics types toward Ocaml's counterparts, conversions from/to int and big\_int, or even

complete mapping of nat,Z,N to int or big\_int, or mapping of ascii to char and string to char list (in this case recognition of ascii constants is hard-wired in the extraction).

# Program

- Streamlined definitions using well-founded recursion and measures so that they can work on any subset of the arguments directly (uses currying).
- Try to automatically clear structural fixpoint prototypes in obligations to avoid issues with opacity.
- Use return type clause inference in pattern-matching as in the standard typing algorithm.
- Support [Local Obligation Tactic] and [Next Obligation with tactic].
- Use [Show Obligation Tactic] to print the current default tactic.
- [fst] and [snd] have maximal implicit arguments in Program now (possible source of incompatibility).

## Type classes

- Declaring axiomatic type class instances in Module Type should be now done via new command "Declare Instance", while the syntax "Instance" now always provides a concrete instance, both in and out of Module Type.
- Use [Existing Class foo] to declare foo as a class a posteriori. [foo] can be an inductive type or a constant definition. No projections or instances are defined.
- Various bug fixes and improvements: support for defined fields, anonymous instances, declarations giving terms, better handling of sections and [Context].

### Vernacular commands

- New command "Timeout <n> <command>." interprets a command and a timeout interrupts the interpretation after <n> seconds.
- New command "Compute <expr>." is a shortcut for "Eval vm\_compute in <expr>".
- New command "Fail <command>." interprets a command and is successful iff the command fails on an error (but not an anomaly). Handy for tests and illustration of wrong commands.
- Most commands referring to constant (e.g. Print or About) now support referring to the constant by a notation string.
- New option "Boolean Equality Schemes" to make generation of boolean equality automatic for datatypes (together with option "Decidable Equality Schemes", this replaces deprecated option "Equality Scheme").
- Made support for automatic generation of case analysis schemes available to user (governed by option "Set Case Analysis Schemes").
- New command Global Generalizable All No Variable Variables ident to declare which identifiers are generalizable in "{} `and "() `binders.
- New command "Print Opaque Dependencies" to display opaque constants in addition to all variables, parameters or axioms a theorem or definition relies on.
- New command "Declare Reduction <id> := <conv\_expr>", allowing to write later "Eval <id> in ...". This command accepts a Local variant.
- Syntax of Implicit Type now supports more than one block of variables of a given type.
- Command "Canonical Structure" now warns when it has no effects.
- Commands of the form "Set X" or "Unset X" now support "Local" and "Global" prefixes.

### Library

3.9. Version 8.3 99

- Use "standard" Coq names for the properties of eq and identity (e.g. refl\_equal is now eq\_refl). Support for compatibility is provided.
- The function Compare\_dec.nat\_compare is now defined directly, instead of relying on lt\_eq\_lt\_dec. The earlier version is still available under the name nat\_compare\_alt.
- Lemmas in library Relations and Reals have been homogenized a bit.
- The implicit argument of Logic.eq is now maximally inserted, allowing to simply write "eq" instead of "@eq" in morphism signatures.
- Wrongly named lemmas (Zlt\_gt\_succ and Zlt\_succ\_gt) fixed (potential source of incompatibilities)
- List library:
  - Definitions of list, length and app are now in Init/Datatypes. Support for compatibility is provided.
  - Definition of Permutation is now in Sorting/Permutation.v
  - Some other light revisions and extensions (possible source of incompatibilities solvable by qualifying names accordingly).
- In ListSet, set\_map has been fixed (source of incompatibilities if used).
- Sorting library:
  - new mergesort of worst-case complexity O(n\*ln(n)) made available in Mergesort.v;
  - former notion of permutation up to setoid from Permutation.v is deprecated and moved to PermutSetoid.v;
  - heapsort from Heap.v of worst-case complexity O(n\*n) is deprecated;
  - new file Sorted.v for some definitions of being sorted.
- Structure library. This new library is meant to contain generic structures such as types with equalities or orders, either in Module version (for now) or Type Classes (still to do):
  - DecidableType.v and OrderedType.v: initial notions for FSets/FMaps, left for compatibility but considered as deprecated.
  - Equalities.v and Orders.v: evolutions of the previous files, with fine-grain Module architecture, many variants, use of Equivalence and other relevant Type Classes notions.
  - OrdersTac.v: a generic tactic for solving chains of (in)equalities over variables. See {Nat,N,Z,P}OrderedType.v for concrete instances.
  - GenericMinMax.v: any ordered type can be equipped with min and max. We derived here all the generic properties of these functions.
- MSets library: an important evolution of the FSets library. "MSets" stands for Modular (Finite) Sets, by contrast with a forthcoming library of Class (Finite) Sets contributed by S. Lescuyer which will be integrated with the next release of Coq. The main features of MSets are:
  - The use of Equivalence, Proper and other Type Classes features easing the handling of setoid equalities.
  - The interfaces are now stated in iff-style. Old specifications are now derived properties.
  - The compare functions are now pure, and return a "comparison" value. Thanks to the CompSpec inductive type, reasoning on them remains easy.
  - Sets structures requiring invariants (i.e. sorted lists) are built first as "Raw" sets (pure objects and separate proofs) and attached with their proofs thanks to a generic functor. "Raw" sets have now a proper interface and can be manipulated directly.

Note: No Maps yet in MSets. The FSets library is still provided for compatibility, but will probably be considered as deprecated in the next release of Coq.

- Numbers library:
  - The abstract layer (NatInt, Natural/Abstract, Integer/Abstract) has been simplified and enhance thanks to new features of the module system such as Include (see above). It has been extended to Euclidean division (three flavors for integers: Trunc, Floor and Math).
  - The arbitrary-large efficient numbers (BigN, BigZ, BigQ) has also been reworked. They benefit from the abstract layer improvements (especially for div and mod). Note that some specifications have slightly changed (compare, div, mod, shift{r,l}). Ring/Field should work better (true recognition of constants).

#### Tools

- Option -R now supports binding Coq root read-only.
- New coqtop/coqc option -beautify to reformat .v files (usable e.g. to globally update notations).
- New tool beautify-archive to beautify a full archive of developments.
- New coqtop/coqc option -compat X.Y to simulate the general behavior of previous versions of Coq (provides e.g. support for 8.2 compatibility).

# Coqdoc

- List have been revamped. List depth and scope is now determined by an "offside" whitespace rule.
- Text may be italicized by placing it in \_underscores\_.
- The "-index <string>" flag changes the filename of the index.
- The "-toc-depth <int>" flag limits the depth of headers which are included in the table of contents.
- The "-lib-name <string>" flag prints "<string> Foo" instead of "Library Foo" where library titles are called for. The "-no-lib-name" flag eliminates the extra title.
- New option "-parse-comments" to allow parsing of regular (\* \*) comments.
- New option "-plain-comments" to disable interpretation inside comments.
- New option "-interpolate" to try and typeset identifiers in Coq escapings using the available globalization information.
- New option "-external url root" to refer to external libraries.
- Links to section variables and notations now supported.

### Internal infrastructure

- To avoid confusion with the repository of user's contributions, the subdirectory "contrib" has been renamed into "plugins". On platforms supporting ocaml native dynlink, code located there is built as loadable plugins for coqtop.
- An experimental build mechanism via ocam<br/>lbuild is provided. From the top of the archive, run ./configure as usual, and then ./build. Feedback about this build mechanism is most welcome. Compiling Coq on platforms such as Windows might be simpler this way, but this remains to be tested.
- The Makefile system has been simplified and factorized with the ocambuild system. In particular "make" takes advantage of .mllib files for building .cma/.cmxa. The .vo files to compile are now listed in several vo.itarget files.

3.9. Version 8.3

# 3.10 Version 8.2

# 3.10.1 Summary of changes

Coq version 8.2 adds new features, new libraries and improves on many various aspects.

Regarding the language of Coq, the main novelty is the introduction by Matthieu Sozeau of a package of commands providing Haskell-style typeclasses. Typeclasses, which come with a few convenient features such as type-based resolution of implicit arguments, play a new landmark role in the architecture of Coq with respect to automation. For instance, thanks to typeclass support, Matthieu Sozeau could implement a new resolution-based version of the tactics dedicated to rewriting on arbitrary transitive relations.

Another major improvement of Coq 8.2 is the evolution of the arithmetic libraries and of the tools associated to them. Benjamin Grégoire and Laurent Théry contributed a modular library for building arbitrarily large integers from bounded integers while Evgeny Makarov contributed a modular library of abstract natural and integer arithmetic together with a few convenient tactics. On his side, Pierre Letouzey made numerous extensions to the arithmetic libraries on  $\mathbb Z$  and  $\mathbb Q$ , including extra support for automation in presence of various number-theory concepts.

Frédéric Besson contributed a reflective tactic based on Krivine-Stengle Positivstellensatz (the easy way) for validating provability of systems of inequalities. The platform is flexible enough to support the validation of any algorithm able to produce a "certificate" for the Positivstellensatz and this covers the case of Fourier-Motzkin (for linear systems in  $\mathbb Q$  and  $\mathbb R$ ), Fourier-Motzkin with cutting planes (for linear systems in  $\mathbb Z$ ) and sum-of-squares (for non-linear systems). Evgeny Makarov made the platform generic over arbitrary ordered rings.

Arnaud Spiwack developed a library of 31-bits machine integers and, relying on Benjamin Grégoire and Laurent Théry's library, delivered a library of unbounded integers in base  $2^{31}$ . As importantly, he developed a notion of "retro-knowledge" so as to safely extend the kernel-located bytecode-based efficient evaluation algorithm of Coq version 8.1 to use 31-bits machine arithmetic for efficiently computing with the library of integers he developed.

Beside the libraries, various improvements were contributed to provide a more comfortable end-user language and more expressive tactic language. Hugo Herbelin and Matthieu Sozeau improved the pattern matching compilation algorithm (detection of impossible clauses in pattern matching, automatic inference of the return type). Hugo Herbelin, Pierre Letouzey and Matthieu Sozeau contributed various new convenient syntactic constructs and new tactics or tactic features: more inference of redundant information, better unification, better support for proof or definition by fixpoint, more expressive rewriting tactics, better support for metavariables, more convenient notations...

Élie Soubiran improved the module system, adding new features (such as an "include" command) and making it more flexible and more general. He and Pierre Letouzey improved the support for modules in the extraction mechanism.

Matthieu Sozeau extended the Russell language, ending in an convenient way to write programs of given specifications, Pierre Corbineau extended the Mathematical Proof Language and the automation tools that accompany it, Pierre Letouzey supervised and extended various parts of the standard library, Stéphane Glondu contributed a few tactics and improvements, Jean-Marc Notin provided help in debugging, general maintenance and coqdoc support, Vincent Siles contributed extensions of the Scheme command and of injection.

Bruno Barras implemented the coqchk tool: this is a stand-alone type checker that can be used to certify vo files. Especially, as this verifier runs in a separate process, it is granted not to be "hijacked" by virtually malicious extensions added to Coq.

Yves Bertot, Jean-Christophe Filliâtre, Pierre Courtieu and Julien Forest acted as maintainers of features they implemented in previous versions of Coq.

Julien Narboux contributed to CoqIDE. Nicolas Tabareau made the adaptation of the interface of the old "setoid rewrite" tactic to the new version. Lionel Mamane worked on the interaction between Coq and its external interfaces. With Samuel Mimram, he also helped making Coq compatible with recent software tools. Russell O'Connor, Cezary Kaliszyk, Milad Niqui contributed to improve the libraries of integers, rational, and real numbers. We also thank many users and partners for suggestions and feedback, in particular Pierre Castéran and Arthur Charguéraud, the INRIA Marelle team, Georges Gonthier and the INRIA-Microsoft Mathematical Components team, the Foundations group at Radboud university in Nijmegen, reporters of bugs and participants to the Coq-Club mailing list.

Palaiseau, June 2008 Hugo Herbelin

# 3.10.2 Details of changes

## Language

- If a fixpoint is not written with an explicit { struct ... }, then all arguments are tried successively (from left to right) until one is found that satisfies the structural decreasing condition.
- New experimental typeclass system giving ad-hoc polymorphism and overloading based on dependent records and implicit arguments.
- New syntax "let 'pat := b in c" for let-binding using irrefutable patterns.
- New syntax "forall {A}, T" for specifying maximally inserted implicit arguments in terms.
- Sort of Record/Structure, Inductive and CoInductive defaults to Type if omitted.
- (Co)Inductive types can be defined as records (e.g. "CoInductive stream := { hd : nat; tl : stream }.")
- New syntax "Theorem id1:t1 ... with idn:tn" for proving mutually dependent statements.
- Support for sort-polymorphism on constants denoting inductive types.
- Several evolutions of the module system (handling of module aliases, functorial module types, an Include feature, etc).
- Prop now a subtype of Set (predicative and impredicative forms).
- Recursive inductive types in Prop with a single constructor of which all arguments are in Prop is now considered to be a singleton type. It consequently supports all eliminations to Prop, Set and Type. As a consequence, Acc\_rect has now a more direct proof [possible source of easily fixed incompatibility in case of manual definition of a recursor in a recursive singleton inductive type].

## Vernacular commands

- Added option Global to "Arguments Scope" for section surviving.
- Added option "Unset Elimination Schemes" to deactivate the automatic generation of elimination schemes.
- Modification of the Scheme command so you can ask for the name to be automatically computed (e.g. Scheme Induction for nat Sort Set).
- New command "Combined Scheme" to build combined mutual induction principles from existing mutual induction principles.
- New command "Scheme Equality" to build a decidable (boolean) equality for simple inductive datatypes and a decision property over this equality (e.g. Scheme Equality for nat).

3.10. Version 8.2

- Added option "Set Equality Scheme" to make automatic the declaration of the boolean equality when
  possible.
- Source of universe inconsistencies now printed when option "Set Printing Universes" is activated.
- New option "Set Printing Existential Instances" for making the display of existential variable instances
  explicit.
- Support for option "[id1 ... idn]", and "-[id1 ... idn]", for the "compute"/"cbv" reduction strategy, respectively meaning reduce only, or everything but, the constants id1 ... idn. "lazy" alone or followed by "[id1 ... idn]", and "-[id1 ... idn]" also supported, meaning apply all of beta-iota-zeta-delta, possibly restricting delta.
- New command "Strategy" to control the expansion of constants during conversion tests. It generalizes
  commands Opaque and Transparent by introducing a range of levels. Lower levels are assigned to
  constants that should be expanded first.
- New options Global and Local to Opaque and Transparent.
- New command "Print Assumptions" to display all variables, parameters or axioms a theorem or definition relies on.
- "Add Rec LoadPath" now provides references to libraries using partially qualified names (this holds also for coqtop/coqc option -R).
- SearchAbout supports negated search criteria, reference to logical objects by their notation, and more generally search of subterms.
- "Declare ML Module" now allows to import .cmxs files when Coq is compiled in native code with a version of OCaml that supports native Dynlink (>= 3.11).
- Specific sort constraints on Record now taken into account.
- "Print LoadPath" supports a path argument to filter the display.

## Libraries

- Several parts of the libraries are now in Type, in particular FSets, SetoidList, ListSet, Sorting, Zmisc. This may induce a few incompatibilities. In case of trouble while fixing existing development, it may help to simply declare Set as an alias for Type (see file SetIsType).
- New arithmetical library in theories/Numbers. It contains:
  - an abstract modular development of natural and integer arithmetics in Numbers/Natural/Abstract and Numbers/Integer/Abstract
  - an implementation of efficient computational bounded and unbounded integers that can be mapped to processor native arithmetics. See Numbers/Cyclic/Int31 for 31-bit integers and Numbers/Natural/BigN for unbounded natural numbers and Numbers/Integer/BigZ for unbounded integers.
  - some proofs that both older libraries Arith, ZArith and NArith and newer BigN and BigZ implement the abstract modular development. This allows in particular BigN and BigZ to already come with a large database of basic lemmas and some generic tactics (ring),

This library has still an experimental status, as well as the processor-acceleration mechanism, but both its abstract and its concrete parts are already quite usable and could challenge the use of nat, N and Z in actual developments. Moreover, an extension of this framework to rational numbers is ongoing, and an efficient Q structure is already provided (see Numbers/Rational/BigQ), but this part is currently incomplete (no abstract layer and generic lemmas).

• Many changes in FSets/FMaps. In practice, compatibility with earlier version should be fairly good, but some adaptations may be required.

- Interfaces of unordered ("weak") and ordered sets have been factorized thanks to new features of Coq modules (in particular Include), see FSetInterface. Same for maps. Hints in these interfaces have been reworked (they are now placed in a "set" database).
- To allow full subtyping between weak and ordered sets, a field "eq\_dec" has been added to OrderedType. The old version of OrderedType is now called MiniOrderedType and functor MOT\_to\_OT allow to convert to the new version. The interfaces and implementations of sets now contain also such a "eq\_dec" field.
- FSetDecide, contributed by Aaron Bohannon, contains a decision procedure allowing to solve basic set-related goals (for instance, is a point in a particular set?). See FSetProperties for examples.
- Functors of properties have been improved, especially the ones about maps, that now propose some induction principles. Some properties of fold need less hypothesis.
- More uniformity in implementations of sets and maps: they all use implicit arguments, and no longer export unnecessary scopes (see bug #1347)
- Internal parts of the implementations based on AVL have evolved a lot. The main files FSe-tAVL and FMapAVL are now much more lightweight now. In particular, minor changes in some functions has allowed to fully separate the proofs of operational correctness from the proofs of well-balancing: well-balancing is critical for efficiency, but not anymore for proving that these trees implement our interfaces, hence we have moved these proofs into appendix files FSetFullAVL and FMapFullAVL. Moreover, a few functions like union and compare have been modified in order to be structural yet efficient. The appendix files also contains alternative versions of these few functions, much closer to the initial Ocaml code and written via the Function framework.
- Library IntMap, subsumed by FSets/FMaps, has been removed from Coq Standard Library and moved into a user contribution Cachan/IntMap
- Better computational behavior of some constants (eq\_nat\_dec and le\_lt\_dec more efficient, Z\_lt\_le\_dec and Positive\_as\_OT.compare transparent, ...) (exceptional source of incompatibilities).
- Boolean operators moved from module Bool to module Datatypes (may need to rename qualified references in script and force notations || and && to be at levels 50 and 40 respectively).
- The constructors xI and xO of type positive now have postfix notations "~1" and "~0", allowing to write numbers in binary form easily, for instance 6 is 1~1~0 and 4\*p is p~0~0 (see BinPos.v).
- Improvements to NArith (Nminus, Nmin, Nmax), and to QArith (in particular a better power function).
- Changes in ZArith: several additional lemmas (used in theories/Numbers), especially in Zdiv, Znumtheory, Zpower. Moreover, many results in Zdiv have been generalized: the divisor may simply be non-null instead of strictly positive (see lemmas with name ending by "\_full"). An alternative file ZOdiv proposes a different behavior (the one of Ocaml) when dividing by negative numbers.
- Changes in Arith: EqNat and Wf\_nat now exported from Arith, some constructions on nat that were outside Arith are now in (e.g. iter\_nat).
- In SetoidList, eqlistA now expresses that two lists have similar elements at the same position, while the predicate previously called eqlistA is now equivlistA (this one only states that the lists contain the same elements, nothing more).
- Changes in Reals:
  - Most statement in "sigT" (including the completeness axiom) are now in "sig" (in case of incompatibility, use proj1\_sig instead of projT1, sig instead of sigT, etc).
  - More uniform naming scheme (identifiers in French moved to English, consistent use of 0 zero

     instead of O letter O –, etc).
  - Lemma on prod f SO is now on prod f R0.

3.10. Version 8.2

- Useless hypothesis of ln exists1 dropped.
- New Rlogic.v states a few logical properties about R axioms.
- RIneq.v extended and made cleaner.
- Slight restructuration of the Logic library regarding choice and classical logic. Addition of files providing intuitionistic axiomatizations of descriptions: Epsilon.v, Description.v and IndefiniteDescription.v.
- Definition of pred and minus made compatible with the structural decreasing criterion for use in fixpoints.
- Files Relations/Rstar.v and Relations/Newman.v moved out to the user contribution repository (contribution CoC\_History). New lemmas about transitive closure added and some bound variables renamed (exceptional risk of incompatibilities).
- Syntax for binders in terms (e.g. for "exists") supports anonymous names.

## Notations, coercions, implicit arguments and type inference

- More automation in the inference of the return clause of dependent pattern-matching problems.
- Experimental allowance for omission of the clauses easily detectable as impossible in pattern-matching problems.
- Improved inference of implicit arguments.
- New options "Set Maximal Implicit Insertion", "Set Reversible Pattern Implicit", "Set Strongly Strict Implicit" and "Set Printing Implicit Defensive" for controlling inference and use of implicit arguments.
- New modifier in "Implicit Arguments" to force an implicit argument to be maximally inserted.
- New modifier of "Implicit Arguments" to enrich the set of implicit arguments.
- New options Global and Local to "Implicit Arguments" for section surviving or non export outside module.
- Level "constr" moved from 9 to 8.
- Structure/Record now printed as Record (unless option Printing All is set).
- Support for parametric notations defining constants.
- Insertion of coercions below product types refrains to unfold constants (possible source of incompatibility).
- New support for fix/cofix in notations.

### Tactic Language

- Second-order pattern-matching now working in Ltac "match" clauses (syntax for second-order unification variable is "@?X").
- Support for matching on let bindings in match context using syntax "H := body" or "H := body : type".
- Ltac accepts integer arguments (syntax is "ltac:nnn" for nnn an integer).
- The general sequence tactical "expr\_0; [expr\_1 | ... | expr\_n]" is extended so that at most one expr\_i may have the form "expr .." or just "..". Also, n can be different from the number of subgoals generated by expr\_0. In this case, the value of expr (or idtac in case of just "..") is applied to the intermediate subgoals to make the number of tactics equal to the number of subgoals.
- A name used as the name of the parameter of a lemma (like f in "apply f\_equal with (f:=t)") is now interpreted as a ltac variable if such a variable exists (this is a possible source of incompatibility and it

can be fixed by renaming the variables of a ltac function into names that do not clash with the lemmas parameter names used in the tactic).

- New syntax "Ltac tac ::= ..." to rebind a tactic to a new expression.
- "let rec ... in ..." now supported for expressions without explicit parameters; interpretation is lazy to the contrary of "let ... in ..."; hence, the "rec" keyword can be used to turn the argument of a "let ... in ..." into a lazy one.
- Patterns for hypotheses types in "match goal" are now interpreted in type\_scope.
- A bound variable whose name is not used elsewhere now serves as metavariable in "match" and it gets instantiated by an identifier (allow e.g. to extract the name of a statement like "exists x, P x").
- New printing of Ltac call trace for better debugging.

### Tactics

- New tactics "apply -> term", "apply <- term", "apply -> term in ident", "apply <- term in ident" for applying equivalences (iff).
- Slight improvement of the hnf and simpl tactics when applied on expressions with explicit occurrences
  of match or fix.
- New tactics "eapply in", "erewrite", "erewrite in".
- New tactics "ediscriminate", "einjection", "esimplify\_eq".
- Tactics "discriminate", "injection", "simplify\_eq" now support any term as argument. Clause "with" is also supported.
- Unfoldable references can be given by notation's string rather than by name in unfold.
- The "with" arguments are now typed using informations from the current goal: allows support for coercions and more inference of implicit arguments.
- Application of "f\_equal"-style lemmas works better.
- Tactics elim, case, destruct and induction now support variants eelim, ecase, edestruct and einduction.
- Tactics destruct and induction now support the "with" option and the "in" clause option. If the option "in" is used, an equality is added to remember the term to which the induction or case analysis applied (possible source of parsing incompatibilities when destruct or induction is part of a let-in expression in Ltac; extra parentheses are then required).
- New support for "as" clause in tactics "apply in" and "eapply in".
- Some new intro patterns:
  - intro pattern "?A" genererates a fresh name based on A. Caveat about a slight loss of compatibility: Some intro patterns don't need space between them. In particular intros ?a?b used to be legal and equivalent to intros ? a ? b. Now it is still legal but equivalent to intros ?a ?b.
  - intro pattern "(A & ... & Y & Z)" synonym to "(A,...,(Y,Z)))))" for right-associative constructs like /or exists.
- Several syntax extensions concerning "rewrite":
  - "rewrite A,B,C" can be used to rewrite A, then B, then C. These rewrites occur only on the first subgoal: in particular, side-conditions of the "rewrite A" are not concerned by the "rewrite B,C".
  - "rewrite A by tac" allows to apply tac on all side-conditions generated by the "rewrite A".
  - "rewrite A at n" allows to select occurrences to rewrite: rewrite only happen at the n-th exact occurrence of the first successful matching of A in the goal.

3.10. Version 8.2

- "rewrite 3 A" or "rewrite 3!A" is equivalent to "rewrite A,A,A".
- "rewrite !A" means rewriting A as long as possible (and at least once).
- "rewrite 3?A" means rewriting A at most three times.
- "rewrite? A" means rewriting A as long as possible (possibly never).
- many of the above extensions can be combined with each other.
- Introduction patterns better respect the structure of context in presence of missing or extra names in nested disjunction-conjunction patterns [possible source of rare incompatibilities].
- New syntax "rename a into b, c into d" for "rename a into b; rename c into d"
- New tactics "dependent induction/destruction H [generalizing id\_1 .. id\_n]" to do induction-inversion on instantiated inductive families à la BasicElim.
- Tactics "apply" and "apply in" now able to reason modulo unfolding of constants (possible source of incompatibility in situations where apply may fail, e.g. as argument of a try or a repeat and in a ltac function); versions that do not unfold are renamed into "simple apply" and "simple apply in" (usable for compatibility or for automation).
- Tactics "apply" and "apply in" now able to traverse conjunctions and to select the first matching lemma among the components of the conjunction; tactic "apply" also able to apply lemmas of conclusion an empty type.
- Tactic "apply" now supports application of several lemmas in a row.
- Tactics "set" and "pose" can set functions using notation " $(f \times 1..\times n := c)$ ".
- New tactic "instantiate" (without argument).
- Tactic firstorder "with" and "using" options have their meaning swapped for consistency with auto/eauto (source of incompatibility).
- Tactic "generalize" now supports "at" options to specify occurrences and "as" options to name the quantified hypotheses.
- New tactic "specialize H with a" or "specialize (H a)" allows to transform in-place a universally-quantified hypothesis (H: forall x, T x) into its instantiated form (H: T a). Nota: "specialize" was in fact there in earlier versions of Coq, but was undocumented, and had a slightly different behavior.
- New tactic "contradict H" can be used to solve any kind of goal as long as the user can provide afterwards a proof of the negation of the hypothesis H. If H is already a negation, say ~T, then a proof of T is asked. If the current goal is a negation, say ~U, then U is saved in H afterwards, hence this new tactic "contradict" extends earlier tactic "swap", which is now obsolete.
- Tactics f\_equal is now done in ML instead of Ltac: it now works on any equality of functions, regardless of the arity of the function.
- New options "before id", "at top", "at bottom" for tactics "move"/"intro".
- Some more debug of reflexive omega (romega), and internal clarifications. Moreover, romega now has a variant romega with \* that can be also used on non-Z goals (nat, N, positive) via a call to a translation tactic named zify (its purpose is to Z-ify your goal...). This zify may also be used independently of romega.
- Tactic "remember" now supports an "in" clause to remember only selected occurrences of a term.
- Tactic "pose proof" supports name overwriting in case of specialization of an hypothesis.
- Semi-decision tactic "jp" for first-order intuitionistic logic moved to user contributions (subsumed by "first-order").

## Program

- Moved useful tactics in theories/Program and documented them.
- Add Program. Basics which contains standard definitions for functional programming (id, apply, flip...)
- More robust obligation handling, dependent pattern-matching and well-founded definitions.
- New syntax "dest term as pat in term "for destructing objects using an irrefutable pattern while keeping equalities (use this instead of "let" in Programs).
- Program CoFixpoint is accepted, Program Fixpoint uses the new way to infer which argument decreases structurally.
- Program Lemma, Axiom etc... now permit to have obligations in the statement iff they can be automatically solved by the default tactic.
- Renamed "Obligations Tactic" command to "Obligation Tactic".
- New command "Preterm [ of id ]" to see the actual term fed to Coq for debugging purposes.
- New option "Transparent Obligations" to control the declaration of obligations as transparent or opaque. All obligations are now transparent by default, otherwise the system declares them opaque if possible.
- Changed the notations "left" and "right" to "in\_left" and "in\_right" to hide the proofs in standard disjunctions, to avoid breaking existing scripts when importing Program. Also, put them in program\_scope.

## Type Classes

- New "Class", "Instance" and "Program Instance" commands to define classes and instances documented in the reference manual.
- New binding construct " [ Class\_1 param\_1 .. param\_n, Class\_2 ... ] " for binding type classes, usable everywhere.
- New command "Print Classes" and "Print Instances some class" to print tables for typeclasses.
- New default eauto hint database "typeclass\_instances" used by the default typeclass instance search tactic.
- New theories directory "theories/Classes" for standard typeclasses declarations. Module Classes.RelationClasses is a typeclass port of Relation\_Definitions plus a generic development of algebra on n-ary heterogeneous predicates.

## Setoid rewriting

- Complete (and still experimental) rewrite of the tactic based on typeclasses. The old interface and semantics are almost entirely respected, except:
  - Import Setoid is now mandatory to be able to call setoid replace and declare morphisms.
  - "->", "++>" and "==>" are now right associative notations declared at level 55 in scope signature\_scope. Their introduction may break existing scripts that defined them as notations with different levels.
  - One needs to use [Typeclasses unfold [cst]] if [cst] is used as an abbreviation hiding products in types of morphisms, e.g. if ones redefines [relation] and declares morphisms whose type mentions [relation].
  - The [setoid\_rewrite]'s semantics change when rewriting with a lemma: it can rewrite two different instantiations of the lemma at once. Use [setoid\_rewrite H at 1] for (almost) the usual semantics. [setoid\_rewrite] will also try to rewrite under binders now, and can succeed on different terms

3.10. Version 8.2

- than before. In particular, it will unify under let-bound variables. When called through [rewrite], the semantics are unchanged though.
- [Add Morphism term: id] has different semantics when used with parametric morphism: it will try to find a relation on the parameters too. The behavior has also changed with respect to default relations: the most recently declared Setoid/Relation will be used, the documentation explains how to customize this behavior.
- Parametric Relation and Morphism are declared differently, using the new [Add Parametric] commands, documented in the manual.
- Setoid\_Theory is now an alias to Equivalence, scripts building objects of type Setoid\_Theory need to unfold (or "red") the definitions of Reflexive, Symmetric and Transitive in order to get the same goals as before. Scripts which introduced variables explicitly will not break.
- The order of subgoals when doing [setoid\_rewrite] with side-conditions is always the same: first the new goal, then the conditions.
- New standard library modules Classes.Morphisms declares standard morphisms on refl / sym / trans relations. Classes.Morphisms\_Prop declares morphisms on propositional connectives and Classes. Morphisms\_Relations on generalized predicate connectives. Classes.Equivalence declares notations and tactics related to equivalences and Classes.SetoidTactics defines the setoid\_replace tactics and some support for the Add \* interface, notably the tactic applied automatically before each Add Morphism proof.
- User-defined subrelations are supported, as well as higher-order morphisms and rewriting under binders. The tactic is also extensible entirely in Ltac. The documentation has been updated to cover these features.
- [setoid\_rewrite] and [rewrite] now support the [at] modifier to select occurrences to rewrite, and both use the [setoid\_rewrite] code, even when rewriting with leibniz equality if occurrences are specified.

# Extraction

- Improved behavior of the Caml extraction of modules: name clashes should not happen anymore.
- The command Extract Inductive has now a syntax for infix notations. This allows in particular to map Coq lists and pairs onto Caml ones:
  - Extract Inductive list => list ["[]""(::)"].
  - Extract Inductive prod => "(\*)" [ "(,)" ].
- In pattern matchings, a default pattern "| \_ -> ..." is now used whenever possible if several branches are identical. For instance, functions corresponding to decidability of equalities are now linear instead of quadratic.
- A new instruction Extraction Blacklist id1 .. idn allows to prevent filename conflits with existing code, for instance when extracting module List to Ocaml.

## CogIDE

- CoqIDE font defaults to monospace so as indentation to be meaningful.
- CoqIDE supports nested goals and any other kind of declaration in the middle of a proof.
- Undoing non-tactic commands in CoqIDE works faster.
- New CoqIDE menu for activating display of various implicit informations.
- Added the possibility to choose the location of tabs in coqide: (in Edit->Preferences->Misc)
- New Open and Save As dialogs in CogIDE which filter \*.v files.

### Tools

- New stand-alone .vo files verifier "coqchk".
- Extended -I coqtop/coqc option to specify a logical dir: "-I dir -as coqdir".
- New coqtop/coqc option -exclude-dir to exclude subdirs for option -R.
- The binary "parser" has been renamed to "coq-parser".
- Improved coqdoc and dump of globalization information to give more meta-information on identifiers. All categories of Coq definitions are supported, which makes typesetting trivial in the generated documentation. Support for hyperlinking and indexing developments in the tex output has been implemented as well.

### Miscellaneous

- Coq installation provides enough files so that Ocaml's extensions need not the Coq sources to be compiled (this assumes O'Caml 3.10 and Camlp5).
- New commands "Set Whelp Server" and "Set Whelp Getter" to customize the Whelp search tool.
- Syntax of "Test Printing Let ref" and "Test Printing If ref" changed into "Test Printing Let for ref" and "Test Printing If for ref".
- An overhauled build system (new Makefiles); see dev/doc/build-system.txt.
- Add -browser option to configure script.
- Build a shared library for the C part of Coq, and use it by default on non-(Windows or MacOS) systems. Bytecode executables are now pure. The behaviour is configurable with -coqrumbyteflags, -coqtoolsbyteflags and -custom configure options.
- Complexity tests can be skipped by setting the environment variable CO-QTEST\_SKIPCOMPLEXITY.

# 3.11 Version 8.1

# 3.11.1 Summary of changes

Coq version 8.1 adds various new functionalities.

Benjamin Grégoire implemented an alternative algorithm to check the convertibility of terms in the Coq type checker. This alternative algorithm works by compilation to an efficient bytecode that is interpreted in an abstract machine similar to Xavier Leroy's ZINC machine. Convertibility is performed by comparing the normal forms. This alternative algorithm is specifically interesting for proofs by reflection. More generally, it is convenient in case of intensive computations.

Christine Paulin implemented an extension of inductive types allowing recursively non uniform parameters. Hugo Herbelin implemented sort-polymorphism for inductive types (now called template polymorphism).

Claudio Sacerdoti Coen improved the tactics for rewriting on arbitrary compatible equivalence relations. He also generalized rewriting to arbitrary transition systems.

Claudio Sacerdoti Coen added new features to the module system.

Benjamin Grégoire, Assia Mahboubi and Bruno Barras developed a new, more efficient and more general simplification algorithm for rings and semirings.

Laurent Théry and Bruno Barras developed a new, significantly more efficient simplification algorithm for fields.

3.11. Version 8.1

Hugo Herbelin, Pierre Letouzey, Julien Forest, Julien Narboux and Claudio Sacerdoti Coen added new tactic features.

Hugo Herbelin implemented matching on disjunctive patterns.

New mechanisms made easier the communication between Coq and external provers. Nicolas Ayache and Jean-Christophe Filliâtre implemented connections with the provers cvcl, Simplify and zenon. Hugo Herbelin implemented an experimental protocol for calling external tools from the tactic language.

Matthieu Sozeau developed Russell, an experimental language to specify the behavior of programs with subtypes.

A mechanism to automatically use some specific tactic to solve unresolved implicit has been implemented by Hugo Herbelin.

Laurent Théry's contribution on strings and Pierre Letouzey and Jean-Christophe Filliâtre's contribution on finite maps have been integrated to the Coq standard library. Pierre Letouzey developed a library about finite sets "à la Objective Caml". With Jean-Marc Notin, he extended the library on lists. Pierre Letouzey's contribution on rational numbers has been integrated and extended.

Pierre Corbineau extended his tactic for solving first-order statements. He wrote a reflection-based intuitionistic tautology solver.

Pierre Courtieu, Julien Forest and Yves Bertot added extra support to reason on the inductive structure of recursively defined functions.

Jean-Marc Notin significantly contributed to the general maintenance of the system. He also took care of coqdoc.

Pierre Castéran contributed to the documentation of (co-)inductive types and suggested improvements to the libraries.

Pierre Corbineau implemented a declarative mathematical proof language, usable in combination with the tactic-based style of proof.

Finally, many users suggested improvements of the system through the Coq-Club mailing list and bug-tracker systems, especially user groups from INRIA Rocquencourt, Radboud University, University of Pennsylvania and Yale University.

Palaiseau, July 2006 Hugo Herbelin

# 3.11.2 Details of changes in 8.1beta

### Logic

- Added sort-polymorphism on inductive families
- Allowance for recursively non uniform parameters in inductive types

### Syntax

- No more support for version 7 syntax and for translation to version 8 syntax.
- In fixpoints, the { struct ... } annotation is not mandatory any more when only one of the arguments has an inductive type
- Added disjunctive patterns in match-with patterns

- Support for primitive interpretation of string literals
- Extended support for Unicode ranges

### Vernacular commands

- Added "Print Ltac qualid" to print a user defined tactic.
- Added "Print Rewrite HintDb" to print the content of a DB used by autorewrite.
- Added "Print Canonical Projections".
- Added "Example" as synonym of "Definition".
- Added "Proposition" and "Corollary" as extra synonyms of "Lemma".
- New command "Whelp" to send requests to the Helm database of proofs formalized in the Calculus of Inductive Constructions.
- Command "functional induction" has been re-implemented from the new "Function" command.

## Ltac and tactic syntactic extensions

- New primitive "external" for communication with tool external to Coq
- New semantics for "match t with": if a clause returns a tactic, it is now applied to the current goal. If it fails, the next clause or next matching subterm is tried (i.e. it behaves as "match goal with" does). The keyword "lazymatch" can be used to delay the evaluation of tactics occurring in matching clauses.
- Hint base names can be parametric in auto and trivial.
- Occurrence values can be parametric in unfold, pattern, etc.
- Added entry constr\_may\_eval for tactic extensions.
- Low-priority term printer made available in ML-written tactic extensions.
- "Tactic Notation" extended to allow notations of tacticals.

### Tactics

- New implementation and generalization of setoid\_\* (setoid\_rewrite, setoid\_symmetry, setoid\_transitivity, setoid\_reflexivity and autorewite). New syntax for declaring relations and morphisms (old syntax still working with minor modifications, but deprecated).
- New implementation (still experimental) of the ring tactic with a built-in notion of coefficients and a better usage of setoids.
- New conversion tactic "vm\_compute": evaluates the goal (or an hypothesis) with a call-by-value strategy, using the compiled version of terms.
- When rewriting H where H is not directly a Coq equality, search first H for a registered setoid equality before starting to reduce in H. This is unlikely to break any script. Should this happen nonetheless, one can insert manually some "unfold ... in H" before rewriting.
- Fixed various bugs about (setoid) rewrite ... in ... (in particular bug #5941)
- "rewrite ... in" now accepts a clause as place where to rewrite instead of just a simple hypothesis name. For instance: rewrite H in H1,H2 |- \* means rewrite H in H1; rewrite H in H2; rewrite H rewrite H in \* |- will do try rewrite H in Hi for all hypothesis Hi <> H.
- Added "dependent rewrite term" and "dependent rewrite term in hyp".
- Added "autorewrite with ... in hyp [using ...]".
- Tactic "replace" now accepts a "by" tactic clause.
- Added "clear id" to clear all hypotheses except the ones depending in id.

3.11. Version 8.1

- The argument of Declare Left Step and Declare Right Step is now a term (it used to be a reference).
- Omega now handles arbitrary precision integers.
- Several bug fixes in Reflexive Omega (romega).
- Idtac can now be left implicit in a [...|...] construct: for instance, [ foo | | bar ] stands for [ foo | idtac | bar ].
- Fixed a "fold" bug (non critical but possible source of incompatibilities).
- Added classical\_left and classical\_right which transforms  $|-A \setminus B|$  into |-A| and |-B| respectively.
- Added command "Declare Implicit Tactic" to set up a default tactic to be used to solve unresolved subterms of term arguments of tactics.
- Better support for coercions to Sortclass in tactics expecting type arguments.
- Tactic "assert" now accepts "as" intro patterns and "by" tactic clauses.
- New tactic "pose proof" that generalizes "assert (id:=p)" with intro patterns.
- New introduction pattern "?" for letting Coq choose a name.
- Introduction patterns now support side hypotheses (e.g. intros []] on "(nat -> nat) -> nat" works).
- New introduction patterns "->" and "<-" for immediate rewriting of introduced hypotheses.
- Introduction patterns coming after non trivial introduction patterns now force full introduction of the first pattern (e.g. intros [[|] p] on nat->nat->nat now behaves like intros [[|?] p])
- Added "eassumption".
- Added option 'using lemmas' to auto, trivial and eauto.
- Tactic "congruence" is now complete for its intended scope (ground equalities and inequalities with constructors). Furthermore, it tries to equates goal and hypotheses.
- New tactic "rtauto" solves pure propositional logic and gives a reflective version of the available proof.
- Numbering of "pattern", "unfold", "simpl", ... occurrences in "match with" made consistent with the printing of the return clause after the term to match in the "match-with" construct (use "Set Printing All" to see hidden occurrences).
- Generalization of induction "induction x1...xn using scheme" where scheme is an induction principle with complex predicates (like the ones generated by function induction).
- Some small Ltac tactics has been added to the standard library (file Tactics.v):
  - f equal: instead of using the different f equalX lemmas
  - case\_eq: a "case" without loss of information. An equality stating the current situation is generated in every sub-cases.
  - swap : for a negated goal ~B and a negated hypothesis H:~A, swap H asks you to prove A from hypothesis B
  - revert : revert H is generalize H; clear H.

### Extraction

- All type parts should now disappear instead of sometimes producing \_ (for instance in Map.empty).
- Haskell extraction: types of functions are now printed, better unsafeCoerce mechanism, both for hugs and ghc.
- Scheme extraction improved, see http://www.pps.jussieu.fr/~letouzey/scheme.

· Many bug fixes.

### Modules

- Added "Locate Module qualid" to get the full path of a module.
- Module/Declare Module syntax made more uniform.
- Added syntactic sugar "Declare Module Export/Import" and "Module Export/Import".
- Added syntactic sugar "Module M(Export/Import X Y: T)" and "Module Type M(Export/Import X Y: T)" (only for interactive definitions)
- Construct "with" generalized to module paths: T with (Definition|Module) M1.M2....Mn.l := l'.

### Notations

- Option "format" aware of recursive notations.
- Added insertion of spaces by default in recursive notations w/o separators.
- No more automatic printing box in case of user-provided printing "format".
- New notation "exists! x:A, P" for unique existence.
- Notations for specific numerals now compatible with generic notations of numerals (e.g. "1" can be used to denote the unit of a group without hiding 1%nat)

### Libraries

- New library on String and Ascii characters (contributed by L. Thery).
- New library FSets+FMaps of finite sets and maps.
- New library QArith on rational numbers.
- Small extension of Zmin.V, new Zmax.v, new Zminmax.v.
- Reworking and extension of the files on classical logic and description principles (possible incompatibilities)
- Few other improvements in ZArith potentially exceptionally breaking the compatibility (useless hypothesys of Zgt\_square\_simpl and Zlt\_square\_simpl removed; fixed names mentioning letter O instead of digit 0; weaken premises in Z\_lt\_induction).
- Restructuration of Eqdep\_dec.v and Eqdep.v: more lemmas in Type.
- Znumtheory now contains a gcd function that can compute within Coq.
- More lemmas stated on Type in Wf.v, removal of redundant Acc iter and Acc iter2.
- Change of the internal names of lemmas in OmegaLemmas.
- Acc in Wf.v and clos\_refl\_trans in Relation\_Operators.v now rely on the allowance for recursively non uniform parameters (possible source of incompatibilities: explicit pattern-matching on these types may require to remove the occurrence associated to their recursively non uniform parameter).
- Coq.List.In\_dec has been set transparent (this may exceptionally break proof scripts, set it locally opaque for compatibility).
- More on permutations of lists in List.v and Permutation.v.
- List.v has been much expanded.
- New file SetoidList.v now contains results about lists seen with respect to a setoid equality.
- Library NArith has been expanded, mostly with results coming from Intmap (for instance a bitwise xor), plus also a bridge between N and Bitvector.

3.11. Version 8.1

• Intmap has been reorganized. In particular its address type "addr" is now N. User contributions known to use Intmap have been adapted accordingly. If you're using this library please contact us. A wrapper FMapIntMap now presents Intmap as a particular implementation of FMaps. New developments are strongly encouraged to use either this wrapper or any other implementations of FMap instead of using directly this obsolete Intmap.

### Tools

- New semantics for coqtop options ("-batch" expects option "-top dir" for loading vernac file that contains definitions).
- Tool coq makefile now removes custom targets that are file names in "make clean"
- New environment variable COQREMOTEBROWSER to set the command invoked to start the remote browser both in Coq and coqide. Standard syntax: "%s" is the placeholder for the URL.

# 3.11.3 Details of changes in 8.1gamma

### Syntax

• changed parsing precedence of let/in and fun constructions of Ltac: let x := t in e1; e2 is now parsed as let x := t in (e1;e2).

### Language and commands

- Added sort-polymorphism for definitions in Type (but finally abandoned).
- Support for implicit arguments in the types of parameters in (co-)fixpoints and (co-)inductive declarations.
- Improved type inference: use as much of possible general information. before applying irreversible unification heuristics (allow e.g. to infer the predicate in "(exist 0 (refl equal 0): {n:nat | n=0 })").
- Support for Miller-Pfenning's patterns unification in type synthesis (e.g. can infer P such that P x y = phi(x,y)).
- Support for "where" clause in cofixpoint definitions.
- New option "Set Printing Universes" for making Type levels explicit.

# Tactics

- Improved implementation of the ring and field tactics. For compatibility reasons, the previous tactics are renamed as legacy ring and legacy field, but should be considered as deprecated.
- New declarative mathematical proof language.
- Support for argument lists of arbitrary length in Tactic Notation.
- rewrite ... in H now fails if H is used either in an hypothesis or in the goal.
- The semantics of rewrite ... in \* has been slightly modified (see doc).
- Support for as clause in tactic injection.
- New forward-reasoning tactic "apply in".
- Ltac fresh operator now builds names from a concatenation of its arguments.
- New ltac tactic "remember" to abstract over a subterm and keep an equality
- Support for Miller-Pfenning's patterns unification in apply/rewrite/... (may lead to few incompatibilities generally now useless tactic calls).

## Bug fixes

- Fix for notations involving basic "match" expressions.
- Numerous other bugs solved (a few fixes may lead to incompatibilities).

# 3.11.4 Details of changes in 8.1

### Bug fixes

• Many bugs have been fixed (cf coq-bugs web page)

### Tactics

- New tactics ring, ring\_simplify and new tactic field now able to manage power to a positive integer constant. Tactic ring on Z and R, and field on R manage power (may lead to incompatibilities with V8.1gamma).
- Tactic field\_simplify now applicable in hypotheses.
- New field\_simplify\_eq for simplifying field equations into ring equations.
- Tactics ring, ring\_simplify, field, field\_simplify and field\_simplify\_eq all able to apply user-given equations to rewrite monoms on the fly (see documentation).

#### Libraries

• New file ConstructiveEpsilon.v defining an epsilon operator and proving the axiom of choice constructively for a countable domain and a decidable predicate.

# 3.12 Version 8.0

# 3.12.1 Summary of changes

Coq version 8 is a major revision of the Coq proof assistant. First, the underlying logic is slightly different. The so-called *impredicativity* of the sort Set has been dropped. The main reason is that it is inconsistent with the principle of description which is quite a useful principle for formalizing mathematics within classical logic. Moreover, even in an constructive setting, the impredicativity of Set does not add so much in practice and is even subject of criticism from a large part of the intuitionistic mathematician community. Nevertheless, the impredicativity of Set remains optional for users interested in investigating mathematical developments which rely on it.

Secondly, the concrete syntax of terms has been completely revised. The main motivations were

- a more uniform, purified style: all constructions are now lowercase, with a functional programming perfume (e.g. abstraction is now written fun), and more directly accessible to the novice (e.g. dependent product is now written forall and allows omission of types). Also, parentheses are no longer mandatory for function application.
- extensibility: some standard notations (e.g. "<" and ">") were incompatible with the previous syntax. Now all standard arithmetic notations (=, +, \*, /, <, <=, ... and more) are directly part of the syntax.

Together with the revision of the concrete syntax, a new mechanism of *interpretation scopes* permits to reuse the same symbols (typically +, -, \*, /, <, <=) in various mathematical theories without any ambiguities for Coq, leading to a largely improved readability of Coq scripts. New commands to easily add new symbols are also provided.

Coming with the new syntax of terms, a slight reform of the tactic language and of the language of commands has been carried out. The purpose here is a better uniformity making the tactics and commands easier to use and to remember.

3.12. Version 8.0 117

Thirdly, a restructuring and uniformization of the standard library of Coq has been performed. There is now just one Leibniz equality usable for all the different kinds of Coq objects. Also, the set of real numbers now lies at the same level as the sets of natural and integer numbers. Finally, the names of the standard properties of numbers now follow a standard pattern and the symbolic notations for the standard definitions as well.

The fourth point is the release of CoqIDE, a new graphical gtk2-based interface fully integrated with Coq. Close in style to the Proof General Emacs interface, it is faster and its integration with Coq makes interactive developments more friendly. All mathematical Unicode symbols are usable within CoqIDE.

Finally, the module system of Coq completes the picture of Coq version 8.0. Though released with an experimental status in the previous version 7.4, it should be considered as a salient feature of the new version.

Besides, Coq comes with its load of novelties and improvements: new or improved tactics (including a new tactic for solving first-order statements), new management commands, extended libraries.

Bruno Barras and Hugo Herbelin have been the main contributors of the reflection and the implementation of the new syntax. The smart automatic translator from old to new syntax released with Coq is also their work with contributions by Olivier Desmettre.

Hugo Herbelin is the main designer and implementer of the notion of interpretation scopes and of the commands for easily adding new notations.

Hugo Herbelin is the main implementer of the restructured standard library.

Pierre Corbineau is the main designer and implementer of the new tactic for solving first-order statements in presence of inductive types. He is also the maintainer of the non-domain specific automation tactics.

Benjamin Monate is the developer of the CoqIDE graphical interface with contributions by Jean-Christophe Filliâtre, Pierre Letouzey, Claude Marché and Bruno Barras.

Claude Marché coordinated the edition of the Reference Manual for Coq V8.0.

Pierre Letouzey and Jacek Chrząszcz respectively maintained the extraction tool and module system of Coq.

Jean-Christophe Filliâtre, Pierre Letouzey, Hugo Herbelin and other contributors from Sophia-Antipolis and Nijmegen participated in extending the library.

Julien Narboux built a NSIS-based automatic Coq installation tool for the Windows platform.

Hugo Herbelin and Christine Paulin coordinated the development which was under the responsibility of Christine Paulin.

Palaiseau & Orsay, Apr. 2004 Hugo Herbelin & Christine Paulin (updated Apr. 2006)

# 3.12.2 Details of changes in 8.0beta old syntax

## Logic

- Set now predicative by default
- New option -impredicative-set to set Set impredicative
- The standard library doesn't need impredicativity of Set and is compatible with the classical axioms which contradict Set impredicativity

## Syntax for arithmetic

- Notation "=" and "<>" in Z and R are no longer implicitly in Z or R (with possible introduction of a coercion), use <Z>...=... or <Z>.... instead
- Locate applied to a simple string (e.g. "+") searches for all notations containing this string

### Vernacular commands

- "Declare ML Module" now allows to import .cma files. This avoids to use a bunch of "Declare ML Module" statements when using several ML files.
- "Set Printing Width n" added, allows to change the size of width printing.
- "Implicit Variables Type x,y:t" (new syntax: "Implicit Types x y:t") assigns default types for binding variables.
- Declarations of Hints and Notation now accept a "Local" flag not to be exported outside the current file even if not in section
- "Print Scopes" prints all notations
- New command "About name" for light printing of type, implicit arguments, etc.
- New command "Admitted" to declare incompletely proven statement as axioms
- New keyword "Conjecture" to declare an axiom intended to be provable
- SearchAbout can now search for lemmas referring to more than one constant and on substrings of the name of the lemma
- "Print Implicit" displays the implicit arguments of a constant
- Locate now searches for all names having a given suffix
- New command "Functional Scheme" for building an induction principle from a function defined by case analysis and fix.

### Commands

• new coqtop/coqc option -dont-load-proofs not to load opaque proofs in memory

### Implicit arguments

- Inductive in sections declared with implicits now "discharged" with implicits (like constants and variables)
- Implicit Arguments flags are now synchronous with reset
- New switch "Unset/Set Printing Implicits" (new syntax: "Unset/Set Printing Implicit") to globally control printing of implicits

## Grammar extensions

• Many newly supported UTF-8 encoded unicode blocks - Greek letters (0380-03FF), Hebrew letters (U05D0-05EF), letter-like symbols (2100-214F, that includes double N,Z,Q,R), prime signs (from 2080-2089) and characters from many written languages are valid in identifiers - mathematical operators (2200-22FF), supplemental mathematical operators (2A00-2AFF), miscellaneous technical (2300-23FF that includes sqrt symbol), miscellaneous symbols (2600-26FF), arrows (2190-21FF and 2900-297F), invisible mathematical operators (from 2080-2089), ... are valid symbols

### Library

- New file about the factorial function in Arith
- An additional elimination Acc\_iter for Acc, simpler than Acc\_rect. This new elimination principle is used for definition well\_founded\_induction.

3.12. Version 8.0

- New library NArith on binary natural numbers
- R is now of type Set
- Restructuration in ZArith library
  - "true\_sub" used in Zplus now a definition, not a local one (source of incompatibilities in proof referring to true sub, may need extra Unfold)
  - Some lemmas about minus moved from fast integer to Arith/Minus.v (le minus, lt mult left) (theoretical source of incompatibilities)
  - Several lemmas moved from auxiliary.v and zarith aux.v to fast integer.v (theoretical source of incompatibilities)
  - Variables names of iff trans changed (source of incompatibilities)
  - ZArith lemmas named OMEGA something or fast\_ something, and lemma new\_var are now out of ZArith (except OMEGA2)
  - Redundant ZArith lemmas have been renamed: for the following pairs, use the second name (Zle Zmult right2, Zle mult simpl), (OMEGA2, Zle 0 plus), (Zplus assoc l, Zplus\_assoc), (Zmult\_one, Zmult\_1\_n), (Zmult\_assoc\_l, Zmult\_assoc), (Zmult\_minus\_distr, Zmult Zminus distr 1) (add un double moins un xO, is double moins un), (Rlt\_monotony\_rev,Rlt\_monotony\_contra) (source of incompatibilities)
- changes (no more implicit arguments in Zmult\_Zminus\_distr\_l and Zmult Zminus distr r, lemmas moved from Zcomplements to other files) (rare source of incompatibilities)
- New lemmas provided by users added

## Tactic language

- Fail tactic now accepts a failure message
- Idtac tactic now accepts a message
- New primitive tactic "FreshId" (new syntax: "fresh") to generate new names
- Debugger prints levels of calls

### Tactics

120

- Replace can now replace proofs also
- Fail levels are now decremented at "Match Context" blocks only and if the right-hand-side of "Match term With" are tactics, these tactics are never evaluated immediately and do not induce backtracking (in contrast with "Match Context")
- Quantified names now avoid global names of the current module (like Intro names did) [source of rare incompatibilities: 2 changes in the set of user contribs
- NewDestruct/NewInduction accepts intro patterns as introduction names
- NewDestruct/NewInduction now work for non-inductive type using option "using"
- A NewInduction naming bug for inductive types with functional arguments (e.g. the accessibility predicate) has been fixed (source of incompatibilities)
- Symmetry now applies to hypotheses too
- Inversion now accept option "as [ ... ]" to name the hypotheses
- Contradiction now looks also for contradictory hypotheses stating ~A and A (source of incompatibility)
- "Contradiction c" try to find an hypothesis in context which contradicts the type of c

- Ring applies to new library NArith (require file NArithRing)
- Field now works on types in Set
- Auto with reals now try to replace le by ge (Rge\_le is no longer an immediate hint), resulting in shorter proofs
- Instantiate now works in hyps (syntax : Instantiate in ...)
- Some new tactics: EConstructor, ELeft, Eright, ESplit, EExists
- New tactic "functional induction" to perform case analysis and induction following the definition of a function
- Clear now fails when trying to remove a local definition used by a constant appearing in the current goal

# Extraction (See details in plugins/extraction/CHANGES)

- The old commands: (Recursive) Extraction Module M. are now: (Recursive) Extraction Library M. To use these commands, M should come from a library M.v
- The other syntax Extraction & Recursive Extraction now accept module names as arguments.

### Bugs

• see coq-bugs server for the complete list of fixed bugs

### Miscellaneous

• Implicit parameters of inductive types definition now taken into account for inferring other implicit arguments

## Incompatibilities

- Persistence of true\_sub (4 incompatibilities in Coq user contributions)
- Variable names of some constants changed for a better uniformity (2 changes in Coq user contributions)
- Naming of quantified names in goal now avoid global names (2 occurrences)
- NewInduction naming for inductive types with functional arguments (no incompatibility in Coq user contributions)
- Contradiction now solve more goals (source of 2 incompatibilities)
- Merge of eq and eqT may exceptionally result in subgoals now solved automatically
- Redundant pairs of ZArith lemmas may have different names: it may cause "Apply/Rewrite with" to fail if using the first name of a pair of redundant lemmas (this is solved by renaming the variables bound by "with"; 3 incompatibilities in Coq user contribs)
- ML programs referring to constants from fast\_integer.v must use "Coqlib.gen\_constant\_modules Co-qlib.zarith\_base\_modules" instead

# 3.12.3 Details of changes in 8.0beta new syntax

# New concrete syntax

- A completely new syntax for terms
- A more uniform syntax for tactics and the tactic language
- A few syntactic changes for vernacular commands
- A smart automatic translator translating V8.0 files in old syntax to files valid for V8.0

3.12. Version 8.0

### Syntax extensions

- "Grammar" for terms disappears
- "Grammar" for tactics becomes "Tactic Notation"
- "Syntax" disappears
- Introduction of a notion of interpretation scope allowing to use the same notations in various contexts without using specific delimiters (e.g the same expression "4<=3+x" is interpreted either in "nat", "positive", "N" (previously "entier"), "Z", "R", depending on which interpretation scope is currently open) [see documentation for details]
- Notation now mandatorily requires a precedence and associativity (default was to set precedence to 1 and associativity to none)

## Revision of the standard library

- Many lemmas and definitions names have been made more uniform mostly in Arith, NArith, ZArith and Reals (e.g: "times" -> "Pmult", "times\_sym" -> "Pmult\_comm", "Zle\_Zmult\_pos\_right" -> "Zmult\_le compat\_r", "SUPERIEUR" -> "Gt", "ZERO" -> "Z0")
- Order and names of arguments of basic lemmas on nat, Z, positive and R have been made uniform.
- Notions of Coq initial state are declared with (strict) implicit arguments
- eq merged with eqT: old eq disappear, new eq (written =) is old eqT and new eqT is syntactic sugar for new eq (notation == is an alias for = and is written as it, exceptional source of incompatibilities)
- Similarly, ex, ex2, all, identity are merged with exT, exT2, allT, identityT
- Arithmetical notations for nat, positive, N, Z, R, without needing any backquote or double-backquotes
  delimiters.
- In Lists: new concrete notations; argument of nil is now implicit
- All changes in the library are taken in charge by the translator

## Semantical changes during translation

- Recursive keyword set by default (and no longer needed) in Tactic Definition
- Set Implicit Arguments is strict by default in new syntax
- reductions in hypotheses of the form "... in H" now apply to the type also if H is a local definition
- etc

### Gallina

- New syntax of the form "Inductive bool: Set := true, false: bool." for enumerated types
- Experimental syntax of the form p.(fst) for record projections (activable with option "Set Printing Projections" which is recognized by the translator)

## Known problems of the automatic translation

- iso-latin-1 characters are no longer supported: move your files to 7-bits ASCII or unicode before translation (switch to unicode is automatically done if a file is loaded and saved again by coqide)
- Renaming in ZArith: incompatibilities in Coq user contribs due to merging names INZ, from Reals, and inject\_nat.
- Renaming and new lemmas in ZArith: may clash with names used by users
- Restructuration of ZArith: replace requirement of specific modules in ZArith by "Require Import ZArith\_base" or "Require Import ZArith"

- Some implicit arguments must be made explicit before translation: typically for "length nil", the implicit argument of length must be made explicit
- Grammar rules, Infix notations and V7.4 Notations must be updated wrt the new scheme for syntactic extensions (see translator documentation)
- Unsafe for annotation Cases when constructors coercions are used or when annotations are eta-reduced predicates

# 3.12.4 Details of changes in 8.0

## Vernacular commands

- New option "Set Printing All" to deactivate all high-level forms of printing (implicit arguments, coercions, destructing let, if-then-else, notations, projections)
- "Functional Scheme" and "Functional Induction" extended to polymorphic types and dependent types
- Notation now allows recursive patterns, hence recovering parts of the functionalities of pre-V8 Grammar/Syntax commands
- Command "Print." discontinued.
- Redundant syntax "Implicit Arguments On/Off" discontinued

### New syntax

• Semantics change of the if-then-else construction in new syntax: "if c then t1 else t2" now stands for "match c with c1  $\_$  ...  $\_$  => t1 | c2  $\_$  ...  $\_$  => t2 end" with no dependency of t1 and t2 in the arguments of the constructors; this may cause incompatibilities for files translated using coq 8.0beta

### Interpretation scopes

- Delimiting key %bool for bool scope added
- Import no more needed to activate argument scopes from a module

## Tactics and the tactic Language

- Semantics of "assert" is now consistent with the reference manual
- New tactics stepl and stepr for chaining transitivity steps
- Tactic "replace ... with ... in" added
- Intro patterns now supported in Ltac (parsed with prefix "ipattern:")

## Executables and tools

- Added option -top to change the name of the toplevel module "Top"
- Cogdoc updated to new syntax and now part of Cog sources
- XML exportation tool now exports the structure of vernacular files (cf chapter 13 in the reference manual)

## User contributions

• User contributions have been updated to the new syntax

### Bug fixes

• Many bugs have been fixed (cf cog-bugs web page)

3.12. Version 8.0

**CHAPTER** 

**FOUR** 

# THE LANGUAGE

# 4.1 The Gallina specification language

This chapter describes Gallina, the specification language of Coq. It allows developing mathematical theories and to prove specifications of programs. The theories are built from axioms, hypotheses, parameters, lemmas, theorems and definitions of constants, functions, predicates and sets. The syntax of logical objects involved in theories is described in Section *Terms*. The language of commands, called *The Vernacular* is described in Section *The Vernacular*.

In Coq, logical objects are typed to ensure their logical correctness. The rules implemented by the typing algorithm are described in Chapter Calculus of Inductive Constructions.

# 4.1.1 About the grammars in the manual

Grammars are presented in Backus-Naur form (BNF). Terminal symbols are set in black typewriter font. In addition, there are special notations for regular expressions.

An expression enclosed in square brackets [...] means at most one occurrence of this expression (this corresponds to an optional component).

The notation "entry sep ... sep entry" stands for a non empty sequence of expressions parsed by entry and separated by the literal "sep".

Similarly, the notation "entry ... entry" stands for a non empty sequence of expressions parsed by the "entry" entry, without any separator between.

At the end, the notation "[entry sep ... sep entry]" stands for a possibly empty sequence of expressions parsed by the "entry" entry, separated by the literal "sep".

## 4.1.2 Lexical conventions

**Blanks** Space, newline and horizontal tab are considered blanks. Blanks are ignored but they separate tokens.

Comments Comments are enclosed between (\* and \*). They can be nested. They can contain any character. However, embedded *string* literals must be correctly closed. Comments are treated as blanks.

**Identifiers and field identifiers** Identifiers, written *ident*, are sequences of letters, digits, \_ and ', that do not start with a digit or '. That is, they are recognized by the following grammar (except that the string \_ is reserved; it is not a valid identifier):

<sup>&</sup>lt;sup>1</sup> This is similar to the expression "entry { sep entry }" in standard BNF, or "entry ( sep entry )\*" in the syntax of regular expressions.

All characters are meaningful. In particular, identifiers are case-sensitive. unicode\_letter non-exhaustively includes Latin, Greek, Gothic, Cyrillic, Arabic, Hebrew, Georgian, Hangul, Hiragana and Katakana characters, CJK ideographs, mathematical letter-like symbols and non-breaking space. unicode\_id\_part non-exhaustively includes symbols for prime letters and subscripts.

Field identifiers, written field, are identifiers prefixed by . (dot) with no blank between the dot and the identifier. They are used in the syntax of qualified identifiers.

Numerals Numerals are sequences of digits with an optional fractional part and exponent, optionally preceded by a minus sign. *int* is an integer; a numeral without fractional or exponent parts. *num* is a non-negative integer. Underscores embedded in the digits are ignored, for example 1\_000\_000 is the same as 1000000.

```
num[. num][exp[siqn]num]
numeral
         ::=
                 [-] num
int
          ::=
num
                 digit...digit
          ::=
digit
          ::=
                 0..9
          ::=
                 e I E
exp
sign
                 + | -
```

**Strings** Strings begin and end with " (double quote). Use "" to represent a double quote character within a string. In the grammar, strings are identified with string.

Keywords The following character sequences are reserved keywords that cannot be used as identifiers:

```
_ Axiom CoFixpoint Definition Fixpoint Hypothesis IF Parameter Prop SProp Set Theorem Type Variable as at by cofix discriminated else end exists exists2 fix for forall fun if in lazymatch let match multimatch return then using where with
```

Note that plugins may define additional keywords when they are loaded.

Other tokens The set of tokens defined at any given time can vary because the *Notation* command can define new tokens. A *Require* command may load more notation definitions, while the end of a *Section* may remove notations. Some notations are defined in the basic library (see *The Coq library*) and are normally loaded automatically at startup time.

Here are the character sequences that Coq directly defines as tokens without using Notation (omitting 25 specialized tokens that begin with #int63\_):

```
! #[ % & ' ( () (bfs) (dfs) ) * ** + , - ->
. .( .. ... / : ::= := :> :>> ; < <+ <- <:
<<: <= =>> >-> >= ? @ @{ [ [= ] _ eqn
`( `{ { | | |- || }
```

When multiple tokens match the beginning of a sequence of characters, the longest matching token is used. Occasionally you may need to insert spaces to separate tokens. For example, if ~ and ~~ are both defined as tokens, the inputs ~ ~ and ~~ generate different tokens, whereas if ~~ is not defined, then the two inputs are equivalent.

# 4.1.3 Terms

## Syntax of terms

The following grammars describe the basic syntax of the terms of the Calculus of Inductive Constructions (also called Cic). The formal presentation of Cic is given in Chapter Calculus of Inductive Constructions. Extensions of this syntax are given in Chapter Extensions of Gallina. How to customize the syntax is described in Chapter Syntax extensions and interpretation scopes.

```
term
                     forall binders, term
              ::=
                     fun binders => term
                     fix fix bodies
                     cofix cofix_bodies
                     let ident [binders] [: term] := term in term
                     let fix fix_body in term
                     let cofix cofix_body in term
                     let ( [name , ... , name] ) [dep ret type] := term in term
                     let ' pattern [in term] := term [return_type] in term
                     if term [dep_ret_type] then term else term
                     term : term
                     term <: term
                     term :>
                     term -> term
                     term arg ... arg
                     @ qualid [term ... term]
                     term % ident
                     match match_item , ... , match_item [return_type] with
                     [[|] equation | ... | equation] end
                     qualid
                     sort
                     num
                     ( term )
arg
                     term
                     (ident := term)
binders
                     binder ... binder
              ::=
binder
              ::=
                     name
                     ( name ... name : term )
                     (name [: term] := term)
                     ' pattern
                     ident
name
              ::=
                     ident | qualid field
qualid
              ::=
sort
                     SProp | Prop | Set | Type
              ::=
fix_bodies
              ::=
                     fix_body
                     fix_body with fix_body with ... with fix_body for ident
cofix bodies
              ::=
                     cofix body
                     cofix_body with cofix_body with ... with cofix_body for ident
                     ident binders [annotation] [: term] := term
fix_body
              ::=
cofix_body
                     ident [binders] [: term] := term
              ::=
                     { struct ident }
annotation
              ::=
                     term [as name] [in qualid [pattern ... pattern]]
match_item
dep_ret_type
                     [as name] return_type
              ::=
```

```
return_type
               ::=
                     return term
                     mult_pattern | ... | mult_pattern => term
equation
mult_pattern
               ::=
                     pattern , ... , pattern
                     qualid pattern ... pattern
pattern
               ::=
                     @ qualid pattern ... pattern
                     pattern as ident
                     pattern % ident
                     qualid
                     num
                     ( pattern | ... | pattern )
```

## **Types**

Coq terms are typed. Coq types are recognized by the same syntactic class as term. We denote by type the semantic subclass of types inside the syntactic class term.

# Qualified identifiers and simple identifiers

Qualified identifiers (qualid) denote global constants (definitions, lemmas, theorems, remarks or facts), global variables (parameters or axioms), inductive types or constructors of inductive types. Simple identifiers (or shortly ident) are a syntactic subset of qualified identifiers. Identifiers may also denote local variables, while qualified identifiers do not.

### **Numerals**

Numerals have no definite semantics in the calculus. They are mere notations that can be bound to objects through the notation mechanism (see Chapter *Syntax extensions and interpretation scopes* for details). Initially, numerals are bound to Peano's representation of natural numbers (see *Datatypes*).

Note: Negative integers are not at the same level as num, for this would make precedence unnatural.

## **Sorts**

There are four sorts SProp, Prop, Set and Type.

- SProp is the universe of definitionally irrelevant propositions (also called strict propositions).
- Prop is the universe of *logical propositions*. The logical propositions themselves are typing the proofs. We denote propositions by form. This constitutes a semantic subclass of the syntactic class *term*.
- Set is the universe of *program types* or *specifications*. The specifications themselves are typing the programs. We denote specifications by specif. This constitutes a semantic subclass of the syntactic class *term*.
- Type is the type of sorts.

More on sorts can be found in Section Sorts.

### **Binders**

Various constructions such as fun, forall, fix and cofix bind variables. A binding is represented by an identifier. If the binding variable is not used in the expression, the identifier can be replaced by the symbol \_. When the type of a bound variable cannot be synthesized by the system, it can be specified with the notation (ident: type). There is also a notation for a sequence of binding variables sharing the same type: (ident : type). A binder can also be any pattern prefixed by a quote, e.g. '(x,y).

Some constructions allow the binding of a variable to value. This is called a "let-binder". The entry *binder* of the grammar accepts either an assumption binder as defined above or a let-binder. The notation in the latter case is (*ident* := *term*). In a let-binder, only one variable can be introduced at the same time. It is also possible to give the type of the variable as follows: (*ident* : *type* := *term*).

Lists of *binder*s are allowed. In the case of fun and forall, it is intended that at least one binder of the list is an assumption otherwise fun and forall gets identical. Moreover, parentheses can be omitted in the case of a single sequence of bindings sharing the same type (e.g.: fun  $(x \ y \ z : A) \Rightarrow t$  can be shortened in fun  $x \ y \ z : A \Rightarrow t$ ).

### **Abstractions**

The expression fun ident: type => term defines the abstraction of the variable ident, of type type, over the term term. It denotes a function of the variable ident that evaluates to the expression term (e.g. fun x : A => x denotes the identity function on type A). The keyword fun can be followed by several binders as given in Section Binders. Functions over several variables are equivalent to an iteration of one-variable functions. For instance the expression fun  $ident_i$ : type => term denotes the same function as  $fun ident_i$ : type => term. If a let-binder occurs in the list of binders, it is expanded to a let-in definition (see Section Let-in definitions).

## **Products**

The expression forall *ident*: *type*, *term* denotes the *product* of the variable *ident* of type *type*, over the term *term*. As for abstractions, forall is followed by a binder list, and products over several variables are equivalent to an iteration of one-variable products. Note that *term* is intended to be a type.

If the variable *ident* occurs in *term*, the product is called *dependent product*. The intention behind a dependent product forall x : A, B is twofold. It denotes either the universal quantification of the variable x of type A in the proposition B or the functional dependent product from A to B (a construction usually written  $\Pi_{x:A}.B$  in set theory).

Non dependent product types have a special notation: A -> B stands for forall \_ : A, B. The non dependent product is used both to denote the propositional implication and function types.

## **Applications**

The expression  $term_{fun}$  term denotes the application of  $term_{fun}$  (which is expected to have a function type) to term.

The expression  $term_{fun}$   $term_i$  denotes the application of the term  $term_{fun}$  to the arguments  $term_i$ . It is equivalent to ( ... (  $term_{fun}$   $term_i$  ) ... )  $term_n$ : associativity is to the left.

The notation (*ident* := *term*) for arguments is used for making explicit the value of implicit arguments (see Section *Explicit applications*).

### Type cast

```
The expression term: type is a type cast expression. It enforces the type of term to be type.

term <: type locally sets up the virtual machine for checking that term has type type.

term <<: type uses native compilation for checking that term has type type.
```

## Inferable subterms

Expressions often contain redundant pieces of information. Subterms that can be automatically inferred by Coq can be replaced by the symbol \_ and Coq will guess the missing piece of information.

#### Let-in definitions

```
let ident := term in term' denotes the local binding of term to the variable ident in term'. There is a syntactic sugar for let-in definition of functions: let ident binder := term in term' stands for let ident := fun binder => term in term'.
```

## Definition by case analysis

Objects of inductive types can be destructured by a case-analysis construction called *pattern matching* expression. A pattern matching expression is used to analyze the structure of an inductive object and to apply specific treatments accordingly.

This paragraph describes the basic form of pattern matching. See Section Multiple and nested pattern matching and Chapter Extended pattern matching for the description of the general form. The basic form of pattern matching is characterized by a single match\_item expression, a mult\_pattern restricted to a single pattern and pattern restricted to the form qualid ident.

The expression match " $term_0$  return\_type with  $pattern_1 = > term_1 \mid ... \mid pattern_n = > term_n$  end" denotes a pattern matching over the term  $term_0$  (expected to be of an inductive type I). The terms  $term_1...term_n$  are the branches of the pattern matching expression. Each of  $pattern_i$  has a form qualid ident where qualid must denote a constructor. There should be exactly one branch for every constructor of I.

The return\_type expresses the type returned by the whole match expression. There are several cases. In the non dependent case, all branches have the same type, and the return\_type is the common type of branches. In this case, return\_type can usually be omitted as it can be inferred from the type of the branches<sup>2</sup>.

In the dependent case, there are three subcases. In the first subcase, the type in each branch may depend on the exact value being matched in the branch. In this case, the whole pattern matching itself depends on the term being matched. This dependency of the term being matched in the return type is expressed with an "as ident" clause where ident is dependent in the return type. For instance, in the following example:

 $<sup>^{2}</sup>$  Except if the inductive type is empty in which case there is no equation that can be used to infer the return type.

(continued from previous page)

```
| false => or_intror (eq bool false true) (eq bool false false) (eq_refl bool false) end.
```

the branches have respective types "or (eq bool true true) (eq bool true false)" and "or (eq bool false true) (eq bool false false)" while the whole pattern matching expression has type "or (eq bool b true) (eq bool b false)", the identifier b being used to represent the dependency.

**Note:** When the term being matched is a variable, the **as** clause can be omitted and the term being matched can serve itself as binding name in the return type. For instance, the following alternative definition is accepted and has the same meaning as the previous one.

```
Definition bool_case (b:bool) : or (eq bool b true) (eq bool b false) :=
match b return or (eq bool b true) (eq bool b false) with
| true => or_introl (eq bool true true) (eq bool true false) (eq_refl bool true)
| false => or_intror (eq bool false true) (eq bool false false) (eq_refl bool false)
end.
```

The second subcase is only relevant for annotated inductive types such as the equality predicate (see Section Equality), the order predicate on natural numbers or the type of lists of a given length (see Section Matching objects of dependent types). In this configuration, the type of each branch can depend on the type dependencies specific to the branch and the whole pattern matching expression has a type determined by the specific dependencies in the type of the term being matched. This dependency of the return type in the annotations of the inductive type is expressed using a "in  $I_{-}$  ...  $pattern_n$ " clause, where

- *I* is the inductive type of the term being matched;
- the \_ are matching the parameters of the inductive type: the return type is not dependent on them.
- the  $pattern_i$  are matching the annotations of the inductive type: the return type is dependent on them
- in the basic case which we describe below, each  $pattern_i$  is a name  $ident_i$ ; see Patterns in in for the general case

For instance, in the following example:

```
Definition eq_sym (A:Type) (x y:A) (H:eq A x y) : eq A y x := match H in eq _ z return eq A z x with | eq_refl _ => eq_refl A x end.
```

the type of the branch is eq  $A \times x$  because the third argument of eq is x in the type of the pattern eq\_refl. On the contrary, the type of the whole pattern matching expression has type eq  $A \times x$  because the third argument of eq is y in the type of y. This dependency of the case analysis in the third argument of eq is expressed by the identifier y in the return type.

Finally, the third subcase is a combination of the first and second subcase. In particular, it only applies to pattern matching on terms in a type with annotations. For this third subcase, both the clauses as and in are available.

There are specific notations for case analysis on types with one or two constructors: if ... then ... else ... and let (...,...) := ... in ... (see Sections Pattern-matching on boolean values: the if expression and Irrefutable patterns: the destructuring let variants).

### **Recursive functions**

The expression "fix  $ident_1$   $binder_1$ :  $type_1 := term_1$  with … with  $ident_n$   $binder_n$ :  $type_n := term_n$  for  $ident_i$ " denotes the i-th component of a block of functions defined by mutual structural recursion. It is the local counterpart of the Fixpoint command. When n = 1, the "for  $ident_i$ " clause is omitted.

The expression "cofix  $ident_1$   $binder_1$ :  $type_1$  with … with  $ident_n$   $binder_n$ :  $type_n$  for  $ident_i$ " denotes the i-th component of a block of terms defined by a mutual guarded co-recursion. It is the local counterpart of the CoFixpoint command. When n=1, the "for  $ident_i$ " clause is omitted.

The association of a single fixpoint and a local definition have a special syntax: let fix *ident binders* := *term* in stands for let *ident* := fix *ident binders* := *term* in. The same applies for co-fixpoints.

# 4.1.4 The Vernacular

```
decorated-sentence
                            [ decoration ... decoration ] sentence
                     ::=
                            assumption
sentence
                            definition
                            inductive
                            fixpoint
                            assertion proof
                            assumption_keyword assums.
assumption
                     ::=
assumption_keyword
                            Axiom | Conjecture
                     ::=
                            Parameter | Parameters
                            Variable | Variables
                            Hypothesis | Hypotheses
                            ident ... ident : term
assums
                     ::=
                            ( ident ... ident : term ) ... ( ident ... ident : term )
                            [Local] Definition ident [binders] [: term] := term .
definition
                     ::=
                            Let ident [binders] [: term] := term .
inductive
                            Inductive ind_body with ... with ind_body .
                     ::=
                            CoInductive ind_body with ... with ind_body .
ind_body
                            ident [binders] : term :=
                     ::=
                            [[|] ident [binders] [:term] | ... | ident [binders] [:term]]
fixpoint
                     ::=
                            Fixpoint fix\_body with ... with fix\_body .
                            CoFixpoint cofix\_body with ... with cofix\_body .
                     ::=
                            assertion_keyword ident [binders] : term .
assertion
                            Theorem | Lemma
assertion_keyword
                            Remark | Fact
                            Corollary | Property | Proposition
                            Definition | Example
                           Proof . ... Qed .
proof
                     ::=
                            Proof . ... Defined .
                            Proof . ... Admitted .
                            #[ attributes ]
decoration
                     ::=
attributes
                     ::=
                            [attribute, ..., attribute]
attribute
                            ident
                     ::=
                            ident = string
                            ident ( attributes )
```

This grammar describes *The Vernacular* which is the language of commands of Gallina. A sentence of the vernacular language, like in many natural languages, begins with a capital letter and ends with a dot.

Sentences may be decorated with so-called attributes, which are described in the corresponding section (At-

### tributes).

The different kinds of command are described hereafter. They all suppose that the terms occurring in the sentences are well-typed.

### **Assumptions**

Assumptions extend the environment with axioms, parameters, hypotheses or variables. An assumption binds an *ident* to a *type*. It is accepted by Coq if and only if this *type* is a correct type in the environment preexisting the declaration and if *ident* was not previously defined in the same module. This *type* is considered to be the type (or specification, or statement) assumed by *ident* and we say that *ident* has type *type*.

## Command: Parameter ident : type

This command links type to the name ident as its specification in the global context. The fact asserted by type is thus assumed as a postulate.

Error: ident already exists.

Variant: Parameter ident : type


Adds several parameters with specification type.

Variant: Parameter ( ident : type )

Adds blocks of parameters with different specifications.

Variant: Local Parameter ( ident : type )

Such parameters are never made accessible through their unqualified name by *Import* and its variants. You have to explicitly give their fully qualified name to refer to them.



( ident : type ) . For their meaning inside a section, see Variable in Section

Warning: ident is declared as a local axiom [local-declaration, scope] Warning generated when using Variable instead of Local Parameter.

**Note:** It is advised to use the commands <code>Axiom</code>, <code>Conjecture</code> and <code>Hypothesis</code> (and their plural forms) for logical postulates (i.e. when the assertion <code>type</code> is of sort <code>Prop</code>), and to use the commands <code>Parameter</code> and <code>Variable</code> (and their plural forms) in other cases (corresponding to the declaration of an abstract mathematical entity).

#### See also:

Section Section mechanism.

### **Definitions**

Definitions extend the environment with associations of names to terms. A definition can be seen as a way to give a meaning to a name or as a way to abbreviate a term. In any case, the name can later be replaced at any time by its definition.

The operation of unfolding a name into its definition is called  $\delta$ -conversion (see Section  $\delta$ -reduction). A definition is accepted by the system if and only if the defined term is well-typed in the current context of the definition and if the name is not already used. The name defined by the definition is called a *constant* and the term it refers to is its *body*. A definition has a type which is the type of its body.

A formal presentation of constants and environments is given in Section Typing rules.

# Command: Definition ident := term

This command binds term to the name ident in the environment, provided that term is well-typed.

Error: ident already exists.

Variant: Definition ident : type := term

This variant checks that the type of *term* is definitionally equal to *type*, and registers *ident* as being of type *type*, and bound to value *term*.

Error: The term term has type type while it is expected to have type type'.

Variant: Definition ident binders : type := term

This is equivalent to Definition ident : forall binders, type := fun binders => term.

Variant: Local Definition ident binders : type := term

Such definitions are never made accessible through their unqualified name by *Import* and its variants. You have to explicitly give their fully qualified name to refer to them.

Variant: Local Example ident binders : type := term
This is equivalent to Definition.

Variant: Let ident := term

Outside of any section, this variant is a synonym of Local Definition *ident* := *term*. For its meaning inside a section, see *Let* in *Section mechanism*.

Warning: ident is declared as a local definition [local-declaration, scope] Warning generated when using Let instead of Local Definition.

### See also:

Section Section mechanism, commands Opaque, Transparent, and tactic unfold.

### Inductive definitions

We gradually explain simple inductive types, simple annotated inductive types, simple parametric inductive types, mutually inductive types. We explain also co-inductive types.

## Simple inductive types

```
Command: Inductive ident : sort := | ident : type | ident : type
```

This command defines a simple inductive type and its constructors. The first *ident* is the name of the inductively defined type and *sort* is the universe where it lives. The next *idents* are the names of its constructors and *type* their respective types. Depending on the universe where the inductive type *ident* lives (e.g. its type *sort*), Coq provides a number of destructors. Destructors are named *ident\_sind*,:token:ident\_ind, *ident\_rec* or *ident\_rect* which respectively correspond to elimination principles on SProp, Prop, Set and Type. The type of the destructors expresses structural induction/recursion principles over objects of type *ident*. The constant *ident\_ind* is always provided, whereas *ident\_rec* and *ident\_rect* can be impossible to derive (for example, when *ident* is a proposition).

## Error: Non strictly positive occurrence of ident in type.

The types of the constructors have to satisfy a positivity condition (see Section Positivity Condition). This condition ensures the soundness of the inductive definition. The positivity checking can be disabled using the Positivity Checking flag (see Controlling Typing Flags).

## Error: The conclusion of type is not valid; it must be built from ident.

The conclusion of the type of the constructors must be the inductive type *ident* being defined (or *ident* applied to arguments in the case of annotated inductive types — cf. next section).

## Example

The set of natural numbers is defined as:

```
Inductive nat : Set :=
| 0 : nat
| S : nat -> nat.
    nat is defined
    nat_rect is defined
    nat_ind is defined
    nat_rec is defined
    nat_rec is defined
    nat_sind is defined
```

The type nat is defined as the least Set containing O and closed by the S constructor. The names nat, O and S are added to the environment.

Now let us have a look at the elimination principles. They are three of them: nat\_ind, nat\_rec and nat\_rect. The type of nat\_ind is:

This is the well known structural induction principle over natural numbers, i.e. the second-order form of Peano's induction principle. It allows proving some universal property of natural numbers (forall n:nat, P n) by induction on n.

The types of nat\_rec and nat\_rect are similar, except that they pertain to (P:nat->Set) and (P:nat->Type) respectively. They correspond to primitive induction principles (allowing dependent types) respectively over sorts Set and Type.

```
Variant: Inductive ident : sort ? := | ident binders ? : type ?
```

Constructors *idents* can come with *binders* in which case, the actual type of the constructor is forall *binders*, type.

In the case where inductive types have no annotations (next section gives an example of such annotations), a constructor can be defined by only giving the type of its arguments.

### Example

```
Inductive nat : Set := 0 \mid S (::nat).
```

## Simple annotated inductive types

In an annotated inductive types, the universe where the inductive type is defined is no longer a simple sort, but what is called an arity, which is a type whose conclusion is a sort.

## Example

As an example of annotated inductive types, let us define the even predicate:

```
Inductive even : nat -> Prop :=
| even_0 : even 0
| even_SS : forall n:nat, even n -> even (S (S n)).
    even is defined
    even_ind is defined
    even_sind is defined
```

The type nat->Prop means that even is a unary predicate (inductively defined) over natural numbers. The type of its two constructors are the defining clauses of the predicate even. The type of even\_ind is:

From a mathematical point of view it asserts that the natural numbers satisfying the predicate even are exactly in the smallest set of naturals satisfying the clauses even\_0 or even\_SS. This is why, when we want to prove any predicate P over elements of even, it is enough to prove it for 0 and to prove that if any natural number n satisfies P its double successor (S (S n)) satisfies also P. This is indeed analogous to the structural induction principle we got for nat.

### Parameterized inductive types

```
Variant: Inductive ident binders : type := | ? ident : type | ident : type
```

In the previous example, each constructor introduces a different instance of the predicate even. In some cases, all the constructors introduce the same generic instance of the inductive definition, in which case, instead of an annotation, we use a context of parameters which are *binders* shared by all the constructors of the definition.

Parameters differ from inductive type annotations in the fact that the conclusion of each type of constructor invoke the inductive type with the same values of parameters as its specification.

# Example

A typical example is the definition of polymorphic lists:

```
Inductive list (A:Set) : Set :=
| nil : list A
| cons : A -> list A -> list A.
```

In the type of nil and cons, we write (list A) and not just list. The constructors nil and cons will have respectively types:

```
Check nil.
    nil
        : forall A : Set, list A
Check cons.
    cons
        : forall A : Set, A -> list A -> list A
```

Types of destructors are also quantified with (A:Set).

Once again, it is possible to specify only the type of the arguments of the constructors, and to omit the type of the conclusion:

```
Inductive list (A:Set) : Set := nil | cons (_:A) (_:list A).
```

### Note:

• It is possible in the type of a constructor, to invoke recursively the inductive definition on an argument which is not the parameter itself.

One can define:

```
Inductive list2 (A:Set) : Set :=
| nil2 : list2 A
| cons2 : A -> list2 (A*A) -> list2 A.
    list2 is defined
    list2_rect is defined
    list2_ind is defined
    list2_rec is defined
    list2_rec is defined
    list2_sind is defined
```

that can also be written by specifying only the type of the arguments:

```
Inductive list2 (A:Set) : Set := nil2 | cons2 (_:A) (_:list2 (A*A)).
    list2 is defined
    list2_rect is defined
    list2_rec is defined
    list2_rec is defined
    list2_sind is defined

But the following definition will give an error:

Fail Inductive listw (A:Set) : Set :=
    | nilw : listw (A*A)
    | consw : A -> listw (A*A) -> listw (A*A).
    The command has indeed failed with message:
    Last occurrence of "listw" must have "A" as 1st argument in
```

because the conclusion of the type of constructors should be listw A in both cases.

• A parameterized inductive definition can be defined using annotations instead of parameters but it will sometimes give a different (bigger) sort for the inductive definition and will produce a less convenient rule for case elimination.

## Flag: Uniform Inductive Parameters

"listw (A \* A)%type".

When this flag is set (it is off by default), inductive definitions are abstracted over their parameters before type checking constructors, allowing to write:

```
Set Uniform Inductive Parameters.
Inductive list3 (A:Set) : Set :=
| nil3 : list3
| cons3 : A -> list3 -> list3.
    list3 is defined
    list3_rect is defined
    list3_ind is defined
    list3_rec is defined
    list3_rec is defined
```

This behavior is essentially equivalent to starting a new section and using *Context* to give the uniform parameters, like so (cf. *Section mechanism*):

```
Section list3.
Context (A:Set).
   A is declared

Inductive list3 : Set :=
| nil3 : list3
| cons3 : A -> list3 -> list3.
   list3 is defined
   list3_rect is defined
   list3_rec is defined
   list3_rec is defined
   list3_rec is defined
   list3_sind is defined

List3_sind is defined
List3_sind is defined
List3_sind is defined
List3_sind is defined
List3_sind is defined
List3_sind is defined
List3_sind is defined
List3_sind is defined
List3_sind is defined
End list3.
```

## See also:

Section Inductive Definitions and the induction tactic.


### **Variants**

Command: Variant ident binders : type | := | ident : type | ident : type |

The *Variant* command is identical to the *Inductive* command, except that it disallows recursive definition of types (for instance, lists cannot be defined using *Variant*). No induction scheme is generated for this variant, unless the *Nonrecursive Elimination Schemes* flag is on.

Error: The num th argument of ident must be ident in type.

# Mutually defined inductive types



This variant allows defining a block of mutually inductive types. It has the same semantics as the above *Inductive* definition for each *ident*. All *ident* are simultaneously added to the environment. Then well-typing of constructors can be checked. Each one of the *ident* can be used on its own.



In this variant, the inductive definitions are parameterized with *binders*. However, parameters correspond to a local context in which the whole set of inductive declarations is done. For this reason, the parameters must be strictly the same for each inductive types.

## Example

The typical example of a mutual inductive data type is the one for trees and forests. We assume given two types A and B as variables. It can be declared the following way.

```
Parameters A B : Set.
Inductive tree : Set := node : A -> forest -> tree
with forest : Set :=
| leaf : B -> forest
| cons : tree -> forest -> forest.
```

This declaration generates automatically six induction principles. They are respectively called tree\_rec, tree\_ind, tree\_rect, forest\_rec, forest\_ind, forest\_rect. These ones are not the most general ones but are just the induction principles corresponding to each inductive part seen as a single inductive definition.

To illustrate this point on our example, we give the types of tree\_rec and forest\_rec.

Assume we want to parameterize our mutual inductive definitions with the two type variables A and B, the declaration should be done the following way:

```
Inductive tree (A B:Set) : Set := node : A -> forest A B -> tree A B
with forest (A B:Set) : Set :=
| leaf : B -> forest A B
| cons : tree A B -> forest A B -> forest A B.
```

Assume we define an inductive definition inside a section (cf. Section mechanism). When the section is closed, the variables declared in the section and occurring free in the declaration are added as parameters to the inductive definition.

### See also:

A generic command Scheme is useful to build automatically various mutual induction principles.

## Co-inductive types

The objects of an inductive type are well-founded with respect to the constructors of the type. In other words, such objects contain only a *finite* number of constructors. Co-inductive types arise from relaxing this condition, and admitting types whose objects contain an infinity of constructors. Infinite objects are introduced by a non-ending (but effective) process of construction, defined in terms of the constructors of the type.

```
Command: CoInductive ident binders : type := | ident : type | ident : type |
```

This command introduces a co-inductive type. The syntax of the command is the same as the command *Inductive*. No principle of induction is derived from the definition of a co-inductive type, since such principles only make sense for inductive types. For co-inductive types, the only elimination principle is case analysis.

### Example

An example of a co-inductive type is the type of infinite sequences of natural numbers, usually called streams.

```
CoInductive Stream : Set := Seq : nat -> Stream -> Stream.
```

The usual destructors on streams hd:Stream->nat and tl:Str->Str can be defined as follows:

```
Definition hd (x:Stream) := let (a,s) := x in a. Definition tl (x:Stream) := let (a,s) := x in s.
```

Definition of co-inductive predicates and blocks of mutually co-inductive definitions are also allowed.

## Example

An example of a co-inductive predicate is the extensional equality on streams:

In order to prove the extensional equality of two streams s1 and s2 we have to construct an infinite proof of equality, that is, an infinite object of type (EqSt s1 s2). We will see how to introduce infinite objects in Section Definitions of recursive objects in co-inductive types.

#### Caveat

The ability to define co-inductive types by constructors, hereafter called *positive co-inductive types*, is known to break subject reduction. The story is a bit long: this is due to dependent pattern-matching which implies propositional  $\eta$ -equality, which itself would require full  $\eta$ -conversion for subject reduction to hold, but full  $\eta$ -conversion is not acceptable as it would make type-checking undecidable.

Since the introduction of primitive records in Coq 8.5, an alternative presentation is available, called *negative* co-inductive types. This consists in defining a co-inductive type as a primitive record type through its projections. Such a technique is akin to the co-pattern style that can be found in e.g. Agda, and preserves subject reduction.

The above example can be rewritten in the following way.

```
Set Primitive Projections.
CoInductive Stream : Set := Seq { hd : nat; tl : Stream }.
    Stream is defined
    hd is defined
    tl is defined

CoInductive EqSt (s1 s2: Stream) : Prop := eqst {
    eqst_hd : hd s1 = hd s2;
    eqst_tl : EqSt (tl s1) (tl s2);
}.
    EqSt is defined
    eqst_hd is defined
    eqst_tl is defined
```

Some properties that hold over positive streams are lost when going to the negative presentation, typically when they imply equality over streams. For instance, propositional  $\eta$ -equality is lost when going to the negative presentation. It is nonetheless logically consistent to recover it through an axiom.

```
Axiom Stream_eta : forall s: Stream, s = Seq (hd s) (tl s). Stream_eta is declared
```

More generally, as in the case of positive coinductive types, it is consistent to further identify extensional equality of coinductive types with propositional equality:

```
Axiom Stream_ext : forall (s1 s2: Stream), EqSt s1 s2 \rightarrow s1 = s2. Stream_ext is declared
```

As of Coq 8.9, it is now advised to use negative co-inductive types rather than their positive counterparts.

## See also:

Primitive Projections for more information about negative records and primitive projections.

## Definition of recursive functions

## Definition of functions by recursion over inductive objects

This section describes the primitive form of definition by recursion over inductive objects. See the *Function* command for more advanced constructions.

```
Command: Fixpoint ident binders {struct ident} : type := term
```

This command allows defining functions by pattern matching over inductive objects using a fixed point construction. The meaning of this declaration is to define *ident* a recursive function with arguments specified by the *binders* such that *ident* applied to arguments corresponding to these *binders* has type type, and is equivalent to the expression term. The type of *ident* is consequently forall binders, type and its value is equivalent to fun binders => term.

To be accepted, a *Fixpoint* definition has to satisfy some syntactical constraints on a special argument called the decreasing argument. They are needed to ensure that the *Fixpoint* definition always terminates. The point of the {struct *ident*} annotation is to let the user tell the system which argument decreases along the recursive calls.

The {struct ident} annotation may be left implicit, in this case the system tries successively arguments from left to right until it finds one that satisfies the decreasing condition.

### Note:

- Some fixpoints may have several arguments that fit as decreasing arguments, and this choice influences the reduction of the fixpoint. Hence an explicit annotation must be used if the leftmost decreasing argument is not the desired one. Writing explicit annotations can also speed up type checking of large mutual fixpoints.
- In order to keep the strong normalization property, the fixed point reduction will only be performed when the argument in position of the decreasing argument (which type should be in an inductive definition) starts with a constructor.

## Example

One can define the addition function as :

```
Fixpoint add (n m:nat) {struct n} : nat :=
match n with
| 0 => m
| S p => S (add p m)
end.
    add is defined
    add is recursively defined (decreasing on 1st argument)
```

The match operator matches a value (here n) with the various constructors of its (inductive) type. The remaining arguments give the respective values to be returned, as functions of the parameters of the corresponding constructor. Thus here when n equals 0 we return m, and when n equals p we return p (S (add p p).

The match operator is formally described in Section *The match ... with ... end construction*. The system recognizes that in the inductive call (add p m) the first argument actually decreases because it is a *pattern variable* coming from match n with.

# Example

The following definition is not correct and generates an error message:

```
Fail Fixpoint wrongplus (n m:nat) {struct n} : nat :=
match m with
\mid 0 => n
| S p => S (wrongplus n p)
end.
    The command has indeed failed with message:
    Recursive definition of wrongplus is ill-formed.
    In environment
    wrongplus : nat -> nat -> nat
    n : nat
    m : nat
    p: nat
    Recursive call to wrongplus has principal argument equal to
    "n" instead of a subterm of "n".
    Recursive definition is:
    "fun n m : nat => match m with
                       \mid 0 \Rightarrow n
                       | S p => S (wrongplus n p)
                       end".
```

because the declared decreasing argument n does not actually decrease in the recursive call. The function computing the addition over the second argument should rather be written:

```
Fixpoint plus (n m:nat) {struct m} : nat :=
match m with
| 0 => n
| S p => S (plus n p)
end.
    plus is defined
    plus is recursively defined (decreasing on 2nd argument)
```

### Example

The recursive call may not only be on direct subterms of the recursive variable  ${\tt n}$  but also on a deeper subterm and we can directly write the function  ${\tt mod2}$  which gives the remainder modulo 2 of a natural number.

```
Variant: Fixpoint ident binders {struct ident} ? : type ? := term with ident binders : type ?
```

This variant allows defining simultaneously several mutual fixpoints. It is especially useful when defining functions over mutually defined inductive types.

Example

The size of trees and forests can be defined the following way:

```
Fixpoint tree_size (t:tree) : nat :=
match t with
| node a f => S (forest_size f)
end
with forest_size (f:forest) : nat :=
match f with
| leaf b => 1
| cons t f' => (tree_size t + forest_size f')
end.
    tree_size is defined
    forest_size is defined
    tree_size, forest_size are recursively defined
    (decreasing respectively on 1st, 1st arguments)
```

### Definitions of recursive objects in co-inductive types

```
Command: CoFixpoint ident binders : type := term
```

This command introduces a method for constructing an infinite object of a coinductive type. For example, the stream containing all natural numbers can be introduced applying the following method to the number 0 (see Section *Co-inductive types* for the definition of Stream, hd and t1):

```
CoFixpoint from (n:nat): Stream := Seq n (from (S n)). from is defined from is corecursively defined
```

Oppositely to recursive ones, there is no decreasing argument in a co-recursive definition. To be admissible, a method of construction must provide at least one extra constructor of the infinite object for each iteration. A syntactical guard condition is imposed on co-recursive definitions in order to ensure this: each recursive call in the definition must be protected by at least one constructor, and only by constructors. That is the case in the former definition, where the single recursive call of from is guarded by an application of Seq. On the contrary, the following recursive function does not satisfy the guard condition:

```
Fail CoFixpoint filter (p:nat -> bool) (s:Stream) : Stream :=
  if p (hd s) then Seq (hd s) (filter p (tl s)) else filter p (tl s).
  The command has indeed failed with message:
  Recursive definition of filter is ill-formed.
  In environment
  filter : (nat -> bool) -> Stream -> Stream
  p : nat -> bool
  s : Stream
  Unguarded recursive call in "filter p (tl s)".
  Recursive definition is:
  "fun (p : nat -> bool) (s : Stream) =>
   if p (hd s)
   then {| hd := hd s; tl := filter p (tl s) |}
  else filter p (tl s)".
```

The elimination of co-recursive definition is done lazily, i.e. the definition is expanded only when it occurs at the head of an application which is the argument of a case analysis expression. In any other context, it is considered as a canonical expression which is completely evaluated. We can test this using the command *Eval*, which computes the normal forms of a term:

# Assertions and proofs

An assertion states a proposition (or a type) of which the proof (or an inhabitant of the type) is interactively built using tactics. The interactive proof mode is described in Chapter *Proof handling* and the tactics in Chapter *Tactics*. The basic assertion command is:

```
Command: Theorem ident binders: type
```

After the statement is asserted, Coq needs a proof. Once a proof of *type* under the assumptions represented by *binders* is given and validated, the proof is generalized into a proof of **forall** *binders*, *type* and the theorem is bound to the name *ident* in the environment.

Error: The term term has type type which should be Set, Prop or Type.

Error: ident already exists.

The name you provided is already defined. You have then to choose another name.

Error: Nested proofs are not allowed unless you turn the Nested Proofs Allowed flag on. You are asserting a new statement while already being in proof editing mode. This feature, called nested proofs, is disabled by default. To activate it, turn the Nested Proofs Allowed flag on.

```
Variant: Lemma ident binders?: type

Variant: Remark ident binders?: type

Variant: Fact ident binders?: type

Variant: Corollary ident binders?: type

Variant: Proposition ident binders?: type

These commands are all synonyms of Theorem ident binders?: type.

Variant: Theorem ident binders?: type with ident binders?: type
```

This command is useful for theorems that are proved by simultaneous induction over a mutually inductive assumption, or that assert mutually dependent statements in some mutual co-inductive type. It is equivalent to *Fixpoint* or *CoFixpoint* but using tactics to build the proof of the statements (or the body of the specification, depending on the point of view). The inductive or co-inductive types on which the induction or coinduction has to be done is assumed to be non ambiguous and is guessed by the system.

Like in a Fixpoint or CoFixpoint definition, the induction hypotheses have to be used on structurally

smaller arguments (for a Fixpoint) or be quarded by a constructor (for a CoFixpoint). The verification that recursive proof arguments are correct is done only at the time of registering the lemma in the environment. To know if the use of induction hypotheses is correct at some time of the interactive development of a proof, use the command Guarded.

The command can be used also with Lemma, Remark, etc. instead of Theorem.

# Variant: Definition ident binders : type

This allows defining a term of type type using the proof editing mode. It behaves as Theorem but is intended to be used in conjunction with *Defined* in order to define a constant of which the computational behavior is relevant.

The command can be used also with *Example* instead of *Definition*.

#### See also:

Opaque, Transparent, unfold.

```
Variant: Let ident binders : type
```

Like Definition ident binders: type except that the definition is turned into a let-in definition generalized over the declarations depending on it after closing the current section.

```
Variant: Fixpoint ident binders : type with ident binders : type
```

This generalizes the syntax of Fixpoint so that one or more bodies can be defined interactively using the proof editing mode (when a body is omitted, its type is mandatory in the syntax). When the block of proofs is completed, it is intended to be ended by *Defined*.

```
Variant: CoFixpoint ident binders : type with ident binders : type

This generalizes the syntax of CoFixpoint so that one or more badies and in the company type.
```

This generalizes the syntax of CoFixpoint so that one or more bodies can be defined interactively using the proof editing mode.

A proof starts by the keyword *Proof*. Then Coq enters the proof editing mode until the proof is completed. The proof editing mode essentially contains tactics that are described in chapter *Tactics*. Besides tactics, there are commands to manage the proof editing mode. They are described in Chapter *Proof handling*.

When the proof is completed it should be validated and put in the environment using the keyword Qed.

#### Note:

- 1. Several statements can be simultaneously asserted provided the Nested Proofs Allowed flag was turned on.
- 2. Not only other assertions but any vernacular command can be given while in the process of proving a given assertion. In this case, the command is understood as if it would have been given before the statements still to be proved. Nonetheless, this practice is discouraged and may stop working in future versions.
- 3. Proofs ended by Qed are declared opaque. Their content cannot be unfolded (see Performing computations), thus realizing some form of proof-irrelevance. To be able to unfold a proof, the proof should be ended by *Defined*.
- 4. Proof is recommended but can currently be omitted. On the opposite side, Qed (or Defined) is mandatory to validate a proof.
- 5. One can also use Admitted in place of Qed to turn the current asserted statement into an axiom and exit the proof editing mode.

#### **Attributes**

Any vernacular command can be decorated with a list of attributes, enclosed between #[ (hash and opening square bracket) and ] (closing square bracket) and separated by commas, Multiple space-separated blocks may be provided.

Each attribute has a name (an identifier) and may have a value. A value is either a *string* (in which case it is specified with an equal = sign), or a list of attributes, enclosed within brackets.

Some attributes are specific to a command, and so are described with that command. Currently, the following attributes are recognized by a variety of commands:

universes(monomorphic), universes(polymorphic) Equivalent to the Monomorphic and Polymorphic flags (see *Polymorphic Universes*).

program Takes no value, equivalent to the Program flag (see Program).

global, local Take no value, equivalent to the Global and Local flags (see Controlling the locality of commands).

deprecated Takes as value the optional attributes since and note; both have a string value.

This attribute is supported by the following commands: Ltac, Tactic Notation, Notation, Infix.

It can trigger the following warnings:

Warning: Tactic qualid is deprecated since string. string.

Warning: Tactic Notation qualid is deprecated since string. string.

Warning: Notation  $string_1$  is deprecated since  $string_2$ .  $string_3$ .  $string_3$  is the actual notation,  $string_2$  is the version number,  $string_3$  is the note.

### Example

```
From Coq Require Program.
    [Loading ML file extraction_plugin.cmxs ... done]
#[program] Definition one : nat := S _.
   one has type-checked, generating 1 obligation
   Solving obligations automatically...
   1 obligation remaining
   Obligation 1 of one: nat.
Next Obligation.
   1 subgoal
      _____
     nat.
exact 0.
   No more subgoals.
#[deprecated(since="8.9.0", note="Use idtac instead.")]
Ltac foo := idtac.
   foo is defined
Goal True.
   1 subgoal
```

(continues on next page)

(continued from previous page)

```
True

Proof.

now foo.

Toplevel input, characters 4-7:

> now foo.

> ^^^

Warning: Tactic foo is deprecated since 8.9.0. Use idtac instead.

[deprecated-tactic,deprecated]

No more subgoals.

Abort.
```

### Warning: Unsupported attribute

This warning is an error by default. It is caused by using a command with some attribute it does not understand.

## 4.2 Extensions of Gallina

Gallina is the kernel language of Coq. We describe here extensions of Gallina's syntax.

## 4.2.1 Record types

The *Record* construction is a macro allowing the definition of records as is done in many programming languages. Its syntax is described in the grammar below. In fact, the *Record* macro is more general than the usual record types, since it allows also for "manifest" expressions. In this sense, the *Record* construction allows defining "signatures".

The first identifier *ident* is the name of the defined record and *sort* is its type. The optional identifier following := is the name of its constructor. If it is omitted, the default name Build\_*ident*, where *ident* is the record name, is used. If *sort* is omitted, the default sort is Type. The identifiers inside the brackets are the names of fields. For a given field *ident*, its type is *forall binders*, *type*. Remark that the type of a particular identifier may depend on a previously-given identifier. Thus the order of the fields is important. Finally, *binders* are parameters of the record.

More generally, a record may have explicitly defined (a.k.a. manifest) fields. For instance, we might have: Record  $ident\ binders$ : sort:= {  $ident_1$ :  $type_1$ ;  $ident_2$ :=  $term_2$ ;  $ident_3$ :  $type_3$ }. in which case the correctness of  $type_3$  may rely on the instance  $term_2$  of  $ident_2$  and  $term_2$  may in turn depend on  $ident_1$ .

### Example

The set of rational numbers may be defined as:

```
Record Rat : Set := mkRat
{ sign : bool
; top : nat
; bottom : nat
; Rat_bottom_cond : 0 <> bottom
; Rat_irred_cond :
    forall x y z:nat, (x * y) = top /\ (x * z) = bottom -> x = 1
}.
    Rat is defined
    sign is defined
    top is defined
    bottom is defined
    Rat_bottom_cond is defined
    Rat_irred_cond is defined
```

Note here that the fields Rat\_bottom\_cond depends on the field bottom and Rat\_irred\_cond depends on both top and bottom.

Let us now see the work done by the Record macro. First the macro generates a variant type definition with just one constructor: Variant ident binders: : sort := ident\_0 binders.

To build an object of type ident, one should provide the constructor  $ident_0$  with the appropriate number of terms filling the fields of the record.

#### Example

Let us define the rational 1/2:

```
Theorem one_two_irred : forall x y z:nat, x * y = 1 /\ x * z = 2 -> x = 1. Admitted. Definition half := mkRat true 1 2 (0_S 1) one_two_irred. Check half.
```

Alternatively, the following syntax allows creating objects by using named fields, as shown in this grammar. The fields do not have to be in any particular order, nor do they have to be all present if the missing ones can be inferred or prompted for (see *Program*).

```
Definition half' :=
    {| sign := true;
      Rat_bottom_cond := 0_S 1;
      Rat_irred_cond := one_two_irred |}.
    half' is defined
```

The following settings let you control the display format for types:

### Flag: Printing Records

If set, use the record syntax (shown above) as the default display format.

You can override the display format for specified types by adding entries to these tables:

#### Table: Printing Record qualid

Specifies a set of qualids which are displayed as records. Use the Add Otable and Remove Otable commands to update the set of qualids.

### Table: Printing Constructor qualid

Specifies a set of qualids which are displayed as constructors. Use the Add @table and Remove @table commands to update the set of qualids.

This syntax can also be used for pattern matching.

```
Eval compute in (
  match half with
  | {| sign := true; top := n |} => n
  | _ => 0
  end).
  = 1
     : nat
```

The macro generates also, when it is possible, the projection functions for destructuring an object of type *ident*. These projection functions are given the names of the corresponding fields. If a field is named \_ then no projection is built for it. In our example:

An alternative syntax for projections based on a dot notation is available:

```
Eval compute in half.(top).
= 1
: nat
```

### Flag: Printing Projections

This flag activates the dot notation for printing.

#### Example

```
Set Printing Projections.
Check top half.
  half.(top)
     : nat
```

```
projection ::= term `.` ( qualid ) term `.` ( qualid arg ... arg ) term `.` ( Qqualid term ... term )
```

#### Syntax of Record projections

The corresponding grammar rules are given in the preceding grammar. When qualid denotes a projection, the syntax term. (qualid) is equivalent to qualid term, the syntax term. (qualid arg + term. and the syntax term. (Qqualid term + term. In each case, term is the object projected and the other arguments are the parameters of the inductive type.

**Note:** Records defined with the Record keyword are not allowed to be recursive (references to the record's name in the type of its field raises an error). To define recursive records, one can use the Inductive and CoInductive keywords, resulting in an inductive or co-inductive record. Definition of mutually inductive or co-inductive records are also allowed, as long as all of the types in the block are records.

**Note:** Induction schemes are automatically generated for inductive records. Automatic generation of induction schemes for non-recursive records defined with the Record keyword can be activated with the *Nonrecursive Elimination Schemes* flag (see *Generation of induction principles with Scheme*).

**Note:** Structure is a synonym of the keyword Record.

#### Warning: ident cannot be defined.

It can happen that the definition of a projection is impossible. This message is followed by an explanation of this impossibility. There may be three reasons:

- 1. The name *ident* already exists in the environment (see *Axiom*).
- 2. The body of ident uses an incorrect elimination for ident (see Fixpoint and Destructors).
- 3. The type of the projections *ident* depends on previous projections which themselves could not be defined.

### Error: Records declared with the keyword Record or Structure cannot be recursive.

The record name *ident* appears in the type of its fields, but uses the keyword Record. Use the keyword Inductive or CoInductive instead.

### Error: Cannot handle mutually (co)inductive records.

Records cannot be defined as part of mutually inductive (or co-inductive) definitions, whether with records only or mixed with standard definitions.

During the definition of the one-constructor inductive definition, all the errors of inductive definitions, as described in Section *Inductive definitions*, may also occur.

#### See also:

Coercions and records in section Classes as Records of the chapter devoted to coercions.

#### **Primitive Projections**

#### Flag: Primitive Projections

Turns on the use of primitive projections when defining subsequent records (even through the Inductive and CoInductive commands). Primitive projections extended the Calculus of Inductive Constructions with a new binary term constructor  $\mathbf{r}$ . (p) representing a primitive projection  $\mathbf{p}$  applied to a record object  $\mathbf{r}$  (i.e., primitive projections are always applied). Even if the record type has parameters, these do not appear in the internal representation of applications of the projection, considerably reducing the sizes of terms when manipulating parameterized records and type checking time. On the

user level, primitive projections can be used as a replacement for the usual defined ones, although there are a few notable differences.

### Flag: Printing Primitive Projection Parameters

This compatibility flag reconstructs internally omitted parameters at printing time (even though they are absent in the actual AST manipulated by the kernel).

### **Primitive Record Types**

When the *Primitive Projections* flag is on, definitions of record types change meaning. When a type is declared with primitive projections, its match construct is disabled (see *Primitive Projections* though). To eliminate the (co-)inductive type, one must use its defined primitive projections.

For compatibility, the parameters still appear to the user when printing terms even though they are absent in the actual AST manipulated by the kernel. This can be changed by unsetting the *Printing Primitive Projection Parameters* flag.

There are currently two ways to introduce primitive records types:

- 1. Through the Record command, in which case the type has to be non-recursive. The defined type enjoys eta-conversion definitionally, that is the generalized form of surjective pairing for records:  $r = Build_R(r.(p_1) \dots r.(p_n))$ . Eta-conversion allows to define dependent elimination for these types as well.
- 2. Through the Inductive and CoInductive commands, when the body of the definition is a record declaration of the form Build\_R {  $p_1 : t_1; ...; p_n : t_n$  }. In this case the types can be recursive and eta-conversion is disallowed. These kind of record types differ from their traditional versions in the sense that dependent elimination is not available for them and only non-dependent case analysis can be defined.

#### Reduction

The basic reduction rule of a primitive projection is  $p_i$  (Build\_R  $t_1 \dots t_n$ )  $\to_{\iota} t_i$ . However, to take the  $\delta$  flag into account, projections can be in two states: folded or unfolded. An unfolded primitive projection application obeys the rule above, while the folded version delta-reduces to the unfolded version. This allows to precisely mimic the usual unfolding rules of constants. Projections obey the usual simpl flags of the Arguments command in particular. There is currently no way to input unfolded primitive projections at the user-level, and there is no way to display unfolded projections differently from folded ones.

#### Compatibility Projections and match

To ease compatibility with ordinary record types, each primitive projection is also defined as a ordinary constant taking parameters and an object of the record type as arguments, and whose body is an application of the unfolded primitive projection of the same name. These constants are used when elaborating partial applications of the projection. One can distinguish them from applications of the primitive projection if the *Printing Primitive Projection Parameters* flag is off: For a primitive projection application, parameters are printed as underscores while for the compatibility projections they are printed as usual.

Additionally, user-written match constructs on primitive records are desugared into substitution of the projections, they cannot be printed back as match constructs.

### 4.2.2 Variants and extensions of match

### Multiple and nested pattern matching

The basic version of match allows pattern matching on simple patterns. As an extension, multiple nested patterns or disjunction of patterns are allowed, as in ML-like languages.

The extension just acts as a macro that is expanded during parsing into a sequence of match on simple patterns. Especially, a construction defined using the extended match is generally printed under its expanded form (see *Printing Matching*).

#### See also:

Extended pattern matching.

#### Pattern-matching on boolean values: the if expression

For inductive types with exactly two constructors and for pattern matching expressions that do not depend on the arguments of the constructors, it is possible to use a if ... then ... else notation. For instance, the definition

```
Definition not (b:bool) :=
match b with
| true => false
| false => true
end.
    not is defined

can be alternatively written

Definition not (b:bool) := if b then false else true.
    not is defined

More generally, for an inductive type with constructors C<sub>1</sub> and C<sub>2</sub>, we have the following equivalence
if term [dep_ret_type] then term<sub>1</sub> else term<sub>2</sub>
match term [dep_ret_type] with
| C<sub>1</sub> _ ... _ => term<sub>1</sub>
| C<sub>2</sub> _ ... _ => term<sub>2</sub>
end
```

### Example

Notice that the printing uses the if syntax because sumbool is declared as such (see Controlling pretty-printing of match expressions).

#### Irrefutable patterns: the destructuring let variants

Pattern-matching on terms inhabiting inductive type having only one constructor can be alternatively written using let ... in ... constructions. There are two variants of them.

### First destructuring let syntax

The expression let (ident<sub>1</sub>, ..., ident<sub>n</sub>) :=  $term_0$ in  $term_1$  performs case analysis on  $term_0$  which must be in an inductive type with one constructor having itself n arguments. Variables  $ident_1$  ...  $ident_n$  are bound to the n arguments of the constructor in expression  $term_1$ . For instance, the definition

```
Definition fst (A B:Set) (H:A * B) := match H with
| pair x y => x
end.
    fst is defined

can be alternatively written

Definition fst (A B:Set) (p:A * B) := let (x, _) := p in x.
    fst is defined
```

Notice that reduction is different from regular let ... in ... construction since it happens only if term<sub>0</sub> is in constructor form. Otherwise, the reduction is blocked.

The pretty-printing of a definition by matching on a irrefutable pattern can either be done using match or the let construction (see Section Controlling pretty-printing of match expressions).

If term inhabits an inductive type with one constructor C, we have an equivalence between

```
let (ident<sub>1</sub>, ..., ident) [dep_ret_type] := term in term'
and
match term [dep_ret_type] with
C ident<sub>1</sub> ... ident => term'
```

### Second destructuring let syntax

Another destructuring let syntax is available for inductive types with one constructor by giving an arbitrary pattern instead of just a tuple for all the arguments. For example, the preceding example can be written:

```
Definition fst (A B:Set) (p:A*B) := let 'pair x _ := p in x. fst is defined
```

This is useful to match deeper inside tuples and also to use notations for the pattern, as the syntax let 'p := t in b allows arbitrary patterns to do the deconstruction. For example:

```
Definition deep_tuple (A:Set) (x:(A*A)*(A*A)) : A*A*A*A :=
let '((a,b), (c, d)) := x in (a,b,c,d).
    deep_tuple is defined

Notation " x 'With' p " := (exist _ x p) (at level 20).
    Identifier 'With' now a keyword
```

(continues on next page)

(continued from previous page)

```
Definition proj1_sig' (A:Set) (P:A->Prop) (t:{ x:A | P x }) : A :=
let 'x With p := t in x.
    proj1_sig' is defined
```

When printing definitions which are written using this construct it takes precedence over let printing directives for the datatype under consideration (see Section Controlling pretty-printing of match expressions).

### Controlling pretty-printing of match expressions

The following commands give some control over the pretty-printing of match expressions.

#### Printing nested patterns

#### Flag: Printing Matching

The Calculus of Inductive Constructions knows pattern matching only over simple patterns. It is however convenient to re-factorize nested pattern matching into a single pattern matching over a nested pattern.

When this flag is on (default), Coq's printer tries to do such limited re-factorization. Turning it off tells Coq to print only simple pattern matching problems in the same way as the Coq kernel handles them.

#### Factorization of clauses with same right-hand side

### Flag: Printing Factorizable Match Patterns

When several patterns share the same right-hand side, it is additionally possible to share the clauses using disjunctive patterns. Assuming that the printing matching mode is on, this flag (on by default) tells Coq's printer to try to do this kind of factorization.

#### Use of a default clause

### Flag: Printing Allow Match Default Clause

When several patterns share the same right-hand side which do not depend on the arguments of the patterns, yet an extra factorization is possible: the disjunction of patterns can be replaced with a \_ default clause. Assuming that the printing matching mode and the factorization mode are on, this flag (on by default) tells Coq's printer to use a default clause when relevant.

#### Printing of wildcard patterns

#### Flag: Printing Wildcard

Some variables in a pattern may not occur in the right-hand side of the pattern matching clause. When this flag is on (default), the variables having no occurrences in the right-hand side of the pattern matching clause are just printed using the wildcard symbol "\_\_".

### Printing of the elimination predicate

### Flag: Printing Synth

In most of the cases, the type of the result of a matched term is mechanically synthesizable. Especially,

if the result type does not depend of the matched term. When this flag is on (default), the result type is not printed when Coq knows that it can re-synthesize it.

### Printing matching on irrefutable patterns

If an inductive type has just one constructor, pattern matching can be written using the first destructuring let syntax.

### Table: Printing Let qualid

Specifies a set of qualids for which pattern matching is displayed using a let expression. Note that this only applies to pattern matching instances entered with match. It doesn't affect pattern matching explicitly entered with a destructuring let. Use the Add Otable and Remove Otable commands to update this set.

#### Printing matching on booleans

If an inductive type is isomorphic to the boolean type, pattern matching can be written using if ... then ... else .... This table controls which types are written this way:

### Table: Printing If qualid

Specifies a set of qualids for which pattern matching is displayed using if ... then ... else .... Use the Add @table and Remove @table commands to update this set.

This example emphasizes what the printing settings offer.

### Example

```
Definition snd (A B:Set) (H:A * B) := match H with
| pair x y => y
end.
    snd is defined
Test Printing Let for prod.
    Cases on elements of prod are printed using a `let' form
Print snd.
    snd =
    fun (A B : Set) (H : A * B) \Rightarrow let (_, y) \Rightarrow H in y
         : forall A B : Set, A * B -> B
    Arguments snd (_ _)%type_scope
Remove Printing Let prod.
Unset Printing Synth.
Unset Printing Wildcard.
Print snd.
    snd =
    fun (A B : Set) (H : A * B) => match H return B with
                                    | (x, y) => y
                                    end
         : forall A B : Set, A * B -> B
    Arguments snd (_ _)%type_scope
```

### 4.2.3 Advanced recursive functions

The following experimental command is available when the FunInd library has been loaded via Require Import FunInd:

```
Command: Function ident binder { decrease_annot } : type := term
```

This command can be seen as a generalization of Fixpoint. It is actually a wrapper for several ways of defining a function and other useful related objects, namely: an induction principle that reflects the recursive structure of the function (see function induction) and its fixpoint equality. The meaning of this declaration is to define a function ident, similarly to Fixpoint. Like in Fixpoint, the decreasing argument must be given (unless the function is not recursive), but it might not necessarily be structurally decreasing. The point of the { decrease\_annot } annotation is to name the decreasing argument and to describe which kind of decreasing criteria must be used to ensure termination of recursive calls.

The Function construction also enjoys the with extension to define mutually recursive definitions. However, this feature does not work for non structurally recursive functions.

See the documentation of functional induction (function induction) and Functional Scheme (Generation of induction principles with Functional Scheme) for how to use the induction principle to easily reason about the function.

**Note:** To obtain the right principle, it is better to put rigid parameters of the function as first arguments. For example it is better to define plus like this:

```
Function plus (m n : nat) {struct n} : nat :=
match n with
| 0 => m
| S p \Rightarrow S (plus m p)
   plus is defined
    plus is recursively defined (decreasing on 2nd argument)
    plus_equation is defined
   plus_rect is defined
    plus_ind is defined
    plus_rec is defined
    R_plus_correct is defined
   R_plus_complete is defined
than like this:
Function plus (n m : nat) {struct n} : nat :=
match n with
| 0 => m
| S p => S (plus p m)
end.
   plus is defined
    plus is recursively defined (decreasing on 1st argument)
   plus equation is defined
   plus_rect is defined
    plus_ind is defined
```

(continues on next page)

(continued from previous page)

```
plus_rec is defined
R_plus_correct is defined
R_plus_complete is defined
```

#### Limitations

term must be built as a pure pattern matching tree (match ... with) with applications only at the end of each branch.

Function does not support partial application of the function being defined. Thus, the following example cannot be accepted due to the presence of partial application of wrong in the body of wrong:

For now, dependent cases are not treated for non structurally terminating functions.

Error: The recursive argument must be specified.

Error: No argument name ident.

Error: Cannot use mutual definition with well-founded recursion or measure.

### Warning: Cannot define graph for ident.

The generation of the graph relation  $(R\_ident)$  used to compute the induction scheme of ident raised a typing error. Only ident is defined; the induction scheme will not be generated. This error happens generally when:

- the definition uses pattern matching on dependent types, which Function cannot deal with yet.
- the definition is not a pattern matching tree as explained above.

### Warning: Cannot define principle(s) for ident.

The generation of the graph relation (R\_ident) succeeded but the induction principle could not be built. Only ident is defined. Please report.

### Warning: Cannot build functional inversion principle.

functional inversion will not be available for the function.

#### See also:

Generation of induction principles with Functional Scheme and function induction

Depending on the {...} annotation, different definition mechanisms are used by Function. A more precise description is given below.

```
Variant: Function ident binder : type := term
```

Defines the not recursive function *ident* as if declared with *Definition*. Moreover the following are defined:

- *ident\_*rect, *ident\_*rec and *ident\_*ind, which reflect the pattern matching structure of *term* (see *Inductive*);
- The inductive R\_ident corresponding to the graph of ident (silently);
- *ident\_*complete and *ident\_*correct which are inversion information linking the function and its graph.

Variant: Function ident binder { struct ident } : type := term

Defines the structural recursive function *ident* as if declared with *Fixpoint*. Moreover the following are defined:

- The same objects as above;
- The fixpoint equation of *ident*: *ident\_*equation.

```
Variant: Function ident binder { measure term ident } : type := term

Variant: Function ident binder { wf term ident } : type := term
```

Defines a recursive function by well-founded recursion. The module Recdef of the standard library must be loaded for this feature. The {} annotation is mandatory and must be one of the following:

- {measure term ident} with ident being the decreasing argument and term being a function from type of ident to nat for which value on the decreasing argument decreases (for the 1t order on nat) at each recursive call of term. Parameters of the function are bound in term;
- {wf term ident} with ident being the decreasing argument and term an ordering relation on the type of ident (i.e. of type  $T_{ident} \rightarrow T_{ident} \rightarrow Prop$ ) for which the decreasing argument decreases at each recursive call of term. The order must be well-founded. Parameters of the function are bound in term.

If the annotation is measure or fw, the user is left with some proof obligations that will be used to define the function. These proofs are: proofs that each recursive call is actually decreasing with respect to the given criteria, and (if the criteria is wf) a proof that the ordering relation is well-founded. Once proof obligations are discharged, the following objects are defined:

- The same objects as with the struct;
- The lemma  $\mathtt{ident}_{tcc}$  which collects all proof obligations in one property;
- ullet The lemmas  $\mathtt{ident}_{terminate}$  and  $\mathtt{ident}_F$  which is needed to be inlined during extraction of ident.

The way this recursive function is defined is the subject of several papers by Yves Bertot and Antonia Balaa on the one hand, and Gilles Barthe, Julien Forest, David Pichardie, and Vlad Rusu on the other hand. Remark: Proof obligations are presented as several subgoals belonging to a Lemma ident<sub>tcc</sub>.

#### 4.2.4 Section mechanism

Sections create local contexts which can be shared across multiple definitions.

#### Example

Sections are opened by the Section command, and closed by End.

Section s1.

Inside a section, local parameters can be introduced using *Variable*, *Hypothesis*, or *Context* (there are also plural variants for the first two).

```
Variables x y : nat.
x is declared
y is declared
```

The command *Let* introduces section-wide *Let-in definitions*. These definitions won't persist when the section is closed, and all persistent definitions which depend on y' will be prefixed with let y' := y in.

```
Let y' := y.
Definition x' := S x.
Definition x'' := x' + y'.
Print x'.
   x' = S x
         : nat
Print x''.
   x'' = x' + y'
        : nat
End s1.
Print x'.
   x' = fun x : nat => S x
         : nat -> nat
    Arguments x' _%nat_scope
Print x''.
    x'' = fun x y : nat => let y' := y in x' x + y'
         : nat -> nat -> nat
    Arguments x'' (_ _)%nat_scope
```

Notice the difference between the value of x' and x'' inside section s1 and outside.

#### Command: Section ident

This command is used to open a section named *ident*. Section names do not need to be unique.

#### Command: End ident

This command closes the section named *ident*. After closing of the section, the local declarations (variables and local definitions, see *Variable*) get *discharged*, meaning that they stop being visible and that all global objects defined in the section are generalized with respect to the variables and local definitions they each depended on in the section.


Error: This is not the last opened section.

**Note:** Most commands, like *Hint*, *Notation*, option management, ... which appear inside a section are canceled when the section is closed.

### Command: Variable ident : type

This command links *type* to the name *ident* in the context of the current section. When the current section is closed, name *ident* will be unknown and every object using this variable will be explicitly parameterized (the variable is *discharged*).

Error: ident already exists.



#### Command: Let ident := term

This command binds the value *term* to the name *ident* in the environment of the current section. The name *ident* is accessible only within the current section. When the section is closed, all persistent definitions and theorems within it and depending on *ident* will be prefixed by the let-in definition let *ident* := *term* in.

Error: ident already exists.

```
Variant: Let ident binders : type := term
```

```
Variant: Let Fixpoint ident fix_body with fix_body
```

```
Variant: Let CoFixpoint ident cofix_body with cofix_body
```

#### Command: Context binders

Declare variables in the context of the current section, like *Variable*, but also allowing implicit variables, *Implicit generalization*, and let-binders.

```
Context \{A : Type\} (a b : A).
Context `{EqDec A}.
Context (b' := b).
```

#### See also:

Section Binders. Section Sections and contexts in chapter Typeclasses.

### 4.2.5 Module system

The module system provides a way of packaging related elements together, as well as a means of massive abstraction.

```
module_bindings ::= module_binding ... module_binding
module_expression ::= qualid ... qualid
! qualid ... qualid
```

Syntax of modules

In the syntax of module application, the ! prefix indicates that any Inline directive in the type of the functor arguments will be ignored (see the Module Type command below).

#### Command: Module ident

This command is used to start an interactive module named *ident*.

```
Variant: Module ident module_binding *
```

Starts an interactive functor with parameters given by module bindings.

```
Variant: Module ident : module_type
```

Starts an interactive module specifying its module type.

```
Variant: Module ident module_binding : module_type
```

Starts an interactive functor with parameters given by the list of module\_bindings, and output module type module\_type.

```
Variant: Module <a href="module_type" | + type" | + type | - type
```

Starts an interactive module satisfying each module\_type.

Starts an interactive functor with parameters given by the list of module\_binding. The output module type is verified against each module type.

```
Variant: Module Import Export
```

Behaves like *Module*, but automatically imports or exports the module.

#### Reserved commands inside an interactive module

#### Command: Include module

Includes the content of module in the current interactive module. Here module can be a module expression or a module type expression. If module is a high-order module or module type expression then the system tries to instantiate module by the current interactive module.

```
Command: Include module
```

is a shortcut for the commands Include module for each module.

### Command: End ident

This command closes the interactive module *ident*. If the module type was given the content of the module is matched against it and an error is signaled if the matching fails. If the module is basic (is not a functor) its components (constants, inductive types, submodules etc.) are now available through the dot notation.

Error: No such label ident.

Error: Signature components for label ident do not match.

Error: This is not the last opened module.

#### Command: Module ident := module expression

This command defines the module identifier ident to be equal to module\_expression.

Variant: Module ident module\_binding := module\_expression Defines a functor with parameters given by the list of module\_binding and body  $module\_expression.$ Variant: Module ident module\_binding : module\_type := module\_expression Defines a functor with parameters given by the list of module\_binding (possibly none), and output module type module\_type, with body module\_expression. Variant: Module ident module\_binding \* <: module\_type := module\_expression Defines a functor with parameters given by module\_bindings (possibly none) with body module\_expression. The body is checked against each module\_type, Variant: Module ident module\_binding := module\_expression + is equivalent to an interactive module where each module\_expression is included. Command: Module Type ident This command is used to start an interactive module type *ident*. Variant: Module Type ident module\_binding Starts an interactive functor type with parameters given by module\_bindings. Reserved commands inside an interactive module type: Command: Include module Same as Include inside a module. Command: Include module This is a shortcut for the command Include module for each module. Command: assumption keyword Inline assums The instance of this assumption will be automatically expanded at functor application, except when this functor application is prefixed by a ! annotation. Command: End ident This command closes the interactive module type ident. Error: This is not the last opened module type. Command: Module Type ident := module\_type Defines a module type *ident* equal to *module\_type*. Variant: Module Type ident module\_binding := module\_type Defines a functor type ident specifying functors taking arguments module bindings and returning module\_type. Variant: Module Type ident module\_binding := module\_type is equivalent to an interactive module type were each module\_type is included. Command: Declare Module ident : module\_type Declares a module *ident* of type *module\_type*.

Variant: Declare Module ident module\_binding : module\_type

module type module\_type.

Declares a functor with parameters given by the list of module binding and output

### Example

Print M.x.

```
Let us define a simple module.
```

```
Module M.

Interactive Module M started

Definition T := nat.

T is defined

Definition x := 0.

x is defined

Definition y : bool.

1 subgoal

======bool

exact true.

No more subgoals.

Defined.
End M.

Module M is defined
```

Inside a module one can define constants, prove theorems and do any other things that can be done in the toplevel. Components of a closed module can be accessed using the dot notation:

Now we can create a new module from M, giving it a less precise specification: the y component is dropped as well as the body of x.

```
Module N : SIG with Definition T := nat := M.
    Module N is defined

Print N.T.
    N.T = nat
    : Set
```

(continues on next page)

(continued from previous page)

```
Print N.x.
    *** [ N.x : N.T ]
Fail Print N.y.
    The command has indeed failed with message:
    N.y not a defined object.
The definition of N using the module type expression SIG with Definition T := nat is equivalent to the
following one:
Module Type SIG'.
    Interactive Module Type SIG' started
{\tt Definition}\ {\tt T}\ :\ {\tt Set}\ :=\ {\tt nat}\,.
    T is defined
Parameter x : T.
    x is declared
End SIG'.
    Module Type SIG' is defined
Module N : SIG' := M.
    Module N is defined
If we just want to be sure that our implementation satisfies a given module type without restricting the
interface, we can use a transparent constraint
Module P <: SIG := M.
    Module P is defined
Print P.y.
    P.y = true
         : bool
Now let us create a functor, i.e. a parametric module
Module Two (X Y: SIG).
    Interactive Module Two started
Definition T := (X.T * Y.T)\%type.
    T is defined
Definition x := (X.x, Y.x).
    x is defined
End Two.
    Module Two is defined
and apply it to our modules and do some computations:
 \mbox{Module Q} \ := \ \mbox{Two M N} \, . 
    Module Q is defined
Eval compute in (fst Q.x + snd Q.x).
                                                                                        (continues on next page)
```

(continued from previous page)

```
= N.x: nat
```

In the end, let us define a module type with two sub-modules, sharing some of the fields and give one of its possible implementations:

```
Module Type SIG2.
   Interactive Module Type SIG2 started
Declare Module M1 : SIG.
   Module M1 is declared
Module M2 <: SIG.
   Interactive Module M2 started
Definition T := M1.T.
   T is defined
Parameter x : T.
   x is declared
End M2.
   Module M2 is defined
End SIG2.
   Module Type SIG2 is defined
Module Mod <: SIG2.
    Interactive Module Mod started
Module M1.
    Interactive Module M1 started
Definition T := nat.
   T is defined
Definition x := 1.
   x is defined
End M1.
   Module M1 is defined
Module M2 := M.
   Module M2 is defined
End Mod.
   Module Mod is defined
```

Notice that M is a correct body for the component M2 since its T component is equal nat and hence M1.T as specified.

#### Note:

- 1. Modules and module types can be nested components of each other.
- 2. One can have sections inside a module or a module type, but not a module or a module type inside a section.

3. Commands like *Hint* or *Notation* can also appear inside modules and module types. Note that in case of a module definition like:

```
Module N : SIG := M.

or:

Module N : SIG. ... End N.
```

hints and the like valid for N are not those defined in M (or the module body) but the ones defined in SIG.

#### Command: Import qualid

If *qualid* denotes a valid basic module (i.e. its module type is a signature), makes its components available by their short names.

#### Example

```
Module Mod.
    Interactive Module Mod started
Definition T:=nat.
   T is defined
Check T.
   Т
         : Set
End Mod.
   Module Mod is defined
Check Mod.T.
   Mod.T
         : Set
Fail Check T.
   The command has indeed failed with message:
   The reference T was not found in the current environment.
Import Mod.
Check T.
   Т
         : Set
```

Some features defined in modules are activated only when a module is imported. This is for instance the case of notations (see *Notations*).

Declarations made with the Local flag are never imported by the *Import* command. Such declarations are only accessible through their fully qualified name.

### Example

#### Module A.

Interactive Module A started

Module B.

(continues on next page)

(continued from previous page)

Interactive Module B started

```
Local Definition T := nat.

T is defined

End B.

Module B is defined

End A.

Module A is defined

Import A.

Fail Check B.T.

The command has indeed failed with message:

The reference B.T was not found in the current environment.
```

### Variant: Export qualid

When the module containing the command Export qualid is imported, qualid is imported as well.

Error: qualid is not a module.

Warning: Trying to mask the absolute name qualid!

#### Command: Print Module ident

Prints the module type and (optionally) the body of the module *ident*.

### Command: Print Module Type ident

Prints the module type corresponding to *ident*.

#### Flag: Short Module Printing

This flag (off by default) disables the printing of the types of fields, leaving only their names, for the commands *Print Module* and *Print Module Type*.

### 4.2.6 Libraries and qualified names

### Names of libraries

The theories developed in Coq are stored in *library files* which are hierarchically classified into *libraries* and *sublibraries*. To express this hierarchy, library names are represented by qualified identifiers qualid, i.e. as list of identifiers separated by dots (see *Qualified identifiers and simple identifiers*). For instance, the library file Mult of the standard Coq library Arith is named Coq. Arith. Mult. The identifier that starts the name of a library is called a *library root*. All library files of the standard library of Coq have the reserved root Coq but library filenames based on other roots can be obtained by using Coq commands (coqc, coqtop, coqdep, ...) options -Q or -R (see *By command line options*). Also, when an interactive Coq session starts, a library of root Top is started, unless option -top or -notop is set (see *By command line options*).

### **Qualified names**

Library files are modules which possibly contain submodules which eventually contain constructions (axioms, parameters, definitions, lemmas, theorems, remarks or facts). The *absolute name*, or *full name*, of a construction in some library file is a qualified identifier starting with the logical name of the library file, followed by the sequence of submodules names encapsulating the construction and ended by the proper name

of the construction. Typically, the absolute name Coq.Init.Logic.eq denotes Leibniz' equality defined in the module Logic in the sublibrary Init of the standard library of Coq.

The proper name that ends the name of a construction is the short name (or sometimes base name) of the construction (for instance, the short name of Coq.Init.Logic.eq is eq). Any partial suffix of the absolute name is a partially qualified name (e.g. Logic.eq is a partially qualified name for Coq.Init.Logic.eq). Especially, the short name of a construction is its shortest partially qualified name.

Coq does not accept two constructions (definition, theorem, ...) with the same absolute name but different constructions can have the same short name (or even same partially qualified names as soon as the full names are different).

Notice that the notion of absolute, partially qualified and short names also applies to library filenames.

### Visibility

Coq maintains a table called the name table which maps partially qualified names of constructions to absolute names. This table is updated by the commands <code>Require</code>, <code>Import</code> and <code>Export</code> and also each time a new declaration is added to the context. An absolute name is called visible from a given short or partially qualified name when this latter name is enough to denote it. This means that the short or partially qualified name is mapped to the absolute name in Coq name table. Definitions flagged as Local are only accessible with their fully qualified name (see <code>Definitions</code>).

It may happen that a visible name is hidden by the short name or a qualified name of another construction. In this case, the name that has been hidden must be referred to using one more level of qualification. To ensure that a construction always remains accessible, absolute names can never be hidden.

### Example

### See also:

Commands Locate and Locate Library.

#### Libraries and filesystem

**Note:** The questions described here have been subject to redesign in Coq 8.5. Former versions of Coq use the same terminology to describe slightly different things.

Compiled files (.vo and .vio) store sub-libraries. In order to refer to them inside Coq, a translation from file-system names to Coq names is needed. In this translation, names in the file system are called *physical* paths while Coq names are contrastingly called *logical* names.

A logical prefix Lib can be associated with a physical path using the command line option -Q path Lib. All subfolders of path are recursively associated to the logical path Lib extended with the corresponding suffix coming from the physical path. For instance, the folder path/f00/Bar maps to Lib.f00.Bar. Subdirectories corresponding to invalid Coq identifiers are skipped, and, by convention, subdirectories named CVS or \_darcs are skipped too.

Thanks to this mechanism, .vo files are made available through the logical name of the folder they are in, extended with their own basename. For example, the name associated to the file path/f00/Bar/File.vo is Lib.f00.Bar.File. The same caveat applies for invalid identifiers. When compiling a source file, the .vo file stores its logical name, so that an error is issued if it is loaded with the wrong loadpath afterwards.

Some folders have a special status and are automatically put in the path. Coq commands associate automatically a logical path to files in the repository trees rooted at the directory from where the command is launched, coqlib/user-contrib/, the directories listed in the \$COQPATH, \${XDG\_DATA\_HOME}/coq/ and \${XDG\_DATA\_DIRS}/coq/ environment variables (see XDG base directory specification<sup>294</sup>) with the same physical-to-logical translation and with an empty logical prefix.

The command line option -R is a variant of -Q which has the strictly same behavior regarding loadpaths, but which also makes the corresponding .vo files available through their short names in a way not unlike the Import command (see here). For instance, -R path Lib associates to the file /path/f00/Bar/File.vo the logical name Lib.f00.Bar.File, but allows this file to be accessed through the short names f00.Bar.File,Bar.File and File. If several files with identical base name are present in different subdirectories of a recursive loadpath, which of these files is found first may be system-dependent and explicit qualification is recommended. The From argument of the Require command can be used to bypass the implicit shortening by providing an absolute root to the required file (see Compiled files).

There also exists another independent loadpath mechanism attached to OCaml object files (.cmo or .cmxs) rather than Coq object files as described above. The OCaml loadpath is managed using the option -I path (in the OCaml world, there is neither a notion of logical name prefix nor a way to access files in subdirectories of path). See the command <code>Declare ML Module</code> in <code>Compiled files</code> to understand the need of the OCaml loadpath.

See By command line options for a more general view over the Coq command line options.

### 4.2.7 Implicit arguments

An implicit argument of a function is an argument which can be inferred from contextual knowledge. There are different kinds of implicit arguments that can be considered implicit in different ways. There are also various commands to control the setting or the inference of implicit arguments.

#### The different kinds of implicit arguments

 $<sup>^{294}\ \</sup>mathrm{http://standards.freedesktop.org/basedir-spec/basedir-spec-latest.html}$ 

#### Implicit arguments inferable from the knowledge of other arguments of a function

The first kind of implicit arguments covers the arguments that are inferable from the knowledge of the type of other arguments of the function, or of the type of the surrounding context of the application. Especially, such implicit arguments correspond to parameters dependent in the type of the function. Typical implicit arguments are the type arguments in polymorphic functions. There are several kinds of such implicit arguments.

### Strict Implicit Arguments

An implicit argument can be either strict or non strict. An implicit argument is said to be *strict* if, whatever the other arguments of the function are, it is still inferable from the type of some other argument. Technically, an implicit argument is strict if it corresponds to a parameter which is not applied to a variable which itself is another parameter of the function (since this parameter may erase its arguments), not in the body of a match, and not itself applied or matched against patterns (since the original form of the argument can be lost by reduction).

For instance, the first argument of

```
cons: forall A:Set, A -> list A -> list A
```

in module List.v is strict because list is an inductive type and A will always be inferable from the type list A of the third argument of cons. Also, the first argument of cons is strict with respect to the second one, since the first argument is exactly the type of the second argument. On the contrary, the second argument of a term of type

```
forall P:nat->Prop, forall n:nat, P n -> ex nat P
```

is implicit but not strict, since it can only be inferred from the type P n of the third argument and if P is, e.g., fun  $\_$  => True, it reduces to an expression where n does not occur any longer. The first argument P is implicit but not strict either because it can only be inferred from P n and P is not canonically inferable from an arbitrary n and the normal form of P n. Consider, e.g., that n is 0 and the third argument has type True, then any P of the form

```
fun n => match n with 0 => True | _ => anything end
```

would be a solution of the inference problem.

#### Contextual Implicit Arguments

An implicit argument can be *contextual* or not. An implicit argument is said *contextual* if it can be inferred only from the knowledge of the type of the context of the current expression. For instance, the only argument of:

```
nil : forall A:Set, list A`
is contextual. Similarly, both arguments of a term of type:
forall P:nat->Prop, forall n:nat, P n \/ n = 0
are contextual (moreover, n is strict and P is not).
```

### Reversible-Pattern Implicit Arguments

There is another class of implicit arguments that can be reinferred unambiguously if all the types of the remaining arguments are known. This is the class of implicit arguments occurring in the type of another argument in position of reversible pattern, which means it is at the head of an application but applied only to uninstantiated distinct variables. Such an implicit argument is called *reversible-pattern implicit argument*. A typical example is the argument P of nat\_rec in

```
nat_rec : forall P : nat -> Set, P 0 ->
  (forall n : nat, P n -> P (S n)) -> forall x : nat, P x
```

(P is reinferable by abstracting over n in the type P n).

See Controlling reversible-pattern implicit arguments for the automatic declaration of reversible-pattern implicit arguments.

### Implicit arguments inferable by resolution

This corresponds to a class of non-dependent implicit arguments that are solved based on the structure of their type only.

### Maximal or non maximal insertion of implicit arguments

In case a function is partially applied, and the next argument to be applied is an implicit argument, two disciplines are applicable. In the first case, the function is considered to have no arguments furtherly: one says that the implicit argument is not maximally inserted. In the second case, the function is considered to be implicitly applied to the implicit arguments it is waiting for: one says that the implicit argument is maximally inserted.

Each implicit argument can be declared to have to be inserted maximally or non maximally. This can be governed argument per argument by the command Arguments (implicits) or globally by the Maximal Implicit Insertion flag.

#### See also:

Displaying what the implicit arguments are.

### Casual use of implicit arguments

In a given expression, if it is clear that some argument of a function can be inferred from the type of the other arguments, the user can force the given argument to be guessed by replacing it by "\_". If possible, the correct argument will be automatically generated.

```
Error: Cannot infer a term for this placeholder.

Coq was not able to deduce an instantiation of a " ".
```

### **Declaration of implicit arguments**

In case one wants that some arguments of a given object (constant, inductive types, constructors, assumptions, local or not) are always inferred by Coq, one may declare once and for all which are the expected implicit arguments of this object. There are two ways to do this, a priori and a posteriori.

#### **Implicit Argument Binders**

In the first setting, one wants to explicitly give the implicit arguments of a declared object as part of its definition. To do this, one has to surround the bindings of implicit arguments by curly braces:

```
Definition id \{A : Type\} (x : A) : A := x.
id is defined
```

This automatically declares the argument A of id as a maximally inserted implicit argument. One can then do as-if the argument was absent in every situation but still be able to specify it if needed:

The syntax is supported in all top-level definitions: *Definition*, *Fixpoint*, *Lemma* and so on. For (co)inductive datatype declarations, the semantics are the following: an inductive parameter declared as an implicit argument need not be repeated in the inductive definition and will become implicit for the inductive type and the constructors. For example:

```
Inductive list {A : Type} : Type :=
| nil : list
| cons : A -> list -> list.
| list is defined
| list_rect is defined
| list_ind is defined
| list_rec is defined
| list_sind is defined
| list_sind is defined
Print list.

Inductive list (A : Type) : Type := nil : list | cons : A -> list -> list

Arguments list {A}%type_scope
Arguments nil {A}%type_scope
Arguments cons {A}%type_scope
```

One can always specify the parameter if it is not uniform using the usual implicit arguments disambiguation syntax.

### **Declaring Implicit Arguments**

```
Command: Arguments qualid [ ident ] { ident } ident
```

This command is used to set implicit arguments a posteriori, where the list of possibly bracketed *ident* is a prefix of the list of arguments of *qualid* where the ones to be declared implicit are surrounded by square brackets and the ones to be declared as maximally inserted implicits are surrounded by curly braces.

After the above declaration is issued, implicit arguments can just (and have to) be skipped in any expression involving an application of qualid.

#### Command: Arguments qualid : clear implicits


This command clears implicit arguments.

```
Variant: Global Arguments qualid [ ident ] { ident } ident
```

This command is used to recompute the implicit arguments of *qualid* after ending of the current section if any, enforcing the implicit arguments known from inside the section to be the ones declared by the command.



When in a module, tell not to activate the implicit arguments of qualid declared by this command to contexts that require the module.



For names of constants, inductive types, constructors, lemmas which can only be applied to a fixed number of arguments (this excludes for instance constants whose type is polymorphic), multiple implicit arguments declarations can be given. Depending on the number of arguments qualid is applied to in practice, the longest applicable list of implicit arguments is used to select which implicit arguments are inserted. For printing, the omitted arguments are the ones of the longest list of implicit arguments of the sequence.

### Example

```
Inductive list (A : Type) : Type :=
| nil : list A
| cons : A -> list A -> list A.
    list is defined
    list_rect is defined
   list_ind is defined
    list_rec is defined
    list_sind is defined
Check (cons nat 3 (nil nat)).
    cons nat 3 (nil nat)
         : list nat
Arguments cons [A] _ _.
Arguments nil {A}.
Check (cons 3 nil).
   cons 3 nil
         : list nat
Fixpoint map (A B : Type) (f : A \rightarrow B) (1 : list A) : list B :=
 match 1 with nil \Rightarrow nil | cons a t \Rightarrow cons (f a) (map A B f t) end.
   map is defined
    map is recursively defined (decreasing on 4th argument)
Fixpoint length (A : Type) (1 : list A) : nat :=
 match 1 with nil => 0 | cons m => S (length A m) end.
   length is defined
    length is recursively defined (decreasing on 2nd argument)
Arguments map [A B] f 1.
Arguments length {A} 1.
(* A has to be maximally inserted *)
Check (fun 1:list (list nat) => map length 1).
   fun 1 : list (list nat) => map length 1
         : list (list nat) -> list nat
Arguments map [A B] f 1, [A] B f 1, A B f 1.
Check (fun 1 => map length 1 = map (list nat) nat length 1).
    fun 1 : list (list nat) => map length 1 = map length 1
         : list (list nat) -> Prop
```

**Note:** To know which are the implicit arguments of an object, use the command *Print Implicit* (see *Displaying what the implicit arguments are*).

```
Warning: Argument number num is a trailing implicit so must be maximal.
```

For instance in

### Automatic declaration of implicit arguments

#### Command: Arguments qualid : default implicits

This command tells Coq to automatically detect what are the implicit arguments of a defined object.

The auto-detection is governed by flags telling if strict, contextual, or reversible-pattern implicit arguments must be considered or not (see Controlling strict implicit arguments, Controlling strict implicit arguments, Controlling reversible-pattern implicit arguments, and also Controlling the insertion of implicit arguments not followed by explicit arguments).

### Variant: Global Arguments qualid : default implicits

Tell to recompute the implicit arguments of qualid after ending of the current section if any.

### Variant: Local Arguments qualid : default implicits

When in a module, tell not to activate the implicit arguments of qualid computed by this declaration to contexts that requires the module.

### Example

```
Inductive list (A:Set) : Set :=
| nil : list A
| cons : A -> list A -> list A.
    list is defined
    list_rect is defined
    list_ind is defined
    list_rec is defined
    list_sind is defined
Arguments cons : default implicits.
Print Implicit cons.
    cons : forall A : Set, A \rightarrow list A \rightarrow list A
    Argument A is implicit
Arguments nil : default implicits.
Print Implicit nil.
    nil : forall A : Set, list A
Set Contextual Implicit.
Arguments nil : default implicits.
Print Implicit nil.
```

(continues on next page)

(continued from previous page)

```
\label{eq:aniliary} \mbox{nil} \ : \mbox{forall A} : \mbox{Set, list A} \mbox{Argument A is implicit and maximally inserted}
```

The computation of implicit arguments takes account of the unfolding of constants. For instance, the variable p below has type (Transitivity R) which is reducible to forall x,y:U, R x y -> forall z:U, R y z -> R x z. As the variables x, y and z appear strictly in the body of the type, they are implicit.

```
Parameter X : Type.
   X is declared
Definition Relation := X -> X -> Prop.
    Relation is defined
Definition Transitivity (R:Relation) := forall x y:X, R x y -> forall z:X, R y z -> R x z.
    Transitivity is defined
Parameters (R : Relation) (p : Transitivity R).
   R is declared
    p is declared
Arguments p : default implicits.
Print p.
    *** [ p : Transitivity R ]
    Expanded type for implicit arguments
    p : forall x y : X, R x y -> forall z : X, R y z -> R x z
   Arguments p [x y] _ [z]
Print Implicit p.
    p : forall x y : X, R x y -> forall z : X, R y z -> R x z
    Arguments x, y, z are implicit
Parameters (a b c : X) (r1 : R a b) (r2 : R b c).
    a is declared
   b is declared
    c is declared
   r1 is declared
   r2 is declared
Check (p r1 r2).
   p r1 r2
         : Rac
```

### Mode for automatic declaration of implicit arguments

### Flag: Implicit Arguments

This flag (off by default) allows to systematically declare implicit the arguments detectable as such. Auto-detection of implicit arguments is governed by flags controlling whether strict and contextual implicit arguments have to be considered or not.

### Controlling strict implicit arguments

#### Flag: Strict Implicit

When the mode for automatic declaration of implicit arguments is on, the default is to automatically set implicit only the strict implicit arguments plus, for historical reasons, a small subset of the non-strict implicit arguments. To relax this constraint and to set implicit all non strict implicit arguments by default, you can turn this flag off.

#### Flag: Strongly Strict Implicit

Use this flag (off by default) to capture exactly the strict implicit arguments and no more than the strict implicit arguments.

#### Controlling contextual implicit arguments

#### Flag: Contextual Implicit

By default, Coq does not automatically set implicit the contextual implicit arguments. You can turn this flag on to tell Coq to also infer contextual implicit argument.

#### Controlling reversible-pattern implicit arguments

### Flag: Reversible Pattern Implicit

By default, Coq does not automatically set implicit the reversible-pattern implicit arguments. You can turn this flag on to tell Coq to also infer reversible-pattern implicit argument.

### Controlling the insertion of implicit arguments not followed by explicit arguments

#### Flag: Maximal Implicit Insertion

Assuming the implicit argument mode is on, this flag (off by default) declares implicit arguments to be automatically inserted when a function is partially applied and the next argument of the function is an implicit one.

#### **Explicit applications**

In presence of non-strict or contextual argument, or in presence of partial applications, the synthesis of implicit arguments may fail, so one may have to give explicitly certain implicit arguments of an application. The syntax for this is (*ident* := *term*) where *ident* is the name of the implicit argument and term is its corresponding explicit term. Alternatively, one can locally deactivate the hiding of implicit arguments of a function by using the notation *qualid* term. This syntax extension is given in the following grammar:

```
term ::= @ qualid term ... term @ qualid argument ... argument argument ::= term (ident := term)
```

Syntax for explicitly giving implicit arguments

### Example: (continued)

### Renaming implicit arguments

## Command: Arguments qualid name : rename

This command is used to redefine the names of implicit arguments.

# Command: Arguments qualid name : assert

This command is used to assert that a given object has the expected number of arguments and that these arguments are named as expected.

### Example: (continued)

### Displaying what the implicit arguments are

### Command: Print Implicit qualid

Use this command to display the implicit arguments associated to an object, and to know if each of them is to be used maximally or not.

### Explicit displaying of implicit arguments for pretty-printing

### Flag: Printing Implicit

By default, the basic pretty-printing rules hide the inferable implicit arguments of an application. Turn this flag on to force printing all implicit arguments.

### Flag: Printing Implicit Defensive

By default, the basic pretty-printing rules display the implicit arguments that are not detected as strict implicit arguments. This "defensive" mode can quickly make the display cumbersome so this can be deactivated by turning this flag off.

#### See also:

# Printing All.

#### Interaction with subtyping

When an implicit argument can be inferred from the type of more than one of the other arguments, then only the type of the first of these arguments is taken into account, and not an upper type of all of them. As a consequence, the inference of the implicit argument of "=" fails in

```
Fail Check nat = Prop.
   The command has indeed failed with message:
   The term "Prop" has type "Type" while it is expected to have type
   "Set" (universe inconsistency).

but succeeds in

Check Prop = nat.
   Prop = nat
   : Prop
```

#### Deactivation of implicit arguments for parsing

#### Flag: Parsing Explicit

Turning this flag on (it is off by default) deactivates the use of implicit arguments.

In this case, all arguments of constants, inductive types, constructors, etc, including the arguments declared as implicit, have to be given as if no arguments were implicit. By symmetry, this also affects printing.

#### **Canonical structures**

A canonical structure is an instance of a record/structure type that can be used to solve unification problems involving a projection applied to an unknown structure instance (an implicit argument) and a value. The complete documentation of canonical structures can be found in *Canonical Structures*; here only a simple example is given.

```
Command: Canonical Structure qualid
```

This command declares qualid as a canonical instance of a structure (a record).

Assume that qualid denotes an object (Build\_struct  $c_1 \dots c_n$ ) in the structure struct of which the fields are  $x_1, \dots, x_n$ . Then, each time an equation of the form  $(x_i) = \beta \delta i \zeta$   $c_i$  has to be solved during the type checking process, qualid is used as a solution. Otherwise said, qualid is canonically used to extend the field  $c_i$  into a complete structure built on  $c_i$ .

Canonical structures are particularly useful when mixed with coercions and strict implicit arguments.

## Example

Here is an example.

```
Require Import Relations.

Require Import EqNat.

Set Implicit Arguments.

Unset Strict Implicit.

Structure Setoid: Type := {Carrier:> Set; Equal: relation Carrier;

(continues on next page)
```

(continued from previous page)

```
Prf_equiv : equivalence Carrier Equal}.

Setoid is defined
Carrier is defined
Equal is defined
Prf_equiv is defined

Definition is_law (A B:Setoid) (f:A -> B) := forall x y:A, Equal x y -> Equal (f x) (f y).
    is_law is defined

Axiom eq_nat_equiv : equivalence nat eq_nat.
    eq_nat_equiv is declared

Definition nat_setoid : Setoid := Build_Setoid eq_nat_equiv.
    nat_setoid is defined

Canonical nat_setoid.
```

Thanks to  $nat\_setoid$  declared as canonical, the implicit arguments A and B can be synthesized in the next statement.

**Note:** If a same field occurs in several canonical structures, then only the structure declared first as canonical is considered.

**Note:** To prevent a field from being involved in the inference of canonical instances, its declaration can be annotated with the #[canonical(false)] attribute.

# Example

For instance, when declaring the Setoid structure above, the Prf\_equiv field declaration could be written as follows.

```
#[canonical(false)] Prf_equiv : equivalence Carrier Equal
```

See Canonical Structures for a more realistic example.

```
Variant: Canonical Structure | ident : type | := term
```

This is equivalent to a regular definition of *ident* followed by the declaration Canonical *ident*.

# Command: Print Canonical Projections

This displays the list of global names that are components of some canonical structure. For each of them, the canonical structure of which it is a projection is indicated.

## Example

For instance, the above example gives the following output:

```
Print Canonical Projections.
  nat <- Carrier ( nat_setoid )
  eq_nat <- Equal ( nat_setoid )
  eq_nat_equiv <- Prf_equiv ( nat_setoid )</pre>
```

**Note:** The last line would not show up if the corresponding projection (namely Prf\_equiv) were annotated as not canonical, as described above.

## Implicit types of variables

It is possible to bind variable names to a given type (e.g. in a development using arithmetic, it may be convenient to bind the names n or m to the type nat of natural numbers).

# Command: Implicit Types ident : type

The effect of the command is to automatically set the type of bound variables starting with *ident* (either *ident* itself or *ident* followed by one or more single quotes, underscore or digits) to be *type* (unless the bound variable is already declared with an explicit type in which case, this latter type is considered).

# Example

```
Require Import List.
Implicit Types m n : nat.
Lemma cons_inj_nat : forall m n 1, n :: 1 = m :: 1 \rightarrow n = m.
   1 subgoal
      _____
     forall (m \ n : nat) (1 : Datatypes.list nat), n :: 1 = m :: 1 -> n = m
Proof.
intros m n.
   1 subgoal
     m, n : nat
     _____
     forall 1 : Datatypes.list nat, n :: 1 = m :: 1 \rightarrow n = m
Abort.
Lemma cons_inj_bool : forall (m \ n:bool) \ 1, \ n :: 1 = m :: 1 \rightarrow n = m.
   1 subgoal
      _____
      forall (m \ n : bool) (1 : Datatypes.list bool), <math>n :: 1 = m :: 1 \rightarrow n = m
Abort.
```

## Variant: Implicit Type ident : type

This is useful for declaring the implicit type of a single variable.

```
Variant: Implicit Types ( ident : type )
```

Adds blocks of implicit types with different specifications.

#### Implicit generalization

Implicit generalization is an automatic elaboration of a statement with free variables into a closed statement where these variables are quantified explicitly.

It is activated for a binder by prefixing a ', and for terms by surrounding it with '{ } or '( ).

Terms surrounded by '{} introduce their free variables as maximally inserted implicit arguments, and terms surrounded by '() introduce them as explicit arguments.

Generalizing binders always introduce their free variables as maximally inserted implicit arguments. The binder itself introduces its argument as usual.

In the following statement, A and y are automatically generalized, A is implicit and x, y and the anonymous equality argument are explicit.

```
Generalizable All Variables.
Definition sym `(x:A) : `(x = y -> y = x) := fun _ p => eq_sym p.
    sym is defined

Print sym.
    sym =
    fun (A : Type) (x y : A) (p : x = y) => eq_sym p
        : forall (A : Type) (x y : A), x = y -> y = x

Arguments sym {A}%type_scope
```

Dually to normal binders, the name is optional but the type is required:

```
Check (forall \{x = y :> A\}, y = x).

forall (A : Type) \{x : A\}, x = y -> y = x

: Prop
```

When generalizing a binder whose type is a typeclass, its own class arguments are omitted from the syntax and are generalized using automatic names, without instance search. Other arguments are also generalized unless provided. This produces a fully general statement. this behaviour may be disabled by prefixing the type with a ! or by forcing the typeclass name to be an explicit application using @ (however the later ignores implicit argument information).

(continues on next page)

(continued from previous page)

```
Fail Check (forall `{Commutative nat _}, True).
    The command has indeed failed with message:
   Typeclass does not expect more arguments
Fail Check (forall `{!Commutative nat}, True).
    The command has indeed failed with message:
    The term "Commutative nat" has type "Op nat -> Prop"
   which should be Set, Prop or Type.
Arguments Commutative _ {_}}.
Check (forall `{!Commutative nat}, True).
    @Commutative nat nat_op -> True
Check (forall `{@Commutative nat plus}, True).
    @Commutative nat Nat.add -> True
         : Prop
Multiple binders can be merged using, as a separator:
Check (forall `{Commutative A, Hnat : !Commutative nat}, True).
   forall (A : Type) (H : Op A),
    @Commutative A H -> @Commutative nat nat_op -> True
         : Prop
```

One can control the set of generalizable identifiers with the **Generalizable** vernacular command to avoid unexpected generalizations when mistyping identifiers. There are several commands that specify which variables should be generalizable.

# Command: Generalizable All Variables

All variables are candidate for generalization if they appear free in the context under a generalization delimiter. This may result in confusing errors in case of typos. In such cases, the context will probably contain some unexpected generalized variable.

#### Command: Generalizable No Variables

Disable implicit generalization entirely. This is the default behavior.

# Command: Generalizable Variable Variables ident

Allow generalization of the given identifiers only. Calling this command multiple times adds to the allowed identifiers.

#### Command: Global Generalizable

Allows exporting the choice of generalizable variables.

#### 4.2.8 Coercions

Coercions can be used to implicitly inject terms from one *class* in which they reside into another one. A *class* is either a sort (denoted by the keyword Sortclass), a product type (denoted by the keyword Funclass), or a type constructor (denoted by its name), e.g. an inductive type or any constant with a type of the form forall ( $x_1 : A_1$ ) ... ( $x_n : A_n$ ), s where s is a sort.

Then the user is able to apply an object that is not a function, but can be coerced to a function, and more generally to consider that a term of type A is of type B provided that there is a declared coercion between A and B.

More details and examples, and a description of the commands related to coercions are provided in *Implicit Coercions*.

# 4.2.9 Printing constructions in full

# Flag: Printing All

Coercions, implicit arguments, the type of pattern matching, but also notations (see Syntax extensions and interpretation scopes) can obfuscate the behavior of some tactics (typically the tactics applying to occurrences of subterms are sensitive to the implicit arguments). Turning this flag on deactivates all high-level printing features such as coercions, implicit arguments, returned type of pattern matching, notations and various syntactic sugar for pattern matching or record projections. Otherwise said, Printing All includes the effects of the flags Printing Implicit, Printing Coercions, Printing Synth, Printing Projections, and Printing Notations. To reactivate the high-level printing features, use the command Unset Printing All.

# 4.2.10 Printing universes

# Flag: Printing Universes

Turn this flag on to activate the display of the actual level of each occurrence of Type. See *Sorts* for details. This wizard flag, in combination with *Printing All* can help to diagnose failures to unify terms apparently identical but internally different in the Calculus of Inductive Constructions.

# Command: Print Sorted | Universes

This command can be used to print the constraints on the internal level of the occurrences of Type (see *Sorts*).

If the Sorted keyword is present, each universe will be made equivalent to a numbered label reflecting its level (with a linear ordering) in the universe hierarchy.

# Variant: Print Sorted Universes string

This variant accepts an optional output filename.

If *string* ends in .dot or .gv, the constraints are printed in the DOT language, and can be processed by Graphviz tools. The format is unspecified if string doesn't end in .dot or .gv.

# Variant: Print Universes Subgraph(qualid)

Prints the graph restricted to the requested names (adjusting constraints to preserve the implied transitive constraints between kept universes).

## 4.2.11 Existential variables

Coq terms can include existential variables which represents unknown subterms to eventually be replaced by actual subterms.

Existential variables are generated in place of unsolvable implicit arguments or "\_" placeholders when using commands such as Check (see Section Requests to the environment) or when using tactics such as refine, as well as in place of unsolvable instances when using tactics such that eapply. An existential variable is defined in a context, which is the context of variables of the placeholder which generated the existential variable, and a type, which is the expected type of the placeholder.

As a consequence of typing constraints, existential variables can be duplicated in such a way that they possibly appear in different contexts than their defining context. Thus, any occurrence of a given existential variable comes with an instance of its original context. In the simple case, when an existential variable denotes the

placeholder which generated it, or is used in the same context as the one in which it was generated, the context is not displayed and the existential variable is represented by "?" followed by an identifier.

In the general case, when an existential variable ?ident appears outside of its context of definition, its instance, written under the form  $\{ ident := term \}$  is appending to its name, indicating how the variables of its defining context are instantiated. The variables of the context of the existential variables which are instantiated by themselves are not written, unless the  $Printing\ Existential\ Instances$  flag is on (see Section  $Explicit\ displaying\ of\ existential\ instances\ for\ pretty-printing$ ), and this is why an existential variable used in the same context as its context of definition is written with no instance.

Existential variables can be named by the user upon creation using the syntax ?[ident]. This is useful when the existential variable needs to be explicitly handled later in the script (e.g. with a named-goal selector, see *Goal selectors*).

# Explicit displaying of existential instances for pretty-printing

#### Flag: Printing Existential Instances

This flag (off by default) activates the full display of how the context of an existential variable is instantiated at each of the occurrences of the existential variable.

#### Solving existential variables using tactics

Instead of letting the unification engine try to solve an existential variable by itself, one can also provide an explicit hole together with a tactic to solve it. Using the syntax ltac:(tacexpr), the user can put a tactic anywhere a term is expected. The order of resolution is not specified and is implementation-dependent. The inner tactic may use any variable defined in its scope, including repeated alternations between variables introduced by term binding as well as those introduced by tactic binding. The expression tacexpr can be any tactic expression as described in *Ltac*.

```
Definition foo (x : nat) : nat := ltac:(exact x). foo is defined
```

This construction is useful when one wants to define complicated terms using highly automated tactics without resorting to writing the proof-term by means of the interactive proof engine.

# 4.2.12 Primitive Integers

The language of terms features 63-bit machine integers as values. The type of such a value is *axiomatized*; it is declared through the following sentence (excerpt from the Int63 module):

```
Primitive int := #int63_type.
```

This type is equipped with a few operators, that must be similarly declared. For instance, equality of two primitive integers can be decided using the Int63.eqb function, declared and specified as follows:

```
Primitive eqb := \#int63\_eq.

Notation "m '==' n" := (eqb m n) (at level 70, no associativity) : int63\_scope.

Axiom eqb_correct : forall i j, (i == j)%int63 = true -> i = j.
```

The complete set of such operators can be obtained looking at the Int63 module.

These primitive declarations are regular axioms. As such, they must be trusted and are listed by the Print Assumptions command, as in the following example.

```
From Coq Require Import Int63.
Lemma one_minus_one_is_zero : (1 - 1 = 0)%int63.
Proof.
apply eqb_correct; vm_compute; reflexivity.
Qed.

Print Assumptions one_minus_one_is_zero.
    Axioms:
    sub : int -> int -> int
    eqb_correct : forall i j : int, (i == j)%int63 = true -> i = j
    eqb : int -> int -> bool
```

The reduction machines (*vm\_compute*, *native\_compute*) implement dedicated, efficient, rules to reduce the applications of these primitive operations.

The extraction of these primitives can be customized similarly to the extraction of regular axioms (see Extraction of programs in OCaml and Haskell). Nonetheless, the ExtrOCamlInt63 module can be used when extracting to OCaml: it maps the Coq primitives to types and functions of a Uint63 module. Said OCaml module is not produced by extraction. Instead, it has to be provided by the user (if they want to compile or execute the extracted code). For instance, an implementation of this module can be taken from the kernel of Coq.

Literal values (at type Int63.int) are extracted to literal OCaml values wrapped into the Uint63.of\_int (resp. Uint63.of\_int64) constructor on 64-bit (resp. 32-bit) platforms. Currently, this cannot be customized (see the function Uint63.compile from the kernel).

#### 4.2.13 Primitive Floats

The language of terms features Binary64 floating-point numbers as values. The type of such a value is *axiomatized*; it is declared through the following sentence (excerpt from the PrimFloat module):

```
Primitive float := #float64_type.
```

This type is equipped with a few operators, that must be similarly declared. For instance, the product of two primitive floats can be computed using the PrimFloat.mul function, declared and specified as follows:

```
Primitive mul := \#float64\_mul.

Notation "x * y" := (mul x y) : float\_scope.

Axiom mul_spec : forall x y, Prim2SF (x * y)\%float = SF64mul (Prim2SF x) (Prim2SF y).
```

where Prim2SF is defined in the FloatOps module.

The set of such operators is described in section *Floats library*.

These primitive declarations are regular axioms. As such, they must be trusted, and are listed by the Print Assumptions command.

The reduction machines (*vm\_compute*, *native\_compute*) implement dedicated, efficient rules to reduce the applications of these primitive operations, using the floating-point processor operators that are assumed to comply with the IEEE 754 standard for floating-point arithmetic.

The extraction of these primitives can be customized similarly to the extraction of regular axioms (see *Extraction of programs in OCaml and Haskell*). Nonetheless, the Extr0CamlFloats module can be used when extracting to OCaml: it maps the Coq primitives to types and functions of a Float64 module. Said OCaml module is not produced by extraction. Instead, it has to be provided by the user (if they want to compile or execute the extracted code). For instance, an implementation of this module can be taken from the kernel of Coq.

Literal values (of type Float64.t) are extracted to literal OCaml values (of type float) written in hexadecimal notation and wrapped into the Float64.of\_float constructor, e.g.: Float64.of\_float (0x1p+0).

#### 4.2.14 Bidirectionality hints

When type-checking an application, Coq normally does not use information from the context to infer the types of the arguments. It only checks after the fact that the type inferred for the application is coherent with the expected type. Bidirectionality hints make it possible to specify that after type-checking the first arguments of an application, typing information should be propagated from the context to help inferring the types of the remaining arguments.

```
Command: Arguments qualid ident<sub>1</sub> & ident<sub>2</sub> *
```

This commands tells the typechecking algorithm, when type-checking applications of qualid, to first type-check the arguments in  $ident_1$  and then propagate information from the typing context to type-check the remaining arguments (in  $ident_2$ ).

## Example

In a context where a coercion was declared from bool to nat:

```
Definition b2n (b : bool) := if b then 1 else 0. Coercion b2n : bool >-> nat.
```

Coq cannot automatically coerce existential statements over **bool** to statements over **nat**, because the need for inserting a coercion is known only from the expected type of a subterm:

```
Fail Check (ex_intro _ true _ : exists n : nat, n > 0). The command has indeed failed with message: The term "ex_intro ?P true ?y" has type "exists y, ?P y" while it is expected to have type "exists n : nat, n > 0" (cannot unify "bool" and "nat").
```

However, a suitable bidirectionality hint makes the example work:

Coq will attempt to produce a term which uses the arguments you provided, but in some cases involving Program mode the arguments after the bidirectionality starts may be replaced by convertible but syntactically different terms.

# 4.3 The Coq library

The Coq library has two parts:

- The basic library: definitions and theorems for the most commonly used elementary logical notions and data types. Coq normally loads these files automatically when it starts.
- The standard library: general-purpose libraries with definitions and theorems for sets, lists, sorting, arithmetic, etc. To use these files, users must load them explicitly with the Require command (see Compiled files)

There are also many libraries provided by Coq users' community. These libraries and developments are available for download at http://coq.inria.fr (see *Users' contributions*).

This chapter briefly reviews the Coq libraries whose contents can also be browsed at http://coq.inria.fr/stdlib/.

# 4.3.1 The basic library

This section lists the basic notions and results which are directly available in the standard Coq system. Most of these constructions are defined in the Prelude module in directory theories/Init at the Coq root directory; this includes the modules Notations, Logic, Datatypes, Specif, Peano, Wf and Tactics. Module Logic\_Type also makes it in the initial state.

#### **Notations**

This module defines the parsing and pretty-printing of many symbols (infixes, prefixes, etc.). However, it does not assign a meaning to these notations. The purpose of this is to define and fix once for all the

precedence and associativity of very common notations. The main notations fixed in the initial state are:

Notation	Precedence	Associativity
> _	99	right
_ <-> _	95	no
_ \/ _	85	right
_ /\ _	80	right
~ _	75	right
_ = _	70	no
_ = _ = _	70	no
_ = _ :> _	70	no
_ <> _	70	no
_ <> _ :> _	70	no
_ < _	70	no
_ > _	70	no
_ <= _	70	no
_ >= _	70	no
_ < _ < _	70	no
_ < _ <= _	70	no
_ <= _ < _	70	no
_ <= _ <= _	70	no
_ + _	50	left
_ 11 _	50	left
	50	left
_ * _	40	left
	40	left
_ / _	40	left
	35	right
/_	35	right
_ ^ _	30	right

# Logic

The basic library of Coq comes with the definitions of standard (intuitionistic) logical connectives (they are defined as inductive constructions). They are equipped with an appealing syntax enriching the subclass form of the syntactic class term. The syntax of form is shown below:

**Note:** Implication is not defined but primitive (it is a non-dependent product of a proposition over another proposition). There is also a primitive universal quantification (it is a dependent product over a proposition). The primitive universal quantification allows both first-order and higher-order quantification.

# **Propositional Connectives**

First, we find propositional calculus connectives:

```
Inductive True : Prop := I.
Inductive False : Prop := .
Definition not (A: Prop) := A -> False.
Inductive and (A B:Prop) : Prop := conj (_:A) (_:B).
Section Projections.
Variables A B : Prop.
Theorem proj1 : A /\ B -> A.
Theorem proj2 : A /\ B -> B.
End Projections.
Inductive or (A B:Prop) : Prop := | or_introl (_:A) | or_intror (_:B).
Definition iff (P Q:Prop) := (P -> Q) /\ (Q -> P).
Definition IF_then_else (P Q R:Prop) := P /\ Q \/ ~ P /\ R.
```

#### Quantifiers

Then we find first-order quantifiers:

```
Definition all (A:Set) (P:A -> Prop) := forall x:A, P x. Inductive ex (A: Set) (P:A -> Prop) : Prop := ex_intro (x:A) (_:P x). Inductive ex2 (A:Set) (P Q:A -> Prop) : Prop := ex_intro2 (x:A) (_:P x) (_:Q x).
```

The following abbreviations are allowed:

exists x:A, P	ex A (fun x:A => P)
exists x, P	$ex_{(fun x \Rightarrow P)}$
exists2 x:A, P & Q	ex2 A (fun x:A $\Rightarrow$ P) (fun x:A $\Rightarrow$ Q)
exists2 x, P & Q	$ex2 _ (fun x \Rightarrow P) (fun x \Rightarrow Q)$

The type annotation : A can be omitted when A can be synthesized by the system.

## **Equality**

Then, we find equality, defined as an inductive relation. That is, given a type A and an x of type A, the predicate (eq A x) is the smallest one which contains x. This definition, due to Christine Paulin-Mohring, is equivalent to define eq as the smallest reflexive relation, and it is also equivalent to Leibniz' equality.

```
Inductive eq (A:Type) (x:A) : A \rightarrow Prop := eq_refl : eq A x x.
```

#### Lemmas

Finally, a few easy lemmas are provided.

```
Theorem absurd : forall A C:Prop, A -> ~ A -> C.
Section equality.
Variables A B : Type.
Variable f : A \rightarrow B.
Variables x y z : A.
Theorem eq_sym : x = y \rightarrow y = x.
Theorem eq_trans : x = y \rightarrow y = z \rightarrow x = z.
Theorem f_{q} = q = 1: x = y \rightarrow f = f = y.
Theorem not_eq_sym : x \leftrightarrow y \rightarrow y \leftrightarrow x.
End equality.
Definition eq_ind_r :
 \mbox{forall } (A:\mbox{\tt Type}) \ (x:\mbox{\tt A}) \ (P:\mbox{\tt A}->\mbox{\tt Prop}) \,, \ P \ x \ -> \ \mbox{\tt forall} \ y:\mbox{\tt A}, \ y \ = \ x \ -> \ P \ y \,.
Definition eq_rec_r :
 forall (A:Type) (x:A) (P:A->Set), P \times -> forall y:A, y = x -> P y.
Definition eq_rect_r :
 {\tt Hint\ Immediate\ eq\_sym\ not\_eq\_sym\ :\ core.}
```

The theorem f\_equal is extended to functions with two to five arguments. The theorem are names f\_equal2, f\_equal3, f\_equal4 and f\_equal5. For instance f\_equal3 is defined the following way.

```
Theorem f_equal3 : forall (A1 A2 A3 B:Type) (f:A1 -> A2 -> A3 -> B)  (x1 \ y1:A1) \ (x2 \ y2:A2) \ (x3 \ y3:A3) \, , \\ x1 = y1 -> x2 = y2 -> x3 = y3 -> f \ x1 \ x2 \ x3 = f \ y1 \ y2 \ y3 .
```

# **Datatypes**

In the basic library, we find in Datatypes.v the definition of the basic data-types of programming, defined as inductive constructions over the sort Set. Some of them come with a special syntax shown below (this syntax table is common with the next section Specification):

#### **Programming**

```
Inductive unit : Set := tt. Inductive bool : Set := true | false. Inductive nat : Set := 0 \mid S \ (n:nat).
```

(continues on next page)

(continued from previous page)

```
Inductive option (A:Set) : Set := Some (_:A) | None. Inductive identity (A:Type) (a:A) : A \rightarrow Type := refl_identity : identity A a a.
```

Note that zero is the letter 0, and not the numeral 0.

The predicate identity is logically equivalent to equality but it lives in sort Type. It is mainly maintained for compatibility.

We then define the disjoint sum of A+B of two sets A and B, and their product A\*B.

Some operations on bool are also provided: andb (with infix notation &&), orb (with infix notation ||), xorb, implb and negb.

## **Specification**

The following notions defined in module Specif.v allow to build new data-types and specifications. They are available with the syntax shown in the previous section *Datatypes*.

For instance, given A:Type and P:A->Prop, the construct  $\{x:A \mid P x\}$  (in abstract syntax (sig A P)) is a Type. We may build elements of this set as (exist x p) whenever we have a witness x:A with its justification p:P x.

From such a (exist x p) we may in turn extract its witness x:A (using an elimination construct such as match) but not its justification, which stays hidden, like in an abstract data-type. In technical terms, one says that sig is a weak (dependent) sum. A variant sig2 with two predicates is also provided.

```
Inductive sig (A:Set) (P:A -> Prop) : Set := exist (x:A) (_:P x). Inductive sig2 (A:Set) (P Q:A -> Prop) : Set := exist2 (x:A) (_:P x) (_:Q x).
```

A strong (dependent) sum {x:A & P x} may be also defined, when the predicate P is now defined as a constructor of types in Type.

```
Inductive sigT (A:Type) (P:A -> Type) : Type := existT (x:A) (_:P x).
Section Projections2.
Variable A : Type.
Variable P : A -> Type.
Definition projT1 (H:sigT A P) := let (x, h) := H in x.
Definition projT2 (H:sigT A P) :=
match H return P (projT1 H) with
  existT _ x h => h
end.
End Projections2.
```

(continues on next page)

(continued from previous page)

A related non-dependent construct is the constructive sum  $\{A\}+\{B\}$  of two propositions A and B.

```
Inductive sumbool (A B:Prop) : Set := left (_:A) | right (_:B).
```

This sumbool construct may be used as a kind of indexed boolean data-type. An intermediate between sumbool and sum is the mixed sumor which combines A:Set and B:Prop in the construction A+{B} in Set.

```
Inductive sumor (A:Set) (B:Prop) : Set :=
| inleft (_:A)
| inright (_:B).
```

We may define variants of the axiom of choice, like in Martin-Löf's Intuitionistic Type Theory.

```
Lemma Choice :
  forall (S S':Set) (R:S -> S' -> Prop),
    (forall x:S, {y : S' | R x y}) ->
    {f : S -> S' | forall z:S, R z (f z)}.
Lemma Choice2 :
  forall (S S':Set) (R:S -> S' -> Set),
    (forall x:S, {y : S' & R x y}) ->
    {f : S -> S' & forall z:S, R z (f z)}.
Lemma bool_choice :
  forall (S:Set) (R1 R2:S -> Prop),
    (forall x:S, {R1 x} + {R2 x}) ->
    {f : S -> bool |
        forall x:S, f x = true /\ R1 x \/ f x = false /\ R2 x}.
```

The next construct builds a sum between a data-type A:Type and an exceptional value encoding errors:

```
Definition Exc := option.
Definition value := Some.
Definition error := None.
```

This module ends with theorems, relating the sorts Set or Type and Prop in a way which is consistent with the realizability interpretation.

```
Definition except := False_rec. Theorem absurd_set : forall (A:Prop) (C:Set), A -> ~ A -> C. Theorem and_rect2 : forall (A B:Prop) (P:Type), (A -> B -> P) -> A /\ B -> P.
```

#### **Basic Arithmetic**

The basic library includes a few elementary properties of natural numbers, together with the definitions of predecessor, addition and multiplication, in module Peano.v. It also provides a scope nat\_scope gathering standard notations for common operations (+, \*) and a decimal notation for numbers, allowing for instance to write 3 for S (S (S 0))). This also works on the left hand side of a match expression (see for example section refine). This scope is opened by default.

# Example

The following example is not part of the standard library, but it shows the usage of the notations:

Now comes the content of module Peano:

```
Theorem eq_S : forall x y:nat, x = y -> S x = S y.
Definition pred (n:nat) : nat :=
match n with
0 => 0
| S u => u
end.
Theorem pred_Sn : forall m:nat, m = pred (S m).
Hint Immediate eq_add_S : core.
Theorem not_eq_S : forall n m:nat, n <> m -> S n <> S m.
Definition IsSucc (n:nat) : Prop :=
match n with
| 0 => False
| S p => True
end.
Theorem O_S: forall n:nat, 0 \Leftrightarrow S n.
Theorem n_Sn : forall n:nat, n <> S n.
Fixpoint plus (n m:nat) {struct n} : nat :=
match n with
| O => m
| S p => S (p + m)
where "n + m" := (plus n m) : nat_scope.
Lemma plus_n_0 : forall n:nat, n = n + 0.
Lemma plus_n_Sm : forall n m:nat, S(n + m) = n + Sm.
Fixpoint mult (n m:nat) {struct n} : nat :=
match n with
| 0 => 0
| S p => m + p * m
where "n * m" := (mult n m) : nat_scope.
Lemma mult_n_0 : forall n:nat, 0 = n * 0.
Lemma mult_n_{Sm}: forall n = n + n = n + (S = m).
Finally, it gives the definition of the usual orderings le, lt, ge and gt.
Inductive le (n:nat) : nat -> Prop :=
| le_n : le n n
| \ le\_S : forall \ m:nat, \ n \mathrel{<=} m \ -> \ n \mathrel{<=} (S \ m)
where "n \le m" := (le n m) : nat_scope.
Definition lt (n m:nat) := S n \le m.
Definition ge (n m:nat) := m \le n.
Definition gt (n m:nat) := m < n.
```

Properties of these relations are not initially known, but may be required by the user from modules Le and Lt. Finally, Peano gives some lemmas allowing pattern matching, and a double induction principle.

```
Theorem nat_case :
  forall (n:nat) (P:nat -> Prop),
  P 0 -> (forall m:nat, P (S m)) -> P n.
Theorem nat_double_ind :
  forall R:nat -> nat -> Prop,
    (forall n:nat, R 0 n) ->
    (forall n:nat, R (S n) 0) ->
    (forall n m:nat, R n m -> R (S n) (S m)) -> forall n m:nat, R n m.
```

#### Well-founded recursion

The basic library contains the basics of well-founded recursion and well-founded induction, in module Wf.v.

```
Section Well_founded.

Variable A : Type.

Variable R : A -> A -> Prop.

Inductive Acc (x:A) : Prop :=

Acc_intro : (forall y:A, R y x -> Acc y) -> Acc x.

Lemma Acc_inv x : Acc x -> forall y:A, R y x -> Acc y.

Definition well_founded := forall a:A, Acc a.

Hypothesis Rwf : well_founded.

Theorem well_founded_induction :

forall P:A -> Set,
  (forall x:A, (forall y:A, R y x -> P y) -> P x) -> forall a:A, P a.

Theorem well_founded_ind :

forall P:A -> Prop,
  (forall x:A, (forall y:A, R y x -> P y) -> P x) -> forall a:A, P a.
```

The automatically generated scheme Acc\_rect can be used to define functions by fixpoints using well-founded relations to justify termination. Assuming extensionality of the functional used for the recursive call, the fixpoint equation can be proved.

```
Section FixPoint.
Variable P : A -> Type.
Variable F : forall x:A, (forall y:A, R y x \rightarrow P y) \rightarrow P x.
Fixpoint Fix F (x:A) (r:Acc x) {struct r} : P x :=
 F \times (fun (y:A) (p:R y x) \Rightarrow Fix_F y (Acc_inv x r y p)).
Definition Fix (x:A) := Fix_F x (Rwf x).
Hypothesis F_ext :
  forall (x:A) (f g:forall y:A, R y x -> P y),
    (forall (y:A) (p:R y x), f y p = g y p) \rightarrow F x f = F x g.
Lemma Fix_F_eq :
forall (x:A) (r:Acc x),
   F \times (fun (y:A) (p:R y x) \Rightarrow Fix_F y (Acc_inv x r y p)) = Fix_F x r.
Lemma Fix_F_inv: forall (x:A) (r s:Acc x), Fix_F x r = Fix_F x s.
Lemma fix_eq : forall x:A, Fix x = F x (fun (y:A) (p:R y x) => Fix y).
End FixPoint.
End Well_founded.
```

# Accessing the Type level

The standard library includes Type level definitions of counterparts of some logic concepts and basic lemmas about them.

The module Datatypes defines identity, which is the Type level counterpart of equality:

```
Inductive identity (A:Type) (a:A) : A -> Type :=
  identity_refl : identity A a a.
```

Some properties of identity are proved in the module Logic\_Type, which also provides the definition of Type level negation:

```
Definition notT (A:Type) := A -> False.
```

#### **Tactics**

A few tactics defined at the user level are provided in the initial state, in module Tactics.v. They are listed at http://coq.inria.fr/stdlib, in paragraph Init, link Tactics.

# 4.3.2 The standard library

#### Survey

The rest of the standard library is structured into the following subdirectories:

- Logic: Classical logic and dependent equality
- Arith: Basic Peano arithmetic
- PArith: Basic positive integer arithmetic
- NArith: Basic binary natural number arithmetic
- ZArith: Basic relative integer arithmetic
- Numbers: Various approaches to natural, integer and cyclic numbers (currently axiomatically and on top of 2^31 binary words)
- Bool: Booleans (basic functions and results)
- **Lists**: Monomorphic and polymorphic lists (basic functions and results), Streams (infinite sequences defined with co-inductive types)
- Sets: Sets (classical, constructive, finite, infinite, power set, etc.)
- FSets: Specification and implementations of finite sets and finite maps (by lists and by AVL trees)
- **Reals**: Axiomatization of real numbers (classical, basic functions, integer part, fractional part, limit, derivative, Cauchy series, power series and results,...)
- Floats: Machine implementation of floating-point arithmetic (for the binary64 format)
- Relations : Relations (definitions and basic results)
- Sorting: Sorted list (basic definitions and heapsort correctness)
- Strings: 8-bits characters and strings
- Wellfounded: Well-founded relations (basic results)

These directories belong to the initial load path of the system, and the modules they provide are compiled at installation time. So they are directly accessible with the command Require (see Section Compiled files).

The different modules of the Coq standard library are documented online at https://coq.inria.fr/stdlib.

# Peano's arithmetic (nat)

While in the initial state, many operations and predicates of Peano's arithmetic are defined, further operations and results belong to other modules. For instance, the decidability of the basic predicates are defined here. This is provided by requiring the module Arith.

The following table describes the notations available in scope nat\_scope :

Notation	Interpretation
_ < _	1t
_ <= _	le
_ > _	gt
_ >= _	ge
x < y < z	x < y /\ y < z
x < y <= z	x < y /\ y <= z
x <= y < z	x <= y /\ y < z
x <= y <= z	x <= y /\ y <= z
_ + _	plus
	minus
_ * _	mult

# Notations for integer arithmetic

The following table describes the syntax of expressions for integer arithmetic. It is provided by requiring and opening the module ZArith and opening scope Z\_scope. It specifies how notations are interpreted and, when not already reserved, the precedence and associativity.

Notation	Interpretation	Precedence	Associativity
_ < _	Z.lt		
_ <= _	Z.le		
_ > _	Z.gt		
_ >= _	Z.ge		
x < y < z	x < y /\ y < z		
x < y <= z	x < y /\ y <= z		
x <= y < z	x <= y /\ y < z		
x <= y <= z	x <= y /\ y <= z		
_ ?= _	Z.compare	70	no
_ + _	Z.add		
	Z.sub		
_ * _	Z.mul		
_ / _	Z.div		
_ mod _	Z.modulo	40	no
	Z.opp		
_ ^ _	Z.pow		

# Example

```
Require Import ZArith.

[Loading ML file newring_plugin.cmxs ... done]

[Loading ML file zify_plugin.cmxs ... done]
```

(continues on next page)

(continued from previous page)

```
[Loading ML file omega_plugin.cmxs ... done] Check (2 + 3)\%Z. (2 + 3)\%Z : Z

Open Scope Z_scope. Check 2 + 3. 2 + 3 : Z
```

# Real numbers library

# Notations for real numbers

This is provided by requiring and opening the module Reals and opening scope R\_scope. This set of notations is very similar to the notation for integer arithmetic. The inverse function was added.

Notation	Interpretation
_ < _	Rlt
_ <= _	Rle
_ > _	Rgt
_ >= _	Rge
x < y < z	x < y /\ y < z
x < y <= z	x < y /\ y <= z
x <= y < z	x <= y /\ y < z
x <= y <= z	x <= y /\ y <= z
_ + _	Rplus
	Rminus
_ * _	Rmult
_ / _	Rdiv
	Ropp
/_	Rinv
_ ^ _	pow

## Example

#### Some tactics for real numbers

In addition to the powerful ring, field and lra tactics (see Chapter Tactics), there are also:

#### discrR

Proves that two real integer constants are different.

#### Example

```
Require Import DiscrR.

Open Scope R_scope.

Goal 5 <> 0.

1 subgoal

-----

5 <> 0
```

discrR.

#### split\_Rabs

Allows unfolding the Rabs constant and splits corresponding conjunctions.

# Example

## split\_Rmult

Splits a condition that a product is non null into subgoals corresponding to the condition on each operand of the product.

# Example

```
Require Import Reals.
Open Scope R_scope.
Goal forall x y z:R, x * y * z <> 0.
1 subgoal
```

(continues on next page)

(continued from previous page)

These tactics has been written with the tactic language  $L_{tac}$  described in Chapter Ltac.

## List library

Some elementary operations on polymorphic lists are defined here. They can be accessed by requiring module List.

It defines the following notions:

- length
- head : first element (with default)
- tail: all but first element
- app : concatenation
- rev : reverse
- nth: accessing n-th element (with default)
- map: applying a function
- flat\_map : applying a function returning lists
- fold\_left: iterator (from head to tail)
- fold\_right : iterator (from tail to head)

The following table shows notations available when opening scope list\_scope.

Notation	Interpretation	Precedence	Associativity
_ ++ _	app	60	right
_ :: _	cons	60	right

## Floats library

The library of primitive floating-point arithmetic can be loaded by requiring module Floats:

Require Import Floats.

It exports the module PrimFloat that provides a primitive type named float, defined in the kernel (see section *Primitive Floats*), as well as two variant types float\_comparison and float\_class:

```
Print float.
    *** [ float : Set ]
Print float_comparison.
    Variant float_comparison : Set :=
        FEq : float_comparison
      | FLt : float_comparison
      | FGt : float_comparison
      | FNotComparable : float_comparison
Print float_class.
    Variant float_class : Set :=
       PNormal : float_class
      | NNormal : float_class
      | PSubn : float_class
      | NSubn : float_class
      | PZero : float_class
      | NZero : float_class
      | PInf : float_class
      | NInf : float_class
      | NaN : float_class
```

It then defines the primitive operators below, using the processor floating-point operators for binary64 in rounding-to-nearest even:

- abs
- opp
- sub
- add
- mul
- div
- sqrt
- compare : compare two floats and return a float\_comparison
- classify: analyze a float and return a float\_class
- of\_int63: round a primitive integer and convert it into a float
- normfr\_mantissa: take a float in [0.5; 1.0) and return its mantissa
- frshiftexp: convert a float to fractional part in [0.5; 1.0) and integer part
- ldshiftexp: multiply a float by an integral power of 2
- next\_up: return the next float towards positive infinity
- next\_down: return the next float towards negative infinity

For special floating-point values, the following constants are also defined:

- zero
- neg\_zero
- one

- two
- infinity
- neg\_infinity
- nan: Not a Number (assumed to be unique: the "payload" of NaNs is ignored)

The following table shows the notations available when opening scope float\_scope.

Notation	Interpretation
	opp
	sub
_ + _	add
_ * _	mul
_ / _	div
_ == _	eqb
_ < _	ltb
_ <= _	leb
_ ?= _	compare

Floating-point constants are parsed and pretty-printed as (17-digit) decimal constants. This ensures that the composition parse  $\circ$  print amounts to the identity.

Warning: The constant numeral is not a binary64 floating-point value. A closest value will be used and Not all decimal constants are floating-point values. This warning is generated when parsing such a constant (for instance 0.1).

## Example

```
Open Scope float_scope.
Eval compute in 1 + 0.5.
    = 1.5
         : float
Eval compute in 1 / 0.
    = infinity
         : float
Eval compute in 1 / -0.
    = neg_infinity
         : float
Eval compute in 0 / 0.
    = nan
         : float
Eval compute in 0 ?= -0.
    = FEq
         : float_comparison
Eval compute in nan ?= nan.
    = FNotComparable
         : float_comparison
Eval compute in next_down (-1).
```

(continues on next page)

(continued from previous page)

The primitive operators are specified with respect to their Gallina counterpart, using the variant type spec\_float, and the injection Prim2SF:

For more details on the available definitions and lemmas, see the online documentation of the Floats library.

#### 4.3.3 Users' contributions

Numerous users' contributions have been collected and are available at URL http://coq.inria.fr/opam/www/. On this web page, you have a list of all contributions with informations (author, institution, quick description, etc.) and the possibility to download them one by one. You will also find informations on how to submit a new contribution.

# 4.4 Calculus of Inductive Constructions

The underlying formal language of Coq is a *Calculus of Inductive Constructions* (Cic) whose inference rules are presented in this chapter. The history of this formalism as well as pointers to related work are provided in a separate chapter; see *Credits*.

#### 4.4.1 The terms

The expressions of the Cic are terms and all terms have a type. There are types for functions (or programs), there are atomic types (especially datatypes)... but also types for proofs and types for the types themselves. Especially, any object handled in the formalism must belong to a type. For instance, universal quantification is relative to a type and takes the form "for all x of type T, P". The expression "x of type T" is written "x:T". Informally, "x:T" can be thought as "x belongs to T".

The types of types are *sorts*. Types and sorts are themselves terms so that terms, types and sorts are all components of a common syntactic language of terms which is described in Section *Terms* but, first, we describe sorts.

#### Sorts

All sorts have a type and there is an infinite well-founded typing hierarchy of sorts whose base sorts are SProp, Prop and Set.

The sort Prop intends to be the type of logical propositions. If M is a logical proposition then it denotes the class of terms representing proofs of M. An object m belonging to M witnesses the fact that M is provable. An object of type Prop is called a proposition.

The sort SProp is like Prop but the propositions in SProp are known to have irrelevant proofs (all proofs are equal). Objects of type SProp are called strict propositions. See SProp (proof irrelevant propositions) for information about using SProp, and [GCST19] for meta theoretical considerations.

The sort Set intends to be the type of small sets. This includes data types such as booleans and naturals, but also products, subsets, and function types over these data types.

SProp, Prop and Set themselves can be manipulated as ordinary terms. Consequently they also have a type. Because assuming simply that Set has type Set leads to an inconsistent theory [Coq86], the language of Cic has infinitely many sorts. There are, in addition to the base sorts, a hierarchy of universes Type(i) for any integer  $i \ge 1$ .

Like Set, all of the sorts  $\mathsf{Type}(i)$  contain small sets such as booleans, natural numbers, as well as products, subsets and function types over small sets. But, unlike Set, they also contain large sets, namely the sorts Set and  $\mathsf{Type}(j)$  for j < i, and all products, subsets and function types over these sorts.

Formally, we call  $\mathcal{S}$  the set of sorts which is defined by:

$$S \equiv \{\mathsf{SProp}, \mathsf{Prop}, \mathsf{Set}, \mathsf{Type}(i) \mid i \in \mathbb{N}\}$$

Their properties, such as:  $\mathsf{Prop} : \mathsf{Type}(1)$ ,  $\mathsf{Set} : \mathsf{Type}(1)$ , and  $\mathsf{Type}(i) : \mathsf{Type}(i+1)$ , are defined in Section Subtyping rules.

The user does not have to mention explicitly the index i when referring to the universe Type(i). One only writes Type. The system itself generates for each instance of Type a new index for the universe and checks that the constraints between these indexes can be solved. From the user point of view we consequently have Type: Type. We shall make precise in the typing rules the constraints between the indices.

Implementation issues In practice, the Type hierarchy is implemented using algebraic universes. An algebraic universe u is either a variable (a qualified identifier with a number) or a successor of an algebraic universe (an expression u+1), or an upper bound of algebraic universes (an expression  $\max(u_1,...,u_n)$ ), or the base universe (the expression 0) which corresponds, in the arity of template polymorphic inductive types (see Section Well-formed inductive definitions), to the predicative sort Set. A graph of constraints between the universe variables is maintained globally. To ensure the existence of a mapping of the universes to the positive integers, the graph of constraints must remain acyclic. Typing expressions that violate the acyclicity of the graph of constraints results in a Universe inconsistency error.

#### See also:

Section Printing universes.

#### Terms

Terms are built from sorts, variables, constants, abstractions, applications, local definitions, and products. From a syntactic point of view, types cannot be distinguished from terms, except that they cannot start by an abstraction or a constructor. More precisely the language of the *Calculus of Inductive Constructions* is built from the following rules.

- 1. the sorts SProp, Prop, Set, Type(i) are terms.
- 2. variables, hereafter ranged over by letters x, y, etc., are terms

- 3. constants, hereafter ranged over by letters c, d, etc., are terms.
- 4. if x is a variable and T, U are terms then  $\forall x:T$ , U (forall x:T, U in Coq concrete syntax) is a term. If x occurs in U,  $\forall x:T$ , U reads as "for all x of type T, U". As U depends on x, one says that  $\forall x:T$ , U is a dependent product. If x does not occur in U then  $\forall x:T$ , U reads as "if T then U". A non dependent product can be written:  $T \to U$ .
- 5. if x is a variable and T, u are terms then  $\lambda x : T$ . u (fun  $x:T \Rightarrow u$  in Coq concrete syntax) is a term. This is a notation for the  $\lambda$ -abstraction of  $\lambda$ -calculus [Bar81]. The term  $\lambda x : T$ . u is a function which maps elements of T to the expression u.
- 6. if t and u are terms then  $(t \ u)$  is a term  $(t \ u)$  in Coq concrete syntax). The term  $(t \ u)$  reads as "t applied to u".
- 7. if x is a variable, and t, T and u are terms then let x := t : T in u is a term which denotes the term u where the variable x is locally bound to t of type T. This stands for the common "let-in" construction of functional programs such as ML or Scheme.

**Free variables.** The notion of free variables is defined as usual. In the expressions  $\lambda x : T$ . U and  $\forall x : T$ , U the occurrences of x in U are bound.

**Substitution.** The notion of substituting a term t to free occurrences of a variable x in a term u is defined as usual. The resulting term is written  $u\{x/t\}$ .

The logical vs programming readings. The constructions of the Cic can be used to express both logical and programming notions, accordingly to the Curry-Howard correspondence between proofs and programs, and between propositions and types [CFC58][How80][dB72].

For instance, let us assume that nat is the type of natural numbers with zero element written 0 and that True is the always true proposition. Then  $\rightarrow$  is used both to denote nat  $\rightarrow$  nat which is the type of functions from nat to nat, to denote True $\rightarrow$ True which is an implicative proposition, to denote nat  $\rightarrow$  Prop which is the type of unary predicates over the natural numbers, etc.

Let us assume that mult is a function of type  $\operatorname{\mathsf{nat}} \to \operatorname{\mathsf{nat}} \to \operatorname{\mathsf{nat}}$  and eqnat a predicate of type  $\operatorname{\mathsf{nat}} \to \operatorname{\mathsf{nat}} \to \operatorname{\mathsf{Prop}}$ . The  $\lambda$ -abstraction can serve to build "ordinary" functions as in  $\lambda x$ :  $\operatorname{\mathsf{nat}}$ . (mult x x) (i.e. fun x:  $\operatorname{\mathsf{nat}} = x$  mult x x in Coq notation) but may build also predicates over the natural numbers. For instance  $\lambda x$ :  $\operatorname{\mathsf{nat}}$ . (eqnat x 0) (i.e. fun x:  $\operatorname{\mathsf{nat}} = x$  eqnat x 0 in Coq notation) will represent the predicate of one variable x which asserts the equality of x with 0. This predicate has type  $\operatorname{\mathsf{nat}} \to \operatorname{\mathsf{Prop}}$  and it can be applied to any expression of type  $\operatorname{\mathsf{nat}}$ , say t, to give an object t of type  $\operatorname{\mathsf{Prop}}$ , namely a proposition.

Furthermore forall x:nat, P x will represent the type of functions which associate to each natural number n an object of type  $(P \ n)$  and consequently represent the type of proofs of the formula " $\forall x. \ P(x)$ ".

# 4.4.2 Typing rules

As objects of type theory, terms are subjected to *type discipline*. The well typing of a term depends on a global environment and a local context.

**Local context.** A local context is an ordered list of local declarations of names which we call variables. The declaration of some variable x is either a local assumption, written x:T (T is a type) or a local definition, written x:=t:T. We use brackets to write local contexts. A typical example is  $[x:T;\ y:=u:U;\ z:V]$ . Notice that the variables declared in a local context must be distinct. If  $\Gamma$  is a local context that declares some x, we write  $x\in\Gamma$ . By writing  $(x:T)\in\Gamma$  we mean that either x:T is an assumption in  $\Gamma$  or that there exists some t such that x:=t:T is a definition in  $\Gamma$ . If  $\Gamma$  defines some x:=t:T, we also write  $(x:=t:T)\in\Gamma$ . For the rest of the chapter,  $\Gamma:(y:T)$  denotes the local context  $\Gamma$  enriched with the local assumption y:T. Similarly,  $\Gamma:(y:=t:T)$  denotes the local context  $\Gamma$  enriched with the local definition (y:=t:T). The notation [] denotes the empty local context. By  $\Gamma_1;\Gamma_2$  we mean concatenation of the local context  $\Gamma_1$  and the local context  $\Gamma_2$ .

**Global environment.** A global environment is an ordered list of global declarations. Global declarations are either global assumptions or global definitions, but also declarations of inductive objects. Inductive objects themselves declare both inductive or coinductive types and constructors (see Section *Inductive Definitions*).

A global assumption will be represented in the global environment as (c:T) which assumes the name c to be of some type T. A global definition will be represented in the global environment as c:=t:T which defines the name c to have value t and type T. We shall call such names constants. For the rest of the chapter, the E; c:T denotes the global environment E enriched with the global assumption c:T. Similarly, E; c:=t:T denotes the global environment E enriched with the global definition (c:=t:T).

The rules for inductive definitions (see Section *Inductive Definitions*) have to be considered as assumption rules to which the following definitions apply: if the name c is declared in E, we write  $c \in E$  and if c : T or c := t : T is declared in E, we write  $(c : T) \in E$ .

**Typing rules.** In the following, we define simultaneously two judgments. The first one  $E[\Gamma] \vdash t : T$  means the term t is well-typed and has type T in the global environment E and local context  $\Gamma$ . The second judgment  $\mathcal{WF}(E)[\Gamma]$  means that the global environment E is well-formed and the local context  $\Gamma$  is a valid local context in this global environment.

A term t is well typed in a global environment E iff there exists a local context  $\Gamma$  and a term T such that the judgment  $E[\Gamma] \vdash t : T$  can be derived from the following rules.

# W-Empty

 $\overline{\mathcal{WF}([])[]}$ 

W-Local-Assum

$$\frac{E[\Gamma] \vdash T: s \qquad s \in \mathcal{S} \qquad x \not \in \Gamma}{\mathcal{WF}(E)[\Gamma :: (x:T)]}$$

W-Local-Def

$$\frac{E[\Gamma] \vdash t : T \qquad x \not\in \Gamma}{\mathcal{WF}(E)[\Gamma :: (x := t : T)]}$$

W-Global-Assum

$$\frac{E[] \vdash T : s \qquad s \in \mathcal{S} \qquad c \not \in E}{\mathcal{WF}(E; \ c : T)[]}$$

W-Global-Def

$$\frac{E[] \vdash t : T \qquad c \not\in E}{\mathcal{WF}(E; \ c := t : T)[]}$$

Ax-SProp

$$\frac{\mathcal{WF}(E)[\Gamma]}{E[\Gamma] \vdash \mathsf{SProp} : \mathsf{Type}(1)}$$

Ax-Prop

$$\frac{\mathcal{WF}(E)[\Gamma]}{E[\Gamma] \vdash \mathsf{Prop} : \mathsf{Type}(1)}$$

Ax-Set

$$\frac{\mathcal{WF}(E)[\Gamma]}{E[\Gamma] \vdash \mathsf{Set} : \mathsf{Type}(1)}$$

Ax-Type

$$\frac{\mathcal{WF}(E)[\Gamma]}{E[\Gamma] \vdash \mathsf{Type}(i) : \mathsf{Type}(i+1)}$$

Var

$$\frac{\mathcal{WF}(E)[\Gamma] \qquad \quad (x:T) \in \Gamma \ \, \text{or} \ \, (x:=t:T) \in \Gamma \, \, \text{for some} \, \, t}{E[\Gamma] \vdash x:T}$$

Const

$$\frac{\mathcal{WF}(E)[\Gamma] \qquad \quad (c:T) \in E \ \, \text{or} \ \, (c:=t:T) \in E \ \, \text{for some} \, \, t}{E[\Gamma] \vdash c:T}$$

**Prod-SProp** 

$$\frac{E[\Gamma] \vdash T : s \qquad s \in \mathcal{S} \qquad E[\Gamma :: (x : T)] \vdash U : \mathsf{SProp}}{E[\Gamma] \vdash \forall \ x : T, U : \mathsf{SProp}}$$

**Prod-Prop** 

$$\frac{E[\Gamma] \vdash T : s \qquad s \in \mathcal{S} \qquad E[\Gamma :: (x : T)] \vdash U : \mathsf{Prop}}{E[\Gamma] \vdash \forall x : T, \ U : \mathsf{Prop}}$$

**Prod-Set** 

$$\frac{E[\Gamma] \vdash T : s \qquad \quad s \in \{\mathsf{SProp}, \mathsf{Prop}, \mathsf{Set}\} \qquad E[\Gamma :: (x : T)] \vdash U : \mathsf{Set}}{E[\Gamma] \vdash \forall x : T, \ U : \mathsf{Set}}$$

Prod-Type

$$\frac{E[\Gamma] \vdash T : s \qquad \quad s \in \{\mathsf{SProp}, \mathsf{Type}i\} \qquad E[\Gamma :: (x : T)] \vdash U : \mathsf{Type}(i)}{E[\Gamma] \vdash \forall x : T, \ U : \mathsf{Type}(i)}$$

Lam

$$\frac{E[\Gamma] \vdash \forall x:T,\ U:s \qquad E[\Gamma::(x:T)] \vdash t:U}{E[\Gamma] \vdash \lambda x:T.\ t: \forall x:T,\ U}$$

App

$$\frac{E[\Gamma] \vdash t : \forall x : U, \ T}{E[\Gamma] \vdash (t \ u) : T\{x/u\}}$$

Let

$$\frac{E[\Gamma] \vdash t : T \qquad E[\Gamma :: (x := t : T)] \vdash u : U}{E[\Gamma] \vdash \text{let } x := t : T \text{ in } u : U\{x/t\}}$$

**Note: Prod-Prop** and **Prod-Set** typing-rules make sense if we consider the semantic difference between Prop and Set:

- All values of a type that has a sort Set are extractable.
- No values of a type that has a sort Prop are extractable.

**Note:** We may have let x := t : T in u well-typed without having  $((\lambda x : T. u) t)$  well-typed (where T is a type of t). This is because the value t associated to x may be used in a conversion rule (see Section Conversion rules).

# 4.4.3 Conversion rules

In Cic, there is an internal reduction mechanism. In particular, it can decide if two programs are *intentionally* equal (one says *convertible*). Convertibility is described in this section.

#### $\beta$ -reduction

We want to be able to identify some terms as we can identify the application of a function to a given argument with its result. For instance the identity function over a given type T can be written  $\lambda x : T$ . x. In any global environment E and local context  $\Gamma$ , we want to identify any object a (of type T) with the application  $((\lambda x : T, x))$  a). We define for this a reduction (or a conversion) rule we call  $\beta$ :

$$E[\Gamma] \vdash ((\lambda x : T. \ t) \ u) \triangleright_{\beta} \ t\{x/u\}$$

We say that  $t\{x/u\}$  is the  $\beta$ -contraction of  $((\lambda x:T.\ t)\ u)$  and, conversely, that  $((\lambda x:T.\ t)\ u)$  is the  $\beta$ -expansion of  $t\{x/u\}$ .

According to  $\beta$ -reduction, terms of the *Calculus of Inductive Constructions* enjoy some fundamental properties such as confluence, strong normalization, subject reduction. These results are theoretically of great importance but we will not detail them here and refer the interested reader to  $\lceil Coq85 \rceil$ .

#### $\iota$ -reduction

A specific conversion rule is associated to the inductive objects in the global environment. We shall give later on (see Section Well-formed inductive definitions) the precise rules but it just says that a destructor applied to an object built from a constructor behaves as expected. This reduction is called  $\iota$ -reduction and is more precisely studied in [PM93a][Wer94].

#### $\delta$ -reduction

We may have variables defined in local contexts or constants defined in the global environment. It is legal to identify such a reference with its value, that is to expand (or unfold) it into its value. This reduction is called  $\delta$ -reduction and shows as follows.

#### Delta-Local

$$\frac{\mathcal{WF}(E)[\Gamma] \qquad (x:=t:T) \in \Gamma}{E[\Gamma] \vdash x \ \triangleright_{\Delta} \ t}$$

#### Delta-Global

$$\frac{\mathcal{WF}(E)[\Gamma] \qquad (c := t : T) \in E}{E[\Gamma] \vdash c \ \triangleright_{\delta} \ t}$$

## $\zeta$ -reduction

Coq allows also to remove local definitions occurring in terms by replacing the defined variable by its value. The declaration being destroyed, this reduction differs from  $\delta$ -reduction. It is called  $\zeta$ -reduction and shows as follows.

#### Zeta

$$\frac{\mathcal{WF}(E)[\Gamma]}{E[\Gamma] \vdash \text{let } x := u : U \text{ in } t \ \triangleright_{\zeta} \ t\{x/u\}}$$

# $\eta$ -expansion

Another important concept is  $\eta$ -expansion. It is legal to identify any term t of functional type  $\forall x:T,\ U$  with its so-called  $\eta$ -expansion

$$\lambda x : T. (t \ x)$$

for x an arbitrary variable name fresh in t.

**Note:** We deliberately do not define  $\eta$ -reduction:

$$\lambda x : T. (t \ x) \not \triangleright_{\eta} t$$

This is because, in general, the type of t need not to be convertible to the type of  $\lambda x : T$ .  $(t \ x)$ . E.g., if we take f such that:

$$f: \forall x: \mathsf{Type}(2), \; \mathsf{Type}(1)$$

then

$$\lambda x : \mathsf{Type}(1). \ (f \ x) \ : \ \forall x : \mathsf{Type}(1), \ \mathsf{Type}(1)$$

We could not allow

$$\lambda x : \mathsf{Type}(1). \ (f \ x) \ \triangleright_n \ f$$

because the type of the reduced term  $\forall x: \mathsf{Type}(2), \; \mathsf{Type}(1)$  would not be convertible to the type of the original term  $\forall x: \mathsf{Type}(1), \; \mathsf{Type}(1).$ 

#### **Proof Irrelevance**

It is legal to identify any two terms whose common type is a strict proposition  $A : \mathsf{SProp}$ . Terms in a strict propositions are therefore called irrelevant.

# Convertibility

Let us write  $E[\Gamma] \vdash t \triangleright u$  for the contextual closure of the relation t reduces to u in the global environment E and local context  $\Gamma$  with one of the previous reductions  $\beta$ ,  $\delta$ ,  $\iota$  or  $\zeta$ .

We say that two terms  $t_1$  and  $t_2$  are  $\beta\delta\iota\zeta\eta$ -convertible, or simply convertible, or equivalent, in the global environment E and local context  $\Gamma$  iff there exist terms  $u_1$  and  $u_2$  such that  $E[\Gamma] \vdash t_1 \triangleright ... \triangleright u_1$  and  $E[\Gamma] \vdash t_2 \triangleright ... \triangleright u_2$  and either  $u_1$  and  $u_2$  are identical up to irrelevant subterms, or they are convertible up to  $\eta$ -expansion, i.e.  $u_1$  is  $\lambda x : T$ .  $u_1'$  and  $u_2 x$  is recursively convertible to  $u_1'$ , or, symmetrically,  $u_2$  is  $\lambda x : T$ .  $u_2'$  and  $u_1 x$  is recursively convertible to  $u_2'$ . We then write  $E[\Gamma] \vdash t_1 = \beta\delta\iota\zeta\eta$   $t_2$ .

Apart from this we consider two instances of polymorphic and cumulative (see Chapter *Polymorphic Universes*) inductive types (see below) convertible

$$E[\Gamma] \vdash t \ w_1...w_m =_{\beta\delta\iota\zeta\eta} t \ w_1'...w_m'$$

if we have subtypings (see below) in both directions, i.e.,

$$E[\Gamma] \vdash t \ w_1...w_m \leq_{\beta\delta\iota,\zeta_n} t \ w'_1...w'_m$$

and

$$E[\Gamma] \vdash t \ w_1'...w_m' \leq_{\beta\delta\iota\zeta\eta} t \ w_1...w_m.$$

Furthermore, we consider

$$E[\Gamma] \vdash c \ v_1...v_m =_{\beta\delta\iota\zeta\eta} c' \ v_1'...v_m'$$

convertible if

$$E[\Gamma] \vdash v_i =_{\beta \delta \iota \zeta \eta} v_i'$$

and we have that c and c' are the same constructors of different instances of the same inductive types (differing only in universe levels) such that

$$E[\Gamma] \vdash c \ v_1...v_m : t \ w_1...w_m$$

and

$$E[\Gamma] \vdash c' \ v'_1...v'_m : t' \ w'_1...w'_m$$

and we have

$$E[\Gamma] \vdash t \ w_1...w_m =_{\beta\delta\iota\zeta\eta} t \ w_1'...w_m'.$$

The convertibility relation allows introducing a new typing rule which says that two convertible well-formed types have the same inhabitants.

# 4.4.4 Subtyping rules

At the moment, we did not take into account one rule between universes which says that any term in a universe of index i is also a term in the universe of index i + 1 (this is the *cumulativity* rule of Cic). This property extends the equivalence relation of convertibility into a *subtyping* relation inductively defined by:

1. if 
$$E[\Gamma] \vdash t =_{\beta \delta \iota \zeta \eta} u$$
 then  $E[\Gamma] \vdash t \leq_{\beta \delta \iota \zeta \eta} u$ ,

2. if 
$$i \leq j$$
 then  $E[\Gamma] \vdash \mathsf{Type}(i) \leq_{\beta \delta \iota \zeta n} \mathsf{Type}(j)$ ,

- 3. for any i,  $E[\Gamma] \vdash \mathsf{Set} \leq_{\beta\delta\iota\zeta\eta} \mathsf{Type}(i)$ ,
- 4.  $E[\Gamma] \vdash \mathsf{Prop} \leq_{\beta\delta\iota\zeta\eta} \mathsf{Set}$ , hence, by transitivity,  $E[\Gamma] \vdash \mathsf{Prop} \leq_{\beta\delta\iota\zeta\eta} \mathsf{Type}(i)$ , for any i (note:  $\mathsf{SProp}$  is not related by cumulativity to any other term)
- 5. if  $E[\Gamma] \vdash T = \beta \delta \iota \zeta_n U$  and  $E[\Gamma :: (x : T)] \vdash T' \leq \beta \delta \iota \zeta_n U'$  then  $E[\Gamma] \vdash \forall x : T, T' \leq \beta \delta \iota \zeta_n \forall x : U, U'$ .
- 6. if Ind [p] ( $\Gamma_I := \Gamma_C$ ) is a universe polymorphic and cumulative (see Chapter *Polymorphic Universes*) inductive type (see below) and  $(t : \forall \Gamma_P, \forall \Gamma_{Arr(t)}, S) \in \Gamma_I$  and  $(t' : \forall \Gamma_P', \forall \Gamma_{Arr(t)}', S') \in \Gamma_I$  are two different instances of *the same* inductive type (differing only in universe levels) with constructors

$$[c_1:\forall \Gamma_P, \forall T_{1,1}...T_{1,n_1},\ t\ v_{1,1}...v_{1,m};\ ...;\ c_k:\forall \Gamma_P, \forall T_{k,1}...T_{k,n_k},\ t\ v_{k,1}...v_{k,m}]$$

and

$$[c_1:\forall \Gamma_P', \forall T_{1,1}'...T_{1,n_1}', \ t'\ v_{1,1}'...v_{1,m}'; \ ...; \ c_k:\forall \Gamma_P', \forall T_{k,1}'...T_{k,n_k}', \ t'\ v_{k,1}'...v_{k,m}']$$

respectively then

$$E[\Gamma] \vdash t \ w_1...w_m \leq_{\beta\delta\iota\zeta\eta} t' \ w_1'...w_m'$$

(notice that t and t' are both fully applied, i.e., they have a sort as a type) if

$$E[\Gamma] \vdash w_i =_{\beta \delta \iota \zeta \eta} w_i'$$

for  $1 \le i \le m$  and we have

$$E[\Gamma] \vdash T_{i,j} \leq_{\beta\delta\iota\zeta\eta} T'_{i,j}$$

and

$$E[\Gamma] \vdash A_i \leq_{\beta \delta \iota \zeta n} A_i'$$

where 
$$\Gamma_{Arr(t)} = [a_1 : A_1; ...; a_l : A_l]$$
 and  $\Gamma'_{Arr(t)} = [a_1 : A'_1; ...; a_l : A'_l]$ .

The conversion rule up to subtyping is now exactly:

Conv

$$\frac{E[\Gamma] \vdash U : s}{E[\Gamma] \vdash t : T} \qquad E[\Gamma] \vdash T \leq_{\beta \delta \iota \zeta \eta} U$$

Normal form. A term which cannot be any more reduced is said to be in *normal form*. There are several ways (or strategies) to apply the reduction rules. Among them, we have to mention the *head reduction* which will play an important role (see Chapter Tactics). Any term t can be written as  $\lambda x_1 : T_1 .... \lambda x_k : T_k ... (t_0 t_1...t_n)$  where  $t_0$  is not an application. We say then that  $t_0$  is the *head of t*. If we assume that  $t_0$  is  $\lambda x : T$ .  $u_0$  then one step of  $\beta$ -head reduction of t is:

$$\lambda x_1 : T_1 ... \lambda x_k : T_k . (\lambda x : T_1 ... t_n) > \lambda (x_1 : T_1) ... (x_k : T_k) . (u_0 \{x/t_1\} t_2 ... t_n)$$

Iterating the process of head reduction until the head of the reduced term is no more an abstraction leads to the  $\beta$ -head normal form of t:

$$t \triangleright ... \triangleright \lambda x_1 : T_1....\lambda x_k : T_k. \ (v \ u_1...u_m)$$

where v is not an abstraction (nor an application). Note that the head normal form must not be confused with the normal form since some  $u_i$  can be reducible. Similar notions of head-normal forms involving  $\delta$ ,  $\iota$  and  $\zeta$  reductions or any combination of those can also be defined.

# 4.4.5 Inductive Definitions

Formally, we can represent any inductive definition as Ind  $[p](\Gamma_I := \Gamma_C)$  where:

- $\Gamma_I$  determines the names and types of inductive types;
- $\Gamma_C$  determines the names and types of constructors of these inductive types;
- p determines the number of parameters of these inductive types.

These inductive definitions, together with global assumptions and global definitions, then form the global environment. Additionally, for any p there always exists  $\Gamma_P = [a_1:A_1; ...; a_p:A_p]$  such that each T in  $(t:T) \in \Gamma_I \cup \Gamma_C$  can be written as:  $\forall \Gamma_P, T'$  where  $\Gamma_P$  is called the *context of parameters*. Furthermore, we must have that each T in  $(t:T) \in \Gamma_I$  can be written as:  $\forall \Gamma_P, \forall \Gamma_{Arr(t)}, S$  where  $\Gamma_{Arr(t)}$  is called the *Arity* of the inductive type t and S is called the sort of the inductive type t (not to be confused with S which is the set of sorts).

## Example

The declaration for parameterized lists is:

$$\mathsf{Ind}\ [1] \left( [\mathsf{list} : \mathsf{Set} \to \mathsf{Set}] \ := \ \left[ \begin{array}{ccc} \mathsf{nil} & : & \forall A : \mathsf{Set}, \ \mathsf{list}\ A \\ \mathsf{cons} & : & \forall A : \mathsf{Set}, \ A \to \mathsf{list}\ A \to \mathsf{list}\ A \end{array} \right] \right)$$

which corresponds to the result of the Coq declaration:

```
Inductive list (A:Set) : Set :=
| nil : list A
| cons : A -> list A -> list A.
```

#### Example

The declaration for a mutual inductive definition of tree and forest is:

```
\mathsf{Ind}\; [0] \left( \left[ \begin{array}{ccc} \mathsf{tree} & : & \mathsf{Set} \\ \mathsf{forest} & : & \mathsf{Set} \end{array} \right] \; := \; \left[ \begin{array}{ccc} \mathsf{node} \; : \; \mathsf{forest} \to \mathsf{tree} \\ \mathsf{emptyf} \; : \; \mathsf{forest} \\ \mathsf{consf} \; : \; \mathsf{tree} \to \mathsf{forest} \to \mathsf{forest} \end{array} \right] \right)
```

which corresponds to the result of the Coq declaration:

```
Inductive tree : Set :=
| node : forest -> tree
with forest : Set :=
| emptyf : forest
| consf : tree -> forest -> forest.
```

#### Example

The declaration for a mutual inductive definition of even and odd is:

$$\mathsf{Ind}\; [0] \left( \left[ \begin{array}{ccc} \mathsf{even} & : & \mathsf{nat} \to \mathsf{Prop} \\ \mathsf{odd} & : & \mathsf{nat} \to \mathsf{Prop} \end{array} \right] \; := \; \left[ \begin{array}{ccc} \mathsf{even}_\mathsf{O} & : & \mathsf{even}\; 0 \\ \mathsf{even}_\mathsf{S} & : & \forall n, \; \mathsf{odd} \; n \to \mathsf{even} \; (\mathsf{S} \; n) \\ \mathsf{odd}_\mathsf{S} & : & \forall n, \; \mathsf{even} \; n \to \mathsf{odd} \; (\mathsf{S} \; n) \end{array} \right] \right)$$

which corresponds to the result of the Coq declaration:

```
Inductive even : nat -> Prop :=
| even_0 : even 0
| even_S : forall n, odd n -> even (S n)
with odd : nat -> Prop :=
| odd_S : forall n, even n -> odd (S n).
```

#### Types of inductive objects

We have to give the type of constants in a global environment E which contains an inductive definition.

#### Ind

$$\frac{\mathcal{WF}(E)[\Gamma] \qquad \quad \operatorname{Ind} \ [p] \, (\Gamma_I \ := \ \Gamma_C) \in E \qquad \quad (a:A) \in \Gamma_I}{E[\Gamma] \vdash a:A}$$

Constr

$$\frac{\mathcal{WF}(E)[\Gamma] \qquad \quad \ln d \ [p] \ (\Gamma_I \ := \ \Gamma_C) \in E \qquad \quad (c:C) \in \Gamma_C}{E[\Gamma] \vdash c:C}$$

## Example

Provided that our environment E contains inductive definitions we showed before, these two inference rules above enable us to conclude that:

```
\begin{split} E[\Gamma] \vdash \mathsf{even} : \mathsf{nat} \to \mathsf{Prop} \\ E[\Gamma] \vdash \mathsf{odd} : \mathsf{nat} \to \mathsf{Prop} \\ E[\Gamma] \vdash \mathsf{even}_\mathsf{O} : \mathsf{even} \ \mathsf{O} \\ E[\Gamma] \vdash \mathsf{even}_\mathsf{S} : \forall n : \mathsf{nat}, \ \mathsf{odd} \ n \to \mathsf{even} \ (\mathsf{S} \ n) \\ E[\Gamma] \vdash \mathsf{odd}_\mathsf{S} : \forall n : \mathsf{nat}, \ \mathsf{even} \ n \to \mathsf{odd} \ (\mathsf{S} \ n) \end{split}
```

#### Well-formed inductive definitions

We cannot accept any inductive definition because some of them lead to inconsistent systems. We restrict ourselves to definitions which satisfy a syntactic criterion of positivity. Before giving the formal rules, we need a few definitions:

## Arity of a given sort

A type T is an arity of sort s if it converts to the sort s or to a product  $\forall x:T,U$  with U an arity of sort s.

#### Example

 $A \to \mathsf{Set}$  is an arity of sort  $\mathsf{Set}$ .  $\forall A : \mathsf{Prop}$ ,  $A \to \mathsf{Prop}$  is an arity of sort  $\mathsf{Prop}$ .

## **Arity**

A type T is an arity if there is a  $s \in \mathcal{S}$  such that T is an arity of sort s.

## Example

 $A \to \mathsf{Set} \ \mathrm{and} \ \forall A : \mathsf{Prop}, \ A \to \mathsf{Prop} \ \mathrm{are} \ \mathrm{arities}.$ 

## Type of constructor

We say that T is a type of constructor of I in one of the following two cases:

- T is  $(I \ t_1...t_n)$
- T is  $\forall x: U, T'$  where T' is also a type of constructor of I

## Example

nat and nat  $\to$  nat are types of constructor of nat.  $\forall A : \mathsf{Type}$ , list A and  $\forall A : \mathsf{Type}$ ,  $A \to \mathsf{list}\ A \to \mathsf{list}\ A$  are types of constructor of list.

# **Positivity Condition**

The type of constructor T will be said to satisfy the positivity condition for a constant X in the following cases:

- $T = (X \ t_1...t_n)$  and X does not occur free in any  $t_i$
- $T = \forall x : U, V \text{ and } X \text{ occurs only strictly positively in } U \text{ and the type } V \text{ satisfies the positivity condition for } X.$

#### Strict positivity

The constant X occurs strictly positively in T in the following cases:

- X does not occur in T
- T converts to  $(X \ t_1...t_n)$  and X does not occur in any of  $t_i$
- T converts to  $\forall x: U, V$  and X does not occur in type U but occurs strictly positively in type V
- T converts to  $(I \ a_1...a_m \ t_1...t_n)$  where I is the name of an inductive definition of the form

$$\mathsf{Ind}\,\,[m]\,(I:A\,:=\,\,c_1:\forall p_1:P_1,...\forall p_m:P_m,\,\,C_1;\,\,...;\,\,c_n:\forall p_1:P_1,...\forall p_m:P_m,\,\,C_n)$$

(in particular, it is not mutually defined and it has m parameters) and X does not occur in any of the  $t_i$ , and the (instantiated) types of constructor  $C_i\{p_j/a_j\}_{j=1...m}$  of I satisfy the nested positivity condition for X

#### **Nested Positivity**

The type of constructor T of I satisfies the nested positivity condition for a constant X in the following cases:

- $T = (I \ b_1 ... b_m \ u_1 ... u_n), I$  is an inductive type with m parameters and X does not occur in any  $u_i$
- $T = \forall x : U$ , V and X occurs only strictly positively in U and the type V satisfies the nested positivity condition for X

#### Example

For instance, if one considers the following variant of a tree type branching over the natural numbers:

```
Inductive nattree (A:Type) : Type :=
| leaf : nattree A
| natnode : A -> (nat -> nattree A) -> nattree A.
```

Then every instantiated constructor of nattree A satisfies the nested positivity condition for nattree:

- Type nattree A of constructor leaf satisfies the positivity condition for nattree because nattree does not appear in any (real) arguments of the type of that constructor (primarily because nattree does not have any (real) arguments) ... (bullet 1)
- Type A → (nat → nattree A) → nattree A of constructor natnode satisfies the positivity condition for nattree because:
  - nattree occurs only strictly positively in A ... (bullet 1)
  - nattree occurs only strictly positively in nat  $\rightarrow$  nattree A ... (bullet 3+2)
  - nattree satisfies the positivity condition for nattree A ... (bullet 1)

#### Correctness rules

We shall now describe the rules allowing the introduction of a new inductive definition.

Let E be a global environment and  $\Gamma_P$ ,  $\Gamma_I$ ,  $\Gamma_C$  be contexts such that  $\Gamma_I$  is  $[I_1:\forall \Gamma_P,A_1; ...; I_k:\forall \Gamma_P,A_k]$ , and  $\Gamma_C$  is  $[c_1:\forall \Gamma_P,C_1; ...; c_n:\forall \Gamma_P,C_n]$ . Then

## W-Ind

$$\frac{\mathcal{WF}(E)[\Gamma_P] \qquad (E[\Gamma_I;\Gamma_P] \vdash C_i : s_{q_i})_{i=1\dots n}}{\mathcal{WF}(E; \ \text{Ind} \ [p] \ (\Gamma_I \ := \ \Gamma_C))[]}$$

provided that the following side conditions hold:

- k > 0 and all of  $I_i$  and  $c_i$  are distinct names for j = 1...k and i = 1...n,
- p is the number of parameters of  $\operatorname{Ind}[p](\Gamma_I := \Gamma_C)$  and  $\Gamma_P$  is the context of parameters,
- for j = 1...k we have that  $A_j$  is an arity of sort  $s_j$  and  $I_j \notin E$ ,
- for i = 1...n we have that  $C_i$  is a type of constructor of  $I_{q_i}$  which satisfies the positivity condition for  $I_1...I_k$  and  $c_i \notin E$ .

One can remark that there is a constraint between the sort of the arity of the inductive type and the sort of the type of its constructors which will always be satisfied for the impredicative sorts SProp and Prop but may fail to define inductive type on sort Set and generate constraints between universes for inductive types in the Type hierarchy.

#### Example

It is well known that the existential quantifier can be encoded as an inductive definition. The following declaration introduces the second-order existential quantifier  $\exists X.P(X)$ .

```
Inductive exProp (P:Prop->Prop) : Prop :=
| exP_intro : forall X:Prop, P X -> exProp P.

The same definition on Set is not allowed and fails:

Fail Inductive exSet (P:Set->Prop) : Set :=
exS_intro : forall X:Set, P X -> exSet P.
   The command has indeed failed with message:
   Large non-propositional inductive types must be in Type.
```

It is possible to declare the same inductive definition in the universe Type. The exType inductive definition has type  $(\mathsf{Type}(i) \to \mathsf{Prop}) \to \mathsf{Type}(j)$  with the constraint that the parameter X of  $\mathsf{exT}_{\mathsf{intro}}$  has type  $\mathsf{Type}(k)$  with k < j and  $k \le i$ .

```
Inductive exType (P:Type->Prop) : Type :=
exT_intro : forall X:Type, P X -> exType P.
    exType is defined
    exType_rect is defined
    exType_ind is defined
    exType_rec is defined
    exType_sind is defined
```

#### Example: Negative occurrence (first example)

The following inductive definition is rejected because it does not satisfy the positivity condition:

```
Fail Inductive I : Prop := not_I_I (not_I : I -> False) : I.
The command has indeed failed with message:
   Non strictly positive occurrence of "I" in "(I -> False) -> I".
```

If we were to accept such definition, we could derive a contradiction from it (we can test this by disabling the *Positivity Checking* flag):

```
Definition I_not_I : I -> ~ I := fun i =>
   match i with not_I_I not_I => not_I end.
        I_not_I is defined

Lemma contradiction : False.
Proof.
enough (I /\ ~ I) as [] by contradiction.
split.
- apply not_I_I.
intro.
now apply I_not_I.
- intro.
now apply I_not_I.
Qed.
```

Example: Negative occurrence (second example)

Here is another example of an inductive definition which is rejected because it does not satisfy the positivity condition:

```
Fail Inductive Lam := lam (_ : Lam -> Lam).
   The command has indeed failed with message:
    Non strictly positive occurrence of "Lam" in "(Lam -> Lam) -> Lam".
```

Again, if we were to accept it, we could derive a contradiction (this time through a non-terminating recursive function):

## Example: Non strictly positive occurrence

It is less obvious why inductive type definitions with occurrences that are positive but not strictly positive are harmful. We will see that in presence of an impredicative type they are unsound:

```
Fail Inductive A: Type := introA: ((A \rightarrow Prop) \rightarrow Prop) \rightarrow A.

The command has indeed failed with message:

Non strictly positive occurrence of "A" in "((A \rightarrow Prop) \rightarrow Prop) \rightarrow A".
```

If we were to accept this definition we could derive a contradiction by creating an injective function from  $A \to \mathsf{Prop}$  to A.

This function is defined by composing the injective constructor of the type A with the function  $\lambda x.\lambda z.z=x$  injecting any type T into  $T\to \mathsf{Prop}$ .

```
Definition f (x: A -> Prop): A := introA (fun z => z = x).
    f is defined

Lemma f_inj: forall x y, f x = f y -> x = y.
Proof.
unfold f; intros ? ? H; injection H.
set (F := fun z => z = y); intro HF.
symmetry; replace (y = x) with (F y).
+ unfold F; reflexivity.
+ rewrite <- HF; reflexivity.
Qed.</pre>
```

The type  $A \to \mathsf{Prop}$  can be understood as the powerset of the type A. To derive a contradiction from the injective function f we use Cantor's classic diagonal argument.

```
Definition d: A -> Prop := fun x => exists s, x = f s /\ ~s x.
    d is defined

Definition fd: A := f d.
    fd is defined
```

```
Lemma cantor: (d fd) <-> ~(d fd).
Proof.
split.
+ intros [s [H1 H2]]; unfold fd in H1.
replace d with s.
* assumption.
* apply f_inj; congruence.
+ intro; exists d; tauto.
Qed.
Lemma bad: False.
Proof.
pose cantor; tauto.
Qed.
```

This derivation was first presented by Thierry Coquand and Christine Paulin in [CP90].

#### Template polymorphism

Inductive types can be made polymorphic over the universes introduced by their parameters in Type, if the minimal inferred sort of the inductive declarations either mention some of those parameter universes or is computed to be Prop or Set.

If A is an arity of some sort and s is a sort, we write  $A_{/s}$  for the arity obtained from A by replacing its sort with s. Especially, if A is well-typed in some global environment and local context, then  $A_{/s}$  is typable by typability of all products in the Calculus of Inductive Constructions. The following typing rule is added to the theory.

Let  $\operatorname{Ind}\left[p\right]\left(\Gamma_{I}:=\Gamma_{C}\right)$  be an inductive definition. Let  $\Gamma_{P}=\left[p_{1}:P_{1};\ldots;p_{p}:P_{p}\right]$  be its context of parameters,  $\Gamma_{I}=\left[I_{1}:\forall\Gamma_{P},A_{1};\ldots;I_{k}:\forall\Gamma_{P},A_{k}\right]$  its context of definitions and  $\Gamma_{C}=\left[c_{1}:\forall\Gamma_{P},C_{1};\ldots;c_{n}:\forall\Gamma_{P},C_{n}\right]$  its context of constructors, with  $c_{i}$  a constructor of  $I_{q_{i}}$ . Let  $m\leq p$  be the length of the longest prefix of parameters such that the m first arguments of all occurrences of all  $I_{j}$  in all  $C_{k}$  (even the occurrences in the hypotheses of  $C_{k}$ ) are exactly applied to  $p_{1}...p_{m}$  (m is the number of recursively uniform parameters and the p-m remaining parameters are the recursively non-uniform parameters). Let  $q_{1},...,q_{r}$ , with  $0\leq r\leq m$ , be a (possibly) partial instantiation of the recursively uniform parameters of  $\Gamma_{P}$ . We have:

## **Ind-Family**

$$\begin{cases} & \text{Ind } [p] \, (\Gamma_I \, := \, \Gamma_C) \in E \\ & (E[] \vdash q_l : P_l')_{l=1...r} \\ & (E[] \vdash P_l' \leq_{\beta\delta\iota\zeta\eta} P_l \{p_u/q_u\}_{u=1...l-1})_{l=1...r} \\ & 1 \leq j \leq k \end{cases}$$
 
$$E[] \vdash I_j \, q_1...q_r : \forall [p_{r+1} : P_{r+1}; \, ...; \, p_p : P_p], (A_j)_{/s_j}$$

provided that the following side conditions hold:

- $\Gamma_{P'}$  is the context obtained from  $\Gamma_P$  by replacing each  $P_l$  that is an arity with  $P'_l$  for  $1 \le l \le r$  (notice that  $P_l$  arity implies  $P'_l$  arity since  $E[] \vdash P'_l \le_{\beta\delta\iota\zeta\eta} P_l\{p_u/q_u\}_{u=1...l-1}\};$
- there are sorts  $s_i$ , for  $1 \leq i \leq k$  such that, for  $\Gamma_{I'} = [I_1 : \forall \Gamma_{P'}, (A_1)_{/s_1}; \dots; I_k : \forall \Gamma_{P'}, (A_k)_{/s_k}]$  we have  $(E[\Gamma_{I'}; \Gamma_{P'}] \vdash C_i : s_{q_i})_{i=1...n}$ ;
- the sorts  $s_i$  are all introduced by the inductive declaration and have no universe constraints beside being greater than or equal to Prop, and such that all eliminations, to Prop, Set and Type(j), are allowed (see Section *Destructors*).

Notice that if  $I_j$   $q_1...q_r$  is typable using the rules **Ind-Const** and **App**, then it is typable using the rule **Ind-Family**. Conversely, the extended theory is not stronger than the theory without **Ind-Family**. We get an equiconsistency result by mapping each Ind [p] ( $\Gamma_I := \Gamma_C$ ) occurring into a given derivation into as many different inductive types and constructors as the number of different (partial) replacements of sorts, needed for this derivation, in the parameters that are arities (this is possible because Ind [p] ( $\Gamma_I := \Gamma_C$ ) well-formed implies that Ind [p] ( $\Gamma_{I'} := \Gamma_{C'}$ ) is well-formed and has the same allowed eliminations, where  $\Gamma_{I'}$  is defined as above and  $\Gamma_{C'} = [c_1 : \forall \Gamma_{P'}, C_1; ...; c_n : \forall \Gamma_{P'}, C_n]$ ). That is, the changes in the types of each partial instance  $q_1...q_r$  can be characterized by the ordered sets of arity sorts among the types of parameters, and to each signature is associated a new inductive definition with fresh names. Conversion is preserved as any (partial) instance  $I_j$   $q_1...q_r$  or  $C_i$   $q_1...q_r$  is mapped to the names chosen in the specific instance of Ind [p] ( $\Gamma_I := \Gamma_C$ ).

Warning: The restriction that sorts are introduced by the inductive declaration prevents inductive types declared in sections to be template-polymorphic on universes introduced previously in the section: they cannot parameterize over the universes introduced with section variables that become parameters at section closing time, as these may be shared with other definitions from the same section which can impose constraints on them.

#### Flag: Auto Template Polymorphism

This flag, enabled by default, makes every inductive type declared at level Type (without annotations or hiding it behind a definition) template polymorphic if possible.

This can be prevented using the universes (notemplate) attribute.

## Warning: Automatically declaring ident as template polymorphic.

Warning auto-template can be used to find which types are implicitly declared template polymorphic by Auto Template Polymorphism.

An inductive type can be forced to be template polymorphic using the universes(template) attribute: it should then fulfill the criterion to be template polymorphic or an error is raised.

## Error: Inductive ident cannot be made template polymorphic.

This error is raised when the #[universes(template)] attribute is on but the inductive cannot be made polymorphic on any universe or be inferred to live in Prop or Set.

Template polymorphism and universe polymorphism (see Chapter *Polymorphic Universes*) are incompatible, so if the later is enabled it will prevail over automatic template polymorphism and cause an error when using the universes(template) attribute.

#### Flag: Template Check

This flag is on by default. Turning it off disables the check of locality of the sorts when abstracting the inductive over its parameters. This is a deprecated and *unsafe* flag that can introduce inconsistencies, it is only meant to help users incrementally update code from Coq versions < 8.10 which did not implement this check. The Coq89.v compatibility file sets this flag globally. A global -no-template-check command line option is also available. Use at your own risk. Use of this flag is recorded in the typing flags associated to a definition but is *not* supported by the Coq checker (coqchk). It will appear in Print Assumptions and About @ident output involving inductive declarations that were (potentially unsoundly) assumed to be template polymorphic.

In practice, the rule **Ind-Family** is used by Coq only when all the inductive types of the inductive definition are declared with an arity whose sort is in the Type hierarchy. Then, the polymorphism is over the parameters whose type is an arity of sort in the Type hierarchy. The sorts  $s_j$  are chosen canonically so that each  $s_j$  is minimal with respect to the hierarchy  $\mathsf{Prop} \subset \mathsf{Set}_p \subset \mathsf{Type}$  where  $\mathsf{Set}_p$  is predicative  $\mathsf{Set}$ . More precisely, an empty or small singleton inductive definition (i.e. an inductive definition of which all inductive types are singleton – see Section  $\mathsf{Destructors}$ ) is set in  $\mathsf{Prop}$ , a small non-singleton inductive type is set in  $\mathsf{Set}$  (even in

case Set is impredicative – see Section *The-Calculus-of-Inductive-Construction-with-impredicative-Set*), and otherwise in the Type hierarchy.

Note that the side-condition about allowed elimination sorts in the rule **Ind-Family** avoids to recompute the allowed elimination sorts at each instance of a pattern matching (see Section *Destructors*). As an example, let us consider the following definition:

## Example

```
Inductive option (A:Type) : Type :=
| None : option A
| Some : A -> option A.
```

As the definition is set in the Type hierarchy, it is used polymorphically over its parameters whose types are arities of a sort in the Type hierarchy. Here, the parameter A has this property, hence, if option is applied to a type in Set, the result is in Set. Note that if option is applied to a type in Prop, then, the result is not set in Prop but in Set still. This is because option is not a singleton type (see Section *Destructors*) and it would lose the elimination to Set and Type if set in Prop.

#### Example

Here is another example.

## Example

```
Inductive prod (A B:Type) : Type := pair : A -> B -> prod A B.
```

As prod is a singleton type, it will be in Prop if applied twice to propositions, in Set if applied twice to at least one type in Set and none in Type, and in Type otherwise. In all cases, the three kind of eliminations schemes are allowed.

#### Example

(continues on next page)

(continued from previous page)

```
: Prop -> Set -> Set

Check (fun (A:Type) (B:Prop) => prod A B).

fun (A: Type) (B: Prop) => prod A B

: Type -> Prop -> Type
```

**Note:** Template polymorphism used to be called "sort-polymorphism of inductive types" before universe polymorphism (see Chapter *Polymorphic Universes*) was introduced.

#### **Destructors**

The specification of inductive definitions with arities and constructors is quite natural. But we still have to say how to use an object in an inductive type.

This problem is rather delicate. There are actually several different ways to do that. Some of them are logically equivalent but not always equivalent from the computational point of view or from the user point of view.

From the computational point of view, we want to be able to define a function whose domain is an inductively defined type by using a combination of case analysis over the possible constructors of the object and recursion.

Because we need to keep a consistent theory and also we prefer to keep a strongly normalizing reduction, we cannot accept any sort of recursion (even terminating). So the basic idea is to restrict ourselves to primitive recursive functions and functionals.

For instance, assuming a parameter A: Set exists in the local context, we want to build a function length of type list  $A \to \mathsf{nat}$  which computes the length of the list, such that (length ( $\mathsf{nil}\ A$ )) = O and (length ( $\mathsf{cons}\ A\ a\ l$ )) = (S (length l)). We want these equalities to be recognized implicitly and taken into account in the conversion rule.

From the logical point of view, we have built a type family by giving a set of constructors. We want to capture the fact that we do not have any other way to build an object in this type. So when trying to prove a property about an object m in an inductive type it is enough to enumerate all the cases where m starts with a different constructor.

In case the inductive definition is effectively a recursive one, we want to capture the extra property that we have built the smallest fixed point of this recursive equation. This says that we are only manipulating finite objects. This analysis provides induction principles. For instance, in order to prove  $\forall l: \mathsf{list}\ A, \ (\mathsf{has\_length}\ A\ l\ (\mathsf{length}\ l))$  it is enough to prove:

- (has length A (nil A) (length (nil A)))
- $\forall a: A, \forall l: \mathsf{list}\ A, \ (\mathsf{has}\ \mathsf{length}\ A\ l\ (\mathsf{length}\ l)) \to (\mathsf{has}\ \mathsf{length}\ A\ (\mathsf{cons}\ A\ a\ l)\ (\mathsf{length}\ (\mathsf{cons}\ A\ a\ l)))$

which given the conversion equalities satisfied by length is the same as proving:

- (has length A (nil A) O)
- $\forall a: A, \forall l: \mathsf{list}\ A, \ (\mathsf{has}\ \mathsf{length}\ A\ l\ (\mathsf{length}\ l)) \to (\mathsf{has}\ \mathsf{length}\ A\ (\mathsf{cons}\ A\ a\ l)\ (\mathsf{S}\ (\mathsf{length}\ l)))$

One conceptually simple way to do that, following the basic scheme proposed by Martin-Löf in his Intuitionistic Type Theory, is to introduce for each inductive definition an elimination operator. At the logical level it is a proof of the usual induction principle and at the computational level it implements a generic operator for doing primitive recursion over the structure. But this operator is rather tedious to implement and use. We choose in this version of Coq to factorize the operator for primitive recursion into two more primitive operations as was first suggested by Th. Coquand in [Coq92]. One is the definition by pattern matching. The second one is a definition by guarded fixpoints.

#### The match ... with ... end construction

The basic idea of this operator is that we have an object m in an inductive type I and we want to prove a property which possibly depends on m. For this, it is enough to prove the property for  $m = (c_i \ u_1...u_{p_i})$  for each constructor of I. The Coq term for this proof will be written:

match 
$$m$$
 with  $(c_1 \ x_{11}...x_{1p_1}) \Rightarrow f_1|...|(c_n \ x_{n1}...x_{np_n}) \Rightarrow f_n$  end

In this expression, if m eventually happens to evaluate to  $(c_i \ u_1...u_{p_i})$  then the expression will behave as specified in its i-th branch and it will reduce to  $f_i$  where the  $x_{i1}...x_{ip_i}$  are replaced by the  $u_1...u_{p_i}$  according to the  $\iota$ -reduction.

Actually, for type checking a match...with...end expression we also need to know the predicate P to be proved by case analysis. In the general case where I is an inductively defined n-ary relation, P is a predicate over n+1 arguments: the n first ones correspond to the arguments of I (parameters excluded), and the last one corresponds to object m. Coq can sometimes infer this predicate but sometimes not. The concrete syntax for describing this predicate uses the as...in...return construction. For instance, let us assume that I is an unary predicate with one parameter and one argument. The predicate is made explicit using the syntax:

$$\text{match } m \text{ as } x \text{ in } I \ \_ \ a \text{ return } P \text{ with } (c_1 \ x_{11}...x_{1p_1}) \Rightarrow f_1|...|(c_n \ x_{n1}...x_{np_n}) \Rightarrow f_n \text{ end}$$

The as part can be omitted if either the result type does not depend on m (non-dependent elimination) or m is a variable (in this case, m can occur in P where it is considered a bound variable). The in part can be omitted if the result type does not depend on the arguments of I. Note that the arguments of I corresponding to parameters must be \_\_, because the result type is not generalized to all possible values of the parameters. The other arguments of I (sometimes called indices in the literature) have to be variables (a above) and these variables can occur in P. The expression after in must be seen as an inductive type pattern. Notice that expansion of implicit arguments and notations apply to this pattern. For the purpose of presenting the inference rules, we use a more compact notation:

$$case(m, (\lambda ax.P), \lambda x_{11}...x_{1p_1}.f_1 \mid ... \mid \lambda x_{n1}...x_{np_n}.f_n)$$

Allowed elimination sorts. An important question for building the typing rule for match is what can be the type of  $\lambda ax.P$  with respect to the type of m. If m:I and I:A and  $\lambda ax.P:B$  then by [I:A|B] we mean that one can use  $\lambda ax.P$  with m in the above match-construct.

**Notations.** The [I:A|B] is defined as the smallest relation satisfying the following rules: We write [I|B] for [I:A|B] where A is the type of I.

The case of inductive types in sorts Set or Type is simple. There is no restriction on the sort of the predicate to be eliminated.

Prod

$$\frac{[(I\ x):A'|B']}{[I:\forall x:A,\ A'|\forall x:A,\ B']}$$

Set & Type

$$\frac{s_1 \in \{\mathsf{Set}, \mathsf{Type}(j)\}}{[I:s_1|I \to s_2]} \quad s_2 \in \mathcal{S}$$

The case of Inductive definitions of sort Prop is a bit more complicated, because of our interpretation of this sort. The only harmless allowed eliminations, are the ones when predicate P is also of sort Prop or is of the morally smaller sort SProp.

## Prop

$$\frac{s \in \{\mathsf{SProp}, \mathsf{Prop}\}}{[I: \mathsf{Prop}|I \to s]}$$

Prop is the type of logical propositions, the proofs of properties P in Prop could not be used for computation and are consequently ignored by the extraction mechanism. Assume A and B are two propositions, and the logical disjunction  $A \vee B$  is defined inductively by:

#### Example

```
Inductive or (A B:Prop) : Prop :=
or_introl : A -> or A B | or_intror : B -> or A B.
```

The following definition which computes a boolean value by case over the proof of or A B is not accepted:

#### Example

```
Fail Definition choice (A B: Prop) (x:or A B) :=
match x with or_introl _ a => true | or_intror _ b => false end.
   The command has indeed failed with message:
   Incorrect elimination of "x" in the inductive type "or":
   the return type has sort "Set" while it should be "SProp" or "Prop".
   Elimination of an inductive object of sort Prop
   is not allowed on a predicate in sort Set
   because proofs can be eliminated only to build proofs.
```

From the computational point of view, the structure of the proof of (or A B) in this term is needed for computing the boolean value.

In general, if I has type Prop then P cannot have type  $I \to \mathsf{Set}$ , because it will mean to build an informative proof of type  $(P \ m)$  doing a case analysis over a non-computational object that will disappear in the extracted program. But the other way is safe with respect to our interpretation we can have I a computational object and P a non-computational one, it just corresponds to proving a logical property of a computational object.

In the same spirit, elimination on P of type  $I \to \mathsf{Type}$  cannot be allowed because it trivially implies the elimination on P of type  $I \to \mathsf{Set}$  by cumulativity. It also implies that there are two proofs of the same property which are provably different, contradicting the proof-irrelevance property which is sometimes a useful axiom:

#### Example

```
Axiom proof_irrelevance : forall (P : Prop) (x y : P), x=y. proof_irrelevance is declared
```

The elimination of an inductive type of sort Prop on a predicate P of type  $I \to \mathsf{Type}$  leads to a paradox when applied to impredicative inductive definition like the second-order existential quantifier  $\mathsf{exProp}$  defined above, because it gives access to the two projections on this type.

Empty and singleton elimination. There are special inductive definitions in Prop for which more eliminations are allowed.

## Prop-extended

$$\frac{I \text{ is an empty or singleton definition}}{[I: \mathsf{Prop}|I \to s]}$$

A singleton definition has only one constructor and all the arguments of this constructor have type Prop. In that case, there is a canonical way to interpret the informative extraction on an object in that type, such that the elimination on any sort s is legal. Typical examples are the conjunction of non-informative propositions and the equality. If there is a hypothesis h: a=b in the local context, it can be used for rewriting not only in logical propositions but also in any type.

#### Example

An empty definition has no constructors, in that case also, elimination on any sort is allowed.

Inductive types in SProp must have no constructors (i.e. be empty) to be eliminated to produce relevant values.

Note that thanks to proof irrelevance elimination functions can be produced for other types, for instance the elimination for a unit type is the identity.

**Type of branches.** Let c be a term of type C, we assume C is a type of constructor for an inductive type I. Let P be a term that represents the property to be proved. We assume r is the number of parameters and s is the number of arguments.

We define a new type  $\{c:C\}^P$  which represents the type of the branch corresponding to the c:C constructor.

$$\begin{array}{ll} \{c: (I\ q_1 \ldots q_r\ t_1 \ldots t_s)\}^P & \equiv (P\ t_1 \ldots\ t_s\ c) \\ \{c: \forall x: T,\ C\}^P & \equiv \forall x: T,\ \{(c\ x): C\}^P \end{array}$$

We write  $\{c\}^P$  for  $\{c:C\}^P$  with C the type of c.

#### Example

The following term in concrete syntax:

```
match t as 1 return P' with
| nil _ => t1
| cons _ hd t1 => t2
end
```

can be represented in abstract syntax as

$$case(t, P, f_1|f_2)$$

where

$$\begin{array}{rcl} P & = & \lambda l. \; P' \\ f_1 & = & t_1 \\ f_2 & = & \lambda (hd: \mathsf{nat}). \; \lambda (tl: \mathsf{list \; nat}). \; t_2 \end{array}$$

According to the definition:

```
\begin{split} \{(\mathsf{nil}\;\mathsf{nat})\}^P &\equiv \{(\mathsf{nil}\;\mathsf{nat}) : (\mathsf{list}\;\mathsf{nat})\}^P \equiv (P\;(\mathsf{nil}\;\mathsf{nat})) \\ \{(\mathsf{cons}\;\mathsf{nat})\}^P &\equiv \{(\mathsf{cons}\;\mathsf{nat}) : (\mathsf{nat} \to \mathsf{list}\;\mathsf{nat} \to \mathsf{list}\;\mathsf{nat})\}^P \\ &\equiv \forall n : \mathsf{nat}, \; \{(\mathsf{cons}\;\mathsf{nat}\;n) : (\mathsf{list}\;\mathsf{nat} \to \mathsf{list}\;\mathsf{nat})\}^P \\ &\equiv \forall n : \mathsf{nat}, \; \forall l : \mathsf{list}\;\mathsf{nat}, \; \{(\mathsf{cons}\;\mathsf{nat}\;n\;l) : (\mathsf{list}\;\mathsf{nat})\}^P \\ &\equiv \forall n : \mathsf{nat}, \; \forall l : \mathsf{list}\;\mathsf{nat}, \; (P\;(\mathsf{cons}\;\mathsf{nat}\;n\;l)). \end{split}
```

Given some P then  $\{(\mathsf{nil}\;\mathsf{nat})\}^P$  represents the expected type of  $f_1$ , and  $\{(\mathsf{cons}\;\mathsf{nat})\}^P$  represents the expected type of  $f_2$ .

**Typing rule.** Our very general destructor for inductive definition enjoys the following typing rule match

$$\begin{split} E[\Gamma] \vdash c : (I \ q_1...q_r \ t_1...t_s) \\ E[\Gamma] \vdash P : B \\ [(I \ q_1...q_r)|B] \\ (E[\Gamma] \vdash f_i : \{(c_{p_i} \ q_1...q_r)\}^P)_{i=1...l} \\ \hline E[\Gamma] \vdash \mathsf{case}(c, P, f_1|...|f_l) : (P \ t_1...t_s \ c) \end{split}$$

provided I is an inductive type in a definition  $\operatorname{Ind}[r](\Gamma_I := \Gamma_C)$  with  $\Gamma_C = [c_1 : C_1; ...; c_n : C_n]$  and  $c_{p_1}...c_{p_l}$  are the only constructors of I.

#### Example

Below is a typing rule for the term shown in the previous example:

#### list example

$$\begin{split} E[\Gamma] \vdash t : (\mathsf{list\ nat}) \\ E[\Gamma] \vdash P : B \\ [(\mathsf{list\ nat})|B] \\ E[\Gamma] \vdash f_1 : \{(\mathsf{nil\ nat})\}^P \\ E[\Gamma] \vdash f_2 : \{(\mathsf{cons\ nat})\}^P \\ \hline E[\Gamma] \vdash \mathsf{case}(t, P, f_1|f_2) : (P\ t) \end{split}$$

**Definition of**  $\iota$ **-reduction.** We still have to define the  $\iota$ -reduction in the general case.

An  $\iota$ -redex is a term of the following form:

$$case((c_{p_i} \ q_1...q_r \ a_1...a_m), P, f_1|...|f_l)$$

with  $c_{p_i}$  the *i*-th constructor of the inductive type I with r parameters.

The  $\iota$ -contraction of this term is  $(f_i \ a_1...a_m)$  leading to the general reduction rule:

$$case((c_n, q_1...q_r, a_1...a_m), P, f_1|...|f_l) \triangleright_{\iota} (f_i, a_1...a_m)$$

#### **Fixpoint definitions**

The second operator for elimination is fixpoint definition. This fixpoint may involve several mutually recursive definitions. The basic concrete syntax for a recursive set of mutually recursive declarations is (with  $\Gamma_i$  contexts):

$$\mbox{fix } f_1(\Gamma_1): A_1:=t_1 \mbox{ with...with } f_n(\Gamma_n): A_n:=t_n$$

The terms are obtained by projections from this set of declarations and are written

fix 
$$f_1(\Gamma_1):A_1:=t_1$$
 with...with  $f_n(\Gamma_n):A_n:=t_n$  for  $f_i$ 

In the inference rules, we represent such a term by

Fix 
$$f_i\{f_1: A'_1:=t'_1...f_n: A'_n:=t'_n\}$$

with  $t'_i$  (resp.  $A'_i$ ) representing the term  $t_i$  abstracted (resp. generalized) with respect to the bindings in the context  $\Gamma_i$ , namely  $t'_i = \lambda \Gamma_i . t_i$  and  $A'_i = \forall \Gamma_i , A_i$ .

#### Typing rule

The typing rule is the expected one for a fixpoint.

 $\mathbf{Fix}$ 

$$\frac{(E[\Gamma] \vdash A_i : s_i)_{i=1\dots n}}{E[\Gamma] \vdash \mathsf{Fix} \ f_i \{f_1 : A_1 : = t_1 \dots f_n : A_n : = t_n\} : A_i} \\$$

Any fixpoint definition cannot be accepted because non-normalizing terms allow proofs of absurdity. The basic scheme of recursion that should be allowed is the one needed for defining primitive recursive functionals. In that case the fixpoint enjoys a special syntactic restriction, namely one of the arguments belongs to an inductive type, the function starts with a case analysis and recursive calls are done on variables coming from patterns and representing subterms. For instance in the case of natural numbers, a proof of the induction principle of type

$$\forall P: \mathsf{nat} \to \mathsf{Prop}, \ (P \ \mathsf{O}) \to (\forall n: \mathsf{nat}, \ (P \ n) \to (P \ (\mathsf{S} \ n))) \to \forall n: \mathsf{nat}, \ (P \ n) \to (P \ (\mathsf{S} \ n)) \to (P \ (\mathsf{S} \ n))$$

can be represented by the term:

$$\begin{split} \lambda P : \mathsf{nat} &\to \mathsf{Prop.} \ \lambda f : (P \ \mathsf{O}). \ \lambda g : (\forall n : \mathsf{nat}, \ (P \ n) \to (P \ (\mathsf{S} \ n))). \\ \mathsf{Fix} \ h \{h : \forall n : \mathsf{nat}, \ (P \ n) := \lambda n : \mathsf{nat}. \ \mathsf{case}(n, P, f | \lambda p : \mathsf{nat}. \ (g \ p \ (h \ p)))\} \end{split}$$

Before accepting a fixpoint definition as being correctly typed, we check that the definition is "guarded". A precise analysis of this notion can be found in [Gimenez94]. The first stage is to precise on which argument

the fixpoint will be decreasing. The type of this argument should be an inductive type. For doing this, the syntax of fixpoints is extended and becomes

Fix 
$$f_i\{f_1/k_1: A_1:=t_1...f_n/k_n: A_n:=t_n\}$$

where  $k_i$  are positive integers. Each  $k_i$  represents the index of parameter of  $f_i$ , on which  $f_i$  is decreasing. Each  $A_i$  should be a type (reducible to a term) starting with at least  $k_i$  products  $\forall y_1 : B_1, ... \forall y_{k_i} : B_{k_i}, A'_i$  and  $B_{k_i}$  an inductive type.

Now in the definition  $t_i$ , if  $f_j$  occurs then it should be applied to at least  $k_j$  arguments and the  $k_j$ -th argument should be syntactically recognized as structurally smaller than  $y_k$ .

The definition of being structurally smaller is a bit technical. One needs first to define the notion of recursive arguments of a constructor. For an inductive definition Ind [r] ( $\Gamma_I := \Gamma_C$ ), if the type of a constructor c has the form  $\forall p_1: P_1, ... \forall p_r: P_r, \ \forall x_1: T_1, ... \forall x_m: T_m, \ (I_j \ p_1...p_r \ t_1...t_s)$ , then the recursive arguments will correspond to  $T_i$  in which one of the  $I_l$  occurs.

The main rules for being structurally smaller are the following. Given a variable y of an inductively defined type in a declaration  $\operatorname{Ind} [r](\Gamma_I := \Gamma_C)$  where  $\Gamma_I$  is  $[I_1 : A_1; ...; I_k : A_k]$ , and  $\Gamma_C$  is  $[c_1 : C_1; ...; c_n : C_n]$ , the terms structurally smaller than y are:

- $(t \ u)$  and  $\lambda x : U$ . t when t is structurally smaller than y.
- $\mathsf{case}(c, P, f_1...f_n)$  when each  $f_i$  is structurally smaller than y. If c is y or is structurally smaller than y, its type is an inductive type  $I_p$  part of the inductive definition corresponding to y. Each  $f_i$  corresponds to a type of constructor  $C_q \equiv \forall p_1 : P_1, \ldots, \forall p_r : P_r, \ \forall y_1 : B_1, \ldots \forall y_m : B_m, \ (I_p \ p_1...p_r \ t_1...t_s)$  and can consequently be written  $\lambda y_1 : B_1' \ldots \lambda y_m : B_m' . \ g_i$ . ( $B_i'$  is obtained from  $B_i$  by substituting parameters for variables) the variables  $y_j$  occurring in  $g_i$  corresponding to recursive arguments  $B_i$  (the ones in which one of the  $I_l$  occurs) are structurally smaller than y.

The following definitions are correct, we enter them using the Fixpoint command and show the internal representation.

#### Example

```
Fixpoint plus (n m:nat) {struct n} : nat :=
match n with
\mid 0 => m
\mid S p => S (plus p m)
end.
    plus is defined
    plus is recursively defined (decreasing on 1st argument)
Print plus.
   plus =
   fix plus (n m : nat) {struct n} : nat :=
     match n with
      | 0 => m
      | S p => S (plus p m)
         : nat -> nat -> nat
    Arguments plus (_ _)%nat_scope
Fixpoint lgth (A:Set) (1:list A) {struct 1} : nat :=
match 1 with
| nil _ => 0
| cons _ a l' => S (lgth A l')
```

(continues on next page)

(continued from previous page)

```
end.
   lgth is defined
    lgth is recursively defined (decreasing on 2nd argument)
Print lgth.
    lgth =
   fix lgth (A : Set) (1 : list A) {struct 1} : nat :=
     match 1 with
      | nil _ => 0
      | cons _ _ 1' => S (lgth A 1')
         : forall A : Set, list A -> nat
    Arguments lgth _%type_scope
Fixpoint sizet (t:tree) : nat := let (f) := t in S (sizef f)
with sizef (f:forest) : nat :=
match f with
| emptyf => 0
| consf t f => plus (sizet t) (sizef f)
end.
   sizet is defined
    sizef is defined
    sizet, sizef are recursively defined (decreasing respectively on 1st,
    1st arguments)
Print sizet.
    sizet =
    fix sizet (t : tree) : nat := let (f) := t in S (sizef f)
    with sizef (f : forest) : nat :=
     match f with
      | emptyf => 0
      | consf t f0 => plus (sizet t) (sizef f0)
      end
    for sizet
        : tree -> nat
```

## Reduction rule

Let F be the set of declarations:  $f_1/k_1:A_1:=t_1...f_n/k_n:A_n:=t_n$ . The reduction for fixpoints is:

$$(\text{Fix } f_i\{F\} \ a_1...a_k) \ \triangleright_{\iota} \ t_i\{f_k/\text{Fix } f_k\{F\}\}_{k=1...n} \ a_1...a_k$$

when  $a_{k_i}$  starts with a constructor. This last restriction is needed in order to keep strong normalization and corresponds to the reduction for primitive recursive operators. The following reductions are now possible:

$$\begin{array}{cccc} \mathsf{plus}\; (\mathsf{S}\; (\mathsf{S}\; \mathsf{O}))\; (\mathsf{S}\; \mathsf{O}) & \; \rhd_{\iota} & \mathsf{S}\; (\mathsf{plus}\; (\mathsf{S}\; \mathsf{O})\; (\mathsf{S}\; \mathsf{O})) \\ & \; \rhd_{\iota} & \mathsf{S}\; (\mathsf{S}\; (\mathsf{plus}\; \mathsf{O}\; (\mathsf{S}\; \mathsf{O}))) \\ & \; \rhd_{\iota} & \mathsf{S}\; (\mathsf{S}\; (\mathsf{S}\; \mathsf{O})) \end{array}$$

## Mutual induction

The principles of mutual induction can be automatically generated using the Scheme command described in Section Generation of induction principles with Scheme.

## 4.4.6 Admissible rules for global environments

From the original rules of the type system, one can show the admissibility of rules which change the local context of definition of objects in the global environment. We show here the admissible rules that are used in the discharge mechanism at the end of a section.

**Abstraction.** One can modify a global declaration by generalizing it over a previously assumed constant c. For doing that, we need to modify the reference to the global declaration in the subsequent global environment and local context by explicitly applying this constant to the constant c.

Below, if  $\Gamma$  is a context of the form  $[y_1:A_1;...;y_n:A_n]$ , we write  $\forall x:U,\ \Gamma\{c/x\}$  to mean  $[y_1:\forall x:U,\ A_1\{c/x\};...;y_n:\forall x:U,\ A_n\{c/x\}]$  and  $E\{|\Gamma|/|\Gamma|c\}$  to mean the parallel substitution  $E\{y_1/(y_1\ c)\}...\{y_n/(y_n\ c)\}.$ 

First abstracting property:

$$\frac{\mathcal{WF}(E;\; c:U;\; E';\; c':=t:T;\; E'')[\Gamma]}{\mathcal{WF}(E;\; c:U;\; E';\; c':=\lambda x:U.\; t\{c/x\}:\; \forall x:U,\; T\{c/x\};\; E''\{c'/(c'\;c)\})[\Gamma\{c'/(c'\;c)\}]} \\ \frac{\mathcal{WF}(E;\; c:U;\; E';\; c':T;\; E'')[\Gamma]}{\mathcal{WF}(E;\; c:U;\; E';\; c':\forall x:U,\; T\{c/x\};\; E''\{c'/(c'\;c)\})[\Gamma\{c'/(c'\;c)\}]} \\ \frac{\mathcal{WF}(E;\; c:U;\; E';\; \ln d\; [p]\; (\Gamma_I\; :=\; \Gamma_C)\; ;\; E'')[\Gamma]}{\mathcal{WF}\;\; (E;\; c:U;\; E';\; \ln d\; [p+1]\; (\forall x:U,\; \Gamma_I\{c/x\}\; :=\; \forall x:U,\; \Gamma_C\{c/x\})\; ;\; E''\{|\Gamma_I;\Gamma_C|/|\Gamma_I;\Gamma_C|c\})} \\ \frac{[\Gamma\{|\Gamma_I;\Gamma_C|/|\Gamma_I;\Gamma_C|c\}]}{[\Gamma\{|\Gamma_I;\Gamma_C|/|\Gamma_I;\Gamma_C|c\}]}$$

One can similarly modify a global declaration by generalizing it over a previously defined constant c. Below, if  $\Gamma$  is a context of the form  $[y_1:A_1; ...; y_n:A_n]$ , we write  $\Gamma\{c/u\}$  to mean  $[y_1:A_1\{c/u\}; ...; y_n:A_n\{c/u\}]$ .

Second abstracting property:

$$\begin{split} \mathcal{WF}(E; \ c := u : U; \ E'; \ c' := t : T; \ E'')[\Gamma] \\ \overline{\mathcal{WF}(E; \ c := u : U; \ E'; \ c' := (\text{let } x := u : U \text{ in } t\{c/x\}) : T\{c/u\}; \ E'')[\Gamma]} \\ & \frac{\mathcal{WF}(E; \ c := u : U; \ E'; \ c' : T; \ E'')[\Gamma]}{\overline{\mathcal{WF}(E; \ c := u : U; \ E'; \ \text{Ind} \ [p] \ (\Gamma_I := \Gamma_C); \ E'')[\Gamma]} \\ & \frac{\mathcal{WF}(E; \ c := u : U; \ E'; \ \text{Ind} \ [p] \ (\Gamma_I := \Gamma_C); \ E'')[\Gamma]}{\overline{\mathcal{WF}(E; \ c := u : U; \ E'; \ \text{Ind} \ [p] \ (\Gamma_I\{c/u\} := \Gamma_C\{c/u\}); \ E'')[\Gamma]} \end{split}$$

**Pruning the local context.** If one abstracts or substitutes constants with the above rules then it may happen that some declared or defined constant does not occur any more in the subsequent global environment and in the local context. One can consequently derive the following property.

First pruning property:

$$\frac{\mathcal{WF}(E;\ c:U;\ E')[\Gamma] \qquad c \text{ does not occur in } E' \text{ and } \Gamma}{\mathcal{WF}(E;E')[\Gamma]}$$

Second pruning property:

$$\frac{\mathcal{WF}(E;\ c:=u:U;\ E')[\Gamma] \qquad c \text{ does not occur in } E' \text{ and } \Gamma}{\mathcal{WF}(E;E')[\Gamma]}$$

#### 4.4.7 Co-inductive types

The implementation contains also co-inductive definitions, which are types inhabited by infinite objects. More information on co-inductive definitions can be found in [Gimenez95][Gimenez98][GimenezCasteran05].

## 4.4.8 The Calculus of Inductive Constructions with impredicative Set

Coq can be used as a type checker for the Calculus of Inductive Constructions with an impredicative sort Set by using the compiler option -impredicative-set. For example, using the ordinary coqtop command, the following is rejected,

#### Example

```
Fail Definition id: Set := forall X:Set,X->X.
   The command has indeed failed with message:
   The term "forall X : Set, X -> X" has type "Type"
   while it is expected to have type "Set" (universe inconsistency).
```

while it will type check, if one uses instead the coqtop -impredicative-set option..

The major change in the theory concerns the rule for product formation in the sort Set, which is extended to a domain in any sort:

#### **ProdImp**

$$\frac{E[\Gamma] \vdash T : s \qquad s \in \mathcal{S} \qquad E[\Gamma :: (x : T)] \vdash U : \mathsf{Set}}{E[\Gamma] \vdash \forall x : T, \ U : \mathsf{Set}}$$

This extension has consequences on the inductive definitions which are allowed. In the impredicative system, one can build so-called *large inductive definitions* like the example of second-order existential quantifier (exSet).

There should be restrictions on the eliminations which can be performed on such definitions. The elimination rules in the impredicative system for sort Set become:

Set1

$$\frac{s \in \{\mathsf{Prop}, \mathsf{Set}\}}{[I : \mathsf{Set}|I \to s]}$$

Set2

$$\frac{I \text{ is a small inductive definition}}{[I:\mathsf{Set}|I\to s]} \frac{s \in \{\mathsf{Type}(i)\}}{}$$

## 4.5 The Module System

The module system extends the Calculus of Inductive Constructions providing a convenient way to structure large developments as well as a means of massive abstraction.

## 4.5.1 Modules and module types

**Access path.** An access path is denoted by p and can be either a module variable X or, if p' is an access path and id an identifier, then p'.id is an access path.

**Structure element.** A structure element is denoted by e and is either a definition of a constant, an assumption, a definition of an inductive, a definition of a module, an alias of a module or a module type abbreviation.

**Structure expression.** A structure expression is denoted by S and can be:

- an access path p
- a plain structure Struct e; ...; e End
- a functor Functor(X:S) S', where X is a module variable, S and S' are structure expressions
- an application S p, where S is a structure expression and p an access path
- a refined structure S with p := p or S with p := t : T where S is a structure expression, p and p' are access paths, t is a term and T is the type of t.

**Module definition.** A module definition is written Mod(X : S [:= S']) and consists of a module variable X, a module type S which can be any structure expression and optionally a module implementation S' which can be any structure expression except a refined structure.

**Module alias.** A module alias is written  $\mathsf{ModA}(X == p)$  and consists of a module variable X and a module path p.

Module type abbreviation. A module type abbreviation is written  $\mathsf{ModType}(Y := S)$ , where Y is an identifier and S is any structure expression .

## 4.5.2 Typing Modules

In order to introduce the typing system we first slightly extend the syntactic class of terms and environments given in section *The terms*. The environments, apart from definitions of constants and inductive types now also hold any other structure elements. Terms, apart from variables, constants and complex terms, include also access paths.

We also need additional typing judgments:

- $E[] \vdash \mathcal{WF}(S)$ , denoting that a structure S is well-formed,
- $E[] \vdash p : S$ , denoting that the module pointed by p has type S in environment E.
- $E[] \vdash S \longrightarrow \overline{S}$ , denoting that a structure S is evaluated to a structure S in weak head normal form.
- $E[] \vdash S_1 \lt: S_2$ , denoting that a structure  $S_1$  is a subtype of a structure  $S_2$ .
- $E[]\vdash e_1 <: e_2$  , denoting that a structure element e\_1 is more precise than a structure element e\_2.

The rules for forming structures are the following:

#### WF-STR

$$\frac{\mathcal{WF}(E;E')[]}{E[] \vdash \mathcal{WF}(\mathsf{Struct}\ E'\ \mathsf{End})}$$

WF-FUN

$$\frac{E;\mathsf{Mod}(X:S)[] \vdash \mathcal{WF}(\overline{S'})}{E[] \vdash \mathcal{WF}(\mathsf{Functor}(X:S)\ S')}$$

Evaluation of structures to weak head normal form:

## WEVAL-APP

$$\frac{E[] \vdash S \longrightarrow \mathsf{Functor}(X:S_1) \ S_2 \quad E[] \vdash S_1 \longrightarrow \overline{S_1}}{E[] \vdash S \ p \longrightarrow S_2\{p/X, t_1/p_1.c_1, ..., t_n/p_n.c_n\}}$$

In the last rule,  $\{t_1/p_1.c_1,...,t_n/p_n.c_n\}$  is the resulting substitution from the inlining mechanism. We substitute in S the inlined fields  $p_i.c_i$  from  $\mathsf{Mod}(X:S_1)$  by the corresponding delta- reduced term  $t_i$  in p.

#### **WEVAL-WITH-MOD**

$$\begin{split} E[] \vdash S &\longrightarrow \mathsf{Struct}\ e_1; ...; e_i; \mathsf{Mod}(X:S_1); e_{i+2}; ...; e_n \ \mathsf{End} \\ E; e_1; ...; e_i[] \vdash S_1 &\longrightarrow \overline{S_1} \qquad E[] \vdash p:S_2 \\ E; e_1; ...; e_i[] \vdash S_2 \lessdot: \overline{S_1} \\ E[] \vdash S \ \mathsf{with}\ x := p &\longrightarrow \\ \mathsf{Struct}\ e_1; ...; e_i; \mathsf{ModA}(X == p); e_{i+2}\{p/X\}; ...; e_n\{p/X\} \ \mathsf{End} \end{split}$$

#### WEVAL-WITH-MOD-REC

$$\begin{split} E[] \vdash S &\longrightarrow \mathsf{Struct}\ e_1; ...; e_i; \mathsf{Mod}(X_1:S_1); e_{i+\underline{2}}; ...; e_n \ \mathsf{End} \\ & E[e_1; ...; e_i]] \vdash S_1 \ \mathsf{with}\ p := p_1 \longrightarrow \overline{S_2} \\ \hline & E[] \vdash S \ \mathsf{with}\ X_1.p := p_1 \longrightarrow \\ \mathsf{Struct}\ e_1; ...; e_i; \mathsf{Mod}(X:\overline{S_2}); e_{i+\underline{2}}\{p_1/X_1.p\}; ...; e_n\{p_1/X_1.p\} \ \mathsf{End} \end{split}$$

#### WEVAL-WITH-DEF

$$\begin{split} E[] \vdash S &\longrightarrow \mathsf{Struct}\ e_1; ...; e_i; \mathsf{Assum}()(c:T_1); e_{i+2}; ...; e_n \ \mathsf{End} \\ E; e_1; ...; e_i[] \vdash Def()(c := t:T) <: \mathsf{Assum}()(c:T_1) \\ \hline E[] \vdash S \ \mathsf{with}\ c := t:T &\longrightarrow \\ \mathsf{Struct}\ e_1; ...; e_i; Def()(c := t:T); e_{i+2}; ...; e_n \ \mathsf{End} \end{split}$$

#### WEVAL-WITH-DEF-REC

$$\begin{split} E[] \vdash S &\longrightarrow \mathsf{Struct}\ e_1; ...; e_i; \mathsf{Mod}(X_1:S_1); e_{i+2}; ...; e_n \ \mathsf{End} \\ E; e_1; ...; e_i[] \vdash S_1 \ \mathsf{with}\ p := p_1 &\longrightarrow \overline{S_2} \\ E[] \vdash S \ \mathsf{with}\ X_1.p := t:T &\longrightarrow \\ \mathsf{Struct}\ e_1; ...; e_i; \mathsf{Mod}(X:\overline{S_2}); e_{i+2}; ...; e_n \ \mathsf{End} \end{split}$$

#### WEVAL-PATH-MOD1

$$\begin{split} E[] \vdash p \longrightarrow \mathsf{Struct}\ e_1; ...; e_i; \mathsf{Mod}(X : S \, [:= S_1]); e_{i+2}; ...; e_n End \\ E; e_1; ...; e_i[] \vdash S \longrightarrow \overline{S} \\ \hline E[] \vdash p.X \longrightarrow \overline{S} \end{split}$$

#### WEVAL-PATH-MOD2

$$\frac{\mathcal{WF}(E)[] \qquad \quad \mathsf{Mod}(X:S\,[:=S_1]) \in E \qquad \quad E[] \vdash S \longrightarrow \overline{S}}{E[] \vdash X \longrightarrow \overline{S}}$$

## WEVAL-PATH-ALIAS1

$$\begin{split} E[] \vdash p \longrightarrow & \mathsf{Struct}\ e_1; ...; e_i; \mathsf{ModA}(X == p_1); e_{i+2}; ...; e_n End \\ & E; e_1; ...; e_i[] \vdash p_1 \longrightarrow \overline{S} \\ \hline & E[] \vdash p.X \longrightarrow \overline{S} \end{split}$$

#### WEVAL-PATH-ALIAS2

$$\frac{\mathcal{WF}(E)[] \qquad \operatorname{ModA}(X == p_1) \in E \qquad E[] \vdash p_1 \longrightarrow \overline{S}}{E[] \vdash X \longrightarrow \overline{S}}$$

## WEVAL-PATH-TYPE1

$$E[] \vdash p \longrightarrow \mathsf{Struct}\ e_1; ...; e_i; \mathsf{ModType}(Y \vcentcolon= S); e_{i+2}; ...; e_n End \\ E; e_1; ...; e_i[] \vdash S \longrightarrow \overline{S} \\ E[] \vdash p.Y \longrightarrow \overline{S}$$

#### WEVAL-PATH-TYPE2

$$\frac{\mathcal{WF}(E)[] \qquad \operatorname{\mathsf{ModType}}(Y := S) \in E \qquad E[] \vdash S \longrightarrow \overline{S}}{E[] \vdash Y \longrightarrow \overline{S}}$$

Rules for typing module:

MT-EVAL

$$\frac{E[] \vdash p \longrightarrow \overline{S}}{E[] \vdash p : \overline{S}}$$

MT-STR

$$\frac{E[] \vdash p : S}{E[] \vdash p : S/p}$$

The last rule, called strengthening is used to make all module fields manifestly equal to themselves. The notation S/p has the following meaning:

- if  $S \longrightarrow \mathsf{Struct}\ e_1; ...; e_n$  End then  $S/p = \mathsf{Struct}\ e_1/p; ...; e_n/p$  End where e/p is defined as follows (note that opaque definitions are processed as assumptions):
  - $\ \mathsf{Def}()(c := t : T)/p = \mathsf{Def}()(c := t : T)$
  - $\ \operatorname{Assum}()(c:U)/p = \operatorname{Def}()(c:=p.c:U)$
  - $\operatorname{\mathsf{Mod}}(X:S)/p = \operatorname{\mathsf{ModA}}(X == p.X)$
  - $-\ \mathsf{ModA}(X == p')/p = \mathsf{ModA}(X == p')$
  - $-\operatorname{Ind}[\Gamma_P](\Gamma_C := \Gamma_I)/p = \operatorname{Ind}_p()[\Gamma_P](\Gamma_C := \Gamma_I)$
  - $-\operatorname{Ind}_{n'}()[\Gamma_P](\Gamma_C := \Gamma_I)/p = \operatorname{Ind}_{n'}()[\Gamma_P](\Gamma_C := \Gamma_I)$
- if  $S \longrightarrow \operatorname{Functor}(X : S') S''$  then S/p = S

The notation  $\operatorname{Ind}_p()[\Gamma_P](\Gamma_C := \Gamma_I)$  denotes an inductive definition that is definitionally equal to the inductive definition in the module denoted by the path p. All rules which have  $\operatorname{Ind}[\Gamma_P](\Gamma_C := \Gamma_I)$  as premises are also valid for  $\operatorname{Ind}_p()[\Gamma_P](\Gamma_C := \Gamma_I)$ . We give the formation rule for  $\operatorname{Ind}_p()[\Gamma_P](\Gamma_C := \Gamma_I)$  below as well as the equality rules on inductive types and constructors.

The module subtyping rules:

## MSUB-STR

$$\begin{split} E; e_1; ...; e_n[] \vdash e_{\sigma(i)} <: e_i' \text{ for } i = 1..m \\ \sigma: \{1...m\} \rightarrow \{1...n\} \text{ injective} \\ \hline E[] \vdash \text{Struct } e_1; ...; e_n \text{ End} <: \text{ Struct } e_1'; ...; e_m' \text{ End} \end{split}$$

**MSUB-FUN** 

$$\frac{E[] \vdash \overline{S_1'} <: \overline{S_1} \qquad E; \mathsf{Mod}(X:S_1')[] \vdash \overline{S_2} <: \overline{S_2'}}{E[] \vdash \mathsf{Functor}(X:S_1)S_2 <: \mathsf{Functor}(X:S_1')S_2'}$$

Structure element subtyping rules:

## ASSUM-ASSUM

$$\frac{E[] \vdash T_1 \leq_{\beta\delta\iota\zeta\eta} T_2}{E[] \vdash \mathsf{Assum}()(c:T_1) <: \mathsf{Assum}()(c:T_2)}$$

**DEF-ASSUM** 

$$\frac{E[] \vdash T_1 \leq_{\beta \delta \iota \zeta \eta} T_2}{E[] \vdash \mathsf{Def}()(c := t : T_1) <: \mathsf{Assum}()(c : T_2)}$$

**ASSUM-DEF** 

$$\frac{E[] \vdash T_1 \leq_{\beta\delta\iota\zeta\eta} T_2 \qquad E[] \vdash c =_{\beta\delta\iota\zeta\eta} t_2}{E[] \vdash \mathsf{Assum}()(c:T_1) <: \mathsf{Def}()(c:=t_2:T_2)}$$

**DEF-DEF** 

$$\frac{E[] \vdash T_1 \leq_{\beta\delta\iota\zeta\eta} T_2}{E[] \vdash \mathsf{Def}()(c := t_1 : T_1) <: \mathsf{Def}()(c := t_2 : T_2)}$$

IND-IND

$$\frac{E[] \vdash \Gamma_P =_{\beta \delta \iota \zeta \eta} \Gamma_P' \qquad E[\Gamma_P] \vdash \Gamma_C =_{\beta \delta \iota \zeta \eta} \Gamma_C' \qquad E[\Gamma_P; \Gamma_C] \vdash \Gamma_I =_{\beta \delta \iota \zeta \eta} \Gamma_I'}{E[] \vdash \operatorname{Ind} \left[\Gamma_P\right] \left(\Gamma_C \ := \ \Gamma_I\right) <: \operatorname{Ind} \left[\Gamma_P'\right] \left(\Gamma_C' \ := \ \Gamma_I'\right)}$$

INDP-IND

$$\frac{E[] \vdash \Gamma_P =_{\beta \delta \iota \zeta \eta} \Gamma_P' \qquad E[\Gamma_P] \vdash \Gamma_C =_{\beta \delta \iota \zeta \eta} \Gamma_C' \qquad E[\Gamma_P; \Gamma_C] \vdash \Gamma_I =_{\beta \delta \iota \zeta \eta} \Gamma_I'}{E[] \vdash \operatorname{Ind}_p()[\Gamma_P](\Gamma_C := \Gamma_I) <: \operatorname{Ind} \left[\Gamma_P'\right] \left(\Gamma_C' := \Gamma_I'\right)}$$

**INDP-INDP** 

$$E[] \vdash \Gamma_P =_{\beta\delta\iota\zeta\eta} \Gamma_P' \qquad E[\Gamma_P] \vdash \Gamma_C =_{\beta\delta\iota\zeta\eta} \Gamma_C' \\ E[\Gamma_P; \Gamma_C] \vdash \Gamma_I =_{\beta\delta\iota\zeta\eta} \Gamma_I' \qquad E[] \vdash p =_{\beta\delta\iota\zeta\eta} p' \\ E[] \vdash \operatorname{Ind}_p()[\Gamma_P](\Gamma_C := \Gamma_I) <: \operatorname{Ind}_{p'}()[\Gamma_P'](\Gamma_C' := \Gamma_I')$$

MOD-MOD

$$\frac{E[] \vdash S_1 <: S_2}{E[] \vdash \mathsf{Mod}(X:S_1) <: \mathsf{Mod}(X:S_2)}$$

**ALIAS-MOD** 

$$\frac{E[] \vdash p : S_1}{E[] \vdash \mathsf{ModA}(X == p) <: \mathsf{Mod}(X : S_2)}$$

**MOD-ALIAS** 

$$\frac{E[] \vdash p : S_2 \qquad E[] \vdash S_1 <: S_2 \qquad E[] \vdash X =_{\beta \delta \iota \zeta \eta} p}{E[] \vdash \mathsf{Mod}(X : S_1) <: \mathsf{ModA}(X == p)}$$

**ALIAS-ALIAS** 

$$\frac{E[] \vdash p_1 =_{\beta \delta \iota \zeta \eta} p_2}{E[] \vdash \mathsf{ModA}(X == p_1) <: \mathsf{ModA}(X == p_2)}$$

MODTYPE-MODTYPE

$$\frac{E[] \vdash S_1 <: S_2 \qquad E[] \vdash S_2 <: S_1}{E[] \vdash \mathsf{ModType}(Y := S_1) <: \mathsf{ModType}(Y := S_2)}$$

New environment formation rules

WF-MOD1

$$\frac{\mathcal{WF}(E)[]}{WF(E;\mathsf{Mod}(X:S))[]}$$

WF-MOD2

$$\frac{E[] \vdash S_2 <: S_1 \qquad \mathcal{WF}(E)[] \qquad E[] \vdash \mathcal{WF}(S_1) \qquad E[] \vdash \mathcal{WF}(S_2)}{\mathcal{WF}(E; \mathsf{Mod}(X:S_1 \, [:= S_2]))[]}$$

WF-ALIAS

$$\frac{\mathcal{WF}(E)[] \qquad E[] \vdash p : S}{\mathcal{WF}(E, \mathsf{ModA}(X == p))[]}$$

WF-MODTYPE

$$\frac{\mathcal{WF}(E)[] \qquad E[] \vdash \mathcal{WF}(S)}{\mathcal{WF}(E,\mathsf{ModType}(Y:=S))[]}$$

WF-IND

$$\frac{\mathcal{WF}(E;\operatorname{Ind}\left[\Gamma_{P}\right]\left(\Gamma_{C}:=\Gamma_{I}\right))[]}{E[]\vdash p:\ \operatorname{Struct}\ e_{1};...;e_{n};\operatorname{Ind}\left[\Gamma_{P}'\right]\left(\Gamma_{C}':=\Gamma_{I}'\right);...\ \operatorname{End}:}{E[]\vdash \operatorname{Ind}\left[\Gamma_{P}'\right]\left(\Gamma_{C}':=\Gamma_{I}'\right)<:\operatorname{Ind}\left[\Gamma_{P}\right]\left(\Gamma_{C}:=\Gamma_{I}\right)}$$

$$\frac{\mathcal{WF}(E;\operatorname{Ind}_{p}()[\Gamma_{P}](\Gamma_{C}:=\Gamma_{I}))[]}{}$$

Component access rules

ACC-TYPE1

$$\frac{E[\Gamma] \vdash p: \ \mathsf{Struct} \ e_1; ...; e_i; \mathsf{Assum}()(c:T); ... \ \mathsf{End}}{E[\Gamma] \vdash p.c:T}$$

ACC-TYPE2

$$\frac{E[\Gamma] \vdash p: \ \mathsf{Struct} \ e_1; ...; e_i; \mathsf{Def}()(c := t : T); ... \ \mathsf{End}}{E[\Gamma] \vdash p.c : T}$$

Notice that the following rule extends the delta rule defined in section Conversion rules

**ACC-DELTA** 

$$\frac{E[\Gamma] \vdash p: \ \mathsf{Struct} \ e_1; ...; e_i; \mathsf{Def}()(c := t : U); ... \ \mathsf{End}}{E[\Gamma] \vdash p.c \, \triangleright_{\delta} t}$$

In the rules below we assume  $\Gamma_P$  is  $[p_1:P_1;...;p_r:P_r],$   $\Gamma_I$  is  $[I_1:A_1;...;I_k:A_k],$  and  $\Gamma_C$  is  $[c_1:C_1;...;c_n:C_n].$ 

ACC-IND1

$$\frac{E[\Gamma] \vdash p: \ \mathsf{Struct} \ e_1; ...; e_i; \mathsf{Ind} \ [\Gamma_P] \left(\Gamma_C \ := \ \Gamma_I\right); ... \ \mathsf{End}}{E[\Gamma] \vdash p.I_j: \left(p_1:P_1\right) ... \left(p_r:P_r\right) A_j}$$

ACC-IND2

$$\frac{E[\Gamma] \vdash p : \text{ Struct } e_1; ...; e_i; \text{Ind } [\Gamma_P] \left(\Gamma_C \ := \ \Gamma_I\right); ... \text{ End}}{E[\Gamma] \vdash p.c_m : (p_1:P_1)...(p_r:P_r)C_mI_j(I_j \ p_1...p_r)_{j=1...k}}$$

ACC-INDP1

$$\frac{E[] \vdash p: \ \mathsf{Struct} \ e_1; ...; e_i; \mathsf{Ind}_{p'}()[\Gamma_P](\Gamma_C := \Gamma_I); ... \ \mathsf{End}}{E[] \vdash p.I_i \triangleright_{\delta} p'.I_i}$$

ACC-INDP2

$$\frac{E[] \vdash p: \ \mathsf{Struct} \ e_1; ...; e_i; \mathsf{Ind}_{p'}()[\Gamma_P](\Gamma_C := \Gamma_I); ... \ \mathsf{End}}{E[] \vdash p.c_i \triangleright_{\delta} p'.c_i}$$

## THE PROOF ENGINE

## 5.1 Vernacular commands

## 5.1.1 Displaying

## Command: Print qualid

This command displays on the screen information about the declared or defined object referred by qualid.

Error messages:

Error: qualid not a defined object.

Error: Universe instance should have length num.

Error: This object does not support universe names.

Variant: Print Term qualid

This is a synonym of *Print qualid* when *qualid* denotes a global constant.

Variant: Print Term qualid@name

This locally renames the polymorphic universes of qualid. An underscore means the usual name is printed.

#### Command: About qualid

This displays various information about the object denoted by *qualid*: its kind (module, constant, assumption, inductive, constructor, abbreviation, ...), long name, type, implicit arguments and argument scopes. It does not print the body of definitions or proofs.

## Variant: About qualid@name

This locally renames the polymorphic universes of *qualid*. An underscore means the usual name is printed.

#### Command: Print All

This command displays information about the current state of the environment, including sections and modules.

## Variant: Inspect num

This command displays the num last objects of the current environment, including sections and modules.

#### Variant: Print Section ident

The name *ident* should correspond to a currently open section, this command displays the objects defined since the beginning of this section.

## 5.1.2 Flags, Options and Tables

Coq has many settings to control its behavior. Setting types include flags, options and tables:

- A flag has a boolean value, such as Asymmetric Patterns.
- An option generally has a numeric or string value, such as *Firstorder Depth*.
- A table contains a set of strings or qualids.
- In addition, some commands provide settings, such as Extraction Language.

Flags, options and tables are identified by a series of identifiers, each with an initial capital letter.

Command: Local Global Export Set flag
Sets flag on. Scoping qualifiers are described here.

Command: Local Global Export Unset flag
Sets flag off. Scoping qualifiers are described here.

Command: Test flag

Prints the current value of flag.

Command: Local Global Export Set option num string
Sets option to the specified value. Scoping qualifiers are described here.

Command: Local Global Export Unset option
Sets option to its default value. Scoping qualifiers are described here.

Command: Test option

Prints the current value of option.

Command: Print Options

Prints the current value of all flags and options, and the names of all tables.

Command: Add table string qualid Adds the specified value to table.

Command: Remove table string qualid Removes the specified value from table.

Command: Test table for string qualid

Reports whether table contains the specified value.

Command: Print Table table
Prints the values in table.


Command: Test table

A synonym for Print Table @table.

Command: Print Tables

A synonym for Print Options.

Scope qualifiers for Set and Unset



Flag and option settings can be global in scope or local to nested scopes created by <code>Module</code> and <code>Section</code> commands. There are four alternatives:

• no qualifier: the original setting is *not* restored at the end of the current module or section.

- Local: the setting is applied within the current scope. The original value of the option or flag is restored at the end of the current module or section.
- **Global**: similar to no qualifier, the original setting is *not* restored at the end of the current module or section. In addition, if the value is set in a file, then *Require*-ing the file sets the option.
- Export: similar to Local, the original value of the option or flag is restored at the end of the current module or section. In addition, if the value is set in a file, then Import-ing the file sets the option.

Newly opened scopes inherit the current settings.

## 5.1.3 Requests to the environment

#### Command: Check term

This command displays the type of *term*. When called in proof mode, the term is checked in the local context of the current subgoal.

#### Variant: selector: Check term

This variant specifies on which subgoal to perform typing (see Section *Invocation of tactics*).

#### Command: Eval redexpr in term

This command performs the specified reduction on *term*, and displays the resulting term with its type. The term to be reduced may depend on hypothesis introduced in the first subgoal (if a proof is in progress).

#### See also:

Section Performing computations.

#### Command: Compute term

This command performs a call-by-value evaluation of term by using the bytecode-based virtual machine. It is a shortcut for Eval vm\_compute in term.

#### See also:

Section Performing computations.

## Command: Print Assumptions qualid

This commands display all the assumptions (axioms, parameters and variables) a theorem or definition depends on. Especially, it informs on the assumptions with respect to which the validity of a theorem relies.

#### Variant: Print Opaque Dependencies qualid

Displays the set of opaque constants qualid relies on in addition to the assumptions.

## Variant: Print Transparent Dependencies qualid

Displays the set of transparent constants qualid relies on in addition to the assumptions.

#### Variant: Print All Dependencies qualid

Displays all assumptions and constants qualid relies on.

#### Command: Search qualid

This command displays the name and type of all objects (hypothesis of the current goal, theorems, axioms, etc) of the current context whose statement contains *qualid*. This command is useful to remind the user of the name of library lemmas.

## Error: The reference qualid was not found in the current environment.

There is no constant in the environment named qualid.

#### Variant: Search string

If *string* is a valid identifier, this command displays the name and type of all objects (theorems, axioms, etc) of the current context whose name contains string. If string is a notation's string

denoting some reference *qualid* (referred to by its main symbol as in "+" or by its notation's string as in "\_ + \_" or "\_ 'U' \_", see Section *Notations*), the command works like Search *qualid*.

#### Variant: Search string%ident


The string string must be a notation or the main symbol of a notation which is then interpreted in the scope bound to the delimiting key *ident* (see Section *Local interpretation rules for notations*).

#### Variant: Search term pattern

This searches for all statements or types of definition that contains a subterm that matches the pattern term\_pattern (holes of the pattern are either denoted by \_ or by ?ident when non linear patterns are expected).

# Variant: Search -?term\_pattern\_string

where <code>term\_pattern\_string</code> is a term\_pattern, a string, or a string followed by a scope delimiting key <code>%key</code>. This generalization of <code>Search</code> searches for all objects whose statement or type contains a subterm matching <code>term\_pattern</code> (or <code>qualid</code> if <code>string</code> is the notation for a reference qualid) and whose name contains all string of the request that correspond to valid identifiers. If a term\_pattern or a string is prefixed by <code>-</code>, the search excludes the objects that mention that term\_pattern or that string.



This restricts the search to constructions defined in the modules named by the given qualid sequence.

```
Variant: Search -? term_pattern_string outside qualid
```

This restricts the search to constructions not defined in the modules named by the given qualid sequence.

```
Variant: selector: Search -?term_pattern_string
```

This specifies the goal on which to search hypothesis (see Section *Invocation of tactics*). By default the 1st goal is searched. This variant can be combined with other variants presented here.

## Example

```
Require Import ZArith.

Search Z.mul Z.add "distr".

    Z.mul_add_distr_1: forall n m p : Z, (n * (m + p))%Z = (n * m + n * p)%Z
    Z.mul_add_distr_r: forall n m p : Z, ((n + m) * p)%Z = (n * p + m * p)%Z
    fast_Zmult_plus_distr_1:
        forall (n m p : Z) (P : Z -> Prop),
        P (n * p + m * p)%Z -> P ((n + m) * p)%Z

Search "+"%Z "*"%Z "distr" -positive -Prop.
    Z.mul_add_distr_1: forall n m p : Z, (n * (m + p))%Z = (n * m + n * p)%Z
    Z.mul_add_distr_r: forall n m p : Z, ((n + m) * p)%Z = (n * p + m * p)%Z

Search (?x * _ + ?x * _)%Z outside OmegaLemmas.
    Z.mul_add_distr_1: forall n m p : Z, (n * (m + p))%Z = (n * m + n * p)%Z
```

#### Variant: SearchAbout

Deprecated since version 8.5.

Up to Coq version 8.4, Search had the behavior of current SearchHead and the behavior of current Search was obtained with command SearchAbout. For compatibility, the deprecated name SearchAbout can still be used as a synonym of Search. For compatibility, the list of objects to search when using SearchAbout may also be enclosed by optional [ ] delimiters.

#### Command: SearchHead term

This command displays the name and type of all hypothesis of the current goal (if any) and theorems of the current context whose statement's conclusion has the form (term t1 .. tn). This command is useful to remind the user of the name of library lemmas.

#### Example

```
SearchHead le.
    le_n: forall n : nat, n <= n
    le_0_n: forall n : nat, 0 <= n
    le_S: forall n m : nat, n <= m -> n <= S m
    le_pred: forall n m : nat, n <= m -> Nat.pred n <= Nat.pred m
    le_n_S: forall n m : nat, n <= m -> S n <= S m
    le_S_n: forall n m : nat, S n <= S m -> n <= m</pre>
SearchHead (@eq bool).
    andb_true_intro:
        forall b1 b2 : bool, b1 = true /\ b2 = true -> (b1 && b2)%bool = true
```

## Variant: SearchHead term inside qualid

This restricts the search to constructions defined in the modules named by the given qualid sequence.

```
Variant: SearchHead term outside qualid +
```

This restricts the search to constructions not defined in the modules named by the given qualid sequence.

#### Error: Module/section qualid not found.

No module qualid has been required (see Section Compiled files).

#### Variant: selector: SearchHead term

This specifies the goal on which to search hypothesis (see Section *Invocation of tactics*). By default the 1st goal is searched. This variant can be combined with other variants presented here.

Note: Up to Coq version 8.4, SearchHead was named Search.

#### Command: SearchPattern term

This command displays the name and type of all hypothesis of the current goal (if any) and theorems of the current context whose statement's conclusion or last hypothesis and conclusion matches the expression where holes in the latter are denoted by \_. It is a variant of Search term\_pattern that does not look for subterms but searches for statements whose conclusion has exactly the expected form, or whose statement finishes by the given series of hypothesis/conclusion.

#### Example

Require Import Arith.

```
SearchPattern ( +  =  + ).
   Nat.add\_comm: forall n m : nat, n + m = m + n
   plus_Snm_nSm: forall n m : nat, S n + m = n + S m
    Nat.add_succ_comm: forall n m : nat, S n + m = n + S m
   Nat.add_shuffle3: forall n m p : nat, n + (m + p) = m + (n + p)
   plus_assoc_reverse: forall n m p : nat, n + m + p = n + (m + p)
    Nat.add_assoc: forall n m p : nat, n + (m + p) = n + m + p
   Nat.add_shuffle0: forall n m p : nat, n + m + p = n + p + m
    f_equal2_plus:
      forall x1 y1 x2 y2 : nat, x1 = y1 -> x2 = y2 -> x1 + x2 = y1 + y2
    Nat.add\_shuffle2: forall n m p q : nat, n + m + (p + q) = n + q + (m + p)
   Nat.add_shuffle1: forall n m p q : nat, n + m + (p + q) = n + p + (m + q)
SearchPattern (nat -> bool).
   Nat.odd: nat -> bool
    Init.Nat.odd: nat -> bool
    Nat.even: nat -> bool
    Init.Nat.even: nat -> bool
    Init.Nat.testbit: nat -> nat -> bool
   Nat.leb: nat -> nat -> bool
   Nat.eqb: nat -> nat -> bool
    Init.Nat.eqb: nat -> nat -> bool
   Nat.ltb: nat -> nat -> bool
   Nat.testbit: nat -> nat -> bool
    Init.Nat.leb: nat -> nat -> bool
    Init.Nat.ltb: nat -> nat -> bool
   BinNat.N.testbit_nat: BinNums.N -> nat -> bool
   BinPosDef.Pos.testbit_nat: BinNums.positive -> nat -> bool
   BinPos.Pos.testbit_nat: BinNums.positive -> nat -> bool
    BinNatDef.N.testbit_nat: BinNums.N -> nat -> bool
SearchPattern (forall 1 : list _, _ 1 1).
   List.incl_refl: forall (A : Type) (1 : list A), List.incl 1 1
   List.lel_refl: forall (A : Type) (1 : list A), List.lel 1 1
```

Patterns need not be linear: you can express that the same expression must occur in two places by using pattern variables ?ident.

## Example

```
SearchPattern (?X1 + _ = _ + ?X1).
Nat.add_comm: forall n m : nat, n + m = m + n
```

# Variant: SearchPattern term inside qualid +

This restricts the search to constructions defined in the modules named by the given qualid sequence.

# Variant: SearchPattern term outside qualid +

This restricts the search to constructions not defined in the modules named by the given qualid sequence.

#### Variant: selector: SearchPattern term

This specifies the goal on which to search hypothesis (see Section *Invocation of tactics*). By default the 1st goal is searched. This variant can be combined with other variants presented here.

#### Command: SearchRewrite term

This command displays the name and type of all hypothesis of the current goal (if any) and theorems of the current context whose statement's conclusion is an equality of which one side matches the expression term. Holes in term are denoted by "\_\_".

#### Example

```
Require Import Arith.

SearchRewrite (_ + _ + _ ).
    Nat.add_shuffle0: forall n m p : nat, n + m + p = n + p + m
    plus_assoc_reverse: forall n m p : nat, n + m + p = n + (m + p)
    Nat.add_assoc: forall n m p : nat, n + (m + p) = n + m + p
    Nat.add_shuffle1: forall n m p q : nat, n + m + (p + q) = n + p + (m + q)
    Nat.add_shuffle2: forall n m p q : nat, n + m + (p + q) = n + q + (m + p)
    Nat.add_carry_div2:
    forall (a b : nat) (c0 : bool),
        (a + b + Nat.b2n c0) / 2 =
        a / 2 + b / 2 +
    Nat.b2n
        (Nat.testbit a 0 && Nat.testbit b 0
        | | c0 && (Nat.testbit a 0 | | Nat.testbit b 0))
```

## Variant: SearchRewrite term inside qualid +

This restricts the search to constructions defined in the modules named by the given qualid sequence.

## Variant: SearchRewrite term outside qualid

This restricts the search to constructions not defined in the modules named by the given qualid sequence.

#### Variant: selector: SearchRewrite term

This specifies the goal on which to search hypothesis (see Section *Invocation of tactics*). By default the 1st goal is searched. This variant can be combined with other variants presented here.

### Note:

## Table: Search Blacklist string

Specifies a set of strings used to exclude lemmas from the results of <code>Search</code>, <code>SearchHead</code>, <code>SearchPattern</code> and <code>SearchRewrite</code> queries. A lemma whose fully-qualified name contains any of the strings will be excluded from the search results. The default blacklisted substrings are <code>\_subterm</code>, <code>\_subproof</code> and <code>Private\_</code>.

Use the Add Otable and Remove Otable commands to update the set of blacklisted strings.

## Command: Locate qualid

This command displays the full name of objects whose name is a prefix of the qualified identifier *qualid*, and consequently the Coq module in which they are defined. It searches for objects from the different qualified namespaces of Coq: terms, modules, Ltac, etc.

## Example

```
Locate nat.
    Inductive Coq.Init.Datatypes.nat

Locate Datatypes.O.
    Constructor Coq.Init.Datatypes.O
        (shorter name to refer to it in current context is 0)

Locate Init.Datatypes.O.
    Constructor Coq.Init.Datatypes.O
        (shorter name to refer to it in current context is 0)

Locate Coq.Init.Datatypes.O.
    Constructor Coq.Init.Datatypes.O
        (shorter name to refer to it in current context is 0)

Locate Coq.Init.Datatypes.O
        (shorter name to refer to it in current context is 0)

Locate I.Dont.Exist.
    No object of suffix I.Dont.Exist
```

Variant: Locate Term qualid

As Locate but restricted to terms.

Variant: Locate Module qualid

As Locate but restricted to modules.

Variant: Locate Ltac qualid

As Locate but restricted to tactics.

#### See also:

Section Locating notations

## 5.1.4 Printing flags

#### Flag: Fast Name Printing

When turned on, Coq uses an asymptotically faster algorithm for the generation of unambiguous names of bound variables while printing terms. While faster, it is also less clever and results in a typically less elegant display, e.g. it will generate more names rather than reusing certain names across subterms. This flag is not enabled by default, because as Ltac observes bound names, turning it on can break existing proof scripts.

#### 5.1.5 Loading files

Coq offers the possibility of loading different parts of a whole development stored in separate files. Their contents will be loaded as if they were entered from the keyboard. This means that the loaded files are ASCII files containing sequences of commands for Coq's toplevel. This kind of file is called a *script* for Coq. The standard (and default) extension of Coq's script files is .v.

#### Command: Load ident

This command loads the file named ident.v, searching successively in each of the directories specified in the loadpath. (see Section Libraries and filesystem)

Files loaded this way cannot leave proofs open, and the Load command cannot be used inside a proof either.

#### Variant: Load string

Loads the file denoted by the string string, where string is any complete filename. Then the ~

and .. abbreviations are allowed as well as shell variables. If no extension is specified, Coq will use the default extension .v.

Variant: Load Verbose ident Variant: Load Verbose string

Display, while loading, the answers of Coq to each command (including tactics) contained in the loaded file.

See also:

Section Controlling display.

Error: Can't find file *ident* on loadpath.

Error: Load is not supported inside proofs.

Error: Files processed by Load cannot leave open proofs.

## 5.1.6 Compiled files

This section describes the commands used to load compiled files (see Chapter *The Coq commands* for documentation on how to compile a file). A compiled file is a particular case of module called *library file*.

#### Command: Require qualid

This command looks in the loadpath for a file containing module *qualid* and adds the corresponding module to the environment of Coq. As library files have dependencies in other library files, the command *Require qualid* recursively requires all library files the module qualid depends on and adds the corresponding modules to the environment of Coq too. Coq assumes that the compiled files have been produced by a valid Coq compiler and their contents are then not replayed nor rechecked.

To locate the file in the file system, *qualid* is decomposed under the form dirpath. *ident* and the file *ident*.vo is searched in the physical directory of the file system that is mapped in Coq loadpath to the logical path dirpath (see Section *Libraries and filesystem*). The mapping between physical directories and logical names at the time of requiring the file must be consistent with the mapping used to compile the file. If several files match, one of them is picked in an unspecified fashion.

### Variant: Require Import qualid

This loads and declares the module *qualid* and its dependencies then imports the contents of *qualid* as described *here*. It does not import the modules on which qualid depends unless these modules were themselves required in module *qualid* using *Require Export*, as described below, or recursively required through a sequence of *Require Export*. If the module required has already been loaded, *Require Import qualid* simply imports it, as *Import qualid* would.

## Variant: Require Export qualid

This command acts as Require Import qualid, but if a further module, say A, contains a command Require Export B, then the command Require Import A also imports the module B.

Variant: Require Import Export qualid

This loads the modules named by the *qualid* sequence and their recursive dependencies. If Import or Export is given, it also imports these modules and all the recursive dependencies that were marked or transitively marked as Export.

#### Variant: From dirpath Require qualid

This command acts as *Require*, but picks any library whose absolute name is of the form *dirpath*. *dirpath'*. *qualid* for some *dirpath'*. This is useful to ensure that the *qualid* library comes from a given package by making explicit its absolute root.

Error: Cannot load qualid: no physical path bound to dirpath.

#### Error: Cannot find library foo in loadpath.

The command did not find the file foo.vo. Either foo.v exists but is not compiled or foo.vo is in a directory which is not in your LoadPath (see Section *Libraries and filesystem*).

#### Error: Compiled library ident.vo makes inconsistent assumptions over library qualid.

The command tried to load library file *ident*.vo that depends on some specific version of library *qualid* which is not the one already loaded in the current Coq session. Probably *ident*.v was not properly recompiled with the last version of the file containing module *qualid*.

## Error: Bad magic number.

The file *ident*.vo was found but either it is not a Coq compiled module, or it was compiled with an incompatible version of Coq.

## Error: The file :n: `ident.vo` contains library dirpath and not library dirpath'.

The library file *dirpath*' is indirectly required by the Require command but it is bound in the current loadpath to the file *ident*.vo which was bound to a different library name dirpath at the time it was compiled.

#### Error: Require is not allowed inside a module or a module type.

This command is not allowed inside a module or a module type being defined. It is meant to describe a dependency between compilation units. Note however that the commands Import and Export alone can be used inside modules (see Section *Import*).

#### See also:

Chapter The Coq commands

#### Command: Print Libraries

This command displays the list of library files loaded in the current Coq session.

## Command: Declare ML Module string +

This commands loads the OCaml compiled files with names given by the *string* sequence (dynamic link). It is mainly used to load tactics dynamically. The files are searched into the current OCaml loadpath (see the command *Add ML Path*). Loading of OCaml files is only possible under the bytecode version of coqtop (i.e. coqtop called with option -byte, see chapter *The Coq commands*), or when Coq has been compiled with a version of OCaml that supports native Dynlink (3.11).

## Variant: Local Declare ML Module string

This variant is not exported to the modules that import the module where they occur, even if outside a section.

Error: File not found on loadpath: string.

Error: Loading of ML object file forbidden in a native Coq.

#### Command: Print ML Modules

This prints the name of all OCaml modules loaded with *Declare ML Module*. To know from where these module were loaded, the user should use the command *Locate File*.

## 5.1.7 Loadpath

Loadpaths are preferably managed using Coq command line options (see Section libraries-and-filesystem) but there remain vernacular commands to manage them for practical purposes. Such commands are only meant to be issued in the toplevel, and using them in source files is discouraged.

#### Command: Pwd

This command displays the current working directory.

#### Command: Cd string

This command changes the current directory according to string which can be any valid path.

#### Variant: Cd

Is equivalent to Pwd.

## Command: Add LoadPath string as dirpath

This command is equivalent to the command line option -Q string dirpath. It adds the physical directory string to the current Coq loadpath and maps it to the logical directory dirpath.

## Variant: Add LoadPath string

Performs as Add LoadPath string dirpath but for the empty directory path.

## Command: Add Rec LoadPath string as dirpath

This command is equivalent to the command line option -R string dirpath. It adds the physical directory string and all its subdirectories to the current Coq loadpath.

#### Variant: Add Rec LoadPath string

Works as Add Rec LoadPath string as dirpath but for the empty logical directory path.

#### Command: Remove LoadPath string

This command removes the path *string* from the current Coq loadpath.

#### Command: Print LoadPath

This command displays the current Coq loadpath.

#### Variant: Print LoadPath dirpath

Works as Print LoadPath but displays only the paths that extend the dirpath prefix.

#### Command: Add ML Path string

This command adds the path *string* to the current OCaml loadpath (see the command Declare ML Module` in Section *Compiled files*).

## Command: Add Rec ML Path string

This command adds the directory *string* and all its subdirectories to the current OCaml loadpath (see the command *Declare ML Module*).

#### Command: Print ML Path string

This command displays the current OCaml loadpath. This command makes sense only under the bytecode version of coqtop, i.e. using option -byte (see the command Declare ML Module in Section Compiled files).

#### Command: Locate File string

This command displays the location of file string in the current loadpath. Typically, string is a .cmo or .vo or .v file.

#### Command: Locate Library dirpath

This command gives the status of the Coq module dirpath. It tells if the module is loaded and if not searches in the load path for a module of logical name *dirpath*.

## 5.1.8 Backtracking

The backtracking commands described in this section can only be used interactively, they cannot be part of a vernacular file loaded via Load or compiled by coqc.

#### Command: Reset ident

This command removes all the objects in the environment since *ident* was introduced, including *ident*. *ident* may be the name of a defined or declared object as well as the name of a section. One cannot reset over the name of a module or of an object inside a module.

Error: ident: no such entry.

#### Variant: Reset Initial

Goes back to the initial state, just after the start of the interactive session.

#### Command: Back

This command undoes all the effects of the last vernacular command. Commands read from a vernacular file via a *Load* are considered as a single command. Proof management commands are also handled by this command (see Chapter *Proof handling*). For that, Back may have to undo more than one command in order to reach a state where the proof management information is available. For instance, when the last command is a *Qed*, the management information about the closed proof has been discarded. In this case, *Back* will then undo all the proof steps up to the statement of this proof.

#### Variant: Back num

Undo *num* vernacular commands. As for Back, some extra commands may be undone in order to reach an adequate state. For instance Back *num* will not re-enter a closed proof, but rather go just before that proof.

#### Error: Invalid backtrack.

The user wants to undo more commands than available in the history.

#### Command: BackTo num

This command brings back the system to the state labeled <code>num</code>, forgetting the effect of all commands executed after this state. The state label is an integer which grows after each successful command. It is displayed in the prompt when in -emacs mode. Just as <code>Back</code> (see above), the <code>BackTo</code> command now handles proof states. For that, it may have to undo some extra commands and end on a state <code>num num</code> if necessary.

## 5.1.9 Quitting and debugging

#### Command: Quit

This command permits to quit Coq.

#### Command: Drop

This is used mostly as a debug facility by Coq's implementers and does not concern the casual user. This command permits to leave Coq temporarily and enter the OCaml toplevel. The OCaml command:

```
#use "include";;
```

adds the right loadpaths and loads some toplevel printers for all abstract types of Coq- section\_path, identifiers, terms, judgments, .... You can also use the file base\_include instead, that loads only the pretty-printers for section\_paths and identifiers. You can return back to Coq with the command:

go();;

## Warning:

- 1. It only works with the bytecode version of Coq (i.e. coqtop.byte, see Section interactive-use).
- 2. You must have compiled Coq from the source package and set the environment variable COQTOP to the root of your copy of the sources (see Section customization-by-environment-variables).

#### Command: Time command

This command executes the vernacular command command and displays the time needed to execute it.

#### Command: Redirect string command

This command executes the vernacular command command, redirecting its output to "string.out".

#### Command: Timeout num command

This command executes the vernacular command *command*. If the command has not terminated after the time specified by the *num* (time expressed in seconds), then it is interrupted and an error message is displayed.

#### Option: Default Timeout num

This option controls a default timeout for subsequent commands, as if they were passed to a *Timeout* command. Commands already starting by a *Timeout* are unaffected.

#### Command: Fail command

For debugging scripts, sometimes it is desirable to know whether a command or a tactic fails. If the given *command* fails, then Fail *command* succeeds (excepts in the case of critical errors, like a "stack overflow"), without changing the proof state, and in interactive mode, the system prints a message confirming the failure.

#### Error: The command has not failed!

If the given *command* succeeds, then Fail *command* fails with this error message.

## 5.1.10 Controlling display

#### Flag: Silent

This flag controls the normal displaying.



This option configures the display of warnings. It is experimental, and expects, between quotes, a comma-separated list of warning names or categories. Adding - in front of a warning or category disables it, adding + makes it an error. It is possible to use the special categories all and default, the latter containing the warnings enabled by default. The flags are interpreted from left to right, so in case of an overlap, the flags on the right have higher priority, meaning that A,-A is equivalent to -A.

## Flag: Search Output Name Only

This flag restricts the output of search commands to identifier names; turning it on causes invocations of Search, SearchHead, SearchPattern, SearchRewrite etc. to omit types from their output, printing only identifiers.

#### Option: Printing Width num

This command sets which left-aligned part of the width of the screen is used for display. At the time of writing this documentation, the default value is 78.

## Option: Printing Depth num

This option controls the nesting depth of the formatter used for pretty- printing. Beyond this depth, display of subterms is replaced by dots. At the time of writing this documentation, the default value is 50.

## Flag: Printing Compact Contexts

This flag controls the compact display mode for goals contexts. When on, the printer tries to reduce the vertical size of goals contexts by putting several variables (even if of different types) on the same line provided it does not exceed the printing width (see *Printing Width*). At the time of writing this documentation, it is off by default.

#### Flag: Printing Unfocused

This flag controls whether unfocused goals are displayed. Such goals are created by focusing other goals with bullets (see *Bullets* or *curly braces*). It is off by default.

#### Flag: Printing Dependent Evars Line

This flag controls the printing of the "(dependent evars: ...)" information after each tactic. The information is used by the Prooftree tool in Proof General. (https://askra.de/software/prooftree)

## 5.1.11 Controlling the reduction strategies and the conversion algorithm

Coq provides reduction strategies that the tactics can invoke and two different algorithms to check the convertibility of types. The first conversion algorithm lazily compares applicative terms while the other is a brute-force but efficient algorithm that first normalizes the terms before comparing them. The second algorithm is based on a bytecode representation of terms similar to the bytecode representation used in the ZINC virtual machine [Ler90]. It is especially useful for intensive computation of algebraic values, such as numbers, and for reflection-based tactics. The commands to fine- tune the reduction strategies and the lazy conversion algorithm are described first.

# Command: Opaque qualid

This command has an effect on unfoldable constants, i.e. on constants defined by Definition or Let (with an explicit body), or by a command assimilated to a definition such as Fixpoint, Program Definition, etc, or by a proof ended by Defined. The command tells not to unfold the constants in the qualid sequence in tactics using  $\delta$ -conversion (unfolding a constant is replacing it by its definition).

*Opaque* has also an effect on the conversion algorithm of Coq, telling it to delay the unfolding of a constant as much as possible when Coq has to check the conversion (see Section *Conversion rules*) of two distinct applied constants.

# Variant: Global Opaque qualid +

The scope of Opaque is limited to the current section, or current file, unless the variant Global Opaque is used.

#### See also:

Sections Performing computations, Automating, Switching on/off the proof editing mode

#### Error: The reference qualid was not found in the current environment.

There is no constant referred by *qualid* in the environment. Nevertheless, if you asked *Opaque* foo bar and if bar does not exist, foo is set opaque.

## Command: Transparent qualid

This command is the converse of *Opaque* and it applies on unfoldable constants to restore their unfoldability after an Opaque command.

Note in particular that constants defined by a proof ended by Qed are not unfoldable and Transparent has no effect on them. This is to keep with the usual mathematical practice of *proof irrelevance*: what matters in a mathematical development is the sequence of lemma statements, not their actual proofs. This distinguishes lemmas from the usual defined constants, whose actual values are of course relevant in general.

# Variant: Global Transparent qualid +

The scope of Transparent is limited to the current section, or current file, unless the variant Global Transparent is used.

## Error: The reference qualid was not found in the current environment.

There is no constant referred by qualid in the environment.

#### See also:

Sections Performing computations, Automating, Switching on/off the proof editing mode

# Command: Strategy level [ qualid | ]

This command generalizes the behavior of Opaque and Transparent commands. It is used to fine-tune the strategy for unfolding constants, both at the tactic level and at the kernel level. This command associates a level to the qualified names in the *qualid* sequence. Whenever two expressions with two distinct head constants are compared (for instance, this comparison can be triggered by a type cast), the one with lower level is expanded first. In case of a tie, the second one (appearing in the cast type) is expanded.

Levels can be one of the following (higher to lower):

- opaque : level of opaque constants. They cannot be expanded by tactics (behaves like  $+\infty$ , see next item).
- num: levels indexed by an integer. Level 0 corresponds to the default behavior, which corresponds to transparent constants. This level can also be referred to as transparent. Negative levels correspond to constants to be expanded before normal transparent constants, while positive levels correspond to constants to be expanded after normal transparent constants.
- expand: level of constants that should be expanded first (behaves like  $-\infty$ )

## Variant: Local Strategy level [ qualid ]

These directives survive section and module closure, unless the command is prefixed by Local. In the latter case, the behavior regarding sections and modules is the same as for the *Transparent* and *Opaque* commands.

#### Command: Print Strategy qualid

This command prints the strategy currently associated to *qualid*. It fails if *qualid* is not an unfoldable reference, that is, neither a variable nor a constant.

Error: The reference is not unfoldable.

#### Variant: Print Strategies

Print all the currently non-transparent strategies.

## Command: Declare Reduction ident := redexpr

This command allows giving a short name to a reduction expression, for instance lazy beta delta [foo bar]. This short name can then be used in Eval *ident* in or eval directives. This command accepts the Local modifier, for discarding this reduction name at the end of the file or module. For the moment, the name is not qualified. In particular declaring the same name in several modules or in several functor applications will be rejected if these declarations are not local. The name *ident* cannot be used directly as an Ltac tactic, but nothing prevents the user from also performing a Ltac *ident*:= redexpr.

#### See also:

Performing computations

## 5.1.12 Controlling the locality of commands

# Command: Local command Command: Global command

Some commands support a Local or Global prefix modifier to control the scope of their effect. There are four kinds of commands:

• Commands whose default is to extend their effect both outside the section and the module or library file they occur in. For these commands, the Local modifier limits the effect of the command

to the current section or module it occurs in. As an example, the *Coercion* and *Strategy* commands belong to this category.

- Commands whose default behavior is to stop their effect at the end of the section they occur in but to extend their effect outside the module or library file they occur in. For these commands, the Local modifier limits the effect of the command to the current module if the command does not occur in a section and the Global modifier extends the effect outside the current sections and current module if the command occurs in a section. As an example, the Arguments, Ltac or Notation commands belong to this category. Notice that a subclass of these commands do not support extension of their scope outside sections at all and the Global modifier is not applicable to them.
- Commands whose default behavior is to stop their effect at the end of the section or module they occur in. For these commands, the Global modifier extends their effect outside the sections and modules they occur in. The *Transparent* and *Opaque* (see Section *Controlling the reduction strategies and the conversion algorithm*) commands belong to this category.
- Commands whose default behavior is to extend their effect outside sections but not outside modules when they occur in a section and to extend their effect outside the module or library file they occur in when no section contains them. For these commands, the Local modifier limits the effect to the current section or module while the Global modifier extends the effect outside the module even when the command occurs in a section. The <code>Set</code> and <code>Unset</code> commands belong to this category.

## 5.1.13 Controlling Typing Flags

#### Flag: Guard Checking

This flag can be used to enable/disable the guard checking of fixpoints. Warning: this can break the consistency of the system, use at your own risk. Decreasing argument can still be specified: the decrease is not checked anymore but it still affects the reduction of the term. Unchecked fixpoints are printed by *Print Assumptions*.

## Flag: Positivity Checking

This flag can be used to enable/disable the positivity checking of inductive types and the productivity checking of coinductive types. Warning: this can break the consistency of the system, use at your own risk. Unchecked (co)inductive types are printed by *Print Assumptions*.

#### Flag: Universe Checking

This flag can be used to enable/disable the checking of universes, providing a form of "type in type". Warning: this breaks the consistency of the system, use at your own risk. Constants relying on "type in type" are printed by *Print Assumptions*. It has the same effect as -type-in-type command line argument (see *By command line options*).

#### Command: Print Typing Flags

Print the status of the three typing flags: guard checking, positivity checking and universe checking.

## Example

```
Unset Guard Checking.
Print Typing Flags.
    check_guarded: false
    check_positive: true
    check_universes: true

Fixpoint f (n : nat) : False
    := f n.
```

(continued from previous page)

```
f is defined
f is recursively defined (decreasing on 1st argument)

Fixpoint ackermann (m n : nat) {struct m} : nat :=
    match m with
    | 0 => S n
    | S m =>
        match n with
    | 0 => ackermann m 1
    | S n => ackermann m (ackermann (S m) n)
    end
end.
    ackermann is defined
    ackermann is recursively defined (decreasing on 1st argument)

Print Assumptions ackermann.
    Axioms:
    ackermann is assumed to be guarded.
```

Note that the proper way to define the Ackermann function is to use an inner fixpoint:

```
Fixpoint ack m :=
  fix ackm n :=
  match m with
  | 0 => S n
  | S m' =>
  match n with
  | 0 => ack m' 1
  | S n' => ack m' (ackm n')
  end
end.
  ack is defined
  ack is recursively defined (decreasing on 1st argument)
```

## **5.1.14** Internal registration commands

Due to their internal nature, the commands that are presented in this section are not for general use. They are meant to appear only in standard libraries and in support libraries of plug-ins.

#### **Exposing constants to OCaml libraries**

#### Command: Register qualid, as qualid,

This command exposes the constant  $qualid_1$  to OCaml libraries under the name  $qualid_2$ . This constant can then be dynamically located calling Coqlib.lib\_ref " $qualid_2$ "; i.e., there is no need to known where is the constant defined (file, module, library, etc.).

As a special case, when the first segment of  $qualid_2$  is kernel, the constant is exposed to the kernel. For instance, the Int63 module features the following declaration:

```
Register bool as kernel.ind_bool.
```

This makes the kernel aware of what is the type of boolean values. This information is used for instance to define the return type of the #int63\_eq primitive.

## See also:

Primitive Integers

#### Inlining hints for the fast reduction machines

## Command: Register Inline qualid

This command gives as a hint to the reduction machines (VM and native) that the body of the constant qualid should be inlined in the generated code.

## Registering primitive operations

## Command: Primitive ident; := #ident;.

Declares *ident*<sub>1</sub> as the primitive operator #*ident*<sub>2</sub>. When running this command, the type of the primitive should be already known by the kernel (this is achieved through this command for primitive types and through the *Register* command with the kernel name-space for other types).

## 5.2 Proof handling

In Coq's proof editing mode all top-level commands documented in Chapter *Vernacular commands* remain available and the user has access to specialized commands dealing with proof development pragmas documented in this section. They can also use some other specialized commands called *tactics*. They are the very tools allowing the user to deal with logical reasoning. They are documented in Chapter *Tactics*.

Coq user interfaces usually have a way of marking whether the user has switched to proof editing mode. For instance, in coqtop the prompt Coq < i is changed into ident < i where ident is the declared name of the theorem currently edited.

At each stage of a proof development, one has a list of goals to prove. Initially, the list consists only in the theorem itself. After having applied some tactics, the list of goals contains the subgoals generated by the tactics.

To each subgoal is associated a number of hypotheses called the *local context* of the goal. Initially, the local context contains the local variables and hypotheses of the current section (see Section *Assumptions*) and the local variables and hypotheses of the theorem statement. It is enriched by the use of certain tactics (see e.g. *intro*).

When a proof is completed, the message Proof completed is displayed. One can then register this proof as a defined constant in the environment. Because there exists a correspondence between proofs and terms of  $\lambda$ -calculus, known as the *Curry-Howard isomorphism* [How80][Bar81][GLT89][Hue89], Coq stores proofs as terms of Cic. Those terms are called *proof terms*.

#### Error: No focused proof.

Coq raises this error message when one attempts to use a proof editing command out of the proof editing mode.

## 5.2.1 Switching on/off the proof editing mode

The proof editing mode is entered by asserting a statement, which typically is the assertion of a theorem using an assertion command like *Theorem*. The list of assertion commands is given in *Assertions and proofs*. The command *Goal* can also be used.

5.2. Proof handling 253

#### Command: Goal form

This is intended for quick assertion of statements, without knowing in advance which name to give to the assertion, typically for quick testing of the provability of a statement. If the proof of the statement is eventually completed and validated, the statement is then bound to the name Unnamed\_thm (or a variant of this name not already used for another statement).

#### Command: Qed

This command is available in interactive editing proof mode when the proof is completed. Then *Qed* extracts a proof term from the proof script, switches back to Coq top-level and attaches the extracted proof term to the declared name of the original goal. This name is added to the environment as an opaque constant.

Error: Attempt to save an incomplete proof.

**Note:** Sometimes an error occurs when building the proof term, because tactics do not enforce completely the term construction constraints.

The user should also be aware of the fact that since the proof term is completely rechecked at this point, one may have to wait a while when the proof is large. In some exceptional cases one may even incur a memory overflow.

#### Variant: Defined

Same as *Qed* but the proof is then declared transparent, which means that its content can be explicitly used for type checking and that it can be unfolded in conversion tactics (see *Performing computations*, *Opaque*, *Transparent*).

#### Variant: Save ident

Forces the name of the original goal to be *ident*. This command (and the following ones) can only be used if the original goal has been opened using the *Goal* command.

#### Command: Admitted

This command is available in interactive editing mode to give up the current proof and declare the initial goal as an axiom.

#### Command: Abort

This command cancels the current proof development, switching back to the previous proof development, or to the Coq toplevel if no other proof was edited.

Error: No focused proof (No proof-editing in progress).

#### Variant: Abort ident

Aborts the editing of the proof named *ident* (in case you have nested proofs).

#### See also:

Nested Proofs Allowed

#### Variant: Abort All

Aborts all current goals.

#### Command: Proof term

This command applies in proof editing mode. It is equivalent to exact *term*. Qed. That is, you have to give the full proof in one gulp, as a proof term (see Section *Applying theorems*).

## Command: Proof

Is a no-op which is useful to delimit the sequence of tactic commands which start a proof, after a Theorem command. It is a good practice to use Proof as an opening parenthesis, closed in the script with a closing Qed.

See also:

## Proof with

# Command: Proof using ident

This command applies in proof editing mode. It declares the set of section variables (see *Assumptions*) used by the proof. At *Qed* time, the system will assert that the set of section variables actually used in the proof is a subset of the declared one.

The set of declared variables is closed under type dependency. For example, if T is a variable and a is a variable of type T, then the commands Proof using a and Proof using T a are equivalent.

## Variant: Proof using ident with tactic

Combines in a single line Proof with and Proof using.

#### See also:

Setting implicit automation tactics

## Variant: Proof using All

Use all section variables.

## Variant: Proof using Type ?

Use only section variables occurring in the statement.

## Variant: Proof using Type\*

The \* operator computes the forward transitive closure. E.g. if the variable H has type p < 5 then H is in p\* since p occurs in the type of H. Type\* is the forward transitive closure of the entire set of section variables occurring in the statement.

## Variant: Proof using -(ident)

Use all section variables except the list of *ident*.

### Variant: Proof using collection, + collection,

Use section variables from the union of both collections. See *Name a set of section hypotheses for Proof using* to know how to form a named collection.

#### Variant: Proof using collection<sub>1</sub> - collection<sub>2</sub>

Use section variables which are in the first collection but not in the second one.

## Variant: Proof using collection - (ident)

Use section variables which are in the first collection but not in the list of ident.

#### Variant: Proof using collection \*

Use section variables in the forward transitive closure of the collection. The \* operator binds stronger than + and -.

#### **Proof using options**

The following options modify the behavior of Proof using.

#### Option: Default Proof Using "collection"

Use *collection* as the default Proof using value. E.g. Set Default Proof Using "a b" will complete all Proof commands not followed by a using part with using a b.

## Flag: Suggest Proof Using

When Qed is performed, suggest a using annotation if the user did not provide one.

5.2. Proof handling 255

#### Name a set of section hypotheses for Proof using

## Command: Collection ident := collection

This can be used to name a set of section hypotheses, with the purpose of making Proof using annotations more compact.

## Example

Define the collection named Some containing x, y and z:

```
Collection Some := x y z.
```

Define the collection named Fewer containing only x and y:

```
Collection Fewer := Some - z
```

Define the collection named Many containing the set union or set difference of Fewer and Some:

```
Collection Many := Fewer + Some
Collection Many := Fewer - Some
```

Define the collection named Many containing the set difference of Fewer and the unnamed collection x y:

```
Collection Many := Fewer - (x y)
```

#### Command: Existential num := term

This command instantiates an existential variable. *num* is an index in the list of uninstantiated existential variables displayed by *Show Existentials*.

This command is intended to be used to instantiate existential variables when the proof is completed but some uninstantiated existential variables remain. To instantiate existential variables during proof edition, you should use the tactic *instantiate*.

#### Command: Grab Existential Variables

This command can be run when a proof has no more goal to be solved but has remaining uninstantiated existential variables. It takes every uninstantiated existential variable and turns it into a goal.

#### **Proof modes**

When entering proof mode through commands such as Goal and Proof, Coq picks by default the  $L_{tac}$  mode. Nonetheless, there exist other proof modes shipped in the standard Coq installation, and furthermore some plugins define their own proof modes. The default proof mode used when opening a proof can be changed using the following option.

#### Option: Default Proof Mode string

Select the proof mode to use when starting a proof. Depending on the proof mode, various syntactic constructs are allowed when writing an interactive proof. The possible option values are listed below.

- "Classic": this is the default. It activates the  $L_{\rm tac}$  language to interact with the proof, and also allows vernacular commands.
- "Noedit": this proof mode only allows vernacular commands. No tactic language is activated at all. This is the default when the prelude is not loaded, e.g. through the -noinit option for coqc.
- "Ltac2": this proof mode is made available when requiring the Ltac2 library, and is set to be the default when it is imported. It allows to use the Ltac2 language, as well as vernacular commands.

• Some external plugins also define their own proof mode, which can be activated via this command.

## 5.2.2 Navigation in the proof tree

#### Command: Undo

This command cancels the effect of the last command. Thus, it backtracks one step.

#### Variant: Undo num

Repeats Undo num times.

#### Variant: Restart

This command restores the proof editing process to the original goal.

Error: No focused proof to restart.

#### Command: Focus

This focuses the attention on the first subgoal to prove and the printing of the other subgoals is suspended until the focused subgoal is solved or unfocused. This is useful when there are many current subgoals which clutter your screen.

Deprecated since version 8.8: Prefer the use of bullets or focusing brackets (see below).

#### Variant: Focus num

This focuses the attention on the *num* th subgoal to prove.

Deprecated since version 8.8: Prefer the use of focusing brackets with a goal selector (see below).

#### Command: Unfocus

This command restores to focus the goal that were suspended by the last Focus command.

Deprecated since version 8.8.

#### Command: Unfocused

Succeeds if the proof is fully unfocused, fails if there are some goals out of focus.

## Command: { }

The command { (without a terminating period) focuses on the first goal, much like *Focus* does, however, the subproof can only be unfocused when it has been fully solved ( *i.e.* when there is no focused goal left). Unfocusing is then handled by } (again, without a terminating period). See also an example in the next section.

Note that when a focused goal is proved a message is displayed together with a suggestion about the right bullet or } to unfocus it or focus the next one.

## Variant: num: {

This focuses on the num-th subgoal to prove.

#### Variant: [ident]: {

This focuses on the named goal *ident*.

**Note:** Goals are just existential variables and existential variables do not get a name by default. You can give a name to a goal by using refine ?[ident]. You may also wrap this in an Ltac-definition like:

Ltac name\_goal name := refine ?[name].

#### See also:

Existential variables

5.2. Proof handling 257

#### Example

This first example uses the Ltac definition above, and the named goals only serve for documentation.

```
Goal forall n, n + 0 = n.
   1 subgoal
     _____
     forall n : nat, n + 0 = n
Proof.
induction n; [ name_goal base | name_goal step ].
   2 subgoals
     _____
     0 + 0 = 0
   subgoal 2 is:
    S n + 0 = S n
[base]: {
   1 subgoal
     _____
     0 + 0 = 0
reflexivity.
   This subproof is complete, but there are some unfocused goals.
   Try unfocusing with "}".
   1 subgoal
   subgoal 1 is:
   S n + 0 = S n
}
[step]: {
   1 subgoal
     n : nat
     IHn : n + 0 = n
     _____
     S n + 0 = S n
simpl.
   1 subgoal
     n : nat
     IHn : n + 0 = n
     _____
     S(n + 0) = Sn
f_equal.
   1 subgoal
```

 $({\rm continues\ on\ next\ page})$ 

(continued from previous page)

```
n : nat
     IHn : n + 0 = n
     _____
     n + 0 = n
assumption.
   No more subgoals.
}
Qed.
   No more subgoals.
This can also be a way of focusing on a shelved goal, for instance:
Goal exists n : nat, n = n.
   1 subgoal
     _____
     exists n : nat, n = n
eexists ?[x].
   1 focused subgoal
   (shelved: 1)
     _____
     ?x = ?x
reflexivity.
   All the remaining goals are on the shelf.
   1 subgoal
   subgoal 1 is:
    nat
[x]: exact 0.
   No more subgoals.
Qed.
```

## Error: This proof is focused, but cannot be unfocused this way.

You are trying to use } but the current subproof has not been fully solved.

```
Error: No such goal (num).

Error: No such goal (ident).
```

## Error: Brackets do not support multi-goal selectors.

Brackets are used to focus on a single goal given either by its position or by its name if it has one.

#### See also:

The error messages about bullets below.

5.2. Proof handling 259

#### **Bullets**

Alternatively to { and }, proofs can be structured with bullets. The use of a bullet b for the first time focuses on the first goal g, the same bullet cannot be used again until the proof of g is completed, then it is mandatory to focus the next goal with b. The consequence is that g and all goals present when g was focused are focused with the same bullet b. See the example below.

Different bullets can be used to nest levels. The scope of bullet does not go beyond enclosing  $\{$  and  $\}$ , so bullets can be reused as further nesting levels provided they are delimited by these. Bullets are made of repeated  $\neg$ , + or \* symbols:

Note again that when a focused goal is proved a message is displayed together with a suggestion about the right bullet or } to unfocus it or focus the next one.

Note: In Proof General (Emacs interface to Coq), you must use bullets with the priority ordering shown above to have a correct indentation. For example - must be the outer bullet and \*\* the inner one in the example below.

The following example script illustrates all these features:

#### Example

```
{\tt Goal} \ ((({\tt True} \ / \setminus \ {\tt True}) \ / \setminus \ {\tt True}) \ / \setminus \ {\tt True}.
   1 subgoal
      ______
      (((True /\ True) /\ True) /\ True
Proof.
split.
   2 subgoals
      _____
      ((True /\ True) /\ True) /\ True
   subgoal 2 is:
    True
- split.
   1 subgoal
      ((True /\ True) /\ True) /\ True
   2 subgoals
      _____
      (True /\ True) /\ True
   subgoal 2 is:
    True
+ split.
```

(continued from previous page)

```
1 subgoal
    _____
    (True /\ True) /\ True
  2 subgoals
    _____
    True /\ True
  subgoal 2 is:
   True
** { split.
  1 subgoal
    _____
    True /\ True
  1 subgoal
    _____
    True /\ True
  2 subgoals
    _____
    True
  subgoal 2 is:
   True
- trivial.
  1 subgoal
    _____
    True
  This subproof is complete, but there are some unfocused goals.
  Focus next goal with bullet -.
  4 subgoals
  subgoal 1 is:
   True
  subgoal 2 is:
   True
  subgoal 3 is:
   True
  subgoal 4 is:
   True
- trivial.
  1 subgoal
    _____
```

True

(continued from previous page)

```
This subproof is complete, but there are some unfocused goals.
   Try unfocusing with "}".
   3 subgoals
   subgoal 1 is:
    True
   subgoal 2 is:
    True
   subgoal 3 is:
    True
** trivial.
   This subproof is complete, but there are some unfocused goals.
   Focus next goal with bullet **.
   3 subgoals
   subgoal 1 is:
    True
   subgoal 2 is:
    True
   subgoal 3 is:
    True
   1 subgoal
     _____
     True
   This subproof is complete, but there are some unfocused goals.
   Focus next goal with bullet +.
   2 subgoals
   subgoal 1 is:
    True
   subgoal 2 is:
    True
+ trivial.
   1 subgoal
     _____
     True
   This subproof is complete, but there are some unfocused goals.
   Focus next goal with bullet -.
   1 subgoal
   subgoal 1 is:
    True
```

(continued from previous page)

```
1 subgoal
     _____
     True
   2 subgoals
     _____
     True
   subgoal 2 is:
    True
{ trivial.
   1 subgoal
     _____
     True
   This subproof is complete, but there are some unfocused goals.
   Try unfocusing with "}".
   1 subgoal
   subgoal 1 is:
    True
}
assumption.
   1 subgoal
     H : True
     _____
     True
   No more subgoals.
Qed.
Error: Wrong bullet bullet; Current bullet bullet; is not finished.
     Before using bullet bullet_1 again, you should first finish proving the current focused goal. Note that
     bullet_1 and bullet_2 may be the same.
Error: Wrong bullet bullet_1: Bullet bullet_2 is mandatory here.
     You must put bullet_2 to focus on the next goal. No other bullet is allowed here.
Error: No such goal. Focus next goal with bullet bullet.
     You tried to apply a tactic but no goals were under focus. Using bullet is mandatory here.
Error: No such goal. Try unfocusing with }.
     You just finished a goal focused by {, you must unfocus it with }.
```

- assert True.

5.2. Proof handling 263

## **Mandatory Bullets**

Using *Default Goal Selector* with the ! selector forces tactic scripts to keep focus to exactly one goal (e.g. using bullets) or use explicit goal selectors.

#### Set Bullet Behavior

Option: Bullet Behavior "None" | "Strict Subproofs"

This option controls the bullet behavior and can take two possible values:

- "None": this makes bullets inactive.
- "Strict Subproofs": this makes bullets active (this is the default behavior).

## **5.2.3** Requesting information

Command: Show

This command displays the current goals.

Error: No focused proof.

Variant: Show num

Displays only the num-th subgoal.

Error: No such goal.

Variant: Show ident

Displays the named goal *ident*. This is useful in particular to display a shelved goal but only works if the corresponding existential variable has been named by the user (see *Existential variables*) as in the following example.

#### Example

Variant: Show Proof Diffs removed?

Displays the proof term generated by the tactics that have been applied so far. If the proof

is incomplete, the term will contain holes, which correspond to subterms which are still to be constructed. Each hole is an existential variable, which appears as a question mark followed by an identifier.

Experimental: Specifying "Diffs" highlights the difference between the current and previous proof step. By default, the command shows the output once with additions highlighted. Including "removed" shows the output twice: once showing removals and once showing additions. It does not examine the *Diffs* option. See *Showing differences between proof steps*.

#### Variant: Show Conjectures

It prints the list of the names of all the theorems that are currently being proved. As it is possible to start proving a previous lemma during the proof of a theorem, this list may contain several names.

#### Variant: Show Intro

If the current goal begins by at least one product, this command prints the name of the first product, as it would be generated by an anonymous *intro*. The aim of this command is to ease the writing of more robust scripts. For example, with an appropriate Proof General macro, it is possible to transform any anonymous *intro* into a qualified one such as *intro* y13. In the case of a non-product goal, it prints nothing.

#### Variant: Show Intros

This command is similar to the previous one, it simulates the naming process of an *intros*.

#### Variant: Show Existentials

Displays all open goals / existential variables in the current proof along with the type and the context of each variable.

#### Variant: Show Match ident

This variant displays a template of the Gallina match construct with a branch for each constructor of the type *ident* 

#### Example

Error: Unknown inductive type.

#### Variant: Show Universes

It displays the set of all universe constraints and its normalized form at the current stage of the proof, useful for debugging universe inconsistencies.

#### Variant: Show Goal num at num

This command is only available in coqtop. Displays a goal at a proof state using the goal ID number and the proof state ID number. It is primarily for use by tools such as Prooftree that need to fetch goal history in this way. Prooftree is a tool for visualizing a proof as a tree that runs in Proof General.

#### Command: Guarded

Some tactics (e.g. *refine*) allow to build proofs using fixpoint or co-fixpoint constructions. Due to the incremental nature of interactive proof construction, the check of the termination (or guardedness) of the recursive calls in the fixpoint or cofixpoint constructions is postponed to the time of the completion of the proof.


5.2. Proof handling 265

The command *Guarded* allows checking if the guard condition for fixpoint and cofixpoint is violated at some time of the construction of the proof without having to wait the completion of the proof.

## 5.2.4 Showing differences between proof steps

Coq can automatically highlight the differences between successive proof steps and between values in some error messages. Also, as an experimental feature, Coq can also highlight differences between proof steps shown in the *Show Proof* command, but only, for now, when using coqtop and Proof General.

For example, the following screenshots of CoqIDE and coqtop show the application of the same *intros* tactic. The tactic creates two new hypotheses, highlighted in green. The conclusion is entirely in pale green because although it's changed, no tokens were added to it. The second screenshot uses the "removed" option, so it shows the conclusion a second time with the old text, with deletions marked in red. Also, since the hypotheses are new, no line of old text is shown for them.



This image shows an error message with diff highlighting in CoqIDE:

```
Unable to unify "(if p a then 1 else 0) + (count p \bullet \bullet \bullet + count p \bullet \bullet \bullet)" with "(if p a then 1 else 0) + (count p \bullet \bullet \bullet + count p \bullet \bullet \bullet)".
```

#### How to enable diffs

#### Option: Diffs "on" | "off" | "removed"

The "on" setting highlights added tokens in green, while the "removed" setting additionally reprints items with removed tokens in red. Unchanged tokens in modified items are shown with pale green or red. Diffs in error messages use red and green for the compared values; they appear regardless of the setting. (Colors are user-configurable.)

For coqtop, showing diffs can be enabled when starting coqtop with the -diffs on of premoved command-line option or by setting the *Diffs* option within Coq. You will need to provide the -color on auto command-line option when you start coqtop in either case.

Colors for coqtop can be configured by setting the COQ\_COLORS environment variable. See section *By environment variables*. Diffs use the tags diff.added, diff.added.bg, diff.removed and diff.removed.bg.

In CoqIDE, diffs should be enabled from the View menu. Don't use the Set Diffs command in CoqIDE. You can change the background colors shown for diffs from the Edit | Preferences | Tags panel by changing the settings for the diff.added, diff.added.bg, diff.removed and diff.removed.bg tags. This panel also lets you control other attributes of the highlights, such as the foreground color, bold, italic, underline and strikeout.

As of June 2019, Proof General can also display Coq-generated proof diffs automatically. Please see the PG documentation section "Showing Proof Diffs" of details.

 $<sup>^{295}\ \</sup>mathrm{https://proofgeneral.github.io/doc/master/userman/Coq-Proof-General\#Showing-Proof-Diffs}$ 

#### How diffs are calculated


Diffs are calculated as follows:

- 1. Select the old proof state to compare to, which is the proof state before the last tactic that changed the proof. Changes that only affect the view of the proof, such as all: swap 1 2, are ignored.
- 2. For each goal in the new proof state, determine what old goal to compare it to—the one it is derived from or is the same as. Match the hypotheses by name (order is ignored), handling compacted items specially.
- 3. For each hypothesis and conclusion (the "items") in each goal, pass them as strings to the lexer to break them into tokens. Then apply the Myers diff algorithm [Mye86] on the tokens and add appropriate highlighting.


#### Notes:

- Aside from the highlights, output for the "on" option should be identical to the undiffed output.
- Goals completed in the last proof step will not be shown even with the "removed" setting.

This screen shot shows the result of applying a *split* tactic that replaces one goal with 2 goals. Notice that the goal P 1 is not highlighted at all after the split because it has not changed.



This is how diffs may appear after applying a *intro* tactic that results in compacted hypotheses:



## 5.2.5 Controlling the effect of proof editing commands

#### Option: Hyps Limit num

This option controls the maximum number of hypotheses displayed in goals after the application of a tactic. All the hypotheses remain usable in the proof development. When unset, it goes back to the default mode which is to print all available hypotheses.

#### Flag: Nested Proofs Allowed

When turned on (it is off by default), this flag enables support for nested proofs: a new assertion command can be inserted before the current proof is finished, in which case Coq will temporarily switch to the proof of this *nested lemma*. When the proof of the nested lemma is finished (with *Qed* or *Defined*), its statement will be made available (as if it had been proved before starting the previous proof) and Coq will switch back to the proof of the previous assertion.

## 5.2.6 Controlling memory usage

When experiencing high memory usage the following commands can be used to force Coq to optimize some of its internal data structures.

#### Command: Optimize Proof

This command forces Coq to shrink the data structure used to represent the ongoing proof.

5.2. Proof handling 267

#### Command: Optimize Heap

This command forces the OCaml runtime to perform a heap compaction. This is in general an expensive operation. See: OCaml  $Gc^{296}$  There is also an analogous tactic optimize\_heap.

## 5.3 Tactics

A deduction rule is a link between some (unique) formula, that we call the *conclusion* and (several) formulas that we call the *premises*. A deduction rule can be read in two ways. The first one says: "if I know this and this then I can deduce this". For instance, if I have a proof of A and a proof of B then I have a proof of A B. This is forward reasoning from premises to conclusion. The other way says: "to prove this I have to prove this and this". For instance, to prove A B, I have to prove A and I have to prove B. This is backward reasoning from conclusion to premises. We say that the conclusion is the *goal* to prove and premises are the *subgoals*. The tactics implement *backward reasoning*. When applied to a goal, a tactic replaces this goal with the subgoals it generates. We say that a tactic reduces a goal to its subgoal(s).

Each (sub)goal is denoted with a number. The current goal is numbered 1. By default, a tactic is applied to the current goal, but one can address a particular goal in the list by writing n:tactic which means "apply tactic tactic to goal number n". We can show the list of subgoals by typing Show (see Section *Requesting information*).

Since not every rule applies to a given statement, not every tactic can be used to reduce a given goal. In other words, before applying a tactic to a given goal, the system checks that some *preconditions* are satisfied. If it is not the case, the tactic raises an error message.

Tactics are built from atomic tactics and tactic expressions (which extends the folklore notion of tactical) to combine those atomic tactics. This chapter is devoted to atomic tactics. The tactic language will be described in Chapter Ltac.

#### 5.3.1 Common elements of tactics

#### Invocation of tactics

A tactic is applied as an ordinary command. It may be preceded by a goal selector (see Section Semantics). If no selector is specified, the default selector is used.

```
tactic\_invocation ::= toplevel\_selector : tactic.
```

#### Option: Default Goal Selector "toplevel\_selector"

This option controls the default selector, used when no selector is specified when applying a tactic. The initial value is 1, hence the tactics are, by default, applied to the first goal.

Using value all will make it so that tactics are, by default, applied to every goal simultaneously. Then, to apply a tactic tac to the first goal only, you can write 1:tac.

Using value! enforces that all tactics are used either on a single focused goal or with a local selector ("strict focusing mode").

Although more selectors are available, only all, ! or a single natural number are valid default goal selectors.

 $<sup>^{296}</sup>$ http://caml.inria.fr/pub/docs/manual-ocaml/libref/Gc.html#VALcompact

## **Bindings list**

Tactics that take a term as an argument may also support a bindings list to instantiate some parameters of the term by name or position. The general form of a term with a bindings list is *term* with *bindings\_list* where *bindings\_list* can take two different forms:

• In a bindings list of the form (ref:= term), ref is either an ident or a num. The references are determined according to the type of term. If ref is an identifier, this identifier has to be bound in the type of term and the binding provides the tactic with an instance for the parameter of this name. If ref is a number n, it refers to the n-th non dependent premise of the term, as determined by the type of term.

Error: No such binder.

• A bindings list can also be a simple list of terms term. In that case the references to which these terms correspond are determined by the tactic. In case of induction, destruct, elim and case, the terms have to provide instances for all the dependent products in the type of term while in the case of apply, or of constructor and its variants, only instances for the dependent products that are not bound in the conclusion of the type are required.

Error: Not the right number of missing arguments.

## Intro patterns

Intro patterns let you specify the name to assign to variables and hypotheses introduced by tactics. They also let you split an introduced hypothesis into multiple hypotheses or subgoals. Common tactics that accept intro patterns include assert, intros and destruct.

```
intropattern_list
                                    intropattern ... intropattern
                              ::=
                                    empty
empty
{\tt intropattern}
                              ::=
                                    simple_intropattern
                                    simple_intropattern_closed [ % term ... % term ]
simple_intropattern
simple_intropattern_closed
                                    naming\_intropattern
                              ::=
                                    or\_and\_intropattern
                                    rewriting_intropattern
                                    injection_intropattern
naming_intropattern
                              ::=
                                    ident
                                    ?
                                    ?ident
                                    [ intropattern\_list | ... | intropattern\_list ]
or_and_intropattern
                              ::=
                                    ( simple intropattern , ... , simple intropattern )
                                    ( simple_intropattern & ... & simple_intropattern )
rewriting_intropattern
                              ::=
```

Note that the intro pattern syntax varies between tactics. Most tactics use *simple\_intropattern* in the grammar. *destruct*, *edestruct*, *induction*, *einduction*, *case*, *ecase* and the various *inversion* tactics use *or\_and\_intropattern\_loc*, while *intros* and *eintros* use *intropattern\_list*. The eqn: construct in various tactics uses *naming\_intropattern*.

## Naming patterns

Use these elementary patterns to specify a name:

- *ident* use the specified name
- ? let Coq choose a name
- ?ident generate a name that begins with ident
- \_ discard the matched part (unless it is required for another hypothesis)
- if a disjunction pattern omits a name, such as [IH2], Coq will choose a name

## Splitting patterns

The most common splitting patterns are:

- split a hypothesis in the form A /\ B into two hypotheses H1: A and H2: B using the pattern (H1 & H2) or [H1 H2]. *Example*. This also works on A <-> B, which is just a notation representing (A -> B) /\ (B -> A).
- split a hypothesis in the form A \/ B into two subgoals using the pattern [H1|H2]. The first subgoal will have the hypothesis H1: A and the second subgoal will have the hypothesis H2: B. Example
- split a hypothesis in either of the forms A /\ B or A \/ B using the pattern [].

Patterns can be nested: [[Ha|Hb] H] can be used to split (A  $\$  B)  $\$  C.

Note that there is no equivalent to intro patterns for goals. For a goal A  $\land \land$  B, use the split tactic to replace the current goal with subgoals A and B. For a goal A  $\land \land$  B, use left to replace the current goal with A, or right to replace the current goal with B.

- ( <u>simple\_intropattern</u>, ) matches a product over an inductive type with a <u>single constructor</u>. If the number of patterns equals the number of constructor arguments, then it applies the patterns only to the arguments, and ( <u>simple\_intropattern</u>, ) is equivalent to [ <u>simple\_intropattern</u>]. If the number of patterns equals the number of constructor arguments plus the number of let-ins, the patterns are applied to the arguments and let-in variables.
- ( simple\_intropattern ) matches a right-hand nested term that consists of one or more nested binary inductive types such as al OPl al OPl ... (where the OPn are right-associative). (If the OPn are left-associative, additional parentheses will be needed to make the term right-hand nested, such as al OPl (al OPl ...).) The splitting pattern can have more than 2 names, for example (H1 & H2 & H3) matches A /\ B /\ C. The inductive types must have a single constructor with two parameters. Example
- [ intropattern\_list ] splits an inductive type that has multiple constructors such as A \/ B into multiple subgoals. The number of intropattern\_list must be the same as the number of constructors for the matched part.

- [ intropattern ] splits an inductive type that has a single constructor with multiple parameters such as A /\ B into multiple hypotheses. Use [H1 [H2 H3]] to match A /\ B /\ C.
- [] splits an inductive type: If the inductive type has multiple constructors, such as A \/ B, create one subgoal for each constructor. If the inductive type has a single constructor with multiple parameters, such as A /\ B, split it into multiple hypotheses.

## Equality patterns

These patterns can be used when the hypothesis is an equality:

- -> replaces the right-hand side of the hypothesis with the left-hand side of the hypothesis in the conclusion of the goal; the hypothesis is cleared; if the left-hand side of the hypothesis is a variable, it is substituted everywhere in the context and the variable is removed. *Example*
- <- similar to ->, but replaces the left-hand side of the hypothesis with the right-hand side of the hypothesis.
- [= intropattern, ] If the product is over an equality type, applies either injection or discriminate. If injection is applicable, the intropattern is used on the hypotheses generated by injection. If the number of patterns is smaller than the number of hypotheses generated, the pattern? is used to complete the list. Example

#### Other patterns

- \* introduces one or more quantified variables from the result until there are no more quantified variables. *Example*
- \*\* introduces one or more quantified variables or hypotheses from the result until there are no more quantified variables or implications (->). intros \*\* is equivalent to intros. Example
- simple\_intropattern\_closed % term first applies each of the terms with the apply ... in tactic on the hypothesis to be introduced, then it uses simple\_intropattern\_closed. Example

## Flag: Bracketing Last Introduction Pattern

For introp intropattern\_list, controls how to handle a conjunctive pattern that doesn't give enough simple patterns to match all the arguments in the constructor. If set (the default), Coq generates additional names to match the number of arguments. Unsetting the flag will put the additional hypotheses in the goal instead, behavior that is more similar to SSReflect's intro patterns.

Deprecated since version 8.10.

Note: A \/ B and A /\ B use infix notation to refer to the inductive types or and and. or has multiple constructors (or\_introl and or\_intror), while and has a single constructor (conj) with multiple parameters (A and B). These are defined in theories/Init/Logic.v. The "where" clauses define the infix notation for "or" and "and".

```
Inductive or (A B:Prop) : Prop :=
    | or_introl : A -> A \/ B
    | or_intror : B -> A \/ B
where "A \/ B" := (or A B) : type_scope.

Inductive and (A B:Prop) : Prop :=
    conj : A -> B -> A /\ B
where "A /\ B" := (and A B) : type_scope.
```

Note: intros p is not always equivalent to intros p; ...; intros p if some of the p are \_. In the first form, all erasures are done at once, while they're done sequentially for each tactic in the second form. If the second matched term depends on the first matched term and the pattern for both is \_ (i.e., both will be erased), the first intros in the second form will fail because the second matched term still has the dependency on the first.

Examples:

## Example: intro pattern for \/

```
1 subgoal
    A, B : Prop
    H : A \setminus / B
    _____
    True
destruct H as [HA|HB].
   2 subgoals
    A, B : Prop
    HA : A
    _____
    True
   subgoal 2 is:
   True
all: swap 1 2.
   2 subgoals
    A, B : Prop
    HB : B
    _____
```

 $({\rm continues\ on\ next\ page})$ 

(continued from previous page)

```
True
subgoal 2 is:
True
```

## Example: -> intro pattern

## Example: [=] intro pattern

The first intros [=] uses *injection* to strip (S ...) from both sides of the matched equality. The second uses *discriminate* on the contradiction 1 = 2 (internally represented as  $(S \ 0) = (S \ 0)$ ) to complete the goal.

## Example: (A & B & ...) intro pattern

1 subgoal

 $({\rm continues\ on\ next\ page})$ 

(continued from previous page)

## Example: \* intro pattern

## Example: compound intro pattern

```
1 subgoal

-----
forall A B C : Prop, A \/ B /\ C -> (A -> C) -> C
```

Example: combined intro pattern using [=] -> and %

```
1 subgoal
      A : Type
      xs, ys : list A
      S (length ys) = 1 \rightarrow xs ++ ys = xs
intros [=->%length_zero_iff_nil].
    1 subgoal
      A : Type
      xs : list A
      xs ++ nil = xs
  • intros would add H : S (length ys) = 1
  • intros [=] would additionally apply injection to H to yield HO : length ys = 0
  • intros [=->%length_zero_iff_nil] applies the theorem, making H the equality l=nil,
    which is then applied as for \rightarrow.
Theorem length_zero_iff_nil (1 : list A):
   length l = 0 <-> l=nil.
The example is based on Tej Chajed's coq-tricks<sup>297</sup>
```

 $<sup>^{297}\ \</sup>mathrm{https://github.com/tchajed/coq\text{-}tricks/blob/8e6efe4971ed828ac8bdb5512c1f615d7d62691e/src/IntroPatterns.v}$ 

#### Occurrence sets and occurrence clauses

An occurrence clause is a modifier to some tactics that obeys the following syntax:

The role of an occurrence clause is to select a set of occurrences of a term in a goal. In the first case, the

ident at num\* parts indicate that occurrences have to be selected in the hypotheses named ident. If no numbers are given for hypothesis ident, then all the occurrences of term in the hypothesis are selected. If numbers are given, they refer to occurrences of term when the term is printed using the Printing All flag, counting from left to right. In particular, occurrences of term in implicit arguments (see Implicit arguments) or coercions (see Coercions) are counted.

If a minus sign is given between at and the list of occurrences, it negates the condition so that the clause denotes all the occurrences except the ones explicitly mentioned after the minus sign.

As an exception to the left-to-right order, the occurrences in the return subexpression of a match are considered *before* the occurrences in the matched term.

In the second case, the \* on the left of |- means that all occurrences of term are selected in every hypothesis.

In the first and second case, if \* is mentioned on the right of |-, the occurrences of the conclusion of the goal have to be selected. If some numbers are given, then only the occurrences denoted by these numbers are selected. If no numbers are given, all occurrences of term in the goal are selected.

Finally, the last notation is an abbreviation for \* |- \*. Note also that |- is optional in the first case when no \* is given.

Here are some tactics that understand occurrence clauses: set, remember, induction, destruct.

#### See also:

Managing the local context, Case analysis and induction, Printing constructions in full.

## 5.3.2 Applying theorems

#### exact term

This tactic applies to any goal. It gives directly the exact proof term of the goal. Let T be our goal, let p be a term of type U then exact p succeeds iff T and U are convertible (see *Conversion rules*).

Error: Not an exact proof.

Variant: eexact term.

This tactic behaves like *exact* but is able to handle terms and goals with existential variables.

#### assumption

This tactic looks in the local context for a hypothesis whose type is convertible to the goal. If it is the case, the subgoal is proved. Otherwise, it fails.

Error: No such assumption.

#### Variant: eassumption

This tactic behaves like assumption but is able to handle goals with existential variables.

#### refine term

This tactic applies to any goal. It behaves like <code>exact</code> with a big difference: the user can leave some holes (denoted by <code>\_</code> or (<code>\_</code>: <code>type</code>) in the term. <code>refine</code> will generate as many subgoals as there are remaining holes in the elaborated term. The type of holes must be either synthesized by the system or declared by an explicit cast like (<code>\_</code>: <code>nat -> Prop</code>). Any subgoal that occurs in other subgoals is automatically shelved, as if calling <code>shelve\_unifiable</code>. The produced subgoals (shelved or not) are <code>not</code> candidates for typeclass resolution, even if they have a type-class type as conclusion, letting the user control when and how typeclass resolution is launched on them. This low-level tactic can be useful to advanced users.

#### Example

```
Inductive Option : Set :=
| Fail : Option
| Ok : bool -> Option.
   Option is defined
   Option_rect is defined
   Option_ind is defined
   Option_rec is defined
   Option_sind is defined
Definition get : forall x:Option, x <> Fail -> bool.
   1 subgoal
     forall x : Option, x <> Fail -> bool
refine
    (fun x:Option =>
     match x return x <> Fail -> bool with
     | Fail => _
     | 0k b => fun _ => b
     end).
    1 subgoal
     x : Option
      _____
     Fail <> Fail -> bool
intros; absurd (Fail = Fail); trivial.
   No more subgoals.
Defined.
```

#### Error: Invalid argument.

The tactic *refine* does not know what to do with the term you gave.

#### Error: Refine passed ill-formed term.

The term you gave is not a valid proof (not easy to debug in general). This message may also occur in higher-level tactics that call *refine* internally.

#### Error: Cannot infer a term for this placeholder.

There is a hole in the term you gave whose type cannot be inferred. Put a cast around it.

#### Variant: simple refine term

This tactic behaves like refine, but it does not shelve any subgoal. It does not perform any beta-reduction either.

#### Variant: notypeclasses refine term

This tactic behaves like *refine* except it performs type checking without resolution of typeclasses.

#### Variant: simple notypeclasses refine term

This tactic behaves like the combination of *simple refine* and *notypeclasses refine*: it performs type checking without resolution of typeclasses, does not perform beta reductions or shelve the subgoals.

#### Flag: Debug Unification

Enables printing traces of unification steps used during elaboration/typechecking and the *refine* tactic.

## apply term

This tactic applies to any goal. The argument term is a term well-formed in the local context. The tactic apply tries to match the current goal against the conclusion of the type of term. If it succeeds, then the tactic returns as many subgoals as the number of non-dependent premises of the type of term. If the conclusion of the type of term does not match the goal and the conclusion is an inductive type isomorphic to a tuple type, then each component of the tuple is recursively matched to the goal in the left-to-right order.

The tactic apply relies on first-order unification with dependent types unless the conclusion of the type of term is of the form P  $(t_1 \ldots t_n)$  with P to be instantiated. In the latter case, the behavior depends on the form of the goal. If the goal is of the form  $(fun \ x \Rightarrow Q) \ u_1 \ldots u_n$  and the  $t_i$  and  $u_i$  unify, then P is taken to be  $(fun \ x \Rightarrow Q)$ . Otherwise, apply tries to define P by abstracting over  $t_1 \ldots t_n$  in the goal. See pattern to transform the goal so that it gets the form  $(fun \ x \Rightarrow Q) \ u_1 \ldots u_n$ .

## Error: Unable to unify term with term.

The apply tactic failed to match the conclusion of term and the current goal. You can help the apply tactic by transforming your goal with the change or pattern tactics.

## Error: Unable to find an instance for the variables ident.

This occurs when some instantiations of the premises of term are not deducible from the unification. This is the case, for instance, when you want to apply a transitivity property. In this case, you have to use one of the variants below:

## Variant: apply term with term

Provides apply with explicit instantiations for all dependent premises of the type of term that do not occur in the conclusion and consequently cannot be found by unification. Notice that the collection term must be given according to the order of these dependent premises of the type of term.

Error: Not the right number of missing arguments.

#### Variant: apply term with bindings\_list

This also provides apply with values for instantiating premises. Here, variables are referred by names and non-dependent products by increasing numbers (see *bindings list*).

# Variant: apply term,

This is a shortcut for apply  $term_1$ ; [... | ...; [... | apply  $term_n$ ] ...], i.e. for the successive applications of  $term_{i+1}$  on the last subgoal generated by apply  $term_i$ , starting from the application of  $term_i$ .

## Variant: eapply term


The tactic *eapply* behaves like *apply* but it does not fail when no instantiations are deducible for some variables in the premises. Rather, it turns these variables into existential variables which are variables still to instantiate (see *Existential variables*). The instantiation is intended to be found later in the proof.

## Variant: simple apply term.

This behaves like *apply* but it reasons modulo conversion only on subterms that contain no variables to instantiate. For instance, the following example does not succeed because it would require the conversion of id ?foo and 0.

## Example

Because it reasons modulo a limited amount of conversion, *simple apply* fails quicker than *apply* and it is then well-suited for uses in user-defined tactics that backtrack often. Moreover, it does not traverse tuples as *apply* does.



This summarizes the different syntaxes for apply and eapply.

#### Variant: lapply term

This tactic applies to any goal, say G. The argument term has to be well-formed in the current context, its type being reducible to a non-dependent product A -> B with B possibly containing products. Then it generates two subgoals B->G and A. Applying lapply H (where H has type A->B and B does not start with a product) does the same as giving the sequence cut B. 2:apply H. where cut is described below.

Warning: When term contains more than one non dependent product the tactic lapply only takes it

## Example

Assume we have a transitive relation R on nat:

```
Parameter R : nat -> nat -> Prop. Axiom Rtrans : forall x y z:nat, R x y -> R y z -> R x z.
```

(continues on next page)

Toplevel input, characters 0-12:

\_\_\_\_\_

Consider the goal (R n p) provable using the transitivity of R:

Error: Unable to find an instance for the variable y.

A solution is to apply (Rtrans n m p) or (Rtrans n m).

Parameters n m p : nat. Axiom Rnm : R n m. Axiom Rmp : R m p.

> apply Rtrans.

apply (Rtrans n m p). 2 subgoals

R n m

subgoal 2 is:

Goal R n p.

apply Rtrans.

```
(continued from previous page)
The direct application of Rtrans with apply fails because no value for y in Rtrans is found by apply:
```

R m pNote that **n** can be inferred from the goal, so the following would work too.

```
apply (Rtrans _ m).
```

More elegantly, apply Rtrans with (y:=m) allows only mentioning the unknown m:

```
apply Rtrans with (y := m).
```

Another solution is to mention the proof of (R x y) in Rtrans

```
apply Rtrans with (1 := Rnm).
   1 subgoal
    _____
    Rmp
... or the proof of (R y z).
apply Rtrans with (2 := Rmp).
   1 subgoal
    _____
    Rnm
```

On the opposite, one can use eapply which postpones the problem of finding m. Then one can apply the hypotheses Rnm and Rmp. This instantiates the existential variable and completes the proof.

```
eapply Rtrans.
    2 focused subgoals
    (shelved: 1)
```

(continued from previous page)

```
R n ?y

subgoal 2 is:
R ?y p

apply Rnm.
1 subgoal

R m p

apply Rmp.
No more subgoals.
```

Note: When the conclusion of the type of the term to apply is an inductive type isomorphic to a tuple type and apply looks recursively whether a component of the tuple matches the goal, it excludes components whose statement would result in applying an universal lemma of the form forall A, ... -> A. Excluding this kind of lemma can be avoided by setting the following flag:

#### Flag: Universal Lemma Under Conjunction

This flag, which preserves compatibility with versions of Coq prior to 8.4 is also available for apply term in ident (see apply ... in).

#### apply term in ident

This tactic applies to any goal. The argument term is a term well-formed in the local context and the argument ident is an hypothesis of the context. The tactic apply term in ident tries to match the conclusion of the type of ident against a non-dependent premise of the type of term, trying them from right to left. If it succeeds, the statement of hypothesis ident is replaced by the conclusion of the type of term. The tactic also returns as many subgoals as the number of other non-dependent premises in the type of term and of the non-dependent premises of the type of ident. If the conclusion of the type of term does not match the goal and the conclusion is an inductive type isomorphic to a tuple type, then the tuple is (recursively) decomposed and the first component of the tuple of which a non-dependent premise matches the conclusion of the type of ident. Tuples are decomposed in a width-first left-to-right order (for instance if the type of H1 is A <-> B and the type of H2 is A then apply H1 in H2 transforms the type of H2 into B). The tactic apply relies on first-order pattern matching with dependent types.

#### Error: Statement without assumptions.

This happens if the type of *term* has no non-dependent premise.

## Error: Unable to apply.

This happens if the conclusion of ident does not match any of the non-dependent premises of the type of term.

Variant: apply term, in ident

This applies each term in sequence in ident.

Variant: apply term with bindings\_list in ident

This does the same but uses the bindings in each (*ident* := *term*) to instantiate the parameters of the corresponding type of *term* (see *bindings list*).

Variant: eapply term with bindings\_list ? in ident


This works as *apply ... in* but turns unresolved bindings into existential variables, if any, instead of failing.

Variant: apply term with bindings\_list in ident as simple\_intropattern

This works as apply ... in then applies the simple\_intropattern to the hypothesis ident.

## Variant: simple apply term in ident

This behaves like  $apply \dots in$  but it reasons modulo conversion only on subterms that contain no variables to instantiate. For instance, if id := fun x:nat => x and H: forall y, id y = y -> True and H0 : 0 = 0 then simple apply H in H0 does not succeed because it would require the conversion of id ?x and 0 where ?x is an existential variable to instantiate. Tactic simple apply term in ident does not either traverse tuples as apply term in ident does.



This summarizes the different syntactic variants of apply term in ident and eapply term in ident.

#### constructor num

This tactic applies to a goal such that its conclusion is an inductive type (say I). The argument *num* must be less or equal to the numbers of constructor(s) of I. Let  $c_i$  be the i-th constructor of I, then constructor i is equivalent to intros; apply  $c_i$ .

Error: Not an inductive product.

Error: Not enough constructors.

## Variant: constructor

This tries constructor 1 then constructor 2, ..., then constructor n where n is the number of constructors of the head of the goal.

#### Variant: constructor num with bindings\_list

Let c be the i-th constructor of I, then constructor i with bindings\_list is equivalent to intros; apply c with bindings\_list.

**Warning:** The terms in the  $bindings\_list$  are checked in the context where constructor is executed and not in the context where apply is executed (the introductions are not taken into account).

## Variant: split with bindings\_list ?

This applies only if I has a single constructor. It is then equivalent to constructor 1 with  $bindings\_list$ . It is typically used in the case of a conjunction  $A \wedge B$ .

#### Variant: exists bindings\_list

This applies only if I has a single constructor. It is then equivalent to intros; constructor 1 with  $bindings\_list$ . It is typically used in the case of an existential quantification  $\exists x, P(x)$ .

Variant: exists bindings\_list ,

This iteratively applies exists bindings\_list.

Error: Not an inductive goal with 1 constructor.

Variant: left with bindings\_list ?

Variant: right | with bindings\_list | ?

These tactics apply only if I has two constructors, for instance in the case of a disjunction  $A \vee B$ . Then, they are respectively equivalent to constructor 1 with bindings\_list? and constructor 2 with bindings\_list?

Error: Not an inductive goal with 2 constructors.

Variant: econstructor Variant: eexists Variant: esplit Variant: eleft Variant: eright

These tactics and their variants behave like *constructor*, *exists*, *split*, *left*, *right* and their variants but they introduce existential variables instead of failing when the instantiation of a variable cannot be found (cf. *eapply* and *apply*).

#### Flag: Debug Tactic Unification

Enables printing traces of unification steps in tactic unification. Tactic unification is used in tactics such as apply and rewrite.

## 5.3.3 Managing the local context

#### intro

This tactic applies to a goal that is either a product or starts with a let-binder. If the goal is a product, the tactic implements the "Lam" rule given in *Typing rules*<sup>1</sup>. If the goal starts with a let-binder, then the tactic implements a mix of the "Let" and "Conv".

If the current goal is a dependent product forall x:T, U (resp let x:=t in U) then intro puts x:T (resp x:=t) in the local context. The new subgoal is U.

If the goal is a non-dependent product  $T \to U$ , then it puts in the local context either  $\mathtt{Hn:T}$  (if T is of type Set or Prop) or  $\mathtt{Xn:T}$  (if the type of T is Type). The optional index n is such that  $\mathtt{Hn}$  or  $\mathtt{Xn}$  is a fresh identifier. In both cases, the new subgoal is  $\mathtt{U}$ .

If the goal is an existential variable, intro forces the resolution of the existential variable into a dependent product  $\forall x:?X$ , ?Y, puts x:?X in the local context and leaves ?Y as a new subgoal allowed to depend on x.

The tactic *intro* applies the tactic *hnf* until *intro* can be applied or the goal is not head-reducible.

Error: No product even after head-reduction.

Variant: intro ident

This applies *intro* but forces *ident* to be the name of the introduced hypothesis.

Error: ident is already used.

<sup>&</sup>lt;sup>1</sup> Actually, only the second subgoal will be generated since the other one can be automatically checked.

**Note:** If a name used by intro hides the base name of a global constant then the latter can still be referred to by a qualified name (see *Qualified names*).

#### Variant: intros

This repeats *intro* until it meets the head-constant. It never reduces head-constants and it never fails.

```
Variant: intros ident
```

This is equivalent to the composed tactic intro *ident*; ...; intro *ident*.

#### Variant: intros until ident

This repeats intro until it meets a premise of the goal having the form (*ident*: *type*) and discharges the variable named *ident* of the current goal.

Error: No such hypothesis in current goal.

#### Variant: intros until num

This repeats *intro* until the *num*-th non-dependent product.

#### Example

On the subgoal forall x y : nat, x = y -> y = x the tactic intros until 1 is equivalent to intros x y H, as x = y -> y = x is the first non-dependent product.

On the subgoal forall x y z : nat,  $x = y \rightarrow y = x$  the tactic intros until 1 is equivalent to intros x y z as the product on z can be rewritten as a non-dependent product: forall x y : nat,  $nat \rightarrow x = y \rightarrow y = x$ .

## Error: No such hypothesis in current goal.

This happens when num is 0 or is greater than the number of non-dependent products of the goal.

```
Variant: intro ident<sub>1</sub>? after ident<sub>2</sub>

Variant: intro ident<sub>1</sub>? before ident<sub>2</sub>

Variant: intro ident<sub>1</sub>? at top

Variant: intro ident<sub>1</sub>? at bottom
```

These tactics apply intro <code>ident\_1</code> and move the freshly introduced hypothesis respectively after the hypothesis <code>ident\_2</code>, before the hypothesis <code>ident\_2</code>, at the top of the local context, or at the bottom of the local context. All hypotheses on which the new hypothesis depends are moved too so as to respect the order of dependencies between hypotheses. It is equivalent to

intro ident<sub>1</sub> followed by the appropriate call to move ... after ..., move ... before ..., move ... at top, or move ... at bottom.

Note: intro at bottom is a synonym for intro with no argument.

Error: No such hypothesis: ident.

## intros intropattern\_list

Introduces one or more variables or hypotheses from the goal by matching the intro patterns. See the description in *Intro patterns*.

#### eintros intropattern\_list

Works just like *intros* ... except that it creates existential variables for any unresolved variables rather than failing.

#### clear ident

This tactic erases the hypothesis named *ident* in the local context of the current goal. As a consequence, *ident* is no more displayed and no more usable in the proof development.

Error: No such hypothesis.

Error: ident is used in the conclusion.

Error: ident is used in the hypothesis ident.

Variant: clear ident

This is equivalent to clear *ident*. ... clear *ident*.

Variant: clear - ident

This variant clears all the hypotheses except the ones depending in the hypotheses named ident and in the goal.

Variant: clear

This variants clears all the hypotheses except the ones the goal depends on.

Variant: clear dependent ident

This clears the hypothesis *ident* and all the hypotheses that depend on it.

Variant: clearbody ident

This tactic expects ident to be local definitions and clears their respective bodies. In other words, it turns the given definitions into assumptions.

Error: ident is not a local definition.

revert ident +

This applies to any goal with variables ident. It moves the hypotheses (possibly defined) to the goal, if this respects dependencies. This tactic is the inverse of intro.

Error: No such hypothesis.

Error:  $ident_1$  is used in the hypothesis  $ident_2$ .

Variant: revert dependent ident

This moves to the goal the hypothesis ident and all the hypotheses that depend on it.

move ident, after ident,

This moves the hypothesis named  $ident_1$  in the local context after the hypothesis named  $ident_2$ , where "after" is in reference to the direction of the move. The proof term is not changed.

If  $ident_1$  comes before  $ident_2$  in the order of dependencies, then all the hypotheses between  $ident_1$  and  $ident_2$  that (possibly indirectly) depend on  $ident_1$  are moved too, and all of them are thus moved after  $ident_2$  in the order of dependencies.

If  $ident_1$  comes after  $ident_2$  in the order of dependencies, then all the hypotheses between  $ident_1$  and  $ident_2$  that (possibly indirectly) occur in the type of  $ident_1$  are moved too, and all of them are thus moved before  $ident_2$  in the order of dependencies.

Variant: move ident, before ident,

This moves  $ident_1$  towards and just before the hypothesis named  $ident_2$ . As for  $move \ldots after \ldots$ , dependencies over  $ident_1$  (when  $ident_1$  comes before  $ident_2$  in the order of dependencies)

```
or in the type of ident_1 (when ident_1 comes after ident_2 in the order of dependencies) are moved
    too.
Variant: move ident at top
    This moves ident at the top of the local context (at the beginning of the context).
Variant: move ident at bottom
    This moves ident at the bottom of the local context (at the end of the context).
Error: No such hypothesis.
Error: Cannot move ident, after ident; it occurs in the type of ident.
Error: Cannot move ident, after ident,: it depends on ident,.
Example
Goal forall x : nat, x = 0 \rightarrow forall z y : nat, y=y-> 0=x.
   1 subgoal
     _____
     forall x : nat, x = 0 \rightarrow nat \rightarrow forall y : nat, y = y \rightarrow 0 = x
intros x H z y HO.
   1 subgoal
     x : nat
     H : x = 0
     z, y : nat
     HO : y = y
     _____
     0 = x
move x after HO.
   1 subgoal
     z, y : nat
     HO : y = y
     x : nat
     H : x = 0
     _____
     0 = x
Undo.
   1 subgoal
     x : nat
     H : x = 0
     z, y : nat
     HO : y = y
     _____
     0 = x
move x before HO.
   1 subgoal
     z, y, x: nat
     H : x = 0
     HO : y = y
```

(continues on next page)

```
x = 0
Undo.
   1 subgoal
    x : nat
    H : x = 0
    z, y: nat
    HO : y = y
    _____
    x = 0
move HO after H.
   1 subgoal
    x, y : nat
    HO : y = y
    H : x = 0
    z : nat
    _____
Undo.
   1 subgoal
    x : nat
    H : x = 0
    z, y: nat
    HO : y = y
    _____
move HO before H.
   1 subgoal
    x : nat
    H : x = 0
    y : nat
    HO : y = y
    z : nat
    _____
    x = 0
```

\_\_\_\_\_

# rename $ident_1$ into $ident_2$

This renames hypothesis  $ident_1$  into  $ident_2$  in the current context. The name of the hypothesis in the proof-term, however, is left unchanged.

```
Variant: rename ident_i into ident_j,
```

This renames the variables  $ident_i$  into  $ident_j$  in parallel. In particular, the target identifiers may contain identifiers that exist in the source context, as long as the latter are also renamed by the same tactic.

Error: No such hypothesis.

Error: ident is already used.

```
set (ident := term)
     This replaces term by ident in the conclusion of the current goal and adds the new definition ident
     := term to the local context.
     If term has holes (i.e. subexpressions of the form "_"), the tactic first checks that all subterms matching
     the pattern are compatible before doing the replacement using the leftmost subterm matching the
     Error: The variable ident is already defined.
     Variant: set (ident := term) in goal_occurrences
          This notation allows specifying which occurrences of term have to be substituted in the context.
          The in qoal_occurrences clause is an occurrence clause whose syntax and behavior are described
          in goal occurrences.
     Variant: set (ident binders := term) in goal_occurrences
         This is equivalent to set (ident := fun binders => term) in goal_occurrences
     Variant: set term in goal occurrences
         This behaves as set (ident := term) in goal_occurrences but ident is generated by Coq.
     Variant: eset (ident binders := term) in goal_occurrences
     Variant: eset term in goal_occurrences
          While the different variants of set expect that no existential variables are generated by the tactic,
          eset removes this constraint. In practice, this is relevant only when eset is used as a synonym
          of epose, i.e. when the term does not occur in the goal.
remember term as ident; eqn:naming_intropattern
     This behaves as set (ident := term) in *, using a logical (Leibniz's) equality instead of a local
     definition. Use naming_intropattern to name or split up the new equation.
     Variant: remember term as ident, eqn:naming_intropattern in goal_occurrences
          This is a more general form of remember that remembers the occurrences of term specified by an
          occurrence set.
     Variant: eremember term as ident, eqn:naming_intropattern in goal_occurrences
          While the different variants of remember expect that no existential variables are generated by the
          tactic, eremember removes this constraint.
pose (ident := term)
     This adds the local definition ident := term to the current context without performing any replace-
     ment in the goal or in the hypotheses. It is equivalent to set (ident := term) in |-.
     Variant: pose (ident binders := term)
          This is equivalent to pose (ident := fun binders => term).
```

# Variant: pose term

This behaves as pose (ident := term) but ident is generated by Coq.

```
Variant: epose (ident binders := term)
```

Variant: epose term

While the different variants of pose expect that no existential variables are generated by the tactic, epose removes this constraint.

```
decompose [qualid | term
```

This tactic recursively decomposes a complex proposition in order to obtain atomic ones.

```
Example
```

```
Goal forall A B C:Prop, A /\setminus B /\setminus C \setminus/ B /\setminus C \setminus/ A \rightarrow C.
    1 subgoal
      intros A B C H; decompose [and or] H.
    3 subgoals
      A, B, C: Prop
      H : A / \backslash B / \backslash C \backslash / B / \backslash C \backslash / C / \backslash A
      H1 : A
      HO : B
      H3 : C
      _____
    subgoal 2 is:
    subgoal 3 is:
     C
all: assumption.
    No more subgoals.
Qed.
```

Note: decompose does not work on right-hand sides of implications or products.

Variant: decompose sum term

This decomposes sum types (like or).

Variant: decompose record term

This decomposes record types (inductive types with one constructor, like and and exists and those defined with the *Record* command.

# 5.3.4 Controlling the proof flow

```
assert (ident : type)
```

This tactic applies to any goal. assert (H:U) adds a new hypothesis of name H asserting U to the current goal and opens a new subgoal  $U^2$ . The subgoal U comes first in the list of subgoals remaining to prove.

Error: Not a proposition or a type.

Arises when the argument type is neither of type Prop, Set nor Type.

<sup>&</sup>lt;sup>2</sup> This corresponds to the cut rule of sequent calculus.

Variant: assert type

This behaves as assert (ident: type) but ident is generated by Coq.

Variant: assert type by tactic

This tactic behaves like assert but applies tactic to solve the subgoals generated by assert.

Error: Proof is not complete.

Variant: assert type as simple\_intropattern

If simple\_intropattern is an intro pattern (see *Intro patterns*), the hypothesis is named after this introduction pattern (in particular, if simple\_intropattern is *ident*, the tactic behaves like assert (*ident*: *type*)). If simple\_intropattern is an action introduction pattern, the tactic behaves like assert *type* followed by the action done by this introduction pattern.

Variant: assert type as simple\_intropattern by tactic

This combines the two previous variants of assert.

Variant: assert (ident := term)

This behaves as assert (*ident*: *type*) by exact *term* where *type* is the type of *term*. This is equivalent to using *pose* proof. If the head of term is *ident*, the tactic behaves as *specialize*.

Error: Variable *ident* is already declared.

Variant: eassert type as simple\_intropattern by tactic

While the different variants of assert expect that no existential variables are generated by the tactic, eassert removes this constraint. This lets you avoid specifying the asserted statement completely before starting to prove it.

Variant: pose proof term as simple\_intropattern ?

This tactic behaves like assert type as simple\_intropattern by exact term where type is the type of term. In particular, pose proof term as ident behaves as assert (ident := term) and pose proof term as simple\_intropattern is the same as applying the simple\_intropattern to term.

Variant: epose proof term as simple\_intropattern ?

While pose proof expects that no existential variables are generated by the tactic, epose proof removes this constraint.

Variant: enough (ident : type)

This adds a new hypothesis of name ident asserting type to the goal the tactic enough is applied to. A new subgoal stating type is inserted after the initial goal rather than before it as assert would do.

Variant: enough type

This behaves like enough (ident: type) with the name ident of the hypothesis generated by Coq.

Variant: enough type as simple\_intropattern

This behaves like enough type using simple\_intropattern to name or destruct the new hypothesis.

Variant: enough (ident : type) by tactic

Variant: enough type as simple\_intropattern by tactic

This behaves as above but with tactic expected to solve the initial goal after the extra assumption type is added and possibly destructed. If the as simple\_intropattern clause generates more than one subgoal, tactic is applied to all of them.

Variant: eenough (ident : type) by tactic ?

While the different variants of enough expect that no existential variables are generated by the tactic,

eenough removes this constraint.

## Variant: cut type

This tactic applies to any goal. It implements the non-dependent case of the "App" rule given in  $Typing\ rules$ . (This is Modus Ponens inference rule.) cut U transforms the current goal T into the two following subgoals: U -> T and U. The subgoal U -> T comes first in the list of remaining subgoal to prove.

Variant: specialize (ident term \*) as simple\_intropattern ?

Variant: specialize ident with bindings\_list as simple\_intropattern ?

tions or non-dependent implications) are instantiated by concrete terms coming either from arguments term or from a bindings list. In the first form the application to term can be partial. The first form is equivalent to assert (ident := ident term). In the second form, instantiation elements can also be partial. In this case the uninstantiated arguments are inferred by unification if possible or left quantified in the hypothesis otherwise. With the as clause, the local hypothesis ident is left unchanged and instead, the modified hypothesis is introduced as specified by the simple\_intropattern. The name ident can also refer to a global lemma or hypothesis. In this case, for compatibility reasons, the behavior of specialize is close to that of generalize: the instantiated statement becomes an additional premise of the goal. The as clause is especially useful in this case to immediately introduce

This tactic works on local hypothesis ident. The premises of this hypothesis (either universal quantifica-

the instantiated statement as a local hypothesis. Error: ident is used in hypothesis ident.

Error: ident is used in conclusion.

#### generalize term

This tactic applies to any goal. It generalizes the conclusion with respect to some term.

#### Example

If the goal is G and t is a subterm of type T in the goal, then generalize t replaces the goal by forall (x:T), G where G is obtained from G by replacing all occurrences of t by x. The name of the variable (here n) is chosen based on T.

Variant: generalize term

This is equivalent to generalize term; ...; generalize term. Note that the sequence of term  $_i$  's are processed from n to 1.

Variant: generalize term at num +

This is equivalent to generalize *term* but it generalizes only over the specified occurrences of *term* (counting from left to right on the expression printed using the *Printing All* flag).

### Variant: generalize term as ident

This is equivalent to generalize term but it uses ident to name the generalized hypothesis.

```
Variant: generalize term at num + as ident,
```

This is the most general form of generalize that combines the previous behaviors.

### Variant: generalize dependent term

This generalizes term but also all hypotheses that depend on term. It clears the generalized hypotheses.

```
evar (ident : term)
```

The evar tactic creates a new local definition named *ident* with type *term* in the context. The body of this binding is a fresh existential variable.

```
instantiate (ident := term )
```

The instantiate tactic refines (see *refine*) an existential variable *ident* with the term *term*. It is equivalent to only [ident]: refine *term* (preferred alternative).

**Note:** To be able to refer to an existential variable by name, the user must have given the name explicitly (see *Existential variables*).

**Note:** When you are referring to hypotheses which you did not name explicitly, be aware that Coq may make a different decision on how to name the variable in the current goal and in the context of the existential variable. This can lead to surprising behaviors.

#### Variant: instantiate (num := term)

This variant allows to refer to an existential variable which was not named by the user. The *num* argument is the position of the existential variable from right to left in the goal. Because this variant is not robust to slight changes in the goal, its use is strongly discouraged.

```
Variant: instantiate ( num := term ) in ident
Variant: instantiate ( num := term ) in ( value of ident )
Variant: instantiate ( num := term ) in ( type of ident )
```

These allow to refer respectively to existential variables occurring in a hypothesis or in the body or the type of a local definition.

#### Variant: instantiate

Without argument, the instantiate tactic tries to solve as many existential variables as possible, using information gathered from other tactics in the same tactical. This is automatically done after each complete tactic (i.e. after a dot in proof mode), but not, for example, between each tactic when they are sequenced by semicolons.

#### admit

This tactic allows temporarily skipping a subgoal so as to progress further in the rest of the proof. A proof containing admitted goals cannot be closed with <code>Qed</code> but only with <code>Admitted</code>.

#### Variant: give\_up

Synonym of admit.

#### absurd term

This tactic applies to any goal. The argument term is any proposition P of type Prop. This tactic applies False elimination, that is it deduces the current goal from False, and generates as subgoals P

and P. It is very useful in proofs by cases, where some cases are impossible. In most cases, P or P is one of the hypotheses of the local context.

#### contradiction

This tactic applies to any goal. The contradiction tactic attempts to find in the current context (after all intros) a hypothesis that is equivalent to an empty inductive type (e.g. False), to the negation of a singleton inductive type (e.g. True or x=x), or two contradictory hypotheses.

#### Error: No such assumption.

# Variant: contradiction ident

The proof of False is searched in the hypothesis named *ident*.

#### contradict ident

This tactic allows manipulating negated hypothesis and goals. The name *ident* should correspond to a hypothesis. With contradict H, the current goal and context is transformed in the following way:

- H:¬A B becomes A
- H:¬A ¬B becomes H: B A
- H: A B becomes ¬A
- H: A ¬B becomes H: B ¬A

#### exfalso

This tactic implements the "ex falso quodlibet" logical principle: an elimination of False is performed on the current goal, and the user is then required to prove that False is indeed provable in the current context. This tactic is a macro for elimtype False.

# 5.3.5 Case analysis and induction

The tactics presented in this section implement induction or case analysis on inductive or co-inductive objects (see *Inductive Definitions*).

#### destruct term

This tactic applies to any goal. The argument *term* must be of inductive or co-inductive type and the tactic generates subgoals, one for each possible form of *term*, i.e. one for each constructor of the inductive or co-inductive type. Unlike *induction*, no induction hypothesis is generated by *destruct*.

#### Variant: destruct ident

If *ident* denotes a quantified variable of the conclusion of the goal, then **destruct** *ident* behaves as intros until *ident*; **destruct** *ident*. If *ident* is not anymore dependent in the goal after application of *destruct*, it is erased (to avoid erasure, use parentheses, as in **destruct** (*ident*)).

If *ident* is a hypothesis of the context, and *ident* is not anymore dependent in the goal after application of *destruct*, it is erased (to avoid erasure, use parentheses, as in *destruct* (*ident*)).

#### Variant: destruct num

destruct *num* behaves as intros until *num* followed by destruct applied to the last introduced hypothesis.

Note: For destruction of a numeral, use syntax destruct (num) (not very interesting anyway).

#### Variant: destruct pattern

The argument of *destruct* can also be a pattern of which holes are denoted by "\_". In this case, the tactic checks that all subterms matching the pattern in the conclusion and the hypotheses are compatible and performs case analysis using this subterm.

# Variant: destruct term,

This is a shortcut for destruct term; ...; destruct term.

#### Variant: destruct term as or\_and\_intropattern\_loc

This behaves as destruct term but uses the names in or\_and\_intropattern\_loc to name the variables introduced in the context. The or\_and\_intropattern\_loc must have the form [p11 ... p1n | ... | pm1 ... pmn ] with m being the number of constructors of the type of term. Each variable introduced by destruct in the context of the i-th goal gets its name from the list pi1 ... pin in order. If there are not enough names, destruct invents names for the remaining variables to introduce. More generally, the pij can be any introduction pattern (see intros). This provides a concise notation for chaining destruction of a hypothesis.

# Variant: destruct term eqn:naming\_intropattern

This behaves as destruct *term* but adds an equation between *term* and the value that it takes in each of the possible cases. The name of the equation is specified by *naming\_intropattern* (see *intros*), in particular? can be used to let Coq generate a fresh name.

#### Variant: destruct term with bindings\_list

This behaves like destruct *term* providing explicit instances for the dependent premises of the type of *term*.

#### Variant: edestruct term

This tactic behaves like destruct term except that it does not fail if the instance of a dependent premises of the type of term is not inferable. Instead, the unresolved instances are left as existential variables to be inferred later, in the same way as eapply does.

# Variant: destruct term using term with bindings\_list

This is synonym of induction term using term with bindings\_list

### Variant: destruct term in goal\_occurrences

This syntax is used for selecting which occurrences of *term* the case analysis has to be done on. The in *goal\_occurrences* clause is an occurrence clause whose syntax and behavior is described in *occurrences sets*.

```
Variant: destruct term with bindings_list as or_and_intropattern_loc eqn:naming_intropattern
```

```
Variant: edestruct term with bindings_list as or_and_intropattern_loc eqn:naming_intropattern

These are the general forms of destruct and edestruct. They combine the effects of the with,

as, eqn:, using, and in clauses.
```

#### case term

The tactic case is a more basic tactic to perform case analysis without recursion. It behaves as elim term but using a case-analysis elimination principle and not a recursive one.

# Variant: case term with bindings\_list

Analogous to elim term with bindings list above.

# Variant: ecase term with bindings\_list ?

In case the type of term has dependent premises, or dependent premises whose values are not inferable from the with bindings\_list clause, ecase turns them into existential variables to be resolved later on

#### Variant: simple destruct ident

This tactic behaves as intros until *ident*; case *ident* when *ident* is a quantified variable of the goal.

#### Variant: simple destruct num

This tactic behaves as intros until *num*; case *ident* where *ident* is the name given by intros until *num* to the *num* -th non-dependent premise of the goal.

#### Variant: case\_eq term

The tactic case\_eq is a variant of the case tactic that allows to perform case analysis on a term without completely forgetting its original form. This is done by generating equalities between the original form of the term and the outcomes of the case analysis.

#### induction term

This tactic applies to any goal. The argument term must be of inductive type and the tactic induction generates subgoals, one for each possible form of term, i.e. one for each constructor of the inductive type.

If the argument is dependent in either the conclusion or some hypotheses of the goal, the argument is replaced by the appropriate constructor form in each of the resulting subgoals and induction hypotheses are added to the local context using names whose prefix is **IH**.

There are particular cases:

- If term is an identifier *ident* denoting a quantified variable of the conclusion of the goal, then inductionident behaves as intros until *ident*; induction *ident*. If *ident* is not anymore dependent in the goal after application of induction, it is erased (to avoid erasure, use parentheses, as in induction (*ident*)).
- If *term* is a *num*, then induction *num* behaves as intros until *num* followed by induction applied to the last introduced hypothesis.

**Note:** For simple induction on a numeral, use syntax induction (num) (not very interesting anyway).

- In case term is a hypothesis *ident* of the context, and *ident* is not anymore dependent in the goal after application of induction, it is erased (to avoid erasure, use parentheses, as in induction (*ident*)).
- The argument *term* can also be a pattern of which holes are denoted by "\_". In this case, the tactic checks that all subterms matching the pattern in the conclusion and the hypotheses are compatible and performs induction using this subterm.

#### Example

(continues on next page)

Error: Not an inductive product.

Error: Unable to find an instance for the variables ident ... ident.

Use in this case the variant elim ... with below.

# Variant: induction term as or\_and\_intropattern\_loc

This behaves as <code>induction</code> but uses the names in <code>or\_and\_intropattern\_loc</code> to name the variables introduced in the context. The <code>or\_and\_intropattern\_loc</code> must typically be of the form [ p  $_{11}$  ... p  $_{1n}$  | ... | p $_{m1}$  ... p $_{mn}$  ] with m being the number of constructors of the type of <code>term</code>. Each variable introduced by induction in the context of the i-th goal gets its name from the list p $_{i1}$  ... p $_{in}$  in order. If there are not enough names, induction invents names for the remaining variables to introduce. More generally, the p $_{ij}$  can be any disjunctive/conjunctive introduction pattern (see <code>intros</code> ...). For instance, for an inductive type with one constructor, the pattern notation (p $_1$  , ... , p $_n$ ) can be used instead of [ p $_1$  ... p $_n$ ].

# Variant: induction term with bindings list

This behaves like *induction* providing explicit instances for the premises of the type of term (see bindings list).

# Variant: einduction term

This tactic behaves like *induction* except that it does not fail if some dependent premise of the type of *term* is not inferable. Instead, the unresolved premises are posed as existential variables to be inferred later, in the same way as *eapply* does.

#### Variant: induction term using term

This behaves as *induction* but using *term* as induction scheme. It does not expect the conclusion of the type of the first *term* to be inductive.

# Variant: induction term using term with bindings\_list

This behaves as *induction* ... *using* ... but also providing instances for the premises of the type of the second *term*.

# Variant: induction term, using qualid

This syntax is used for the case *qualid* denotes an induction principle with complex predicates as the induction principles generated by Function or Functional Scheme may be.

# Variant: induction term in goal\_occurrences

This syntax is used for selecting which occurrences of *term* the induction has to be carried on. The in *goal\_occurrences* clause is an occurrence clause whose syntax and behavior is described in *occurrences* 

sets. If variables or hypotheses not mentioning term in their type are listed in goal\_occurrences, those are generalized as well in the statement to prove.

### Example

```
Lemma comm x y : x + y = y + x.
   1 subgoal
    x, y : nat
    _____
    x + y = y + x
induction y in x |- *.
   2 subgoals
    x : nat
    _____
    x + 0 = 0 + x
   subgoal 2 is:
    x + S y = S y + x
Show 2.
   subgoal 2 is:
    x, y : nat
    IHy : forall x : nat, x + y = y + x
    _____
    x + S y = S y + x
```

Variant: induction term with bindings\_list as or\_and\_intropattern\_loc using term with bindings\_list in gas Variant: einduction term with bindings\_list as or\_and\_intropattern\_loc using term with bindings\_list in These are the most general forms of induction and einduction. It combines the effects of the with, as, using, and in clauses.

### Variant: elim term

This is a more basic induction tactic. Again, the type of the argument term must be an inductive type. Then, according to the type of the goal, the tactic elim chooses the appropriate destructor and applies it as the tactic apply would do. For instance, if the proof context contains n:nat and the current goal is T of type Prop, then elim n is equivalent to apply  $nat_ind$  with (n:=n). The tactic elim does not modify the context of the goal, neither introduces the induction loading into the context of hypotheses. More generally, elim term also works when the type of term is a statement with premises and whose conclusion is inductive. In that case the tactic performs induction on the conclusion of the type of term and leaves the non-dependent premises of the type as subgoals. In the case of dependent products, the tactic tries to find an instance for which the elimination lemma applies and fails otherwise.

# Variant: elim term with bindings\_list

Allows to give explicit instances to the premises of the type of term (see bindings list).

#### Variant: eelim term

In case the type of term has dependent premises, this turns them into existential variables to be resolved later on.

```
Variant: elim term using term
Variant: elim term using term with bindings_list
```

Allows the user to give explicitly an induction principle term that is not the standard one for the

underlying inductive type of term. The  $bindings\_list$  clause allows instantiating premises of the type of term.

# Variant: elim term with bindings\_list using term with bindings\_list Variant: eelim term with bindings\_list using term with bindings\_list

These are the most general forms of *elim* and *eelim*. It combines the effects of the using clause and of the two uses of the with clause.

#### Variant: elimtype type

The argument *type* must be inductively defined. elimtype I is equivalent to cut I. intro Hn; elim Hn; clear Hn. Therefore the hypothesis Hn will not appear in the context(s) of the subgoal(s). Conversely, if t is a *term* of (inductive) type I that does not occur in the goal, then elim t is equivalent to elimtype I; 2:exact t.

#### Variant: simple induction ident

This tactic behaves as intros until *ident*; elim *ident* when *ident* is a quantified variable of the goal.

#### Variant: simple induction num

This tactic behaves as intros until *num*; elim *ident* where *ident* is the name given by intros until *num* to the *num*-th non-dependent premise of the goal.

#### double induction ident ident

This tactic is deprecated and should be replaced by induction *ident*; induction *ident* (or induction *ident*; destruct *ident* depending on the exact needs).

#### Variant: double induction num, num,

This tactic is deprecated and should be replaced by induction num1; induction num3 where num3 is the result of num2 - num1

#### dependent induction ident

The experimental tactic dependent induction performs induction- inversion on an instantiated inductive predicate. One needs to first require the Coq.Program. Equality module to use this tactic. The tactic is based on the BasicElim tactic by Conor McBride [McB00] and the work of Cristina Cornes around inversion [CT95]. From an instantiated inductive predicate and a goal, it generates an equivalent goal where the hypothesis has been generalized over its indexes which are then constrained by equalities to be the right instances. This permits to state lemmas without resorting to manually adding these equalities and still get enough information in the proofs.

### Example

Here we did not get any information on the indexes to help fulfill this proof. The problem is that, when we

use the induction tactic, we lose information on the hypothesis instance, notably that the second argument is 1 here. Dependent induction solves this problem by adding the corresponding equality to the context.

The subgoal is cleaned up as the tactic tries to automatically simplify the subgoals with respect to the generated equalities. In this enriched context, it becomes possible to solve this subgoal.

Now we are in a contradictory context and the proof can be solved.

# inversion H.

No more subgoals.

This technique works with any inductive predicate. In fact, the dependent induction tactic is just a wrapper around the induction tactic. One can make its own variant by just writing a new tactic based on the definition found in Coq.Program.Equality.

# Variant: dependent induction ident generalizing ident

This performs dependent induction on the hypothesis *ident* but first generalizes the goal by the given variables so that they are universally quantified in the goal. This is generally what one wants to do with the variables that are inside some constructors in the induction hypothesis. The other ones need not be further generalized.

#### Variant: dependent destruction ident

This performs the generalization of the instance *ident* but uses **destruct** instead of induction on the generalized hypothesis. This gives results equivalent to inversion or dependent inversion if the hypothesis is dependent.

See also the larger example of dependent induction and an explanation of the underlying technique.

# function induction (qualid term +)

The tactic functional induction performs case analysis and induction following the definition of a function. It makes use of a principle generated by Function (see Advanced recursive functions) or

Functional Scheme (see Generation of induction principles with Functional Scheme). Note that this tactic is only available after a Require Import FunInd.

### Example

```
Require Import FunInd.
    [Loading ML file extraction_plugin.cmxs ... done]
    [Loading ML file recdef_plugin.cmxs ... done]
Functional Scheme minus_ind := Induction for minus Sort Prop.
    sub equation is defined
    minus_ind is defined
Check minus_ind.
    minus_ind
          : forall P : nat -> nat -> nat -> Prop,
            (forall n m : nat, n = 0 \rightarrow P 0 m n) \rightarrow
            (forall n m k : nat, n = S k \rightarrow m = 0 \rightarrow P (S k) 0 n) \rightarrow
            (forall n m k : nat.
            n = S k \rightarrow
             forall 1 : nat, m = S 1 \rightarrow P k 1 (k - 1) \rightarrow P (S k) (S 1) (k - 1)) \rightarrow
            forall n m : nat, P n m (n - m)
Lemma le minus (n m:nat) : n - m \le n.
    1 subgoal
      n. m : nat
      _____
functional induction (minus n m) using minus_ind; simpl; auto.
    No more subgoals.
Qed.
```

Note: (qualid term) must be a correct full application of qualid. In particular, the rules for implicit arguments are the same as usual. For example use qualid if you want to write implicit arguments explicitly.

**Note:** Parentheses around *qualid* term are not mandatory and can be skipped.

Note: functional induction (f x1 x2 x3) is actually a wrapper for induction x1, x2, x3, (f x1 x2 x3) using qualid followed by a cleaning phase, where qualid is the induction principle registered for f (by the Function (see Advanced recursive functions) or Functional Scheme (see Generation of induction principles with Functional Scheme) command) corresponding to the sort of the goal. Therefore functional induction may fail if the induction scheme qualid is not defined. See also Advanced recursive functions for the function terms accepted by Function.

Note: There is a difference between obtaining an induction scheme for a function by using Function (see *Advanced recursive functions*) and by using Functional Scheme after a normal definition using Fixpoint

or Definition. See Advanced recursive functions for details.

#### See also:

Advanced recursive functions, Generation of induction principles with Functional Scheme and inversion

Error: Cannot find induction information on qualid.

Error: Not the right number of induction arguments.

Variant: functional induction (qualid term) as simple\_intropattern using term with bindings\_list Similarly to induction and elim, this allows giving explicitly the name of the introduced variables, the induction principle, and the values of dependent premises of the elimination scheme, including predicates for mutual induction when qualid is part of a mutually recursive definition.

#### discriminate term

This tactic proves any goal from an assumption stating that two structurally different terms of an inductive set are equal. For example, from (S (S 0))=(S 0) we can derive by absurdity any proposition.

The argument term is assumed to be a proof of a statement of conclusion term = term with the two terms being elements of an inductive set. To build the proof, the tactic traverses the normal forms<sup>3</sup> of the terms looking for a couple of subterms u and w (u subterm of the normal form of term and w subterm of the normal form of term), placed at the same positions and whose head symbols are two different constructors. If such a couple of subterms exists, then the proof of the current goal is completed, otherwise the tactic fails.

**Note:** The syntax discriminate *ident* can be used to refer to a hypothesis quantified in the goal. In this case, the quantified hypothesis whose name is *ident* is first introduced in the local context using intros until *ident*.

Error: No primitive equality found.

Error: Not a discriminable equality.

# Variant: discriminate num

This does the same thing as intros until *num* followed by discriminate *ident* where *ident* is the identifier for the last introduced hypothesis.

#### Variant: discriminate term with bindings\_list

This does the same thing as discriminate term but using the given bindings to instantiate parameters or hypotheses of term.

Variant: ediscriminate num

# Variant: ediscriminate term with bindings\_list ?

This works the same as discriminate but if the type of term, or the type of the hypothesis referred to by num, has uninstantiated parameters, these parameters are left as existential variables.

#### Variant: discriminate

This behaves like discriminate *ident* if ident is the name of an hypothesis to which discriminate is applicable; if the current goal is of the form *term* <> *term*, this behaves as intro *ident*; discriminate *ident*.

Error: No discriminable equalities.

<sup>&</sup>lt;sup>3</sup> Reminder: opaque constants will not be expanded by  $\delta$  reductions.

#### injection term

The injection tactic exploits the property that constructors of inductive types are injective, i.e. that if c is a constructor of an inductive type and c  $t_1$  and c  $t_2$  are equal then  $t_1$  and  $t_2$  are equal too.

If term is a proof of a statement of conclusion term = term, then injection applies the injectivity of constructors as deep as possible to derive the equality of all the subterms of term and term at positions where the terms start to differ. For example, from (S p, S n) = (q, S (S m)) we may derive S p = q and n = S m. For this tactic to work, the terms should be typed with an inductive type and they should be neither convertible, nor having a different head constructor. If these conditions are satisfied, the tactic derives the equality of all the subterms at positions where they differ and adds them as antecedents to the conclusion of the current goal.

### Example

```
Consider the following goal:
```

```
Inductive list : Set :=
| nil : list
| cons : nat -> list -> list.
Parameter P : list -> Prop.
Goal forall l n, P nil \rightarrow cons n l = cons 0 nil \rightarrow P 1.
intros.
   1 subgoal
     1 : list
     n : nat
     H : P nil
     HO : cons n l = cons O nil
     _____
     P 1
injection HO.
   1 subgoal
     1 : list
     n : nat
     H : P nil
     HO : cons n l = cons O nil
     _____
     1 = nil -> n = 0 -> P 1
```

Beware that injection yields an equality in a sigma type whenever the injected object has a dependent type P with its two instances in different types (P  $t_1 \ldots t_n$ ) and (P  $u_1 \ldots u_n$ ). If  $t_1$  and  $u_1$  are the same and have for type an inductive type for which a decidable equality has been declared using the command *Scheme Equality* (see *Generation of induction principles with Scheme*), the use of a sigma type is avoided.

**Note:** If some quantified hypothesis of the goal is named *ident*, then injection *ident* first introduces the hypothesis in the local context using intros until *ident*.

Error: Not a projectable equality but a discriminable one.

Error: Nothing to do, it is an equality between convertible terms.

Error: Not a primitive equality.

# Error: Nothing to inject.

#### Variant: injection num

This does the same thing as intros until *num* followed by injection *ident* where *ident* is the identifier for the last introduced hypothesis.

#### Variant: injection term with bindings\_list

This does the same as injection *term* but using the given bindings to instantiate parameters or hypotheses of *term*.

# Variant: einjection num

```
Variant: einjection term with bindings_list?
```

This works the same as injection but if the type of *term*, or the type of the hypothesis referred to by *num*, has uninstantiated parameters, these parameters are left as existential variables.

#### Variant: injection

If the current goal is of the form term  $\Leftrightarrow$  term, this behaves as intro ident; injection ident.

Error: goal does not satisfy the expected preconditions.

```
Variant: injection term with bindings_list? as simple_intropattern +
Variant: injection num as simple_intropattern +
Variant: injection as simple_intropattern +
Variant: einjection term with bindings_list? as simple_intropattern +
Variant: einjection num as simple_intropattern +
Variant: einjection as simple_intropattern +
```

These variants apply intros <u>simple\_intropattern</u> after the call to <u>injection</u> or <u>einjection</u> so that all equalities generated are moved in the context of hypotheses. The number of <u>simple\_intropattern</u> must not exceed the number of equalities newly generated. If it is smaller, fresh names are automatically generated to adjust the list of <u>simple\_intropattern</u> to the number of new equalities. The original equality is erased if it corresponds to a hypothesis.

```
Variant: injection term with bindings_list as injection_intropattern
Variant: injection num as injection_intropattern
Variant: injection as injection_intropattern

Variant: einjection term with bindings_list as injection_intropattern
Variant: einjection num as injection_intropattern

Variant: einjection as injection_intropattern

These are equivalent to the previous variants but using instead the syntax

injection_intropattern which intros uses. In particular as [= simple_intropattern + ]

behaves the same as as simple_intropattern +.
```

# Flag: Structural Injection

This flag ensures that injection *term* erases the original hypothesis and leaves the generated equalities in the context rather than putting them as antecedents of the current goal, as if giving injection *term* as (with an empty list of names). This flag is off by default.

#### Flag: Keep Proof Equalities

By default, *injection* only creates new equalities between *terms* whose type is in sort Type or Set, thus implementing a special behavior for objects that are proofs of a statement in Prop. This flag controls this behavior.

#### inversion ident

Let the type of *ident* in the local context be (I t), where I is a (co)inductive predicate. Then, inversion applied to *ident* derives for each possible constructor c i of (I t), all the necessary conditions that should hold for the instance (I t) to be proved by c i.

**Note:** If *ident* does not denote a hypothesis in the local context but refers to a hypothesis quantified in the goal, then the latter is first introduced in the local context using intros until *ident*.

**Note:** As inversion proofs may be large in size, we recommend the user to stock the lemmas whenever the same instance needs to be inverted several times. See *Generation of inversion principles with Derive Inversion*.

**Note:** Part of the behavior of the inversion tactic is to generate equalities between expressions that appeared in the hypothesis that is being processed. By default, no equalities are generated if they relate two proofs (i.e. equalities between *terms* whose type is in sort Prop). This behavior can be turned off by using the *Keep Proof Equalities* setting.

#### Variant: inversion num

This does the same thing as intros until *num* then inversion *ident* where *ident* is the identifier for the last introduced hypothesis.

#### Variant: inversion clear ident

This behaves as inversion and then erases *ident* from the context.

#### Variant: inversion ident as or\_and\_intropattern\_loc

This generally behaves as inversion but using names in  $or\_and\_intropattern\_loc$  for naming hypotheses. The  $or\_and\_intropattern\_loc$  must have the form  $[p_{11} \dots p_{1n} | \dots | p_{m1} \dots p_{mn}]$  with m being the number of constructors of the type of ident. Be careful that the list must be of length m even if inversion discards some cases (which is precisely one of its roles): for the discarded cases, just use an empty list (i.e. n=0). The arguments of the i-th constructor and the equalities that inversion introduces in the context of the goal corresponding to the i-th constructor, if it exists, get their names from the list  $p_{i1} \dots p_{in}$  in order. If there are not enough names, inversion invents names for the remaining variables to introduce. In case an equation splits into several equations (because inversion applies injection on the equalities it generates), the corresponding name  $p_{ij}$  in the list must be replaced by a sublist of the form  $[p_{ij1} \dots p_{ijq}]$  (or, equivalently,  $(p_{ij1}, \dots, p_{ijq})$ ) where q is the number of subequalities obtained from splitting the original equation. Here is an example. The inversion ... as variant of inversion generally behaves in a slightly more expectable way than inversion (no artificial duplication of some hypotheses referring to other hypotheses). To take benefit of these improvements, it is enough to use inversion ... as [], letting the names being finally chosen by Coq.

# Example

```
Inductive contains0 : list nat -> Prop :=
| in_hd : forall 1, contains0 (0 :: 1)
| in_t1 : forall 1 b, contains0 1 -> contains0 (b :: 1).
    contains0 is defined
    contains0_ind is defined
    contains0_sind is defined
```

(continues on next page)

# Variant: inversion num as or\_and\_intropattern\_loc

This allows naming the hypotheses introduced by inversion num in the context.

# Variant: inversion\_clear ident as or\_and\_intropattern\_loc

This allows naming the hypotheses introduced by inversion\_clear in the context. Notice that hypothesis names can be provided as if inversion were called, even though the inversion\_clear will eventually erase the hypotheses.

# Variant: inversion ident in ident

Let <u>ident</u> be identifiers in the local context. This tactic behaves as generalizing <u>ident</u>, and then performing inversion.

# Variant: inversion ident as or\_and\_intropattern\_loc in ident

This allows naming the hypotheses introduced in the context by inversion *ident* in *ident* +.

# Variant: inversion\_clear ident in ident +

Let <u>ident</u> be identifiers in the local context. This tactic behaves as generalizing <u>ident</u>, and then performing inversion\_clear.

# Variant: inversion\_clear ident as or\_and\_intropattern\_loc in ident

This allows naming the hypotheses introduced in the context by inversion\_clear *ident* in *ident*.

#### Variant: dependent inversion ident

That must be used when *ident* appears in the current goal. It acts like **inversion** and then substitutes *ident* for the corresponding @term in the goal.

# Variant: dependent inversion ident as or\_and\_intropattern\_loc

This allows naming the hypotheses introduced in the context by dependent inversion ident.

# Variant: dependent inversion\_clear ident

Like dependent inversion, except that *ident* is cleared from the local context.

#### Variant: dependent inversion\_clear ident as or\_and\_intropattern\_loc

This allows naming the hypotheses introduced in the context by dependent inversion\_clear ident.

#### Variant: dependent inversion ident with term

This variant allows you to specify the generalization of the goal. It is useful when the system fails to generalize the goal automatically. If ident has type (I t) and I has type forall (x:T), s, then term must be of type I:forall (x:T), I x -> s' where s' is the type of the goal.

### Variant: dependent inversion ident as or\_and\_intropattern\_loc with term

This allows naming the hypotheses introduced in the context by dependent inversion *ident* with *term*.

#### Variant: dependent inversion\_clear ident with term

Like dependent inversion ... with ... with but clears ident from the local context.

# Variant: dependent inversion\_clear ident as or\_and\_intropattern\_loc with term

This allows naming the hypotheses introduced in the context by dependent inversion\_clear *ident* with *term*.

#### Variant: simple inversion ident

It is a very primitive inversion tactic that derives all the necessary equalities but it does not simplify the constraints as inversion does.

#### Variant: simple inversion ident as or and intropattern loc

This allows naming the hypotheses introduced in the context by simple inversion.

# Variant: inversion ident using ident

Let *ident* have type (I t) (I an inductive predicate) in the local context, and *ident* be a (dependent) inversion lemma. Then, this tactic refines the current goal with the specified lemma.

```
Variant: inversion ident using ident in ident
```

This tactic behaves as generalizing ident, then doing inversion ident using ident.

# Variant: inversion\_sigma

This tactic turns equalities of dependent pairs (e.g., existT P x p = existT P y q, frequently left over by inversion on a dependent type family) into pairs of equalities (e.g., a hypothesis H: x = y and a hypothesis of type rew H in p = q); these hypotheses can subsequently be simplified using subst, without ever invoking any kind of axiom asserting uniqueness of identity proofs. If you want to explicitly specify the hypothesis to be inverted, or name the generated hypotheses, you can invoke induction H as  $[H1 \ H2]$  using eq\_sigT\_rect. This tactic also works for sig, sigT2, and sig2, and there are similar eq\_sig \*\*\*\_rect induction lemmas.

#### Example

Non-dependent inversion.

Let us consider the relation Le over natural numbers:

```
Inductive Le : nat \rightarrow nat \rightarrow Set := 
| LeO : forall n:nat, Le 0 n
| LeS : forall n m:nat, Le n m \rightarrow Le (S n) (S m).
```

Let us consider the following goal:

1 subgoal

To prove the goal, we may need to reason by cases on H and to derive that m is necessarily of the form (S m0) for certain m0 and that (Le n m0). Deriving these conditions corresponds to proving that the only possible constructor of (Le (S n) m) is LeS and that we can invert the arrow in the type of LeS. This inversion is possible because Le is the smallest set closed by the constructors LeO and LeS.

Note that m has been substituted in the goal for (S m0) and that the hypothesis (Le n m0) has been added to the context.

Sometimes it is interesting to have the equality m = (S m0) in the context to use it after. In that case we can use *inversion* that does not clear the equalities:

```
inversion H.
```

1 subgoal

```
P : nat -> nat -> Prop
Q : forall n m : nat, Le n m -> Prop
n, m : nat
H : Le (S n) m
n0, m0 : nat
H1 : Le n m0
H0 : n0 = n
H2 : S m0 = m
```

\_\_\_\_\_

# Example

Dependent inversion.

P n (S m0)

Let us consider the following goal:

As H occurs in the goal, we may want to reason by cases on its structure and so, we would like inversion tactics to substitute H by the corresponding @term in constructor form. Neither *inversion* nor *inversion\_clear* do such a substitution. To have such a behavior we use the dependent inversion tactics:

```
dependent inversion_clear H.
     1 subgoal
```

Q (S n) m H

(continues on next page)

Note that H has been substituted by (LeS n m0 1) and m by (S m0).

#### Example

 $Using\ inversion\_sigma.$ 

Let us consider the following inductive type of length-indexed lists, and a lemma about inverting equality of cons:

```
Require Import Coq.Logic.Eqdep_dec.
Inductive vec A : nat -> Type :=
| nil : vec A O
| \ \mathsf{cons} \ \{\mathtt{n}\} \ (\mathtt{x} \ : \ \mathtt{A}) \ (\mathtt{xs} \ : \ \mathsf{vec} \ \mathtt{A} \ \mathtt{n}) \ : \ \mathsf{vec} \ \mathtt{A} \ (\mathtt{S} \ \mathtt{n}) \, .
    vec is defined
    vec_rect is defined
    vec_ind is defined
    vec_rec is defined
    vec_sind is defined
Lemma invert_cons : forall A n x xs y ys,
          @cons A n x xs = @cons A n y ys
          -> xs = ys.
    1 subgoal
       _____
      forall (A : Type) (n : nat) (x : A) (xs : vec A n) (y : A) (ys : vec A n),
      cons A x xs = cons A y ys -> xs = ys
Proof.
intros A n x xs y ys H.
    1 subgoal
      A : Type
      n : nat
      x : A
      xs : vec A n
      y : A
      ys : vec A n
      H : cons A x xs = cons A y ys
      _____
      xs = ys
```

After performing inversion, we are left with an equality of existTs:

```
inversion H.

1 subgoal
```

(continues on next page)

We can turn this equality into a usable form with inversion\_sigma:

To finish cleaning up the proof, we will need to use the fact that all proofs of n = n for n a nat are eq\_refl:

```
let H := match goal with H : n = n |- _ => H end in
pose proof (Eqdep_dec.UIP_refl_nat _ H); subst H.
   1 subgoal
     A : Type
     n : nat
     x : A
     xs : vec A n
     y : A
     ys : vec A n
     H : cons A x xs = cons A y ys
     H1 : x = y
     H3 : eq_rect n (fun a : nat => vec A a) xs n eq_refl = ys
     _____
     xs = ys
simpl in *.
   1 subgoal
     A : Type
     n : nat
     x : A
     xs : vec A n
```

(continues on next page)

Finally, we can finish the proof:

#### assumption.

No more subgoals.

Qed.

#### fix ident num

This tactic is a primitive tactic to start a proof by induction. In general, it is easier to rely on higher-level induction tactics such as the ones described in *induction*.

In the syntax of the tactic, the identifier *ident* is the name given to the induction hypothesis. The natural number *num* tells on which premise of the current goal the induction acts, starting from 1, counting both dependent and non dependent products, but skipping local definitions. Especially, the current lemma must be composed of at least *num* products.

Like in a fix expression, the induction hypotheses have to be used on structurally smaller arguments. The verification that inductive proof arguments are correct is done only at the time of registering the lemma in the environment. To know if the use of induction hypotheses is correct at some time of the interactive development of a proof, use the command Guarded (see Section Requesting information).

```
Variant: fix ident num with (ident binder [{struct ident}] : type)
```

This starts a proof by mutual induction. The statements to be simultaneously proved are respectively forall binder ... binder, type. The identifiers *ident* are the names of the induction hypotheses. The identifiers *ident* are the respective names of the premises on which the induction is performed in the statements to be simultaneously proved (if not given, the system tries to guess itself what they are).

# cofix ident

This tactic starts a proof by coinduction. The identifier *ident* is the name given to the coinduction hypothesis. Like in a cofix expression, the use of induction hypotheses have to guarded by a constructor. The verification that the use of co-inductive hypotheses is correct is done only at the time of registering the lemma in the environment. To know if the use of coinduction hypotheses is correct at some time of the interactive development of a proof, use the command Guarded (see Section Requesting information).

```
Variant: cofix ident with (ident binder : type)
```

This starts a proof by mutual coinduction. The statements to be simultaneously proved are respectively forall binder ... binder, type The identifiers *ident* are the names of the coinduction hypotheses.

#### 5.3.6 Rewriting expressions

These tactics use the equality eq:forall A:Type, A->A->Prop defined in file Logic.v (see Logic). The notation for eq T t u is simply t=u dropping the implicit type of t and u.

#### rewrite term

This tactic applies to any goal. The type of term must have the form

```
forall (x_1 : A_1) ... (x_n : A_n), eq term_1 term_2 .
```

where eq is the Leibniz equality or a registered setoid equality.

Then rewrite term finds the first subterm matching  $term_1$  in the goal, resulting in instances  $term_1$ ' and  $term_2$ ' and then replaces every occurrence of  $term_1$ ' by  $term_2$ '. Hence, some of the variables  $x_i$  are solved by unification, and some of the types  $A_1$ , ...,  $A_n$  become new subgoals.

Error: The term provided does not end with an equation.

Error: Tactic generated a subgoal identical to the original goal. This happens if term does not occ

#### Variant: rewrite -> term

Is equivalent to rewrite term

#### Variant: rewrite <- term

Uses the equality  $term_1 = term_2$  from right to left

#### Variant: rewrite term in goal\_occurrences

Analogous to rewrite term but rewriting is done following the clause goal\_occurrences. For instance:

- rewrite H in H' will rewrite H in the hypothesis H' instead of the current goal.
- rewrite H in H' at 1, H'' at 2 |- \* means rewrite H; rewrite H in H' at 1; rewrite H in H'' at 2. In particular a failure will happen if any of these three simpler tactics fails.
- rewrite H in \* |- will do rewrite H in H' for all hypotheses H' different from H. A success will happen as soon as at least one of these simpler tactics succeeds.
- rewrite H in \* is a combination of rewrite H and rewrite H in \* |- that succeeds if at least one of these two tactics succeeds.

Orientation  $\rightarrow$  or  $\leftarrow$  can be inserted before the term to rewrite.

#### Variant: rewrite term at occurrences

Rewrite only the given occurrences of term. Occurrences are specified from left to right as for pattern (pattern). The rewrite is always performed using setoid rewriting, even for Leibniz's equality, so one has to Import Setoid to use this variant.

# Variant: rewrite term by tactic

Use tactic to completely solve the side-conditions arising from the rewrite.

```
Variant: rewrite orientation term, in ident?
```

Is equivalent to the n successive tactics rewrite term;, each one working on the first subgoal generated by the previous one. An orientation -> or <- can be inserted before each term to rewrite. One unique clause can be added at the end after the keyword in; it will then affect all rewrite operations.

In all forms of rewrite described above, a *term* to rewrite can be immediately prefixed by one of the following modifiers:

- ?: the tactic rewrite ?term performs the rewrite of term as many times as possible (perhaps zero time). This form never fails.
- num?: works similarly, except that it will do at most num rewrites.
- !: works as ?, except that at least one rewrite should succeed, otherwise the tactic fails.

num! (or simply num): precisely num rewrites of term will be done, leading to failure if these num
rewrites are not possible.

#### Variant: erewrite term

This tactic works as rewrite term but turning unresolved bindings into existential variables, if any, instead of failing. It has the same variants as rewrite has.

#### Flag: Keyed Unification

Makes higher-order unification used by *rewrite* rely on a set of keys to drive unification. The subterms, considered as rewriting candidates, must start with the same key as the left- or right-hand side of the lemma given to rewrite, and the arguments are then unified up to full reduction.

#### replace term with term'

This tactic applies to any goal. It replaces all free occurrences of term in the current goal with term and generates an equality term = term as a subgoal. This equality is automatically solved if it occurs among the assumptions, or if its symmetric form occurs. It is equivalent to cut term = term; [intro  $H_n$ ; rewrite  $\leftarrow H_n$ ; clear  $H_n \mid l$  assumption  $\mid l$  symmetry; try assumption].

Error: Terms do not have convertible types.

#### Variant: replace term with term' by tactic

This acts as replace *term* with *term*, but applies tactic to solve the generated subgoal *term* = *term*.

#### Variant: replace term

Replaces term with term, using the first assumption whose type has the form term = term, or term, = term.

#### Variant: replace -> term

Replaces term with term' using the first assumption whose type has the form term = term'

#### Variant: replace <- term

Replaces term with term' using the first assumption whose type has the form term' = term

```
Variant: replace term with term? in goal_occurrences by tactic?
```

Variant: replace -> term in goal\_occurrences

Variant: replace <- term in goal\_occurrences

Acts as before but the replacements take place in the specified clauses (goal\_occurrences) (see Performing computations) and not only in the conclusion of the goal. The clause argument must not contain any type of nor value of.

#### Variant: cutrewrite <- (term = term')

Deprecated since version 8.5: This tactic can be replaced by enough (term = term') as <-.

# Variant: cutrewrite -> (term = term')

Deprecated since version 8.5: This tactic can be replaced by enough (term = term') as ->.

# subst ident

This tactic applies to a goal that has ident in its context and (at least) one hypothesis, say H, of type ident = t or t = ident with ident not occurring in t. Then it replaces ident by t everywhere in the goal (in the hypotheses and in the conclusion) and clears ident and H from the context.

If *ident* is a local definition of the form *ident* := t, it is also unfolded and cleared.

#### Note:

- When several hypotheses have the form ident = t or t = ident, the first one is used.
- If H is itself dependent in the goal, it is replaced by the proof of reflexivity of equality.

Variant: subst ident

This is equivalent to subst  $ident_1$ ; ...; subst  $ident_n$ .

#### Variant: subst

This applies subst repeatedly from top to bottom to all identifiers of the context for which an equality of the form ident = t or t = ident or ident := t exists, with ident not occurring in t.

#### Flag: Regular Subst Tactic

This flag controls the behavior of *subst*. When it is activated (it is by default), *subst* also deals with the following corner cases:

- A context with ordered hypotheses  $ident_1 = ident_2$  and  $ident_1 = t$ , or  $t = ident_1$  with t not a variable, and no other hypotheses of the form  $ident_2 = u$  or  $u = ident_2$ ; without the flag, a second call to subst would be necessary to replace  $ident_2$  by t or t respectively.
- The presence of a recursive equation which without the flag would be a cause of failure of subst.
- A context with cyclic dependencies as with hypotheses ident<sub>1</sub> = f ident<sub>2</sub> and ident<sub>2</sub> = g ident<sub>1</sub> which without the flag would be a cause of failure of subst.

Additionally, it prevents a local definition such as ident := t to be unfolded which otherwise it would exceptionally unfold in configurations containing hypotheses of the form ident = u, or u = ident with u not a variable. Finally, it preserves the initial order of hypotheses, which without the flag it may break. default.

#### stepl term

This tactic is for chaining rewriting steps. It assumes a goal of the form R term where R is a binary relation and relies on a database of lemmas of the form forall x y z, R x y -> eq x z -> R z y where eq is typically a setoid equality. The application of stepl term then replaces the goal by R term term and adds a new goal stating eq term term.

#### Command: Declare Left Step term

Adds *term* to the database used by *stepl*.

This tactic is especially useful for parametric setoids which are not accepted as regular setoids for rewrite and setoid\_replace (see Generalized rewriting).

#### Variant: stepl term by tactic

This applies stepl term then applies tactic to the second goal.

#### Variant: stepr term by tactic

This behaves as stepl but on the right-hand-side of the binary relation. Lemmas are expected to be of the form forall x y z, R x y -> eq y z -> R x z.

# Command: Declare Right Step term

Adds term to the database used by stepr.

#### change term

This tactic applies to any goal. It implements the rule Conv given in *Subtyping rules*. change U replaces the current goal T with U providing that U is well-formed and that T and U are convertible.

Error: Not convertible.

#### Variant: change term with term'

This replaces the occurrences of *term* by *term*' in the current goal. The term *term* and *term*' must be convertible.

Variant: change term at num + with term'

This replaces the occurrences numbered num of term by term' in the current goal. The terms

term and term' must be convertible.

Error: Too few occurrences.

```
Variant: change term at num with term in ident
```

This applies the *change* tactic not to the goal but to the hypothesis *ident*.

Variant: now\_show term

This is a synonym of **change** *term*. It can be used to make some proof steps explicit when refactoring a proof script to make it readable.

See also:

Performing computations

# 5.3.7 Performing computations

This set of tactics implements different specialized usages of the tactic *change*.

All conversion tactics (including *change*) can be parameterized by the parts of the goal where the conversion can occur. This is done using *goal clauses* which consists in a list of hypotheses and, optionally, of a reference to the conclusion of the goal. For defined hypothesis it is possible to specify if the conversion should occur on the type part, the body part or both (default).

Goal clauses are written after a conversion tactic (tactics set, rewrite, replace and autorewrite also use goal clauses) and are introduced by the keyword in. If no goal clause is provided, the default is to perform the conversion only in the conclusion.

The syntax and description of the various goal clauses is the following:

- in ident + I- only in hypotheses ident
- in ident | \* in hypotheses ident | and in the conclusion
- in \* |- in every hypothesis
- in \* (equivalent to in \* | \*) everywhere
- in (type of *ident*) (value of *ident*) ... |- in type part of *ident*, in the value part of *ident*, etc.

For backward compatibility, the notation in ident performs the conversion in hypotheses ident.



These parameterized reduction tactics apply to any goal and perform the normalization of the goal according to the specified flags. In correspondence with the kinds of reduction considered in Coq namely  $\beta$  (reduction of functional application),  $\delta$  (unfolding of transparent constants, see *Controlling the reduction strategies and the conversion algorithm*),  $\iota$  (reduction of pattern matching over a constructed term, and unfolding of fix and cofix expressions) and  $\zeta$  (contraction of local definitions), the flags are either beta, delta, match, fix, cofix, iota or zeta. The iota flag is a shorthand for match, fix and cofix. The delta flag itself can be refined into delta [ qualid ] or delta - [ qualid ], restricting in the first case the constants to unfold to the constants listed, and restricting in the second case the constant to unfold to all but the ones explicitly mentioned. Notice that the delta flag does not apply to variables bound by a let-in construction inside the term itself (use here the zeta

flag). In any cases, opaque constants are not unfolded (see Controlling the reduction strategies and the conversion algorithm).

Normalization according to the flags is done by first evaluating the head of the expression into a weak-head normal form, i.e. until the evaluation is blocked by a variable (or an opaque constant, or an axiom), as e.g. in x u1 ... un , or match x with ... end, or (fix f x {struct x} := ...) x, or is a constructed form (a  $\lambda$ -expression, a constructor, a cofixpoint, an inductive type, a product type, a sort), or is a redex that the flags prevent to reduce. Once a weak-head normal form is obtained, subterms are recursively reduced using the same strategy.

Reduction to weak-head normal form can be done using two strategies: *lazy* (lazy tactic), or *call-by-value* (cbv tactic). The lazy strategy is a call-by-need strategy, with sharing of reductions: the arguments of a function call are weakly evaluated only when necessary, and if an argument is used several times then it is weakly computed only once. This reduction is efficient for reducing expressions with dead code. For instance, the proofs of a proposition exists x. P(x) reduce to a pair of a witness t, and a proof that t satisfies the predicate P. Most of the time, t may be computed without computing the proof of P(t), thanks to the lazy strategy.

The call-by-value strategy is the one used in ML languages: the arguments of a function call are systematically weakly evaluated first. Despite the lazy strategy always performs fewer reductions than the call-by-value strategy, the latter is generally more efficient for evaluating purely computational expressions (i.e. with little dead code).

# Variant: compute Variant: cbv

These are synonyms for cbv beta delta iota zeta.

## Variant: lazy

This is a synonym for lazy beta delta iota zeta.

```
Variant: compute [ qualid + ]

Variant: cbv [ qualid + ]
```

These are synonyms of cbv beta delta qualid iota zeta.

```
Variant: compute - [ qualid + ]

Variant: cbv - [ qualid + ]
```

These are synonyms of cbv beta delta - qualid iota zeta.

```
Variant: lazy [ qualid + ]
Variant: lazy - [ qualid + ]
```

These are respectively synonyms of lazy beta delta qualid iota zeta and lazy beta delta qualid iota zeta.

# Variant: vm\_compute

This tactic evaluates the goal using the optimized call-by-value evaluation by tecode-based virtual machine described in [GregoireL02]. This algorithm is dramatically more efficient than the algorithm used for the cbv tactic, but it cannot be fine-tuned. It is especially interesting for full evaluation of algebraic objects. This includes the case of reflection-based tactics.

#### Variant: native\_compute

This tactic evaluates the goal by compilation to OCaml as described in [BDenesGregoire11]. If Coq is running in native code, it can be typically two to five times faster than <code>vm\_compute</code>. Note however that the compilation cost is higher, so it is worth using only for intensive computations.

## Flag: NativeCompute Profiling

On Linux, if you have the perf profiler installed, this flag makes it possible to profile native compute evaluations.

### Option: NativeCompute Profile Filename string

This option specifies the profile output; the default is native\_compute\_profile.data. The actual filename used will contain extra characters to avoid overwriting an existing file; that filename is reported to the user. That means you can individually profile multiple uses of native\_compute in a script. From the Linux command line, run perf report on the profile file to see the results. Consult the perf documentation for more details.

### Flag: Debug Cbv

This flag makes cbv (and its derivative compute) print information about the constants it encounters and the unfolding decisions it makes.

red

This tactic applies to a goal that has the form:

```
forall (x:T1) ... (xk:Tk), T
```

with T  $\beta\iota\zeta$ -reducing to c  $t_1$  ...  $t_n$  and c a constant. If c is transparent then it replaces c with its definition (say t) and then reduces (t  $t_1$  ...  $t_n$ ) according to  $\beta\iota\zeta$ -reduction rules.

Error: Not reducible.

Error: No head constant to reduce.

hnf

This tactic applies to any goal. It replaces the current goal with its head normal form according to the  $\beta\delta\iota\zeta$ -reduction rules, i.e. it reduces the head of the goal until it becomes a product or an irreducible term. All inner  $\beta\iota$ -redexes are also reduced.

Example: The term fun  $n : nat \Rightarrow S n + S n$  is not reduced by hnf.

**Note:** The  $\delta$  rule only applies to transparent constants (see Controlling the reduction strategies and the conversion algorithm on transparency and opacity).

# cbn simpl

These tactics apply to any goal. They try to reduce a term to something still readable instead of fully normalizing it. They perform a sort of strong normalization with two key differences:

- They unfold a constant if and only if it leads to a *ι*-reduction, i.e. reducing a match or unfolding a fixpoint.
- While reducing a constant unfolding to (co)fixpoints, the tactics use the name of the constant the (co)fixpoint comes from instead of the (co)fixpoint definition in recursive calls.

The cbn tactic is claimed to be a more principled, faster and more predictable replacement for simpl.

The cbn tactic accepts the same flags as cbv and lazy. The behavior of both simpl and cbn can be tuned using the Arguments vernacular command as follows:

• A constant can be marked to be never unfolded by cbn or simpl:

# Example

Arguments minus n m : simpl never.

After that command an expression like (minus (S x) y) is left untouched by the tactics cbn and simpl.

• A constant can be marked to be unfolded only if applied to enough arguments. The number of arguments required can be specified using the / symbol in the argument list of the Arguments vernacular command.

# Example

After that command the expression ( $f \setminus g$ ) is left untouched by simpl while (( $f \setminus g$ ) t) is reduced to ( $f \setminus g$ ). The same mechanism can be used to make a constant volatile, i.e. always unfolded.

#### Example

```
Definition volatile := fun x : nat => x. volatile is defined 
Arguments volatile / x.
```

• A constant can be marked to be unfolded only if an entire set of arguments evaluates to a constructor. The ! symbol can be used to mark such arguments.

#### Example

```
Arguments minus !n !m.
```

After that command, the expression (minus (S x) y) is left untouched by simpl, while (minus (S x) (S y)) is reduced to (minus x y).

• A special heuristic to determine if a constant has to be unfolded can be activated with the following command:

#### Example

```
Arguments minus n m : simpl nomatch.
```

The heuristic avoids to perform a simplification step that would expose a match construct in head position. For example the expression (minus  $(S \times x)$ )  $(S \times y)$  is simplified to (minus  $(S \times x)$ ) even if an extra simplification is possible.

In detail, the tactic simpl first applies  $\beta\iota$ -reduction. Then, it expands transparent constants and tries to reduce further using  $\beta\iota$ -reduction. But, when no  $\iota$  rule is applied after unfolding then  $\delta$ -reductions are not applied. For instance trying to use simpl on (plus n 0) = n changes nothing.

Notice that only transparent constants whose name can be reused in the recursive calls are possibly unfolded by simpl. For instance a constant defined by plus' := plus is possibly unfolded and reused in the recursive calls, but a constant such as succ := plus (S 0) is never unfolded. This is the main difference between simpl and cbn. The tactic cbn reduces whenever it will be able to reuse it or not: succ t is reduced to S t.

Variant: cbn [ qualid + ]

Variant: cbn - [ qualid + ]

These are respectively synonyms of cbn beta delta [ qualid ] iota zeta and cbn beta delta - [ qualid ] iota zeta (see cbn).

# Variant: simpl pattern

This applies *simpl* only to the subterms matching *pattern* in the current goal.

Variant: simpl pattern at num +

This applies simpl only to the num occurrences of the subterms matching pattern in the current goal.

Error: Too few occurrences.

Variant: simpl qualid Variant: simpl string

This applies simpl only to the applicative subterms whose head occurrence is the unfoldable constant qualid (the constant can be referred to by its notation using string if such a notation exists).

Variant: simpl qualid at num + Variant: simpl string at num +

This applies simpl only to the num applicative subterms whose head occurrence is qualid (or string).

#### Flag: Debug RAKAM

This flag makes cbn print various debugging information. RAKAM is the Refolding Algebraic Krivine Abstract Machine.

#### unfold qualid

This tactic applies to any goal. The argument qualid must denote a defined transparent constant or local definition (see *Definitions* and *Controlling the reduction strategies and the conversion algorithm*). The tactic unfold applies the  $\delta$  rule to each occurrence of the constant to which qualid refers in the current goal and then replaces it with its  $\beta\iota\zeta$ -normal form. Use the general reduction tactics if you want to avoid this final reduction, for instance cbv delta [qualid].

# Error: Cannot coerce qualid to an evaluable reference.

This error is frequent when trying to unfold something that has defined as an inductive type (or constructor) and not as a definition.

# 

unfold le.

(continues on next page)

```
Toplevel input, characters 0-10:
> unfold le.
> ^^^^^^
Error: Cannot coerce le to an evaluable reference.
```

This error can also be raised if you are trying to unfold something that has been marked as opaque.

# 

# Variant: unfold qualid in goal\_occurrences

Replaces *qualid* in hypothesis (or hypotheses) designated by *goal\_occurrences* with its definition and replaces the hypothesis with its  $\beta\iota$  normal form.

Variant: unfold qualid,

Replaces qualid, with their definitions and replaces the current goal with its  $\beta\iota$  normal form.

Variant: unfold qualid at occurrences,

The list *occurrences* specify the occurrences of *qualid* to be unfolded. Occurrences are located from left to right.

Error: Bad occurrence number of qualid.

Error: qualid does not occur.

# Variant: unfold string

If string denotes the discriminating symbol of a notation (e.g. "+") or an expression defining a notation (e.g. "\_ + \_"), and this notation denotes an application whose head symbol is an unfoldable constant, then the tactic unfolds it.

#### Variant: unfold string%ident

This is variant of unfold string where string gets its interpretation from the scope bound to the delimiting key ident instead of its default interpretation (see Local interpretation rules for notations).



This is the most general form.

#### fold term

This tactic applies to any goal. The term term is reduced using the red tactic. Every occurrence of the resulting term in the goal is then replaced by term. This tactic is particularly useful when a fixpoint definition has been wrongfully unfolded, making the goal very hard to read. On the other hand, when an unfolded function applied to its argument has been reduced, the fold tactic won't do anything.

```
Example
Goal \sim 0=0.
   1 subgoal
     _____
     0 <> 0
unfold not.
   1 subgoal
     0 = 0 -> False
Fail progress fold not.
   The command has indeed failed with message:
   Failed to progress.
pattern (0 = 0).
   1 subgoal
     _____
     (fun P : Prop \Rightarrow P \rightarrow False) (0 = 0)
fold not.
   1 subgoal
     _____
     0 <> 0
```

# Variant: fold term

Equivalent to fold term; ...; fold term.

#### pattern term

This command applies to any goal. The argument term must be a free subterm of the current goal. The command pattern performs  $\beta$ -expansion (the inverse of  $\beta$ -reduction) of the current goal (say T) by

- replacing all occurrences of term in T with a fresh variable
- abstracting this variable
- applying the abstracted goal to term

For instance, if the current goal T is expressible as  $\varphi(t)$  where the notation captures all the instances of t in  $\varphi(t)$ , then pattern t transforms it into (fun x:A =>  $\varphi(x)$ ) t. This tactic can be used, for instance, when the tactic apply fails on matching.

# Variant: pattern term at num +

Only the occurrences  $num^+$  of term are considered for  $\beta$ -expansion. Occurrences are located from left to right.

Variant: pattern term at - num +

All occurrences except the occurrences of indexes num of term are considered for  $\beta$ -expansion. Occurrences are located from left to right.

Variant: pattern term,

Starting from a goal  $\varphi(t_1 \ldots t_m)$ , the tactic pattern  $t_1$ , ...,  $t_m$  generates the equivalent goal (fun  $(x_1:A_1)$  ...  $(x_m:A_m) \Rightarrow \varphi(x_1 \ldots x_m)$ )  $t_1 \ldots t_m$ . If  $t_i$  occurs in one of the generated types  $A_i$  these occurrences will also be considered and possibly abstracted.

Variant: pattern term at num +

This behaves as above but processing only the occurrences num + of term starting from term.

Variant: pattern term at -? num +,

This is the most general syntax that combines the different variants.

# Conversion tactics applied to hypotheses

tactic in ident,

Applies tactic (any of the conversion tactics listed in this section) to the hypotheses ident

If *ident* is a local definition, then *ident* can be replaced by type of *ident* to address not the body but the type of the local definition.

Example: unfold not in (type of H1) (type of H3).

Error: No such hypothesis: ident.

# 5.3.8 Automation

auto

This tactic implements a Prolog-like resolution procedure to solve the current goal. It first tries to solve the goal using the *assumption* tactic, then it reduces the goal to an atomic one using *intros* and introduces the newly generated hypotheses as hints. Then it looks at the list of tactics associated to the head symbol of the goal and tries to apply one of them (starting from the tactics with lower cost). This process is recursively applied to the generated subgoals.

By default, *auto* only uses the hypotheses of the current goal and the hints of the database named core.

Warning: auto uses a weaker version of apply that is closer to simple apply so it is expected that sometimes auto will fail even if applying manually one of the hints would succeed.

Variant: auto num

Forces the search depth to be num. The maximal search depth is 5 by default.

Variant: auto with ident to the database core.

**Note:** Use the fake database nocore if you want to *not* use the core database.

#### Variant: auto with \*

Uses all existing hint databases. Using this variant is highly discouraged in finished scripts since it is both slower and less robust than the variant where the required databases are explicitly listed.

#### See also:

The Hints Databases for auto and eauto for the list of pre-defined databases and the way to create or extend a database.



Uses lemmas  $qualid_i$  in addition to hints. If qualid is an inductive type, it is the collection of its constructors which are added as hints.

**Note:** The hints passed through the using clause are used in the same way as if they were passed through a hint database. Consequently, they use a weaker version of *apply* and auto using *qualid* may fail where apply *qualid* succeeds.

Given that this can be seen as counter-intuitive, it could be useful to have an option to use full-blown apply for lemmas passed through the using clause. Contributions welcome!

#### Variant: info\_auto

Behaves like *auto* but shows the tactics it uses to solve the goal. This variant is very useful for getting a better understanding of automation, or to know what lemmas/assumptions were used.

#### Variant: debug auto


Behaves like *auto* but shows the tactics it tries to solve the goal, including failing paths.



This is the most general form, combining the various options.

#### Variant: trivial

This tactic is a restriction of auto that is not recursive and tries only hints that cost 0. Typically it solves trivial equalities like X=X.



**Note:** *auto* and *trivial* either solve completely the goal or else succeed without changing the goal. Use solve [ auto ] and solve [ trivial ] if you would prefer these tactics to fail when they do not manage to solve the goal.

Flag: Info Auto Flag: Debug Auto Flag: Info Trivial

#### Flag: Debug Trivial

These flags enable printing of informative or debug information for the auto and trivial tactics.

#### eauto

This tactic generalizes auto. While auto does not try resolution hints which would leave existential variables in the goal, eauto does try them (informally speaking, it internally uses a tactic close to simple eapply instead of a tactic close to simple apply in the case of auto). As a consequence, eauto can solve such a goal:

#### Example

Note that ex\_intro should be declared as a hint.



The various options for eauto are the same as for auto.

eauto also obeys the following flags:

Flag: Info Eauto Flag: Debug Eauto

See also:

The Hints Databases for auto and eauto

```
autounfold with ident +
```

This tactic unfolds constants that were declared through a *Hint Unfold* in the given databases.

```
Variant: autounfold with ident in goal_occurrences

Performs the unfolding in the given clause (goal_occurrences).
```

Variant: autounfold with \*

Uses the unfold hints declared in all the hint databases.

```
autorewrite with ident
```

This tactic carries out rewritings according to the rewriting rule bases ident.

Each rewriting rule from the base *ident* is applied to the main subgoal until it fails. Once all the rules have been processed, if the main subgoal has progressed (e.g., if it is distinct from the initial main goal) then the rules of this base are processed again. If the main subgoal has not progressed then the next base is processed. For the bases, the behavior is exactly similar to the processing of the rewriting rules.

The rewriting rule bases are built with the *Hint Rewrite* command.

Warning: This tactic may loop if you build non terminating rewriting systems.

Variant: autorewrite with ident using tactic

Performs, in the same way, all the rewritings of the bases ident applying tactic to the main subgoal after each rewriting step.

Variant: autorewrite with ident in qualid

Performs all the rewritings in hypothesis qualid.

Variant: autorewrite with ident in qualid using tactic

Performs all the rewritings in hypothesis qualid applying tactic to the main subgoal after each rewriting step.

Variant: autorewrite with <u>ident</u> in goal\_occurrences

Performs all the rewriting in the clause goal\_occurrences.

#### See also:

Hint-Rewrite for feeding the database of lemmas used by autorewrite and autorewrite for examples showing the use of this tactic.

#### easy

This tactic tries to solve the current goal by a number of standard closing steps. In particular, it tries to close the current goal using the closing tactics trivial, reflexivity, symmetry, contradiction and inversion of hypothesis. If this fails, it tries introducing variables and splitting and-hypotheses, using the closing tactics afterwards, and splitting the goal using split and recursing.

This tactic solves goals that belong to many common classes; in particular, many cases of unsatisfiable hypotheses, and simple equality goals are usually solved by this tactic.

#### Variant: now tactic

Run tactic followed by easy. This is a notation for tactic; easy.

#### 5.3.9 Controlling automation

#### The hints databases for auto and eauto

The hints for auto and eauto are stored in databases. Each database maps head symbols to a list of hints.

#### Command: Print Hint ident

Use this command to display the hints associated to the head symbol *ident* (see *Print Hint*). Each hint has a cost that is a nonnegative integer, and an optional pattern. The hints with lower cost are tried first. A hint is tried by *auto* when the conclusion of the current goal matches its pattern or when it has no pattern.

#### **Creating Hint databases**

One can optionally declare a hint database using the command *Create HintDb*. If a hint is added to an unknown database, it will be automatically created.

## Command: Create HintDb ident discriminated?

This command creates a new database named *ident*. The database is implemented by a Discrimination Tree (DT) that serves as an index of all the lemmas. The DT can use transparency information to

decide if a constant should be indexed or not (c.f. The hints databases for auto and eauto), making the retrieval more efficient. The legacy implementation (the default one for new databases) uses the DT only on goals without existentials (i.e., auto goals), for non-Immediate hints and does not make use of transparency hints, putting more work on the unification that is run after retrieval (it keeps a list of the lemmas in case the DT is not used). The new implementation enabled by the discriminated option makes use of DTs in all cases and takes transparency information into account. However, the order in which hints are retrieved from the DT may differ from the order in which they were inserted, making this implementation observationally different from the legacy one.

# Command: Hint hint\_definition : ident +

The general command to add a hint to some databases ident. The various possible hint\_definitions are given below.

#### Variant: Hint hint definition

No database name is given: the hint is registered in the core database.

Deprecated since version 8.10.

# Variant: Local Hint hint\_definition : ident +

This is used to declare hints that must not be exported to the other modules that require and import the current module. Inside a section, the flag Local is useless since hints do not survive anyway to the closure of sections.

# Variant: Hint Resolve term | num | pattern | : ident

This command adds simple apply term to the hint list with the head symbol of the type of term. The cost of that hint is the number of subgoals generated by simple apply term or num if specified. The associated pattern is inferred from the conclusion of the type of term or the given pattern if specified. In case the inferred type of term does not start with a product the tactic added in the hint list is exact term. In case this type can however be reduced to a type starting with a product, the tactic simple apply term is also stored in the hints list. If the inferred type of term contains a dependent quantification on a variable which occurs only in the premisses of the type and not in its conclusion, no instance could be inferred for the variable by unification with the goal. In this case, the hint is added to the hint list of eauto instead of the hint list of auto and a warning is printed. A typical example of a hint that is used only by eauto is a transitivity lemma.

#### Error: term cannot be used as a hint

The head symbol of the type of term is a bound variable such that this tactic cannot be associated to a constant.

Variant: Hint Resolve term : ident
Adds each Hint Resolve term.

Variant: Hint Resolve -> term : ident

Adds the left-to-right implication of an equivalence as a hint (informally the hint will be used as apply <- term, although as mentioned before, the tactic actually used is a restricted version of apply).

#### Variant: Hint Resolve <- term

Adds the right-to-left implication of an equivalence as a hint.

#### Variant: Hint Immediate term : ident

This command adds simple apply *term*; trivial to the hint list associated with the head symbol of the type of *ident* in the given database. This tactic will fail if all the subgoals generated by simple apply *term* are not solved immediately by the *trivial* tactic (which only tries tactics with cost 0). This command is useful for theorems such as the symmetry of equality or n+1=m+1 ->

n=m that we may like to introduce with a limited use in order to avoid useless proof-search. The cost of this tactic (which never generates subgoals) is always 1, so that it is not used by trivial itself

Error: term cannot be used as a hint

Variant: Hint Immediate term: : ident
Adds each Hint Immediate term.

Variant: Hint Constructors qualid : ident

If *qualid* is an inductive type, this command adds all its constructors as hints of type Resolve. Then, when the conclusion of current goal has the form (*qualid* ...), *auto* will try to apply each constructor.

Error: qualid is not an inductive type

Variant: Hint Constructors qualid : ident

Extends the previous command for several inductive types.

Variant: Hint Unfold qualid: ident

This adds the tactic unfold qualid to the hint list that will only be used when the head constant of the goal is qualid. Its cost is 4.

Variant: Hint Unfold qualid +

Extends the previous command for several defined constants.

Variant: Hint Transparent qualid : ident

Variant: Hint Opaque qualid : ident

This adds transparency hints to the database, making *qualid* transparent or opaque constants during resolution. This information is used during unification of the goal with any lemma in the database and inside the discrimination network to relax or constrain it in the case of discriminated databases.

This sets the transparency flag used during unification of hints in the database for all constants or all variables, overwriting the existing settings of opacity. It is advised to use this just after a *Create HintDb* command.

Variant: Hint Extern num pattern? => tactic : ident

This hint type is to extend auto with tactics other than apply and unfold. For that, we must specify a cost, an optional pattern and a tactic to execute.

#### Example

Hint Extern 4 ( $\sim$ (\_ = \_)) => discriminate : core.

Now, when the head of the goal is a disequality, **auto** will try discriminate if it does not manage to solve the goal with hints with a cost less than 4.

One can even use some sub-patterns of the pattern in the tactic script. A sub-pattern is a question mark followed by an identifier, like ?X1 or ?X2. Here is an example:

#### Example

Variant: Hint Cut regexp : ident

Warning: These hints currently only apply to typeclass proof search and the typeclasses eauto tactic.

This command can be used to cut the proof-search tree according to a regular expression matching paths to be cut. The grammar for regular expressions is the following. Beware, there is no operator precedence during parsing, one can check with *Print HintDb* to verify the current cut expression:

```
regexp ::= ident (hint or instance identifier)
    _ (any hint)
    regexp | regexp (disjunction)
    regexp regexp (sequence)
    regexp * (Kleene star)
    emp (empty)
    eps (epsilon)
    ( regexp )
```

The emp regexp does not match any search path while eps matches the empty path. During proof search, the path of successive successful hints on a search branch is recorded, as a list of identifiers for the hints (note that <code>Hint Extern</code>'s do not have an associated identifier). Before applying any hint <code>ident</code> the current path p extended with <code>ident</code> is matched against the current cut expression c associated to the hint database. If matching succeeds, the hint is <code>not</code> applied. The semantics of <code>Hint Cut regexp</code> is to set the cut expression to <code>c | regexp</code>, the initial cut expression being emp.

```
Variant: Hint Mode qualid + ! - : ident
```

This sets an optional mode of use of the identifier <code>qualid</code>. When proof-search faces a goal that ends in an application of <code>qualid</code> to arguments <code>term...term</code>, the mode tells if the hints associated to <code>qualid</code> can be applied or not. A mode specification is a list of n +, ! or - items that specify if an argument of the identifier is to be treated as an input (+), if its head only is an input (!) or an output (-) of the identifier. For a mode to match a list of arguments, input terms and input heads <code>must not</code> contain existential variables or be existential variables respectively, while outputs can be any term. Multiple modes can be declared for a single identifier, in that case only one mode needs to match the arguments for the hints to be applied. The head of a term is understood here as the applicative head, or the match or projection scrutinee's head, recursively, casts being ignored. <code>Hint Mode</code> is especially useful for typeclasses, when one does not want to

support default instances and avoid ambiguity in general. Setting a parameter of a class as an input forces proof-search to be driven by that index of the class, with ! giving more flexibility by allowing existentials to still appear deeper in the index but not at its head.

#### Note:

- One can use a *Hint Extern* with no pattern to do pattern matching on hypotheses using match goal with inside the tactic.
- If you want to add hints such as *Hint Transparent*, *Hint Cut*, or *Hint Mode*, for typeclass resolution, do not forget to put them in the typeclass\_instances hint database.

#### Hint databases defined in the Coq standard library

Several hint databases are defined in the Coq standard library. The actual content of a database is the collection of hints declared to belong to this database in each of the various modules currently loaded. Especially, requiring new modules may extend the database. At Coq startup, only the core database is nonempty and can be used.

- core This special database is automatically used by auto, except when pseudo-database nocore is given to auto. The core database contains only basic lemmas about negation, conjunction, and so on. Most of the hints in this database come from the Init and Logic directories.
- arith This database contains all lemmas about Peano's arithmetic proved in the directories Init and Arith.
- zarith contains lemmas about binary signed integers from the directories theories/ZArith. When required, the module Omega also extends the database zarith with a high-cost hint that calls omega on equations and inequalities in nat or Z.
- **bool** contains lemmas about booleans, mostly from directory theories/Bool.
- datatypes is for lemmas about lists, streams and so on that are mainly proved in the Lists subdirectory.
- sets contains lemmas about sets and relations from the directories Sets and Relations.
- typeclass\_instances contains all the typeclass instances declared in the environment, including those used for setoid\_rewrite, from the Classes directory.
- fset internal database for the implementation of the FSets library.
- ordered\_type lemmas about ordered types (as defined in the legacy OrderedType module),
   mainly used in the FSets and FMaps libraries.

You are advised not to put your own hints in the core database, but use one or several databases specific to your development.

Command: Remove Hints term : ident +

This command removes the hints associated to terms term in databases ident.

#### Command: Print Hint

This command displays all hints that apply to the current goal. It fails if no proof is being edited, while the two variants can be used at every moment.

#### Variants:

#### Command: Print Hint ident

This command displays only tactics associated with *ident* in the hints list. This is independent of the goal being edited, so this command will not fail if no goal is being edited.

#### Command: Print Hint \*

This command displays all declared hints.

#### Command: Print HintDb ident

This command displays all hints from database *ident*.

# Command: Hint Rewrite term + : ident +

This vernacular command adds the terms term (their types must be equalities) in the rewriting bases ident with the default orientation (left to right). Notice that the rewriting bases are distinct from the auto hint bases and that auto does not take them into account.

This command is synchronous with the section mechanism (see *Section mechanism*): when closing a section, all aliases created by Hint Rewrite in that section are lost. Conversely, when loading a module, all Hint Rewrite declarations at the global level of that module are loaded.

#### Variants:

# Command: Hint Rewrite -> term : ident +

This is strictly equivalent to the command above (we only make explicit the orientation which otherwise defaults to ->).

# Command: Hint Rewrite <- term : ident :

Adds the rewriting rules term with a right-to-left orientation in the bases ident.

# Command: Hint Rewrite term using tactic : ident +

When the rewriting rules term in ident will be used, the tactic tactic will be applied to the generated subgoals, the main subgoal excluded.

#### Command: Print Rewrite HintDb ident

This command displays all rewrite hints contained in *ident*.

#### **Hint locality**

Hints provided by the Hint commands are erased when closing a section. Conversely, all hints of a module A that are not defined inside a section (and not defined with option Local) become available when the module A is imported (using e.g. Require Import A.).

As of today, hints only have a binary behavior regarding locality, as described above: either they disappear at the end of a section scope, or they remain global forever. This causes a scalability issue, because hints coming from an unrelated part of the code may badly influence another development. It can be mitigated to some extent thanks to the *Remove Hints* command, but this is a mere workaround and has some limitations (for instance, external hints cannot be removed).

A proper way to fix this issue is to bind the hints to their module scope, as for most of the other objects Coq uses. Hints should only be made available when the module they are defined in is imported, not just required. It is very difficult to change the historical behavior, as it would break a lot of scripts. We propose a smooth transitional path by providing the *Loose Hint Behavior* option which accepts three flags allowing for a fine-grained handling of non-imported hints.

#### Option: Loose Hint Behavior "Lax" | "Warn" | "Strict"

This option accepts three values, which control the behavior of hints w.r.t. Import:

- "Lax": this is the default, and corresponds to the historical behavior, that is, hints defined outside of a section have a global scope.
- "Warn": outputs a warning when a non-imported hint is used. Note that this is an over-approximation, because a hint may be triggered by a run that will eventually fail and backtrack, resulting in the hint not being actually useful for the proof.
- "Strict": changes the behavior of an unloaded hint to a immediate fail tactic, allowing to emulate an import-scoped hint mechanism.

#### Setting implicit automation tactics

#### Command: Proof with tactic

This command may be used to start a proof. It defines a default tactic to be used each time a tactic command  $\mathtt{tactic}_1$  is ended by .... In this case the tactic command typed by the user is equivalent to  $\mathtt{tactic}_1$ ;  $\mathtt{tactic}$ .

#### See also:

Proof in Switching on/off the proof editing mode.

Variant: Proof with tactic using ident +

Combines in a single line Proof with and Proof using, see Switching on/off the proof editing mode

Variant: Proof using ident with tactic

Combines in a single line Proof with and Proof using, see Switching on/off the proof editing mode

#### 5.3.10 Decision procedures

#### tauto

This tactic implements a decision procedure for intuitionistic propositional calculus based on the contraction-free sequent calculi LJT\* of Roy Dyckhoff [Dyc92]. Note that tauto succeeds on any instance of an intuitionistic tautological proposition. tauto unfolds negations and logical equivalence but does not unfold any other definition.

#### Example

The following goal can be proved by tauto whereas auto would fail:

(continues on next page)

(continued from previous page)

Pх

tauto.

No more subgoals.

Moreover, if it has nothing else to do, tauto performs introductions. Therefore, the use of intros in the previous proof is unnecessary. tauto can for instance for:

#### Example

Note: In contrast, tauto cannot solve the following goal Goal forall (A:Prop) (P:nat -> Prop), A \/ (forall x:nat, ~ A -> P x) -> forall x:nat, ~ ~ (A \/ P x). because (forall x:nat, ~ A -> P x) cannot be treated as atomic and an instantiation of x is necessary.

#### Variant: dtauto

While *tauto* recognizes inductively defined connectives isomorphic to the standard connectives and, prod, or, sum, False, Empty\_set, unit, True, *dtauto* also recognizes all inductive types with one constructor and no indices, i.e. record-style connectives.

#### intuition tactic

The tactic *intuition* takes advantage of the search-tree built by the decision procedure involved in the tactic *tauto*. It uses this information to generate a set of subgoals equivalent to the original one (but simpler than it) and applies the tactic *tactic* to them [Mun94]. If this tactic fails on some goals then *intuition* fails. In fact, *tauto* is simply intuition fail.

#### Example

For instance, the tactic intuition auto applied to the goal:

```
(forall (x:nat), P x) / B -> (forall (y:nat), P y) / P O / B / P O
```

internally replaces it by the equivalent one:

```
(forall (x:nat), P x), B |- P 0
```

and then uses *auto* which completes the proof.

Originally due to César Muñoz, these tactics (tauto and intuition) have been completely re-engineered by David Delahaye using mainly the tactic language (see Ltac). The code is now much shorter and a significant increase in performance has been noticed. The general behavior with respect to dependent types, unfolding and introductions has slightly changed to get clearer semantics. This may lead to some incompatibilities.

#### Variant: intuition

Is equivalent to intuition auto with \*.

#### Variant: dintuition

While *intuition* recognizes inductively defined connectives isomorphic to the standard connectives and, prod, or, sum, False, Empty\_set, unit, True, *dintuition* also recognizes all inductive types with one constructor and no indices, i.e. record-style connectives.

#### Flag: Intuition Negation Unfolding

Controls whether *intuition* unfolds inner negations which do not need to be unfolded. This flag is on by default.

#### rtauto

The *rtauto* tactic solves propositional tautologies similarly to what *tauto* does. The main difference is that the proof term is built using a reflection scheme applied to a sequent calculus proof of the goal. The search procedure is also implemented using a different technique.

Users should be aware that this difference may result in faster proof-search but slower proof-checking, and *rtauto* might not solve goals that *tauto* would be able to solve (e.g. goals involving universal quantifiers).

Note that this tactic is only available after a Require Import Rtauto.

#### firstorder

The tactic *firstorder* is an experimental extension of *tauto* to first- order reasoning, written by Pierre Corbineau. It is not restricted to usual logical connectives but instead may reason about any first-order class inductive definition.

#### Option: Firstorder Solver tactic

The default tactic used by firstorder when no rule applies is auto with \*, it can be reset locally or globally using this option.

#### Command: Print Firstorder Solver

Prints the default tactic used by *firstorder* when no rule applies.

#### Variant: firstorder tactic

Tries to solve the goal with *tactic* when no logical rule may apply.

## Variant: firstorder using qualid

Deprecated since version 8.3: Use the syntax below instead (with commas).

# Variant: firstorder using qualid,

Adds lemmas qualid to the proof-search environment. If qualid refers to an inductive type, it is the collection of its constructors which are added to the proof-search environment.

## Variant: firstorder with ident

Adds lemmas from *auto* hint bases *ident* to the proof-search environment.

# Variant: firstorder tactic using qualid with ident +

This combines the effects of the different variants of firstorder.

#### Option: Firstorder Depth num

This option controls the proof-search depth bound.

#### congruence

The tactic *congruence*, by Pierre Corbineau, implements the standard Nelson and Oppen congruence closure algorithm, which is a decision procedure for ground equalities with uninterpreted symbols. It

also includes constructor theory (see *injection* and *discriminate*). If the goal is a non-quantified equality, congruence tries to prove it with non-quantified equalities in the context. Otherwise it tries to infer a discriminable equality from those in the context. Alternatively, congruence tries to prove that a hypothesis is equal to the goal or to the negation of another hypothesis.

congruence is also able to take advantage of hypotheses stating quantified equalities, but you have to provide a bound for the number of extra equalities generated that way. Please note that one of the sides of the equality must contain all the quantified variables in order for congruence to match against it.

#### Example

```
Theorem T (A:Type) (f:A -> A) (g: A -> A -> A) a b: a=(f a) -> (g b (f a)) = (f (f a)) -> (g a b) = (f (f a)) -> (g (f a)) -> (g a b) = (f (f a)) -> (g (f a)) -> (
  \hookrightarrow (g b a)) \rightarrow (g a b)=a.
              1 subgoal
                     A : Type
                     g : A \rightarrow A \rightarrow A
                     a, b : A
                     _____
                     a = f a -> g b (f a) = f (f a) -> g a b = f (g b a) -> g a b = a
intros.
              1 subgoal
                     A : Type
                     \mathtt{f} \ : \ \mathtt{A} \ -\!\!\!> \ \mathtt{A}
                     g : A -> A -> A
                     a, b : A
                    H : a = f a
                    HO: gb(fa) = f(fa)
                     H1 : gab = f(gba)
                     _____
                     g a b = a
congruence.
             No more subgoals.
Theorem inj (A:Type) (f:A \rightarrow A * A) (a c d: A) : f = pair a \rightarrow Some (f c) = Some (f d) <math>\rightarrow c=d.
              1 subgoal
                     A : Type
                     f : A \rightarrow A * A
                     a, c, d : A
                     _____
                     f = pair a \rightarrow Some (f c) = Some (f d) \rightarrow c = d
intros.
             1 subgoal
                     A : Type
                     f : A \rightarrow A * A
                     a, c, d : A
                    H : f = pair a
                     HO : Some (f c) = Some (f d)
                                                                                                                                                                                                                                                                                               (continues on next page)
```

(continued from previous page)

-----

c = d

#### congruence.

No more subgoals.

Qed.

#### Variant: congruence num

Tries to add at most *num* instances of hypotheses stating quantified equalities to the problem in order to solve it. A bigger value of *num* does not make success slower, only failure. You might consider adding some lemmas as hypotheses using assert in order for *congruence* to use them.

Variant: congruence with term

Adds term to the pool of terms used by congruence. This helps in case you have partially applied constructors in your goal.

#### Error: I don't know how to handle dependent equality.

The decision procedure managed to find a proof of the goal or of a discriminable equality but this proof could not be built in Coq because of dependently-typed functions.

Error: Goal is solvable by congruence but some arguments are missing. Try congruence with term

The decision procedure could solve the goal with the provision that additional arguments are supplied for some partially applied constructors. Any term of an appropriate type will allow the tactic to successfully solve the goal. Those additional arguments can be given to congruence by filling in the holes in the terms given in the error message, using the congruence with variant described above.

#### Flag: Congruence Verbose

This flag makes *congruence* print debug information.

#### 5.3.11 Checking properties of terms

Each of the following tactics acts as the identity if the check succeeds, and results in an error otherwise.

#### constr\_eq term term

This tactic checks whether its arguments are equal modulo alpha conversion, casts and universe constraints. It may unify universes.

Error: Not equal.

Error: Not equal (due to universes).

#### constr eq strict term term

This tactic checks whether its arguments are equal modulo alpha conversion, casts and universe constraints. It does not add new constraints.

Error: Not equal.

Error: Not equal (due to universes).

unify term term

This tactic checks whether its arguments are unifiable, potentially instantiating existential variables.

Error: Unable to unify term with term.

#### Variant: unify term term with ident

Unification takes the transparency information defined in the hint database *ident* into account (see the hints databases for auto and eauto).

#### is evar term

This tactic checks whether its argument is a current existential variable. Existential variables are uninstantiated variables generated by *eapply* and some other tactics.

Error: Not an evar.

#### has evar term

This tactic checks whether its argument has an existential variable as a subterm. Unlike context patterns combined with is\_evar, this tactic scans all subterms, including those under binders.

Error: No evars.

#### is\_var term

This tactic checks whether its argument is a variable or hypothesis in the current goal context or in the opened sections.

Error: Not a variable or hypothesis.

#### **5.3.12 Equality**

#### f\_equal

This tactic applies to a goal of the form  $f a_1 \ldots a_n = f a_1 \ldots a_n$ . Using  $f_{equal}$  on such a goal leads to subgoals f=f and  $a_1 = a_1$  and so on up to  $a_n = a_n$ . Amongst these subgoals, the simple ones (e.g. provable by reflexivity or congruence) are automatically solved by  $f_{equal}$ .

#### reflexivity

This tactic applies to a goal that has the form t=u. It checks that t and u are convertible and then solves the goal. It is equivalent to apply refl\_equal.

Error: The conclusion is not a substitutive equation.

Error: Unable to unify ... with ...

#### symmetry

This tactic applies to a goal that has the form t=u and changes it into u=t.

#### Variant: symmetry in ident

If the statement of the hypothesis ident has the form t=u, the tactic changes it to u=t.

#### transitivity term

This tactic applies to a goal that has the form t=u and transforms it into the two subgoals t=term and term=u.

#### Variant: etransitivity

This tactic behaves like transitivity, using a fresh evar instead of a concrete term.

#### 5.3.13 Equality and inductive sets

We describe in this section some special purpose tactics dealing with equality and inductive sets or types. These tactics use the equality eq:forall (A:Type), A->A->Prop, simply written with the infix symbol =.

#### decide equality

This tactic solves a goal of the form forall x y : R,  $\{x = y\} + \{\sim x = y\}$ , where R is an inductive type such that its constructors do not take proofs or functions as arguments, nor objects in dependent types. It solves goals of the form  $\{x = y\} + \{\sim x = y\}$  as well.

#### compare term term

This tactic compares two given objects *term* and *term* of an inductive datatype. If G is the current goal, it leaves the sub-goals *term* = *term* -> G and ~ *term* = *term* -> G. The type of *term* and *term* must satisfy the same restrictions as in the tactic decide equality.

#### simplify\_eq term

Let *term* be the proof of a statement of conclusion *term* = *term*. If *term* and *term* are structurally different (in the sense described for the tactic *discriminate*), then the tactic *simplify\_eq* behaves as discriminate *term*, otherwise it behaves as injection *term*.

Note: If some quantified hypothesis of the goal is named *ident*, then simplify\_eq *ident* first introduces the hypothesis in the local context using intros until *ident*.

#### Variant: simplify\_eq num

This does the same thing as intros until *num* then simplify\_eq *ident* where *ident* is the identifier for the last introduced hypothesis.

#### Variant: simplify\_eq term with bindings\_list

This does the same as simplify\_eq term but using the given bindings to instantiate parameters or hypotheses of term.

#### Variant: esimplify\_eq num

# Variant: esimplify\_eq term with bindings\_list |

This works the same as  $simplify_eq$  but if the type of term, or the type of the hypothesis referred to by num, has uninstantiated parameters, these parameters are left as existential variables.

#### Variant: simplify\_eq

If the current goal has form t1 <> t2, it behaves as intro ident; simplify\_eq ident.

#### dependent rewrite -> ident

This tactic applies to any goal. If *ident* has type (existT B a b)=(existT B a' b') in the local context (i.e. each *term* of the equality has a sigma type { a:A & (B a)}) this tactic rewrites a into a' and b into b' in the current goal. This tactic works even if B is also a sigma type. This kind of equalities between dependent pairs may be derived by the *injection* and *inversion* tactics.

#### Variant: dependent rewrite <- ident

Analogous to dependent rewrite -> but uses the equality from right to left.

#### 5.3.14 Inversion

#### functional inversion ident

functional inversion is a tactic that performs inversion on hypothesis ident of the form qualid term + where qualid must have been defined using Function (see Advanced recursive functions). Note that this tactic is only available after a Require Import FunInd.

Error: Hypothesis ident must contain at least one Function.

#### Error: Cannot find inversion information for hypothesis ident.

This error may be raised when some inversion lemma failed to be generated by Function.

#### Variant: functional inversion num

This does the same thing as intros until num followed by functional inversion ident where ident is the identifier for the last introduced hypothesis.

Variant: functional inversion ident qualid

#### Variant: functional inversion num qualid

If the hypothesis ident (or num) has a type of the form  $qualid_1$   $term_i$  =  $qualid_2$   $term_j$  where  $qualid_1$  and  $qualid_2$  are valid candidates to functional inversion, this variant allows choosing which qualid is inverted.

#### 5.3.15 Classical tactics

In order to ease the proving process, when the Classical module is loaded, a few more tactics are available. Make sure to load the module using the Require Import command.

```
classical_left
classical_right
```

These tactics are the analog of *left* and *right* but using classical logic. They can only be used for disjunctions. Use *classical\_left* to prove the left part of the disjunction with the assumption that the negation of right part holds. Use *classical\_right* to prove the right part of the disjunction with the assumption that the negation of left part holds.

#### 5.3.16 Automating

#### btauto

The tactic *btauto* implements a reflexive solver for boolean tautologies. It solves goals of the form t = u where t and u are constructed over the following grammar:

Whenever the formula supplied is not a tautology, it also provides a counter-example.

Internally, it uses a system very similar to the one of the ring tactic.

Note that this tactic is only available after a Require Import Btauto.

#### Error: Cannot recognize a boolean equality.

The goal is not of the form t = u. Especially note that btauto doesn't introduce variables into the context on its own.

#### omega

The tactic omega, due to Pierre Crégut, is an automatic decision procedure for Presburger arithmetic. It solves quantifier-free formulas built with  $\sim$ ,  $\backslash /$ ,  $\rightarrow$  on top of equalities, inequalities and disequalities on both the type nat of natural numbers and Z of binary integers. This tactic must be loaded by the command Require Import Omega. See the additional documentation about omega (see Chapter Omega: a solver for quantifier-free problems in Presburger Arithmetic).

#### ring

This tactic solves equations upon polynomial expressions of a ring (or semiring) structure. It proceeds by normalizing both hand sides of the equation (w.r.t. associativity, commutativity and distributivity, constant propagation) and comparing syntactically the results.

```
ring_simplify term *
```

This tactic applies the normalization procedure described above to the given terms. The tactic then replaces all occurrences of the terms given in the conclusion of the goal by their normal forms. If no term is given, then the conclusion should be an equation and both hand sides are normalized.

See *The ring and field tactic families* for more information on the tactic and how to declare new ring structures. All declared field structures can be printed with the Print Rings command.

# field\_simplify term field\_simplify\_eq

The field tactic is built on the same ideas as ring: this is a reflexive tactic that solves or simplifies equations in a field structure. The main idea is to reduce a field expression (which is an extension of ring expressions with the inverse and division operations) to a fraction made of two polynomial expressions.

Tactic field is used to solve subgoals, whereas field\_simplify term replaces the provided terms by their reduced fraction. field\_simplify\_eq applies when the conclusion is an equation: it simplifies both hand sides and multiplies so as to cancel denominators. So it produces an equation without division nor inverse.

All of these 3 tactics may generate a subgoal in order to prove that denominators are different from zero.

See *The ring and field tactic families* for more information on the tactic and how to declare new field structures. All declared field structures can be printed with the Print Fields command.

#### Example

```
Require Import Reals.
    [Loading ML file newring_plugin.cmxs ... done]
    [Loading ML file r_syntax_plugin.cmxs ... done]
    [Loading ML file zify_plugin.cmxs ... done]
    [Loading ML file micromega_plugin.cmxs ... done]
Goal forall x y:R,
(x * y > 0) \%R \rightarrow
(x * (1 / x + x / (x + y))) R =
((-1/y) * y * (-x * (x / (x + y)) - 1))%R.
   1 subgoal
     _____
     forall x y : R,
     (x * y > 0)%R ->
     (x * (1 / x + x / (x + y)))%R = (-1 / y * y * (-x * (x / (x + y)) - 1))%R
intros; field.
   1 subgoal
     x, y : R
     H : (x * y > 0) \%R
     _____
     (x + y)%R <> 0%R /\ y <> 0%R /\ x <> 0%R
```

See also:

File plugins/setoid\_ring/RealField.v for an example of instantiation, theory theories/Reals for many examples of use of field.

#### 5.3.17 Non-logical tactics

#### cycle num

This tactic puts the num first goals at the end of the list of goals. If num is negative, it will put the last |num| goals at the beginning of the list.

#### Example

```
Goal P 1 / P 2 / P 3 / P 4 / P 5.
   1 subgoal
     P 1 /\ P 2 /\ P 3 /\ P 4 /\ P 5
repeat split.
   5 subgoals
     _____
     P 1
   subgoal 2 is:
    P 2
   subgoal 3 is:
    P 3
   subgoal 4 is:
    P 4
   subgoal 5 is:
    P 5
all: cycle 2.
   5 subgoals
     _____
     Р 3
   subgoal 2 is:
   subgoal 3 is:
    P 5
   subgoal 4 is:
    P 1
   subgoal 5 is:
    P 2
all: cycle -3.
   5 subgoals
     _____
     P 5
   subgoal 2 is:
    P 1
   subgoal 3 is:
```

(continues on next page)

(continued from previous page)

```
P 2
subgoal 4 is:
P 3
subgoal 5 is:
P 4
```

#### swap num num

This tactic switches the position of the goals of indices *num* and *num*. If either *num* or *num* is negative then goals are counted from the end of the focused goal list. Goals are indexed from 1, there is no goal with position 0.

#### Example

```
Goal P 1 /\ P 2 /\ P 3 /\ P 4 /\ P 5.
   1 subgoal
    _____
    P 1 /\ P 2 /\ P 3 /\ P 4 /\ P 5
repeat split.
   5 subgoals
    _____
    P 1
   subgoal 2 is:
   P 2
   subgoal 3 is:
   subgoal 4 is:
   P 4
   subgoal 5 is:
   P 5
all: swap 1 3.
   5 subgoals
    _____
    P 3
   subgoal 2 is:
   P 2
   subgoal 3 is:
   P 1
   subgoal 4 is:
   P 4
   subgoal 5 is:
   P 5
all: swap 1 - 1.
   5 subgoals
     _____
    P 5
```

(continues on next page)

(continued from previous page)

```
subgoal 2 is:
P 2
subgoal 3 is:
P 1
subgoal 4 is:
P 4
subgoal 5 is:
P 3
```

#### revgoals

This tactics reverses the list of the focused goals.

#### Example

```
Goal P 1 /\ P 2 /\ P 3 /\ P 4 /\ P 5.
   1 subgoal
     _____
     P 1 /\ P 2 /\ P 3 /\ P 4 /\ P 5
repeat split.
   5 subgoals
     _____
     P 1
   subgoal 2 is:
   P 2
   subgoal 3 is:
   P 3
   subgoal 4 is:
   subgoal 5 is:
    P 5
all: revgoals.
   5 subgoals
     _____
   subgoal 2 is:
   subgoal 3 is:
   subgoal 4 is:
    P 2
   subgoal 5 is:
    P 1
```

#### shelve

This tactic moves all goals under focus to a shelf. While on the shelf, goals will not be focused on. They can be solved by unification, or they can be called back into focus with the command *Unshelve*.

#### Variant: shelve unifiable

Shelves only the goals under focus that are mentioned in other goals. Goals that appear in the type of other goals can be solved by unification.

#### Example

#### Command: Unshelve

This command moves all the goals on the shelf (see *shelve*) from the shelf into focus, by appending them to the end of the current list of focused goals.

#### unshelve tactic

Performs *tactic*, then unshelves existential variables added to the shelf by the execution of *tactic*, prepending them to the current goal.

#### give\_up

This tactic removes the focused goals from the proof. They are not solved, and cannot be solved later in the proof. As the goals are not solved, the proof cannot be closed.

The give\_up tactic can be used while editing a proof, to choose to write the proof script in a non-sequential order.

#### 5.3.18 Delaying solving unification constraints

#### solve\_constraints

#### Flag: Solve Unification Constraints

By default, after each tactic application, postponed typechecking unification problems are resolved using heuristics. Unsetting this flag disables this behavior, allowing tactics to leave unification constraints unsolved. Use the <code>solve\_constraints</code> tactic at any point to solve the constraints.

#### 5.3.19 Proof maintenance

Experimental. Many tactics, such as *intros*, can automatically generate names, such as "H0" or "H1" for a new hypothesis introduced from a goal. Subsequent proof steps may explicitly refer to these names. However, future versions of Coq may not assign names exactly the same way, which could cause the proof to fail because the new names don't match the explicit references in the proof.

The following "Mangle Names" settings let users find all the places where proofs rely on automatically generated names, which can then be named explicitly to avoid any incompatibility. These settings cause Coq to generate different names, producing errors for references to automatically generated names.

#### Flag: Mangle Names

When set, generated names use the prefix specified in the following option instead of the default prefix.

#### Option: Mangle Names Prefix string

Specifies the prefix to use when generating names.

#### 5.3.20 Performance-oriented tactic variants

#### change\_no\_check term

For advanced usage. Similar to change term, but as an optimization, it skips checking that term is convertible to the goal.

Recall that the Coq kernel typechecks proofs again when they are concluded to ensure safety. Hence, using *change* checks convertibility twice overall, while *change\_no\_check* can produce ill-typed terms, but checks convertibility only once. Hence, *change\_no\_check* can be useful to speed up certain proof scripts, especially if one knows by construction that the argument is indeed convertible to the goal.

In the following example, <code>change\_no\_check</code> replaces False by True, but Qed then rejects the proof, ensuring consistency.

```
Example
Goal False.
   1 subgoal
     _____
     False
change_no_check True.
   1 subgoal
     _____
     True
exact I.
   No more subgoals.
Fail Qed.
   The command has indeed failed with message:
   The term "I" has type "True" while it is expected to have type "False".
change_no_check supports all of change's variants.
Variant: change_no_check term with term'
Variant: change no check term at num + with term'
                              at num +
Variant: change no check term
                                          with term
                                                      in ident
```

## Example Goal True -> False. 1 subgoal \_\_\_\_\_ True -> False intro H. 1 subgoal H : True \_\_\_\_\_ False change\_no\_check False in H. 1 subgoal H : False \_\_\_\_\_ False exact H. No more subgoals. Fail Qed. The command has indeed failed with message: The term "fun H : True => H" has type "True -> True" while it is expected to have type "True -> False".

#### Variant: convert\_concl\_no\_check term

Deprecated since version 8.11.

Deprecated old name for change\_no\_check. Does not support any of its variants.

#### exact\_no\_check term

For advanced usage. Similar to exact term, but as an optimization, it skips checking that term has the goal's type, relying on the kernel check instead. See change\_no\_check for more explanations.

#### Example

Variant: vm\_cast\_no\_check term

For advanced usage. Similar to exact\_no\_check term, but additionally instructs the kernel to use vm\_compute to compare the goal's type with the term's type.

# Example Goal False. 1 subgoal -----False vm\_cast\_no\_check I. No more subgoals. Fail Qed. The command has indeed failed with message: The term "I" has type "True" while it is expected to have type "False".

#### Variant: native\_cast\_no\_check term

for advanced usage. similar to exact\_no\_check term, but additionally instructs the kernel to use native\_compute to compare the goal's type with the term's type.

```
Example

Goal False.

1 subgoal

False

native_cast_no_check I.

No more subgoals.

Fail Qed.

The command has indeed failed with message:

The term "I" has type "True" while it is expected to have type "False".
```

#### 5.4 Ltac

This chapter documents the tactic language  $L_{\rm tac}$ .

We start by giving the syntax, and next, we present the informal semantics. To learn more about the language and especially about its foundations, please refer to [Del00].

#### Example: Basic tactic macros

Here are some examples of simple tactic macros that the language lets you write.

```
Ltac reduce_and_try_to_solve := simpl; intros; auto.
Ltac destruct_bool_and_rewrite b H1 H2 :=
  destruct b; [ rewrite H1; eauto | rewrite H2; eauto ].
```

5.4. Ltac 345

See Section Examples of using Ltac for more advanced examples.

#### **5.4.1** Syntax

The syntax of the tactic language is given below. See Chapter *The Gallina specification language* for a description of the BNF metasyntax used in these grammar rules. Various already defined entries will be used in this chapter: entries *num*, *int*, *ident qualid*, *term*, *cpattern* and tactic represent respectively natural and integer numbers, identifiers, qualified names, Coq terms, patterns and the atomic tactics described in Chapter *Tactics*.

The syntax of cpattern is the same as that of terms, but it is extended with pattern matching metavariables. In cpattern, a pattern matching metavariable is represented with the syntax ?ident. The notation \_ can also be used to denote metavariable whose instance is irrelevant. In the notation ?ident, the identifier allows us to keep instantiations and to make constraints whereas \_ shows that we are not interested in what will be matched. On the right hand side of pattern matching clauses, the named metavariables are used without the question mark prefix. There is also a special notation for second-order pattern matching problems: in an applicative pattern of the form  $%@?ident\ ident_1\ ...\ ident_n$ , the variable ident matches any complex expression with (possible) dependencies in the variables  $ident_i$  and returns a functional term of the form  $ident_1\ ...\ ident_n\ =>\ term$ .

The main entry of the grammar is  $ltac\_expr$ . This language is used in proof mode but it can also be used in toplevel definitions as shown below.

#### Note:

• The infix tacticals ... | | ..., ... + ..., and ...; ... are associative.

#### Example

If you want that  $tactic_2$ ;  $tactic_3$  be fully run on the first subgoal generated by  $tactic_1$ , before running on the other subgoals, then you should not write  $tactic_1$ ; ( $tactic_2$ ;  $tactic_3$ ) but rather  $tactic_1$ ; [>  $tactic_2$ ;  $tactic_3$  .. ].

- In tacarg, there is an overlap between qualid as a direct tactic argument and qualid as a particular case of term. The resolution is done by first looking for a reference of the tactic language and if it fails, for a reference to a term. To force the resolution as a reference of the tactic language, use the form ltac:(qualid). To force the resolution as a reference to a term, use the syntax (qualid).
- As shown by the figure, tactical ... | | ... binds more than the prefix tacticals try, repeat, do and abstract which themselves bind more than the postfix tactical ...; [ ... ] which binds at the same level as ...; ....

#### Example

```
try repeat tactic_1 \mid \mid tactic_2; tactic_3; [ tactic]; tactic_4 is understood as: ((try (repeat (<math>tactic_1 \mid \mid tactic_2)); tactic_3); [ tactic]); tactic_4
```

```
ltac_expr ; ltac_expr
ltac_expr
                   ::=
                         [> ltac expr | ... | ltac expr ]
                         ltac_expr ; [ ltac_expr | ... | ltac_expr ]
                         ltac expr3
                         do (natural | ident) ltac expr3
ltac_expr3
                   ::=
                         progress ltac expr3
                         repeat ltac expr3
                         try ltac_expr3
                         once ltac_expr3
                         exactly_once ltac_expr3
                         timeout (natural | ident) ltac_expr3
                         time [string] ltac_expr3
                         only selector: ltac_expr3
                         ltac_expr2
ltac_expr2
                         ltac_expr1 || ltac_expr3
                   ::=
                         ltac_expr1 + ltac_expr3
                         tryif ltac_expr1 then ltac_expr1 else ltac_expr1
                         ltac_expr1
ltac_expr1
                   ::=
                         fun name ... name => atom
                         let [rec] let_clause with ... with let_clause in atom
                         match goal with context_rule | ... | context_rule end
                         match reverse goal with context_rule | ... | context_rule end
                         match ltac_expr with match_rule | ... | match_rule end
                         lazymatch goal with context_rule | ... | context_rule end
                         lazymatch reverse goal with context_rule | ... | context_rule end
                         lazymatch ltac_expr with match_rule | ... | match_rule end
                         multimatch goal with context_rule | ... | context_rule end
                         multimatch reverse goal with context_rule | ... | context_rule end
                         multimatch ltac_expr with match_rule | ... | match_rule end
                         abstract atom
                         abstract atom using ident
                         first [ ltac_expr | ... | ltac_expr ]
                         solve [ ltac_expr | ... | ltac_expr ]
                         idtac [ message token ... message token]
                         fail [natural] [message_token ... message_token]
                         gfail [natural] [message token ... message token]
                         fresh [ component ... component ]
                         context ident [term]
                         eval redexpr in term
                         type of term
                         constr : term
                         uconstr : term
                         type_term term
                         numgoals
                         guard test
                         assert_fails ltac_expr3
                         assert_succeeds ltac_expr3
                         tactic
                         qualid tacarq ... tacarq
                         atom
atom
                   ::=
                         qualid
                         ()
                         int
```

5.4. Ltac 347

```
( ltac_expr )
                          string | qualid
component
                    ::=
message_token
                    ::=
                          string | ident | int
                          qualid
tacarg
                    ::=
                          ()
                          ltac : atom
                          term
let_clause
                    ::=
                          ident [name ... name] := ltac_expr
context_rule
                          context_hyp, ..., context_hyp |- cpattern => ltac_expr
                    ::=
                          cpattern => ltac_expr
                          |- cpattern => ltac_expr
                          _ => ltac_expr
                          name: cpattern
context_hyp
                    ::=
                          name := cpattern [: cpattern]
                          cpattern => ltac_expr
match_rule
                    ::=
                          context [ident] [ cpattern ] => ltac_expr
                          _ => ltac_expr
                          int = int
test
                    ::=
                          int (< | <= | > | >=) int
selector
                    ::=
                          [ident]
                          (int \mid int - int), \ldots, (int \mid int - int)
toplevel_selector
                          selector
                    ::=
                          all
                          par
                          !
                 [Local] Ltac ltac_def with ... with ltac_def
top
                 ident [ident ... ident] := ltac_expr
ltac_def
          ::=
                 qualid [ident ... ident] ::= ltac_expr
```

#### 5.4.2 Semantics

Tactic expressions can only be applied in the context of a proof. The evaluation yields either a term, an integer or a tactic. Intermediate results can be terms or integers but the final result must be a tactic which is then applied to the focused goals.

There is a special case for match goal expressions of which the clauses evaluate to tactics. Such expressions can only be used as end result of a tactic expression (never as argument of a non-recursive local definition or of an application).

The rest of this section explains the semantics of every construction of  $L_{\rm tac}$ .

#### Sequence

348

A sequence is an expression of the following form:

```
ltac_expr<sub>1</sub> ; ltac_expr<sub>2</sub>
```

The expression  $ltac\_expr_1$  is evaluated to  $v_1$ , which must be a tactic value. The tactic  $v_1$  is applied to the current goal, possibly producing more goals. Then  $ltac\_expr_2$  is evaluated to produce  $v_2$ , which must be a tactic value. The tactic  $v_2$  is applied to all the goals produced by the prior application. Sequence is associative.

#### Local application of tactics

Different tactics can be applied to the different goals using the following form:

The expressions  $ltac\_expr_i$  are evaluated to  $v_i$ , for i = 1, ..., n and all have to be tactics. The  $v_i$  is applied to the i-th goal, for i = 1, ..., n. It fails if the number of focused goals is not exactly n.

Note: If no tactic is given for the i-th goal, it behaves as if the tactic idtac were given. For instance, [> | auto] is a shortcut for [> idtac | auto].

In this variant,  $ltac\_expr$  is used for each goal coming after those covered by the list of  $ltac\_expr_i$  but before those covered by the list of  $ltac\_expr_i$ .

In this variant, idtac is used for the goals not covered by the two lists of ltac\_expr.

Variant: [> ltac\_expr .. ]

In this variant, the tactic <code>ltac\_expr</code> is applied independently to each of the goals, rather than globally. In particular, if there are no goals, the tactic is not run at all. A tactic which expects multiple goals, such as <code>swap</code>, would act as if a single goal is focused.

This variant of local tactic application is paired with a sequence. In this variant, there must be as many  $ltac\_expr_i$  as goals generated by the application of  $ltac\_expr_0$  to each of the individual goals independently. All the above variants work in this form too. Formally,  $ltac\_expr$ ; [ . . . ] is equivalent to [>  $ltac\_expr$ ; [> . . . ] . . ].

#### **Goal selectors**

We can restrict the application of a tactic to a subset of the currently focused goals with:

```
toplevel_selector : ltac_expr
```

We can also use selectors as a tactical, which allows to use them nested in a tactic expression, by using the keyword only:

Variant: only selector : ltac\_expr

When selecting several goals, the tactic ltac\_expr is applied globally to all selected goals.

Variant: [ident] : ltac\_expr

In this variant,  $ltac\_expr$  is applied locally to a goal previously named by the user (see *Existential variables*).

Variant: num : ltac\_expr

In this variant, ltac\_expr is applied locally to the num-th goal.

Variant: num-num ; : ltac\_expr

In this variant,  $\overline{ltac\_expr}$  is applied globally to the subset of goals described by the given ranges. You can write a single n as a shortcut for n-n when specifying multiple ranges.

5.4. Ltac 349

#### Variant: all: ltac\_expr

In this variant, ltac\_expr is applied to all focused goals. all: can only be used at the toplevel of a tactic expression.

#### Variant: !: ltac\_expr

In this variant, if exactly one goal is focused, *ltac\_expr* is applied to it. Otherwise the tactic fails. !: can only be used at the toplevel of a tactic expression.

#### Variant: par: ltac\_expr

In this variant, <code>ltac\_expr</code> is applied to all focused goals in parallel. The number of workers can be controlled via the command line option <code>-async-proofs-tac-j</code> taking as argument the desired number of workers. Limitations: <code>par:</code> only works on goals containing no existential variables and <code>ltac\_expr</code> must either solve the goal completely or do nothing (i.e. it cannot make some progress). <code>par:</code> can only be used at the toplevel of a tactic expression.

Error: No such goal.

#### For loop

There is a for loop that repeats a tactic num times:

#### do num ltac\_expr

 $ltac\_expr$  is evaluated to v which must be a tactic value. This tactic value v is applied num times. Supposing num > 1, after the first application of v, v is applied, at least once, to the generated subgoals and so on. It fails if the application of v fails before the num applications have been completed.

#### Repeat loop

We have a repeat loop with:

#### repeat ltac\_expr

ltac\_expr is evaluated to v. If v denotes a tactic, this tactic is applied to each focused goal independently. If the application succeeds, the tactic is applied recursively to all the generated subgoals until it eventually fails. The recursion stops in a subgoal when the tactic has failed to make progress. The tactic repeat ltac\_expr itself never fails.

#### **Error catching**

We can catch the tactic errors with:

#### try ltac\_expr

*ltac\_expr* is evaluated to v which must be a tactic value. The tactic value v is applied to each focused goal independently. If the application of v fails in a goal, it catches the error and leaves the goal unchanged. If the level of the exception is positive, then the exception is re-raised with its level decremented.

#### **Detecting progress**

We can check if a tactic made progress with:

#### progress ltac\_expr

*ltac\_expr* is evaluated to v which must be a tactic value. The tactic value v is applied to each focused subgoal independently. If the application of v to one of the focused subgoal produced subgoals equal to the initial goals (up to syntactical equality), then an error of level 0 is raised.

Error: Failed to progress.

#### **Backtracking branching**

We can branch with the following structure:

```
ltac\_expr_1 + ltac\_expr_2
```

 $ltac\_expr_1$  and  $ltac\_expr_2$  are evaluated respectively to  $v_1$  and  $v_2$  which must be tactic values. The tactic value  $v_1$  is applied to each focused goal independently and if it fails or a later tactic fails, then the proof backtracks to the current goal and  $v_2$  is applied.

Tactics can be seen as having several successes. When a tactic fails it asks for more successes of the prior tactics.  $ltac\_expr_1 + ltac\_expr_2$  has all the successes of  $v_1$  followed by all the successes of  $v_2$ . Algebraically,  $(ltac\_expr_1 + ltac\_expr_2)$ ;  $ltac\_expr_3 = (ltac\_expr_1; ltac\_expr_3) + (ltac\_expr_2; ltac\_expr_3)$ .

Branching is left-associative.

#### First tactic to work

Backtracking branching may be too expensive. In this case we may restrict to a local, left biased, branching and consider the first tactic to work (i.e. which does not fail) among a panel of tactics:

```
first [ltac_expr *]
```

The  $ltac\_expr_i$  are evaluated to  $v_i$  and  $v_i$  must be tactic values for i=1,...,n. Supposing n>1, first  $\lceil ltac\_expr_1 \mid ... \mid ltac\_expr_n \rceil$  applies  $v_1$  in each focused goal independently and stops if it succeeds; otherwise it tries to apply  $v_2$  and so on. It fails when there is no applicable tactic. In other words, first  $\lceil ltac\_expr_1 \mid ... \mid ltac\_expr_n \rceil$  behaves, in each goal, as the first  $v_i$  to have at least one success.

Error: No applicable tactic.

#### Variant: first ltac\_expr

This is an  $L_{\rm tac}$  alias that gives a primitive access to the first tactical as an  $L_{\rm tac}$  definition without going through a parsing rule. It expects to be given a list of tactics through a Tactic Notation, allowing to write notations of the following form:

#### Example

```
Tactic Notation "foo" tactic_list(tacs) := first tacs.
```

#### Left-biased branching

Yet another way of branching without backtracking is the following structure:

```
ltac_expr<sub>1</sub> || ltac_expr<sub>2</sub>
```

 $ltac\_expr_1$  and  $ltac\_expr_2$  are evaluated respectively to  $v_1$  and  $v_2$  which must be tactic values. The tactic value  $v_1$  is applied in each subgoal independently and if it fails to progress then  $v_2$  is applied.  $ltac\_expr_1 \mid ltac\_expr_2$  is equivalent to first [ progress  $ltac\_expr_1 \mid ltac\_expr_2$  ] (except that if it fails, it fails like  $v_2$ ). Branching is left-associative.

5.4. Ltac 351

#### Generalized biased branching

The tactic

```
tryif ltac_expr1 then ltac_expr2 else ltac_expr3
```

is a generalization of the biased-branching tactics above. The expression  $ltac\_expr_1$  is evaluated to  $v_1$ , which is then applied to each subgoal independently. For each goal where  $v_1$  succeeds at least once,  $ltac\_expr_2$  is evaluated to  $v_2$  which is then applied collectively to the generated subgoals. The  $v_2$  tactic can trigger backtracking points in  $v_1$ : where  $v_1$  succeeds at least once, tryif  $ltac\_expr_1$  then  $ltac\_expr_2$  else  $ltac\_expr_3$  is equivalent to  $v_1$ ;  $v_2$ . In each of the goals where  $v_1$  does not succeed at least once,  $ltac\_expr_3$  is evaluated in  $v_3$  which is is then applied to the goal.

#### Soft cut

Another way of restricting backtracking is to restrict a tactic to a single success a posteriori:

```
once ltac_expr
```

ltac\_expr is evaluated to v which must be a tactic value. The tactic value v is applied but only its first
success is used. If v fails, once ltac\_expr fails like v. If v has at least one success, once ltac\_expr
succeeds once, but cannot produce more successes.

#### Checking the successes

Coq provides an experimental way to check that a tactic has exactly one success:

```
exactly_once ltac_expr
```

ltac\_expr is evaluated to v which must be a tactic value. The tactic value v is applied if it has at
most one success. If v fails, exactly\_once ltac\_expr fails like v. If v has a exactly one success,
exactly\_once ltac\_expr succeeds like v. If v has two or more successes, exactly\_once ltac\_expr
fails.

Warning: The experimental status of this tactic pertains to the fact if v performs side effects, they may occur in an unpredictable way. Indeed, normally v would only be executed up to the first success until backtracking is needed, however exactly\_once needs to look ahead to see whether a second success exists, and may run further effects immediately.

Error: This tactic has more than one success.

#### Checking the failure

Coq provides a derived tactic to check that a tactic fails:

```
assert_fails ltac_expr
```

This behaves like *idtac* if *ltac\_expr* fails, and behaves like fail 0 *ltac\_expr* "succeeds" if *ltac\_expr* has at least one success.

#### Checking the success

Coq provides a derived tactic to check that a tactic has at least one success:

#### assert\_succeeds ltac\_expr

This behaves like tryif (assert\_fails <code>ltac\_expr</code>) then fail 0 <code>ltac\_expr</code> "fails" else idtac.

#### Solving

We may consider the first to solve (i.e. which generates no subgoal) among a panel of tactics:

```
solve [ltac_expr *]
```

The  $ltac\_expr_i$  are evaluated to  $v_i$  and  $v_i$  must be tactic values, for i=1, ..., n. Supposing n>1, solve  $[ltac\_expr_1 \mid ... \mid ltac\_expr_n]$  applies  $v_i$  to each goal independently and stops if it succeeds; otherwise it tries to apply  $v_i$  and so on. It fails if there is no solving tactic.

Error: Cannot solve the goal.

#### Variant: solve ltac\_expr

This is an  $L_{tac}$  alias that gives a primitive access to the solve: tactical. See the first tactical for more information.

#### Identity

The constant idtac is the identity tactic: it leaves any goal unchanged but it appears in the proof script.



This prints the given tokens. Strings and integers are printed literally. If a (term) variable is given, its contents are printed.

#### **Failing**

#### fail

This is the always-failing tactic: it does not solve any goal. It is useful for defining other tacticals since it can be caught by try, repeat, match goal, or the branching tacticals.

#### Variant: fail num

The number is the failure level. If no level is specified, it defaults to 0. The level is used by try, repeat, match goal and the branching tacticals. If 0, it makes match goal consider the next clause (backtracking). If nonzero, the current match goal block, try, repeat, or branching command is aborted and the level is decremented. In the case of +, a nonzero level skips the first backtrack point, even if the call to fail num is not enclosed in a + command, respecting the algebraic identity.

Variant: fail message\_token \*

The given tokens are used for printing the failure message.

Variant: fail num message\_token \*

This is a combination of the previous variants.

#### Variant: gfail

This variant fails even when used after; and there are no goals left. Similarly, gfail fails even when used after all: and there are no goals left. See the example for clarification.

Variant: gfail message\_token

5.4. Ltac 353

```
Variant: gfail num message_token
```

These variants fail with an error message or an error level even if there are no goals left. Be careful however if Coq terms have to be printed as part of the failure: term construction always forces the tactic into the goals, meaning that if there are no goals when it is evaluated, a tactic call like let x := H in fail 0 x will succeed.

Error: Tactic Failure message (level num).

Error: No such goal.

```
Example
Goal True.
   1 subgoal
     _____
     True
Proof.
fail.
   Toplevel input, characters 0-5:
   > fail.
   Error: Tactic failure.
Abort.
Goal True.
   1 subgoal
     _____
     True
Proof.
trivial; fail.
   No more subgoals.
Qed.
Goal True.
   1 subgoal
     _____
     True
Proof.
trivial.
   No more subgoals.
fail.
   Toplevel input, characters 0-5:
   > fail.
   Error: No such goal.
Abort.
Goal True.
   1 subgoal
```

(continues on next page)

(continued from previous page)

```
_____
     True
Proof.
trivial.
   No more subgoals.
all: fail.
Qed.
Goal True.
   1 subgoal
     _____
     True
Proof.
gfail.
   Toplevel input, characters 0-6:
   > gfail.
   > ^^^^
   Error: Tactic failure.
Abort.
Goal True.
   1 subgoal
     _____
     True
Proof.
trivial; gfail.
   Toplevel input, characters 0-7:
   > trivial; gfail.
   Error: Tactic failure.
Abort.
Goal True.
   1 subgoal
     _____
     True
Proof.
trivial.
   No more subgoals.
gfail.
   Toplevel input, characters 0-6:
   > gfail.
   Error: No such goal.
Abort.
Goal True.
   1 subgoal
```

(continues on next page)

5.4. Ltac 355

(continued from previous page)

```
True

Proof.
trivial.
No more subgoals.

all: gfail.
Toplevel input, characters 0-11:
> all: gfail.
> ^^^^^^
Error: Tactic failure.
```

#### **Timeout**

We can force a tactic to stop if it has not finished after a certain amount of time:

```
timeout num ltac_expr
```

*ltac\_expr* is evaluated to v which must be a tactic value. The tactic value v is applied normally, except that it is interrupted after *num* seconds if it is still running. In this case the outcome is a failure.

Warning: For the moment, timeout is based on elapsed time in seconds, which is very machine-dependent: a script that works on a quick machine may fail on a slow one. The converse is even possible if you combine a timeout with some other tacticals. This tactical is hence proposed only for convenience during debugging or other development phases, we strongly advise you to not leave any timeout in final scripts. Note also that this tactical isn't available on the native Windows port of Coq.

#### Timing a tactic

A tactic execution can be timed:

```
time string ltac_expr
```

evaluates  $ltac\_expr$  and displays the running time of the tactic expression, whether it fails or succeeds. In case of several successes, the time for each successive run is displayed. Time is in seconds and is machine-dependent. The string argument is optional. When provided, it is used to identify this particular occurrence of time.

#### Timing a tactic that evaluates to a term

Tactic expressions that produce terms can be timed with the experimental tactic

```
time_constr ltac_expr
```

which evaluates  $ltac\_expr$  () and displays the time the tactic expression evaluated, assuming successful evaluation. Time is in seconds and is machine-dependent.

This tactic currently does not support nesting, and will report times based on the innermost execution. This is due to the fact that it is implemented using the following internal tactics:

```
restart_timer string
Reset a timer

finish_timing (string) string
```

Display an optionally named timer. The parenthesized string argument is also optional, and determines the label associated with the timer for printing.

By copying the definition of  $time\_constr$  from the standard library, users can achieve support for a fixed pattern of nesting by passing different string parameters to  $restart\_timer$  and  $finish\_timing$  at each level of nesting.

#### Example

```
Ltac time_constr1 tac :=
 let eval_early := match goal with _ => restart_timer "(depth 1)" end in
 let ret := tac () in
 let eval_early := match goal with _ => finish_timing ( "Tactic evaluation" ) "(depth 1)"
 ⊶end in
 ret.
   time_constr1 is defined
Goal True.
   1 subgoal
     _____
     True
let v := time_constr
      ltac:(fun =>
              let x := time_constr1 ltac:(fun _ => constr:(10 * 10)) in
              let y := time_constr1 ltac:(fun _ => eval compute in x) in
              y) in
 pose v.
   Tactic evaluation (depth 1) ran for 0. secs (0.u,0.s)
   Tactic evaluation (depth 1) ran for 0. secs (0.u,0.s)
   Tactic evaluation ran for 0.001 secs (0.u,0.s)
   1 subgoal
     n := 100 : nat
     _____
     True
```

#### Local definitions

Local definitions can be done as follows:

```
let ident_i := ltac\_expr_i with ident_i := ltac\_expr_i in ltac\_expr each ltac\_expr_i is evaluated to v_i, then, ltac\_expr is evaluated by substituting v_i to each occurrence of ident_i, for i = 1, ..., n. There are no dependencies between the ltac\_expr_i and the ident_i.
```

Local definitions can be made recursive by using let rec instead of let. In this latter case, the definitions are evaluated lazily so that the rec keyword can be used also in non-recursive cases so as to avoid the eager evaluation of local definitions.

5.4. Ltac 357

## **Application**

An application is an expression of the following form:

The reference qualid must be bound to some defined tactic definition expecting at least as many arguments as the provided tacarg. The expressions  $ltac_{expr_i}$  are evaluated to  $v_i$ , for i = 1, ..., n.

## **Function construction**

A parameterized tactic can be built anonymously (without resorting to local definitions) with:

Indeed, local definitions of functions are a syntactic sugar for binding a fun tactic to an identifier.

## Pattern matching on terms

We can carry out pattern matching on terms with:

```
match ltac_expr with cpattern; => ltac_expr; end
```

The expression <code>ltac\_expr</code> is evaluated and should yield a term which is matched against <code>cpattern\_1</code>. The matching is non-linear: if a metavariable occurs more than once, it should match the same expression every time. It is first-order except on the variables of the form <code>@?id</code> that occur in head position of an application. For these variables, the matching is second-order and returns a functional term.

Alternatively, when a metavariable of the form ?id occurs under binders, say  $\mathbf{x_1}$ , ...,  $\mathbf{x_n}$  and the expression matches, the metavariable is instantiated by a term which can then be used in any context which also binds the variables  $\mathbf{x_1}$ , ...,  $\mathbf{x_n}$  with same types. This provides with a primitive form of matching under context which does not require manipulating a functional term.

If the matching with  $cpattern_1$  succeeds, then  $ltac\_expr_1$  is evaluated into some value by substituting the pattern matching instantiations to the metavariables. If  $ltac\_expr_1$  evaluates to a tactic and the match expression is in position to be applied to a goal (e.g. it is not bound to a variable by a let in), then this tactic is applied. If the tactic succeeds, the list of resulting subgoals is the result of the match expression. If  $ltac\_expr_1$  does not evaluate to a tactic or if the match expression is not in position to be applied to a goal, then the result of the evaluation of  $ltac\_expr_1$  is the result of the match expression.

If the matching with  $cpattern_1$  fails, or if it succeeds but the evaluation of  $ltac\_expr_1$  fails, or if the evaluation of  $ltac\_expr_1$  succeeds but returns a tactic in execution position whose execution fails, then  $cpattern_2$  is used and so on. The pattern  $\_$  matches any term and shadows all remaining patterns if any. If all clauses fail (in particular, there is no pattern  $\_$ ) then a no-matching-clause error is raised.

Failures in subsequent tactics do not cause backtracking to select new branches or inside the right-hand side of the selected branch even if it has backtracking points.

Error: No matching clauses for match.

No pattern can be used and, in particular, there is no \_ pattern.

Error: Argument of match does not evaluate to a term.

This happens when *ltac\_expr* does not denote a term.

```
Variant: multimatch ltac_expr with cpattern; => ltac_expr; end
```

Using multimatch instead of match will allow subsequent tactics to backtrack into a right-hand

side tactic which has backtracking points left and trigger the selection of a new matching branch when all the backtracking points of the right-hand side have been consumed.

The syntax match ... is, in fact, a shorthand for once multimatch ....

```
Variant: lazymatch ltac_expr with cpattern => ltac_expr end
```

Using lazymatch instead of match will perform the same pattern matching procedure but will commit to the first matching branch rather than trying a new matching if the right-hand side fails. If the right-hand side of the selected branch is a tactic with backtracking points, then subsequent failures cause this tactic to backtrack.

#### Variant: context ident [cpattern]

This special form of patterns matches any term with a subterm matching cpattern. If there is a match, the optional *ident* is assigned the "matched context", i.e. the initial term where the matched subterm is replaced by a hole. The example below will show how to use such term contexts.

If the evaluation of the right-hand-side of a valid match fails, the next matching subterm is tried. If no further subterm matches, the next clause is tried. Matching subterms are considered top-bottom and from left to right (with respect to the raw printing obtained by setting the *Printing All* flag).

## Example

```
Ltac f x :=
 match x with
   context f [S ?X] =>
                               (* To display the evaluation order *)
   idtac X;
   assert (p := eq_refl 1 : X=1);  (* To filter the case X=1 *)
   let x:= context f[0] in assert (x=0) (* To observe the context *)
 end.
   f is defined
Goal True.
   1 subgoal
     True
f (3+4).
   2
   1
   2 subgoals
     p : 1 = 1
      _____
     1 + 4 = 0
   subgoal 2 is:
    True
```

#### Pattern matching on goals

We can perform pattern matching on goals using the following expression:

If each hypothesis pattern  $hyp_{1,i}$ , with  $i=1,...,m_1$  is matched (non-linear first-order unification) by a hypothesis of the goal and if  $cpattern_1$  is matched by the conclusion of the goal, then  $ltac_expr_1$  is evaluated to  $v_1$  by substituting the pattern matching to the metavariables and the real hypothesis names bound to the possible hypothesis names occurring in the hypothesis patterns. If  $v_1$  is a tactic value, then it is applied to the goal. If this application fails, then another combination of hypotheses is tried with the same proof context pattern. If there is no other combination of hypotheses then the second proof context pattern is tried and so on. If the next to last proof context pattern fails then the last  $ltac_expr$  is evaluated to v and v is applied. Note also that matching against subterms (using the context ident [ cpattern ]) is available and is also subject to yielding several matchings.

Failures in subsequent tactics do not cause backtracking to select new branches or combinations of hypotheses, or inside the right-hand side of the selected branch even if it has backtracking points.

## Error: No matching clauses for match goal.

No clause succeeds, i.e. all matching patterns, if any, fail at the application of the right-hand-side.

**Note:** It is important to know that each hypothesis of the goal can be matched by at most one hypothesis pattern. The order of matching is the following: hypothesis patterns are examined from right to left (i.e.  $hyp_{i,mi}$  before  $hyp_{i,1}$ ). For each hypothesis pattern, the goal hypotheses are matched in order (newest first), but it possible to reverse this order (oldest first) with the match reverse goal with variant.

Using multimatch instead of match will allow subsequent tactics to backtrack into a right-hand side tactic which has backtracking points left and trigger the selection of a new matching branch or combination of hypotheses when all the backtracking points of the right-hand side have been consumed.

The syntax match [reverse] goal ... is, in fact, a shorthand for once multimatch [reverse] goal ....

Using lazymatch instead of match will perform the same pattern matching procedure but will commit to the first matching branch with the first matching combination of hypotheses rather than trying a new matching if the right-hand side fails. If the right-hand side of the selected branch is a tactic with backtracking points, then subsequent failures cause this tactic to backtrack.

#### Filling a term context

The following expression is not a tactic in the sense that it does not produce subgoals but generates a term to be used in tactic expressions:

## context ident [ltac\_expr]

*ident* must denote a context variable bound by a context pattern of a match expression. This expression evaluates replaces the hole of the value of *ident* by the value of *ltac\_expr*.

Error: Not a context variable.

Error: Unbound context identifier ident.

## Generating fresh hypothesis names

Tactics sometimes have to generate new names for hypothesis. Letting the system decide a name with the intro tactic is not so good since it is very awkward to retrieve the name the system gave. The following expression returns an identifier:

# fresh component \*

It evaluates to an identifier unbound in the goal. This fresh identifier is obtained by concatenating the value of the *components* (each of them is, either a *qualid* which has to refer to a (unqualified) name, or directly a name denoted by a *string*).

If the resulting name is already used, it is padded with a number so that it becomes fresh. If no component is given, the name is a fresh derivative of the name H.

## Computing in a constr

Evaluation of a term can be performed with:

#### eval redexpr in term

where redexpr is a reduction tactic among red, hnf, compute, simpl, cbv, lazy, unfold, fold, pattern.

## Recovering the type of a term

## type of term

This tactic returns the type of term.

## Manipulating untyped terms

#### uconstr : term

The terms built in  $L_{\rm tac}$  are well-typed by default. It may not be appropriate for building large terms using a recursive  $L_{\rm tac}$  function: the term has to be entirely type checked at each step, resulting in potentially very slow behavior. It is possible to build untyped terms using  $L_{\rm tac}$  with the uconstr: term syntax.

# type\_term term

An untyped term, in  $L_{tac}$ , can contain references to hypotheses or to  $L_{tac}$  variables containing typed or untyped terms. An untyped term can be type checked using the function type\_term whose argument is parsed as an untyped term and returns a well-typed term which can be used in tactics.

Untyped terms built using uconstr: can also be used as arguments to the *refine* tactic. In that case the untyped term is type checked against the conclusion of the goal, and the holes which are not solved by the typing procedure are turned into new subgoals.

## Counting the goals

#### numgoals

The number of goals under focus can be recovered using the numgoals function. Combined with the guard command below, it can be used to branch over the number of goals produced by previous tactics.

#### Example

```
Ltac pr_numgoals := let n := numgoals in idtac "There are" n "goals".
Goal True /\ True /\ True.
split;[|split].
all:pr_numgoals.
   There are 3 goals
```

## **Testing boolean expressions**

#### guard test

The *guard* tactic tests a boolean expression, and fails if the expression evaluates to false. If the expression evaluates to true, it succeeds without affecting the proof.

The accepted tests are simple integer comparisons.

#### Example

```
Goal True /\ True /\ True.
split;[|split].

all:let n:= numgoals in guard n<4.
Fail all:let n:= numgoals in guard n=2.
   The command has indeed failed with message:
   Condition not satisfied: 3=2</pre>
```

Error: Condition not satisfied.

# Proving a subgoal as a separate lemma

#### abstract ltac\_expr

From the outside, abstract *ltac\_expr* is the same as solve *ltac\_expr*. Internally it saves an auxiliary lemma called ident\_subproofn where ident is the name of the current goal and n is chosen so that this is a fresh name. Such an auxiliary lemma is inlined in the final proof term.

This tactical is useful with tactics such as <code>omega</code> or <code>discriminate</code> that generate huge proof terms. With that tool the user can avoid the explosion at time of the Save command without having to cut manually the proof in smaller lemmas.

It may be useful to generate lemmas minimal w.r.t. the assumptions they depend on. This can be obtained thanks to the option below.

Warning: The abstract tactic, while very useful, still has some known limitations, see https://github.com/coq/coq/issues/9146 for more details. Thus we recommend using it caution in some "non-standard" contexts. In particular, abstract won't properly work when used inside quotations ltac:(...), or if used as part of typeclass resolution, it may produce wrong terms when in universe polymorphic mode.

#### Variant: abstract ltac\_expr using ident

Give explicitly the name of the auxiliary lemma.

Warning: Use this feature at your own risk; explicitly named and reused subterms don't play well with asynchronous proofs.

## Variant: transparent\_abstract ltac\_expr

Save the subproof in a transparent lemma rather than an opaque one.

Warning: Use this feature at your own risk; building computationally relevant terms with tactics is fragile.

## Variant: transparent\_abstract ltac\_expr using ident

Give explicitly the name of the auxiliary transparent lemma.

Warning: Use this feature at your own risk; building computationally relevant terms with tactics is fragile, and explicitly named and reused subterms don't play well with asynchronous proofs.

Error: Proof is not complete.

# 5.4.3 Tactic toplevel definitions

# Defining $L_{tac}$ functions

Basically,  $L_{\rm tac}$  toplevel definitions are made as follows:

This defines a new  $L_{tac}$  function that can be used in any tactic script or new  $L_{tac}$  toplevel definition.

If preceded by the keyword Local, the tactic definition will not be exported outside the current module.

**Note:** The preceding definition can equivalently be written:

```
Variant: Ltac ident ident with ident ident := ltac_expr
```

This syntax allows recursive and mutual recursive function definitions.

```
Variant: Ltac qualid ident ::= ltac_expr
```

This syntax redefines an existing user-defined tactic.

A previous definition of qualid must exist in the environment. The new definition will always be used instead of the old one and it goes across module boundaries.

# Printing L<sub>tac</sub> tactics

## Command: Print Ltac qualid

Defined  $L_{\text{tac}}$  functions can be displayed using this command.

## Command: Print Ltac Signatures

This command displays a list of all user-defined tactics, with their arguments.

# 5.4.4 Examples of using L<sub>tac</sub>

## Proof that the natural numbers have at least two elements

# Example: Proof that the natural numbers have at least two elements

The first example shows how to use pattern matching over the proof context to prove that natural numbers have at least two elements. This can be done as follows:

```
Lemma card_nat :
  ~ exists x y : nat, forall z:nat, x = z \setminus / y = z.
   1 subgoal
     _____
     ~ (exists x y : nat, forall z : nat, x = z \setminus / y = z)
Proof.
intros (x & y & Hz).
   1 subgoal
     x, y : nat
     Hz : forall z : nat, x = z \setminus / y = z
     _____
     False
destruct (Hz 0), (Hz 1), (Hz 2).
   8 subgoals
     x, y : nat
     Hz : forall z : nat, x = z \setminus / y = z
     H : x = 0
     HO : x = 1
     H1 : x = 2
     _____
     False
   subgoal 2 is:
    False
   subgoal 3 is:
    False
   subgoal 4 is:
    False
   subgoal 5 is:
    False
   subgoal 6 is:
    False
   subgoal 7 is:
```

(continues on next page)

(continued from previous page)

```
False
    subgoal 8 is:
     False
At this point, the congruence tactic would finish the job:
all: congruence.
    No more subgoals.
But for the purpose of the example, let's craft our own custom tactic to solve this:
all: match goal with
     |  : ?a = ?b, |  : ?a = ?c |  => assert (b = c) by now transitivity a
     end.
    8 subgoals
      x, y : nat
      Hz : forall z : nat, x = z \setminus / y = z
      H : x = 0
      HO : x = 1
      H1 : x = 2
      H2 : 1 = 2
      _____
      False
    subgoal 2 is:
    False
    subgoal 3 is:
    False
    subgoal 4 is:
     False
    subgoal 5 is:
     False
    subgoal 6 is:
    False
    subgoal 7 is:
```

all: discriminate.

No more subgoals.

False subgoal 8 is: False

Notice that all the (very similar) cases coming from the three eliminations (with three distinct natural numbers) are successfully solved by a match goal structure and, in particular, with only one pattern (use of non-linear matching).

Proving that a list is a permutation of a second list

# Example: Proving that a list is a permutation of a second list

Let's first define the permutation predicate:

```
Section Sort.
Variable A : Set.
Inductive perm : list A -> list A -> Prop :=
    | perm_refl : forall 1, perm 1 1
    | perm_cons : forall a 10 11, perm 10 11 -> perm (a :: 10) (a :: 11)
    | perm_append : forall a 1, perm (a :: 1) (1 ++ a :: nil)
    | perm_trans : forall 10 11 12, perm 10 11 -> perm 11 12 -> perm 10 12.
End Sort.
```

Next we define an auxiliary tactic perm\_aux which takes an argument used to control the recursion depth. This tactic works as follows: If the lists are identical (i.e. convertible), it completes the proof. Otherwise, if the lists have identical heads, it looks at their tails. Finally, if the lists have different heads, it rotates the first list by putting its head at the end.

Every time we perform a rotation, we decrement n. When n drops down to 1, we stop performing rotations and we fail. The idea is to give the length of the list as the initial value of n. This way of counting the number of rotations will avoid going back to a head that had been considered before.

From Section Syntax we know that Ltac has a primitive notion of integers, but they are only used as arguments for primitive tactics and we cannot make computations with them. Thus, instead, we use Coq's natural number type nat.

The main tactic is solve\_perm. It computes the lengths of the two lists and uses them as arguments to call perm\_aux if the lengths are equal. (If they aren't, the lists cannot be permutations of each other.)

```
Ltac solve_perm :=
  match goal with
  | |- (perm _ ?11 ?12) =>
    match eval compute in (length 11 = length 12) with
    | (?n = ?n) => perm_aux n
    end
end.
```

And now, here is how we can use the tactic solve\_perm:

## Deciding intuitionistic propositional logic

Pattern matching on goals allows powerful backtracking when returning tactic values. An interesting application is the problem of deciding intuitionistic propositional logic. Considering the contraction-free sequent calculi LJT\* of Roy Dyckhoff [Dyc92], it is quite natural to code such a tactic using the tactic language as shown below.

```
Ltac basic :=
match goal with
    | |- True => trivial
    | _ : False |- _ => contradiction
    | _ : ?A |- ?A => assumption
end.
Ltac simplify :=
repeat (intros;
    match goal with
        | H : ~ _ |- _ => red in H
| H : _ /\ _ |- _ =>
             elim H; do 2 intro; clear H
         | H : _ \/ _ |- _ =>
             elim H; intro; clear H
         \mid H : ?A / \ ?B -> ?C \mid - \_ =>
             cut (A -> B -> C);
                 [ intro | intros; apply H; split; assumption ]
         \mid H: ?A \backslash/ ?B \rightarrow ?C \mid- \mid- \mid>
             cut (B -> C);
                 [ cut (A -> C);
                      [ intros; clear H
                      | intro; apply H; left; assumption ]
                 | intro; apply H; right; assumption ]
         | HO : ?A -> ?B, H1 : ?A |- _ =>
             cut B; [ intro; clear HO | apply HO; assumption ]
         | |- _ /\ _ => split
         | |- ~ _ => red
    end).
Ltac my_tauto :=
  simplify; basic ||
  match goal with
      | H : (?A -> ?B) -> ?C |- _ =>
           cut (B -> C);
               [ intro; cut (A -> B);
                    [ intro; cut C;
                        [ intro; clear H | apply H; assumption ]
```

(continues on next page)

(continued from previous page)

```
| clear H ]
| intro; apply H; intro; assumption ]; my_tauto
| H : ~ ?A -> ?B |- _ =>
cut (False -> B);
        [ intro; cut (A -> False);
        [ intro; cut B;
        [ intro; clear H | apply H; assumption ]
        | clear H ]
        | intro; apply H; red; intro; assumption ]; my_tauto
| |- _ \/ _ => (left; my_tauto) || (right; my_tauto)
end.
```

The tactic basic tries to reason using simple rules involving truth, falsity and available assumptions. The tactic simplify applies all the reversible rules of Dyckhoff's system. Finally, the tactic my\_tauto (the main tactic to be called) simplifies with simplify, tries to conclude with basic and tries several paths using the backtracking rules (one of the four Dyckhoff's rules for the left implication to get rid of the contraction and the right or).

Having defined my\_tauto, we can prove tautologies like these:

```
Lemma my_tauto_ex1 :
   forall A B : Prop, A /\ B -> A \/ B.
Proof.
my_tauto.
Qed.

Lemma my_tauto_ex2 :
   forall A B : Prop, (~ ~ B -> B) -> (A -> B) -> ~ ~ A -> B.
Proof.
my_tauto.
Qed.
```

#### **Deciding type isomorphisms**

A trickier problem is to decide equalities between types modulo isomorphisms. Here, we choose to use the isomorphisms of the simply typed  $\lambda$ -calculus with Cartesian product and unit type (see, for example, [dC95]). The axioms of this  $\lambda$ -calculus are given below.

```
Open Scope type_scope.

Section Iso_axioms.

Variables A B C : Set.

Axiom Com : A * B = B * A.

Axiom Ass : A * (B * C) = A * B * C.

Axiom Cur : (A * B -> C) = (A -> B -> C).

Axiom Dis : (A -> B * C) = (A -> B) * (A -> C).

Axiom P_unit : A * unit = A.

Axiom AR_unit : (A -> unit) = unit.

Axiom AL_unit : (unit -> A) = A.
```

```
Lemma Cons : B = C \rightarrow A * B = A * C.
Proof.
intro Heq; rewrite Heq; reflexivity.
Qed.
End Iso_axioms.
Ltac simplify_type ty :=
match ty with
    | ?A * ?B * ?C =>
       rewrite <- (Ass A B C); try simplify_type_eq</pre>
    | ?A * ?B -> ?C =>
       rewrite (Cur A B C); try simplify_type_eq
    | ?A -> ?B * ?C =>
        rewrite (Dis A B C); try simplify_type_eq
    | ?A * unit =>
        rewrite (P_unit A); try simplify_type_eq
    | unit * ?B =>
        rewrite (Com unit B); try simplify_type_eq
    | ?A -> unit =>
        rewrite (AR_unit A); try simplify_type_eq
    | unit -> ?B =>
        rewrite (AL_unit B); try simplify_type_eq
    | ?A * ?B =>
        (simplify_type A; try simplify_type_eq) ||
        (simplify_type B; try simplify_type_eq)
    | ?A -> ?B =>
        (simplify_type A; try simplify_type_eq) ||
        (simplify_type B; try simplify_type_eq)
end
with simplify_type_eq :=
match goal with
    | |- ?A = ?B => try simplify_type A; try simplify_type B
end.
Ltac len trm :=
match trm with
    | * ?B => let succ := len B in constr:(S succ)
    | _ => constr:(1)
end.
Ltac assoc := repeat rewrite <- Ass.
Ltac solve_type_eq n :=
match goal with
    | |- ?A = ?A => reflexivity
    | - ?A * ?B = ?A * ?C =>
        apply Cons; let newn := len B in solve_type_eq newn
    | - ?A * ?B = ?C =>
        match eval compute in n with
            | 1 => fail
                pattern (A * B) at 1; rewrite Com; assoc; solve_type_eq (pred n)
        end
end.
```

Ltac solve\_iso := simplify\_type\_eq; compare\_structure.

The tactic to judge equalities modulo this axiomatization is shown above. The algorithm is quite simple. First types are simplified using axioms that can be oriented (this is done by simplify\_type and simplify\_type\_eq). The normal forms are sequences of Cartesian products without a Cartesian product in the left component. These normal forms are then compared modulo permutation of the components by the tactic compare\_structure. If they have the same length, the tactic solve\_type\_eq attempts to prove that the types are equal. The main tactic that puts all these components together is solve\_iso.

Here are examples of what can be solved by solve\_iso.

```
Lemma solve_iso_ex1 :
    forall A B : Set, A * unit * B = B * (unit * A).
Proof.
intros; solve_iso.
Qed.

Lemma solve_iso_ex2 :
    forall A B C : Set,
        (A * unit -> B * (C * unit)) =
        (A * unit -> (C -> unit) * C) * (unit -> A -> B).
Proof.
intros; solve_iso.
Qed.
```

# 5.4.5 Debugging L<sub>tac</sub> tactics

#### **Backtraces**

#### Flag: Ltac Backtrace

Setting this flag displays a backtrace on Ltac failures that can be useful to find out what went wrong. It is disabled by default for performance reasons.

## Info trace

#### Command: Info num ltac\_expr

This command can be used to print the trace of the path eventually taken by an  $L_{tac}$  script. That is, the list of executed tactics, discarding all the branches which have failed. To that end the Info command can be used with the following syntax.

The number *num* is the unfolding level of tactics in the trace. At level 0, the trace contains a sequence of tactics in the actual script, at level 1, the trace will be the concatenation of the traces of these tactics, etc...

## Example

```
Ltac t x := exists x; reflexivity.
Goal exists n, n=0.

Info 0 t 1||t 0.
    exists with 0;<ltac_plugin::reflexivity@0>
    No more subgoals.

Undo.

Info 1 t 1||t 0.
    <ltac_plugin::exists@1> with 0;simple refine ?X12;<unknown>
    No more subgoals.
```

The trace produced by Info tries its best to be a reparsable  $L_{tac}$  script, but this goal is not achievable in all generality. So some of the output traces will contain oddities.

As an additional help for debugging, the trace produced by Info contains (in comments) the messages produced by the idtac tactical at the right position in the script. In particular, the calls to idtac in branches which failed are not printed.

## Option: Info Level num

This option is an alternative to the *Info* command.

This will automatically print the same trace as Info num at each tactic call. The unfolding level can be overridden by a call to the Info command.

## Interactive debugger

#### Flag: Ltac Debug

This flag governs the step-by-step debugger that comes with the  $L_{tac}$  interpreter.

When the debugger is activated, it stops at every step of the evaluation of the current  $L_{\text{tac}}$  expression and prints information on what it is doing. The debugger stops, prompting for a command which can be one of the following:

simple newline:	go to the next step
h:	get help
x:	exit current evaluation
s:	continue current evaluation without stopping
r n:	advance n steps further
r string:	advance up to the next call to "idtac string"

## Error: Debug mode not available in the IDE

A non-interactive mode for the debugger is available via the flag:

# Flag: Ltac Batch Debug

This flag has the effect of presenting a newline at every prompt, when the debugger is on. The debug log thus created, which does not require user input to generate when this flag is set, can then be run through external tools such as diff.

# Profiling $L_{tac}$ tactics

It is possible to measure the time spent in invocations of primitive tactics as well as tactics defined in  $L_{\rm tac}$  and their inner invocations. The primary use is the development of complex tactics, which can sometimes be so slow as to impede interactive usage. The reasons for the performance degradation can be intricate, like a slowly performing  $L_{\rm tac}$  match or a sub-tactic whose performance only degrades in certain situations. The profiler generates a call tree and indicates the time spent in a tactic depending on its calling context. Thus it allows to locate the part of a tactic definition that contains the performance issue.

#### Flag: Ltac Profiling

This flag enables and disables the profiler.

# Command: Show Ltac Profile

Prints the profile

## Variant: Show Ltac Profile string

Prints a profile for all tactics that start with *string*. Append a period (.) to the string if you only want exactly that name.

#### Command: Reset Ltac Profile

Resets the profile, that is, deletes all accumulated information.

Warning: Backtracking across a Reset Ltac Profile will not restore the information.

```
Require Import Coq.omega.Omega.
Ltac mytauto := tauto.
Ltac tac := intros; repeat split; omega || mytauto.
Notation max x y := (x + (y - x)) (only parsing).
Goal forall x y z A B C D E F G H I J K L M N O P Q R S T U V W X Y Z,
   \max x (\max y z) = \max (\max x y) z / \max x (\max y z) = \max (\max x y) z
    (A /\ B /\ C /\ D /\ E /\ F /\ G /\ H /\ I /\ J /\ K /\ L /\ M /\
    N /\ O /\ P /\ Q /\ R /\ S /\ T /\ U /\ V /\ W /\ X /\ Y /\ Z
    Z /\ Y /\ X /\ W /\ V /\ U /\ T /\ S /\ R /\ Q /\ P /\ O /\ N /\
    M \ / \ L \ / \ K \ / \ J \ / \ I \ / \ H \ / \ G \ / \ F \ / \ E \ / \ D \ / \ C \ / \ B \ / \ A).
Proof.
Set Ltac Profiling.
   No more subgoals.
Show Ltac Profile.
                    2.258s
   total time:
    tactic
                                            local total
                                                          calls
    tac -----
                                                                  2.258s
                                            0.1% 100.0%
    <Coq.Init.Tauto.with_uniform_flags> ---
                                            0.0% 73.3%
                                                             26
                                                                  0.109s
    <Coq.Init.Tauto.tauto_gen> ------
                                            0.0% 73.3%
                                                                  0.109s
                                                             26
    <Coq.Init.Tauto.tauto_intuitionistic> -
                                            0.0% 73.2%
                                                             26
                                                                  0.109s
    t_tauto_intuit ----- 0.1%
                                                  73.1%
                                                             26
                                                                  0.109s
    <Coq.Init.Tauto.simplif> ----- 51.0%
                                                  70.6%
                                                             26
                                                                  0.107s
    omega ----- 26.4% 26.4%
                                                             28
                                                                  0.284s
```

<Coq.Init.Tauto.is\_conj> ----- 12.3% 12.3%

elim id ------

(continues on next page)

28756

650

4.4%

4.4%

0.017s

0.000s

(continued from previous page)

				,
<coq.init.tauto.axioms></coq.init.tauto.axioms>	1.9%	2.4%	0	0.002s
tactic	local	total	calls	max
tac	0.1%	100.0%	1	2.258s
<pre><coq.init.tauto.with_uniform_flags> -</coq.init.tauto.with_uniform_flags></pre>	0.0%	73.3%	26	0.109s
<pre><coq.init.tauto.tauto_gen></coq.init.tauto.tauto_gen></pre>	0.0%	73.2%	26	0.109s
<coq.init.tauto.tauto_intuitionistic></coq.init.tauto.tauto_intuitionistic>	0.0%	73.2%	26	0.109s
t_tauto_intuit	0.1%	73.1%	26	0.109s
<pre><coq.init.tauto.simplif></coq.init.tauto.simplif></pre>	51.0%	70.6%	26	0.107s
<coq.init.tauto.is_conj></coq.init.tauto.is_conj>	12.3%	12.3%	28756	0.017s
elim id				0.000s
<coq.init.tauto.axioms></coq.init.tauto.axioms>	1.9%	2.4%	0	0.002s
omega	26.4%	26.4%	28	0.284s
Show Ltac Profile "omega".				
total time: 2.258s				
tactic	local	total	calls	max
omega	26.4%	26.4%	28	0.284s
tactic	local	total	calls	max

#### Abort.

Unset Ltac Profiling.

## start ltac profiling

This tactic behaves like *idtac* but enables the profiler.

## stop ltac profiling

Similarly to *start ltac profiling*, this tactic behaves like *idtac*. Together, they allow you to exclude parts of a proof script from profiling.

# reset ltac profile

This tactic behaves like the corresponding vernacular command and allow displaying and resetting the profile from tactic scripts for benchmarking purposes.

## show ltac profile

This tactic behaves like the corresponding vernacular command and allow displaying and resetting the profile from tactic scripts for benchmarking purposes.

# show ltac profile string

This tactic behaves like the corresponding vernacular command and allow displaying and resetting the profile from tactic scripts for benchmarking purposes.

You can also pass the -profile-ltac command line option to coqc, which turns the *Ltac Profiling* flag on at the beginning of each document, and performs a *Show Ltac Profile* at the end.

Warning: Note that the profiler currently does not handle backtracking into multi-success tactics, and issues a warning to this effect in many cases when such backtracking occurs.

#### Run-time optimization tactic

## optimize\_heap

This tactic behaves like idtac, except that running it compacts the heap in the OCaml run-time system. It is analogous to the Vernacular command Optimize Heap.

# 5.5 Ltac2

The Ltac tactic language is probably one of the ingredients of the success of Coq, yet it is at the same time its Achilles' heel. Indeed, Ltac:

- has often unclear semantics
- is very non-uniform due to organic growth
- lacks expressivity (data structures, combinators, types, ...)
- is slow
- is error-prone and fragile
- has an intricate implementation

Following the need of users who are developing huge projects relying critically on Ltac, we believe that we should offer a proper modern language that features at least the following:

- at least informal, predictable semantics
- a type system
- standard programming facilities (e.g., datatypes)

This new language, called Ltac2, is described in this chapter. It is still experimental but we nonetheless encourage users to start testing it, especially wherever an advanced tactic language is needed. The previous implementation of Ltac, described in the previous chapter, will be referred to as Ltac1.

## 5.5.1 General design

There are various alternatives to Ltac1, such as Mtac or Rtac for instance. While those alternatives can be quite different from Ltac1, we designed Ltac2 to be as close as reasonably possible to Ltac1, while fixing the aforementioned defects.

In particular, Ltac2 is:

- a member of the ML family of languages, i.e.
  - a call-by-value functional language
  - with effects
  - together with the Hindley-Milner type system
- a language featuring meta-programming facilities for the manipulation of Coq-side terms
- a language featuring notation facilities to help write palatable scripts

We describe more in details each point in the remainder of this document.

# 5.5.2 ML component

## Overview

Ltac2 is a member of the ML family of languages, in the sense that it is an effectful call-by-value functional language, with static typing à la Hindley-Milner (see [DM82]). It is commonly accepted that ML constitutes a sweet spot in PL design, as it is relatively expressive while not being either too lax (unlike dynamic typing) nor too strict (unlike, say, dependent types).

The main goal of Ltac2 is to serve as a meta-language for Coq. As such, it naturally fits in the ML lineage, just as the historical ML was designed as the tactic language for the LCF prover. It can also be seen as a general-purpose language, by simply forgetting about the Coq-specific features.

Sticking to a standard ML type system can be considered somewhat weak for a meta-language designed to manipulate Coq terms. In particular, there is no way to statically guarantee that a Coq term resulting from an Ltac2 computation will be well-typed. This is actually a design choice, motivated by backward compatibility with Ltac1. Instead, well-typedness is deferred to dynamic checks, allowing many primitive functions to fail whenever they are provided with an ill-typed term.

The language is naturally effectful as it manipulates the global state of the proof engine. This allows to think of proof-modifying primitives as effects in a straightforward way. Semantically, proof manipulation lives in a monad, which allows to ensure that Ltac2 satisfies the same equations as a generic ML with unspecified effects would do, e.g. function reduction is substitution by a value.

To import Ltac2, use the following command:

From Ltac2 Require Import Ltac2.

## Type Syntax

At the level of terms, we simply elaborate on Ltac1 syntax, which is quite close to OCaml. Types follow the simply-typed syntax of OCaml.

The non-terminal lident designates identifiers starting with a lowercase.

The set of base types can be extended thanks to the usual ML type declarations such as algebraic datatypes and records.

Built-in types include:

- int, machine integers (size not specified, in practice inherited from OCaml)
- string, mutable strings
- 'a array, mutable arrays
- exn, exceptions
- constr, kernel-side terms

- pattern, term patterns
- ident, well-formed identifiers

#### Type declarations

One can define new types with the following commands.

```
Command: Ltac2 Type <a href="Itac2_typeparams">Itac2_typeparams</a> lident
```

This command defines an abstract type. It has no use for the end user and is dedicated to types representing data coming from the OCaml world.

```
Variant: Ltac2 Type rec ? ltac2_typeparams ? lident := ltac2_typedef
```

This command defines a type with a manifest. There are four possible kinds of such definitions: alias, variant, record and open variant types.

Aliases are just a name for a given type expression and are transparently unfoldable to it. They cannot be recursive. The non-terminal uident designates identifiers starting with an uppercase.

Variants are sum types defined by constructors and eliminated by pattern-matching. They can be recursive, but the rec flag must be explicitly set. Pattern matching must be exhaustive.

Records are product types with named fields and eliminated by projection. Likewise they can be recursive if the rec flag is set.

```
Variant: Ltac2 Type <a href="Itac2_typeparams">Itac2_qualid ::= [ ltac2_constructordef ]</a>
Open variants are a special kind of variant types whose constructors are not statically defined, but can instead be extended dynamically. A typical example is the standard exn type. Pattern matching on open variants must always include a catch-all clause. They can be extended with
```

## **Term Syntax**

this command.

The syntax of the functional fragment is very close to the one of Ltac1, except that it adds a true pattern-matching feature, as well as a few standard constructs from ML.

```
match ltac2_term with ltac2_branch ... ltac2_branch end
                          int
                          string
                          ltac2_term ; ltac2_term
                          [| ltac2_term ; ... ; ltac2_term |]
                          ( ltac2_term , ... , ltac2_term )
                          { ltac2_field ltac2_field ... ltac2_field }
                          ltac2_term . ( ltac2_qualid )
                          ltac2\_term . ( ltac2\_qualid ) := ltac2\_term
                          [; ltac2_term ; ... ; ltac2_term ]
                          ltac2_term :: ltac2_term
ltac2_branch
                          ltac2_pattern => ltac2_term
                   ::=
ltac2_pattern
                   ::=
                          ltac2_var
                          ( ltac2_pattern , ... , ltac2_pattern )
                          ltac2_constructor ltac2_pattern ... ltac2_pattern
                          ltac2_pattern :: ltac2_pattern
ltac2 field
                   ::=
                          ltac2\_qualid := ltac2\_term
```

In practice, there is some additional syntactic sugar that allows e.g. to bind a variable and match on it at the same time, in the usual ML style.

There is dedicated syntax for list and array literals.

**Note:** For now, deep pattern matching is not implemented.

#### Ltac Definitions

Command: Ltac2 mutable | rec | lident := ltac2\_term

This command defines a new global Ltac2 value.

For semantic reasons, the body of the Ltac2 definition must be a syntactical value, that is, a function, a constant or a pure constructor recursively applied to values.

If rec is set, the tactic is expanded into a recursive binding.

If mutable is set, the definition can be redefined at a later stage (see below).

## Command: Ltac2 Set qualid := ltac2\_term

This command redefines a previous mutable definition. Mutable definitions act like dynamic binding, i.e. at runtime, the last defined value for this entry is chosen. This is useful for global flags and the like.

#### Reduction

We use the usual ML call-by-value reduction, with an otherwise unspecified evaluation order. This is a design choice making it compatible with OCaml, if ever we implement native compilation. The expected equations are as follows:

```
(fun x => t) V t{x := V} (\betav) let x := V in t t{x := V} (let) match C V<sub>0</sub> ... V with ... | C x<sub>0</sub> ... x => t | ... end t {x := V} (\iota) (t any term, V values, C constructor)
```

Note that call-by-value reduction is already a departure from Ltac1 which uses heuristics to decide when to evaluate an expression. For instance, the following expressions do not evaluate the same way in Ltac1.

```
foo (idtac; let x := 0 in bar)
foo (let x := 0 in bar)
```

Instead of relying on the idtac idiom, we would now require an explicit thunk to not compute the argument, and foo would have e.g. type (unit -> unit) -> unit.

```
foo (fun () \Rightarrow let x := 0 in bar)
```

## **Typing**

Typing is strict and follows the Hindley-Milner system. Unlike Ltac1, there are no type casts at runtime, and one has to resort to conversion functions. See notations though to make things more palatable.

In this setting, all the usual argument-free tactics have type unit -> unit, but one can return a value of type t thanks to terms of type unit -> t, or take additional arguments.

## Effects

Effects in Ltac2 are straightforward, except that instead of using the standard IO monad as the ambient effectful world, Ltac2 is has a tactic monad.

Note that the order of evaluation of application is not specified and is implementation-dependent, as in OCaml.

We recall that the Proofview.tactic monad is essentially a IO monad together with backtracking state representing the proof state.

Intuitively a thunk of type unit -> 'a can do the following:

- It can perform non-backtracking IO like printing and setting mutable variables
- It can fail in a non-recoverable way
- It can use first-class backtracking. One way to think about this is that thunks are isomorphic to this type: (unit -> 'a) ~ (unit -> exn + ('a \* (exn -> 'a))) i.e. thunks can produce a lazy list of results where each tail is waiting for a continuation exception.
- It can access a backtracking proof state, consisting among other things of the current evar assignation and the list of goals under focus.

We now describe more thoroughly the various effects in Ltac2.

## Standard IO

The Ltac2 language features non-backtracking IO, notably mutable data and printing operations.

Mutable fields of records can be modified using the set syntax. Likewise, built-in types like string and array feature imperative assignment. See modules String and Array respectively.

A few printing primitives are provided in the Message module, allowing to display information to the user.

#### **Fatal errors**

The Ltac2 language provides non-backtracking exceptions, also known as *panics*, through the following primitive in module Control:

```
val throw : exn -> 'a
```

Unlike backtracking exceptions from the next section, this kind of error is never caught by backtracking primitives, that is, throwing an exception destroys the stack. This is codified by the following equation, where E is an evaluation context:

```
E[throw e] throw e
(e value)
```

There is currently no way to catch such an exception, which is a deliberate design choice. Eventually there might be a way to catch it and destroy all backtrack and return values.

## **Backtracking**

In Ltac2, we have the following backtracking primitives, defined in the Control module:

```
Ltac2 Type 'a result := [ Val ('a) | Err (exn) ].
val zero : exn -> 'a
val plus : (unit -> 'a) -> (exn -> 'a) -> 'a
val case : (unit -> 'a) -> ('a * (exn -> 'a)) result
```

If one views thunks as lazy lists, then zero is the empty list and plus is list concatenation, while case is pattern-matching.

The backtracking is first-class, i.e. one can write plus (fun () => "x") (fun \_ => "y") : string producing a backtracking string.

These operations are expected to satisfy a few equations, most notably that they form a monoid compatible with sequentialization.:

```
plus t zero t ()
plus (fun () => zero e) f  f  e
plus (plus t f) g  plus t (fun e => plus (f e) g)

case (fun () => zero e)   Err  e
case (fun () => plus (fun () => t) f)   Val (t,f)

let x := zero e in u  zero e
let x := plus t f in u  plus (fun () => let x := t in u) (fun e => let x := f e in u)

(t, u, f, g, e values)
```

#### Goals

A goal is given by the data of its conclusion and hypotheses, i.e. it can be represented as  $[\Gamma \quad A]$ .

The tactic monad naturally operates over the whole proofview, which may represent several goals, including none. Thus, there is no such thing as the current goal. Goals are naturally ordered, though.

It is natural to do the same in Ltac2, but we must provide a way to get access to a given goal. This is the role of the enter primitive, which applies a tactic to each currently focused goal in turn:

```
val enter : (unit -> unit) -> unit
```

It is guaranteed that when evaluating enter f, f is called with exactly one goal under focus. Note that f may be called several times, or never, depending on the number of goals under focus before the call to enter.

Accessing the goal data is then implicit in the Ltac2 primitives, and may panic if the invariants are not respected. The two essential functions for observing goals are given below.:

```
val hyp : ident -> constr
val goal : unit -> constr
```

The two above functions panic if there is not exactly one goal under focus. In addition, hyp may also fail if there is no hypothesis with the corresponding name.

# 5.5.3 Meta-programming

#### Overview

One of the major implementation issues of Ltac1 is the fact that it is never clear whether an object refers to the object world or the meta-world. This is an incredible source of slowness, as the interpretation must be aware of bound variables and must use heuristics to decide whether a variable is a proper one or referring to something in the Ltac context.

Likewise, in Ltac1, constr parsing is implicit, so that foo 0 is not foo applied to the Ltac integer expression 0 (Ltac does have a notion of integers, though it is not first-class), but rather the Coq term Datatypes.0.

The implicit parsing is confusing to users and often gives unexpected results. Ltac2 makes these explicit using quoting and unquoting notation, although there are notations to do it in a short and elegant way so as not to be too cumbersome to the user.

#### **Generic Syntax for Quotations**

In general, quotations can be introduced in terms using the following syntax, where quotentry is some parsing entry.

```
ltac2_term += ident : ( quotentry )
```

#### **Built-in quotations**

The current implementation recognizes the following built-in quotations:

- ident, which parses identifiers (type Init.ident).
- constr, which parses Coq terms and produces an-evar free term at runtime (type Init.constr).

- open\_constr, which parses Coq terms and produces a term potentially with holes at runtime (type Init.constr as well).
- pattern, which parses Coq patterns and produces a pattern used for term matching (type Init. pattern).
- reference, which parses either a *qualid* or &ident. Qualified names are globalized at internalization into the corresponding global reference, while &id is turned into Std.VarRef id. This produces at runtime a Std.reference. There shall be no white space between the ampersand symbol (&) and the identifier (ident).

The following syntactic sugar is provided for two common cases.

- @id is the same as ident:(id)
- 't is the same as open\_constr:(t)

#### Strict vs. non-strict mode

Depending on the context, quotation-producing terms (i.e. constr or open\_constr) are not internalized in the same way. There are two possible modes, the *strict* and the *non-strict* mode.

- In strict mode, all simple identifiers appearing in a term quotation are required to be resolvable statically. That is, they must be the short name of a declaration which is defined globally, excluding section variables and hypotheses. If this doesn't hold, internalization will fail. To work around this error, one has to specifically use the & notation.
- In non-strict mode, any simple identifier appearing in a term quotation which is not bound in the global context is turned into a dynamic reference to a hypothesis. That is to say, internalization will succeed, but the evaluation of the term at runtime will fail if there is no such variable in the dynamic context.

Strict mode is enforced by default, such as for all Ltac2 definitions. Non-strict mode is only set when evaluating Ltac2 snippets in interactive proof mode. The rationale is that it is cumbersome to explicitly add & interactively, while it is expected that global tactics enforce more invariants on their code.

# **Term Antiquotations**

## **Syntax**

One can also insert Ltac2 code into Coq terms, similarly to what is possible in Ltac1.

```
term += ltac2:( ltac2 term )
```

Antiquoted terms are expected to have type unit, as they are only evaluated for their side-effects.

#### **Semantics**

A quoted Coq term is interpreted in two phases, internalization and evaluation.

- Internalization is part of the static semantics, that is, it is done at Ltac2 typing time.
- Evaluation is part of the dynamic semantics, that is, it is done when a term gets effectively computed by Ltac2.

Note that typing of Coq terms is a dynamic process occurring at Ltac2 evaluation time, and not at Ltac2 typing time.

#### Static semantics

During internalization, Coq variables are resolved and antiquotations are type-checked as Ltac2 terms, effectively producing a glob\_constr in Coq implementation terminology. Note that although it went through the type-checking of Ltac2, the resulting term has not been fully computed and is potentially ill-typed as a runtime Coq term.

#### Example

The following term is valid (with type unit -> constr), but will fail at runtime:

```
Ltac2 myconstr () := constr:(nat -> 0).
```

Term antiquotations are type-checked in the enclosing Ltac2 typing context of the corresponding term expression.

#### Example

The following will type-check, with type constr.

```
let x := '0 in constr:(1 + ltac2:(exact x))
```

Beware that the typing environment of antiquotations is **not** expanded by the Coq binders from the term.

## Example

The following Ltac2 expression will **not** type-check:

```
`constr:(fun x : nat => ltac2:(exact x))`
`(* Error: Unbound variable 'x' *)`
```

There is a simple reason for that, which is that the following expression would not make sense in general.

```
constr:(fun x : nat => ltac2:(clear @x; exact x))
```

Indeed, a hypothesis can suddenly disappear from the runtime context if some other tactic pulls the rug from under you.

Rather, the tactic writer has to resort to the **dynamic** goal environment, and must write instead explicitly that she is accessing a hypothesis, typically as follows.

```
constr:(fun x : nat => ltac2:(exact (hyp @x)))
```

This pattern is so common that we provide dedicated Ltac2 and Coq term notations for it.

- &x as an Ltac2 expression expands to hyp @x.
- &x as a Coq constr expression expands to ltac2:(Control.refine (fun () => hyp @x)).

In the special case where Ltac2 antiquotations appear inside a Coq term notation, the notation variables are systematically bound in the body of the tactic expression with type Ltac2.Init.preterm. Such a type represents untyped syntactic Coq expressions, which can by typed in the current context using the Ltac2.Constr.pretype function.

## Example

The following notation is essentially the identity.

## **Dynamic semantics**

During evaluation, a quoted term is fully evaluated to a kernel term, and is in particular type-checked in the current environment.

Evaluation of a quoted term goes as follows.

- The quoted term is first evaluated by the pretyper.
- Antiquotations are then evaluated in a context where there is exactly one goal under focus, with the hypotheses coming from the current environment extended with the bound variables of the term, and the resulting term is fed into the quoted term.

Relative orders of evaluation of antiquotations and quoted term are not specified.

For instance, in the following example, tac will be evaluated in a context with exactly one goal under focus, whose last hypothesis is H: nat. The whole expression will thus evaluate to the term fun H: nat => H.

```
let tac () := hyp @H in constr:(fun H : nat => ltac2:(tac ()))
```

Many standard tactics perform type-checking of their argument before going further. It is your duty to ensure that terms are well-typed when calling such tactics. Failure to do so will result in non-recoverable exceptions.

## **Trivial Term Antiquotations**

It is possible to refer to a variable of type constr in the Ltac2 environment through a specific syntax consistent with the antiquotations presented in the notation section.

```
term += $lident
```

In a Coq term, writing \$x is semantically equivalent to ltac2:(Control.refine (fun () => x)), up to re-typechecking. It allows to insert in a concise way an Ltac2 variable of type constr into a Coq term.

#### Match over terms

Ltac2 features a construction similar to Ltac1 match over terms, although in a less hard-wired way.

```
ltac2_term ::= match! ltac2_term with constrmatching .. constrmatching end
lazy_match! ltac2_term with constrmatching .. constrmatching end
multi_match! ltac2_term with constrmatching .. constrmatching end
constrmatching ::= | constrpattern => ltac2_term
constrpattern ::= term
context [ term ]
context lident [ term ]
```

This construction is not primitive and is desugared at parsing time into calls to term matching functions from the Pattern module. Internally, it is implemented thanks to a specific scope accepting the *constrmatching* syntax.

Variables from the *constrpattern* are statically bound in the body of the branch, to values of type constr for the variables from the *term* pattern and to a value of type Pattern.context for the variable *lident*.

Note that unlike Ltac, only lowercase identifiers are valid as Ltac2 bindings, so that there will be a syntax error if one of the bound variables starts with an uppercase character.

The semantics of this construction is otherwise the same as the corresponding one from Ltac1, except that it requires the goal to be focused.

#### Match over goals

Similarly, there is a way to match over goals in an elegant way, which is just a notation desugared at parsing time.

Variables from hypmatching and constrpattern are bound in the body of the branch. Their types are:

- constr for pattern variables appearing in a term
- Pattern.context for variables binding a context
- ident for variables binding a hypothesis name.

The same identifier caveat as in the case of matching over constrapplies, and this features has the same semantics as in Ltac1. In particular, a reverse flag can be specified to match hypotheses from the more recently introduced to the least recently introduced one.

#### 5.5.4 Notations

Notations are the crux of the usability of Ltac1. We should be able to recover a feeling similar to the old implementation by using and abusing notations.

# **Scopes**

A scope is a name given to a grammar entry used to produce some Ltac2 expression at parsing time. Scopes are described using a form of S-expression.

```
ltac2_scope ::= string int lident (ltac2_scope ;)
```

A few scopes contain antiquotation features. For the sake of uniformity, all antiquotations are introduced by the syntax \$lident.

The following scopes are built-in.

• constr:

```
- parses c = term and produces constr:(c)
```

This scope can be parameterized by a list of delimiting keys of interpretation scopes (as described in *Local interpretation rules for notations*), describing how to interpret the parsed term. For instance, constr(A, B) parses c = term and produces constr(CAB).

```
• ident:
     - parses id = ident and produces ident:(id)
     - parses (x = ident) and produces the variable x
• list0(ltac2_scope):
     - if ltac2\_scope parses quotentry, then it parses (quotentry<sub>0</sub>, ..., quotentry<sub>n</sub>) and produces
       [quotentry<sub>0</sub>; ...; quotentry<sub>n</sub>].
• list0(ltac2_scope, sep = string_sen):
     - if ltac2_scope parses quotentry, then it parses (quotentry, string_sen ... string_sen
       quotentry<sub>n</sub>) and produce [quotentry<sub>0</sub>; ...; quotentry<sub>n</sub>].
• list1: same as list0 (with or without separator) but parses quotentry instead of quotentry
• opt(ltac2_scope)
    - if ltac2_scope parses quotentry, parses quotentry and produces either None or Some x
       where x is the parsed expression.
• self:

    parses a Ltac2 expression at the current level and returns it as is.

• next:
     - parses a Ltac2 expression at the next level and returns it as is.
• tactic(n = int):
     - parses a Ltac2 expression at the provided level n and returns it as is.
• thunk(ltac2_scope):
     - parses the same as scope, and if e is the parsed expression, returns fun () \Rightarrow e.
• STRING:
     - parses the corresponding string as an identifier and returns ().
• keyword(s = string):
     - parses the string s as a keyword and returns ().
• terminal(s = string):

    parses the string s as a keyword, if it is already a keyword, otherwise as an ident. Returns ().

• seq(ltac2_scope<sub>1</sub>, ..., ltac2_scope<sub>2</sub>):
     - parses scope, ..., scope, in this order, and produces a tuple made out of the parsed values in
```

A few other specific scopes exist to handle Ltac1-like syntax, but their use is discouraged and they are thus not documented.

the same order. As an optimization, all subscopes of the form STRING are left out of the returned tuple, instead of returning a useless unit value. It is forbidden for the various subscopes to refer

For now there is no way to declare new scopes from Ltac2 side, but this is planned.

to the global entry using self or next.

#### **Notations**

The Ltac2 parser can be extended with syntactic notations.

```
Command: Ltac2 Notation lident (ltac2_scope) string : int := ltac2_term
```

A Ltac2 notation adds a parsing rule to the Ltac2 grammar, which is expanded to the provided body where every token from the notation is let-bound to the corresponding generated expression.

## Example

Assume we perform:

```
Ltac2 Notation "foo" c(thunk(constr)) ids(list0(ident)) := Bar.f c ids.
```

Then the following expression

```
let y := @X in foo (nat -> nat) x $y
```

will expand at parsing time to

```
let y := @X \text{ in let } c := fun () => constr:(nat -> nat) with ids := [@x; y] in Bar.f c ids
```

Beware that the order of evaluation of multiple let-bindings is not specified, so that you may have to resort to thunking to ensure that side-effects are performed at the right time.

#### **Abbreviations**

## Variant: Ltac2 Notation lident := ltac2\_term

This command introduces a special kind of notation, called an abbreviation, that is designed so that it does not add any parsing rules. It is similar in spirit to Coq abbreviations, insofar as its main purpose is to give an absolute name to a piece of pure syntax, which can be transparently referred to by this name as if it were a proper definition.

The abbreviation can then be manipulated just as a normal Ltac2 definition, except that it is expanded at internalization time into the given expression. Furthermore, in order to make this kind of construction useful in practice in an effectful language such as Ltac2, any syntactic argument to an abbreviation is thunked on-the-fly during its expansion.

For instance, suppose that we define the following.

```
Ltac2 Notation foo := fun x \Rightarrow x ().
```

Then we have the following expansion at internalization time.

```
foo 0 (fun x => x ()) (fun _ => 0)
```

Note that abbreviations are not typechecked at all, and may result in typing errors after expansion.

#### 5.5.5 Evaluation

Ltac2 features a toplevel loop that can be used to evaluate expressions.

## Command: Ltac2 Eval ltac2\_term

This command evaluates the term in the current proof if there is one, or in the global environment otherwise, and displays the resulting value to the user together with its type. This command is pure in the sense that it does not modify the state of the proof, and in particular all side-effects are discarded.

# **5.5.6** Debug

#### Flag: Ltac2 Backtrace

When this flag is set, toplevel failures will be printed with a backtrace.

# 5.5.7 Compatibility layer with Ltac1

#### Ltac1 from Ltac2

## Simple API

One can call Ltac1 code from Ltac2 by using the ltac1 quotation. It parses a Ltac1 expression, and semantics of this quotation is the evaluation of the corresponding code for its side effects. In particular, it cannot return values, and the quotation has type unit.

```
ltac2_term ::= ltac1 : ( ltac_expr )
```

Ltac1 cannot implicitly access variables from the Ltac2 scope, but this can be done with an explicit annotation on the ltac1 quotation.

```
ltac2_term ::= ltac1 : ( ident ... ident |- ltac_expr )
```

The return type of this expression is a function of the same arity as the number of identifiers, with arguments of type Ltac2.Ltac1.t (see below). This syntax will bind the variables in the quoted Ltac1 code as if they had been bound from Ltac1 itself. Similarly, the arguments applied to the quotation will be passed at runtime to the Ltac1 code.

#### Low-level API

There exists a lower-level FFI into Ltac1 that is not recommended for daily use, which is available in the Ltac2.Ltac1 module. This API allows to directly manipulate dynamically-typed Ltac1 values, either through the function calls, or using the ltac1val quotation. The latter parses the same as ltac1, but has type Ltac2.Ltac1.t instead of unit, and dynamically behaves as an Ltac1 thunk, i.e. ltac1val:(foo) corresponds to the tactic closure that Ltac1 would generate from idtac; foo.

Due to intricate dynamic semantics, understanding when Ltac1 value quotations focus is very hard. This is why some functions return a continuation-passing style value, as it can dispatch dynamically between focused and unfocused behaviour.

The same mechanism for explicit binding of variables as described in the previous section applies.

#### Ltac2 from Ltac1

Same as above by switching Ltac1 by Ltac2 and using the ltac2 quotation instead.

The typing rules are dual, that is, the optional identifiers are bound with type Ltac2.Ltac1.t in the Ltac2

expression, which is expected to have type unit. The value returned by this quotation is an Ltac1 function with the same arity as the number of bound variables.

Note that when no variables are bound, the inner tactic expression is evaluated eagerly, if one wants to use it as an argument to a Ltac1 function, one has to resort to the good old idtac; ltac2:(foo) trick. For instance, the code below will fail immediately and won't print anything.

```
From Ltac2 Require Import Ltac2.
Set Default Proof Mode "Classic".
Ltac mytac tac := idtac "I am being evaluated"; tac.
   mytac is defined
Goal True.
   1 subgoal
     _____
     True
Proof.
(* Doesn't print anything *)
Fail mytac ltac2:(fail).
   The command has indeed failed with message:
   Uncaught Ltac2 exception: Tactic_failure (None)
(* Prints and fails *)
Fail mytac ltac:(idtac; ltac2:(fail)).
   I am being evaluated
   The command has indeed failed with message:
   Uncaught Ltac2 exception: Tactic_failure (None)
```

In any case, the value returned by the fully applied quotation is an unspecified dummy Ltac1 closure and should not be further used.

## Switching between Ltac languages

We recommend using the *Default Proof Mode* option to switch between tactic languages with a proof-based granularity. This allows to incrementally port the proof scripts.

## 5.5.8 Transition from Ltac1

Owing to the use of a lot of notations, the transition should not be too difficult. In particular, it should be possible to do it incrementally. That said, we do *not* guarantee you it is going to be a blissful walk either. Hopefully, owing to the fact Ltac2 is typed, the interactive dialogue with Coq will help you.

We list the major changes and the transition strategies hereafter.

# Syntax changes

Due to conflicts, a few syntactic rules have changed.

- The dispatch tactical tac; [foo|bar] is now written tac > [foo|bar].
- Levels of a few operators have been revised. Some tacticals now parse as if they were normal functions. Parentheses are now required around complex arguments, such as abstractions. The tacticals affected are: try, repeat, do, once, progress, time, abstract.

• idtac is no more. Either use () if you expect nothing to happen, (fun () => ()) if you want a thunk (see next section), or use printing primitives from the Message module if you want to display something.

#### Tactic delay

Tactics are not magically delayed anymore, neither as functions nor as arguments. It is your responsibility to thunk them beforehand and apply them at the call site.

A typical example of a delayed function:

```
Ltac foo := blah.
```

becomes

```
Ltac2 foo () := blah.
```

All subsequent calls to foo must be applied to perform the same effect as before.

Likewise, for arguments:

```
Ltac bar tac := tac; tac; tac.
```

becomes

```
Ltac2 bar tac := tac (); tac (); tac ().
```

We recommend the use of syntactic notations to ease the transition. For instance, the first example can alternatively be written as:

```
Ltac2 foo0 () := blah. Ltac2 Notation foo := foo0 ().
```

This allows to keep the subsequent calls to the tactic as-is, as the expression foo will be implicitly expanded everywhere into fool (). Such a trick also works for arguments, as arguments of syntactic notations are implicitly thunked. The second example could thus be written as follows.

```
Ltac2 bar0 tac := tac (); tac (); tac (). Ltac2 Notation bar := bar0.
```

## Variable binding

Ltac1 relies on complex dynamic trickery to be able to tell apart bound variables from terms, hypotheses, etc. There is no such thing in Ltac2, as variables are recognized statically and other constructions do not live in the same syntactic world. Due to the abuse of quotations, it can sometimes be complicated to know what a mere identifier represents in a tactic expression. We recommend tracking the context and letting the compiler print typing errors to understand what is going on.

We list below the typical changes one has to perform depending on the static errors produced by the type-checker.

## In Ltac expressions

Error: Unbound value constructor X

- if X is meant to be a term from the current stactic environment, replace the problematic use by
   'X.
- if X is meant to be a hypothesis from the goal context, replace the problematic use by &X.

#### In quotations

Error: The reference X was not found in the current environment

- if X is meant to be a tactic expression bound by a Ltac2 let or function, replace the problematic use by \$X.
- if X is meant to be a hypothesis from the goal context, replace the problematic use by &X.

## **Exception catching**

Ltac2 features a proper exception-catching mechanism. For this reason, the Ltac1 mechanism relying on fail taking integers, and tacticals decreasing it, has been removed. Now exceptions are preserved by all tacticals, and it is your duty to catch them and re-raise them as needed.

# 5.6 Detailed examples of tactics

This chapter presents detailed examples of certain tactics, to illustrate their behavior.

# 5.6.1 dependent induction

The tactics dependent induction and dependent destruction are another solution for inverting inductive predicate instances and potentially doing induction at the same time. It is based on the BasicElim tactic of Conor McBride which works by abstracting each argument of an inductive instance by a variable and constraining it by equalities afterwards. This way, the usual induction and destruct tactics can be applied to the abstracted instance and after simplification of the equalities we get the expected goals.

The abstracting tactic is called generalize\_eqs and it takes as argument a hypothesis to generalize. It uses the JMeq datatype defined in Coq.Logic.JMeq, hence we need to require it before. For example, revisiting the first example of the inversion documentation:

The index S n gets abstracted by a variable here, but a corresponding equality is added under the abstract instance so that no information is actually lost. The goal is now almost amenable to do induction or case analysis. One should indeed first move n into the goal to strengthen it before doing induction, or n will be fixed in the inductive hypotheses (this does not matter for case analysis). As a rule of thumb, all the variables that appear inside constructors in the indices of the hypothesis should be generalized. This is exactly what the generalize\_eqs\_vars variant does:

As the hypothesis itself did not appear in the goal, we did not need to use an heterogeneous equality to relate the new hypothesis to the old one (which just disappeared here). However, the tactic works just as well in this case, e.g.:

One drawback of this approach is that in the branches one will have to substitute the equalities back into the instance to get the right assumptions. Sometimes injection of constructors will also be needed to recover the needed equalities. Also, some subgoals should be directly solved because of inconsistent contexts arising from the constraints on indexes. The nice thing is that we can make a tactic based on discriminate, injection and variants of substitution to automatically do such simplifications (which may involve the axiom K). This is what the simplify\_dep\_elim tactic from Coq.Program.Equality does. For example, we might simplify the previous goals considerably:

The higher-order tactic <code>do\_depind</code> defined in <code>Coq.Program.Equality</code> takes a tactic and combines the building blocks we have seen with it: generalizing by equalities calling the given tactic with the generalized induction hypothesis as argument and cleaning the subgoals with respect to equalities. Its most important instantiations are <code>dependent induction</code> and <code>dependent destruction</code> that do induction or simply case analysis on the generalized hypothesis. For example we can redo what we've done manually with dependent

destruction:

This gives essentially the same result as inversion. Now if the destructed hypothesis actually appeared in the goal, the tactic would still be able to invert it, contrary to dependent inversion. Consider the following example on vectors:

Set Implicit Arguments.

In this case, the v variable can be replaced in the goal by the generalized hypothesis only when it has a type of the form vector (S n), that is only in the second case of the destruct. The first one is dismissed because S n <> 0.

#### A larger example

Let's see how the technique works with induction on inductive predicates on a real example. We will develop an example application to the theory of simply-typed lambda-calculus formalized in a dependently-typed style:

```
Notation " t \longrightarrow t' " := (arrow t t') (at level 20, t' at next level).
Inductive ctx : Type :=
         | empty : ctx
         | snoc : ctx -> type -> ctx.
Notation " G , tau " := (snoc G tau) (at level 20, tau at next level).
Fixpoint conc (G D : ctx) : ctx :=
         match D with
         | empty => G
         | snoc D' x => snoc (conc G D') x
Notation " G; D " := (conc G D) (at level 20).
Inductive term : ctx -> type -> Type :=
         | ax : forall G tau, term (G, tau) tau
         | weak : forall G tau,
                    term G tau -> forall tau', term (G, tau') tau
         | abs : forall G tau tau',
                   term (G , tau) tau' -> term G (tau --> tau')
         | app : forall G tau tau',
                   term G (tau --> tau') -> term G tau -> term G tau'.
```

We have defined types and contexts which are snoc-lists of types. We also have a conc operation that concatenates two contexts. The term datatype represents in fact the possible typing derivations of the calculus, which are isomorphic to the well-typed terms, hence the name. A term is either an application of:

- the axiom rule to type a reference to the first variable in a context
- the weakening rule to type an object in a larger context
- the abstraction or lambda rule to type a function
- the application to type an application of a function to an argument

Once we have this datatype we want to do proofs on it, like weakening:

```
Lemma weakening : forall G D tau, term (G; D) tau -> forall tau', term (G; tau'; D) tau.
```

The problem here is that we can't just use induction on the typing derivation because it will forget about the G; D constraint appearing in the instance. A solution would be to rewrite the goal as:

```
Lemma weakening' : forall G' tau, term G' tau \rightarrow forall G D, (G ; D) = G' \rightarrow forall tau', term (G, tau' ; D) tau.
```

With this proper separation of the index from the instance and the right induction loading (putting G and D after the inducted-on hypothesis), the proof will go through, but it is a very tedious process. One is also forced to make a wrapper lemma to get back the more natural statement. The dependent induction tactic alleviates this trouble by doing all of this plumbing of generalizing and substituting back automatically. Indeed we can simply write:

```
Require Import Coq.Program.Tactics.
Require Import Coq.Program.Equality.
```

```
Lemma weakening : forall G D tau, term (G; D) tau ->
forall tau', term (G, tau'; D) tau.

Proof with simpl in *; simpl_depind; auto.

intros G D tau H.
dependent induction H generalizing G D; intros.
```

This call to dependent induction has an additional arguments which is a list of variables appearing in the instance that should be generalized in the goal, so that they can vary in the induction hypotheses. By default, all variables appearing inside constructors (except in a parameter position) of the instantiated hypothesis will be generalized automatically but one can always give the list explicitly.

```
Show.
4 subgoals

G0 : ctx
tau : type
G, D : ctx
x : G0, tau = G; D
tau' : type
=======term ((G, tau'); D) tau

subgoal 2 is:
term ((G, tau'0); D) tau
subgoal 3 is:
term ((G, tau'0); D) (tau --> tau')
subgoal 4 is:
term ((G, tau'0); D) tau'
```

The simpl\_depind tactic includes an automatic tactic that tries to simplify equalities appearing at the beginning of induction hypotheses, generally using trivial applications of reflexivity. In cases where the equality is not between constructor forms though, one must help the automation by giving some arguments, using the specialize tactic for example.

```
destruct D... apply weak; apply ax.
apply ax.
destruct D...
Show.
   4 subgoals
     GO : ctx
     tau : type
     H : term GO tau
     tau' : type
     IHterm : forall G D : ctx,
              GO = G; D \rightarrow forall tau' : type, term ((G, tau'); D) tau
     tau'0 : type
     _____
     term ((GO, tau'), tau'O) tau
   subgoal 2 is:
    term (((G, tau'0); D), t) tau
```

(continues on next page)

(continued from previous page)

```
subgoal 3 is:
    term ((G, tau'0); D) (tau --> tau')
    subgoal 4 is:
     term ((G, tau'0); D) tau'
specialize (IHterm GO empty eq_refl).
    4 subgoals
     GO : ctx
     tau : type
     H : term GO tau
     tau' : type
     IHterm : forall tau' : type, term ((GO, tau'); empty) tau
     tau'0 : type
      _____
     term ((GO, tau'), tau'0) tau
   subgoal 2 is:
     term (((G, tau'0); D), t) tau
    subgoal 3 is:
    term ((G, tau'0); D) (tau --> tau')
    subgoal 4 is:
     term ((G, tau'0); D) tau'
Once the induction hypothesis has been narrowed to the right equality, it can be used directly.
apply weak, IHterm.
   3 subgoals
     tau : type
     G, D : ctx
     IHterm : forall GO DO : ctx,
               G; D = GO; DO \rightarrow forall tau' : type, term ((GO, tau'); DO) tau
     H : term (G; D) tau
```

term ((G, tau'0); D) tau'

Now concluding this subgoal is easy.

t, tau'0 : type

subgoal 2 is:

subgoal 3 is:

constructor; apply IHterm; reflexivity.

term (((G, tau'0); D), t) tau

term ((G, tau'0); D) (tau --> tau')

#### See also:

The induction, case, and inversion tactics.

# 5.6.2 autorewrite

Here are two examples of autorewrite use. The first one ( *Ackermann function*) shows actually a quite basic use where there is no conditional rewriting. The second one ( *Mac Carthy function*) involves conditional rewritings and shows how to deal with them using the optional tactic of the Hint Rewrite command.

## Example: Ackermann function

# Example: MacCarthy function

```
Require Import Omega.
Parameter g : nat -> nat -> nat.
Axiom g0: forall m:nat, g 0 m = m.
Hint Rewrite g0 g1 g2 using omega : base1.
Lemma Resg0 : g 1 110 = 100.
  1 subgoal
   _____
   g 1 110 = 100
autorewrite with base1 using reflexivity || simpl.
  No more subgoals.
Lemma Resg1 : g 1 95 = 91.
  1 subgoal
    _____
   g 1 95 = 91
autorewrite with base1 using reflexivity || simpl.
  No more subgoals.
```

# 5.7 The SSReflect proof language

Authors Georges Gonthier, Assia Mahboubi, Enrico Tassi

# 5.7.1 Introduction

This chapter describes a set of tactics known as SSReflect originally designed to provide support for the so-called *small scale reflection* proof methodology. Despite the original purpose this set of tactic is of general interest and is available in Coq starting from version 8.7.

SSReflect was developed independently of the tactics described in Chapter *Tactics*. Indeed the scope of the tactics part of SSReflect largely overlaps with the standard set of tactics. Eventually the overlap will be reduced in future releases of Coq.

Proofs written in SSReflect typically look quite different from the ones written using only tactics as per Chapter *Tactics*. We try to summarise here the most "visible" ones in order to help the reader already accustomed to the tactics described in Chapter *Tactics* to read this chapter.

The first difference between the tactics described in this chapter and the tactics described in Chapter *Tactics* is the way hypotheses are managed (we call this *bookkeeping*). In Chapter *Tactics* the most common approach is to avoid moving explicitly hypotheses back and forth between the context and the conclusion of the goal. On the contrary in SSReflect all bookkeeping is performed on the conclusion of the goal, using for that purpose a couple of syntactic constructions behaving similar to tacticals (and often named as such in this chapter). The: tactical moves hypotheses from the context to the conclusion, while => moves hypotheses from the conclusion to the context, and in moves back and forth a hypothesis from the context to the conclusion for the time of applying an action to it.

While naming hypotheses is commonly done by means of an as clause in the basic model of Chapter *Tactics*, it is here to => that this task is devoted. Tactics frequently leave new assumptions in the conclusion, and are often followed by => to explicitly name them. While generalizing the goal is normally not explicitly needed in Chapter *Tactics*, it is an explicit operation performed by :.

#### See also:

#### Bookkeeping

Beside the difference of bookkeeping model, this chapter includes specific tactics which have no explicit counterpart in Chapter *Tactics* such as tactics to mix forward steps and generalizations as *generally have* or *without loss*.

SSReflect adopts the point of view that rewriting, definition expansion and partial evaluation participate all to a same concept of rewriting a goal in a larger sense. As such, all these functionalities are provided by the rewrite tactic.

SSReflect includes a little language of patterns to select subterms in tactics or tacticals where it matters. Its most notable application is in the *rewrite* tactic, where patterns are used to specify where the rewriting step has to take place.

Finally, SSReflect supports so-called reflection steps, typically allowing to switch back and forth between the computational view and logical view of a concept.

To conclude it is worth mentioning that SSReflect tactics can be mixed with non SSReflect tactics in the same proof, or in the same Ltac expression. The few exceptions to this statement are described in section *Compatibility issues*.

#### **Acknowledgments**

The authors would like to thank Frédéric Blanqui, François Pottier and Laurence Rideau for their comments and suggestions.

# **5.7.2** Usage

# **Getting started**

To be available, the tactics presented in this manual need the following minimal set of libraries to be loaded: ssreflect.v, ssrfun.v and ssrbool.v. Moreover, these tactics come with a methodology specific to the authors of SSReflect and which requires a few options to be set in a different way than in their default way. All in all, this corresponds to working in the following context:

```
From Coq Require Import ssreflect ssrfun ssrbool.
Set Implicit Arguments.
Unset Strict Implicit.
Unset Printing Implicit Defensive.
```

#### See also:

```
Implicit Arguments, Strict Implicit, Printing Implicit Defensive
```

## Compatibility issues

Requiring the above modules creates an environment which is mostly compatible with the rest of Coq, up to a few discrepancies:

- New keywords (is) might clash with variable, constant, tactic or tactical names, or with quasi-keywords in tactic or vernacular notations.
- New tactic(al)s names (last, done, have, suffices, suff, without loss, wlog, congr, unlock) might clash with user tactic names.
- Identifiers with both leading and trailing \_, such as \_x\_, are reserved by SSReflect and cannot appear
  in scripts.
- The extensions to the *rewrite* tactic are partly incompatible with those available in current versions of Coq; in particular: rewrite . . in (type of k) or rewrite . . in \* or any other variant of *rewrite* will not work, and the SSReflect syntax and semantics for occurrence selection and rule chaining is different. Use an explicit rewrite direction (rewrite <- ... or rewrite -> ...) to access the Coq rewrite tactic.
- New symbols (//, /=, //=) might clash with adjacent existing symbols. This can be avoided by inserting white spaces.
- New constant and theorem names might clash with the user theory. This can be avoided by not importing all of SSReflect:

```
From Coq Require ssreflect. Import ssreflect.SsrSyntax.
```

Note that the full syntax of SSReflect's rewrite and reserved identifiers are enabled only if the ssreflect module has been required and if SsrSyntax has been imported. Thus a file that requires (without importing) ssreflect and imports SsrSyntax, can be required and imported without automatically enabling SSReflect's extended rewrite syntax and reserved identifiers.

- Some user notations (in particular, defining an infix;) might interfere with the "open term", parenthesis free, syntax of tactics such as have, set and pose.
- The generalization of if statements to non-Boolean conditions is turned off by SSReflect, because it is mostly subsumed by Coercion to bool of the sumXXX types (declared in ssrfun.v) and the if term is pattern then term else term construct (see Pattern conditional). To use the generalized form, turn off the SSReflect Boolean if notation using the command: Close Scope boolean\_if\_scope.
- The following flags can be unset to make SSReflect more compatible with parts of Coq:

# Flag: SsrRewrite

Controls whether the incompatible rewrite syntax is enabled (the default). Disabling the flag makes the syntax compatible with other parts of Coq.

## Flag: SsrIdents

Controls whether tactics can refer to SSReflect-generated variables that are in the form \_xxx\_. Scripts with explicit references to such variables are fragile; they are prone to failure if the proof is later modified or if the details of variable name generation change in future releases of Coq.

The default is on, which gives an error message when the user tries to create such identifiers. Disabling the flag generates a warning instead, increasing compatibility with other parts of Coq.

## 5.7.3 Gallina extensions

Small-scale reflection makes an extensive use of the programming subset of Gallina, Coq's logical specification language. This subset is quite suited to the description of functions on representations, because it closely follows the well-established design of the ML programming language. The SSReflect extension provides three additions to Gallina, for pattern assignment, pattern testing, and polymorphism; these mitigate minor but annoying discrepancies between Gallina and ML.

# Pattern assignment

The SSReflect extension provides the following construct for irrefutable pattern matching, that is, destructuring assignment:

```
term += let: pattern := term in term
```

Note the colon: after the let keyword, which avoids any ambiguity with a function definition or Coq's basic destructuring let. The let: construct differs from the latter in that

• The pattern can be nested (deep pattern matching), in particular, this allows expression of the form:

```
let: exist (x, y) p_xy := Hp in ...
```

• The destructured constructor is explicitly given in the pattern, and is used for type inference.

# Example

```
Definition f u := let: (m, n) := u in m + n.
    f is defined
Check f.
    f
        : nat * nat -> nat
```

Using let: Coq infers a type for f, whereas with a usual let the same term requires an extra type annotation in order to type check.

```
Fail Definition f u := let (m, n) := u in m + n. The command has indeed failed with message: Cannot infer a type for this expression.
```

The let: construct is just (more legible) notation for the primitive Gallina expression match term with pattern => term end.

The SSReflect destructuring assignment supports all the dependent match annotations; the full syntax is

```
term += let: pattern as ident ? in pattern := term return term ? in term
```

where the second pattern and the second term are types.

When the as and return keywords are both present, then *ident* is bound in both the second *pattern* and the second *term*; variables in the optional type *pattern* are bound only in the second term, and other variables in the first *pattern* are bound only in the third *term*, however.

#### Pattern conditional

The following construct can be used for a refutable pattern matching, that is, pattern testing:

```
term += if term is pattern then term else term
```

Although this construct is not strictly ML (it does exist in variants such as the pattern calculus or the  $\rho$ -calculus), it turns out to be very convenient for writing functions on representations, because most such functions manipulate simple data types such as Peano integers, options, lists, or binary trees, and the pattern conditional above is almost always the right construct for analyzing such simple types. For example, the null and all list function(al)s can be defined as follows:

#### Example

```
Variable d: Set.
    d is declared

Fixpoint null (s : list d) :=
    if s is nil then true else false.
    null is defined
    null is recursively defined (decreasing on 1st argument)

Variable a : d -> bool.
    a is declared

Fixpoint all (s : list d) : bool :=
    if s is cons x s' then a x && all s' else true.
    all is defined
    all is recursively defined (decreasing on 1st argument)
```

The pattern conditional also provides a notation for destructuring assignment with a refutable pattern, adapted to the pure functional setting of Gallina, which lacks a Match\_Failure exception.

Like let: above, the if...is construct is just (more legible) notation for the primitive Gallina expression match term with pattern => term | \_ => term end.

Similarly, it will always be displayed as the expansion of this form in terms of primitive match expressions (where the default expression may be replicated).

Explicit pattern testing also largely subsumes the generalization of the if construct to all binary data types; compare if *term* is inl \_ then *term* else *term* and if *term* then *term* else *term*.

The latter appears to be marginally shorter, but it is quite ambiguous, and indeed often requires an explicit annotation (term : {\_}} + {\_}}) to type check, which evens the character count.

Therefore, SSReflect restricts by default the condition of a plain if construct to the standard bool type; this avoids spurious type annotations.

## Example

```
Definition orb b1 b2 := if b1 then true else b2. orb is defined
```

As pointed out in section Compatibility issues, this restriction can be removed with the command:

Close Scope boolean\_if\_scope.

Like let: above, the if-is-then-else construct supports the dependent match annotations:

```
term += if term is pattern as ident in pattern return term then term else term
```

As in let: the variable *ident* (and those in the type pattern) are bound in the second *term*; *ident* is also bound in the third *term* (but not in the fourth *term*), while the variables in the first *pattern* are bound only in the third *term*.

Another variant allows to treat the else case first:

```
term += if term isn't pattern then term else term
```

Note that pattern eventually binds variables in the third term and not in the second term.

#### Parametric polymorphism

Unlike ML, polymorphism in core Gallina is explicit: the type parameters of polymorphic functions must be declared explicitly, and supplied at each point of use. However, Coq provides two features to suppress redundant parameters:

- Sections are used to provide (possibly implicit) parameters for a set of definitions.
- Implicit arguments declarations are used to tell Coq to use type inference to deduce some parameters from the context at each point of call.

The combination of these features provides a fairly good emulation of ML-style polymorphism, but unfortunately this emulation breaks down for higher-order programming. Implicit arguments are indeed not inferred at all points of use, but only at points of call, leading to expressions such as

#### Example

Unfortunately, such higher-order expressions are quite frequent in representation functions, especially those which use Coq's Structures to emulate Haskell typeclasses.

Therefore, SSReflect provides a variant of Coq's implicit argument declaration, which causes Coq to fill in some implicit parameters at each point of use, e.g., the above definition can be written:

## Example

```
Prenex Implicits null.
Definition all_null (s : list T) := all null s.
    all_null is defined
```

Better yet, it can be omitted entirely, since all\_null s isn't much of an improvement over all null s.

The syntax of the new declaration is

# Command: Prenex Implicits ident;

This command checks that each  $ident_i$  is the name of a functional constant, whose implicit arguments are prenex, i.e., the first  $n_i > 0$  arguments of  $ident_i$  are implicit; then it assigns Maximal Implicit status to these arguments.

As these prenex implicit arguments are ubiquitous and have often large display strings, it is strongly recommended to change the default display settings of Coq so that they are not printed (except after a Set Printing All command). All SSReflect library files thus start with the incantation

```
Set Implicit Arguments.
Unset Strict Implicit.
Unset Printing Implicit Defensive.
```

## **Anonymous arguments**

When in a definition, the type of a certain argument is mandatory, but not its name, one usually uses "arrow" abstractions for prenex arguments, or the (\_ : term) syntax for inner arguments. In SSReflect, the latter can be replaced by the open syntax of term or (equivalently) & term, which are both syntactically equivalent to a (\_ : term) expression. This feature almost behaves as the following extension of the binder syntax:

```
binder += & term of term
```

Caveat: & T and of T abbreviations have to appear at the end of a binder list. For instance, the usual two-constructor polymorphic type list, i.e. the one of the standard List library, can be defined by the following declaration:

#### Example

```
Inductive list (A : Type) : Type := nil | cons of A & list A.
    list is defined
    list_rect is defined
    list_rec is defined
    list_rec is defined
    list_sind is defined
```

# Wildcards

The terms passed as arguments to SSReflect tactics can contain *holes*, materialized by wildcards \_. Since SSReflect allows a more powerful form of type inference for these arguments, it enhances the possibilities of

using such wildcards. These holes are in particular used as a convenient shorthand for abstractions, especially in local definitions or type expressions.

Wildcards may be interpreted as abstractions (see for example sections *Definitions* and *Structure*), or their content can be inferred from the whole context of the goal (see for example section *Abbreviations*).

#### **Definitions**

#### pose

This tactic allows to add a defined constant to a proof context. SSReflect generalizes this tactic in several ways. In particular, the SSReflect pose tactic supports *open syntax*: the body of the definition does not need surrounding parentheses. For instance:

```
pose t := x + y.
```

is a valid tactic expression.

The pose tactic is also improved for the local definition of higher order terms. Local definitions of functions can use the same syntax as global ones. For example, the tactic pose supports parameters:

#### Example

The SSReflect pose tactic also supports (co)fixpoints, by providing the local counterpart of the Fixpoint f := ... and CoFixpoint f := ... constructs. For instance, the following tactic:

```
pose fix f (x y : nat) {struct x} : nat :=
  if x is S p then S (f p y) else 0.
```

defines a local fixpoint f, which mimics the standard plus operation on natural numbers.

Similarly, local cofixpoints can be defined by a tactic of the form:

```
pose cofix f (arg : T) := \dots .
```

The possibility to include wildcards in the body of the definitions offers a smooth way of defining local abstractions. The type of "holes" is guessed by type inference, and the holes are abstracted. For instance the tactic:

```
pose f := _ + 1.
```

is shorthand for:

```
pose f n := n + 1.
```

When the local definition of a function involves both arguments and holes, hole abstractions appear first. For instance, the tactic:

```
pose f x := x + _.
```

is shorthand for:

```
pose f n x := x + n.
```

The interaction of the pose tactic with the interpretation of implicit arguments results in a powerful and concise syntax for local definitions involving dependent types. For instance, the tactic:

```
pose f x y := (x, y).
```

adds to the context the local definition:

```
pose f (Tx Ty : Type) (x : Tx) (y : Ty) := (x, y).
```

The generalization of wildcards makes the use of the pose tactic resemble ML-like definitions of polymorphic functions.

#### **Abbreviations**

The SSReflect set tactic performs abbreviations: it introduces a defined constant for a subterm appearing in the goal and/or in the context.

SSReflect extends the set tactic by supplying:

- an open syntax, similarly to the pose (ssreflect) tactic;
- a more aggressive matching algorithm;
- an improved interpretation of wildcards, taking advantage of the matching algorithm;
- an improved occurrence selection mechanism allowing to abstract only selected occurrences of a term.

where:

- *ident* is a fresh identifier chosen by the user.
- term 1 is an optional type annotation. The type annotation term 1 can be given in open syntax (no surrounding parentheses). If no occ\_switch (described hereafter) is present, it is also the case for the second term. On the other hand, in presence of occ\_switch, parentheses surrounding the second term are mandatory.
- In the occurrence switch occ\_switch, if the first element of the list is a natural, this element should be a number, and not an Ltac variable. The empty list {} is not interpreted as a valid occurrence switch, it is rather used as a flag to signal the intent of the user to clear the name following it (see Occurrence switches and redex switches and Introduction in the context)

The tactic:

### Example

```
Lemma test x : f x + f x = f x.
   1 subgoal
    x : nat
    _____
    f x + f x = f x
set t := f_{-}.
   1 subgoal
    x : nat
    t := f x : nat
    _____
    t + t = t
set t := \{2\}(f_{-}).
   1 subgoal
    x : nat
    t := f x : nat
    _____
    f x + t = f x
```

The type annotation may contain wildcards, which will be filled with the appropriate value by the matching process.

The tactic first tries to find a subterm of the goal matching the second term (and its type), and stops at the first subterm it finds. Then the occurrences of this subterm selected by the optional  $occ_switch$  are replaced by ident and a definition ident := term is added to the context. If no  $occ_switch$  is present, then all the occurrences are abstracted.

## Matching

The matching algorithm compares a pattern *term* with a subterm of the goal by comparing their heads and then pairwise unifying their arguments (modulo conversion). Head symbols match under the following conditions:

- If the head of term is a constant, then it should be syntactically equal to the head symbol of the subterm.
- If this head is a projection of a canonical structure, then canonical structure equations are used for the matching.
- If the head of term is *not* a constant, the subterm should have the same structure ( $\lambda$  abstraction, let...in structure ...).
- If the head of term is a hole, the subterm should have at least as many arguments as term.

## Example

(continues on next page)

(continued from previous page)

```
x + y = z

set t := _ x.
1 subgoal

x, y, z : nat
t := Nat.add x : nat -> nat
=======t y = z
```

• In the special case where term is of the form (let f := t0 in f) t1 ... tn, then the pattern term is treated as (\_ t1 ... tn). For each subterm in the goal having the form (A u1 ... um) with m n, the matching algorithm successively tries to find the largest partial application (A u1 ... uj) convertible to the head t0 of term.

## Example

The notation unkeyed defined in ssreflect.v is a shorthand for the degenerate term let x := ... in x.

# Moreover:

• Multiple holes in term are treated as independent placeholders.

## Example

- The type of the subterm matched should fit the type (possibly casted by some type annotations) of the pattern term.
- The replacement of the subterm found by the instantiated pattern should not capture variables. In the example above x is bound and should not be captured.

#### Example

```
Lemma test : forall x : nat, x + 1 = 0.

1 subgoal

------

forall x : nat, x + 1 = 0

Fail set t := _ + 1.

The command has indeed failed with message:

The pattern (_ + 1) did not match and has holes. Did you mean pose?
```

 Typeclass inference should fill in any residual hole, but matching should never assign a value to a global existential variable.

#### Occurrence selection

SSReflect provides a generic syntax for the selection of occurrences by their position indexes. These occurrence switches are shared by all SSReflect tactics which require control on subterm selection like rewriting, generalization, ...

An occurrence switch can be:

• A list natural numbers  $\{+$  n1 ... nm $\}$  of occurrences affected by the tactic.

## Example

```
Lemma test : f 2 + f 8 = f 2 + f 2.

1 subgoal

f 2 + f 8 = f 2 + f 2

set x := {+1 3}(f 2).

1 subgoal

x := f 2 : nat

x + f 8 = f 2 + x
```

Notice that some occurrences of a given term may be hidden to the user, for example because of a notation. The vernacular Set Printing All command displays all these hidden occurrences and should be used to find the correct coding of the occurrences to be selected<sup>298</sup>.

# Example

 $<sup>^{298}</sup>$  Unfortunately, even after a call to the Set Printing All command, some occurrences are still not displayed to the user, essentially the ones possibly hidden in the predicate of a dependent match structure.

- A list of natural numbers between {n1 ... nm}. This is equivalent to the previous {+ n1 ... nm} but the list should start with a number, and not with an Ltac variable.
- A list {- n1 ... nm} of occurrences not to be affected by the tactic.

### Example

Note that, in this goal, it behaves like set  $x := \{1 \ 3\}(f \ 2)$ .

- In particular, the switch {+} selects *all* the occurrences. This switch is useful to turn off the default behavior of a tactic which automatically clears some assumptions (see section *Discharge* for instance).
- The switch  $\{-\}$  imposes that *no* occurrences of the term should be affected by the tactic. The tactic: set  $x := \{-\}(f \ 2)$ . leaves the goal unchanged and adds the definition  $x := f \ 2$  to the context. This kind of tactic may be used to take advantage of the power of the matching algorithm in a local definition, instead of copying large terms by hand.

It is important to remember that matching precedes occurrence selection.

## Example

(continues on next page)

(continued from previous page)

Hence, in the following goal, the same tactic fails since there is only one occurrence of the selected term.

## Example

#### **Basic localization**

It is possible to define an abbreviation for a term appearing in the context of a goal thanks to the in tactical.

```
Variant: set ident := term in ident +
```

This variant of set (ssreflect) introduces a defined constant called ident in the context, and folds it in the context entries mentioned on the right hand side of in. The body of ident is the first subterm matching these context entries (taken in the given order).

# Example

(continues on next page)

(continued from previous page)

x + t = 4

```
Variant: set ident := term in ident + *
```

This variant matches *term* and then folds *ident* similarly in all the given context entries but also folds *ident* in the goal.

## Example

Indeed, remember that 4 is just a notation for (S 3).

The use of the in tactical is not limited to the localization of abbreviations: for a complete description of the in tactical, see section *Bookkeeping* and *Localization*.

#### 5.7.4 Basic tactics

A sizable fraction of proof scripts consists of steps that do not "prove" anything new, but instead perform menial bookkeeping tasks such as selecting the names of constants and assumptions or splitting conjuncts. Although they are logically trivial, bookkeeping steps are extremely important because they define the structure of the data-flow of a proof script. This is especially true for reflection-based proofs, which often involve large numbers of constants and assumptions. Good bookkeeping consists in always explicitly declaring (i.e., naming) all new constants and assumptions in the script, and systematically pruning irrelevant constants and assumptions in the context. This is essential in the context of an interactive development environment (IDE), because it facilitates navigating the proof, allowing to instantly "jump back" to the point at which a questionable assumption was added, and to find relevant assumptions by browsing the pruned context. While novice or casual Coq users may find the automatic name selection feature convenient, the usage of such a feature severely undermines the readability and maintainability of proof scripts, much like automatic variable declaration in programming languages. The SSReflect tactics are therefore designed to support precise bookkeeping and to eliminate name generation heuristics. The bookkeeping features of SSReflect are implemented as tacticals (or pseudo-tacticals), shared across most SSReflect tactics, and thus form the foundation of the SSReflect proof language.

#### **Bookkeeping**

During the course of a proof Coq always present the user with a sequent whose general form is:

The goal to be proved appears below the double line; above the line is the context of the sequent, a set of declarations of constants ci, defined constants dj, and facts Fk that can be used to prove the goal (usually, Ti, Tj: Type and Pk: Prop). The various kinds of declarations can come in any order. The top part of the context consists of declarations produced by the Section commands Variable, Let, and Hypothesis. This section context is never affected by the SSReflect tactics: they only operate on the lower part — the proof context. As in the figure above, the goal often decomposes into a series of (universally) quantified variables (xl: Tl), local definitions let ym:= bm in, and assumptions P n ->, and a conclusion C (as in the context, variables, definitions, and assumptions can appear in any order). The conclusion is what actually needs to be proved — the rest of the goal can be seen as a part of the proof context that happens to be "below the line".

However, although they are logically equivalent, there are fundamental differences between constants and facts on the one hand, and variables and assumptions on the others. Constants and facts are *unordered*, but *named* explicitly in the proof text; variables and assumptions are *ordered*, but *unnamed*: the display names of variables may change at any time because of  $\alpha$ -conversion.

Similarly, basic deductive steps such as apply can only operate on the goal because the Gallina terms that control their action (e.g., the type of the lemma used by apply) only provide unnamed bound variables.<sup>299</sup> Since the proof script can only refer directly to the context, it must constantly shift declarations from the goal to the context and conversely in between deductive steps.

In SSReflect these moves are performed by two *tacticals* => and :, so that the bookkeeping required by a deductive step can be directly associated to that step, and that tactics in an SSReflect script correspond to actual logical steps in the proof rather than merely shuffle facts. Still, some isolated bookkeeping is unavoidable, such as naming variables and assumptions at the beginning of a proof. SSReflect provides a specific move tactic for this purpose.

Now move does essentially nothing: it is mostly a placeholder for => and :. The => tactical moves variables, local definitions, and assumptions to the context, while the : tactical moves facts and constants to the goal.

## Example

For example, the proof of  $^{300}$ 

<sup>&</sup>lt;sup>299</sup> Thus scripts that depend on bound variable names, e.g., via intros or with, are inherently fragile.

<sup>&</sup>lt;sup>300</sup> The name subnK reads as "right cancellation rule for nat subtraction".

where move does nothing, but  $=> m n le_m_n$  changes the variables and assumption of the goal in the constants m n : nat and the fact  $le_n_m : n \le m$ , thus exposing the conclusion m - n + n = m.

The: tactical is the converse of =>, indeed it removes facts and constants from the context by turning them into variables and assumptions.

turns back m and  $le_m_n$  into a variable and an assumption, removing them from the proof context, and changing the goal to forall m,  $n \le m - n + n = m$  which can be proved by induction on n using elim: n.

Because they are tacticals, : and => can be combined, as in

```
move: m le_n_m \Rightarrow p le_n_p.
```

simultaneously renames m and le\_m\_n into p and le\_n\_p, respectively, by first turning them into unnamed variables, then turning these variables back into constants and facts.

Furthermore, SSReflect redefines the basic Coq tactics case, elim, and apply so that they can take better advantage of : and =>. In there SSReflect variants, these tactic operate on the first variable or constant of the goal and they do not use or change the proof context. The : tactical is used to operate on an element in the context.

#### Example

For instance the proof of subnK could continue with elim: n. Instead of elim n (note, no colon), this has the advantage of removing n from the context. Better yet, this elim can be combined with previous move and with the branching version of the => tactical (described in *Introduction in the context*), to encapsulate the inductive step in a single command:

(continues on next page)

(continued from previous page)

which breaks down the proof into two subgoals, the second one having in its context  $lt_n_m : S n \le m$  and  $lhn : forall m, n \le m -> m - n + n = m$ .

The : and => tacticals can be explained very simply if one views the goal as a stack of variables and assumptions piled on a conclusion:

- tactic : a b c pushes the context constants a, b, c as goal variables before performing tactic.
- tactic => a b c pops the top three goal variables as context constants a, b, c, after tactic has been performed.

These pushes and pops do not need to balance out as in the examples above, so move:  $m = n_m = p$  would rename m into p, but leave an extra assumption  $n \le p$  in the goal.

Basic tactics like apply and elim can also be used without the ':' tactical: for example we can directly start a proof of subnK by induction on the top variable m with

```
elim=> [|m IHm] n le_n.
```

The general form of the localization tactical in is also best explained in terms of the goal stack:

```
tactic in a H1 H2 *.
```

is basically equivalent to

```
move: a H1 H2; tactic => a H1 H2.
```

with two differences: the in tactical will preserve the body of an if a is a defined constant, and if the \* is omitted it will use a temporary abbreviation to hide the statement of the goal from tactic.

The general form of the in tactical can be used directly with the move, case and elim tactics, so that one can write

instead of

```
elim: n m le_n_m \Rightarrow [|n IHn] m le_n_m.
```

This is quite useful for inductive proofs that involve many facts.

See section *Localization* for the general syntax and presentation of the in tactical.

#### The defective tactics

In this section we briefly present the three basic tactics performing context manipulations and the main backward chaining tool.

#### The move tactic.

#### move

This tactic, in its defective form, behaves like the *hnf* tactic.

## Example

More precisely, the *move* tactic inspects the goal and does nothing (*idtac*) if an introduction step is possible, i.e. if the goal is a product or a let ... in, and performs *hnf* otherwise.

Of course this tactic is most often used in combination with the bookkeeping tacticals (see section Introduction in the context and Discharge). These combinations mostly subsume the intros, generalize, revert, rename, clear and pattern tactics.

## The case tactic

#### case

This tactic performs *primitive case analysis* on (co)inductive types; specifically, it destructs the top variable or assumption of the goal, exposing its constructor(s) and its arguments, as well as setting the value of its type family indices if it belongs to a type family (see section *Type families*).

The SSReflect case tactic has a special behavior on equalities. If the top assumption of the goal is an equality, the case tactic "destructs" it as a set of equalities between the constructor arguments of its left and right hand sides, as per the tactic injection. For example, case changes the goal:

$$(x, y) = (1, 2) \rightarrow G.$$
  
into:  
 $x = 1 \rightarrow y = 2 \rightarrow G.$ 

Note also that the case of SSReflect performs False elimination, even if no branch is generated by this case operation. Hence the tactic case on a goal of the form False -> G will succeed and prove the goal.

#### The elim tactic

#### elim

This tactic performs inductive elimination on inductive types. In its defective form, the tactic performs inductive elimination on a goal whose top assumption has an inductive type.

## Example

#### The apply tactic

# apply term?

This is the main backward chaining tactic of the proof system. It takes as argument any *term* and applies it to the goal. Assumptions in the type of *term* that don't directly match the goal may generate one or more subgoals.

In its defective form, this tactic is a synonym for:

```
intro top; first [refine top | refine (top _) | refine (top _ _) | ...]; clear top.
```

where top is a fresh name, and the sequence of *refine* tactics tries to catch the appropriate number of wildcards to be inserted. Note that this use of the *refine* tactic implies that the tactic tries to match the goal up to expansion of constants and evaluation of subterms.

apply (ssreflect) has a special behavior on goals containing existential metavariables of sort Prop.

## Example

(continued from previous page)

```
(shelved: 2)
      y : nat
      y_gt1: 1 < y
      y_1t2 : y < 2
      y < 3
    subgoal 2 is:
     forall Hyp0 : y < 3, 0 < proj1_sig (exist (fun n : nat => n < 3) y Hyp0)
by apply: lt_trans y_lt2 _.
    1 focused subgoal
    (shelved: 1)
      y : nat
      y_gt1: 1 < y
      y_1t2 : y < 2
      forall Hyp0 : y < 3, 0 < proj1_sig (exist (fun n : nat => n < 3) y Hyp0)
by move=> y_lt3; apply: lt_trans y_gt1.
    No more subgoals.
```

Note that the last  $\_$  of the tactic apply: (ex\_intro  $\_$  (exist  $\_$  y  $\_$ )) represents a proof that y < 3. Instead of generating the goal:

```
0 < proj1\_sig (exist (fun n : nat => n < 3) y ?Goal).
```

the system tries to prove y < 3 calling the trivial tactic. If it succeeds, let's say because the context contains H : y < 3, then the system generates the following goal:

```
0 < proj1\_sig (exist (fun n => n < 3) y H).
```

Otherwise the missing proof is considered to be irrelevant, and is thus discharged generating the two goals shown above.

Last, the user can replace the trivial tactic by defining an Ltac expression named ssrautoprop.

## **Discharge**

The general syntax of the discharging tactical: is:

```
tactic ident ? : d_item + clear_switch ?
d_item ::= occ_switch clear_switch ? term
clear_switch ::= { ident + }
```

with the following requirements:

• tactic must be one of the four basic tactics described in *The defective tactics*, i.e., move, case, elim or apply, the exact tactic (section *Terminators*), the congr tactic (section *Congruence*), or the application of the *view* tactical '/' (section *Interpreting assumptions*) to one of move, case, or elim.

- The optional *ident* specifies *equation generation* (section *Generation of equations*), and is only allowed if tactic is move, case or elim, or the application of the view tactical '/' (section *Interpreting assumptions*) to case or elim.
- An occ\_switch selects occurrences of term, as in Abbreviations; occ\_switch is not allowed if tactic
  is apply or exact.
- A clear item *clear\_switch* specifies facts and constants to be deleted from the proof context (as per the clear tactic).

The : tactical first discharges all the  $d\_item$ , right to left, and then performs tactic, i.e., for each  $d\_item$ , starting with the last one :

- 1. The SSReflect matching algorithm described in section *Abbreviations* is used to find occurrences of term in the goal, after filling any holes '\_' in term; however if tactic is apply or exact a different matching algorithm, described below, is used<sup>301</sup>.
- 2. These occurrences are replaced by a new variable; in particular, if term is a fact, this adds an assumption to the goal.
- 3. If term is exactly the name of a constant or fact in the proof context, it is deleted from the context, unless there is an occ\_switch.

Finally, tactic is performed just after the first d\_item has been generalized — that is, between steps 2 and 3. The names listed in the final clear\_switch (if it is present) are cleared first, before d\_item n is discharged.

Switches affect the discharging of a  $d_item$  as follows:

- An occ\_switch restricts generalization (step 2) to a specific subset of the occurrences of term, as per section Abbreviations, and prevents clearing (step 3).
- All the names specified by a *clear\_switch* are deleted from the context in step 3, possibly in addition to term.

For example, the tactic:

```
move: n {2}n (refl_equal n).
```

- first generalizes (refl\_equal n : n = n);
- then generalizes the second occurrence of n.
- finally generalizes all the other occurrences of n, and clears n from the proof context (assuming n is a proof constant).

Therefore this tactic changes any goal G into

```
forall n n0 : nat, n = n0 \rightarrow G.
```

where the name n0 is picked by the Coq display function, and assuming n appeared only in G.

Finally, note that a discharge operation generalizes defined constants as variables, and not as local definitions. To override this behavior, prefix the name of the local definition with a Q, like in move: Qn.

This is in contrast with the behavior of the in tactical (see section *Localization*), which preserves local definitions by default.

 $<sup>^{301}</sup>$  Also, a slightly different variant may be used for the first  $d\_item$  of case and elim; see section Type families.

#### Clear rules

The clear step will fail if term is a proof constant that appears in other facts; in that case either the facts should be cleared explicitly with a <code>clear\_switch</code>, or the clear step should be disabled. The latter can be done by adding an <code>occ\_switch</code> or simply by putting parentheses around term: both <code>move</code>: (n). and <code>move</code>: {+}n. generalize n without clearing n from the proof context.

The clear step will also fail if the *clear\_switch* contains a *ident* that is not in the *proof* context. Note that SSReflect never clears a section constant.

If tactic is move or case and an equation *ident* is given, then clear (step 3) for *d\_item* is suppressed (see section *Generation of equations*).

Intro patterns (see section *Introduction in the context*) and the rewrite tactic (see section *Rewriting*) let one place a *clear\_switch* in the middle of other items (namely identifiers, views and rewrite rules). This can trigger the addition of proof context items to the ones being explicitly cleared, and in turn this can result in clear errors (e.g. if the context item automatically added occurs in the goal). The relevant sections describe ways to avoid the unintended clear of context items.

#### Matching for apply and exact

The matching algorithm for  $d\_item$  of the SSReflect apply and exact tactics exploits the type of the first  $d\_item$  to interpret wildcards in the other  $d\_item$  and to determine which occurrences of these should be generalized. Therefore, occur switches are not needed for apply and exact.

Indeed, the SSReflect tactic apply: H x is equivalent to refine (@H \_ ... \_ x); clear H x with an appropriate number of wildcards between H and x.

Note that this means that matching for apply and exact has much more context to interpret wildcards; in particular it can accommodate the  $\_d_item$ , which would always be rejected after move:.

## Example

This tactic is equivalent (see section *Bookkeeping*) to: refine (trans\_equal (Hfg \_) \_). and this is a common idiom for applying transitivity on the left hand side of an equation.

#### The abstract tactic



This tactic assigns an abstract constant previously introduced with the [: ident] intro pattern (see section Introduction in the context).

In a goal like the following:

```
m : nat
abs : <hidden>
n : nat
==========
m < 5 + n</pre>
```

The tactic abstract: abs n first generalizes the goal with respect to n (that is not visible to the abstract constant abs) and then assigns abs. The resulting goal is:

Once this subgoal is closed, all other goals having abs in their context see the type assigned to abs. In this case:

```
m : nat
abs : forall n, m < 5 + n
```

For a more detailed example the reader should refer to section *Structure*.

#### Introduction in the context

The application of a tactic to a given goal can generate (quantified) variables, assumptions, or definitions, which the user may want to *introduce* as new facts, constants or defined constants, respectively. If the tactic splits the goal into several subgoals, each of them may require the introduction of different constants and facts. Furthermore it is very common to immediately decompose or rewrite with an assumption instead of adding it to the context, as the goal can often be simplified and even proved after this.

All these operations are performed by the introduction tactical =>, whose general syntax is

```
tactic => i_item +

i_item ::= i_pattern s_item clear_switch i_view i_block

s_item ::= /= // //=

i_view ::= {} /term /ltac:( tactic )

i_pattern ::= ident > _ ? * + occ_switch -> <- [i_item]] - [: ident occ_switch]

i_block ::= [^ ident] [^~ ident num]</pre>
```

The => tactical first executes tactic, then the *i\_items*, left to right. An *s\_item* specifies a simplification operation; a *clear\_switch* specifies context pruning as in *Discharge*. The *i\_patterns* can be seen as a variant of *intro patterns* (see *intros*:) each performs an introduction operation, i.e., pops some variables or assumptions from the goal.

#### Simplification items

An s\_item can simplify the set of subgoals or the subgoals themselves:

- // removes all the "trivial" subgoals that can be resolved by the SSReflect tactic *done* described in *Terminators*, i.e., it executes try done.
- /= simplifies the goal by performing partial evaluation, as per the tactic  $simpl^{302}$ .
- //= combines both kinds of simplification; it is equivalent to /= //, i.e., simpl; try done.

When an s\_item immediately precedes a clear\_switch, then the clear\_switch is executed after the s\_item, e.g., {IHn}// will solve some subgoals, possibly using the fact IHn, and will erase IHn from the context of the remaining subgoals.

#### **Views**

The first entry in the  $i\_view$  grammar rule, /term, represents a view (see section Views and reflection). It interprets the top of the stack with the view term. It is equivalent to move/term.

A clear\_switch that immediately precedes an  $i\_view$  is complemented with the name of the view if an only if the  $i\_view$  is a simple proof context entry<sup>307</sup>. E.g. {}/v is equivalent to  $/v\{v\}$ . This behavior can be avoided by separating the clear\_switch from the  $i\_view$  with the - intro pattern or by putting parentheses around the view.

A clear\_switch that immediately precedes an i\_view is executed after the view application.

If the next  $i\_item$  is a view, then the view is applied to the assumption in top position once all the previous  $i\_item$  have been performed.

The second entry in the  $i\_view$  grammar rule, /ltac:( tactic ), executes tactic. Notations can be used to name tactics, for example

```
Notation "'myop'" := (ltac:(my ltac code)) : ssripat_scope.
```

lets one write just /myop in the intro pattern. Note the scope annotation: views are interpreted opening the ssripat scope.

#### Intro patterns

SSReflect supports the following  $i_patterns$ :

ident pops the top variable, assumption, or local definition into a new constant, fact, or defined constant ident, respectively. Note that defined constants cannot be introduced when δ-expansion is required to expose the top variable or assumption. A clear\_switch (even an empty one) immediately preceding an ident is complemented with that ident if and only if the identifier is a simple proof context entry. As a consequence by prefixing the ident with {} one can replace a context entry. This behavior can be avoided by separating the clear\_switch from the ident with the - intro pattern.

 $<sup>^{302}</sup>$  Except /= does not expand the local definitions created by the SSR eflect in tactical.

 $<sup>^{307}</sup>$  A simple proof context entry is a naked identifier (i.e. not between parentheses) designating a context entry that is not a section variable.

> pops every variable occurring in the rest of the stack. Type class instances are popped even if they don't occur in the rest of the stack. The tactic move=> > is equivalent to move=> ? ? on a goal such as:

```
forall x y, x < y \rightarrow G
```

A typical use if move=>> H to name H the first assumption, in the example above x < y.

- ? pops the top variable into an anonymous constant or fact, whose name is picked by the tactic interpreter. SSReflect only generates names that cannot appear later in the user script<sup>303</sup>.
- \_ pops the top variable into an anonymous constant that will be deleted from the proof context of all the subgoals produced by the => tactical. They should thus never be displayed, except in an error message if the constant is still actually used in the goal or context after the last i\_item has been executed (s\_item can erase goals or terms where the constant appears).
- \* pops all the remaining apparent variables/assumptions as anonymous constants/facts. Unlike? and move the \* i\_item does not expand definitions in the goal to expose quantifiers, so it may be useful to repeat a move=> \* tactic, e.g., on the goal:

```
forall a b : bool, a <> b
```

a first move=> \* adds only a: bool and b: bool to the context; it takes a second move=> \* to add Hyp: a = b.

+ temporarily introduces the top variable. It is discharged at the end of the intro pattern. For example move=> + y on a goal:

```
forall x y, P
```

is equivalent to move=> \_x\_ y; move: \_x\_ that results in the goal:

forall x. P

- occ\_switch | -> (resp. occ\_switch <-) pops the top assumption (which should be a rewritable proposition) into an anonymous fact, rewrites (resp. rewrites right to left) the goal with this fact (using the SSReflect rewrite tactic described in section Rewriting, and honoring the optional occurrence selector), and finally deletes the anonymous fact from the context.
- [ i\_item \* | ... | i\_item \* ] when it is the very first i\_pattern after tactic => tactical and tactic is not a move, is a branchingi\_pattern. It executes the sequence i\_item; on the i-th subgoal produced by tactic. The execution of tactic should thus generate exactly m subgoals, unless the [...] i\_pattern comes after an initial // or //= s\_item that closes some of the goals produced by tactic, in which case exactly m subgoals should remain after the s\_item, or we have the trivial branching i\_pattern [], which always does nothing, regardless of the number of remaining subgoals.
- [ i\_item \* | ... | i\_item \* ] when it is not the first i\_pattern or when tactic is a move, is a destructing i\_pattern. It starts by destructing the top variable, using the SSReflect case tactic described in The defective tactics. It then behaves as the corresponding branching i\_pattern, executing the sequence i\_item\_i in the i-th subgoal generated by the case analysis; unless we have the trivial destructing i\_pattern [], the latter should generate exactly m subgoals, i.e., the top variable should have an inductive type with exactly m constructors 304. While it is good style to use the i\_item i \* to pop the variables and assumptions corresponding to each constructor, this is not enforced by SSReflect.
- does nothing, but counts as an intro pattern. It can also be used to force the interpretation of [ i\_item \* ]
   | ... | i\_item \* ] as a case analysis like in move=> -[H1 H2]. It can also be used to indicate explicitly the link between a view and a name like in move=> /eqP-H1. Last, it can serve as a separator between

<sup>&</sup>lt;sup>303</sup> SSReflect reserves all identifiers of the form " x ", which is used for such generated names.

 $<sup>^{304}</sup>$  More precisely, it should have a quantified inductive type with a assumptions and m - a constructors.

views. Section *Views and reflection*<sup>306</sup> explains in which respect the tactic move=> /v1/v2 differs from the tactic move=> /v1-/v2.

[: ident ...] introduces in the context an abstract constant for each ident. Its type has to be fixed later on by using the abstract tactic. Before then the type displayed is <hidden>.

Note that SSReflect does not support the syntax (ipat, ..., ipat) for destructing intro patterns.

#### Clear switch

Clears are deferred until the end of the intro pattern.

## Example

If the cleared names are reused in the same intro pattern, a renaming is performed behind the scenes.

Facts mentioned in a clear switch must be valid names in the proof context (excluding the section context).

## Branching and destructuring

The rules for interpreting branching and destructing  $i\_pattern$  are motivated by the fact that it would be pointless to have a branching pattern if tactic is a move, and in most of the remaining cases tactic is case or elim, which implies destruction. The rules above imply that:

```
• move=> [a b].
```

- case=> [a b].
- case=> a b.

are all equivalent, so which one to use is a matter of style; move should be used for casual decomposition, such as splitting a pair, and case should be used for actual decompositions, in particular for type families (see *Type families*) and proof by contradiction.

The trivial branching *i\_pattern* can be used to force the branching interpretation, e.g.:

```
• case=> [] [a b] c.
```

- move=> [[a b] c].
- case; case=> a b c.

are all equivalent.

<sup>&</sup>lt;sup>306</sup> The current state of the proof shall be displayed by the Show Proof command of Coq proof mode.

#### **Block introduction**

SSReflect supports the following  $i_blocks$ :

[^ ident ] block destructing i\_pattern. It performs a case analysis on the top variable and introduces, in one go, all the variables coming from the case analysis. The names of these variables are obtained by taking the names used in the inductive type declaration and prefixing them with ident. If the intro pattern immediately follows a call to elim with a custom eliminator (see Interpreting eliminations) then the names are taken from the ones used in the type of the eliminator.

# Example

```
Record r := \{ a : nat; b := (a, 3); _ : bool; \}.
   r is defined
   a is defined
   b is defined
Lemma test : r -> True.
   1 subgoal
     _____
     r -> True
Proof.
move \Rightarrow [^ x ].
   1 subgoal
     xa : nat
     xb := (xa, 3) : nat * nat
     _x?_: bool
     _____
     True
```

[~~ ident ] block destructing using ident as a suffix.

[~ num ] block destructing using num as a suffix.

Only a s\_item is allowed between the elimination tactic and the block destructing.

# Generation of equations

The generation of named equations option stores the definition of a new constant as an equation. The tactic:

```
move En: (size 1) \Rightarrow n.
```

where 1 is a list, replaces size 1 by n in the goal and adds the fact En : size 1 = n to the context. This is quite different from:

```
pose n := (size 1).
```

which generates a definition n := (size 1). It is not possible to generalize or rewrite such a definition; on the other hand, it is automatically expanded during computation, whereas expanding the equation En requires explicit rewriting.

The use of this equation name generation option with a case or an elim tactic changes the status of the first *i\_item*, in order to deal with the possible parameters of the constants introduced.

## Example

If the user does not provide a branching  $i\_item$  as first  $i\_item$ , or if the  $i\_item$  does not provide enough names for the arguments of a constructor, then the constants generated are introduced under fresh SSReflect names.

# Example

```
1 subgoal
    a, b : nat
    _____
    a <> b
case E : a \Rightarrow H.
  2 subgoals
    a, b : nat
    E : a = 0
    H : O = b
    _____
    False
  subgoal 2 is:
   False
Show 2.
  subgoal 2 is:
    a, b, _n_ : nat
    E : a = S _n_
    H : S _n_ = b
    _____
    False
```

Combining the generation of named equations mechanism with the case tactic strengthens the power of a

case analysis. On the other hand, when combined with the <code>elim</code> tactic, this feature is mostly useful for debug purposes, to trace the values of decomposed parameters and pinpoint failing branches.

## Type families

When the top assumption of a goal has an inductive type, two specific operations are possible: the case analysis performed by the *case* tactic, and the application of an induction principle, performed by the *elim* tactic. When this top assumption has an inductive type, which is moreover an instance of a type family, Coq may need help from the user to specify which occurrences of the parameters of the type should be substituted.

```
Variant: case: d_item + / d_item + Variant: elim: d_item + / d_item +
```

A specific / switch indicates the type family parameters of the type of a  $d\_item$  immediately following this / switch. The  $d\_item$  on the right side of the / switch are discharged as described in section *Discharge*. The case analysis or elimination will be done on the type of the top assumption after these discharge operations.

Every  $d_item$  preceding the / is interpreted as arguments of this type, which should be an instance of an inductive type family. These terms are not actually generalized, but rather selected for substitution. Occurrence switches can be used to restrict the substitution. If a term is left completely implicit (e.g. writing just \_), then a pattern is inferred looking at the type of the top assumption. This allows for the compact syntax:

```
case: \{2\}_{\_} / eqP.
```

where  $\underline{\ }$  is interpreted as ( $\underline{\ }$  ==  $\underline{\ }$ ) since eqP T a b : reflect (a = b) (a == b) and reflect is a type family with one index.

Moreover if the d\_item list is too short, it is padded with an initial sequence of \_ of the right length.

## Example

Here is a small example on lists. We define first a function which adds an element at the end of a given list.

```
Require Import List.
Section LastCases.
Variable A : Type.
   A is declared

Implicit Type 1 : list A.
Fixpoint add_last a 1 : list A :=
   match 1 with
   | nil => a :: nil
   | hd :: t1 => hd :: (add_last a t1) end.
   add_last is defined
   add_last is recursively defined (decreasing on 2nd argument)
```

Then we define an inductive predicate for case analysis on lists according to their last element:

(continues on next page)

```
(continued from previous page)
   last_spec_rect is defined
   last_spec_ind is defined
   last_spec_rec is defined
   last_spec_sind is defined
Theorem lastP : forall 1 : list A, last_spec 1.
   1 subgoal
     A : Type
     _____
     forall 1 : list A, last_spec 1
Admitted.
   lastP is declared
We are now ready to use lastP in conjunction with case.
Lemma test 1 : (length 1) * 2 = length (1 ++ 1).
   1 subgoal
     A : Type
     1 : list A
     _____
     length 1 * 2 = length (1 ++ 1)
case: (lastP 1).
   2 subgoals
     A : Type
     1 : list A
     _____
     length nil * 2 = length (nil ++ nil)
    subgoal 2 is:
    forall (s : list A) (x : A),
    length (add_last x s) * 2 = length (add_last x s ++ add_last x s)
Applied to the same goal, the tactc case: 1 / (lastP 1) generates the same subgoals but 1 has been
cleared from both contexts:
case: 1 / (lastP 1).
   2 subgoals
     A : Type
     length nil * 2 = length (nil ++ nil)
    subgoal 2 is:
    forall (s : list A) (x : A),
    length (add_last x s) * 2 = length (add_last x s ++ add_last x s)
Again applied to the same goal:
case: {1 3}1 / (lastP 1).
   2 subgoals
     A : Type
```

(continues on next page)

(continued from previous page)

Note that selected occurrences on the left of the / switch have been substituted with l instead of being affected by the case analysis.

The equation name generation feature combined with a type family / switch generates an equation for the first dependent  $d_item$  specified by the user. Again starting with the above goal, the command:

#### Example

```
Lemma test 1 : (length 1) * 2 = length (1 ++ 1).
   1 subgoal
     A : Type
     1 : list A
     length 1 * 2 = length (1 ++ 1)
case E: \{1\ 3\}1\ /\ (lastP\ 1) \Rightarrow [|s\ x].
   2 subgoals
     A : Type
     1 : list A
     E : 1 = nil
     _____
     length nil * 2 = length (1 ++ nil)
   subgoal 2 is:
    length (add_last x s) * 2 = length (1 ++ add_last x s)
Show 2.
   subgoal 2 is:
     A : Type
     1, s : list A
     x : A
     E : 1 = add_last x s
     _____
     length (add_last x s) * 2 = length (1 ++ add_last x s)
```

There must be at least one  $d\_item$  to the left of the / switch; this prevents any confusion with the view feature. However, the  $d\_item$  to the right of the / are optional, and if they are omitted the first assumption provides the instance of the type family.

The equation always refers to the first  $d_item$  in the actual tactic call, before any padding with initial \_. Thus, if an inductive type has two family parameters, it is possible to have SSReflect generate an equation for the second one by omitting the pattern for the first; note however that this will fail if the type of the second parameter depends on the value of the first parameter.

## 5.7.5 Control flow

#### Indentation and bullets

A linear development of Coq scripts gives little information on the structure of the proof. In addition, replaying a proof after some changes in the statement to be proved will usually not display information to distinguish between the various branches of case analysis for instance.

To help the user in this organization of the proof script at development time, SSReflect provides some bullets to highlight the structure of branching proofs. The available bullets are -, + and \*. Combined with tabulation, this lets us highlight four nested levels of branching; the most we have ever needed is three. Indeed, the use of "simpl and closing" switches, of terminators (see above section *Terminators*) and selectors (see section *Selectors*) is powerful enough to avoid most of the time more than two levels of indentation.

Here is a fragment of such a structured script:

```
case E1: (abezoutn _ _) => [[| k1] [| k2]].
- rewrite !muln0 !gexpn0 mulg1 => H1.
  move/eqP: (sym_equal F0); rewrite -H1 orderg1 eqn_mul1.
  by case/andP; move/eqP.
- rewrite muln0 gexpn0 mulg1 => H1.
  have F1: t %| t * S k2.+1 - 1.
    apply: (@dvdn_trans (orderg x)); first by rewrite F0; exact: dvdn_mull.
    rewrite orderg_dvd; apply/eqP; apply: (mulgI x).
    rewrite -{1}(gexpn1 x) mulg1 gexpn_add leq_add_sub //.
    by move: P1; case t.
  rewrite dvdn_subr in F1; last by exact: dvdn_mulr.
  + rewrite H1 F0 -{2}(muln1 (p ^ 1)); congr (_ * _).
    by apply/eqP; rewrite -dvdn1.
  + by move: P1; case: (t) => [| [| s1]].
- rewrite muln0 gexpn0 mul1g => H1.
...
```

#### **Terminators**

To further structure scripts, SSReflect supplies *terminating* tacticals to explicitly close off tactics. When replaying scripts, we then have the nice property that an error immediately occurs when a closed tactic fails to prove its subgoal.

It is hence recommended practice that the proof of any subgoal should end with a tactic which fails if it does not solve the current goal, like discriminate, contradiction or assumption.

In fact, SSReflect provides a generic tactical which turns any tactic into a closing one (similar to now). Its general syntax is:

#### by tactic

```
The Ltac expression by [tactic | tactic | ...] is equivalent to do [done | by tactic | by tactic | ...], which corresponds to the standard Ltac expression first [done | tactic; done | tactic; done | ...].
```

In the script provided as example in section *Indentation and bullets*, the paragraph corresponding to each sub-case ends with a tactic line prefixed with a by, like in:

```
by apply/eqP; rewrite -dvdn1.
```

#### done

The by tactical is implemented using the user-defined, and extensible done tactic. This done tactic

tries to solve the current goal by some trivial means and fails if it doesn't succeed. Indeed, the tactic expression by tactic is equivalent to tactic; done.

Conversely, the tactic by [ ] is equivalent to done.

The default implementation of the done tactic, in the ssreflect.v file, is:

The lemma not\_locked\_false\_eq\_true is needed to discriminate locked boolean predicates (see section Locking, unlocking). The iterator tactical do is presented in section Iteration. This tactic can be customized by the user, for instance to include an auto tactic.

A natural and common way of closing a goal is to apply a lemma which is the exact one needed for the goal to be solved. The defective form of the tactic:

exact.

is equivalent to:

```
do [done | by move=> top; apply top].
```

where top is a fresh name assigned to the top assumption of the goal. This applied form is supported by the : discharge tactical, and the tactic:

```
exact: MyLemma. is equivalent to:
```

```
by apply: MyLemma.
```

(see section *Discharge* for the documentation of the apply: combination).

Warning: The list of tactics (possibly chained by semicolons) that follows the by keyword is considered to be a parenthesized block applied to the current goal. Hence for example if the tactic:

```
by rewrite my_lemma1.
succeeds, then the tactic:
by rewrite my_lemma1; apply my_lemma2.
usually fails since it is equivalent to:
by (rewrite my_lemma1; apply my_lemma2).
```

#### **Selectors**

# last first

When composing tactics, the two tacticals first and last let the user restrict the application of a tactic to only one of the subgoals generated by the previous tactic. This covers the frequent cases where a tactic generates two subgoals one of which can be easily disposed of.

This is another powerful way of linearization of scripts, since it happens very often that a trivial subgoal can be solved in a less than one line tactic. For instance, tactic; last by tactic tries to solve the last subgoal generated by the first tactic using the given second tactic, and fails if it does not succeed. Its analogue tactic; first by tactic tries to solve the first subgoal generated by the first tactic using the second given tactic, and fails if it does not succeed.

SSReflect also offers an extension of this facility, by supplying tactics to *permute* the subgoals generated by a tactic.

# Variant: last first Variant: first last

These two equivalent tactics invert the order of the subgoals in focus.

```
Variant: last num first
```

If num's value is k, this tactic rotates the n subgoals  $G_1$ , ...,  $G_n$  in focus. The first subgoal becomes  $G_{n+1-k}$  and the circular order of subgoals remains unchanged.

```
first num last
```

If num's value is k, this tactic rotates the n subgoals  $G_1$ , ...,  $G_n$  in focus. The first subgoal becomes  $G_k$  and the circular order of subgoals remains unchanged.

Finally, the tactics last and first combine with the branching syntax of Ltac: if the tactic generates n subgoals on a given goal, then the tactic

```
tactic; last k [ tactic1 |...| tacticm ] || tacticn.
```

where natural denotes the integer k as above, applies tactic 1 to the n-k+1-th goal, ... tacticm to the n-k+2-th goal and tactic to the others.

## Example

Here is a small example on lists. We define first a function which adds an element at the end of a given list.

```
Inductive test : nat -> Prop :=
\mid C1 n of n = 1 : test n
\mid C2 n of n = 2 : test n
\mid C3 n of n = 3 : test n
\mid C4 n of n = 4 : test n.
   test is defined
   test_ind is defined
   test_sind is defined
Lemma example n (t : test n) : True.
   1 subgoal
     n : nat
     t : test n
     _____
     True
case: t; last 2 [move=> k| move=> 1]; idtac.
   4 subgoals
     n : nat
     _____
     forall n0 : nat, n0 = 1 -> True
   subgoal 2 is:
```

```
k = 2 -> True
subgoal 3 is:
l = 3 -> True
subgoal 4 is:
forall n0 : nat, n0 = 4 -> True
```

### **Iteration**



This tactical offers an accurate control on the repetition of tactics. mult is a multiplier.

Brackets can only be omitted if a single tactic is given and a multiplier is present.

A tactic of the form:

```
do [ tactic 1 | ... | tactic n ].
```

is equivalent to the standard Ltac expression:

```
first [ tactic 1 | ... | tactic n ].
```

The optional multiplier mult specifies how many times the action of tactic should be repeated on the current subgoal.

There are four kinds of multipliers:

```
mult ::= num ! ! num ? ?
```

Their meaning is:

- n! the step tactic is repeated exactly n times (where n is a positive integer argument).
- ! the step tactic is repeated as many times as possible, and done at least once.
- ? the step tactic is repeated as many times as possible, optionally.
- n? the step tactic is repeated up to n times, optionally.

For instance, the tactic:

```
tactic; do 1? rewrite mult_comm.
```

rewrites at most one time the lemma mult\_comm in all the subgoals generated by tactic, whereas the tactic:

```
tactic; do 2! rewrite mult_comm.
```

rewrites exactly two times the lemma mult\_comm in all the subgoals generated by tactic, and fails if this rewrite is not possible in some subgoal.

Note that the combination of multipliers and rewrite is so often used that multipliers are in fact integrated to the syntax of the SSReflect rewrite tactic, see section *Rewriting*.

#### Localization

In sections *Basic localization* and *Bookkeeping*, we have already presented the *localization* tactical in, whose general syntax is:

```
tactic in ident + ?
```

where *ident* is a name in the context. On the left side of in, tactic can be move, case, elim, rewrite, set, or any tactic formed with the general iteration tactical do (see section *Iteration*).

The operation described by tactic is performed in the facts listed after in and in the goal if a \* ends the list of names.

The in tactical successively:

- generalizes the selected hypotheses, possibly "protecting" the goal if \* is not present,
- performs tactic, on the obtained goal,
- reintroduces the generalized facts, under the same names.

This defective form of the do tactical is useful to avoid clashes between standard Ltac in and the SSReflect tactical in.

#### Example

the last tactic rewrites the hypothesis H2: y = 3 both in H1: x = y and in the goal x + y = 6.

By default in keeps the body of local definitions. To erase the body of a local definition during the generalization phase, the name of the local definition must be written between parentheses, like in rewrite H in H1 (def\_n) H2.

This is the most general form of the in tactical. In its simplest form the last option lets one rename hypotheses that can't be cleared (like section variables). For example, (y := x) generalizes over x and reintroduces the generalized variable under the name y (and does not clear x). For a more precise description of this form of localization refer to  $Advanced\ generalization$ .

#### Structure

Forward reasoning structures the script by explicitly specifying some assumptions to be added to the proof context. It is closely associated with the declarative style of proof, since an extensive use of these highlighted statements make the script closer to a (very detailed) textbook proof.

Forward chaining tactics allow to state an intermediate lemma and start a piece of script dedicated to the proof of this statement. The use of closing tactics (see section *Terminators*) and of indentation makes syntactically explicit the portion of the script building the proof of the intermediate statement.

#### The have tactic.

#### have : term

This is the main SSReflect forward reasoning tactic. It can be used in two modes: one starts a new (sub)proof for an intermediate result in the main proof, and the other provides explicitly a proof term for this intermediate step.

This tactic supports open syntax for term. Applied to a goal G, it generates a first subgoal requiring a proof of term in the context of G. The second generated subgoal is of the form  $term \rightarrow G$ , where term becomes the new top assumption, instead of being introduced with a fresh name. At the proof-term level, the have tactic creates a  $\beta$  redex, and introduces the lemma under a fresh name, automatically chosen

Like in the case of the pose (ssreflect) tactic (see section *Definitions*), the types of the holes are abstracted in term.

### Example


```
Lemma test : True.
   1 subgoal
     _____
have: _{-} * 0 = 0.
   2 subgoals
     _____
     forall n : nat, n * 0 = 0
   subgoal 2 is:
    (forall n : nat, n * 0 = 0) -> True
The invocation of have is equivalent to:
have: forall n : nat, n * 0 = 0.
   2 subgoals
     _____
     forall n : nat, n * 0 = 0
   subgoal 2 is:
    (forall n : nat, n * 0 = 0) -> True
```

The have tactic also enjoys the same abstraction mechanism as the pose tactic for the non-inferred implicit arguments. For instance, the tactic:

## Example

opens a new subgoal where the type of x is quantified.

The behavior of the defective have tactic makes it possible to generalize it in the following general construction:



Open syntax is supported for both term. For the description of  $i\_item$  and  $s\_item$  see section Introduction in the context. The first mode of the have tactic, which opens a sub-proof for an intermediate result, uses tactics of the form:

```
Variant: have clear_switch i_item : term by tactic which behave like:
```

```
have: term ; first by tactic.
move=> clear_switch i_item.
```

Note that the *clear\_switch precedes* the *i\_item*, which allows to reuse a name of the context, possibly used by the proof of the assumption, to introduce the new assumption itself.

The by feature is especially convenient when the proof script of the statement is very short, basically when it fits in one line like in:

```
have H23 : 3 + 2 = 2 + 3 by rewrite addnC.
```

The possibility of using  $i\_item$  supplies a very concise syntax for the further use of the intermediate step. For instance,

#### Example

```
forall x : nat, x * a = a

subgoal 2 is:
a - 1 = a
```

Note how the second goal was rewritten using the stated equality. Also note that in this last subgoal, the intermediate result does not appear in the context.

Thanks to the deferred execution of clears, the following idiom is also supported (assuming x occurs in the goal only):

```
have \{x\} \rightarrow x = y.
```

Another frequent use of the intro patterns combined with have is the destruction of existential assumptions like in the tactic:

## Example

An alternative use of the have tactic is to provide the explicit proof term for the intermediate lemma, using tactics of the form:

```
Variant: have ident := term
```

This tactic creates a new assumption of type the type of *term*. If the optional *ident* is present, this assumption is introduced under the name *ident*. Note that the body of the constant is lost for the user.

Again, non inferred implicit arguments and explicit holes are abstracted.

## Example

```
Lemma test : True.

1 subgoal

-----
True
```

```
have H := forall x, (x, x) = (x, x).

1 subgoal

H : Type -> Prop

------
True
```

adds to the context H: Type -> Prop. This is a schematic example but the feature is specially useful when the proof term to give involves for instance a lemma with some hidden implicit arguments.

After the  $i_pattern$ , a list of binders is allowed.

#### Example

A proof term provided after := can mention these bound variables (that are automatically introduced with the given names). Since the  $i\_pattern$  can be omitted, to avoid ambiguity, bound variables can be surrounded with parentheses even if no type is specified:

The *i\_item* and *s\_item* can be used to interpret the asserted hypothesis with views (see section *Views and reflection*) or simplify the resulting goals.

The *have* tactic also supports a **suff** modifier which allows for asserting that a given statement implies the current goal without copying the goal itself.

#### Example

```
subgoal 2 is:
  2 + 2 = 3 -> True
```

Note that H is introduced in the second goal.

The suff modifier is not compatible with the presence of a list of binders.

### Generating let in context entries with have

Since SSReflect 1.5 the *have* tactic supports a "transparent" modifier to generate let in context entries: the @ symbol in front of the context entry name.

### Example

```
Inductive Ord n := Sub \times of \times < n.
    Ord is defined
    Ord_rect is defined
    Ord_ind is defined
    Ord_rec is defined
    Ord_sind is defined
Notation "'I_n" := (Ord n) (at level 8, n at level 2, format "''I_n").
Arguments Sub {_} _ _.
Lemma test n m (H : m + 1 < n) : True.
    1 subgoal
      n, m : nat
      H : m + 1 < n
      _____
      True
have @i : 'I_n by apply: (Sub m); omega.
    1 subgoal
      n, m : nat
      H : m + 1 < n
      i := Sub m
              (\texttt{Decidable.dec\_not\_not} \ (\texttt{m} \ < \ \texttt{n}) \ (\texttt{dec\_lt} \ \texttt{m} \ \texttt{n}) \ (\texttt{fun} \ \dots \ \Rightarrow \ \dots \ \dots))
       : 'I_n
      _____
      True
```

Note that the subterm produced by <code>omega</code> is in general huge and uninteresting, and hence one may want to hide it. For this purpose the <code>[: name ]</code> intro pattern and the tactic <code>abstract</code> (see <code>The abstract tactic</code>) are provided.

#### Example

```
Lemma test n m (H : m + 1 < n) : True.  \label{eq:lemma} 1 \text{ subgoal}  n, m : nat
```

The type of pm can be cleaned up by its annotation (\*1\*) by just simplifying it. The annotations are there for technical reasons only.

When intro patterns for abstract constants are used in conjunction with have and an explicit term, they must be used as follows:

## Example

```
Lemma test n m (H : m + 1 < n) : True.
   1 subgoal
     n, m : nat
     H : m + 1 < n
     True
have [:pm] @i : 'I_n := Sub m pm.
   2 subgoals
     n, m : nat
     H : m + 1 < n
     _____
     sm <= n
   subgoal 2 is:
    True
by omega.
   1 subgoal
     n, m : nat
     H : m + 1 < n
     pm : S m \le n (*1*)
     i := Sub m pm : 'I_n : 'I_n
     _____
     True
```

In this case the abstract constant pm is assigned by using it in the term that follows := and its corresponding goal is left to be solved. Goals corresponding to intro patterns for abstract constants are opened in the order in which the abstract constants are declared (not in the "order" in which they are used in the term).

Note that abstract constants do respect scopes. Hence, if a variable is declared after their introduction, it has to be properly generalized (i.e. explicitly passed to the abstract constant when one makes use of it).

## Example

Last, notice that the use of intro patterns for abstract constants is orthogonal to the transparent flag @ for have.

### The have tactic and typeclass resolution

Since SSReflect 1.5 the have tactic behaves as follows with respect to typeclass inference.

```
have foo : ty.
2 subgoals

-----
ty

subgoal 2 is:
True
```

Full inference for ty. The first subgoal demands a proof of such instantiated statement.

```
have foo : ty := .
```

No inference for ty. Unresolved instances are quantified in ty. The first subgoal demands a proof of such quantified statement. Note that no proof term follows :=, hence two subgoals are generated.

No inference for ty and t.

No inference for t. Unresolved instances are quantified in the (inferred) type of t and abstracted in t.

#### Flag: SsrHave NoTCResolution

This flag restores the behavior of SSReflect 1.4 and below (never resolve typeclasses).

## Variants: the suff and wlog tactics

As it is often the case in mathematical textbooks, forward reasoning may be used in slightly different variants. One of these variants is to show that the intermediate step L easily implies the initial goal G. By easily we mean here that the proof of L G is shorter than the one of L itself. This kind of reasoning step usually starts with: "It suffices to show that ...".

This is such a frequent way of reasoning that SSReflect has a variant of the have tactic called suffices (whose abridged name is suff). The have and suff tactics are equivalent and have the same syntax but:

- the order of the generated subgoals is inverted
- ullet the optional clear item is still performed in the second branch. This means that the tactic:

```
suff \{H\} H : forall x : nat, x >= 0.
```

fails if the context of the current goal indeed contains an assumption named H.

The rationale of this clearing policy is to make possible "trivial" refinements of an assumption, without changing its name in the main branch of the reasoning.

The have modifier can follow the suff tactic.

## Example

Note that, in contrast with have suff, the name H has been introduced in the first goal.

Another useful construct is reduction, showing that a particular case is in fact general enough to prove a general property. This kind of reasoning step usually starts with: "Without loss of generality, we can suppose that ...". Formally, this corresponds to the proof of a goal G by introducing a cut wlog\_statement -> G. Hence the user shall provide a proof for both (wlog\_statement -> G) -> G and wlog\_statement -> G. However, such cuts are usually rather painful to perform by hand, because the statement wlog\_statement is tedious to write by hand, and sometimes even to read.

SSReflect implements this kind of reasoning step through the  $without\ loss$  tactic, whose short name is wlog. It offers support to describe the shape of the cut statements, by providing the simplifying hypothesis and by pointing at the elements of the initial goals which should be generalized. The general syntax of without loss is:

where each *ident* is a constant in the context of the goal. Open syntax is supported for term.

In its defective form:

```
Variant: wlog: / term
Variant: without loss: / term
```

on a goal G, it creates two subgoals: a first one to prove the formula (term -> G) -> G and a second one to prove the formula term -> G.

If the optional list of *ident* is present on the left side of /, these constants are generalized in the premise (term -> G) of the first subgoal. By default bodies of local definitions are erased. This behavior can be inhibited by prefixing the name of the local definition with the @ character.

In the second subgoal, the tactic:

```
move=> clear_switch i_item.
```

is performed if at least one of these optional switches is present in the wlog tactic.

The wlog tactic is specially useful when a symmetry argument simplifies a proof. Here is an example showing the beginning of the proof that quotient and reminder of natural number euclidean division are unique.

#### Example

The wlog suff variant is simpler, since it cuts wlog\_statement instead of wlog\_statement -> G. It thus opens the goals wlog\_statement -> G and wlog\_statement.

In its simplest form the generally have: ... tactic is equivalent to wlog suff: ... followed by last first. When the have tactic is used with the generally (or gen) modifier it accepts an extra identifier followed by a comma before the usual intro pattern. The identifier will name the new hypothesis in its more general form, while the intro pattern will be used to process its instance.

## Example

```
Lemma simple n (ngt0 : 0 < n) : P n.
   1 subgoal
     n : nat
     ngt0 : 0 < n
     _____
gen have ltnV, /andP[nge0 neq0] : n ngt0 / (0 <= n) && (n != 0); last first.
   2 subgoals
     n : nat
     ngt0 : 0 < n
     ltnV : forall n : nat, 0 < n \rightarrow (0 <= n) && (n != 0)
     nge0 : 0 \le n
     neq0 : n != 0
     _____
     P n
   subgoal 2 is:
    (0 <= n) && (n != 0)
```

#### Advanced generalization

The complete syntax for the items on the left hand side of the / separator is the following one:

Clear operations are intertwined with generalization operations. This helps in particular avoiding dependency issues while generalizing some facts.

If an ident is prefixed with the @ mark, then a let-in redex is created, which keeps track if its body (if any). The syntax ( $ident := c\_pattern$ ) allows to generalize an arbitrary term using a given name. Note that its simplest form (x := y) is just a renaming of y into x. In particular, this can be useful in order to simulate the generalization of a section variable, otherwise not allowed. Indeed renaming does not require the original variable to be cleared.

The syntax (@x := y) generates a let-in abstraction but with the following caveat: x will not bind y, but its body, whenever y can be unfolded. This covers the case of both local and global definitions, as illustrated in the following example.

## Example

```
Section Test.
Variable x : nat.
   x is declared
Definition addx z := z + x.
   addx is defined
Lemma test : x \le addx x.
   1 subgoal
     x : nat
     _____
     x \le addx x
wlog H : (y := x) (@twoy := addx x) / twoy = 2 * y.
   2 subgoals
     x : nat
     _____
     (forall y : nat, let twoy := y + y in twoy = 2 * y -> y <= twoy) ->
     x \le addx x
   subgoal 2 is:
    y <= twoy
```

To avoid unfolding the term captured by the pattern add x one can use the pattern id (addx x), that would produce the following first subgoal

# 5.7.6 Rewriting

The generalized use of reflection implies that most of the intermediate results handled are properties of effectively computable functions. The most efficient mean of establishing such results are computation and

simplification of expressions involving such functions, i.e., rewriting. SSReflect therefore includes an extended rewrite tactic, that unifies and combines most of the rewriting functionalities.

#### An extended rewrite tactic

The main features of the rewrite tactic are:

- It can perform an entire series of such operations in any subset of the goal and/or context;
- It allows to perform rewriting, simplifications, folding/unfolding of definitions, closing of goals;
- Several rewriting operations can be chained in a single tactic;
- Control over the occurrence at which rewriting is to be performed is significantly enhanced.

The general form of an SSReflect rewrite tactic is:

The combination of a rewrite tactic with the in tactical (see section *Localization*) performs rewriting in both the context and the goal.

A rewrite step rstep has the general form:

```
rstep ::= r_prefix ? r_item

r_prefix ::= -? mult occ_switch clear_switch ? [ r_pattern ] ?

r_pattern ::= term in ident in term term in term as ident in term

r_item ::= /? term s_item
```

An r\_prefix contains annotations to qualify where and how the rewrite operation should be performed:

- The optional initial indicates the direction of the rewriting of  $r\_item$ : if present the direction is right-to-left and it is left-to-right otherwise.
- The multiplier *mult* (see section *Iteration*) specifies if and how the rewrite operation should be repeated.
- A rewrite operation matches the occurrences of a rewrite pattern, and replaces these occurrences by
  another term, according to the given r\_item. The optional redex switch [r\_pattern], which should
  always be surrounded by brackets, gives explicitly this rewrite pattern. In its simplest form, it is a
  regular term. If no explicit redex switch is present the rewrite pattern to be matched is inferred from
  the r\_item.
- This optional term, or the  $r\_item$ , may be preceded by an  $occ\_switch$  (see section Selectors) or a  $clear\_switch$  (see section Discharge), these two possibilities being exclusive.

An occurrence switch selects the occurrences of the rewrite pattern which should be affected by the rewrite operation.

A clear switch, even an empty one, is performed after the  $r_item$  is actually processed and is complemented with the name of the rewrite rule if an only if it is a simple proof context entry<sup>307</sup>. As a consequence one can write rewrite {}H to rewrite with H and dispose H immediately afterwards. This behavior can be avoided by putting parentheses around the rewrite rule.

An  $r_item$  can be:

- A simplification r\_item, represented by a s\_item (see section Introduction in the context). Simplification operations are intertwined with the possible other rewrite operations specified by the list of r item.
- A folding/unfolding r\_item. The tactic: rewrite /term unfolds the head constant of term in every occurrence of the first matching of term in the goal. In particular, if my\_def is a (local or global) defined constant, the tactic: rewrite /my\_def. is analogous to: unfold my\_def. Conversely: rewrite -/ my\_def. is equivalent to: fold my\_def. When an unfold r\_item is combined with a redex pattern, a conversion operation is performed. A tactic of the form: rewrite -[term1]/term2. is equivalent to: change term1 with term2. If term2 is a single constant and term1 head symbol is not term2, then the head symbol of term1 is repeatedly unfolded until term2 appears.
- A term, which can be:
  - A term whose type has the form: forall (x1 : A1)...(xn : An), eq term1 term2 where eq is the Leibniz equality or a registered setoid equality.
  - A list of terms (t1 ,...,tn), each ti having a type above. The tactic: rewrite r\_prefix (t1 ,...,tn). is equivalent to: do [rewrite r\_prefix t1 | ... | rewrite r\_prefix tn ].
  - An anonymous rewrite lemma (\_ : term), where term has a type as above. tactic: rewrite
     (\_ : term) is in fact synonym of: cutrewrite (term)...

#### Example

**Warning:** The SSReflect terms containing holes are *not* typed as abstractions in this context. Hence the following script fails.

## Flag: Ssr0ldRewriteGoalsOrder

Controls the order in which generated subgoals (side conditions) are added to the proof context. The flag is off by default, which puts subgoals generated by conditional rules first, followed by the main goal. When it is on, the main goal appears first. If your proofs are organized to complete proving the main goal before side conditions, turning the flag on will save you from having to add *last first* tactics that would be needed to keep the main goal as the currently focused goal.

## Remarks and examples

#### Rewrite redex selection

The general strategy of SSReflect is to grasp as many redexes as possible and to let the user select the ones to be rewritten thanks to the improved syntax for the control of rewriting.

This may be a source of incompatibilities between the two rewrite tactics.

In a rewrite tactic of the form:

```
rewrite occ_switch [term1]term2.
```

term1 is the explicit rewrite redex and term2 is the rewrite rule. This execution of this tactic unfolds as follows:

- First term1 and term2 are  $\beta\iota$  normalized. Then term2 is put in head normal form if the Leibniz equality constructor eq is not the head symbol. This may involve  $\zeta$  reductions.
- Then, the matching algorithm (see section Abbreviations) determines the first subterm of the goal matching the rewrite pattern. The rewrite pattern is given by term1, if an explicit redex pattern switch is provided, or by the type of term2 otherwise. However, matching skips over matches that would lead to trivial rewrites. All the occurrences of this subterm in the goal are candidates for rewriting.
- Then only the occurrences coded by occ\_switch (see again section Abbreviations) are finally selected for rewriting.
- The left hand side of term2 is unified with the subterm found by the matching algorithm, and if this succeeds, all the selected occurrences in the goal are replaced by the right hand side of term2.
- Finally the goal is  $\beta \iota$  normalized.

In the case term2 is a list of terms, the first top-down (in the goal) left-to-right (in the list) matching rule gets selected.

#### Chained rewrite steps

The possibility to chain rewrite operations in a single tactic makes scripts more compact and gathers in a single command line a bunch of surgical operations which would be described by a one sentence in a pen and paper proof.

Performing rewrite and simplification operations in a single tactic enhances significantly the concision of scripts. For instance the tactic:

```
rewrite /my_def {2}[f _]/= my_eq //=.
```

unfolds my\_def in the goal, simplifies the second occurrence of the first subterm matching pattern [f \_], rewrites my\_eq, simplifies the goals and closes trivial goals.

Here are some concrete examples of chained rewrite operations, in the proof of basic results on natural numbers arithmetic.

#### Example

```
Axiom addn0 : forall m, m + 0 = m.
   addn0 is declared
Axiom addnS : forall m n, m + S n = S (m + n).
   addnS is declared
Axiom addSnnS : forall m n, S m + n = m + S n.
   addSnnS is declared
Lemma addnCA m n p : m + (n + p) = n + (m + p).
   1 subgoal
     m, n, p : nat
     _____
     m + (n + p) = n + (m + p)
by elim: m p => [ | m Hrec] p; rewrite ?addSnnS -?addnS.
   No more subgoals.
Lemma addnC n m : m + n = n + m.
   1 subgoal
     n, m : nat
     _____
     m + n = n + m
by rewrite -{1}[n]addn0 addnCA addn0.
   No more subgoals.
Qed.
```

Note the use of the ? switch for parallel rewrite operations in the proof of addnCA.

## Explicit redex switches are matched first

If an  $r\_prefix$  involves a  $redex\ switch$ , the first step is to find a subterm matching this redex pattern, independently from the left hand side of the equality the user wants to rewrite.

## Example

Note that if this first pattern matching is not compatible with the  $r_item$ , the rewrite fails, even if the goal contains a correct redex matching both the redex switch and the left hand side of the equality.

### Example

Indeed the left hand side of H does not match the redex identified by the pattern x + y \* 4.

#### Occurrence switches and redex switches

## Example

The second subgoal is generated by the use of an anonymous lemma in the rewrite tactic. The effect of the tactic on the initial goal is to rewrite this lemma at the second occurrence of the first matching x + y + 0 of the explicit rewrite redex  $_{-} + y + 0$ .

## Occurrence selection and repetition

Occurrence selection has priority over repetition switches. This means the repetition of a rewrite tactic specified by a multiplier will perform matching each time an elementary rewrite operation is performed. Repeated rewrite tactics apply to every subgoal generated by the previous tactic, including the previous instances of the repetition.

#### Example

```
Lemma test x y (z : nat) : x + 1 = x + y + 1.
   1 subgoal
     x, y, z : nat
     _____
     x + 1 = x + y + 1
rewrite 2!(_ : _ + 1 = z).
   4 subgoals
     x, y, z : nat
     _____
     x + 1 = z
   subgoal 2 is:
    z = z
   subgoal 3 is:
   x + y + 1 = z
   subgoal 4 is:
    z = z
```

This last tactic generates *three* subgoals because the second rewrite operation specified with the 2! multiplier applies to the two subgoals generated by the first rewrite.

#### Multi-rule rewriting

The rewrite tactic can be provided a *tuple* of rewrite rules, or more generally a tree of such rules, since this tuple can feature arbitrary inner parentheses. We call *multirule* such a generalized rewrite rule. This feature is of special interest when it is combined with multiplier switches, which makes the rewrite tactic iterate the rewrite operations prescribed by the rules on the current goal.

## Example

```
Variables (a b c : nat).
   a is declared
   b is declared
   c is declared
Hypothesis eqab : a = b.
   eqab is declared
Hypothesis eqac : a = c.
   eqac is declared
Lemma test : a = a.
   1 subgoal
     a, b, c : nat
     eqab : a = b
     eqac : a = c
     _____
     a = a
rewrite (eqab, eqac).
   1 subgoal
     a, b, c : nat
     eqab : a = b
     eqac : a = c
     _____
     b = b
```

Indeed rule eqab is the first to apply among the ones gathered in the tuple passed to the rewrite tactic. This multirule (eqab, eqac) is actually a Coq term and we can name it with a definition:

```
Definition multi1 := (eqab, eqac).
    multi1 is defined
```

In this case, the tactic rewrite multi1 is a synonym for rewrite (eqab, eqac).

More precisely, a multirule rewrites the first subterm to which one of the rules applies in a left-to-right traversal of the goal, with the first rule from the multirule tree in left-to-right order. Matching is performed according to the algorithm described in Section *Abbreviations*, but literal matches have priority.

#### Example

```
Definition d := a.
    d is defined
```

```
Hypotheses eqd0: d = 0.
   eqd0 is declared
Definition multi2 := (eqab, eqd0).
   multi2 is defined
Lemma test : d = b.
   1 subgoal
     a, b, c : nat
     eqab : a = b
     eqac : a = c
     eqd0 : d = 0
     _____
     d = b
rewrite multi2.
   1 subgoal
     a, b, c : nat
     eqab : a = b
     eqac : a = c
     eqd0 : d = 0
     _____
     0 = b
```

Indeed rule eqd0 applies without unfolding the definition of d.

For repeated rewrites the selection process is repeated anew.

## Example

```
Hypothesis eq_adda_b : forall x, x + a = b.
    eq_adda_b is declared
Hypothesis eq_adda_c : forall x, x + a = c.
    eq_adda_c is declared
Hypothesis eqb0 : b = 0.
    eqb0 is declared
\label{eq:definition multi3} \mbox{ = } (\mbox{eq\_adda\_b}, \mbox{ eq\_adda\_c}, \mbox{ eqb0}) \,.
    multi3 is defined
Lemma test : 1 + a = 12 + a.
    1 subgoal
      a, b, c : nat
      eqab : a = b
      eqac : a = c
      eqd0 : d = 0
      eq_adda_b : forall x : nat, x + a = b
      eq_adda_c : forall x : nat, x + a = c
      eqb0 : b = 0
      _____
```

 $({\rm continues\ on\ next\ page})$ 

It uses  $eq_adda_b$  then eqb0 on the left-hand side only. Without the bound 2 one would obtain 0 = 0.

The grouping of rules inside a multirule does not affect the selection strategy but can make it easier to include one rule set in another or to (universally) quantify over the parameters of a subset of rules (as there is special code that will omit unnecessary quantifiers for rules that can be syntactically extracted). It is also possible to reverse the direction of a rule subset, using a special dedicated syntax: the tactic rewrite (=~multi1) is equivalent to rewrite multi1\_rev.

## Example

```
Hypothesis eqba : b = a.
    eqba is declared

Hypothesis eqca : c = a.
    eqca is declared

Definition multi1_rev := (eqba, eqca).
    multi1_rev is defined
```

except that the constants eqba, eqab, mult1\_rev have not been created.

Rewriting with multirules is useful to implement simplification or transformation procedures, to be applied on terms of small to medium size. For instance the library ssrnat (Mathematical Components library) provides two implementations for arithmetic operations on natural numbers: an elementary one and a tail recursive version, less inefficient but also less convenient for reasoning purposes. The library also provides one lemma per such operation, stating that both versions return the same values when applied to the same arguments:

```
Lemma addE : add =2 addn.

Lemma doubleE : double =1 doublen.

Lemma add_mulE n m s : add_mul n m s = addn (muln n m) s.

Lemma mulE : mul =2 muln.

Lemma mul_expE m n p : mul_exp m n p = muln (expn m n) p.

Lemma expE : exp =2 expn.

Lemma oddE : odd =1 oddn.
```

The operation on the left hand side of each lemma is the efficient version, and the corresponding naive implementation is on the right hand side. In order to reason conveniently on expressions involving the efficient operations, we gather all these rules in the definition trecE:

```
Definition trecE := (addE, (doubleE, oddE), (mulE, add_mulE, (expE, mul_expE))).
```

The tactic: rewrite !trecE. restores the naive versions of each operation in a goal involving the efficient ones, e.g. for the purpose of a correctness proof.

#### Wildcards vs abstractions

The rewrite tactic supports  $r_i$  tems containing holes. For example, in the tactic rewrite (\_ : \_ \* 0 = 0). the term \_ \* 0 = 0 is interpreted as forall n : nat, n \* 0 = 0. Anyway this tactic is not equivalent to rewrite (\_ : forall x, x \* 0 = 0)..

## Example

```
Lemma test y z : y * 0 + y * (z * 0) = 0.
   1 subgoal
     y, z : nat
     _____
     y * 0 + y * (z * 0) = 0
rewrite (_ : _ * 0 = 0).
   2 subgoals
     y, z : nat
     _____
     y * 0 = 0
   subgoal 2 is:
    0 + y * (z * 0) = 0
while the other tactic results in
rewrite (_ : forall x, x * 0 = 0).
   2 subgoals
     y, z : nat
     _____
     forall x : nat, x * 0 = 0
   subgoal 2 is:
    0 + y * (z * 0) = 0
```

The first tactic requires you to prove the instance of the (missing) lemma that was used, while the latter requires you prove the quantified form.

### When SSReflect rewrite fails on standard Coq licit rewrite

In a few cases, the SSReflect rewrite tactic fails rewriting some redexes which standard Coq successfully rewrites. There are two main cases:

• SSReflect never accepts to rewrite indeterminate patterns like:

```
Lemma foo (x : unit) : x = tt.
```

SSReflect will however accept the  $\eta\zeta$  expansion of this rule:

```
Lemma fubar (x : unit) : (let u := x in u) = tt.
```

 The standard rewrite tactic provided by Coq uses a different algorithm to find instances of the rewrite rule.

## Example

```
Variable g : nat -> nat.
   g is declared
Definition f := g.
   f is defined
Axiom H: forall x, g x = 0.
   H is declared
Lemma test: f 3 + f 3 = f 6.
   1 subgoal
     g : nat -> nat
     _____
     f 3 + f 3 = f 6
(* we call the standard rewrite tactic here *)
rewrite -> H.
   1 subgoal
     g : nat -> nat
     _____
     0 + 0 = f 6
```

This rewriting is not possible in SSReflect because there is no occurrence of the head symbol **f** of the rewrite rule in the goal.

Rewriting with H first requires unfolding the occurrences of f where the substitution is to be performed (here there is a single such occurrence), using tactic rewrite /f (for a global replacement of f by g) or rewrite pattern/f, for a finer selection.

alternatively one can override the pattern inferred from H

## Existential metavariables and rewriting

The rewrite tactic will not instantiate existing existential metavariables when matching a redex pattern.

If a rewrite rule generates a goal with new existential metavariables in the Prop sort, these will be generalized as for apply (see *The apply tactic*) and corresponding new goals will be generated.

#### Example

```
Axiom leq : nat -> nat -> bool.
   leq is declared
Notation "m \le n" := (leq m n) : nat_scope.
Notation "m < n" := (S m \le n) : nat_scope.
Inductive Ord n := Sub x of x < n.
   Ord is defined
   Ord_rect is defined
   Ord_ind is defined
   Ord_rec is defined
   Ord_sind is defined
Notation "'I_n" := (Ord n) (at level 8, n at level 2, format "''I_n").
Arguments Sub {_} _ _.
Definition val n (i : 'I_n) := let: Sub a \_ := i in a.
   val is defined
Definition insub n x :=
 if @idP (x < n) is ReflectT _ Px then Some (Sub x Px) else None.
   insub is defined
Axiom insubT : forall n x Px, insub n x = Some (Sub x Px).
   insubT is declared
Lemma test (x : 'I_2) y : Some x = insub 2 y.
   1 subgoal
     x : 'I_2
     y : nat
     _____
     Some x = insub 2 y
rewrite insubT.
   2 subgoals
     x : 'I_2
     y : nat
```

```
forall Hyp0 : y < 2, Some x = Some (Sub y Hyp0) subgoal 2 is: y < 2
```

Since the argument corresponding to Px is not supplied by the user, the resulting goal should be Some x = Some (Sub y ?Goal). Instead, SSReflect rewrite tactic hides the existential variable.

As in *The apply tactic*, the ssrautoprop tactic is used to try to solve the existential variable.

As a temporary limitation, this behavior is available only if the rewriting rule is stated using Leibniz equality (as opposed to setoid relations). It will be extended to other rewriting relations in the future.

#### Rewriting under binders

Goals involving objects defined with higher-order functions often require "rewriting under binders". While setoid rewriting is a possible approach in this case, it is common to use regular rewriting along with dedicated extensionality lemmas. This may cause some practical issues during the development of the corresponding scripts, notably as we might be forced to provide the rewrite tactic with complete terms, as shown by the simple example below.

## Example

```
Axiom subnn : forall n : nat, n - n = 0.
Parameter map : (nat -> nat) -> list nat -> list nat.
Parameter sumlist : list nat -> nat.
Axiom eq_map :
  forall F1 F2 : nat -> nat,
   (forall n : nat, F1 n = F2 n) ->
  forall l : list nat, map F1 l = map F2 l.

Lemma example_map l : sumlist (map (fun m => m - m) l) = 0.
    1 subgoal
```

as we need to explicitly provide the non-inferable argument F2, which corresponds here to the term we want to obtain *after* the rewriting step. In order to perform the rewrite step one has to provide the term by hand as follows:

The *under* tactic lets one perform the same operation in a more convenient way:

## The under tactic

The convenience *under* tactic supports the following syntax:



Operate under the context proved to be extensional by lemma term.

 $Error \colon Incorrect \ number \ of \ tactics \ (expected \ N \ tactics, \ was \ given \ M) \, .$ 

This error can occur when using the version with a do clause.

The multiplier part of  $r\_prefix$  is not supported.

We distinguish two modes, *interactive mode* without a do clause, and *one-liner mode* with a do clause, which are explained in more detail below.

#### Interactive mode

Let us redo the running example in interactive mode.

## Example

```
Lemma example_map 1 : sumlist (map (fun m \Rightarrow m - m) 1) = 0.
   1 subgoal
     1 : list nat
     _____
     sumlist (map (fun m : nat => m - m) 1) = 0
under eq_map => m.
   2 focused subgoals
   (shelved: 2)
     1 : list nat
     m : nat
     _____
     'Under[ m - m ]
   subgoal 2 is:
    sumlist (map ?Goal 1) = 0
rewrite subnn.
   2 focused subgoals
   (shelved: 2)
    1 : list nat
     m : nat
     _____
     'Under[ 0 ]
   subgoal 2 is:
    sumlist (map ?Goal 1) = 0
over.
   1 focused subgoal
   (shelved: 1)
     1 : list nat
     _____
     sumlist (map (fun _ : nat => 0) 1) = 0
```

The execution of the Ltac expression:

```
under term \Rightarrow [i_item_i \mid ... \mid i_item_n].
```

involves the following steps:

- 1. It performs a rewrite *term* without failing like in the first example with rewrite eq\_map., but creating evars (see *evar*). If term is prefixed by a pattern or an occurrence selector, then the modifiers are honoured.
- 2. As a n-branches intro pattern is provided *under* checks that n+1 subgoals have been created. The last one is the main subgoal, while the other ones correspond to premises of the rewrite rule (such as forall n, F1 n = F2 n for eq\_map).
- 3. If so *under* puts these n goals in head normal form (using the defective form of the tactic *move*), then executes the corresponding intro pattern *i\_pattern<sub>i</sub>* in each goal.
- 4. Then *under* checks that the first n subgoals are (quantified) Leibniz equalities, double implications or registered relations (w.r.t. Class RewriteRelation) between a term and an evar, e.g. m m = ?F2 m in the running example. (This support for setoid-like relations is enabled as soon as we do both Require Import ssreflect. and Require Setoid.)
- 5. If so *under* protects these n goals against an accidental instantiation of the evar. These protected goals are displayed using the 'Under[ ... ] notation (e.g. 'Under[ m m ] in the running example).
- 6. The expression inside the 'Under[ ... ] notation can be proved equivalent to the desired expression by using a regular rewrite tactic.
- 7. Interactive editing of the first n goals has to be signalled by using the *over* tactic or rewrite rule (see below), which requires that the underlying relation is reflexive. (The running example deals with Leibniz equality, but PreOrder relations are also supported, for example.)
- 8. Finally, a post-processing step is performed in the main goal to keep the name(s) for the bound variables chosen by the user in the intro pattern for the first branch.

## The over tactic

Two equivalent facilities (a terminator and a lemma) are provided to close intermediate subgoals generated by *under* (i.e. goals displayed as 'Under[ ... ]):

over

This terminator tactic allows one to close goals of the form 'Under[ ... ].

#### Variant: by rewrite over

This is a variant of *over* in order to close 'Under[ ... ] goals, relying on the over rewrite rule.

Note that a rewrite rule UnderE is available as well, if one wants to "unprotect" the evar, without closing the goal automatically (e.g., to instantiate it manually with another rule than reflexivity).

#### One-liner mode

The Ltac expression:

```
under term \Rightarrow [i_item_1 \mid ... \mid i_item_n] do [tactic_1 \mid ... \mid tactic_n].
```

can be seen as a shorter form for the following expression:

```
(under term) => [ i\_item_1 | ... | i\_item_n | ]; [ tactic_1; over | ... | tactic_n; over | cbv beta iota ].
```

#### Notes:

- The beta-iota reduction here is useful to get rid of the beta redexes that could be introduced after the substitution of the evars by the *under* tactic.
- Note that the provided tactics can as well involve other *under* tactics. See below for a typical example involving the bigop theory from the Mathematical Components library.
- If there is only one tactic, the brackets can be omitted, e.g.: under term => i do tactic. and that shorter form should be preferred.
- If the do clause is provided and the intro pattern is omitted, then the default <code>i\_item\*</code> is applied to each branch. E.g., the Ltac expression: under <code>term</code> do [ <code>tactic\_1 | ... | tactic\_n ]</code> is equivalent to: under <code>term => [\* | ... | \* ]</code> do [ <code>tactic\_1 | ... | tactic\_n ]</code> (and it can be noted here that the <code>under</code> tactic performs a move. before processing the intro patterns <code>=> [\* | ... | \* ]</code>).

#### Example

```
Parameter addnC : forall m n : nat, m + n = n + m.
Parameter muln1 : forall n : nat, n * 1 = n.
Check eq_bigr.
   eq_bigr
        : forall (n m : nat) (P : nat -> bool) (F1 F2 : nat -> nat),
          (forall x : nat, P x \rightarrow F1 x = F2 x) \rightarrow
          \sum_(n <= i < m | P i) F1 i = \sum_(n <= i < m | P i) F2 i
Check eq_big.
   eq_big
        : forall (n m : nat) (P1 P2 : nat -> bool) (F1 F2 : nat -> nat),
          (forall x : nat, P1 x = P2 x) \rightarrow
          (forall i : nat, P1 i -> F1 i = F2 i) ->
          \sum_(n <= i < m | P1 i) F1 i = \sum_(n <= i < m | P2 i) F2 i
Lemma test_big_nested (m n : nat) :
 \sum_{0 \le n} (0 \le a \le m \mid prime a) \sum_{0 \le n} (0 \le j \le n \mid odd (j * 1)) (a + j) =
 1 subgoal
     m, n : nat
     \sum_{0 \le n \le n} (0 \le a \le m \mid prime a) \sum_{0 \le j \le n} (0 \le j \le n \mid odd (j * 1)) (a + j) =
     under eq_bigr => i prime_i do
 under eq_big => [ j | j odd_j ] do
   [ rewrite (muln1 j) | rewrite (addnC i j) ].
   1 subgoal
     m, n: nat
     \sum_{i=1}^{n} (0 \le i \le m \mid prime i) \sum_{i=1}^{n} (0 \le j \le n \mid odd j) (j + i) = 0
```

Remark how the final goal uses the name i (the name given in the intro pattern) rather than a in the binder

of the first summation.

## Locking, unlocking

As program proofs tend to generate large goals, it is important to be able to control the partial evaluation performed by the simplification operations that are performed by the tactics. These evaluations can for example come from a /= simplification switch, or from rewrite steps which may expand large terms while performing conversion. We definitely want to avoid repeating large subterms of the goal in the proof script. We do this by "clamping down" selected function symbols in the goal, which prevents them from being considered in simplification or rewriting steps. This clamping is accomplished by using the occurrence switches (see section Abbreviations) together with "term tagging" operations.

SSReflect provides two levels of tagging.

The first one uses auxiliary definitions to introduce a provably equal copy of any term t. However this copy is (on purpose) not convertible to t in the Coq system<sup>305</sup>. The job is done by the following construction:

```
Lemma master_key : unit. Proof. exact tt. Qed. Definition locked A := let: tt := master_key in fun x : A => x. Lemma lock : forall A \times x, x = locked \times x :> A.
```

Note that the definition of master\_key is explicitly opaque. The equation t = locked t given by the lock lemma can be used for selective rewriting, blocking on the fly the reduction in the term t.

### Example

```
Variable A : Type.
   A is declared
Fixpoint has (p : A -> bool) (1 : list A) : bool :=
  if l is cons x l then p x || (has p l) else false.
   has is defined
   has is recursively defined (decreasing on 2nd argument)
Lemma test p \times y \mid (H : p \times = true) : has p (x :: y :: 1) = true.
   1 subgoal
     A : Type
     p : A -> bool
     x, y : A
     1 : list A
     H : p x = true
      _____
     has p(x :: y :: 1) = true
rewrite {2} [cons] lock /= -lock.
   1 subgoal
     A : Type
     p : A -> bool
     x, y : A
     1 : list A
     H : p x = true
```

 $<sup>^{305}</sup>$  This is an implementation feature: there is no such obstruction in the metatheory

```
p x || has p (y :: 1) = true
```

It is sometimes desirable to globally prevent a definition from being expanded by simplification; this is done by adding locked in the definition.

### Example

```
unlock occ_switch ident
```

This tactic unfolds such definitions while removing "locks", i.e. it replaces the occurrence(s) of *ident* coded by the *occ\_switch* with the corresponding body.

We found that it was usually preferable to prevent the expansion of some functions by the partial evaluation switch /=, unless this allowed the evaluation of a condition. This is possible thanks to another mechanism of term tagging, resting on the following *Notation*:

```
Notation "'nosimpl' t" := (let: tt := tt in t).
```

The term (nosimpl t) simplifies to t except in a definition. More precisely, given:

```
Definition foo := (nosimpl bar).
```

the term foo (or (foo t')) will not be expanded by the simpl tactic unless it is in a forcing context (e.g., in match foo t' with ... end, foo t' will be reduced if this allows match to be reduced). Note that nosimpl bar is simply notation for a term that reduces to bar; hence unfold foo will replace foo by bar, and fold foo will replace bar by foo.

Warning: The nosimpl trick only works if no reduction is apparent in t; in particular, the declaration: Definition foo x := nosimpl (bar x).

will usually not work. Anyway, the common practice is to tag only the function, and to use the following definition, which blocks the reduction as expected:

```
Definition foo x := nosimpl bar x.
```

A standard example making this technique shine is the case of arithmetic operations. We define for instance:

```
Definition addn := nosimpl plus.
```

The operation addn behaves exactly like plus, except that (addn (S n) m) will not simplify spontaneously to (S (addn n m)) (the two terms, however, are convertible). In addition, the unfolding step: rewrite /addn will replace addn directly with plus, so the nosimpl form is essentially invisible.

## Congruence

Because of the way matching interferes with parameters of type families, the tactic:

```
apply: my_congr_property.
```

will generally fail to perform congruence simplification, even on rather simple cases. We therefore provide a more robust alternative in which the function is supplied:

```
congr num ? term
```

This tactic:

- checks that the goal is a Leibniz equality;
- matches both sides of this equality with "term applied to some arguments", inferring the right number of arguments from the goal and the type of term. This may expand some definitions or fixpoints:
- generates the subgoals corresponding to pairwise equalities of the arguments present in the goal.

The goal can be a non dependent product  $P \rightarrow Q$ . In that case, the system asserts the equation P =Q, uses it to solve the goal, and calls the congr tactic on the remaining goal P = Q. This can be useful for instance to perform a transitivity step, like in the following situation.

#### Example

```
Lemma test (x y z : nat) (H : x = y) : x = z.
   1 subgoal
    x, y, z : nat
    H : x = y
    _____
congr (_ = _) : H.
   1 focused subgoal
   (shelved: 1)
    x, y, z : nat
     _____
    y = z
```

The optional *num* forces the number of arguments for which the tactic should generate equality proof obligations.

This tactic supports equalities between applications with dependent arguments. Yet dependent arguments should have exactly the same parameters on both sides, and these parameters should appear as first arguments.

## Example

This script shows that the congr tactic matches plus with f 0 on the left hand side and g 1 1 on the right hand side, and solves the goal.

## Example

The tactic rewrite -/plus folds back the expansion of plus which was necessary for matching both sides of the equality with an application of S.

Like most SSReflect arguments, term can contain wildcards.

## Example

# 5.7.7 Contextual patterns

The simple form of patterns used so far, terms possibly containing wild cards, often require an additional occ\_switch to be specified. While this may work pretty fine for small goals, the use of polymorphic functions and dependent types may lead to an invisible duplication of function arguments. These copies usually end up in types hidden by the implicit arguments machinery or by user-defined notations. In these situations computing the right occurrence numbers is very tedious because they must be counted on the goal as printed after setting the Printing All flag. Moreover the resulting script is not really informative for the reader, since it refers to occurrence numbers he cannot easily see.

Contextual patterns mitigate these issues allowing to specify occurrences according to the context they occur in.

#### **Syntax**

The following table summarizes the full syntax of  $c\_pattern$  and the corresponding subterm(s) identified by the pattern. In the third column we use s.m.r. for "the subterms matching the redex" specified in the second column.

$c\_pattern$	redex	subterms affected
term	term	all occurrences of term
ident in term	subterm of term se-	all the subterms identified by ident in all the occurrences
	lected by ident	of term
term1 in ident	term1 in all s.m.r.	in all the subterms identified by ident in all the occur-
in term2		rences of term2
term1 as ident	term 1	in all the subterms identified by ident in all the occur-
in term2		rences of term2[term 1 /ident]

The rewrite tactic supports two more patterns obtained prefixing the first two with in. The intended meaning is that the pattern identifies all subterms of the specified context. The rewrite tactic will infer a pattern for the redex looking at the rule used for rewriting.

$r\_pattern$	redex	subterms affected
in term	inferred from	in all s.m.r. in all occurrences of term
	rule	
in ident in	inferred from	in all s.m.r. in all the subterms identified by ident in all the occur-
term	rule	rences of term

The first  $c\_pattern$  is the simplest form matching any context but selecting a specific redex and has been described in the previous sections. We have seen so far that the possibility of selecting a redex using a term with holes is already a powerful means of redex selection. Similarly, any terms provided by the user in the more complex forms of  $c\_pattern$ s presented in the tables above can contain holes.

For a quick glance at what can be expressed with the last  $r_pattern$  consider the goal a = b and the tactic rewrite [in X in \_ = X]rule.

It rewrites all occurrences of the left hand side of rule inside b only (a, and the hidden type of the equality, are ignored). Note that the variant rewrite [X in \_ = X]rule would have rewritten b exactly (i.e., it would only work if b and the left hand side of rule can be unified).

#### Matching contextual patterns

The  $c\_pattern$  and  $r\_pattern$  involving terms with holes are matched against the goal in order to find a closed instantiation. This matching proceeds as follows:

$c\_pattern$	instantiation order and place for term_i and redex
term	term is matched against the goal, redex is unified with the instantiation of term
ident in	term is matched against the goal, redex is unified with the subterm of the instantiation
term	of term identified by ident
term1 in	term2 is matched against the goal, term1 is matched against the subterm of the instan-
ident in	tiation of term1 identified by ident, redex is unified with the instantiation of term1
term2	
term1 as	term2[term1/ident] is matched against the goal, redex is unified with the instantiation
ident in	of term1
term2	

In the following patterns, the redex is intended to be inferred from the rewrite rule.

$r\_pattern$	instantiation order and place for term_i and redex		
in ident in	term is matched against the goal, the redex is matched against the subterm of the in-		
term	stantiation of term identified by ident		
in term	term is matched against the goal, redex is matched against the instantiation of term		

## **Examples**

## Contextual pattern in set and the : tactical

As already mentioned in section Abbreviations the **set** tactic takes as an argument a term in open syntax. This term is interpreted as the simplest form of  $c\_pattern$ . To avoid confusion in the grammar, open syntax is supported only for the simplest form of patterns, while parentheses are required around more complex patterns.

## Example

```
Lemma test a b : a + b + 1 = b + (a + 1).
   1 subgoal
    a, b: nat
    a + b + 1 = b + (a + 1)
set t := (X in _ = X).
   1 subgoal
    a, b : nat
    t := b + (a + 1) : nat
    _____
    a + b + 1 = t
rewrite {}/t.
   1 subgoal
    a, b : nat
     _____
    a + b + 1 = b + (a + 1)
set t := (a + _ in X in _ = X).
   1 subgoal
    a, b : nat
    t := a + 1 : nat
     _____
     a + b + 1 = b + t
```

Since the user may define an infix notation for in the result of the former tactic may be ambiguous. The disambiguation rule implemented is to prefer patterns over simple terms, but to interpret a pattern with double parentheses as a simple term. For example, the following tactic would capture any occurrence of the term a in A.

```
set t := ((a in A)).
```

Contextual patterns can also be used as arguments of the : tactical. For example:

```
elim: n (n in _ = n) (refl_equal n).
```

## Contextual patterns in rewrite

## Example

```
Notation "n .+1" := (Datatypes.S n) (at level 2, left associativity,
                    format "n .+1") : nat_scope.
Axiom addSn : forall m n, m.+1 + n = (m + n).+1.
   addSn is declared
Axiom addn0 : forall m, m + 0 = m.
   addn0 is declared
Axiom addnC : forall m n, m + n = n + m.
   addnC is declared
Lemma test x y z f : (x.+1 + y) + f (x.+1 + y) (z + (x + y).+1) = 0.
   1 subgoal
     x, y, z : nat
     f : nat \rightarrow nat \rightarrow nat
      _____
     x.+1 + y + f (x.+1 + y) (z + (x + y).+1) = 0
rewrite [in f _ _]addSn.
   1 subgoal
     x, y, z : nat
     f : nat \rightarrow nat \rightarrow nat
     _____
     x.+1 + y + f (x + y).+1 (z + (x + y).+1) = 0
```

Note: the simplification rule addSn is applied only under the f symbol. Then we simplify also the first addition and expand 0 into 0 + 0.

Note that the right hand side of addn0 is undetermined, but the rewrite pattern specifies the redex explicitly. The right hand side of addn0 is unified with the term identified by X, here 0.

The following pattern does not specify a redex, since it identifies an entire region, hence the rewrite rule has to be instantiated explicitly. Thus the tactic:

(x + y).+1 + f (x + y).+1 (z + (y + x.+1)) = 0 + (0 + 0)

The explicit redex \_ .+1 is important since its head constant S differs from the head constant inferred from (addnC x .+1) (that is +). Moreover, the pattern f \_ X is important to rule out the first occurrence of (x + y) .+1. Last, only the subterms of f \_ X identified by X are rewritten, thus the first argument of f is skipped too. Also note the pattern \_ .+1 is interpreted in the context identified by X, thus it gets instantiated to (y + x) .+1 and not (x + y) .+1.

The last rewrite pattern allows to specify exactly the shape of the term identified by X, that is thus unified with the left hand side of the rewrite rule.

#### Patterns for recurrent contexts

The user can define shortcuts for recurrent contexts corresponding to the ident in term part. The notation scope identified with "pattern provides a special notation (X in t) the user must adopt in order to define context shortcuts.

The following example is taken from ssreflect.v where the LHS and RHS shortcuts are defined.

```
Notation RHS := (X \text{ in } \_ = X)\%pattern.
Notation LHS := (X \text{ in } X = \_)\%pattern.
```

Shortcuts defined this way can be freely used in place of the trailing ident in term part of any contextual pattern. Some examples follow:

```
set rhs := RHS.
rewrite [in RHS]rule.
case: (a + _ in RHS).
```

## 5.7.8 Views and reflection

The bookkeeping facilities presented in section *Basic tactics* are crafted to ease simultaneous introductions and generalizations of facts and operations of casing, naming etc. It also a common practice to make a stack operation immediately followed by an *interpretation* of the fact being pushed, that is, to apply a lemma to this fact before passing it to a tactic for decomposition, application and so on.

SSReflect provides a convenient, unified syntax to combine these interpretation operations with the proof stack operations. This *view mechanism* relies on the combination of the / view switch with bookkeeping tactics and tacticals.

## Interpreting eliminations

The view syntax combined with the elim tactic specifies an elimination scheme to be used instead of the default, generated, one. Hence the SSReflect tactic:

```
elim/V.
```

is a synonym for:

```
intro top; elim top using V; clear top.
```

where top is a fresh name and V any second-order lemma.

Since an elimination view supports the two bookkeeping tacticals of discharge and introduction (see section  $Basic\ tactics$ ), the SSReflect tactic:

```
elim/V: x => y.
is a synonym for:
elim x using V; clear x; intro y.
```

where x is a variable in the context, y a fresh name and V any second order lemma; SSReflect relaxes the syntactic restrictions of the Coq elim. The first pattern following: can be a \_ wildcard if the conclusion of the view V specifies a pattern for its last argument (e.g., if V is a functional induction lemma generated by the Function command).

The elimination view mechanism is compatible with the equation name generation (see section *Generation of equations*).

## Example

The following script illustrates a toy example of this feature. Let us define a function adding an element at the end of a list:

```
Variable d : Type.
   d is declared

Fixpoint add_last (s : list d) (z : d) {struct s} : list d :=
   if s is cons x s' then cons x (add_last s' z) else z :: nil.
   add_last is defined
   add_last is recursively defined (decreasing on 1st argument)
```

One can define an alternative, reversed, induction principle on inductively defined lists, by proving the following lemma:

```
Axiom last_ind_list : forall P : list d -> Prop,
P nil -> (forall s (x : d), P s -> P (add_last s x)) ->
forall s : list d, P s.
last_ind_list is declared
```

Then the combination of elimination views with equation names result in a concise syntax for reasoning inductively using the user-defined elimination scheme.

```
Lemma test (x : d) (1 : list d): 1 = 1.
   1 subgoal
     d: Type
     x : d
     1 : list d
     _____
     1 = 1
elim/last_ind_list E : l=> [| u v]; last first.
   2 subgoals
     d : Type
     x : d
     u : list d
     v : d
     1 : list d
     E : l = add_last u v
     u = u -> add_last u v = add_last u v
   subgoal 2 is:
    nil = nil
```

User-provided eliminators (potentially generated with Coq's Function command) can be combined with the type family switches described in section *Type families*. Consider an eliminator foo\_ind of type:

```
foo_ind : forall \dots, forall x : T, P p1 \dots pm. and consider the tactic: elim/foo_ind: e1 \dots / en.
```

The elim/ tactic distinguishes two cases:

truncated eliminator when x does not occur in P p1 ... pm and the type of en unifies with
T and en is not \_. In that case, en is passed to the eliminator as the last argument (x in
foo\_ind) and en-1 ... e1 are used as patterns to select in the goal the occurrences that
will be bound by the predicate P, thus it must be possible to unify the subterm of the goal
matched by en-1 with pm , the one matched by en-2 with pm-1 and so on.

regular eliminator in all the other cases. Here it must be possible to unify the term matched by
en with pm , the one matched by en-1 with pm-1 and so on. Note that standard eliminators
have the shape ...forall x, P ... x, thus en is the pattern identifying the eliminated term,
as expected.

As explained in section *Type families*, the initial prefix of ei can be omitted.

Here is an example of a regular, but nontrivial, eliminator.

## Example

```
Here is a toy example illustrating this feature.
Function plus (m n : nat) {struct n} : nat :=
  if n is S p then S (plus m p) else m.
    plus is defined
   plus is recursively defined (decreasing on 2nd argument)
   plus_equation is defined
   plus_rect is defined
   plus_ind is defined
   plus_rec is defined
   R_plus_correct is defined
   R_plus_complete is defined
About plus_ind.
   plus_ind :
    forall (m : nat) (P : nat -> nat -> Prop),
    (forall\ n\ p\ :\ nat,\ n\ =\ S\ p\ ->\ P\ p\ (plus\ m\ p)\ ->\ P\ (S\ p)\ (S\ (plus\ m\ p)))\ ->
    (forall n _x : nat,
    n = _x \rightarrow match _x with
              | 0 => True
               | S _ => False
               end \rightarrow P _{x} m) \rightarrow forall n : nat, P n (plus m n)
    plus_ind is not universe polymorphic
    Arguments plus_ind [m]%nat_scope [P]%function_scope (_ _)%function_scope
      _%nat_scope
   plus_ind is transparent
   Expands to: Constant Top.Test.plus_ind
Lemma test x y z : plus (plus x y) z = plus x (plus y z).
   1 subgoal
      x, y, z : nat
      _____
      plus (plus x y) z = plus x (plus <math>y z)
The following tactics are all valid and perform the same elimination on this goal.
elim/plus_ind: z / (plus _ z).
elim/plus_ind: \{z\}(plus_z).
elim/plus_ind: {z}_.
elim/plus_ind: z / _.
elim/plus_ind: z / _.
   2 subgoals
      x, y : nat
      _____
     forall n p : nat,
     n = S p \rightarrow
      plus (plus x y) p = plus x (plus y p) ->
      S (plus (plus x y) p) = plus x (plus y (S p))
    subgoal 2 is:
     forall n _x : nat,
                                                                                   (continues on next page)
```

(continued from previous page)

```
n = _x ->
match _x with
| 0 => True
| S _ => False
end -> plus x y = plus x (plus y _x)
```

The two latter examples feature a wildcard pattern: in this case, the resulting pattern is inferred from the type of the eliminator. In both these examples, it is (plus \_ \_), which matches the subterm plus (plus x y) z thus instantiating the last \_ with z. Note that the tactic:

```
Fail elim/plus_ind: y / _. The command has indeed failed with message: The given pattern matches the term y while the inferred pattern z doesn't
```

triggers an error: in the conclusion of the plus\_ind eliminator, the first argument of the predicate P should be the same as the second argument of plus, in the second argument of P, but y and z do no unify.

Here is an example of a truncated eliminator:

Lemma test p n (n\_gt0 : 0 < n) (pr\_p : prime p) :

#### Example

Consider the goal:

```
p %| \prod_(i <- prime_decomp n | i \in prime_decomp n) i.1 ^ i.2 ->
    exists2 x : nat * nat, x \in prime_decomp n & p = x.1.

Proof.
elim/big_prop: _ => [| u v IHu IHv | [q e] /=].

where the type of the big_prop eliminator is

big_prop: forall (R : Type) (Pb : R -> Type)
    (idx : R) (op1 : R -> R -> R), Pb idx ->
    (forall x y : R, Pb x -> Pb y -> Pb (op1 x y)) ->
    forall (I : Type) (r : seq I) (P : pred I) (F : I -> R),
    (forall i : I, P i -> Pb (F i)) ->
    Pb (\big[op1/idx]_(i <- r | P i) F i).</pre>
```

Since the pattern for the argument of Pb is not specified, the inferred one is used instead: big[\_/\_]\_(i <- \_ i \_ i, and after the introductions, the following goals are generated:

```
subgoal 1 is:
    p %| 1 -> exists2 x : nat * nat, x \in prime_decomp n & p = x.1
subgoal 2 is:
    p %| u * v -> exists2 x : nat * nat, x \in prime_decomp n & p = x.1
subgoal 3 is:
    (q, e) \in prime_decomp n -> p %| q ^ e ->
        exists2 x : nat * nat, x \in prime_decomp n & p = x.1.
```

Note that the pattern matching algorithm instantiated all the variables occurring in the pattern.

#### Interpreting assumptions

Interpreting an assumption in the context of a proof consists in applying to it a lemma before generalizing, and/or decomposing this assumption. For instance, with the extensive use of boolean reflection (see section *Views and reflection*), it is quite frequent to need to decompose the logical interpretation of (the boolean expression of) a fact, rather than the fact itself. This can be achieved by a combination of move: \_ => \_ switches, like in the following example, where || is a notation for the boolean disjunction.

## Example

```
Variables P Q : bool -> Prop.
   P is declared
   Q is declared
Hypothesis P2Q: forall a b, P(a \mid \mid b) \rightarrow Qa.
   P2Q is declared
Lemma test a : P (a | | a) -> True.
   1 subgoal
     P, Q : bool -> Prop
     P2Q : forall a b : bool, P (a || b) \rightarrow Q a
     a : bool
     P (a || a) -> True
move=> HPa; move: {HPa}(P2Q HPa) => HQa.
   1 subgoal
     P, Q : bool -> Prop
     P2Q: forall a b : bool, P (a | | b) -> Q a
     a : bool
     HQa : Q a
     _____
     True
```

which transforms the hypothesis HPa : P a which has been introduced from the initial statement into HQa : Q a. This operation is so common that the tactic shell has specific syntax for it. The following scripts:

(continues on next page)

(continued from previous page)

```
HQa : Q a
------
True
```

are equivalent to the former one. The former script shows how to interpret a fact (already in the context), thanks to the discharge tactical (see section *Discharge*) and the latter, how to interpret the top assumption of a goal. Note that the number of wildcards to be inserted to find the correct application of the view lemma to the hypothesis has been automatically inferred.

The view mechanism is compatible with the case tactic and with the equation name generation mechanism (see section *Generation of equations*):

## Example

```
Variables P Q: bool -> Prop.
    P is declared
    Q is declared
Hypothesis Q2P : forall a b, Q (a \mid \mid b) \rightarrow P a \setminus / P b.
    Q2P is declared
Lemma test a b : Q (a | | b) -> True.
    1 subgoal
      P, Q : bool -> Prop
      Q2P : forall a b : bool, Q (a \mid \mid b) \rightarrow P a \setminus / P b
      a, b : bool
      _____
      Q (a || b) -> True
case/Q2P=> [HPa | HPb].
    2 subgoals
      P, Q : bool -> Prop
      Q2P : forall a b : bool, Q (a | | b \rangle \rightarrow P a | P \rangle
      a, b : bool
      HPa : P a
      _____
      True
    subgoal 2 is:
     True
```

This view tactic performs:

```
move=> HQ; case: \{HQ\}(Q2P HQ) => [HPa \mid HPb].
```

The term on the right of the / view switch is called a *view lemma*. Any SSReflect term coercing to a product type can be used as a view lemma.

The examples we have given so far explicitly provide the direction of the translation to be performed. In fact, view lemmas need not to be oriented. The view mechanism is able to detect which application is relevant for the current goal.

## Example

```
Variables P Q: bool -> Prop.
   P is declared
   Q is declared
Hypothesis PQequiv : forall a b, P (a \mid \mid b) <-> Q a.
   PQequiv is declared
Lemma test a b : P (a | | b) -> True.
   1 subgoal
     P, Q : bool -> Prop
     PQequiv : forall a b : bool, P (a \mid \mid b) <-> Q a
     a, b : bool
      _____
     P (a || b) -> True
move/PQequiv=> HQab.
   1 subgoal
     P, Q : bool -> Prop
     PQequiv : forall a b : bool, P (a \mid \mid b) <-> Q a
     a, b : bool
     HQab : Q a
      _____
     True
```

has the same behavior as the first example above.

The view mechanism can insert automatically a *view hint* to transform the double implication into the expected simple implication. The last script is in fact equivalent to:

```
Lemma test a b : P (a || b) -> True. move/(iffLR \ (PQequiv \_ \_)). where: Lemma \ iffLR \ P \ Q : \ (P <-> \ Q) \ -> \ P \ -> \ Q.
```

## **Specializing assumptions**

The special case when the *head symbol* of the view lemma is a wildcard is used to interpret an assumption by *specializing* it. The view mechanism hence offers the possibility to apply a higher-order assumption to some given arguments.

## Example

```
Lemma test z : (forall x y, x + y = z -> z = x) -> z = 0.

1 subgoal

z : nat

------
```

(continues on next page)

(continued from previous page)

## Interpreting goals

In a similar way, it is also often convenient to changing a goal by turning it into an equivalent proposition. The view mechanism of SSReflect has a special syntax apply/ for combining in a single tactic simultaneous goal interpretation operations and bookkeeping steps.

## Example

The following example use the ~~ prenex notation for boolean negation:

```
Variables P Q: bool -> Prop.
   P is declared
   Q is declared
Hypothesis PQequiv : forall a b, P (a \mid \mid b) <-> Q a.
   PQequiv is declared
Lemma test a : P ((\sim a) \mid\mid a).
   1 subgoal
     P, Q : bool -> Prop
     PQequiv : forall a b : bool, P (a \mid \mid b) <-> Q a
     a : bool
     _____
     P (~~ a || a)
apply/PQequiv.
   1 focused subgoal
    (shelved: 1)
     P, Q : bool -> Prop
     PQequiv : forall a b : bool, P (a | | b) <-> Q a
     a : bool
     _____
     Q (~~ a)
```

thus in this case, the tactic apply/PQequiv is equivalent to apply: (iffRL (PQequiv \_ \_)), where iffRL is the analogue of iffRL for the converse implication.

Any SSReflect term whose type coerces to a double implication can be used as a view for goal interpretation.

Note that the goal interpretation view mechanism supports both apply and exact tactics. As expected, a goal interpretation view command exact/term should solve the current goal or it will fail.

**Warning:** Goal interpretation view tactics are *not* compatible with the bookkeeping tactical => since this would be redundant with the apply: term => \_ construction.

#### **Boolean reflection**

In the Calculus of Inductive Constructions, there is an obvious distinction between logical propositions and boolean values. On the one hand, logical propositions are objects of *sort* Prop which is the carrier of intuitionistic reasoning. Logical connectives in Prop are *types*, which give precise information on the structure of their proofs; this information is automatically exploited by Coq tactics. For example, Coq knows that a proof of A  $\$  B is either a proof of A or a proof of B. The tactics left and right change the goal A  $\$  B to A and B, respectively; dually, the tactic case reduces the goal A  $\$  B => G to two subgoals A => G and B => G.

On the other hand, bool is an inductive *datatype* with two constructors true and false. Logical connectives on bool are *computable functions*, defined by their truth tables, using case analysis:

## Example

```
Definition orb (b1 b2 : bool) := if b1 then true else b2. orb is defined
```

Properties of such connectives are also established using case analysis

#### Example

```
Lemma test b : b || ~~ b = true.

1 subgoal

b : bool

-----
b || ~~ b = true

by case: b.

No more subgoals.
```

Once b is replaced by true in the first goal and by false in the second one, the goals reduce by computations to the trivial true = true.

Thus, Prop and bool are truly complementary: the former supports robust natural deduction, the latter allows brute-force evaluation. SSReflect supplies a generic mechanism to have the best of the two worlds and move freely from a propositional version of a decidable predicate to its boolean version.

First, booleans are injected into propositions using the coercion mechanism:

```
Coercion is_true (b : bool) := b = true.
```

This allows any boolean formula b to be used in a context where Coq would expect a proposition, e.g., after Lemma ...: It is then interpreted as (is\_true b), i.e., the proposition b = true. Coercions are elided by the pretty-printer, so they are essentially transparent to the user.

#### The reflect predicate

To get all the benefits of the boolean reflection, it is in fact convenient to introduce the following inductive predicate reflect to relate propositions and booleans:

```
Inductive reflect (P: Prop): bool -> Type :=
| Reflect_true : P -> reflect P true
| Reflect_false : ~P -> reflect P false.
```

The statement (reflect P b) asserts that (is\_true b) and P are logically equivalent propositions.

For instance, the following lemma:

```
Lemma and P: forall b1 b2, reflect (b1 /\ b2) (b1 && b2).
```

relates the boolean conjunction to the logical one /\. Note that in andP, b1 and b2 are two boolean variables and the proposition b1 /\ b2 hides two coercions. The conjunction of b1 and b2 can then be viewed as b1 /\ b2 or as b1 && b2.

Expressing logical equivalences through this family of inductive types makes possible to take benefit from rewritable equations associated to the case analysis of Coq's inductive types.

Since the equivalence predicate is defined in Coq as:

```
Definition iff (A B: Prop) := (A \rightarrow B) / (B \rightarrow A).
```

where  $/\setminus$  is a notation for and:

```
Inductive and (A B:Prop) : Prop := conj : A \rightarrow B \rightarrow and A B.
```

This make case analysis very different according to the way an equivalence property has been defined.

```
Lemma andE (b1 b2 : bool) : (b1 /\ b2) <-> (b1 && b2).
```

Let us compare the respective behaviors of andE and andP.

## Example

(continues on next page)

(continued from previous page)

```
b1 /\ b2 -> b1

subgoal 2 is:
    (b1 /\ b2) -> ~~ (b1 || b2)
```

Expressing reflection relation through the reflect predicate is hence a very convenient way to deal with classical reasoning, by case analysis. Using the reflect predicate allows moreover to program rich specifications inside its two constructors, which will be automatically taken into account during destruction. This formalisation style gives far more efficient specifications than quantified (double) implications.

A naming convention in SSReflect is to postfix the name of view lemmas with P. For example, orP relates || and \/, negP relates ~~ and ~.

The view mechanism is compatible with reflect predicates.

## Example

```
Lemma test (a b : bool) (Ha : a) (Hb : b) : a / \ b.
   1 subgoal
    a, b : bool
    Ha : a
    Hb : b
    _____
    a /\ b
apply/andP.
   1 focused subgoal
   (shelved: 1)
    a, b : bool
    Ha : a
    Hb: b
     _____
     a && b
Conversely
Lemma test (a b : bool) : a / b \rightarrow a.
   1 subgoal
    a, b : bool
     _____
    a / \ b \rightarrow a
move/andP.
   1 subgoal
    a, b : bool
     _____
     a && b -> a
```

The same tactics can also be used to perform the converse operation, changing a boolean conjunction into a logical one. The view mechanism guesses the direction of the transformation to be used i.e., the constructor

of the reflect predicate which should be chosen.

## General mechanism for interpreting goals and assumptions

#### **Specializing assumptions**

```
The SSReflect tactic:

move/(_ term1 ... termn).

is equivalent to the tactic:

intro top; generalize (top term1 ... termn); clear top.

where top is a fresh name for introducing the top assumption of the current goal.
```

## Interpreting assumptions

The general form of an assumption view tactic is:

```
Variant: move | case / term
```

The term , called the *view lemma* can be:

- a (term coercible to a) function;
- a (possibly quantified) implication;
- a (possibly quantified) double implication;
- a (possibly quantified) instance of the reflect predicate (see section Views and reflection).

Let top be the top assumption in the goal.

There are three steps in the behavior of an assumption view tactic:

- It first introduces top.
- If the type of term is neither a double implication nor an instance of the reflect predicate, then the tactic automatically generalises a term of the form: term term1 ... termn where the terms term1 ... termn instantiate the possible quantified variables of term, in order for (term term1 ... termn top) to be well typed.
- If the type of term is an equivalence, or an instance of the reflect predicate, it generalises a term of the form: (termvh (term term1 ... termn )) where the term termvh inserted is called an assumption interpretation view hint.
- It finally clears top.

For a case/term tactic, the generalisation step is replaced by a case analysis step.

View hints are declared by the user (see section Views and reflection) and are stored in the Hint View database. The proof engine automatically detects from the shape of the top assumption top and of the view lemma term provided to the tactic the appropriate view hint in the database to be inserted.

If term is a double implication, then the view hint will be one of the defined view hints for implication. These hints are by default the ones present in the file ssreflect.v:

```
Lemma iffLR : forall P Q, (P \leftarrow Q) \rightarrow P \rightarrow Q.
```

which transforms a double implication into the left-to-right one, or:

```
Lemma iffRL : forall P Q, (P \iff Q) \implies Q \implies P.
```

which produces the converse implication. In both cases, the two first Prop arguments are implicit.

If term is an instance of the reflect predicate, then A will be one of the defined view hints for the reflect predicate, which are by default the ones present in the file ssrbool.v. These hints are not only used for choosing the appropriate direction of the translation, but they also allow complex transformation, involving negations.

## Example

```
Check introN.
   introN
        : forall (P : Prop) (b : bool), reflect P b -> ~ P -> ~~ b
Lemma test (a b : bool) (Ha : a) (Hb : b) : ~~ (a && b).
   1 subgoal
     a, b : bool
     Ha : a
     Hb : b
     _____
     ~~ (a && b)
apply/andP.
   1 focused subgoal
   (shelved: 1)
     a, b : bool
     Ha : a
     Hb : b
     _____
     ~ (a /\ b)
```

In fact this last script does not exactly use the hint introN, but the more general hint:

```
Check introNTF.
  introNTF
     : forall (P : Prop) (b c : bool),
     reflect P b -> (if c then ~ P else P) -> ~~ b = c
```

The lemma introN is an instantiation of introNF using c := true.

Note that views, being part of  $i\_pattern$ , can be used to interpret assertions too. For example the following script asserts a && b but actually uses its propositional interpretation.

## Example

(continues on next page)

(continued from previous page)

b

Interpreting goals

A goal interpretation view tactic of the form:

## Variant: apply/term

applied to a goal top is interpreted in the following way:

- If the type of term is not an instance of the reflect predicate, nor an equivalence, then the term term is applied to the current goal top, possibly inserting implicit arguments.
- If the type of term is an instance of the reflect predicate or an equivalence, then a *goal interpretation* view hint can possibly be inserted, which corresponds to the application of a term (termvh (term \_ \_ \_ \_)) to the current goal, possibly inserting implicit arguments.

Like assumption interpretation view hints, goal interpretation ones are user-defined lemmas stored (see section *Views and reflection*) in the Hint View database bridging the possible gap between the type of term and the type of the goal.

## Interpreting equivalences

Equivalent boolean propositions are simply equal boolean terms. A special construction helps the user to prove boolean equalities by considering them as logical double implications (between their coerced versions), while performing at the same time logical operations on both sides.

The syntax of double views is:

## Variant: apply/term/term

The first term is the view lemma applied to the left hand side of the equality, while the second term is the one applied to the right hand side.

In this context, the identity view can be used when no view has to be applied:

```
Lemma idP : reflect b1 b1.
```

## Example

(continues on next page)

(continued from previous page)

The same goal can be decomposed in several ways, and the user may choose the most convenient interpretation.

## **Declaring new Hint Views**

Command: Hint View for move / ident | num ?

Command: Hint View for apply / ident | num ?

This command can be used to extend the database of hints for the view mechanism.

As library ssrbool.v already declares a corpus of hints, this feature is probably useful only for users who define their own logical connectives.

The *ident* is the name of the lemma to be declared as a hint. If move is used as tactic, the hint is declared for assumption interpretation tactics, apply declares hints for goal interpretations. Goal interpretation view hints are declared for both simple views and left hand side views. The optional natural number is the number of implicit arguments to be considered for the declared hint view lemma.

Variant: Hint View for apply//ident | num

This variant with a double slash //, declares hint views for right hand sides of double views.

See the files ssreflect.v and ssrbool.v for examples.

## Multiple views

The hypotheses and the goal can be interpreted by applying multiple views in sequence. Both move and apply can be followed by an arbitrary number of /term. The main difference between the following two tactics

```
apply/v1/v2/v3.
apply/v1; apply/v2; apply/v3.
```

is that the former applies all the views to the principal goal. Applying a view with hypotheses generates new goals, and the second line would apply the view v2 to all the goals generated by apply/v1.

Note that the NO-OP intro pattern – can be used to separate two views, making the two following examples equivalent:

```
move=> /v1; move=> /v2.
move=> /v1 - /v2.
```

The tactic move can be used together with the in tactical to pass a given hypothesis to a lemma.

## Example

```
Variable P2Q : P -> Q.
   P2Q is declared
Variable Q2R : Q -> R.
   Q2R is declared
Lemma test (p : P) : True.
   1 subgoal
     P, Q, R : Prop
     P2Q : P -> Q
     Q2R : Q -> R
     p : P
     _____
     True
move/P2Q/Q2R in p.
   1 subgoal
     P, Q, R : Prop
     P2Q : P -> Q
     Q2R : Q \rightarrow R
     p : R
     _____
     True
```

If the list of views is of length two, Hint Views for interpreting equivalences are indeed taken into account, otherwise only single Hint Views are used.

## 5.7.9 SSReflect searching tool



This is the SSReflect extension of the Search command. *qualid* is the name of an open module. This command returns the list of lemmas:

- whose *conclusion* contains a subterm matching the optional first pattern. A reverses the test, producing the list of lemmas whose conclusion does not contain any subterm matching the pattern;
- whose name contains the given string. A prefix reverses the test, producing the list of lemmas whose name does not contain the string. A string that contains symbols or is followed by a scope key, is interpreted as the constant whose notation involves that string (e.g., + for addn), if this is unambiguous; otherwise the diagnostic includes the output of the *Locate* vernacular command.
- whose statement, including assumptions and types, contains a subterm matching the next patterns. If a pattern is prefixed by -, the test is reversed;
- contained in the given list of modules, except the ones in the modules prefixed by a -.

#### Note:

- As for regular terms, patterns can feature scope indications. For instance, the command: Search \_ (\_ + \_)%N. lists all the lemmas whose statement (conclusion or hypotheses) involves an application of the binary operation denoted by the infix + symbol in the N scope (which is SSReflect scope for natural numbers).
- Patterns with holes should be surrounded by parentheses.
- Search always volunteers the expansion of the notation, avoiding the need to execute Locate independently. Moreover, a string fragment looks for any notation that contains fragment as a substring. If the ssrbool.v library is imported, the command: Search "~~". answers:

- A diagnostic is issued if there are different matching notations; it is an error if all matches are partial.
- Similarly, a diagnostic warns about multiple interpretations, and signals an error if there is no default
  one.

- The command Search in M. is a way of obtaining the complete signature of the module M.
- Strings and pattern indications can be interleaved, but the first indication has a special status if it is a pattern, and only filters the conclusion of lemmas:
  - The command: Search (\_ =1 \_) "bij". lists all the lemmas whose conclusion features a =1 and whose name contains the string bij.
  - The command: Search "bij" (\_ =1 \_). lists all the lemmas whose statement, including hypotheses, features a =1 and whose name contains the string bij.

## 5.7.10 Synopsis and Index

#### **Parameters**

SSReflect tactics
d\_tactic ::= elim | case | congr | apply | exact | move

Notation scope
key ::= ident
Module name
modname ::= qualid

Natural number
natural ::= num | ident

where *ident* is an Ltac variable denoting a standard Coq numeral (should not be the name of a tactic which can be followed by a bracket [, like do, have,...)

#### Items and switches

```
( ident : term ?
ssr binder ::=
                ident
binder see Abbreviations.
clear_switch ::= { ident | }
clear switch see Discharge
                           term as
c_pattern ::= term in
                                      ident in term
context pattern see Contextual patterns
d_item ::= occ_switch
                           clear_switch
                                                     ( c pattern )
discharge item see Discharge
gen_item ::= 0 ?
                    ident
                             ( ident )
generalization item see Structure
i_pattern ::=
                                                    occ switch
```

[: iden

```
intro pattern Introduction in the context
i_item ::= clear_switch
                            s_{\tt litem}
                                        i_pattern
                                                      i view
                                                                i block
view Introduction in the context
i_view ::= {}
                 /term
                           /ltac:( tactic )
intro block Introduction in the context
i_block ::= [^ ident ]
                            [^~ ident
                                          num
intro item see Introduction in the context
int mult ::= num | mult mark
multiplier see Iteration
occur. switch see Occurrence selection
mult ::= num ? mult mark
multiplier see Iteration
mult_mark ::= ? !
multiplier mark see Iteration
r_item ::=
                          s_{item}
rewrite item see Rewriting
r_prefix ::= -? int_mult ?
                                               clear switch
                                occ switch
rewrite prefix see Rewriting
                                     in ident in
r_pattern ::= term
                       c_pattern
rewrite pattern see Rewriting
r_step ::= r_prefix r_item
rewrite step see Rewriting
s_item ::= /= // //=
simplify switch see Introduction in the context
Tactics
Note: without loss and suffices are synonyms for wlog and suff respectively.
move
     idtac or hnf (see Bookkeeping)
apply
exact
     application (see The defective tactics)
abstract
     see The abstract tactic and Generating let in context entries with have
```

```
elim
     induction (see The defective tactics)
case
     case analysis (see The defective tactics)
rewrite r_step
     rewrite (see Rewriting)
                                        do
                                           tactic
                                                      [ tactic
     under (see Rewriting under binders)
over
     over (see The over tactic)
have i item
               i pattern
                                        ssr binder
                             s item
have i_item
               i_pattern
                             s_{item}
                                        ssr_binder
                                                        : term by tactic
have suff clear_switch ?
                           i_pattern
                                        : term
have suff clear_switch ?
                          i pattern
                                        : term by tactic
gen have ident,
                    i_pattern | ?
                                 : gen_item
generally have ident,
                                        gen_item
                          i_pattern
     forward chaining (see Structure)
wlog suff i_item : gen_item
                                      clear switch
     specializing (see Structure)
suff i_item * i_pattern ?
                                           : term by tactic
                            ssr_binder
suffices i item
                   i_pattern
                                 ssr binder
suff have clear_switch
                                           : term by tactic
                             i_pattern
suffices have clear_switch
                                  i_pattern
     backchaining (see Structure)
pose ident := term
     local definition (see Definitions)
Variant: pose ident ssr_binder
     local function definition
Variant: pose fix fix_body
    local fix definition
Variant: pose cofix fix_body
     local cofix definition
set ident : term := occ_switch
                                               ( c_pattern)
                                      term
     abbreviation (see Abbreviations)
```

```
unlock r_prefix ident
unlock (see Locking, unlocking)

congr num term
congruence (see Congruence)
```

#### **Tacticals**

```
tactic += d_tactic ident : d_item | clear_switch |
discharge Discharge
tactic += tactic => i item
introduction see Introduction in the context
                                  clear switch
tactic += tactic in gen_item
localization see Localization
tactic += do mult
iteration see Iteration
                              last num
tactic += tactic ; first
selector see Selectors
                             last num ?
tactic += tactic ; first
rotation see Selectors
tactic += by tactic
                         [ tactic
closing see Terminators
```

## Commands

## **Settings**

## Flag: Debug Ssreflect

Developer only. Print debug information on reflect.

# Flag: Debug SsrMatching

Developer only. Print debug information on SSR matching.

**CHAPTER** 

SIX

## **USER EXTENSIONS**

## 6.1 Syntax extensions and interpretation scopes

In this chapter, we introduce advanced commands to modify the way Coq parses and prints objects, i.e. the translations between the concrete and internal representations of terms and commands.

The main commands to provide custom symbolic notations for terms are *Notation* and *Infix*; they will be described in the *next section*. There is also a variant of *Notation* which does not modify the parser; this provides a form of *abbreviation*. It is sometimes expected that the same symbolic notation has different meanings in different contexts; to achieve this form of overloading, Coq offers a notion of *interpretation scopes*. The main command to provide custom notations for tactics is *Tactic Notation*.

## 6.1.1 Notations

#### **Basic notations**

## Command: Notation

A notation is a symbolic expression denoting some term or term pattern.

A typical notation is the use of the infix symbol  $\land$  to denote the logical conjunction (and). Such a notation is declared by

```
Notation "A / \setminus B" := (and A B).
```

The expression (and A B) is the abbreviated term and the string "A  $/\$  B" (called a *notation*) tells how it is symbolically written.

A notation is always surrounded by double quotes (except when the abbreviation has the form of an ordinary applicative expression; see *Abbreviations*). The notation is composed of *tokens* separated by spaces. Identifiers in the string (such as A and B) are the *parameters* of the notation. Each of them must occur at least once in the denoted term. The other elements of the string (such as  $\wedge$ ) are the *symbols*.

An identifier can be used as a symbol but it must be surrounded by single quotes to avoid the confusion with a parameter. Similarly, every symbol of at least 3 characters and starting with a simple quote must be quoted (then it starts by two single quotes). Here is an example.

```
Notation "'IF' c1 'then' c2 'else' c3" := (IF_then_else c1 c2 c3).
```

A notation binds a syntactic expression to a term. Unless the parser and pretty-printer of Coq already know how to deal with the syntactic expression (see *Reserving notations*), explicit precedences and associativity rules have to be given.

**Note:** The right-hand side of a notation is interpreted at the time the notation is given. In particular, disambiguation of constants, *implicit arguments* and other notations are resolved at the time of the declaration of the notation.

#### Precedences and associativity

Mixing different symbolic notations in the same text may cause serious parsing ambiguity. To deal with the ambiguity of notations, Coq uses precedence levels ranging from 0 to 100 (plus one extra level numbered 200) and associativity rules.

Consider for example the new notation

```
Notation "A \backslash / B" := (or A B).
```

Clearly, an expression such as forall A:Prop, True /\ A \/ A \/ False is ambiguous. To tell the Coq parser how to interpret the expression, a priority between the symbols /\ and \/ has to be given. Assume for instance that we want conjunction to bind more than disjunction. This is expressed by assigning a precedence level to each notation, knowing that a lower level binds more than a higher level. Hence the level for disjunction must be higher than the level for conjunction.

Since connectives are not tight articulation points of a text, it is reasonable to choose levels not so far from the highest level which is 100, for example 85 for disjunction and 80 for conjunction<sup>308</sup>.

Similarly, an associativity is needed to decide whether True /\ False /\ False defaults to True /\ (False /\ False) (right associativity) or to (True /\ False) /\ False (left associativity). We may even consider that the expression is not well-formed and that parentheses are mandatory (this is a "no associativity")<sup>309</sup>. We do not know of a special convention of the associativity of disjunction and conjunction, so let us apply for instance a right associativity (which is the choice of Coq).

Precedence levels and associativity rules of notations have to be given between parentheses in a list of modifiers that the Notation command understands. Here is how the previous examples refine.

```
Notation "A /\ B" := (and A B) (at level 80, right associativity). Notation "A \/ B" := (or A B) (at level 85, right associativity).
```

By default, a notation is considered nonassociative, but the precedence level is mandatory (except for special cases whose level is canonical). The level is either a number or the phrase next level whose meaning is obvious. Some associativities are predefined in the Notations module.

## **Complex notations**

Notations can be made from arbitrarily complex symbols. One can for instance define prefix notations.

```
Notation "\sim x" := (not x) (at level 75, right associativity).
```

One can also define notations for incomplete terms, with the hole expected to be inferred during type checking.

```
Notation "x = y" := (@eq _ x y) (at level 70, no associativity).
```

 $<sup>^{308}</sup>$  which are the levels effectively chosen in the current implementation of Coq

<sup>309</sup> Coq accepts notations declared as nonassociative but the parser on which Coq is built, namely Camlp5, currently does not implement no associativity and replaces it with left associativity; hence it is the same for Coq: no associativity is in fact left associativity for the purposes of parsing

One can define *closed* notations whose both sides are symbols. In this case, the default precedence level for the inner sub-expression is 200, and the default level for the notation itself is 0.

```
Notation "( x , y )" := (@pair _ x y).
```

One can also define notations for binders.

```
Notation "{ x : A | P}" := (sig A (fun x \Rightarrow P)).
```

In the last case though, there is a conflict with the notation for type casts. The notation for types casts, as shown by the command  $Print\ Grammar\ constr$  is at level 100. To avoid x: A being parsed as a type cast, it is necessary to put x at a level below 100, typically 99. Hence, a correct definition is the following:

```
Notation "{ x : A \mid P}" := (sig A (fun x \Rightarrow P)) (x at level 99). Setting notation at level 0.
```

More generally, it is required that notations are explicitly factorized on the left. See the next section for more about factorization.

#### Simple factorization rules

Coq extensible parsing is performed by *Camlp5* which is essentially a LL1 parser: it decides which notation to parse by looking at tokens from left to right. Hence, some care has to be taken not to hide already existing rules by new rules. Some simple left factorization work has to be done. Here is an example.

```
Notation "x < y" := (lt x y) (at level 70). Fail Notation "x < y < z" := (x < y /\ y < z) (at level 70). The command has indeed failed with message: Notation "_ < _ < _" is already defined at level 70 with arguments constr at next level, constr at next level while it is now required to be at level 70 with arguments constr at next level, constr unknown level, constr at next level.
```

In order to factorize the left part of the rules, the subexpression referred to by y has to be at the same level in both rules. However the default behavior puts y at the next level below 70 in the first rule (no associativity is the default), and at level 200 in the second rule (level 200 is the default for inner expressions). To fix this, we need to force the parsing level of y, as follows.

```
Notation "x < y" := (lt x y) (at level 70).
Notation "x < y < z" := (x < y /\ y < z) (at level 70, y at next level).
```

For the sake of factorization with Coq predefined rules, simple rules have to be observed for notations starting with a symbol, e.g., rules starting with "{" or "(" should be put at level 0. The list of Coq predefined notations can be found in the chapter on *The Coq library*.

#### Command: Print Grammar constr.

This command displays the current state of the Coq term parser.

## Command: Print Grammar pattern.

This displays the state of the subparser of patterns (the parser used in the grammar of the match with constructions).

## Displaying symbolic notations

The command Notation has an effect both on the Coq parser and on the Coq printer. For example:

```
Check (and True True).
    True /\ True
    : Prop
```

However, printing, especially pretty-printing, also requires some care. We may want specific indentations, line breaks, alignment if on several lines, etc. For pretty-printing, Coq relies on OCaml formatting library, which provides indentation and automatic line breaks depending on page width by means of *formatting* boxes

The default printing of notations is rudimentary. For printing a notation, a formatting box is opened in such a way that if the notation and its arguments cannot fit on a single line, a line break is inserted before the symbols of the notation and the arguments on the next lines are aligned with the argument on the first line.

A first, simple control that a user can have on the printing of a notation is the insertion of spaces at some places of the notation. This is performed by adding extra spaces between the symbols and parameters: each extra space (other than the single space needed to separate the components) is interpreted as a space to be inserted by the printer. Here is an example showing how to add spaces around the bar of the notation.

```
Notation "{{ x : A | P }}" := (sig (fun x : A => P)) (at level 0, x at level 99). Check (sig (fun x : nat => x=x)).  \{\{x : nat \mid x = x\}\}  : Set
```

The second, more powerful control on printing is by using the format modifier. Here is an example

```
Notation "'If' c1 'then' c2 'else' c3" := (IF_then_else c1 c2 c3)
(at level 200, right associativity, format
"'[v ''If' c1'/''[''then' c2']''/''[''else' c3']'']'").
   Identifier 'If' now a keyword
Check
  (IF_then_else (IF_then_else True False True)
    (IF_then_else True False True)
    (IF_then_else True False True)).
   If If True
         then False
         else True
      then If True
              then False
              else True
      else If True
              then False
              else True
        : Prop
```

A *format* is an extension of the string denoting the notation with the possible following elements delimited by single quotes:

- tokens of the form '/' are translated into breaking points. If there is a line break, indents the number of spaces appearing after the "/" (no indentation in the example)
- tokens of the form '//' force writing on a new line
- well-bracketed pairs of tokens of the form '[ ' and ']' are translated into printing boxes; if there is a line break, an extra indentation of the number of spaces after the "[" is applied
- well-bracketed pairs of tokens of the form '[hv ' and ']' are translated into horizontal-or-else-vertical printing boxes; if the content of the box does not fit on a single line, then every breaking point forces a

new line and an extra indentation of the number of spaces after the "[hv" is applied at the beginning of each new line

- well-bracketed pairs of tokens of the form '[v ' and ']' are translated into vertical printing boxes; every breaking point forces a new line, even if the line is large enough to display the whole content of the box, and an extra indentation of the number of spaces after the "[v" is applied at the beginning of each new line (3 spaces in the example)
- extra spaces in other tokens are preserved in the output

Notations disappear when a section is closed. No typing of the denoted expression is performed at definition time. Type checking is done only at the time of use of the notation.

**Note:** Sometimes, a notation is expected only for the parser. To do so, the option only parsing is allowed in the list of *modifiers* of *Notation*. Conversely, the only printing *modifier* can be used to declare that a notation should only be used for printing and should not declare a parsing rule. In particular, such notations do not modify the parser.

#### The Infix command

The *Infix* command is a shortening for declaring notations of infix symbols.

```
Command: Infix "symbol" := term (modifiers).

This command is equivalent to

Notation "x symbol y" := (term x y) (modifiers).

where x and y are fresh names. Here is an example.

Infix "/\" := and (at level 80, right associativity).
```

#### Reserving notations

# Command: Reserved Notation string (modifiers)

A given notation may be used in different contexts. Coq expects all uses of the notation to be defined at the same precedence and with the same associativity. To avoid giving the precedence and associativity every time, this command declares a parsing rule (string) in advance without giving its interpretation. Here is an example from the initial state of Coq.

```
Reserved Notation "x = y" (at level 70, no associativity).
```

Reserving a notation is also useful for simultaneously defining an inductive type or a recursive constant and a notation for it.

**Note:** The notations mentioned in the module *Notations* are reserved. Hence their precedence and associativity cannot be changed.

```
Variant: Reserved Infix "symbol" modifiers *
```

This command declares an infix parsing rule without giving its interpretation.

#### Simultaneous definition of terms and notations

Thanks to reserved notations, the inductive, co-inductive, record, recursive and corecursive definitions can benefit from customized notations. To do this, insert a where notation clause after the definition of the (co)inductive type or (co)recursive term (or after the definition of each of them in case of mutual definitions). The exact syntax is given by <code>decl\_notation</code> for inductive, co-inductive, recursive and corecursive definitions and in <code>Record types</code> for records. Here are examples:

#### Displaying information about notations

## Flag: Printing Notations

Controls whether to use notations for printing terms wherever possible. Default is on.

#### See also:

**Printing All** To disable other elements in addition to notations.

#### Locating notations

To know to which notations a given symbol belongs to, use the *Locate* command. You can call it on any (composite) symbol surrounded by double quotes. To locate a particular notation, use a string where the variables of the notation are replaced by "\_" and where possible single quotes inserted around identifiers or tokens starting with a single quote are dropped.

## **Notations and binders**

Notations can include binders. This section lists different ways to deal with binders. For further examples, see also *Notations with recursive patterns involving binders*.

#### Binders bound in the notation and parsed as identifiers

Here is the basic example of a notation using a binder:

```
Notation "'sigma' x : A, B" := (sigT (fun x : A \Rightarrow B)) (at level 200, x ident, A at level 200, right associativity).
```

The binding variables in the right-hand side that occur as a parameter of the notation (here x) dynamically bind all the occurrences in their respective binding scope after instantiation of the parameters of the notation. This means that the term bound to B can refer to the variable name bound to x as shown in the following application of the notation:

```
Check sigma z : nat, z = 0.
sigma z : nat, z = 0
: Set
```

Notice the modifier x ident in the declaration of the notation. It tells to parse x as a single identifier.

## Binders bound in the notation and parsed as patterns

In the same way as patterns can be used as binders, as in fun '(x,y) => x+y or fun '(existT \_ x \_) => x, notations can be defined so that any pattern can be used in place of the binder. Here is an example:

```
Notation "'subset' ' p , P " := (sig (fun p => P))
  (at level 200, p pattern, format "'subset' ' p , P").
Check subset '(x,y), x+y=0.
    subset '(x, y), x + y = 0
    : Set
```

The modifier p pattern in the declaration of the notation tells to parse p as a pattern. Note that a single variable is both an identifier and a pattern, so, e.g., the following also works:

```
Check subset 'x, x=0.
subset 'x, x = 0
: Set
```

If one wants to prevent such a notation to be used for printing when the pattern is reduced to a single identifier, one has to use instead the *modifier* p strict pattern. For parsing, however, a strict pattern will continue to include the case of a variable. Here is an example showing the difference:

```
Notation "'subset_bis' ' p , P" := (sig (fun p => P))
  (at level 200, p strict pattern).
Notation "'subset_bis' p , P " := (sig (fun p => P))
  (at level 200, p ident).

Check subset_bis 'x, x=0.
    subset_bis x, x = 0
    : Set
```

The default level for a pattern is 0. One can use a different level by using pattern at level n where the scale is the same as the one for terms (see *Notations*).

#### Binders bound in the notation and parsed as terms

Sometimes, for the sake of factorization of rules, a binder has to be parsed as a term. This is typically the case for a notation such as the following:

```
Notation "{ x : A | P }" := (sig (fun x : A \Rightarrow P)) (at level 0, x at level 99 as ident).
```

This is so because the grammar also contains rules starting with {} and followed by a term, such as the rule for the notation { A } + { B } for the constant sumbool (see *Specification*).

Then, in the rule, x ident is replaced by x at level 99 as ident meaning that x is parsed as a term at level 99 (as done in the notation for sumbool), but that this term has actually to be an identifier.

The notation  $\{x \mid P\}$  is already defined in the standard library with the as ident modifier. We cannot redefine it but one can define an alternative notation, say  $\{p \in P\}$ , using instead as pattern.

```
Notation "{ p 'such' 'that' P }" := (sig (fun p \Rightarrow P)) (at level 0, p at level 99 as pattern).
```

Then, the following works:

```
Check \{(x,y) \text{ such that } x+y=0\}.

\{(x, y) \text{ such that } x+y=0\}

: Set
```

To enforce that the pattern should not be used for printing when it is just an identifier, one could have said p at level 99 as strict pattern.

Note also that in the absence of a as ident, as strict pattern or as pattern modifiers, the default is to consider sub-expressions occurring in binding position and parsed as terms to be as ident.

## Binders not bound in the notation

We can also have binders in the right-hand side of a notation which are not themselves bound in the notation. In this case, the binders are considered up to renaming of the internal binder. E.g., for the notation

```
Notation "'exists_different' n" := (exists p:nat, p<>n) (at level 200).
```

the next command fails because p does not bind in the instance of n.

```
Fail Check (exists_different p).
   The command has indeed failed with message:
   The reference p was not found in the current environment.
Notation "[> a , .. , b <]" :=
   (cons a .. (cons b nil) .., cons b .. (cons a nil) ..).</pre>
```

## Notations with recursive patterns

A mechanism is provided for declaring elementary notations with recursive patterns. The basic example is:

```
Notation "[ x ; .. ; y ]" := (cons x .. (cons y nil) ..). Setting notation at level 0.
```

On the right-hand side, an extra construction of the form .. t .. can be used. Notice that .. is part of the Coq syntax and it must not be confused with the three-dots notation "..." used in this manual to denote a sequence of arbitrary size.

On the left-hand side, the part "x s .. s y" of the notation parses any number of times (but at least once) a sequence of expressions separated by the sequence of tokens s (in the example, s is just ";").

The right-hand side must contain a subterm of the form either  $\phi(x, ..., \phi(y,t) ...)$  or  $\phi(y, ..., \phi(x,t) ...)$  where  $\varphi([\,]_E,[\,]_I)$ , called the *iterator* of the recursive notation is an arbitrary expression with distinguished placeholders and where t is called the *terminating expression* of the recursive notation. In the example, we choose the names x and y but in practice they can of course be chosen arbitrarily. Note that the placeholder  $[\,]_I$  has to occur only once but  $[\,]_E$  can occur several times.

Parsing the notation produces a list of expressions which are used to fill the first placeholder of the iterating pattern which itself is repeatedly nested as many times as the length of the list, the second placeholder being the nesting point. In the innermost occurrence of the nested iterating pattern, the second placeholder is finally filled with the terminating expression.

In the example above, the iterator  $\varphi([\ ]_E,[\ ]_I)$  is  $cons[\ ]_E[\ ]_I$  and the terminating expression is nil. Here are other examples:

Notations with recursive patterns can be reserved like standard notations, they can also be declared within *interpretation scopes*.

## Notations with recursive patterns involving binders

Recursive notations can also be used with binders. The basic example is:

```
Notation "'exists' x .. y , p" :=  (\text{ex } (\text{fun } x \Rightarrow .. (\text{ex } (\text{fun } y \Rightarrow p)) \ ..)) \\ (\text{at level 200, x binder, y binder, right associativity}).
```

The principle is the same as in *Notations with recursive patterns* except that in the iterator  $\varphi([]_E,[]_I)$ , the placeholder  $[]_E$  can also occur in position of the binding variable of a fun or a forall.

To specify that the part "x .. y" of the notation parses a sequence of binders, x and y must be marked as binder in the list of modifiers of the notation. The binders of the parsed sequence are used to fill the occurrences of the first placeholder of the iterating pattern which is repeatedly nested as many times as the number of binders generated. If ever the generalization operator ' (see *Implicit generalization*) is used in the binding list, the added binders are taken into account too.

There are two flavors of binder parsing. If x and y are marked as binder, then a sequence such as a b c: T will be accepted and interpreted as the sequence of binders (a:T) (b:T) (c:T). For instance, in the notation above, the syntax exists a b: nat, a = b is valid.

The variables x and y can also be marked as closed binder in which case only well-bracketed binders of the form  $(a \ b \ c:T)$  or  $\{a \ b \ c:T\}$  etc. are accepted.

With closed binders, the recursive sequence in the left-hand side can be of the more general form  $x \, s \, \dots \, s$  y where s is an arbitrary sequence of tokens. With open binders though, s has to be empty. Here is an example of recursive notation with closed binders:

```
Notation "'mylet' f x .. y := t 'in' u":=
(let f := fun x => .. (fun y => t) .. in u)
(at level 200, x closed binder, y closed binder, right associativity).
```

A recursive pattern for binders can be used in position of a recursive pattern for terms. Here is an example:

```
Notation "'FUNAPP' x .. y , f" := 
 (fun x => .. (fun y => (.. (f x) ..) y ) ..) 
 (at level 200, x binder, y binder, right associativity).
```

If an occurrence of the  $[\ ]_E$  is not in position of a binding variable but of a term, it is the name used in the binding which is used. Here is an example:

```
Notation "'exists_non_null' x .. y , P" := (ex (fun x => x <> 0 /\ .. (ex (fun y => y <> 0 /\ P)) ..)) (at level 200, x binder).
```

## **Predefined entries**

By default, sub-expressions are parsed as terms and the corresponding grammar entry is called **constr**. However, one may sometimes want to restrict the syntax of terms in a notation. For instance, the following notation will accept to parse only global reference in position of **x**:

```
Notation "'apply' f a1 .. an" := (.. (f a1) .. an) (at level 10, f global, a1, an at level 9).
```

In addition to global, one can restrict the syntax of a sub-expression by using the entry names ident or pattern already seen in *Binders not bound in the notation*, even when the corresponding expression is not used as a binder in the right-hand side. E.g.:

```
Notation "'apply_id' f a1 .. an" := (... (f a1) ... an) (at level 10, f ident, a1, an at level 9).
```

#### **Custom entries**

#### Command: Declare Custom Entry ident

This command allows to define new grammar entries, called *custom entries*, that can later be referred to using the entry name custom *ident*.

#### Example

For instance, we may want to define an ad hoc parser for arithmetical operations and proceed as follows:

(continues on next page)

```
Declare Custom Entry expr.
Notation "[ e ]" := e (e custom expr at level 2).
    Setting notation at level 0.
Notation "1" := One (in custom expr at level 0).
Notation "x y" := (Mul x y) (in custom expr at level 1, left associativity).
Notation "x + y" := (Add x y) (in custom expr at level 2, left associativity).
Notation "(x)" := x (in custom expr, x at level 2).
    Setting notation at level 0.
Notation "\{x\}" := x (in custom expr, x constr).
    Setting notation at level 0.
Notation "x" := x (in custom expr at level 0, x ident).
Axiom f : nat -> Expr.
    f is declared
Check fun x y z \Rightarrow [1 + y z + {f x}].
    fun (x : nat) (y z : Expr) \Rightarrow [1 + y z + {f x}]
         : nat -> Expr -> Expr -> Expr
Unset Printing Notations.
Check fun x y z \Rightarrow [1 + y z + {f x}].
    fun (x : nat) (y z : Expr) \Rightarrow Add (Add One (Mul y z)) (f x)
         : forall (_ : nat) (_ : Expr) (_ : Expr), Expr
Set Printing Notations.
Check fun e => match e with
[1 + 1] => [1]
| [x y + z] \Rightarrow [x + y z]
| y => [y + e]
end.
    fun e : Expr =>
    match e with
    | [1 + 1] => [1]
    | [x y + z] \Rightarrow [x + y z]
    | _ => [e + e]
    end
         : Expr -> Expr
```

Custom entries have levels, like the main grammar of terms and grammar of patterns have. The lower level is 0 and this is the level used by default to put rules delimited with tokens on both ends. The level is left to be inferred by Coq when using in custom *ident*. The level is otherwise given explicitly by using the syntax in custom *ident* at level *num*, where *num* refers to the level.

Levels are cumulative: a notation at level n of which the left end is a term shall use rules at level less than n to parse this subterm. More precisely, it shall use rules at level strictly less than n if the rule is declared with right associativity and rules at level less or equal than n if the rule is declared with left associativity. Similarly, a notation at level n of which the right end is a term shall use by default rules at level strictly less than n to parse this subterm if the rule is declared left associative and rules at level less or equal than n if the rule is declared right associative. This is what happens for instance in the rule

```
Notation "x + y" := (Add x y) (in custom expr at level 2, left associativity).
```

where x is any expression parsed in entry expr at level less or equal than 2 (including, recursively, the given rule) and y is any expression parsed in entry expr at level strictly less than 2.

Rules associated to an entry can refer different sub-entries. The grammar entry name constr can be used to refer to the main grammar of term as in the rule

```
Notation "\{x\}" := x (in custom expr at level 0, x constr).
```

which indicates that the subterm x should be parsed using the main grammar. If not indicated, the level is computed as for notations in constr, e.g. using 200 as default level for inner sub-expressions. The level can otherwise be indicated explicitly by using constr at level n for some n, or constr at next level.

Conversely, custom entries can be used to parse sub-expressions of the main grammar, or from another custom entry as is the case in

```
Notation "[ e ]" := e (e custom expr at level 2).
```

to indicate that **e** has to be parsed at level **2** of the grammar associated to the custom entry **expr**. The level can be omitted, as in

```
Notation "[ e ]" := e (e custom expr).
```

in which case Coq infer it. If the sub-expression is at a border of the notation (as e.g. x and y in x + y), the level is determined by the associativity. If the sub-expression is not at the border of the notation (as e.g. e in "[ e ]), the level is inferred to be the highest level used for the entry. In particular, this level depends on the highest level existing in the entry at the time of use of the notation.

In the absence of an explicit entry for parsing or printing a sub-expression of a notation in a custom entry, the default is to consider that this sub-expression is parsed or printed in the same custom entry where the notation is defined. In particular, if x at level n is used for a sub-expression of a notation defined in custom entry foo, it shall be understood the same as x custom foo at level n.

In general, rules are required to be *productive* on the right-hand side, i.e. that they are bound to an expression which is not reduced to a single variable. If the rule is not productive on the right-hand side, as it is the case above for

```
Notation "( x )" := x (in custom expr at level 0, x at level 2). and  \text{Notation "} \{ \text{ x } \} \text{"} := \text{x (in custom expr at level 0, x constr)}.
```

it is used as a *grammar coercion* which means that it is used to parse or print an expression which is not available in the current grammar at the current level of parsing or printing for this grammar but which is available in another grammar or in another level of the current grammar. For instance,

```
Notation "(x)" := x (in custom expr at level 0, x at level 2).
```

tells that parentheses can be inserted to parse or print an expression declared at level 2 of expr whenever this expression is expected to be used as a subterm at level 0 or 1. This allows for instance to parse and print Add x y as a subterm of Mul (Add x y) z using the syntax (x + y) z. Similarly,

```
Notation "\{x\}" := x (in custom expr at level 0, x constr).
```

gives a way to let any arbitrary expression which is not handled by the custom entry expr be parsed or printed by the main grammar of term up to the insertion of a pair of curly brackets.

```
Command: Print Custom Grammar ident.
```

This displays the state of the grammar for terms associated to the custom entry *ident*.

#### Summary

# Syntax of notations

The different syntactic forms taken by the commands declaring notations are given below. The optional scope is described in *Interpretation scopes*.

```
[Local] Notation string := term [(modifiers)] [: scope].
notation
                   ::=
                          [Local] Infix string := qualid [(modifiers)] [: scope].
                          [Local] Reserved Notation string [(modifiers)] .
                          Inductive ind_body [decl_notation] with ... with ind_body [decl_notation].
                         CoInductive ind_body [decl_notation] with ... with ind_body [decl_notation].
                         Fixpoint fix_body [decl_notation] with ... with fix_body [decl_notation].
                         CoFixpoint cofix_body [decl_notation] with ... with cofix_body [decl_notation].
                          [Local] Declare Custom Entry ident.
decl_notation
                          [where string := term [: scope] and ... and string := term [: scope]].
                   ::=
modifiers
                         modifier, ..., modifier
                   ::=
modifier
                   ::=
                         at level num
                         in custom ident
                         in custom ident at level num
                          ident , ... , ident at level num [binderinterp]
                          ident , ... , ident at next level [binderinterp]
                          ident explicit_subentry
                         left associativity
                         right associativity
                         no associativity
                         only parsing
                         only printing
                         format string
explicit_subentry ::=
                         ident
                         global
                         bigint
                          [strict] pattern [at level num]
                         binder
                         closed binder
                         constr [binderinterp]
                         constr at level num [binderinterp]
                         constr at next level [binderinterp]
                         custom [binderinterp]
                         custom at level num [binderinterp]
                         custom at next level [binderinterp]
binderinterp
                         as ident
                   ::=
                         as pattern
                         as strict pattern
```

**Note:** No typing of the denoted expression is performed at definition time. Type checking is done only at the time of use of the notation.

Note: Some examples of Notation may be found in the files composing the initial state of Coq (see directory

\$COQLIB/theories/Init).

Note: The notation "{ x }" has a special status in the main grammars of terms and patterns so that complex notations of the form "x + { y }" or "x \* { y }" can be nested with correct precedences. Especially, every notation involving a pattern of the form "{ x }" is parsed as a notation where the pattern "{ x }" has been simply replaced by "x" and the curly brackets are parsed separately. E.g. "y + { z }" is not parsed as a term of the given form but as a term of the form "y + z" where z has been parsed using the rule parsing "{ x }". Especially, level and precedences for a rule including patterns of the form "{ x }" are relative not to the textual notation but to the notation where the curly brackets have been removed (e.g. the level and the associativity given to some notation, say "{ y } & { z }" in fact applies to the underlying "{ x }"-free rule which is "y & z").

Note: Notations such as "( p | q )" (or starting with "( x | ", more generally) are deprecated as they conflict with the syntax for nested disjunctive patterns (see  $Extended\ pattern\ matching$ ), and are not honored in pattern expressions.

Warning: Use of string Notation is deprecated as it is inconsistent with pattern syntax. This warning is disabled by default to avoid spurious diagnostics due to legacy notation in the Coq standard library. It can be turned on with the -w disj-pattern-notation flag.

#### Persistence of notations

Notations disappear when a section is closed.

# Command: Local Notation notation

Notations survive modules unless the command Local Notation is used instead of Notation.

# Command: Local Declare Custom Entry ident

Custom entries survive modules unless the command Local Declare Custom Entry is used instead of Declare Custom Entry.

# **6.1.2** Interpretation scopes

An interpretation scope is a set of notations for terms with their interpretations. Interpretation scopes provide a weak, purely syntactical form of notation overloading: the same notation, for instance the infix symbol +, can be used to denote distinct definitions of the additive operator. Depending on which interpretation scopes are currently open, the interpretation is different. Interpretation scopes can include an interpretation for numerals and strings, either at the OCaml level or using Numeral Notation or String Notation.

#### Command: Declare Scope scope

This adds a new scope named *scope*. Note that the initial state of Coq declares by default the following interpretation scopes: core\_scope, type\_scope, function\_scope, nat\_scope, bool\_scope, list\_scope, int\_scope, uint\_scope.

The syntax to associate a notation to a scope is given *above*. Here is a typical example which declares the notation for conjunction in the scope type\_scope.

Notation "A  $/\$  B" := (and A B) : type\_scope.

**Note:** A notation not defined in a scope is called a *lonely* notation. No example of lonely notations can be found in the initial state of Coq though.

#### Global interpretation rules for notations

At any time, the interpretation of a notation for a term is done within a *stack* of interpretation scopes and lonely notations. In case a notation has several interpretations, the actual interpretation is the one defined by (or in) the more recently declared (or opened) lonely notation (or interpretation scope) which defines this notation. Typically if a given notation is defined in some scope scope but has also an interpretation not assigned to a scope, then, if scope is open before the lonely interpretation is declared, then the lonely interpretation is used (and this is the case even if the interpretation of the notation in scope is given after the lonely interpretation: otherwise said, only the order of lonely interpretations and opening of scopes matters, and not the declaration of interpretations within a scope).

#### Command: Open Scope scope

The command to add a scope to the interpretation scope stack is Open Scope scope.

# Command: Close Scope scope

It is also possible to remove a scope from the interpretation scope stack by using the command Close Scope scope.

Notice that this command does not only cancel the last Open Scope but all its invocations.

**Note:** Open Scope and Close Scope do not survive the end of sections where they occur. When defined outside of a section, they are exported to the modules that import the module where they occur.

# Command: Local Open Scope scope.

# Command: Local Close Scope scope.

These variants are not exported to the modules that import the module where they occur, even if outside a section.

# Command: Global Open Scope scope.

# Command: Global Close Scope scope.

These variants survive sections. They behave as if Global were absent when not inside a section.

# Local interpretation rules for notations

In addition to the global rules of interpretation of notations, some ways to change the interpretation of subterms are available.

# Local opening of an interpretation scope

It is possible to locally extend the interpretation scope stack using the syntax (term)%ident (or simply term%ident for atomic terms), where ident is a special identifier called  $delimiting\ key$  and bound to a given scope.

In such a situation, the term term, and all its subterms, are interpreted in the scope stack extended with the scope bound to ident.

# Command: Delimit Scope scope with ident

To bind a delimiting key to a scope, use the command Delimit Scope scope with ident

#### Command: Undelimit Scope scope

To remove a delimiting key of a scope, use the command Undelimit Scope scope

# Binding arguments of a constant to an interpretation scope

Command: Arguments qualid name%ident

It is possible to set in advance that some arguments of a given constant have to be interpreted in a given scope. The command is Arguments qualid name%ident where the list is a prefix of the arguments of qualid optionally annotated with their scope ident. Grouping round parentheses can be used to decorate multiple arguments with the same scope. ident can be either a scope name or its delimiting key. For example the following command puts the first two arguments of plus\_fct in the scope delimited by the key F (Rfun\_scope) and the last argument in the scope delimited by the key R  $(R_scope).$ 

Arguments plus\_fct (f1 f2)%F x%R.

The Arguments command accepts scopes decoration to all grouping parentheses. In the following example arguments A and B are marked as maximally inserted implicit arguments and are put into the type scope scope.

Arguments respectful {A B}%type (R R')%signature \_ \_.

When interpreting a term, if some of the arguments of qualid are built from a notation, then this notation is interpreted in the scope stack extended by the scope bound (if any) to this argument. The effect of the scope is limited to the argument itself. It does not propagate to subterms but the subterms that, after interpretation of the notation, turn to be themselves arguments of a reference are interpreted accordingly to the argument scopes bound to this reference.

# Variant: Arguments qualid : clear scopes

This command can be used to clear argument scopes of qualid.

# Variant: Arguments qualid name%ident : extra scopes

Defines extra argument scopes, to be used in case of coercion to Funclass (see the Implicit Coercions chapter) or with a computed type.

Variant: Global Arguments qualid name%ident

This behaves like Arguments qualid name%ident but survives when a section is closed instead of stopping working at section closing. Without the Global modifier, the effect of the command stops when the section it belongs to ends.

Variant: Local Arguments qualid name%ident

This behaves like Arguments qualid name%ident but does not survive modules and files. Without the Local modifier, the effect of the command is visible from within other modules or files.

# See also:

The command *About* can be used to show the scopes bound to the arguments of a function.

**Note:** In notations, the subterms matching the identifiers of the notations are interpreted in the scope in which the identifiers occurred at the time of the declaration of the notation. Here is an example:

```
Parameter g : bool -> bool.
    g is declared
Declare Scope mybool_scope.
Notation "@@" := true (only parsing) : bool_scope.
   Setting notation at level 0.
Notation "@@" := false (only parsing): mybool_scope.
Bind Scope bool_scope with bool.
Notation "# x #" := (g x) (at level 40).
Check # @@ #.
    # true #
        : bool
Arguments g _%mybool_scope.
Check # @@ #.
    # true #
         : bool
Delimit Scope mybool_scope with mybool.
Check # @@%mybool #.
    # false #
         : bool
```

# Binding types of arguments to an interpretation scope

#### Command: Bind Scope scope with qualid

When an interpretation scope is naturally associated to a type (e.g. the scope of operations on the natural numbers), it may be convenient to bind it to this type. When a scope *scope* is bound to a type *type*, any function gets its arguments of type *type* interpreted by default in scope *scope* (this default behavior can however be overwritten by explicitly using the command *Arguments*).

Whether the argument of a function has some type type is determined statically. For instance, if f is a polymorphic function of type forall X:Type, X -> X and type t is bound to a scope scope, then a of type t in f t a is not recognized as an argument to be interpreted in scope scope.

More generally, any coercion *class* (see the *Implicit Coercions* chapter) can be bound to an interpretation scope. The command to do it is Bind Scope *scope* with *class* 

**Note:** When active, a bound scope has effect on all defined functions (even if they are defined after the *Bind Scope* directive), except if argument scopes were assigned explicitly using the *Arguments* command.

Note: The scopes type\_scope and function\_scope also have a local effect on interpretation. See the next section.

# The type\_scope interpretation scope

The scope type\_scope has a special status. It is a primitive interpretation scope which is temporarily activated each time a subterm of an expression is expected to be a type. It is delimited by the key type, and bound to the coercion class Sortclass. It is also used in certain situations where an expression is statically known to be a type, including the conclusion and the type of hypotheses within an Ltac goal match (see Pattern matching on goals), the statement of a theorem, the type of a definition, the type of a binder, the domain and codomain of implication, the codomain of products, and more generally any type argument of a declared or defined constant.

# The function\_scope interpretation scope

The scope function\_scope also has a special status. It is temporarily activated each time the argument of a global reference is recognized to be a Funclass instance, i.e., of type forall x:A, B or  $A \rightarrow B$ .

#### Interpretation scopes used in the standard library of Coq

We give an overview of the scopes used in the standard library of Coq. For a complete list of notations in each scope, use the commands *Print Scopes* or *Print Scope*.

- type\_scope This scope includes infix \* for product types and infix + for sum types. It is delimited by the key type, and bound to the coercion class Sortclass, as described above.
- function\_scope This scope is delimited by the key function, and bound to the coercion class Funclass, as described above.
- nat\_scope This scope includes the standard arithmetical operators and relations on type nat. Positive
  integer numerals in this scope are mapped to their canonical representent built from O and S. The
  scope is delimited by the key nat, and bound to the type nat (see above).
- $N\_scope$  This scope includes the standard arithmetical operators and relations on type N (binary natural numbers). It is delimited by the key N and comes with an interpretation for numerals as closed terms of type N.
- Z\_scope This scope includes the standard arithmetical operators and relations on type Z (binary integer numbers). It is delimited by the key Z and comes with an interpretation for numerals as closed terms of type Z.
- positive\_scope This scope includes the standard arithmetical operators and relations on type positive (binary strictly positive numbers). It is delimited by key positive and comes with an interpretation for numerals as closed terms of type positive.
- Q\_scope This scope includes the standard arithmetical operators and relations on type Q (rational numbers defined as fractions of an integer and a strictly positive integer modulo the equality of the numerator-denominator cross-product) and comes with an interpretation for numerals as closed terms of type Q.

- Qc\_scope This scope includes the standard arithmetical operators and relations on the type Qc of rational numbers defined as the type of irreducible fractions of an integer and a strictly positive integer.
- R\_scope This scope includes the standard arithmetical operators and relations on type R (axiomatic real numbers). It is delimited by the key R and comes with an interpretation for numerals using the IZR morphism from binary integer numbers to R and Z.pow\_pos for potential exponent parts.
- bool\_scope This scope includes notations for the boolean operators. It is delimited by the key bool, and bound to the type bool (see above).
- list\_scope This scope includes notations for the list operators. It is delimited by the key list, and bound to the type list (see above).
- core\_scope This scope includes the notation for pairs. It is delimited by the key core.
- string\_scope This scope includes notation for strings as elements of the type string. Special characters and escaping follow Coq conventions on strings (see *Lexical conventions*). Especially, there is no convention to visualize non printable characters of a string. The file String.v shows an example that contains quotes, a newline and a beep (i.e. the ASCII character of code 7).
- char\_scope This scope includes interpretation for all strings of the form "c" where c is an ASCII character, or of the form "nnn" where nnn is a three-digits number (possibly with leading 0's), or of the form """". Their respective denotations are the ASCII code of c, the decimal ASCII code nnn, or the ascii code of the character " (i.e. the ASCII code 34), all of them being represented in the type ascii.

#### Displaying information about scopes

# Command: Print Visibility

This displays the current stack of notations in scopes and lonely notations that is used to interpret a notation. The top of the stack is displayed last. Notations in scopes whose interpretation is hidden by the same notation in a more recently opened scope are not displayed. Hence each notation is displayed only once.

# Variant: Print Visibility scope

This displays the current stack of notations in scopes and lonely notations assuming that scope is pushed on top of the stack. This is useful to know how a subterm locally occurring in the scope scope is interpreted.

# Command: Print Scopes

This displays all the notations, delimiting keys and corresponding classes of all the existing interpretation scopes. It also displays the lonely notations.

#### Variant: Print Scope scope

This displays all the notations defined in the interpretation scope *scope*. It also displays the delimiting key if any and the class to which the scope is bound, if any.

# 6.1.3 Abbreviations

Command: Local Notation ident ident := term (only parsing) .

An abbreviation is a name, possibly applied to arguments, that denotes a (presumably) more complex expression. Here are examples:

Notation Nlist := (list nat).

An abbreviation expects no precedence nor associativity, since it is parsed as an usual application. Abbreviations are used as much as possible by the Coq printers unless the modifier (only parsing) is given.

An abbreviation is bound to an absolute name as an ordinary definition is and it also can be referred to by a qualified name.

Abbreviations are syntactic in the sense that they are bound to expressions which are not typed at the time of the definition of the abbreviation but at the time they are used. Especially, abbreviations can be bound to terms with holes (i.e. with "\_"). For example:

```
Definition explicit_id (A:Set) (a:A) := a.
Notation id := (explicit_id _).
Check (id 0).
   id 0
      : nat
```

Abbreviations disappear when a section is closed. No typing of the denoted expression is performed at definition time. Type checking is done only at the time of use of the abbreviation.

# 6.1.4 Numeral notations

Command: Numeral Notation ident, ident, ident, ident, scope.

This command allows the user to customize the way numeral literals are parsed and printed.

The token  $ident_1$  should be the name of an inductive type, while  $ident_2$  and  $ident_3$  should be the names of the parsing and printing functions, respectively. The parsing function  $ident_2$  should have one of the following types:

```
Decimal.int -> ident<sub>1</sub>
Decimal.int -> option ident<sub>1</sub>
Decimal.uint -> ident<sub>1</sub>
Decimal.uint -> option ident<sub>1</sub>
Z -> ident<sub>1</sub>
Z -> option ident<sub>1</sub>
Decimal.decimal -> ident<sub>1</sub>
```

• Decimal.decimal -> option ident<sub>1</sub>

And the printing function *ident*<sub>3</sub> should have one of the following types:

- ident, -> Decimal.int
- $ident_1$  -> option Decimal.int
- ident, -> Decimal.uint
- ident, -> option Decimal.uint
- *ident*, -> Z
- *ident*, -> option Z
- ident, -> Decimal.decimal
- ident, -> option Decimal.decimal

When parsing, the application of the parsing function  $ident_2$  to the number will be fully reduced, and universes of the resulting term will be refreshed.

Note that only fully-reduced ground terms (terms containing only function application, constructors, inductive type families, sorts, and primitive integers) will be considered for printing.

Variant: Numeral Notation ident, ident, ident, ident, scope (warning after num).

When a literal larger than *num* is parsed, a warning message about possible stack overflow, resulting from evaluating *ident*<sub>2</sub>, will be displayed.

Variant: Numeral Notation ident, ident, ident, ident, scope (abstract after num).

When a literal m larger than num is parsed, the result will be ( $ident_2$  m), without reduction of this application to a normal form. Here m will be a Decimal.int or Decimal.uint or Z, depending on the type of the parsing function  $ident_2$ . This allows for a more compact representation of literals in types such as nat, and limits parse failures due to stack overflow. Note that a warning will be emitted when an integer larger than num is parsed. Note that (abstract after num) has no effect when  $ident_2$  lands in an option type.

# Error: Cannot interpret this number as a value of type type

The numeral notation registered for *type* does not support the given numeral. This error is given when the interpretation function returns None, or if the interpretation is registered only for integers or non-negative integers, and the given numeral has a fractional or exponent part or is negative.

Error: ident should go from Decimal.int to type or (option type). Instead of Decimal.int, the types

The parsing function given to the Numeral Notation vernacular is not of the right type.

Error: ident should go from type to Decimal.int or (option Decimal.int). Instead of Decimal.int, the The printing function given to the Numeral Notation vernacular is not of the right type.

Error: type is not an inductive type.

Numeral notations can only be declared for inductive types with no arguments.

Error: Unexpected term term while parsing a numeral notation.

Parsing functions must always return ground terms, made up of applications of constructors, inductive types, and primitive integers. Parsing functions may not return terms containing axioms, bare (co)fixpoints, lambdas, etc.

Error: Unexpected non-option term term while parsing a numeral notation.

Parsing functions expected to return an option must always return a concrete Some or None when applied to a concrete numeral expressed as a decimal. They may not return opaque constants.

Error: Cannot interpret in scope because ident could not be found in the current environment.

The inductive type used to register the numeral notation is no longer available in the environment. Most likely, this is because the numeral notation was declared inside a functor for an inductive type inside the functor. This use case is not currently supported.

Alternatively, you might be trying to use a primitive token notation from a plugin which forgot to specify which module you must Require for access to that notation.

Error: Syntax error: [prim:reference] expected after 'Notation' (in [vernac:command]).

The type passed to Numeral Notation must be a single identifier.

Error: Syntax error: [prim:reference] expected after [prim:reference] (in [vernac:command]).

Both functions passed to *Numeral Notation* must be single identifiers.

Error: The reference <u>ident</u> was not found in the current environment.

Identifiers passed to *Numeral Notation* must exist in the global environment.

Error: ident is bound to a notation that does not denote a reference.

Identifiers passed to Numeral Notation must be global references, or notations which denote to single identifiers.

Warning: Stack overflow or segmentation fault happens when working with large numbers in type (through When a Numeral Notation is registered in the current scope with (warning after num), this warning is emitted when parsing a numeral greater than or equal to num.

Warning: To avoid stack overflow, large numbers in type are interpreted as applications of ident<sub>2</sub>. When a Numeral Notation is registered in the current scope with (abstract after num), this warning is emitted when parsing a numeral greater than or equal to num. Typically, this indicates that the fully computed representation of numerals can be so large that non-tail-recursive OCaml functions run out of stack space when trying to walk them.

For example

Warning: The 'abstract after' directive has no effect when the parsing function (ident<sub>2</sub>) targets a As noted above, the (abstract after num) directive has no effect when ident<sub>2</sub> lands in an option type.

# **6.1.5 String notations**

Command: String Notation  $ident_1$   $ident_2$   $ident_3$ : scope.

This command allows the user to customize the way strings are parsed and printed.

The token  $ident_1$  should be the name of an inductive type, while  $ident_2$  and  $ident_3$  should be the names of the parsing and printing functions, respectively. The parsing function  $ident_2$  should have one of the following types:

```
Byte.byte -> ident<sub>1</sub>
Byte.byte -> option ident<sub>1</sub>
list Byte.byte -> ident<sub>1</sub>
```

• list Byte.byte -> option ident,

And the printing function *ident*<sub>3</sub> should have one of the following types:

- *ident*<sub>1</sub> -> Byte.byte
- *ident*, -> option Byte.byte
- *ident*, -> list Byte.byte
- ident<sub>1</sub> -> option (list Byte.byte)

When parsing, the application of the parsing function  $ident_2$  to the string will be fully reduced, and universes of the resulting term will be refreshed.

Note that only fully-reduced ground terms (terms containing only function application, constructors, inductive type families, sorts, and primitive integers) will be considered for printing.

# Error: Cannot interpret this string as a value of type type

The string notation registered for *type* does not support the given string. This error is given when the interpretation function returns None.

Error: ident should go from Byte.byte or (list Byte.byte) to type or (option type).

The parsing function given to the String Notation vernacular is not of the right type.

Error: ident should go from type to Byte.byte or (option Byte.byte) or (list Byte.byte) or (option The printing function given to the String Notation vernacular is not of the right type.

Error: type is not an inductive type.

String notations can only be declared for inductive types with no arguments.

Error: Unexpected term term while parsing a string notation.

Parsing functions must always return ground terms, made up of applications of constructors, inductive types, and primitive integers. Parsing functions may not return terms containing axioms, bare (co)fixpoints, lambdas, etc.

Error: Unexpected non-option term term while parsing a string notation.

Parsing functions expected to return an option must always return a concrete Some or None when applied to a concrete string expressed as a decimal. They may not return opaque constants.

Error: Cannot interpret in scope because ident could not be found in the current environment.

The inductive type used to register the string notation is no longer available in the environment. Most likely, this is because the string notation was declared inside a functor for an inductive type inside the functor. This use case is not currently supported.

Alternatively, you might be trying to use a primitive token notation from a plugin which forgot to specify which module you must Require for access to that notation.

Error: Syntax error: [prim:reference] expected after 'Notation' (in [vernac:command]).

The type passed to String Notation must be a single identifier.

Error: Syntax error: [prim:reference] expected after [prim:reference] (in [vernac:command]). Both functions passed to *String Notation* must be single identifiers.

Error: The reference ident was not found in the current environment.

Identifiers passed to String Notation must exist in the global environment.

Error: ident is bound to a notation that does not denote a reference.

Identifiers passed to *String Notation* must be global references, or notations which denote to single identifiers.

# 6.1.6 Tactic Notations

Tactic notations allow to customize the syntax of tactics. They have the following syntax:

```
tacn
                            Tactic Notation [tactic_level] [prod_item ... prod_item] := tactic.
prod_item
                             string | tactic_argument_type(ident)
                      ::=
                             (at level num)
tactic_level
                       ::=
                            ident | simple_intropattern | reference
tactic_argument_type
                      ::=
                            hyp | hyp_list | ne_hyp_list
                            constr | uconstr | constr_list | ne_constr_list
                            integer | integer_list | ne_integer_list
                            int_or_var | int_or_var_list | ne_int_or_var_list
                            tactic | tactic0 | tactic1 | tactic2 | tactic3
                            tactic4 | tactic5
```

Command: Tactic Notation (at level num) | prod\_item | := tactic.

A tactic notation extends the parser and pretty-printer of tactics with a new rule made of the list of production items. It then evaluates into the tactic expression tactic. For simple tactics, it is recommended to use a terminal symbol, i.e. a string, for the first production item. The tactic level indicates the parsing precedence of the tactic notation. This information is particularly relevant for notations of tacticals. Levels 0 to 5 are available (default is 5).

# Command: Print Grammar tactic

To know the parsing precedences of the existing tacticals, use the command Print Grammar tactic.

Each type of tactic argument has a specific semantic regarding how it is parsed and how it is interpreted. The semantic is described in the following table. The last command gives examples of tactics which use the corresponding kind of argument.

Tactic argument type	parsed as	interpreted as	as in tactic
ident	identifier	a user-given name	intro
simple_intropattern	simple_intropattern	an introduction pattern	assert as
hyp	identifier	a hypothesis defined in context	clear
reference	qualified identifier	a global reference of term	unfold
constr	term	a term	exact
uconstr	term	an untyped term	refine
integer	integer	an integer	
int_or_var	identifier or integer	an integer	do
tactic	tactic at level 5	a tactic	
tacticn	tactic at level n	a tactic	
entry_list	list of entry	a list of how <i>entry</i> is interpreted	
ne_entry_list	non-empty list of entry	a list of how <i>entry</i> is interpreted	

Note: In order to be bound in tactic definitions, each syntactic entry for argument type must include the case of a simple L<sub>tac</sub> identifier as part of what it parses. This is naturally the case for ident, simple\_intropattern, reference, constr, ... but not for integer. This is the reason for introducing a special entry int\_or\_var which evaluates to integers only but which syntactically includes identifiers in order to be usable in tactic definitions.

**Note:** The *entry\_*list and ne\_*entry\_*list entries can be used in primitive tactics or in other notations at places where a list of the underlying entry can be used: entry is either constr, hyp, integer or int\_or\_var.

#### Variant: Local Tactic Notation

Tactic notations disappear when a section is closed. They survive when a module is closed unless the command Local Tactic Notation is used instead of *Tactic Notation*.

# 6.2 Proof schemes

# 6.2.1 Generation of induction principles with Scheme

The **Scheme** command is a high-level tool for generating automatically (possibly mutual) induction principles for given types and sorts. Its syntax follows the schema:

```
Command: Scheme ident_1 := Induction for ident_2 Sort sort with ident_i := Induction for ident_j Sort sort This command is a high-level tool for generating automatically (possibly mutual) induction principles for given types and sorts. Each ident_j is a different inductive type identifier belonging to the same package of mutual inductive definitions. The command generates the ident_is to be mutually recursive definitions. Each term ident_i proves a general principle of mutual induction for objects in type ident_i.
```

Variant: Scheme <u>ident</u> := Minimality for <u>ident</u> Sort <u>sort</u> with <u>ident</u> := Minimality for <u>ident</u> Sort <u>sort</u>

Same as before but defines a non-dependent elimination principle more natural in case of inductively defined relations.

# Variant: Scheme Equality for ident

Tries to generate a Boolean equality and a proof of the decidability of the usual equality. If ident involves some other inductive types, their equality has to be defined first.

Variant: Scheme Induction for ident Sort sort with Induction for ident Sort sort

If you do not provide the name of the schemes, they will be automatically computed from the sorts involved (works also with Minimality).

# Example

Induction scheme for tree and forest.

A mutual induction principle for tree and forest in sort Set can be defined using the command

```
Inductive tree : Set := node : A -> forest -> tree
with forest : Set :=
   leaf : B -> forest
| cons : tree -> forest -> forest.
   tree, forest are defined
   tree_rect is defined
   tree_ind is defined
   tree_rec is defined
   tree_sind is defined
   forest_rect is defined
   forest_rect is defined
   forest_rect is defined
   forest_rec is defined
   forest_rec is defined
   forest_rec is defined
```

(continues on next page)

```
Scheme tree_forest_rec := Induction for tree Sort Set
with forest_tree_rec := Induction for forest Sort Set.
forest_tree_rec is defined
   tree_forest_rec is defined
   tree_forest_rec, forest_tree_rec are recursively defined
```

You may now look at the type of tree forest rec:

This principle involves two different predicates for trees andforests; it also has three premises each one corresponding to a constructor of one of the inductive definitions.

The principle forest\_tree\_rec shares exactly the same premises, only the conclusion now refers to the property of forests.

# Example

Predicates odd and even on naturals.

Let odd and even be inductively defined as:

```
Inductive odd : nat -> Prop := oddS : forall n:nat, even n -> odd (S n)
with even : nat -> Prop :=
    | even0 : even 0
    | evenS : forall n:nat, odd n -> even (S n).
    odd, even are defined
    odd_ind is defined
    odd_sind is defined
    even_ind is defined
    even_sind is defined
```

The following command generates a powerful elimination principle:

```
Scheme odd_even := Minimality for odd Sort Prop
with even_odd := Minimality for even Sort Prop.
    even_odd is defined
    odd_even is defined
    odd_even, even_odd are recursively defined
```

The type of odd even for instance will be:

```
Check odd_even.
    odd_even
        : forall P PO : nat -> Prop,
            (forall n : nat, even n -> PO n -> P (S n)) ->
            PO 0 ->
            (forall n : nat, odd n -> P n -> PO (S n)) ->
            forall n : nat, odd n -> P n
```

6.2. Proof schemes 517

The type of even odd shares the same premises but the conclusion is (n:nat) (even n)->(P0 n).

#### Automatic declaration of schemes

#### Flag: Elimination Schemes

Enables automatic declaration of induction principles when defining a new inductive type. Defaults to on.

#### Flag: Nonrecursive Elimination Schemes

Enables automatic declaration of induction principles for types declared with the *Variant* and *Record* commands. Defaults to off.

# Flag: Case Analysis Schemes

This flag governs the generation of case analysis lemmas for inductive types, i.e. corresponding to the pattern matching term alone and without fixpoint.

#### Flag: Boolean Equality Schemes

# Flag: Decidable Equality Schemes

These flags control the automatic declaration of those Boolean equalities (see the second variant of Scheme).

**Warning:** You have to be careful with these flags since Coq may now reject well-defined inductive types because it cannot compute a Boolean equality for them.

# Flag: Rewriting Schemes

This flag governs generation of equality-related schemes such as congruence.

#### **Combined Scheme**

# Command: Combined Scheme ident from ident;

This command is a tool for combining induction principles generated by the Scheme command. Each  $ident_i$  is a different inductive principle that must belong to the same package of mutual inductive principle definitions. This command generates ident to be the conjunction of the principles: it is built from the common premises of the principles and concluded by the conjunction of their conclusions. In the case where all the inductive principles used are in sort Prop, the propositional conjunction and is used, otherwise the simple product prod is used instead.

# Example

We can define the induction principles for trees and forests using:

```
Scheme tree_forest_ind := Induction for tree Sort Prop
with forest_tree_ind := Induction for forest Sort Prop.
   forest_tree_ind is defined
   tree_forest_ind is defined
   tree_forest_ind, forest_tree_ind are recursively defined
```

Then we can build the combined induction principle which gives the conjunction of the conclusions of each individual principle:

# Example

We can also combine schemes at sort Type:

# 6.2.2 Generation of induction principles with Functional Scheme

Command: Functional Scheme  $ident_0$  := Induction for ident' Sort sort with  $ident_i$  := Induction for ident. This command is a high-level experimental tool for generating automatically induction principles corresponding to (possibly mutually recursive) functions. First, it must be made available via Require Import FunInd. Each  $ident_i$  is a different mutually defined function name (the names must be in the same order as when they were defined). This command generates the induction principle for each  $ident_i$ , following the recursive structure and case analyses of the corresponding function  $ident_i'$ .

Warning: There is a difference between induction schemes generated by the command Functional Scheme and these generated by the Function. Indeed, Function generally produces smaller principles that are closer to how a user would implement them. See Advanced recursive functions for details.

6.2. Proof schemes 519

# Example

```
Induction scheme for div2.
```

We define the function div2 as follows:

```
Require Import FunInd.
    [Loading ML file extraction_plugin.cmxs ... done]
    [Loading ML file recdef_plugin.cmxs ... done]

Require Import Arith.
    [Loading ML file newring_plugin.cmxs ... done]

Fixpoint div2 (n:nat) : nat :=
match n with
| 0 => 0
| S 0 => 0
| S (S n') => S (div2 n')
end.
    div2 is defined
    div2 is recursively defined (decreasing on 1st argument)
```

The definition of a principle of induction corresponding to the recursive structure of div2 is defined by the command:

```
Functional Scheme div2_ind := Induction for div2 Sort Prop. div2_equation is defined div2_ind is defined
```

You may now look at the type of div2\_ind:

```
Check div2_ind.
    div2_ind
    : forall P : nat -> nat -> Prop,
        (forall n : nat, n = 0 -> P 0 0) ->
        (forall n n0 : nat, n = S n0 -> n0 = 0 -> P 1 0) ->
        (forall n n0 : nat,
        n = S n0 ->
        forall n' : nat,
```

 $n0 = S n' \rightarrow P n' (div2 n') \rightarrow P (S (S n')) (S (div2 n'))) \rightarrow$ 

We can now prove the following lemma using this principle:

forall n : nat, P n (div2 n)

(continues on next page)

```
1 subgoal
     n : nat
     _____
     (fun n0 n1 : nat => n1 <= n0) n (div2 n)
apply div2_ind; intros.
   3 subgoals
     n, n0 : nat
     e : n0 = 0
     _____
     0 <= 0
   subgoal 2 is:
    0 <= 1
   subgoal 3 is:
    S (div2 n') \le S (S n')
auto with arith.
   2 subgoals
     n,\ n0,\ n1\ :\ nat
     e : n0 = S n1
     e0 : n1 = 0
     _____
     0 <= 1
   subgoal 2 is:
    S (div2 n') \le S (S n')
auto with arith.
   1 subgoal
     n, n0, n1 : nat
     e : n0 = S n1
     n' : nat
     e0 : n1 = S n'
     H : div2 n' <= n'
     _____
     S (div2 n') \le S (S n')
simpl; auto with arith.
   No more subgoals.
Qed.
We can use directly the functional induction (function induction) tactic instead of the pattern/apply
trick:
Reset div2_le'.
\label{lemma_lemma} \mbox{Lemma div2\_le : forall n:nat, div2 n <= n.}
   1 subgoal
     _____
     forall n : nat, div2 n <= n</pre>
                                                                           (continues on next page)
```

6.2. Proof schemes 521

```
intro n.
   1 subgoal
    n : nat
     _____
     div2 n \le n
functional induction (div2 n).
   3 subgoals
     _____
     0 <= 0
   subgoal 2 is:
   0 <= 1
   subgoal 3 is:
    S (div2 n') \le S (S n')
auto with arith.
   2 subgoals
     _____
     0 <= 1
   subgoal 2 is:
    S (div2 n') \le S (S n')
auto with arith.
   1 subgoal
    n' : nat
     IHn0 : div2 n' \le n'
     _____
    S (div2 n') \le S (S n')
auto with arith.
   No more subgoals.
Qed.
```

# Example

Induction scheme for tree\_size.

We define trees by the following mutual inductive type:

```
Axiom A : Set.
   A is declared

Inductive tree : Set :=
node : A -> forest -> tree
with forest : Set :=
| empty : forest
| cons : tree -> forest -> forest.
```

(continues on next page)

```
tree, forest are defined
tree_rect is defined
tree_ind is defined
tree_rec is defined
tree_sind is defined
forest_rect is defined
forest_ind is defined
forest_rec is defined
forest_sind is defined
```

We define the function tree\_size that computes the size of a tree or a forest. Note that we use Function which generally produces better principles.

```
Require Import FunInd.
Function tree_size (t:tree) : nat :=
match t with
| node A f => S (forest_size f)
end
with forest_size (f:forest) : nat :=
match f with
| empty => 0
| cons t f' => (tree_size t + forest_size f')
    tree_size is defined
    forest_size is defined
    tree_size, forest_size are recursively defined
    (decreasing respectively on 1st, 1st arguments)
    tree_size_equation is defined
    tree_size_rect is defined
    tree_size_ind is defined
    tree_size_rec is defined
    forest_size_equation is defined
    forest_size_rect is defined
    forest_size_ind is defined
    forest_size_rec is defined
    R_tree_size_correct is defined
    R_forest_size_correct is defined
    R_tree_size_complete is defined
    {\tt R\_forest\_size\_complete} \  \, {\tt is} \  \, {\tt defined}
```

Notice that the induction principles tree\_size\_ind and forest\_size\_ind generated by Function are not mutual.

```
Check tree_size_ind.
    tree_size_ind
    : forall P : tree -> nat -> Prop,
        (forall (t : tree) (A : A) (f : forest),
        t = node A f -> P (node A f) (S (forest_size f))) ->
        forall t : tree, P t (tree_size t)
```

Mutual induction principles following the recursive structure of tree\_size and forest\_size can be generated by the following command:

```
Functional Scheme tree_size_ind2 := Induction for tree_size Sort Prop with forest_size_ind2 := Induction for forest_size Sort Prop. tree_size_ind2 is defined forest_size_ind2 is defined
```

6.2. Proof schemes 523

You may now look at the type of tree\_size\_ind2:

```
Check tree_size_ind2.
    tree_size_ind2
    : forall (P : tree -> nat -> Prop) (P0 : forest -> nat -> Prop),
        (forall (t : tree) (A : A) (f : forest),
            t = node A f ->
            P0 f (forest_size f) -> P (node A f) (S (forest_size f))) ->
            (forall f0 : forest, f0 = empty -> P0 empty 0) ->
            (forall (f1 : forest) (t : tree) (f' : forest),
            f1 = cons t f' ->
            P t (tree_size t) ->
            P0 f' (forest_size f') ->
            P0 (cons t f') (tree_size t + forest_size f')) ->
            forall t : tree, P t (tree_size t)
```

# 6.2.3 Generation of inversion principles with Derive Inversion

```
Command: Derive Inversion ident with ident Sort sort
Command: Derive Inversion ident with (forall binders, ident term) Sort sort
```

This command generates an inversion principle for the *inversion ... using ...* tactic. The first *ident* is the name of the generated principle. The second *ident* should be an inductive predicate, and *binders* the variables occurring in the term *term*. This command generates the inversion lemma for the sort *sort* corresponding to the instance forall *binders*, *ident term*. When applied, it is equivalent to having inverted the instance with the tactic inversion.

```
Variant: Derive Inversion_clear ident with ident Sort sort
```

Variant: Derive Inversion\_clear ident with (forall binders, ident term) Sort sort

When applied, it is equivalent to having inverted the instance with the tactic inversion replaced by the tactic inversion\_clear.

```
Variant: Derive Dependent Inversion ident with ident Sort sort
```

Variant: Derive Dependent Inversion ident with (forall binders, ident term) Sort sort

When applied, it is equivalent to having inverted the instance with the tactic dependent inversion.

```
Variant: Derive Dependent Inversion_clear ident with ident Sort sort
```

Variant: Derive Dependent Inversion\_clear ident with (forall binders, ident term) Sort sort
When applied, it is equivalent to having inverted the instance with the tactic dependent
inversion\_clear.

#### Example

Consider the relation Le over natural numbers and the following parameter P:

```
Inductive Le : nat -> nat -> Set :=
| Le0 : forall n:nat, Le 0 n
| LeS : forall n m:nat, Le n m -> Le (S n) (S m).
    Le is defined
    Le_rect is defined
    Le_ind is defined
    Le_rec is defined
    Le_sind is defined

Parameter P : nat -> nat -> Prop.
P is declared
```

To generate the inversion lemma for the instance (Le (S n) m) and the sort Prop, we do:

 $\mathtt{n}$ ,  $\mathtt{m}$ :  $\mathtt{nat}$   $\mathtt{H}$ :  $\mathtt{Le}$  ( $\mathtt{S}$   $\mathtt{n}$ )  $\mathtt{m}$ 

\_\_\_\_\_

forall m0 : nat, Le n m0  $\rightarrow$  P n (S m0)

6.2. Proof schemes 525

# PRACTICAL TOOLS

# 7.1 The Coq commands

There are three Coq commands:

- coqtop: the Coq toplevel (interactive mode);
- coqc: the Coq compiler (batch compilation);
- cogchk: the Coq checker (validation of compiled libraries).

The options are (basically) the same for the first two commands, and roughly described below. You can also look at the man pages of coqtop and coqc for more details.

# 7.1.1 Interactive use (coqtop)

In the interactive mode, also known as the Coq toplevel, the user can develop his theories and proofs step by step. The Coq toplevel is run by the command coqtop.

There are two different binary images of Coq: the byte-code one and the native-code one (if OCaml provides a native-code compiler for your platform, which is supposed in the following). By default, coqtop executes the native-code version; run coqtop.byte to get the byte-code version.

The byte-code toplevel is based on an OCaml toplevel (to allow dynamic linking of tactics). You can switch to the OCaml toplevel with the command Drop., and come back to the Coq toplevel with the command Coqloop.loop();;.

# Flag: Coqtop Exit On Error

This flag, off by default, causes coqtop to exit with status code 1 if a command produces an error instead of recovering from it.

# 7.1.2 Batch compilation (coqc)

The coqc command takes a name file as argument. Then it looks for a vernacular file named file.v, and tries to compile it into a file.vo file (See Compiled files).

Caution: The name *file* should be a regular Coq identifier as defined in Section *Lexical conventions*. It should contain only letters, digits or underscores (\_). For example /bar/foo/toto.v is valid, but /bar/foo/to-to.v is not.

# 7.1.3 Customization at launch time

# By resource file

When Coq is launched, with either coqtop or coqc, the resource file \$XDG\_CONFIG\_HOME/coq/coqrc.xxx, if it exists, will be implicitly prepended to any document read by Coq, whether it is an interactive session or a file to compile. Here, \$XDG\_CONFIG\_HOME is the configuration directory of the user (by default it's ~/.config) and xxx is the version number (e.g. 8.8). If this file is not found, then the file \$XDG\_CONFIG\_HOME/coqrc is searched. If not found, it is the file ~/.coqrc.xxx which is searched, and, if still not found, the file ~/.coqrc. If the latter is also absent, no resource file is loaded. You can also specify an arbitrary name for the resource file (see option -init-file below).

The resource file may contain, for instance, Add LoadPath commands to add directories to the load path of Coq. It is possible to skip the loading of the resource file with the option -q.

# By environment variables

Load path can be specified to the Coq system by setting up \$COQPATH environment variable. It is a list of directories separated by: (; on Windows). Coq will also honor \$XDG\_DATA\_HOME and \$XDG\_DATA\_DIRS (see Section Libraries and filesystem).

Some Coq commands call other Coq commands. In this case, they look for the commands in directory specified by \$COQBIN. If this variable is not set, they look for the commands in the executable path.

The \$COQ\_COLORS environment variable can be used to specify the set of colors used by coqtop to highlight its output. It uses the same syntax as the \$LS\_COLORS variable from GNU's ls, that is, a colon-separated list of assignments of the form name=attr; where name is the name of the corresponding highlight tag and each attr is an ANSI escape code. The list of highlight tags can be retrieved with the -list-tags command-line option of coqtop.

The string uses ANSI escape codes to represent attributes. For example:

```
export COQ_COLORS="diff.added=4;48;2;0;0;240:diff.removed=41"
```

sets the highlights for added text in diffs to underlined (the 4) with a background RGB color (0, 0, 240) and for removed text in diffs to a red background. Note that if you specify COQ\_COLORS, the predefined attributes are ignored.

# By command line options

The following command-line options are recognized by the commands coqc and coqtop, unless stated otherwise:

-I directory, -include directory Add physical path directory to the OCaml loadpath.

# See also:

Names of libraries and the command Declare ML Module Section Compiled files.

-Q directory dirpath Add physical path directory to the list of directories where Coq looks for a file and bind it to the logical directory dirpath. The subdirectory structure of directory is recursively available from Coq using absolute names (extending the dirpath prefix) (see Section Qualified names). Note that only those subdirectories and files which obey the lexical conventions of what is an ident are taken into account. Conversely, the underlying file systems or operating systems may be more restrictive than Coq. While Linux's ext4 file system supports any Coq recursive layout (within the limit of 255 bytes per filename), the

default on NTFS (Windows) or HFS+ (MacOS X) file systems is on the contrary to disallow two files differing only in the case in the same directory.

#### See also:

Section Names of libraries.

-R directory dirpath Do as -Q directory dirpath but make the subdirectory structure of directory recursively visible so that the recursive contents of physical directory is available from Coq using short or partially qualified names.

#### See also:

Section Names of libraries.

- -top dirpath Set the toplevel module name to dirpath instead of Top. Not valid for coqc as the toplevel module name is inferred from the name of the output file.
- **-exclude-dir** directory Exclude any subdirectory named directory while processing options such as -R and -Q. By default, only the conventional version control management directories named CVS and darcs are excluded.
- -nois Start from an empty state instead of loading the Init.Prelude module.
- -init-file *file* Load *file* as the resource file instead of loading the default resource file from the standard configuration directories.
- **-q** Do not to load the default resource file.
- -load-ml-source file Load the OCaml source file file.
- -load-ml-object file Load the OCaml object file file.
- -1 file, -load-vernac-source file Load and execute the Coq script from file.v.
- -lv *file*, -load-vernac-source-verbose *file* Load and execute the Coq script from *file.v*. Write its contents to the standard output as it is executed.
- -load-vernac-object qualid Load Coq compiled library qualid. This is equivalent to running Require qualid.
- -ri qualid, -require-import qualid Load Coq compiled library qualid and import it. This is equivalent to running Require Import qualid.
- -re qualid, -require-export qualid Load Coq compiled library qualid and transitively import it. This is equivalent to running Require Export qualid.
- -rifrom dirpath qualid, -require-import-from dirpath qualid Load Coq compiled library qualid and import it. This is equivalent to running From dirpath Require Import qualid.
- -refrom dirpath qualid, -require-export-from dirpath qualid Load Coq compiled library qualid and transitively import it. This is equivalent to running From dirpath Require Export qualid.
- -require qualid Deprecated; use -ri qualid.
- -batch Exit just after argument parsing. Available for coqtop only.
- -verbose Output the content of the input file as it is compiled. This option is available for coqc only.
- -vos Indicate Coq to skip the processing of opaque proofs (i.e., proofs ending with Qed or Admitted), output a .vos files instead of a .vo file, and to load .vos files instead of .vo files when interpreting Require commands.

- -vok Indicate Coq to check a file completely, to load .vos files instead of .vo files when interpreting Require commands, and to output an empty .vok files upon success instead of writing a .vo file.
- -w (all|none|w<sub>1</sub>,...,w) Configure the display of warnings. This option expects all, none or a comma-separated list of warning names or categories (see Section *Controlling display*).
- -color (on|off|auto) Coqtop only. Enable or disable color output. Default is auto, meaning color is shown only if the output channel supports ANSI escape sequences.
- -diffs (on|off|removed) Coqtop only. Controls highlighting of differences between proof steps. on highlights added tokens, removed highlights both added and removed tokens. Requires that -color is enabled. (see Section Showing differences between proof steps).
- **-beautify** Pretty-print each command to *file.beautified* when compiling *file.v*, in order to get old-fashioned syntax/definitions/notations.
- -emacs, -ide-slave Start a special toplevel to communicate with a specific IDE.
- -impredicative-set Change the logical theory of Coq by declaring the sort Set impredicative.

**Warning:** This is known to be inconsistent with some standard axioms of classical mathematics such as the functional axiom of choice or the principle of description.

-type-in-type Collapse the universe hierarchy of Coq.

Warning: This makes the logic inconsistent.

- -mangle-names ident Experimental. Do not depend on this option. Replace Coq's autogenerated name scheme with names of the form ident0, ident1, etc. Within Coq, the Mangle Names flag turns this behavior on, and the Mangle Names Prefix option sets the prefix to use. This feature is intended to be used as a linter for developments that want to be robust to changes in the auto-generated name scheme. The options are provided to facilitate tracking down problems.
- -set string Enable flags and set options. string should be Option Name=value, the value is interpreted according to the type of the option. For flags Option Name is equivalent to Option Name=true. For instance -set "Universe Polymorphism" will enable Universe Polymorphism. Note that the quotes are shell syntax, Coq does not see them.
- -unset string As -set but used to disable options and flags.
- -compat version Attempt to maintain some backward-compatibility with a previous version.
- -dump-glob file Dump references for global names in file file (to be used by coqdoc, see Documenting Coq files with coqdoc). By default, if file.v is being compiled, file.glob is used.
- **-no-glob** Disable the dumping of references for global names.
- -image *file* Set the binary image to be used by coqc to be *file* instead of the standard one. Not of general use.
- **-bindir** *directory* Set the directory containing Coq binaries to be used by coqc. It is equivalent to doing export COQBIN= *directory* before launching coqc.
- **-where** Print the location of Cog's standard library and exit.
- -config Print the locations of Coq's binaries, dependencies, and libraries, then exit.

- -filteropts Print the list of command line arguments that coqtop has recognized as options and exit.
- -v Print Cog's version and exit.
- -list-tags Print the highlight tags known by Coq as well as their currently associated color and exit.
- -h, -help Print a short usage and exit.

# 7.1.4 Compiled interfaces (produced using -vos)

Compiled interfaces help saving time while developing Coq formalizations, by compiling the formal statements exported by a library independently of the proofs that it contains.

Warning: Compiled interfaces should only be used for development purposes. At the end of the day, one still needs to proof check all files by producing standard .vo files. (Technically, when using -vos, fewer universe constraints are collected.) Moreover, this feature is still experimental, it may be subject to change without prior notice.

#### Principle.

The compilation using coqc -vos foo.v produces a file called foo.vos, which is similar to foo.vo except that all opaque proofs are skipped in the compilation process.

The compilation using coqc -vok foo.v checks that the file foo.v correctly compiles, including all its opaque proofs. If the compilation succeeds, then the output is a file called foo.vok, with empty contents. This file is only a placeholder indicating that foo.v has been successfully compiled. (This placeholder is useful for build systems such as make.)

When compiling a file bar.v that depends on foo.v (for example via a Require Foo. command), if the compilation command is coqc -vos bar.v or coqc -vok bar.v, then the file foo.vos gets loaded (instead of foo.vo). A special case is if file foo.vos exists and has empty contents, and foo.vo exists, then foo.vo is loaded.

Appart from the aforementioned case where foo.vo can be loaded in place of foo.vos, in general the .vos and .vok files live totally independently from the .vo files.

# Dependencies generated by "coq\_makefile".

The files foo.vos and foo.vok both depend on foo.v.

Furthermore, if a file foo.v requires bar.v, then foo.vos and foo.vok also depend on bar.vos.

Note, however, that foo.vok does not depend on bar.vok. Hence, as detailed further, parallel compilation of proofs is possible.

In addition, coq\_makefile generates for a file foo.v a target foo.required\_vos which depends on the list of .vos files that foo.vos depends upon (excluding foo.vos itself). As explained next, the purpose of this target is to be able to request the minimal working state for editing interactively the file foo.v.

Warning: When writing a custom build system, be aware that coqdep only produces dependencies related to .vos and .vok if the -vos command line flag is passed. This is to maintain compatibility with dune (see ocaml/dune#2642 on github<sup>310</sup>).

 $<sup>^{310}</sup>$ https://github.com/ocaml/dune/issues/2842

#### Typical compilation of a set of file using a build system.

Assume a file foo.v that depends on two files f1.v and f2.v. The command make foo.required\_vos will compile f1.v and f2.v using the option -vos to skip the proofs, producing f1.vos and f2.vos. At this point, one is ready to work interactively on the file foo.v, even though it was never needed to compile the proofs involved in the files f1.v and f2.v.

Assume a set of files f1.v ... fn.v with linear dependencies. The command make vos enables compiling the statements (i.e. excluding the proofs) in all the files. Next, make -j vok enables compiling all the proofs in parallel. Thus, calling make -j vok directly enables taking advantage of a maximal amount of parallelism during the compilation of the set of files.

Note that this comes at the cost of parsing and typechecking all definitions twice, once for the .vos file and once for the .vok file. However, if files contain nontrivial proofs, or if the files have many linear chains of dependencies, or if one has many cores available, compilation should be faster overall.

# Need for "Proof using"

When a theorem is part of a section, typechecking the statement of this theorem might be insufficient for deducing the type of this statement as of at the end of the section. Indeed, the proof of the theorem could make use of section variables or section hypotheses that are not mentioned in the statement of the theorem.

For this reason, proofs inside section should begin with *Proof using* instead of *Proof*, where after the using clause one should provide the list of the names of the section variables that are required for the proof but are not involved in the typechecking of the statement. Note that it is safe to write **Proof using**. instead of **Proof**. also for proofs that are not within a section.

Warning: You should use the "Proof using [...]." syntax instead of "Proof." to enable skipping this proof of the command in the command proof inside a section, it will compile the proof, that is, refuse to skip it, and it will raise a warning. To disable the warning, one may pass the flag -w -proof-without-using-in-section.

# Interaction with standard compilation

When compiling a file foo.v using coqc in the standard way (i.e., without -vos nor -vok), an empty file foo.vos and an empty file foo.vok are created in addition to the regular output file foo.vo. If coqc is subsequently invoked on some other file bar.v using option -vos or -vok, and that bar.v requires foo.v, if Coq finds an empty file foo.vos, then it will load foo.vo instead of foo.vos.

The purpose of this feature is to allow users to benefit from the -vos option even if they depend on libraries that were compiled in the traditional manner (i.e., never compiled using the -vos option).

# 7.1.5 Compiled libraries checker (cogchk)

The coqchk command takes a list of library paths as argument, described either by their logical name or by their physical filename, hich must end in .vo. The corresponding compiled libraries (.vo files) are searched in the path, recursively processing the libraries they depend on. The content of all these libraries is then type checked. The effect of coqchk is only to return with normal exit code in case of success, and with positive exit code if an error has been found. Error messages are not deemed to help the user understand what is wrong. In the current version, it does not modify the compiled libraries to mark them as successfully checked.

Note that non-logical information is not checked. By logical information, we mean the type and optional body associated to names. It excludes for instance anything related to the concrete syntax of objects (customized syntax rules, association between short and long names), implicit arguments, etc.

This tool can be used for several purposes. One is to check that a compiled library provided by a third-party

has not been forged and that loading it cannot introduce inconsistencies<sup>311</sup>. Another point is to get an even higher level of security. Since coqtop can be extended with custom tactics, possibly ill-typed code, it cannot be guaranteed that the produced compiled libraries are correct. coqchk is a standalone verifier, and thus it cannot be tainted by such malicious code.

Command-line options -Q, -R, -where and -impredicative-set are supported by coqchk and have the same meaning as for coqtop. As there is no notion of relative paths in object files -Q and -R have exactly the same meaning.

- **-norec** *module* Check *module* but do not check its dependencies.
- -admit module Do not check module and any of its dependencies, unless explicitly required.
- **-o** At exit, print a summary about the context. List the names of all assumptions and variables (constants without body).
- -silent Do not write progress information to the standard output.

Environment variable \$COQLIB can be set to override the location of the standard library.

The algorithm for deciding which modules are checked or admitted is the following: assuming that coqchk is called with argument M, option -norec N, and -admit A. Let us write  $\overline{S}$  for the set of reflexive transitive dependencies of set S. Then:

- Modules  $C = \overline{M} \setminus \overline{A} \cup M \cup N$  are loaded and type checked before being added to the context.
- And  $M \cup N \setminus C$  is the set of modules that are loaded and added to the context without type checking. Basic integrity checks (checksums) are nonetheless performed.

As a rule of thumb, -admit can be used to tell Coq that some libraries have already been checked. So coqchk A B can be split in coqchk A && coqchk B -admit A without type checking any definition twice. Of course, the latter is slightly slower since it makes more disk access. It is also less secure since an attacker might have replaced the compiled library A after it has been read by the first command, but before it has been read by the second command.

# 7.2 Utilities

The distribution provides utilities to simplify some tedious works beside proof development, tactics writing or documentation.

# 7.2.1 Using Coq as a library

In previous versions, coqmktop was used to build custom toplevels - for example for better debugging or custom static linking. Nowadays, the preferred method is to use ocamlfind.

The most basic custom toplevel is built using:

For example, to statically link  $L_{\rm tac},$  you can just do:

<sup>311</sup> Ill-formed non-logical information might for instance bind Coq.Init.Logic.True to short name False, so apparently False is inhabited, but using fully qualified names, Coq.Init.Logic.False will always refer to the absurd proposition, what we guarantee is that there is no proof of this latter constant.

and similarly for other plugins.

# 7.2.2 Building a Coq project

As of today it is possible to build Coq projects using two tools:

- coq\_makefile, which is distributed by Coq and is based on generating a makefile,
- Dune, the standard OCaml build tool, which, since version 1.9, supports building Coq libraries.

# Building a Coq project with coq\_makefile

The majority of Coq projects are very similar: a collection of .v files and eventually some .ml ones (a Coq plugin). The main piece of metadata needed in order to build the project are the command line options to coqc (e.g. -R, Q, -I, see *command line options*). Collecting the list of files and options is the job of the \_CoqProject file.

A simple example of a \_CoqProject file follows:

```
-R theories/ MyCode
-arg -w
-arg all
theories/foo.v
theories/bar.v
-I src/
src/baz.mlg
src/bazaux.ml
src/qux_plugin.mlpack
```

where options -R, -Q and -I are natively recognized, as well as file names. The lines of the form -arg foo are used in order to tell to literally pass an argument foo to coqc: in the example, this allows to pass the two-word option -w all (see *command line options*).

Currently, both CoqIDE and Proof-General (version 4.3pre) understand \_CoqProject files and invoke Coq with the desired options.

The coq\_makefile utility can be used to set up a build infrastructure for the Coq project based on makefiles. The recommended way of invoking coq\_makefile is the following one:

```
coq_makefile -f _CoqProject -o CoqMakefile
```

Such command generates the following files:

CoqMakefile is a generic makefile for GNU Make that provides targets to build the project (both .v and .ml\* files), to install it system-wide in the coq-contrib directory (i.e. where Coq is installed) as well as to invoke coqdoc to generate HTML documentation.

CoqMakefile.conf contains make variables assignments that reflect the contents of the \_CoqProject file as well as the path relevant to Coq.

An optional file CoqMakefile.local can be provided by the user in order to extend CoqMakefile. In particular one can declare custom actions to be performed before or after the build process. Similarly one can customize the install target or even provide new targets. Extension points are documented in paragraph CoqMakefile.local.

7.2. Utilities 533

The extensions of the files listed in \_CoqProject is used in order to decide how to build them. In particular:

- Coq files must use the .v extension
- OCaml files must use the .ml or .mli extension
- OCaml files that require pre processing for syntax extensions (like VERNAC EXTEND) must use the .mlg extension
- In order to generate a plugin one has to list all OCaml modules (i.e. Baz for baz.ml) in a .mlpack file (or .mllib file).

The use of .mlpack files has to be preferred over .mllib files, since it results in a "packed" plugin: All auxiliary modules (as Baz and Bazaux) are hidden inside the plugin's "namespace" (Qux\_plugin). This reduces the chances of begin unable to load two distinct plugins because of a clash in their auxiliary module names.

# CoqMakefile.local

The optional file CoqMakefile.local is included by the generated file CoqMakefile. It can contain two kinds of directives.

#### Variable assignment

The variable must belong to the variables listed in the Parameters section of the generated makefile. Here we describe only few of them.

- **CAMLPKGS** can be used to specify third party findlib packages, and is passed to the OCaml compiler on building or linking of modules. Eg: -package yojson.
- **CAMLFLAGS** can be used to specify additional flags to the OCaml compiler, like -bin-annot or -w....
- **OCAMLWARN** it contains a default of -warn-error +a-3, useful to modify this setting; beware this is not recommended for projects in Coq's CI.
- COQC, COQDEP, COQDOC can be set in order to use alternative binaries (e.g. wrappers)
- COQ\_SRC\_SUBDIRS can be extended by including other paths in which \*.cm\* files are searched. For example COQ\_SRC\_SUBDIRS+=user-contrib/Unicoq lets you build a plugin containing OCaml code that depends on the OCaml code of Unicoq
- COQFLAGS override the flags passed to coqc. By default -q.
- COQEXTRAFLAGS extend the flags passed to coqc
- COQCHKFLAGS override the flags passed to coqchk. By default -silent -o.
- COQCHKEXTRAFLAGS extend the flags passed to coqchk
- COQDOCFLAGS override the flags passed to coqdoc. By default -interpolate -utf8.
- COQDOCEXTRAFLAGS extend the flags passed to coqdoc

# Rule extension

The following makefile rules can be extended.

# Example

# Timing targets and performance testing

The generated Makefile supports the generation of two kinds of timing data: per-file build-times, and per-line times for an individual file.

The following targets and Makefile variables allow collection of per- file timing data:

• TIMED=1 passing this variable will cause make to emit a line describing the user-space build-time and peak memory usage for each file built.

Note: On Mac OS, this works best if you've installed gnu-time.

#### Example

For example, the output of make TIMED=1 may look like this:

```
COQDEP Fast.v
COQDEP Slow.v
COQC Slow.v
Slow (user: 0.34 mem: 395448 ko)
COQC Fast.v
Fast (user: 0.01 mem: 45184 ko)
```

• pretty-timed this target stores the output of make TIMED=1 into time-of-build.log, and displays a table of the times, sorted from slowest to fastest, which is also stored in time-of-build-pretty. log. If you want to construct the log for targets other than the default one, you can pass them via the variable TGTS, e.g., make pretty-timed TGTS="a.vo b.vo".

7.2. Utilities 535

**Note:** This target will *append* to the timing log; if you want a fresh start, you must remove the filetime-of-build.log or run make cleanall.

# Example

For example, the output of make pretty-timed may look like this:

• print-pretty-timed-diff this target builds a table of timing changes between two compilations; run make make-pretty-timed-before to build the log of the "before" times, and run make make-pretty-timed-after to build the log of the "after" times. The table is printed on the command line, and stored in time-of-build-both.log. This target is most useful for profiling the difference between two commits in a repository.

Note: This target requires python to build the table.

Note: The make-pretty-timed-before and make-pretty-timed-after targets will append to the timing log; if you want a fresh start, you must remove the files time-of-build-before. log and time-of-build-after.log or run make cleanall before building either the "before" or "after" targets.

**Note:** The table will be sorted first by absolute time differences rounded towards zero to a whole-number of seconds, then by times in the "after" column, and finally lexicographically by file name. This will put the biggest changes in either direction first, and will prefer sorting by build-time over subsecond changes in build time (which are frequently noise); lexicographic sorting forces an order on files which take effectively no time to compile.

#### Example

For example, the output table from make print-pretty-timed-diff may look like this:

```
After | File Name | Before | | Change | % Change | 0m00.39s | Total | 0m00.35s | +0m00.03s | +11.42%
```

(continues on next page)

```
0m00.37s | Slow | 0m00.01s || +0m00.36s | +3600.00%
0m00.02s | Fast | 0m00.34s || -0m00.32s | -94.11%
```

The following targets and Makefile variables allow collection of per-line timing data:

• TIMING=1 passing this variable will cause make to use coqc -time to write to a .v.timing file for each .v file compiled, which contains line-by-line timing information.

#### Example

For example, running make all TIMING=1 may result in a file like this:

```
Chars 0 - 26 [Require-Coq.ZArith.BinInt.] 0.157 secs (0.128u,0.028s)

Chars 27 - 68 [Declare-Reduction-comp-:=-vm_c...] 0. secs (0.u,0.s)

Chars 69 - 162 [Definition-foo0-:=-Eval-comp-i...] 0.153 secs (0.136u,0.019s)

Chars 163 - 208 [Definition-foo1-:=-Eval-comp-i...] 0.239 secs (0.236u,0.s)
```

• print-pretty-single-time-diff

this target will make a sorted table of the per-line timing differences between the timing logs in the BEFORE and AFTER files, display it, and save it to the file specified by the TIME\_OF\_PRETTY\_BUILD\_FILE variable, which defaults to time-of-build-pretty.log. To generate the .v.before-timing or .v.after-timing files, you should pass TIMING=before or TIMING=after rather than TIMING=1.

Note: The sorting used here is the same as in the print-pretty-timed-diff target.

**Note:** This target requires python to build the table.

# Example

For example, running print-pretty-single-time-diff might give a table like this:

```
After
         | Code
                                                                | Before
⇔Change
           | % Change
 .....
Om00.50s | Total
                                                                | 0m04.17s || -0m03.
 -66s | -87.96%
Om00.145s | Chars 069 - 162 [Definition~foo0~:=~Eval~comp~i...] | Om00.192s || -Om00.
904s | -24.47%
Om00.126s | Chars 000 - 026 [Require~Coq.ZArith.BinInt.]
                                                                | 0m00.143s || -0m00.
→01s | -11.88%
         | Chars 027 - 068 [Declare~Reduction~comp~:=~nati...] | 0m00.s
  N/A
→00s | N/A
                                                                 (continues on next page)
```

7.2. Utilities 537

• all.timing.diff, path/to/file.v.timing.diff The path/to/file.v.timing.diff target will make a .v.timing.diff file for the corresponding .v file, with a table as would be generated by the print-pretty-single-time-diff target; it depends on having already made the corresponding .v.before-timing and .v.after-timing files, which can be made by passing TIMING-before and TIMING-after. The all.timing.diff target will make such timing difference files for all of the .v files that the Makefile knows about. It will fail if some .v.before-timing or .v. after-timing files don't exist.

**Note:** This target requires python to build the table.

### Reusing/extending the generated Makefile

Including the generated makefile with an include directive is discouraged. The contents of this file, including variable names and status of rules shall change in the future. Users are advised to include Makefile.conf or call a target of the generated Makefile as in make -f Makefile target from another Makefile.

One way to get access to all targets of the generated CoqMakefile is to have a generic target for invoking unknown targets.

### Example

```
# KNOWNTARGETS will not be passed along to CoqMakefile
KNOWNTARGETS := CoqMakefile extra-stuff extra-stuff2
# KNOWNFILES will not get implicit targets from the final rule, and so
# depending on them won't invoke the submake
# Warning: These files get declared as PHONY, so any targets depending
# on them always get rebuilt
KNOWNFILES
           := Makefile _CoqProject
. {\tt DEFAULT\_GOAL} \ := \ {\tt invoke-coqmakefile}
CoqMakefile: Makefile _CoqProject
       $(COQBIN)coq_makefile -f _CoqProject -o CoqMakefile
invoke-coqmakefile: CoqMakefile
       $(MAKE) --no-print-directory -f CoqMakefile $(filter-out $(KNOWNTARGETS),$(MAKECMDGOALS))
.PHONY: invoke-coqmakefile $(KNOWNFILES)
Your targets here
# This should be the last rule, to handle any targets not declared above
%: invoke-coqmakefile
       @t.rue
```

### Building a subset of the targets with -j

To build, say, two targets foo.vo and bar.vo in parallel one can use make only TGTS="foo.vo bar.vo" -j.

Note: make foo.vo bar.vo -j has a different meaning for the make utility, in particular it may build a shared prerequisite twice.

**Note:** For users of coq\_makefile with version < 8.7

- Support for "subdirectory" is deprecated. To perform actions before or after the build (like invoking make on a subdirectory) one can hook in pre-all and post-all extension points.
- -extra-phony and -extra are deprecated. To provide additional target (.PHONY or not) please use CoqMakefile.local.

# Building a Coq project with Dune

Note: Dune's Coq support is still experimental; we strongly recommend using Dune 2.3 or later.

**Note:** The canonical documentation for the Coq Dune extension is maintained upstream; please refer to the Dune manual<sup>312</sup> for up-to-date information. This documentation is up to date for Dune 2.3.

Building a Coq project with Dune requires setting up a Dune project for your files. This involves adding a dune-project and pkg.opam file to the root (pkg.opam can be empty or generated by Dune itself), and then providing dune files in the directories your .v files are placed. For the experimental version "0.1" of the Coq Dune language, Coq library stanzas look like:

```
(coq.theory
  (name <module_prefix>)
  (package <opam_package>)
  (synopsis <text>)
  (modules <ordered_set_lang>)
  (libraries <ocaml_libraries>)
  (flags <coq_flags>))
```

This stanza will build all .v files in the given directory, wrapping the library under <module\_prefix>. If you declare an <opam\_package>, an .install file for the library will be generated; the optional (modules <ordered\_set\_lang>) field allows you to filter the list of modules, and (libraries <ocaml\_libraries>) allows the Coq theory depend on ML plugins. For the moment, Dune relies on Coq's standard mechanisms (such as COQPATH) to locate installed Coq libraries.

By default Dune will skip  $.\,v$  files present in subdirectories. In order to enable the usual recursive organization of Coq projects add

7.2. Utilities 539

<sup>312</sup> https://dune.readthedocs.io/

```
(include_subdirs qualified)
```

to you dune file.

Once your project is set up, dune build will generate the pkg.install files and all the files necessary for the installation of your project.

### Example

A typical stanza for a Coq plugin is split into two parts. An OCaml build directive, which is standard Dune:

```
(name equations_plugin)
  (public_name equations.plugin)
   (flags :standard -warn-error -3-9-27-32-33-50)
   (libraries coq.plugins.cc coq.plugins.extraction))

(coq.pp (modules g_equations))

And a Coq-specific part that depends on it via the libraries field:

(coq.theory
   (name Equations) ; -R flag
   (package equations)
   (synopsis "Equations Plugin")
   (libraries coq.plugins.extraction equations.plugin)
   (modules :standard \ IdDec NoCycle)) ; exclude some modules that don't build

(include_subdirs qualified)
```

### 7.2.3 Computing Module dependencies

In order to compute module dependencies (to be used by make or dune), Coq provides the coqdep tool.

coqdep computes inter-module dependencies for Coq and OCaml programs, and prints the dependencies on the standard output in a format readable by make. When a directory is given as argument, it is recursively looked at.

Dependencies of Coq modules are computed by looking at Require commands (Require, Require Export, Require Import), but also at the command Declare ML Module.

Dependencies of OCaml modules are computed by looking at open commands and the dot notation *module.value*. However, this is done approximately and you are advised to use ocamldep instead for the OCaml module dependencies.

See the man page of coqdep for more details and options.

Both Dune and coq\_makefile use coqdep to compute the dependencies among the files part of a Coq project.

### 7.2.4 Documenting Coq files with coqdoc

coqdoc is a documentation tool for the proof assistant Coq, similar to javadoc or ocamldoc. The task of coqdoc is

1. to produce a nice LaTeX and/or HTML document from Coq source files, readable for a human and not only for the proof assistant;

2. to help the user navigate his own (or third-party) sources.

### **Principles**

Documentation is inserted into Coq files as *special comments*. Thus your files will compile as usual, whether you use coqdoc or not. coqdoc presupposes that the given Coq files are well-formed (at least lexically). Documentation starts with (\*\*, followed by a space, and ends with \*). The documentation format is inspired by Todd A. Coram's *Almost Free Text (AFT)* tool: it is mainly ASCII text with some syntax-light controls, described below. coqdoc is robust: it shouldn't fail, whatever the input is. But remember: "garbage in, garbage out".

### Coq material inside documentation.

Coq material is quoted between the delimiters [ and ]. Square brackets may be nested, the inner ones being understood as being part of the quoted code (thus you can quote a term like  $fun \ x \Rightarrow u$  by writing [ $fun \ x \Rightarrow u$ ]). Inside quotations, the code is pretty-printed in the same way as it is in code parts.

Preformatted vernacular is enclosed by [[ and ]]. The former must be followed by a newline and the latter must follow a newline.

### Pretty-printing.

coqdoc uses different faces for identifiers and keywords. The pretty- printing of Coq tokens (identifiers or symbols) can be controlled using one of the following commands:

```
(** printing *token* %...LATEX...% #...html...# *)
or
(** printing *token* $...LATEX math...$ #...html...# *)
```

It gives the LaTeX and HTML texts to be produced for the given Coq token. Either the LaTeX or the HTML rule may be omitted, causing the default pretty-printing to be used for this token.

The printing for one token can be removed with

```
(** remove printing *token* *)
```

Initially, the pretty-printing table contains the following mapping:

->	$\rightarrow$	<-	$\leftarrow$	*	×
<=		>=		=>	
<b>&lt;&gt;</b>		<->		1-	
\/		\		<b>?</b>	_

Any of these can be overwritten or suppressed using the printing commands.

**Note:** The recognition of tokens is done by a (ocaml) lex automaton and thus applies the longest-match rule. For instance, ->~ is recognized as a single token, where Coq sees two tokens. It is the responsibility of the user to insert space between tokens or to give pretty-printing rules for the possible combinations, e.g.

7.2. Utilities 541

```
(** printing ->~ %\ensuremath{\rightarrow\lnot}% *)
```

#### **Sections**

Sections are introduced by 1 to 4 asterisks at the beginning of a line followed by a space and the title of the section. One asterisk is a section, two a subsection, etc.

### Example

```
(** * Well-founded relations
In this section, we introduce... *)
```

#### Lists.

List items are introduced by a leading dash. coqdoc uses whitespace to determine the depth of a new list item and which text belongs in which list items. A list ends when a line of text starts at or before the level of indenting of the list's dash. A list item's dash must always be the first non-space character on its line (so, in particular, a list can not begin on the first line of a comment - start it on the second line instead).

#### Example

```
We go by induction on [n]:
- If [n] is 0...
- If [n] is [S n'] we require...

two paragraphs of reasoning, and two subcases:
- In the first case...
- In the second case...
So the theorem holds.
```

#### Rules.

More than 4 leading dashes produce a horizontal rule.

### Emphasis.

Text can be italicized by enclosing it in underscores. A non-identifier character must precede the leading underscore and follow the trailing underscore, so that uses of underscores in names aren't mistaken for emphasis. Usually, these are spaces or punctuation.

This sentence contains some \_emphasized text\_.

### Escaping to LaTeX and HTML.

Pure LaTeX or HTML material can be inserted using the following escape sequences:

- \$...LATEX stuff...\$ inserts some LaTeX material in math mode. Simply discarded in HTML output.
- %...LATEX stuff...% inserts some LaTeX material. Simply discarded in HTML output.
- #...HTML stuff...# inserts some HTML material. Simply discarded in LaTeX output.

Note: to simply output the characters \$, % and # and escaping their escaping role, these characters must be doubled.

#### **Verbatim**

Verbatim material is introduced by a leading << and closed by >> at the beginning of a line.

# Example

```
Here is the corresponding caml code:
<<
  let rec fact n =
    if n <= 1 then 1 else n * fact (n-1)
>>
```

### **Hyperlinks**

Hyperlinks can be inserted into the HTML output, so that any identifier is linked to the place of its definition.

coqc file.v automatically dumps localization information in file.glob or appends it to a file specified using the option --dump-glob file. Take care of erasing this global file, if any, when starting the whole compilation process.

Then invoke coqdoc or coqdoc --glob-from file to tell coqdoc to look for name resolutions in the file file (it will look in file.glob by default).

Identifiers from the Coq standard library are linked to the Coq website http://coq.inria.fr/library/. This behavior can be changed using command line options --no-externals and --coqlib; see below.

#### Hiding / Showing parts of the source.

Some parts of the source can be hidden using command line options -g and -1 (see below), or using such comments:

```
(* begin hide *)
 *some Coq material*
(* end hide *)
```

Conversely, some parts of the source which would be hidden can be shown using such comments:

7.2. Utilities 543

```
(* begin show *)
 *some Coq material*
(* end show *)
```

The latter cannot be used around some inner parts of a proof, but can be used around a whole proof.

### **Usage**

coqdoc is invoked on a shell command line as follows: coqdoc <options and files>. Any command line argument which is not an option is considered to be a file (even if it starts with a -). Coq files are identified by the suffixes .v and .g and LaTeX files by the suffix .tex.

- HTML output This is the default output format. One HTML file is created for each Coq file given on the command line, together with a file index.html (unless option-no-index is passed). The HTML pages use a style sheet named style.css. Such a file is distributed with coqdoc.
- LaTeX output A single LaTeX file is created, on standard output. It can be redirected to a file using the option -o. The order of files on the command line is kept in the final document. LaTeX files given on the command line are copied 'as is' in the final document. DVI and PostScript can be produced directly with the options -dvi and -ps respectively.
- **TEXmacs output** To translate the input files to TEXmacs format, to be used by the TEXmacs Coq interface.

#### **Command line options**

# Overall options

- -HTML Select a HTML output.
- -LaTeX Select a LaTeX output.
- -dvi Select a DVI output.
- -ps Select a PostScript output.
- -texmacs Select a TEXmacs output.
- -stdout Write output to stdout.
- -o file, -output file Redirect the output into the file 'file' (meaningless with -html).
- -d dir, -directory dir Output files into directory 'dir' instead of the current directory (option -d does not change the filename specified with the option -o, if any).
- **-body-only** Suppress the header and trailer of the final document. Thus, you can insert the resulting document into a larger one.
- -p string, -preamble string Insert some material in the LaTeX preamble, right before \begin{document} (meaningless with -html).
- -vernac-file file,-tex-file file Considers the file 'file' respectively as a .v (or .g) file or a .tex file.
- -files-from file Read filenames to be processed from the file 'file' as if they were given on the command line. Useful for program sources split up into several directories.
- -q, -quiet Be quiet. Do not print anything except errors.

- -h, -help Give a short summary of the options and exit.
- -v, -version Print the version and exit.

# Index options

The default behavior is to build an index, for the HTML output only, into index.html.

- -no-index Do not output the index.
- -multi-index Generate one page for each category and each letter in the index, together with a top page index.html.
- -index string Make the filename of the index string instead of "index". Useful since "index.html" is special.

### Table of contents option

- -toc, -table-of-contents Insert a table of contents. For a LaTeX output, it inserts a \tableofcontents at the beginning of the document. For a HTML output, it builds a table of contents into toc.html.
- -toc-depth int Only include headers up to depth int in the table of contents.

### Hyperlink options

- -glob-from file Make references using Coq globalizations from file file. (Such globalizations are obtained with Coq option -dump-glob).
- -no-externals Do not insert links to the Coq standard library.
- **-external url coqdir** Use given URL for linking references whose name starts with prefix coqdir.
- -coqlib url Set base URL for the Coq standard library (default is http://coq.inria. fr/library/). This is equivalent to --external url Coq.
- -R dir coqdir Recursively map physical directory dir to Coq logical directory coqdir (similarly to Coq option -R).
- -Q dir coqdir Map physical directory dir to Coq logical directory coqdir (similarly to Coq option -Q).

Note: options -R and -Q only have effect on the files *following* them on the command line, so you will probably need to put this option first.

#### Title options

- -s , —short Do not insert titles for the files. The default behavior is to insert a title like "Library Foo" for each file.
- -lib-name string Print "string Foo" instead of "Library Foo" in titles. For example "Chapter" and "Module" are reasonable choices.
- -no-lib-name Print just "Foo" instead of "Library Foo" in titles.
- -lib-subtitles Look for library subtitles. When enabled, the beginning of each file is checked for a comment of the form:

```
(** * ModuleName : text *)
```

where ModuleName must be the name of the file. If it is present, the text is used as a subtitle for the module in appropriate places.

7.2. Utilities 545

-t string, -title string Set the document title.

### Contents options

- -g, -gallina Do not print proofs.
- -l, -light Light mode. Suppress proofs (as with -g) and the following commands:
  - [Recursive] Tactic Definition
  - Hint / Hints
  - Require
  - Transparent / Opaque
  - Implicit Argument / Implicits
  - Section / Variable / Hypothesis / End

The behavior of options -g and -1 can be locally overridden using the (\* begin show \*) ... (\* end show \*) environment (see above).

There are a few options that control the parsing of comments:

- -parse-comments Parse regular comments delimited by (\* and \*) as well. They are typeset inline.
- **-plain-comments** Do not interpret comments, simply copy them as plain-text.
- -interpolate Use the globalization information to typeset identifiers appearing in Coq escapings inside comments.

### Language options

The default behavior is to assume ASCII 7 bit input files.

- -latin1, -latin1 Select ISO-8859-1 input files. It is equivalent to -inputenc latin1 -charset iso-8859-1.
- -utf8, -utf8 Set -inputenc utf8x for LaTeX output and-charset utf-8 for HTML output. Also use Unicode replacements for a couple of standard plain ASCII notations such as → for -> and for forall. LaTeX UTF-8 support can be found at http://www.ctan.org/pkg/unicode. For the interpretation of Unicode characters by LaTeX, extra packages which coqdoc does not provide by default might be required, such as textgreek for some Greek letters or stmaryrd for some mathematical symbols. If a Unicode character is missing an interpretation in the utf8x input encoding, add \DeclareUnicodeCharacter{code}{LATEX-interpretation}. Packages and declarations can be added with option -p.
- -inputenc string Give a LaTeX input encoding, as an option to LaTeX package inputenc.
- -charset string Specify the HTML character set, to be inserted in the HTML header.

### The coqdoc LaTeX style file

In case you choose to produce a document without the default LaTeX preamble (by using option --no-preamble), then you must insert into your own preamble the command

\usepackage{coqdoc}

The package optionally takes the argument [color] to typeset identifiers with colors (this requires the xcolor package).

Then you may alter the rendering of the document by redefining some macros:

```
coqdockw, coqdocid, ... The one-argument macros for typesetting keywords and identifiers.
Defaults are sans-serif for keywords and italic for identifiers.For example, if you would like
a slanted font for keywords, you may insert

\renewcommand{\coqdockw}[1]{\textsl{#1}}

anywhere between \usepackage{coqdoc} and \begin{document}.

coqdocmodule One-argument macro for typesetting the title of a .v file. Default is
\newcommand{\coqdocmodule}[1]{\section*{Module #1}}

and you may redefine it using \renewcommand.
```

# 7.2.5 Embedded Coq phrases inside LaTeX documents

When writing documentation about a proof development, one may want to insert Coq phrases inside a LaTeX document, possibly together with the corresponding answers of the system. We provide a mechanical way to process such Coq phrases embedded in LaTeX files: the coq-tex filter. This filter extracts Coq phrases embedded in LaTeX files, evaluates them, and insert the outcome of the evaluation after each phrase.

Starting with a file file.tex containing Coq phrases, the coq-tex filter produces a file named file.v.tex with the Coq outcome.

There are options to produce the Coq parts in smaller font, italic, between horizontal rules, etc. See the man page of coq-tex for more details.


# 7.2.6 Man pages

There are man pages for the commands coqdep and coq-tex. Man pages are installed at installation time (see installation instructions in file INSTALL, step 6).

# 7.3 Coq Integrated Development Environment

The Coq Integrated Development Environment is a graphical tool, to be used as a user-friendly replacement to coqtop. Its main purpose is to allow the user to navigate forward and backward into a Coq vernacular file, executing corresponding commands or undoing them respectively.

CoqIDE is run by typing the command coqide on the command line. Without argument, the main screen is displayed with an "unnamed buffer", and with a filename as argument, another buffer displaying the contents of that file. Additionally, coqide accepts the same options as coqtop, given in *The Coq commands*, the ones having obviously no meaning for CoqIDE being ignored.



A sample CoqIDE main screen, while navigating into a file Fermat.v, is shown in the figure CoqIDE main screen. At the top is a menu bar, and a tool bar below it. The large window on the left is displaying the various script buffers. The upper right window is the goal window, where goals to be proven are displayed. The lower right window is the message window, where various messages resulting from commands are displayed. At the bottom is the status bar.

# 7.3.1 Managing files and buffers, basic editing

In the script window, you may open arbitrarily many buffers to edit. The *File* menu allows you to open files or create some, save them, print or export them into various formats. Among all these buffers, there is always one which is the current *running buffer*, whose name is displayed on a background in the *processed* color (green by default), which is the one where Coq commands are currently executed.

Buffers may be edited as in any text editor, and classical basic editing commands (Copy/Paste, ...) are available in the *Edit* menu. CoqIDE offers only basic editing commands, so if you need more complex editing commands, you may launch your favorite text editor on the current buffer, using the *Edit/External Editor* menu.

# 7.3.2 Interactive navigation into Coq scripts

The running buffer is the one where navigation takes place. The toolbar offers five basic commands for this. The first one, represented by a down arrow icon, is for going forward executing one command. If that command is successful, the part of the script that has been executed is displayed on a background with the processed color. If that command fails, the error message is displayed in the message window, and the location of the error is emphasized by an underline in the error foreground color (red by default).

In the figure *CoqIDE main screen*, the running buffer is Fermat.v, all commands until the Theorem have been already executed, and the user tried to go forward executing Induction n. That command failed because no such tactic exists (names of standard tactics are written in lowercase), and the failing command is underlined.

Notice that the processed part of the running buffer is not editable. If you ever want to modify something you have to go backward using the up arrow tool, or even better, put the cursor where you want to go back and use the goto button. Unlike with coqtop, you should never use Undo to go backward.

There are two additional buttons for navigation within the running buffer. The "down" button with a line goes directly to the end; the "up" button with a line goes back to the beginning. The handling of errors when using the go-to-the-end button depends on whether Coq is running in asynchronous mode or not (see Chapter Asynchronous and Parallel Proof Processing). If it is not running in that mode, execution stops as soon as an error is found. Otherwise, execution continues, and the error is marked with an underline in the error foreground color, with a background in the error background color (pink by default). The same characterization of error-handling applies when running several commands using the "goto" button.

If you ever try to execute a command that runs for a long time and would like to abort it before it terminates, you may use the interrupt button (the white cross on a red circle).

There are other buttons on the CoqIDE toolbar: a button to save the running buffer; a button to close the current buffer (an "X"); buttons to switch among buffers (left and right arrows); an "information" button; and a "gears" button.

The "gears" button submits proof terms to the Coq kernel for type checking. When Coq uses asynchronous processing (see Chapter Asynchronous and Parallel Proof Processing), proofs may have been completed without kernel-checking of generated proof terms. The presence of unchecked proof terms is indicated by Qed statements that have a subdued being-processed color (light blue by default), rather than the processed color, though their preceding proofs have the processed color.


Notice that for all these buttons, except for the "gears" button, their operations are also available in the menu, where their keyboard shortcuts are given.

### 7.3.3 Vernacular commands, templates

The Templates menu allows using shortcuts to insert vernacular commands. This is a nice way to proceed if you are not sure of the syntax of the command you want.

Moreover, from this menu you can automatically insert templates of complex commands like Fixpoint that you can conveniently fill afterwards.

### 7.3.4 Queries



We call *query* any vernacular command that does not change the current state, such as Check, Search, etc. To run such commands interactively, without writing them in scripts, CoqIDE offers a *query pane*. The query pane can be displayed on demand by using the View menu, or using the shortcut F1. Queries can also be performed by selecting a particular phrase, then choosing an item from the Queries menu. The response then appears in the message window. The image above shows the result after selecting of the phrase Nat.mul in the script window, and choosing Print from the Queries menu.

### 7.3.5 Compilation

The Compile menu offers direct commands to:

- compile the current buffer
- run a compilation using make
- go to the last compilation error
- create a Makefile using coq\_makefile.

### 7.3.6 Customizations

You may customize your environment using the menu Edit/Preferences. A new window will be displayed, with several customization sections presented as a notebook.

The first section is for selecting the text font used for scripts, goal and message windows.

The second and third sections are for controlling colors and style of the three main buffers. A predefined Coq highlighting style as well as standard GtkSourceView styles are available. Other styles can be added e.g. in \$HOME/.local/share/gtksourceview-3.0/styles/ (see the general documentation about GtkSourceView for the various possibilities). Note that the style of the rest of graphical part of Coqide is not under the control of GtkSourceView but of GTK+ and governed by files such as settings.ini and gtk.css in \$XDG\_CONFIG\_HOME/gtk-3.0 or files in \$HOME/.themes/NameOfTheme/gtk-3.0, as well as the environment variable GTK\_THEME (search on internet for the various possibilities).

The fourth section is for customizing the editor. It includes in particular the ability to activate an Emacs mode named micro-Proof-General (use the Help menu to know more about the available bindings).

The next section is devoted to file management: you may configure automatic saving of files, by periodically saving the contents into files named #f# for each opened file f. You may also activate the *revert* feature: in case a opened file is modified on the disk by a third party, CoqIDE may read it again for you. Note that in the case you edited that same file, you will be prompted to choose to either discard your changes or not. The File charset encoding choice is described below in *Character encoding for saved files*.

The Externals section allows customizing the external commands for compilation, printing, web browsing. In the browser command, you may use %s to denote the URL to open, for example: firefox -remote "OpenURL(%s)".

Notice that these settings are saved in the file coqiderc in the coq subdirectory of the user configuration directory which is the value of \$XDG\_CONFIG\_HOME if this environment variable is set and which otherwise is \$HOME/.config/.

A GTK+ accelerator keymap is saved under the name coqide.keys in the same coq subdirectory of the user configuration directory. It is not recommended to edit this file manually: to modify a given menu shortcut, go to the corresponding menu item without releasing the mouse button, press the key you want for the new shortcut, and release the mouse button afterwards. If your system does not allow it, you may still edit this configuration file by hand, but this is more involved.

# 7.3.7 Using Unicode symbols

CoqIDE is based on GTK+ and inherits from it support for Unicode in its text windows. Consequently a large set of symbols is available for notations. Furthermore, CoqIDE conveniently provides a simple way to input Unicode characters.

### **Displaying Unicode symbols**

You just need to define suitable notations as described in the chapter *Syntax extensions and interpretation scopes*. For example, to use the mathematical symbols and , you may define:

```
Notation " x .. y , P" := (forall x, .. (forall y, P) ..) (at level 200, x binder, y binder, right associativity) : type_scope. Notation " x .. y , P" := (exists x, .. (exists y, P) ..) (at level 200, x binder, y binder, right associativity) : type_scope.
```

There exists a small set of such notations already defined, in the file utf8.v of Coq library, so you may enable them just by Require Import Unicode.Utf8 inside CoqIDE, or equivalently, by starting CoqIDE with coqide -1 utf8.

However, there are some issues when using such Unicode symbols: you of course need to use a character font which supports them. In the Fonts section of the preferences, the Preview line displays some Unicode symbols, so you could figure out if the selected font is OK. Related to this, one thing you may need to do is choosing whether GTK+ should use antialiased fonts or not, by setting the environment variable GDK\_USE\_XFT to 1 or 0 respectively.

### Bindings for input of Unicode symbols

CoqIDE supports a builtin mechanism to input non-ASCII symbols. For example, to input  $\pi$ , it suffices to type \pi then press the combination of key Shift+Space (default key binding). Often, it suffices to type a prefix of the latex token, e.g. typing \p then Shift+Space suffices to insert a  $\pi$ .

For several symbols, ASCII art is also recognized, e.g. \-> for a right arrow, or \>= for a greater than or equal sign.

A larger number of latex tokens are supported by default. The full list is available here: https://github.com/coq/coq/blob/master/ide/default\_bindings\_src.ml

Custom bindings may be added, as explained further on.

**Note:** It remains possible to input non-ASCII symbols using system-wide approaches independent of CoqIDE.

### Adding custom bindings

To extend the default set of bindings, create a file named coqide.bindings and place it in the same folder as coqide.keys. This would be the folder \$XDG\_CONFIG\_HOME/coq, defaulting to ~/.config/coq if XDG\_CONFIG\_HOME is unset. The file coqide.bindings should contain one binding per line, in the form \key value, followed by an optional priority integer. (The key and value should not contain any space character.)

### Example

Here is an example configuration file:

\par || \pi  $\pi$  1 \le 1 \lambda  $\lambda$  2 \lambdas  $\lambda$ s

Above, the priority number 1 on \pi indicates that the prefix \p should resolve to \pi, and not to something else (e.g. \par). Similarly, the above settings ensure than \l resolves to \le, and that \la resolves to \lambda.

It can be useful to work with per-project binding files. For this purpose CoqIDE accepts a command line argument of the form -unicode-bindings file1,file2,...,fileN. Each of the file tokens provided may consists of one of:

• a path to a custom bindings file,

- the token default, which resolves to the default bindings file,
- the token local, which resolves to the coqide.bindings file stored in the user configuration directory.

Warning: If a filename other than the first one includes a "~" to refer to the home directory, it won't be expanded properly. To work around that issue, one should not use comas but instead repeat the flag, in the form: -unicode-bindings file1 .. -unicode-bindings fileN.

**Note:** If two bindings for a same token both have the same priority value (or both have no priority value set), then the binding considered is the one from the file that comes first on the command line.

### Character encoding for saved files

In the Files section of the preferences, the encoding option is related to the way files are saved.

If you have no need to exchange files with non UTF-8 aware applications, it is better to choose the UTF-8 encoding, since it guarantees that your files will be read again without problems. (This is because when CoqIDE reads a file, it tries to automatically detect its character encoding.)

If you choose something else than UTF-8, then missing characters will be written encoded by  $x\{....\}$  or  $x\{....\}$  where each dot is an hexadecimal digit: the number between braces is the hexadecimal Unicode index for the missing character.

**CHAPTER** 

**EIGHT** 

# **ADDENDUM**

# 8.1 Extended pattern matching

Authors Cristina Cornes and Hugo Herbelin

This section describes the full form of pattern matching in Coq terms.

### 8.1.1 Patterns

The full syntax of match is presented in section *Terms*. Identifiers in patterns are either constructor names or variables. Any identifier that is not the constructor of an inductive or co-inductive type is considered to be a variable. A variable name cannot occur more than once in a given pattern. It is recommended to start variable names by a lowercase letter.

If a pattern has the form c x where c is a constructor symbol and x is a linear vector of (distinct) variables, it is called simple: it is the kind of pattern recognized by the basic version of match. On the opposite, if it is a variable x or has the form c p with p not only made of variables, the pattern is called nested.

A variable pattern matches any value, and the identifier is bound to that value. The pattern "\_" (called "don't care" or "wildcard" symbol) also matches any value, but does not bind anything. It may occur an arbitrary number of times in a pattern. Alias patterns written (pattern as ident) are also accepted. This pattern matches the same values as pattern does and ident is bound to the matched value. A pattern of the form pattern | pattern is called disjunctive. A list of patterns separated with commas is also considered as a pattern and is called multiple pattern. However multiple patterns can only occur at the root of pattern matching equations. Disjunctions of multiple patterns are allowed though.

Since extended match expressions are compiled into the primitive ones, the expressiveness of the theory remains the same. Once parsing has finished only simple patterns remain. The original nesting of the match expressions is recovered at printing time. An easy way to see the result of the expansion is to toggle off the nesting performed at printing (use here *Printing Matching*), then by printing the term with *Print* if the term is a constant, or using the command *Check*.

The extended match still accepts an optional *elimination predicate* given after the keyword return. Given a pattern matching expression, if all the right-hand-sides of => have the same type, then this type can be sometimes synthesized, and so we can omit the return part. Otherwise the predicate after return has to be provided, like for the basicmatch.

Let us illustrate through examples the different aspects of extended pattern matching. Consider for example the function that computes the maximum of two natural numbers. We can write it in primitive syntax by:

```
Fixpoint max (n m:nat) {struct m} : nat :=
  match n with
  | 0 => m
```

```
 | \ S \ n' \ => \ match \ m \ with \\ | \ 0 \ => \ S \ n' \\ | \ S \ m' \ => \ S \ (max \ n' \ m') \\ end \\ end.
```

# 8.1.2 Multiple patterns

Using multiple patterns in the definition of max lets us write:

```
Fixpoint max (n m:nat) {struct m} : nat :=
    match n, m with
    | 0, _ => m
    | S n', 0 => S n'
    | S n', S m' => S (max n' m')
    end.
```

which will be compiled into the previous form.

The pattern matching compilation strategy examines patterns from left to right. A match expression is generated **only** when there is at least one constructor in the column of patterns. E.g. the following example does not build a match expression.

```
Check (fun x:nat => match x return nat with  \mid \ y \ => \ y \\  \qquad \qquad end) \, . fun x : nat => x  \qquad : \ nat \ -> \ nat
```

# 8.1.3 Aliasing subpatterns

We can also use **as** *ident* to associate a name to a sub-pattern:

```
Fixpoint max (n m:nat) {struct n} : nat :=
  match n, m with
  | 0, _ => m
  | S n' as p, 0 => p
  | S n', S m' => S (max n' m')
  end.
```

# 8.1.4 Nested patterns

Here is now an example of nested patterns:

```
Fixpoint even (n:nat) : bool :=
  match n with
  | 0 => true
  | S 0 => false
  | S (S n') => even n'
  end.
```

This is compiled into:

```
Unset Printing Matching.
Print even.
  even =
  fix even (n : nat) : bool :=
  match n with
   | 0 => true
  | S n0 => match n0 with
   | 0 => false
   | S n' => even n'
   end
end
  : nat -> bool
```

Arguments even \_%nat\_scope

In the previous examples patterns do not conflict with, but sometimes it is comfortable to write patterns that admit a non trivial superposition. Consider the boolean function lef that given two natural numbers yields true if the first one is less or equal than the second one and false otherwise. We can write it as follows:

```
Fixpoint lef (n m:nat) {struct m} : bool :=
  match n, m with
  | 0, x => true
  | x, 0 => false
  | S n, S m => lef n m
  end.
```

Note that the first and the second multiple pattern overlap because the couple of values 0 0 matches both. Thus, what is the result of the function on those values? To eliminate ambiguity we use the *textual priority* rule: we consider patterns to be ordered from top to bottom. A value is matched by the pattern at the ith row if and only if it is not matched by some pattern from a previous row. Thus in the example, 0 0 is matched by the first pattern, and so (lef 0 0) yields true.

Another way to write this function is:

```
Fixpoint lef (n m:nat) {struct m} : bool :=
  match n, m with
  | 0, x => true
  | S n, S m => lef n m
  | _, _ => false
  end.
```

Here the last pattern superposes with the first two. Because of the priority rule, the last pattern will be used only for values that do not match neither the first nor the second one.

Terms with useless patterns are not accepted by the system. Here is an example:

# 8.1.5 Disjunctive patterns

Multiple patterns that share the same right-hand-side can be factorized using the notation mult\_pattern For instance, max can be rewritten as follows:

```
Fixpoint max (n m:nat) {struct m} : nat :=
  match n, m with
  | S n', S m' => S (max n' m')
  | 0, p | p, 0 => p
  end.
```

Similarly, factorization of (not necessarily multiple) patterns that share the same variables is possible by using the notation pattern. Here is an example:

```
Definition filter_2_4 (n:nat) : nat :=
  match n with
  | 2 as m | 4 as m => m
  | _ => 0
  end.
```

Nested disjunctive patterns are allowed, inside parentheses, with the notation (pattern), as in:

```
Definition filter_some_square_corners (p:nat*nat) : nat*nat :=
  match p with
  | ((2 as m | 4 as m), (3 as n | 5 as n)) => (m,n)
  | _ => (0,0)
  end.
```

# 8.1.6 About patterns of parametric types

### Parameters in patterns

When matching objects of a parametric type, parameters do not bind in patterns. They must be substituted by "\_". Consider for example the type of polymorphic lists:

```
Inductive List (A:Set) : Set :=
| nil : List A
| cons : A -> List A -> List A.
```

We can check the function *tail*:

Check

When we use parameters in patterns there is an error message:

```
Fail Check
  (fun 1:List nat =>
    match 1 with
     | nil A => nil nat
     | cons A _ 1' => 1'
     end).
    The command has indeed failed with message:
    The parameters do not bind in patterns; they must be replaced by '_'.
Flag: Asymmetric Patterns
     This flag (off by default) removes parameters from constructors in patterns:
Set Asymmetric Patterns.
Check (fun 1:List nat =>
 match 1 with
  | nil => nil _
  | cons _ 1' => 1'
 end).
   fun 1 : List nat => match 1 with
                        | @nil _ => nil nat
                        | @cons _ _ 1' => 1'
         : List nat -> List nat
```

# 8.1.7 Implicit arguments in patterns

Unset Asymmetric Patterns.

By default, implicit arguments are omitted in patterns. So we write:

But the possibility to use all the arguments is given by "C" implicit explicitations (as for terms, see *Explicit applications*).

```
end
: List nat -> List nat
```

# 8.1.8 Matching objects of dependent types

The previous examples illustrate pattern matching on objects of non-dependent types, but we can also use the expansion strategy to destructure objects of dependent types. Consider the type listn of lists of a certain length:

```
Inductive listn : nat -> Set :=
| niln : listn 0
| consn : forall n:nat, nat -> listn n -> listn (S n).
```

# 8.1.9 Understanding dependencies in patterns

We can define the function length over listn by:

```
Definition length (n:nat) (1:listn n) := n.
```

Just for illustrating pattern matching, we can define it by case analysis:

```
Definition length (n:nat) (1:listn n) :=
  match 1 with
  | niln => 0
  | consn n _ _ => S n
  end.
```

We can understand the meaning of this definition using the same notions of usual pattern matching.

# 8.1.10 When the elimination predicate must be provided

### Dependent pattern matching

The examples given so far do not need an explicit elimination predicate because all the right hand sides have the same type and Coq succeeds to synthesize it. Unfortunately when dealing with dependent patterns it often happens that we need to write cases where the types of the right hand sides are different instances of the elimination predicate. The function concat for listn is an example where the branches have different types and we need to provide the elimination predicate:

```
Fixpoint concat (n:nat) (1:listn n) (m:nat) (1':listn m) {struct l} :
  listn (n + m) :=
  match l in listn n return listn (n + m) with
  | niln => l'
  | consn n' a y => consn (n' + m) a (concat n' y m l')
  end.
```

The elimination predicate is fun (n:nat) (1:listn n) => listn (n+m). In general if m has type (I q1 ... qr t1 ... ts) where q1, ..., qr are parameters, the elimination predicate should be of the form fun y1 ... ys x : (I q1 ... qr y1 ... ys ) => Q.

In the concrete syntax, it should be written: match m as x in (I \_ ... \_ y1 ... ys) return Q with ... end. The variables which appear in the in and as clause are new and bounded in the property Q in the return clause. The parameters of the inductive definitions should not be mentioned and are replaced by \_.

### Multiple dependent pattern matching

Recall that a list of patterns is also a pattern. So, when we destructure several terms at the same time and the branches have different types we need to provide the elimination predicate for this multiple pattern. It is done using the same scheme: each term may be associated to an **as** clause and an **in** clause in order to introduce a dependent product.

For example, an equivalent definition for concat (even though the matching on the second term is trivial) would have been:

```
Fixpoint concat (n:nat) (1:listn n) (m:nat) (1':listn m) {struct 1} :
  listn (n + m) :=
  match 1 in listn n, 1' return listn (n + m) with
  | niln, x => x
  | consn n' a y, x => consn (n' + m) a (concat n' y m x)
  end.
```

Even without real matching over the second term, this construction can be used to keep types linked. If a and b are two listn of the same length, by writing

```
Check (fun n (a b: listn n) =>
match a, b with
  | niln, b0 => tt
  | consn n' a y, bS => tt
end).
```

we have a copy of b in type listn 0 resp. listn (S n').

#### Patterns in in

If the type of the matched term is more precise than an inductive applied to variables, arguments of the inductive in the in branch can be more complicated patterns than a variable.

Moreover, constructors whose types do not follow the same pattern will become impossible branches. In an impossible branch, you can answer anything but False\_rect unit has the advantage to be subterm of anything.

To be concrete: the tail function can be written:

```
Definition tail n (v: listn (S n)) :=
  match v in listn (S m) return listn m with
  | niln => False_rect unit
  | consn n' a y => y
  end.
```

and tail n v will be subterm of v.

### 8.1.11 Using pattern matching to write proofs

In all the previous examples the elimination predicate does not depend on the object(s) matched. But it may depend and the typical case is when we write a proof by induction or a function that yields an object

of a dependent type. An example of a proof written using match is given in the description of the tactic refine.

For example, we can write the function **buildlist** that given a natural number **n** builds a list of length **n** containing zeros as follows:

```
Fixpoint buildlist (n:nat) : listn n :=
  match n return listn n with
  | 0 => niln
  | S n => consn n 0 (buildlist n)
  end.
```

We can also use multiple patterns. Consider the following definition of the predicate less-equal Le:

We can use multiple patterns to write the proof of the lemma forall (n m:nat), (LE n m) \/ (LE m n):

```
Fixpoint dec (n m:nat) {struct n} : LE n m \/ LE m n :=
  match n, m return LE n m \/ LE m n with
  | 0, x => or_introl (LE x 0) (LEO x)
  | x, 0 => or_intror (LE x 0) (LEO x)
  | S n as n', S m as m' =>
      match dec n m with
  | or_introl h => or_introl (LE m' n') (LES n m h)
  | or_intror h => or_intror (LE n' m') (LES m n h)
  end
end.
```

In the example of dec, the first match is dependent while the second is not.

The user can also use match in combination with the tactic *refine* to build incomplete proofs beginning with a match construction.

# 8.1.12 Pattern-matching on inductive objects involving local definitions

If local definitions occur in the type of a constructor, then there are two ways to match on this constructor. Either the local definitions are skipped and matching is done only on the true arguments of the constructors, or the bindings for local definitions can also be caught in the matching.

### Example

```
Inductive list : nat -> Set :=
| nil : list 0
| cons : forall n:nat, let m := (2 * n) in list m -> list (S (S m)).
```

In the next example, the local definition is not caught.

```
Fixpoint length n (1:list n) {struct 1} : nat :=
  match 1 with
  | nil => 0
  | cons n 10 => S (length (2 * n) 10)
  end.
```

But in this example, it is.

```
Fixpoint length' n (1:list n) {struct 1} : nat :=
  match 1 with
  | nil => 0
  | @cons _ m 10 => S (length' m 10)
  end.
```

**Note:** For a given matching clause, either none of the local definitions or all of them can be caught.

Note: You can only catch let bindings in mode where you bind all variables and so you have to use @ syntax.

**Note:** this feature is incoherent with the fact that parameters cannot be caught and consequently is somehow hidden. For example, there is no mention of it in error messages.

# 8.1.13 Pattern-matching and coercions

If a mismatch occurs between the expected type of a pattern and its actual type, a coercion made from constructors is sought. If such a coercion can be found, it is automatically inserted around the pattern.

### Example

# 8.1.14 When does the expansion strategy fail?

The strategy works very like in ML languages when treating patterns of non-dependent types. But there are new cases of failure that are due to the presence of dependencies.

The error messages of the current implementation may be sometimes confusing. When the tactic fails because patterns are somehow incorrect then error messages refer to the initial expression. But the strategy may succeed to build an expression whose sub-expressions are well typed when the whole expression is not. In this situation the message makes reference to the expanded expression. We encourage users, when they have patterns with the same outer constructor in different equations, to name the variable patterns in the same positions with the same name. E.g. to write  $(cons \ n \ x) \Rightarrow e1$  and  $(cons \ n \ x) \Rightarrow e2$  instead

of  $(\cos n \ 0 \ x) => e1$  and  $(\cos n' \ x') => e2$ . This helps to maintain certain name correspondence between the generated expression and the original.

Here is a summary of the error messages corresponding to each situation:

Error: The constructor ident expects num arguments.

The variable ident is bound several times in pattern termFound a constructor of inductive type term while a constructor of term is expectedPatterns are incorrect (because constructors are not applied to the correct number of the arguments, because they are not linear or they are wrongly typed).

Error: Non exhaustive pattern matching.

The pattern matching is not exhaustive.

Error: The elimination predicate term should be of arity num (for non dependent case) or num (for dependent case). The elimination predicate provided to match has not the expected arity.

Error: Unable to infer a match predicate

Error: Either there is a type incompatibility or the problem involves dependencies.

There is a type mismatch between the different branches. The user should provide an elimination predicate.

# 8.2 Implicit Coercions

Author Amokrane Saïbi

### 8.2.1 General Presentation

This section describes the inheritance mechanism of Coq. In Coq with inheritance, we are not interested in adding any expressive power to our theory, but only convenience. Given a term, possibly not typable, we are interested in the problem of determining if it can be well typed modulo insertion of appropriate coercions. We allow to write:

- f a where f:(forall x:A,B) and a:A' when A' can be seen in some sense as a subtype of A.
- x:A when A is not a type, but can be seen in a certain sense as a type: set, group, category etc.
- f a when f is not a function, but can be seen in a certain sense as a function: bijection, functor, any structure morphism etc.

### 8.2.2 Classes

A class with n parameters is any defined name with a type forall  $(ident_1 : type_1)..(ident_n : type_n)$ , sort. Thus a class with parameters is considered as a single class and not as a family of classes. An object of a class is any term of type  $class \ term_1 ... \ term_n$ . In addition to these user-defined classes, we have two built-in classes:

- Sortclass, the class of sorts; its objects are the terms whose type is a sort (e.g. Prop or Type).
- Funclass, the class of functions; its objects are all the terms with a functional type, i.e. of form forall x:A,B.

Formally, the syntax of classes is defined as:

```
\begin{array}{ccc} {\tt class} & ::= & \textit{qualid} \\ & {\tt Sortclass} \end{array}
```

Funclass

### 8.2.3 Coercions

A name f can be declared as a coercion between a source user-defined class C with n parameters and a target class D if one of these conditions holds:

- D is a user-defined class, then the type of f must have the form forall  $(x_1:A_1)..(x:A)(y:C x_1..x)$ , D  $u_1..u$  where m is the number of parameters of D.
- D is Funclass, then the type of f must have the form forall  $(x_1:A_1)..(x:A)(y:C x_1..x)(x:A)$ , B.
- D is Sortclass, then the type of f must have the form forall  $(x_1:A_1)..(x:A)(y:C x_1..x)$ , s with s a sort.

We then write f : C >-> D. The restriction on the type of coercions is called the uniform inheritance condition.

Note: The built-in class Sortclass can be used as a source class, but the built-in class Funclass cannot.

To coerce an object t:C  $t_1...t$  of C towards D, we have to apply the coercion f to it; the obtained term f  $t_1...t$  is then an object of D.

# 8.2.4 Identity Coercions

Identity coercions are special cases of coercions used to go around the uniform inheritance condition. Let C and D be two classes with respectively n and m parameters and  $f:forall\ (x_1:T_1)..(x:T)(y:C\ u_1..u)$ ,  $D\ v_1..v$  a function which does not verify the uniform inheritance condition. To declare f as coercion, one has first to declare a subclass C' of C:

$$C' := fun (x_1:T_1)..(x:T) => C u_1..u$$

We then define an *identity coercion* between C' and C:

$$Id_C'_C := fun (x_1:T_1)..(x:T)(y:C' x_1..x) \Rightarrow (y:C u_1..u)$$

We can now declare f as coercion from C' to D, since we can "cast" its type as forall  $(x_1:T_1)..(x:T)(y:C'x_1..x)$ , D  $v_1..v$ .

The identity coercions have a special status: to coerce an object  $t:C' t_1...t$  of C' towards C, we do not have to insert explicitly  $Id_C'_C$  since  $Id_C'_C t_1...t$  t is convertible with t. However we "rewrite" the type of t to become an object of C; in this case, it becomes C u'...u' where each u' is the result of the substitution in u of the variables x by t.

### 8.2.5 Inheritance Graph

Coercions form an inheritance graph with classes as nodes. We call *coercion path* an ordered list of coercions between two nodes of the graph. A class C is said to be a subclass of D if there is a coercion path in the graph from C to D; we also say that C inherits from D. Our mechanism supports multiple inheritance since a class may inherit from several classes, contrary to simple inheritance where a class inherits from at most one class. However there must be at most one path between two classes. If this is not the case, only the *oldest* one is valid and the others are ignored. So the order of declaration of coercions is important.

We extend notations for coercions to coercion paths. For instance  $[f_1; ...; f]: C >-> D$  is the coercion path composed by the coercions  $f_1...f$ . The application of a coercion path to a term consists of the successive application of its coercions.

# 8.2.6 Declaring Coercions

Command: Coercion qualid : class >-> class

Declares the construction denoted by qualid as a coercion between the two given classes.

Error: qualid not declared.

Error: qualid is already a coercion.

Error: Funclass cannot be a source class.

Error: qualid is not a function.

Error: Cannot find the source class of qualid.

Error: Cannot recognize class as a source class of qualid.

Warning: qualid does not respect the uniform inheritance condition.

Error: Found target class ... instead of ...

Warning: New coercion path ... is ambiguous with existing ...

When the coercion qualid is added to the inheritance graph, new coercion paths which have the same classes as existing ones are ignored. The Coercion command tries to check the convertibility of new ones and existing ones. The paths for which this check fails are displayed by a warning in the form  $[f_1; ...; f]$ : C >-> D.

The convertibility checking procedure for coercion paths is complete for paths consisting of coercions satisfying the uniform inheritance condition, but some coercion paths could be reported as ambiguous even if they are convertible with existing ones when they have coercions that don't satisfy the uniform inheritance condition.

Variant: Local Coercion qualid : class >-> class

Declares the construction denoted by qualid as a coercion local to the current section.

```
Variant: Coercion ident := term type ?
```

This defines *ident* just like Definition *ident* := term type?, and then declares *ident* as a coercion between it source and its target.

```
Variant: Local Coercion ident := term type
```

This defines *ident* just like Let *ident* := term type, and then declares *ident* as a coercion between it source and its target.

Assumptions can be declared as coercions at declaration time. This extends the grammar of assumptions from Figure *The Vernacular* as follows:

If the extra > is present before the type of some assumptions, these assumptions are declared as coercions.

Similarly, constructors of inductive types can be declared as coercions at definition time of the inductive type. This extends and modifies the grammar of inductive types from Figure *The Vernacular* as follows:

Especially, if the extra > is present in a constructor declaration, this constructor is declared as a coercion.

### Command: Identity Coercion ident : class >-> class

If C is the source class and D the destination, we check that C is a constant with a body of the form fun  $(x_1:T_1)..(x:T) \Rightarrow D \ t_1..t$  where m is the number of parameters of D. Then we define an identity function with type forall  $(x_1:T_1)..(x:T)(y:C \ x_1..x)$ , D  $t_1..t$ , and we declare it as an identity coercion between C and D.

Error: class must be a transparent constant.

```
Variant: Local Identity Coercion ident: ident >-> ident
Same as Identity Coercion but locally to the current section.
```

```
Variant: SubClass ident := type
```

If type is a class ident' applied to some arguments then ident is defined and an identity coercion of name  $Id\_ident\_ident'$  is declared. Otherwise said, this is an abbreviation for

```
Definition ident := type. Identity Coercion Id_ident_ident' : ident >-> ident'.
```

#### Variant: Local SubClass ident := type

Same as before but locally to the current section.

# 8.2.7 Displaying Available Coercions

### Command: Print Classes

Print the list of declared classes in the current context.

### Command: Print Coercions

Print the list of declared coercions in the current context.

#### Command: Print Graph

Print the list of valid coercion paths in the current context.

### Command: Print Coercion Paths class class

Print the list of valid coercion paths between the two given classes.

# 8.2.8 Activating the Printing of Coercions

# Flag: Printing Coercions

When on, this flag forces all the coercions to be printed. By default, coercions are not printed.

### Table: Printing Coercion qualid

Specifies a set of qualids for which coercions are always displayed. Use the Add @table and Remove @table commands to update the set of qualids.

### 8.2.9 Classes as Records

We allow the definition of *Structures with Inheritance* (or classes as records) by extending the existing *Record* macro. Its new syntax is:

The first identifier *ident* is the name of the defined record and *sort* is its type. The optional identifier after := is the name of the constructor (it will be Build\_*ident* if not given). The other identifiers are the names of the fields, and *term* are their respective types. If :> is used instead of : in the declaration of a field, then the name of this field is automatically declared as a coercion from the record name to the class of this field type. Note that the fields always verify the uniform inheritance condition. If the optional > is given before the record name, then the constructor name is automatically declared as a coercion from the class of the last field type to the record name (this may fail if the uniform inheritance condition is not satisfied).

```
Variant: Structure > ident binders : sort := ident ? { ident :> ? term }
```

This is a synonym of Record.

### 8.2.10 Coercions and Sections

The inheritance mechanism is compatible with the section mechanism. The global classes and coercions defined inside a section are redefined after its closing, using their new value and new type. The classes and coercions which are local to the section are simply forgotten. Coercions with a local source class or a local target class, and coercions which do not verify the uniform inheritance condition any longer are also forgotten.

# 8.2.11 Coercions and Modules

The coercions present in a module are activated only when the module is explicitly imported.

# 8.2.12 Examples

There are three situations:

### Coercion at function application

f a is ill-typed where f:forall x:A,B and a:A'. If there is a coercion path between A' and A, then f a is transformed into f a' where a' is the result of the application of this coercion path to a.

We first give an example of coercion between atomic inductive types

```
Definition bool_in_nat (b:bool) := if b then 0 else 1.
   bool_in_nat is defined

Coercion bool_in_nat : bool >-> nat.
   bool_in_nat is now a coercion

Check (0 = true).
   0 = true
```

```
: Prop

Set Printing Coercions.
Check (0 = true).
0 = bool_in_nat true
: Prop

Unset Printing Coercions.
```

Warning: Note that Check (true = 0) would fail. This is "normal" behavior of coercions. To validate true=0, the coercion is searched from nat to bool. There is none.

We give an example of coercion between classes with parameters.

```
Parameters (C : nat \rightarrow Set) (D : nat \rightarrow bool \rightarrow Set) (E : bool \rightarrow Set).
    C is declared
    D is declared
    E is declared
Parameter f : forall n:nat, C n \rightarrow D (S n) true.
    f is declared
Coercion f : C >-> D.
    f is now a coercion
Parameter g : forall (n:nat) (b:bool), D n b -> E b.
    g is declared
Coercion g : D >-> E.
    g is now a coercion
Parameter c : C 0.
    c is declared
Parameter T : E true -> nat.
    T is declared
Check (T c).
    Тс
         : nat
Set Printing Coercions.
Check (T c).
    T (g 1 true (f 0 c))
         : nat
Unset Printing Coercions.
We give now an example using identity coercions.
Definition D' (b:bool) := D 1 b.
    D' is defined
Identity Coercion IdD'D : D' >-> D.
```

```
Print IdD'D.
    IdD'D =
    (fun (b : bool) (x : D' b) \Rightarrow x) : forall b : bool, D' b \Rightarrow D 1 b
          : forall b : bool, D' b \rightarrow D 1 b
    Arguments IdD'D _%bool_scope
    IdD'D is a coercion
Parameter d' : D' true.
    d' is declared
Check (T d').
   T d'
          : nat
Set Printing Coercions.
Check (T d').
    T (g 1 true d')
         : nat
Unset Printing Coercions.
```

In the case of functional arguments, we use the monotonic rule of sub-typing. To coerce t: forall x: A, B towards forall x: A', B', we have to coerce A' towards A and B towards B'. An example is given below:

```
Parameters (A B : Set) (h : A \rightarrow B).
    A is declared
    B is declared
    h is declared
Coercion h : A > -> B.
    h is now a coercion
Parameter U : (A -> E true) -> nat.
    U is declared
Parameter t : B -> C 0.
    t is declared
Check (U t).
    U (fun x : A \Rightarrow t x)
         : nat
Set Printing Coercions.
Check (U t).
    U (fun x : A \Rightarrow g 1 true (f 0 (t (h x))))
          : nat
Unset Printing Coercions.
```

Remark the changes in the result following the modification of the previous example.

```
Parameter U' : (C 0 \rightarrow B) \rightarrow nat. U' is declared
```

### Coercion to a type

An assumption x:A when A is not a type, is ill-typed. It is replaced by x:A' where A' is the result of the application to A of the coercion path between the class of A and Sortclass if it exists. This case occurs in the abstraction fun x:A => t, universal quantification forall x:A,B, global variables and parameters of (co-)inductive definitions and functions. In forall x:A,B, such a coercion path may also be applied to B if necessary.

```
Parameter Graph : Type.
    Graph is declared
Parameter Node : Graph -> Type.
    Node is declared
Coercion Node : Graph >-> Sortclass.
    Node is now a coercion
Parameter G : Graph.
    G is declared
Parameter Arrows : G -> G -> Type.
    Arrows is declared
Check Arrows.
    Arrows
        : G -> G -> Type
Parameter fg : G \rightarrow G.
    fg is declared
Check fg.
         : G -> G
Set Printing Coercions.
Check fg.
    fg
         : Node G -> Node G
```

Unset Printing Coercions.

### Coercion to a function

f a is ill-typed because f:A is not a function. The term f is replaced by the term obtained by applying to f the coercion path between A and Funclass if it exists.

```
Parameter bij : Set -> Set -> Set.
    bij is declared
Parameter ap : forall A B:Set, bij A B -> A -> B.
    ap is declared
Coercion ap : bij >-> Funclass.
   ap is now a coercion
Parameter b : bij nat nat.
   b is declared
Check (b 0).
   b 0
         : nat
Set Printing Coercions.
Check (b 0).
   ap nat nat b 0
         : nat
Unset Printing Coercions.
```

Let us see the resulting graph after all these examples.

```
Print Graph.
```

```
[bool_in_nat] : bool >-> nat
[f] : C >-> D
[f; g] : C >-> E
[g] : D >-> E
[IdD'D] : D' >-> D
[IdD'D; g] : D' >-> E
[h] : A >-> B
[Node] : Graph >-> Sortclass
[ap] : bij >-> Funclass
```

# 8.3 Canonical Structures

Authors Assia Mahboubi and Enrico Tassi

This chapter explains the basics of canonical structures and how they can be used to overload notations and build a hierarchy of algebraic structures. The examples are taken from [MT13]. We invite the interested reader to refer to this paper for all the details that are omitted here for brevity. The interested reader shall also find in [GZND11] a detailed description of another, complementary, use of canonical structures: advanced proof search. This latter papers also presents many techniques one can employ to tune the inference of canonical structures.

# 8.3.1 Notation overloading

We build an infix notation == for a comparison predicate. Such notation will be overloaded, and its meaning will depend on the types of the terms that are compared.

```
Module EQ.
    Interactive Module EQ started
Record class (T : Type) := Class \{ cmp : T \rightarrow T \rightarrow Prop \}.
    class is defined
    cmp is defined
Structure type := Pack { obj : Type; class_of : class obj }.
    type is defined
    obj is defined
    class_of is defined
Definition op (e : type) : obj e -> obj e -> Prop :=
    let 'Pack (Class the cmp) := e in the cmp.
    op is defined
Check op.
    op
         : forall e : type, obj e -> obj e -> Prop
Arguments op {e} x y : simpl never.
Arguments Class {T} cmp.
Module theory.
    Interactive Module theory started
Notation "x == y" := (op x y) (at level 70).
End theory.
    Module theory is defined
End EQ.
    Module EQ is defined
```

We use Coq modules as namespaces. This allows us to follow the same pattern and naming convention for the rest of the chapter. The base namespace contains the definitions of the algebraic structure. To keep the example small, the algebraic structure EQ.type we are defining is very simplistic, and characterizes terms on which a binary relation is defined, without requiring such relation to validate any property. The inner theory module contains the overloaded notation == and will eventually contain lemmas holding all the instances of the algebraic structure (in this case there are no lemmas).

Note that in practice the user may want to declare EQ.obj as a coercion, but we will not do that here.

The following line tests that, when we assume a type e that is in the EQ class, we can relate two of its objects with ==.

```
Import EQ.theory.
Check forall (e : EQ.type) (a b : EQ.obj e), a == b.
    forall (e : EQ.type) (a b : EQ.obj e), a == b
        : Prop

Still, no concrete type is in the EQ class.
Fail Check 3 == 3.
    The command has indeed failed with message:
```

```
The term "3" has type "nat" while it is expected to have type "EQ.obj ?e".
```

We amend that by equipping nat with a comparison relation.

```
Definition nat_eq (x y : nat) := Nat.compare x y = Eq.
    nat_eq is defined

Definition nat_EQcl : EQ.class nat := EQ.Class nat_eq.
    nat_EQcl is defined

Canonical Structure nat_EQty : EQ.type := EQ.Pack nat nat_EQcl.
    nat_EQty is defined

Check 3 == 3.
    3 == 3
        : Prop

Eval compute in 3 == 4.
    = Lt = Eq
        : Prop
```

This last test shows that Coq is now not only able to type check 3 == 3, but also that the infix relation was bound to the nat\_eq relation. This relation is selected whenever == is used on terms of type nat. This can be read in the line declaring the canonical structure nat\_EQty, where the first argument to Pack is the key and its second argument a group of canonical values associated to the key. In this case we associate to nat only one canonical value (since its class, nat\_EQcl has just one member). The use of the projection op requires its argument to be in the class EQ, and uses such a member (function) to actually compare its arguments.

Similarly, we could equip any other type with a comparison relation, and use the == notation on terms of this type.

#### **Derived Canonical Structures**

We know how to use == on base types, like nat, bool, Z. Here we show how to deal with type constructors, i.e. how to make the following example work:

```
Fail Check forall (e : EQ.type) (a b : EQ.obj e), (a, b) == (a, b).
The command has indeed failed with message:
In environment
e : EQ.type
a : EQ.obj e
b : EQ.obj e
The term "(a, b)" has type "(EQ.obj e * EQ.obj e)%type"
while it is expected to have type "EQ.obj ?e".
```

The error message is telling that Coq has no idea on how to compare pairs of objects. The following construction is telling Coq exactly how to do that.

```
Definition pair_eq (e1 e2 : EQ.type) (x y : EQ.obj e1 * EQ.obj e2) :=
  fst x == fst y /\ snd x == snd y.
    pair_eq is defined

Definition pair_EQcl e1 e2 := EQ.Class (pair_eq e1 e2).
    pair_EQcl is defined

(continues on next page)
```

```
Canonical Structure pair_EQty (e1 e2 : EQ.type) : EQ.type :=
    EQ.Pack (EQ.obj e1 * EQ.obj e2) (pair_EQcl e1 e2).
    pair_EQty is defined

Check forall (e : EQ.type) (a b : EQ.obj e), (a, b) == (a, b).
    forall (e : EQ.type) (a b : EQ.obj e), (a, b) == (a, b)
        : Prop

Check forall n m : nat, (3, 4) == (n, m).
    forall n m : nat, (3, 4) == (n, m)
        : Prop
```

Thanks to the pair\_EQty declaration, Coq is able to build a comparison relation for pairs whenever it is able to build a comparison relation for each component of the pair. The declaration associates to the key \* (the type constructor of pairs) the canonical comparison relation pair\_eq whenever the type constructor \* is applied to two types being themselves in the EQ class.

#### 8.3.2 Hierarchy of structures

To get to an interesting example we need another base class to be available. We choose the class of types that are equipped with an order relation, to which we associate the infix <= notation.

```
Module LE.
    Interactive Module LE started
Record class T := Class \{ cmp : T \rightarrow T \rightarrow Prop \}.
    class is defined
    cmp is defined
Structure type := Pack { obj : Type; class_of : class obj }.
    type is defined
    obj is defined
    class_of is defined
Definition op (e : type) : obj e -> obj e -> Prop :=
    let 'Pack _ (Class _ f) := e in f.
    op is defined
Arguments op \{\_\} x y : simpl never.
Arguments Class {T} cmp.
Module theory.
    Interactive Module theory started
Notation "x \le y" := (op x y) (at level 70).
    Module theory is defined
End LE.
    Module LE is defined
As before we register a canonical LE class for nat.
Import LE. theory.
Definition nat_le x y := Nat.compare x y <> Gt.
```

(continues on next page)

```
Definition nat_LEcl : LE.class nat := LE.Class nat_le.
    nat_LEcl is defined
Canonical Structure nat_LEty : LE.type := LE.Pack nat nat_LEcl.
    nat_LEty is defined
And we enable Coq to relate pair of terms with <=.
Definition pair_le e1 e2 (x y : LE.obj e1 * LE.obj e2) :=
   fst x \le fst y / snd x \le snd y.
    pair_le is defined
Definition pair_LEcl e1 e2 := LE.Class (pair_le e1 e2).
    pair LEcl is defined
Canonical Structure pair_LEty (e1 e2 : LE.type) : LE.type :=
   {\tt LE.Pack} \ ({\tt LE.obj\ e1}\ *\ {\tt LE.obj\ e2}) \ ({\tt pair\_LEcl\ e1}\ {\tt e2}) \,.
    pair_LEty is defined
Check (3,4,5) \le (3,4,5).
    (3, 4, 5) \leftarrow (3, 4, 5)
         : Prop
At the current stage we can use == and <= on concrete types, like tuples of natural numbers, but we can't
develop an algebraic theory over the types that are equipped with both relations.
Check 2 <= 3 /\ 2 == 2.
    2 <= 3 /\ 2 == 2
         : Prop
Fail Check forall (e : EQ.type) (x y : EQ.obj e), x \le y - y \le x - x = y.
    The command has indeed failed with message:
    In environment
    e : EQ.type
    x : EQ.obj e
    y : EQ.obj e
    The term "x" has type "EQ.obj e" while it is expected to have type
Fail Check forall (e : LE.type) (x y : LE.obj e), x \le y - y \le x - x = y.
    The command has indeed failed with message:
    In environment
    e : LE.type
    x : LE.obj e
    y : LE.obj e
    The term "x" has type "LE.obj e" while it is expected to have type
     "EQ.obj ?e".
We need to define a new class that inherits from both EQ and LE.
Module LEQ.
    Interactive Module LEQ started
Record mixin (e : EQ.type) (le : EQ.obj e -> EQ.obj e -> Prop) :=
    Mixin { compat : forall x y : EQ.obj e, le x y / le y x <-> x == y }.
                                                                                     (continues on next page)
```

nat\_le is defined

```
mixin is defined
    compat is defined
Record class T := Class {
                      EQ_class : EQ.class T;
                      LE_class : LE.class T;
                      extra : mixin (EQ.Pack T EQ_class) (LE.cmp T LE_class) }.
    class is defined
    EQ_class is defined
   LE_class is defined
    extra is defined
Structure type := _Pack { obj : Type; #[canonical(false)] class_of : class obj }.
   type is defined
    obj is defined
    class_of is defined
Arguments Mixin {e le} _.
Arguments Class \{T\} _ _ _.
```

The mixin component of the LEQ class contains all the extra content we are adding to EQ and LE. In particular it contains the requirement that the two relations we are combining are compatible.

The class\_of projection of the type structure is annotated as not canonical; it plays no role in the search for instances.

Unfortunately there is still an obstacle to developing the algebraic theory of this new class.

```
Module theory.
```

Interactive Module theory started

```
Fail Check forall (le : type) (n m : obj le), n <= m -> n <= m -> n == m.
   The command has indeed failed with message:
   In environment
   le : type
   n : obj le
   m : obj le
   The term "n" has type "obj le" while it is expected to have type "LE.obj ?e".
```

The problem is that the two classes LE and LEQ are not yet related by a subclass relation. In other words Coq does not see that an object of the LEQ class is also an object of the LE class.

The following two constructions tell Coq how to canonically build the LE.type and EQ.type structure given an LEQ.type structure on the same type.

```
Definition to_EQ (e : type) : EQ.type :=
   EQ.Pack (obj e) (EQ_class _ (class_of e)).
   to_EQ is defined

Canonical Structure to_EQ.
Definition to_LE (e : type) : LE.type :=
   LE.Pack (obj e) (LE_class _ (class_of e)).
   to_LE is defined

Canonical Structure to_LE.
```

We can now formulate out first theorem on the objects of the LEQ structure.

```
Lemma lele_eq (e : type) (x y : obj e) : x \le y \rightarrow y \le x \rightarrow x == y.
    1 subgoal
      e : type
      x, y : obj e
      _____
      x \ll y \gg y \ll x \gg x = y
now intros; apply (compat _ _ (extra _ (class_of e)) x y); split.
    No more subgoals.
Qed.
Arguments lele_eq {e} x y _ _.
End theory.
    Module theory is defined
End LEQ.
    Module LEQ is defined
Import LEQ.theory.
Check lele_eq.
    lele_eq
          : forall x y : LEQ.obj ?e, x <= y -> y <= x -> x == y
    where
    ?e : [ |- LEQ.type]
Of course one would like to apply results proved in the algebraic setting to any concrete instate of the
algebraic structure.
Example test_algebraic (n m : nat) : n \le m \rightarrow m \le n \rightarrow n == m.
    1 subgoal
      n, m : nat
      _____
      \mathtt{n} \ \mathrel{<=} \ \mathtt{m} \ \mathrel{->} \ \mathtt{m} \ \mathrel{<=} \ \mathtt{n} \ \mathrel{->} \ \mathtt{n} \ \mathrel{==} \ \mathtt{m}
Fail apply (lele_eq n m).
    The command has indeed failed with message:
    In environment
    n, m : nat
    The term "n" has type "nat" while it is expected to have type "LEQ.obj ?e".
n \ll m \gg m \ll n \gg n = m.
    1 subgoal
      11, 12 : LEQ.type
      n, m : LEQ.obj 11 * LEQ.obj 12
      _____
      \mathtt{n} \ \mathrel{<=} \ \mathtt{m} \ \mathrel{->} \ \mathtt{m} \ \mathrel{<=} \ \mathtt{n} \ \mathrel{->} \ \mathtt{n} \ \mathrel{==} \ \mathtt{m}
Fail apply (lele_eq n m).
    The command has indeed failed with message:
    In environment
    11, 12 : LEQ.type
    n, m : LEQ.obj 11 * LEQ.obj 12
                                                                                           (continues on next page)
```

```
The term "n" has type "(LEQ.obj l1 * LEQ.obj l2)%type" while it is expected to have type "LEQ.obj ?e".
```

Abort.

Again one has to tell Coq that the type nat is in the LEQ class, and how the type constructor \* interacts with the LEQ class. In the following proofs are omitted for brevity.

```
\label{lemma_nat_leq_compat} \mbox{Lemma nat_LEQ\_compat (n m : nat) : n <= m / \mbox{m} <= n <-> n == m.}
   1 subgoal
     n, m : nat
     _____
     n \ll m / m \ll n \ll n = m
Admitted.
   nat_LEQ_compat is declared
Definition nat_LEQmx := LEQ.Mixin nat_LEQ_compat.
   nat LEQmx is defined
n \ll m / m \ll n \ll n = m.
   1 subgoal
     11, 12 : LEQ.type
     n, m : LEQ.obj 11 * LEQ.obj 12
     _____
     n \ll m / m \ll n \ll n = m
Admitted.
   pair_LEQ_compat is declared
Definition pair_LEQmx 11 12 := LEQ.Mixin (pair_LEQ_compat 11 12).
   pair_LEQmx is defined
```

The following script registers an LEQ class for nat and for the type constructor \*. It also tests that they work as expected.

Unfortunately, these declarations are very verbose. In the following subsection we show how to make them more compact.

(continues on next page)

```
Example test_algebraic (n m : nat) : n \le m \rightarrow m \le n \rightarrow n == m.
    1 subgoal
      n, m : nat
      _____
      n \ll m \gg m \ll n \gg m = m
now apply (lele_eq n m).
    No more subgoals.
Qed.
Example test_algebraic2 (n m : nat * nat) : n \le m -> m \le n -> n == m.
    1 subgoal
      n, m : nat * nat
      _____
      \mathtt{n} <= \mathtt{m} -> \mathtt{m} <= \mathtt{n} -> \mathtt{n} == \mathtt{m}
now apply (lele_eq n m).
    No more subgoals.
Qed.
End Add_instance_attempt.
    Module Add_instance_attempt is defined
```

Note that no direct proof of  $n \le m > m \le n = m$  is provided by the user for n and m of type nat \* nat. What the user provides is a proof of this statement for n and m of type nat and a proof that the pair constructor preserves this property. The combination of these two facts is a simple form of proof search that Coq performs automatically while inferring canonical structures.

#### **Compact declaration of Canonical Structures**

We need some infrastructure for that.

```
Require Import Strings.String.
    [Loading ML file newring_plugin.cmxs ... done]
Module infrastructure.
    Interactive Module infrastructure started
Inductive phantom \{T : Type\} \{t : T\} : Type := Phantom.
    phantom is defined
    phantom_rect is defined
   phantom_ind is defined
    phantom_rec is defined
   phantom_sind is defined
Definition unify {T1 T2} (t1 : T1) (t2 : T2) (s : option string) :=
   phantom t1 -> phantom t2.
    unify is defined
Definition id \{T\} \{t : T\} (x : phantom t) := x.
   id is defined
Notation "[find v \mid t1 \sim t2] p" := (fun v (_ : unify t1 t2 None) => p)
```

(continues on next page)

```
(at level 50, v ident, only parsing).
Notation "[find v | t1 ~ t2 | s ] p" := (fun v (_ : unify t1 t2 (Some s)) => p)
    (at level 50, v ident, only parsing).
Notation "'Error : t : s" := (unify _ t (Some s))
    (at level 50, format "''Error' : t : s").
Open Scope string_scope.
End infrastructure.
    Module infrastructure is defined
```

To explain the notation [find  $v \mid t1 \sim t2$ ] let us pick one of its instances: [find  $e \mid EQ.obj e \sim T \mid$  "is not an EQ.type"]. It should be read as: "find a class e such that its objects have type T or fail with message "T is not an EQ.type".

The other utilities are used to ask Coq to solve a specific unification problem, that will in turn require the inference of some canonical structures. They are explained in more details in [MT13].

We now have all we need to create a compact "packager" to declare instances of the LEQ class.

#### Import infrastructure.

```
Definition packager T e0 le0 (m0 : LEQ.mixin e0 le0) :=
   [find e | EQ.obj e ~ T | "is not an EQ.type"]
   [find o | LE.obj o ~ T | "is not an LE.type"]
   [find ce | EQ.class_of e ~ ce ]
   [find co | LE.class_of o ~ co ]
   [find m | m ~ m0 | "is not the right mixin"]
   LEQ._Pack T (LEQ.Class ce co m).
    packager is defined
Notation Pack T m := (packager T _ m _ id _ id _ id _ id _ id).
```

The object Pack takes a type T (the key) and a mixin m. It infers all the other pieces of the class LEQ and declares them as canonical values associated to the T key. All in all, the only new piece of information we add in the LEQ class is the mixin, all the rest is already canonical for T and hence can be inferred by Coq.

Pack is a notation, hence it is not type checked at the time of its declaration. It will be type checked when it is used, an in that case T is going to be a concrete type. The odd arguments \_ and id we pass to the packager represent respectively the classes to be inferred (like e, o, etc) and a token (id) to force their inference. Again, for all the details the reader can refer to [MT13].

The declaration of canonical instances can now be way more compact:

```
Canonical Structure nat_LEQty := Eval hnf in Pack nat nat_LEQmx.
    nat_LEQty is defined

Canonical Structure pair_LEQty (11 12 : LEQ.type) :=
    Eval hnf in Pack (LEQ.obj 11 * LEQ.obj 12) (pair_LEQmx 11 12).
    pair_LEQty is defined

Error messages are also quite intelligible (if one skips to the end of the message).

Fail Canonical Structure err := Eval hnf in Pack bool nat_LEQmx.
    The command has indeed failed with message:
    The term "id" has type "phantom (EQ.obj ?e) -> phantom (EQ.obj ?e)"
```

while it is expected to have type "'Error:bool:"is not an EQ.type"".

### 8.4 Typeclasses

This chapter presents a quick reference of the commands related to type classes. For an actual introduction to type classes, there is a description of the system [SO08] and the literature on type classes in Haskell which also applies.

#### 8.4.1 Class and Instance declarations

The syntax for class and instance declarations is the same as the record syntax of Coq:

```
Class classname (p1 : t1) (pn : tn) [: sort] := { f1 : u1 ; ; fm : um }. Instance instancename q1 qm : classname p1 pn := { f1 := t1 ; ; fm := tm }.
```

The pi: ti variables are called the *parameters* of the class and the fi: ti are called the *methods*. Each class definition gives rise to a corresponding record declaration and each instance is a regular definition whose name is given by instancename and type is an instantiation of the record type.

We'll use the following example class in the rest of the chapter:

```
Class EqDec (A : Type) :=
    { eqb : A -> A -> bool ;
     eqb_leibniz : forall x y, eqb x y = true -> x = y }.
```

This class implements a boolean equality test which is compatible with Leibniz equality on some type. An example implementation is:

Using the attribute refine, if the term is not sufficient to finish the definition (e.g. due to a missing field or non-inferable hole) it must be finished in proof mode. If it is sufficient a trivial proof mode with no open goals is started.

```
#[refine] Instance unit_EqDec' : EqDec unit := { eqb x y := true }.
Proof.
intros [] [];reflexivity.
Defined.
```

Note that if you finish the proof with Qed the entire instance will be opaque, including the fields given in the initial term.

Alternatively, in *Program Mode* if one does not give all the members in the Instance declaration, Coq generates obligations for the remaining fields, e.g.:

```
Require Import Program.Tactics.
Program Instance eq_bool : EqDec bool :=
   { eqb x y := if x then y else negb y }.

Next Obligation.
   1 subgoal
```

(continues on next page)

8.4. Typeclasses 581

Defined.

One has to take care that the transparency of every field is determined by the transparency of the *Instance* proof. One can use alternatively the *Program Instance* variant which has richer facilities for dealing with obligations.

#### 8.4.2 Binding classes

Once a typeclass is declared, one can use it in class binders:

```
Definition neqb {A} {eqa : EqDec A} (x \ y : A) := negb (eqb \ x \ y). neqb is defined
```

When one calls a class method, a constraint is generated that is satisfied only in contexts where the appropriate instances can be found. In the example above, a constraint EqDec A is generated and satisfied by eqa: EqDec A. In case no satisfying constraint can be found, an error is raised:

```
Fail Definition neqb' (A : Type) (x y : A) := negb (eqb x y).
   The command has indeed failed with message:
   Unable to satisfy the following constraints:
   In environment:
   A : Type
   x, y : A

?EqDec : "EqDec A"
```

The algorithm used to solve constraints is a variant of the *eauto* tactic that does proof search with a set of lemmas (the instances). It will use local hypotheses as well as declared lemmas in the typeclass\_instances database. Hence the example can also be written:

```
Definition neqb' A (eqa : EqDec A) (x y : A) := negb (eqb x y). neqb' is defined
```

However, the generalizing binders should be used instead as they have particular support for typeclasses:

- They automatically set the maximally implicit status for typeclass arguments, making derived functions as easy to use as class methods. In the example above, A and eqa should be set maximally implicit.
- They support implicit quantification on partially applied type classes (*Implicit generalization*). Any argument not given as part of a typeclass binder will be automatically generalized.
- They also support implicit quantification on Superclasses.

Following the previous example, one can write:

```
Generalizable Variables A B C. Definition neqb_implicit `{eqa : EqDec A} (x y : A) := negb (eqb x y). neqb_implicit is defined
```

Here A is implicitly generalized, and the resulting function is equivalent to the one above.

#### 8.4.3 Parameterized Instances

One can declare parameterized instances as in Haskell simply by giving the constraints as a binding context before the instance, e.g.:

```
Program Instance prod_eqb `(EA : EqDec A, EB : EqDec B) : EqDec (A * B) := \{ \text{ eqb x y := match x, y with } | (la, ra), (lb, rb) => \text{ andb (eqb la lb) (eqb ra rb) }  end \}.
```

These instances are used just as well as lemmas in the instance hint database.

#### 8.4.4 Sections and contexts

To ease developments parameterized by many instances, one can use the *Context* command to introduce these parameters into section contexts, it works similarly to the command *Variable*, except it accepts any binding context as an argument, so variables can be implicit, and *Implicit generalization* can be used. For example:

```
Section EqDec_defs.
Context `{EA : EqDec A}.
    A is declared
   EA is declared
Global Program Instance option_eqb : EqDec (option A) :=
  \{ eqb x y := match x, y with \}
         | Some x, Some y => eqb x y
         | None, None => true
         | _, _ => false
         end }.
Admit Obligations.
End EqDec_defs.
About option_eqb.
    option_eqb : forall A : Type, EqDec A -> EqDec (option A)
    option_eqb is not universe polymorphic
    Arguments option_eqb {A}%type_scope {EA}
    option_eqb is transparent
    Expands to: Constant Top.option_eqb
```

Here the *Global* modifier redeclares the instance at the end of the section, once it has been generalized by the context variables it uses.

#### See also:

Section Section mechanism

#### 8.4.5 Building hierarchies

8.4. Typeclasses 583

#### **Superclasses**

One can also parameterize classes by other classes, generating a hierarchy of classes and superclasses. In the same way, we give the superclasses as a binding context:

```
Class Ord `(E : EqDec A) := { le : A -> A -> bool }.
   Ord is defined
   le is defined
```

Contrary to Haskell, we have no special syntax for superclasses, but this declaration is equivalent to:

This declaration means that any instance of the Ord class must have an instance of EqDec. The parameters of the subclass contain at least all the parameters of its superclasses in their order of appearance (here A is the only one). As we have seen, Ord is encoded as a record type with two parameters: a type A and an E of type EqDec A. However, one can still use it as if it had a single parameter inside generalizing binders: the generalization of superclasses will be done automatically.

```
Definition le_eqb `{Ord A} (x y : A) := andb (le x y) (le y x). le_eqb is defined
```

In some cases, to be able to specify sharing of structures, one may want to give explicitly the superclasses. It is possible to do it directly in regular binders, and using the ! modifier in class binders. For example:

```
Definition lt `{eqa : EqDec A, ! Ord eqa} (x \ y : A) := andb (le \ x \ y) (neqb \ x \ y). It is defined
```

The ! modifier switches the way a binder is parsed back to the regular interpretation of Coq. In particular, it uses the implicit arguments mechanism if available, as shown in the example.

#### **Substructures**

Substructures are components of a class which are instances of a class themselves. They often arise when using classes for logical properties, e.g.:

```
Class Reflexive (A : Type) (R : relation A) :=
  reflexivity : forall x, R x x.
Class Transitive (A : Type) (R : relation A) :=
  transitivity : forall x y z, R x y -> R y z -> R x z.
```

This declares singleton classes for reflexive and transitive relations, (see the *singleton class* variant for an explanation). These may be used as parts of other classes:

```
Class PreOrder (A : Type) (R : relation A) :=
  { PreOrder_Reflexive :> Reflexive A R ;
   PreOrder_Transitive :> Transitive A R }.
   PreOrder is defined
   PreOrder_Reflexive is defined
   PreOrder_Transitive is defined
```

The syntax :> indicates that each PreOrder can be seen as a Reflexive relation. So each time a reflexive relation is needed, a preorder can be used instead. This is very similar to the coercion mechanism of Structure declarations. The implementation simply declares each projection as an instance.

#### Warning: Ignored instance declaration for "ident": "term" is not a class

Using this :> syntax with a right-hand-side that is not itself a Class has no effect (apart from emitting this warning). In particular, is does not declare a coercion.

One can also declare existing objects or structure projections using the Existing Instance command to achieve the same effect.

#### 8.4.6 Summary of the commands

The *Class* command is used to declare a typeclass with parameters *binders* and fields the declared record fields.

This variant declares a *singleton* class with a single method. This singleton class is a so-called definitional class, represented simply as a definition ident binders := term and whose instances are themselves objects of this type. Definitional classes are not wrapped inside records, and the trivial projection of an instance of such a class is convertible to the instance itself. This can be useful to make instances of existing objects easily and to reduce proof size by not inserting useless projections. The class constant itself is declared rigid during resolution so that the class abstraction is maintained.

#### Variant: Existing Class ident

This variant declares a class a posteriori from a constant or inductive definition. No methods or instances are defined.

#### Warning: ident is already declared as a typeclass

This command has no effect when used on a typeclass.

This command is used to declare a typeclass instance named *ident* of the class *term*<sub>0</sub> with parameters *term* and fields defined by *field\_def*, where each field must be a declared field of the class.

An arbitrary context of *binders* can be put after the name of the instance and before the colon to declare a parameterized instance. An optional priority can be declared, 0 being the highest priority as for *auto* hints. If the priority *num* is not specified, it defaults to the number of non-dependent binders of the instance.

Variant: Instance ident binders?: forall binders, termo term ! num := term This syntax is used for declaration of singleton class instances or for directly giving an explicit term of type forall binders, termo term. One need not even mention the unique field name for singleton classes.

#### Variant: Global Instance

One can use the *Global* modifier on instances declared in a section so that their generalization is automatically redeclared after the section is closed.

#### Variant: Program Instance

Switches the type checking to Program (chapter *Program*) and uses the obligation mechanism to manage missing fields.

#### Variant: Declare Instance

In a Module Type, this command states that a corresponding concrete instance should exist in

8.4. Typeclasses 585

any implementation of this Module Type. This is similar to the distinction between Parameter vs. Definition, or between Declare Module and Module.

Besides the Class and Instance vernacular commands, there are a few other commands related to type-classes.

## Command: Existing Instance ident | num

This command adds an arbitrary list of constants whose type ends with an applied typeclass to the instance database with an optional priority *num*. It can be used for redeclaring instances at the end of sections, or declaring structure projections as instances. This is equivalent to Hint Resolve ident: typeclass\_instances, except it registers instances for *Print Instances*.

#### typeclasses eauto

This tactic uses a different resolution engine than *eauto* and *auto*. The main differences are the following:

- Contrary to *eauto* and *auto*, the resolution is done entirely in the new proof engine (as of Coq 8.6), meaning that backtracking is available among dependent subgoals, and shelving goals is supported. typeclasses eauto is a multi-goal tactic. It analyses the dependencies between subgoals to avoid backtracking on subgoals that are entirely independent.
- When called with no arguments, typeclasses eauto uses the typeclass\_instances database by default (instead of core). Dependent subgoals are automatically shelved, and shelved goals can remain after resolution ends (following the behavior of Coq 8.5).

Note: As of Coq 8.6, all:once (typeclasses eauto) faithfully mimics what happens during typeclass resolution when it is called during refinement/type inference, except that *only* declared class subgoals are considered at the start of resolution during type inference, while all can select non-class subgoals as well. It might move to all:typeclasses eauto in future versions when the refinement engine will be able to backtrack.

- When called with specific databases (e.g. with), typeclasses eauto allows shelved goals to remain at any point during search and treat typeclass goals like any other.
- The transparency information of databases is used consistently for all hints declared in them. It is always used when calling the unifier. When considering local hypotheses, we use the transparent state of the first hint database given. Using an empty database (created with *Create HintDb* for example) with unfoldable variables and constants as the first argument of typeclasses eauto hence makes resolution with the local hypotheses use full conversion during unification.
- When considering local hypotheses, we use the union of all the modes declared in the given databases.

Variant: typeclasses eauto num

Warning: The semantics for the limit num is different than for auto. By default, if no limit is given, the search is unbounded. Contrary to auto, introduction steps are counted, which might result in larger limits being necessary when searching with typeclasses eauto than with auto.

## Variant: typeclasses eauto with ident

This variant runs resolution with the given hint databases. It treats typeclass subgoals the same as other subgoals (no shelving of non-typeclass goals in particular).

#### autoapply term with ident

The tactic autoapply applies a term using the transparency information of the hint database ident, and does no typeclass resolution. This can be used in *Hint Extern*'s for typeclass instances (in the hint database typeclass\_instances) to allow backtracking on the typeclass subgoals created by the lemma application, rather than doing typeclass resolution locally at the hint application time.

#### Typeclasses Transparent, Typeclasses Opaque

## Command: Typeclasses Transparent ident

This command makes the identifiers transparent during typeclass resolution. Shortcut for Hint Transparent ident: typeclass\_instances.

## Command: Typeclasses Opaque ident +

Make the identifiers opaque for typeclass search. Shortcut for Hint Opaque ident : typeclass\_instances.

It is useful when some constants prevent some unifications and make resolution fail. It is also useful to declare constants which should never be unfolded during proof-search, like fixpoints or anything which does not look like an abbreviation. This can additionally speed up proof search as the typeclass map can be indexed by such rigid constants (see *The hints databases for auto and eauto*).

By default, all constants and local variables are considered transparent. One should take care not to make opaque any constant that is used to abbreviate a type, like:

Definition relation  $A := A \rightarrow A \rightarrow Prop$ .

#### **Settings**

#### Flag: Typeclasses Dependency Order

This flag (off by default) respects the dependency order between subgoals, meaning that subgoals on which other subgoals depend come first, while the non-dependent subgoals were put before the dependent ones previously (Coq 8.5 and below). This can result in quite different performance behaviors of proof search.

#### Flag: Typeclasses Filtered Unification

This flag, available since Coq 8.6 and off by default, switches the hint application procedure to a filter-then-unify strategy. To apply a hint, we first check that the goal matches syntactically the inferred or specified pattern of the hint, and only then try to unify the goal with the conclusion of the hint. This can drastically improve performance by calling unification less often, matching syntactic patterns being very quick. This also provides more control on the triggering of instances. For example, forcing a constant to explicitly appear in the pattern will make it never apply on a goal where there is a hole in that place.

#### Flag: Typeclasses Limit Intros

This flag (on by default) controls the ability to apply hints while avoiding (functional) eta-expansions in the generated proof term. It does so by allowing hints that conclude in a product to apply to a goal with a matching product directly, avoiding an introduction.

**Warning:** This can be expensive as it requires rebuilding hint clauses dynamically, and does not benefit from the invertibility status of the product introduction rule, resulting in potentially more expensive proof-search (i.e. more useless backtracking).

8.4. Typeclasses 587

#### Flag: Typeclass Resolution For Conversion

This flag (on by default) controls the use of typeclass resolution when a unification problem cannot be solved during elaboration/type inference. With this flag on, when a unification fails, typeclass resolution is tried before launching unification once again.

#### Flag: Typeclasses Strict Resolution

Typeclass declarations introduced when this flag is set have a stricter resolution behavior (the flag is off by default). When looking for unifications of a goal with an instance of this class, we "freeze" all the existentials appearing in the goals, meaning that they are considered rigid during unification and cannot be instantiated.

#### Flag: Typeclasses Unique Solutions

When a typeclass resolution is launched we ensure that it has a single solution or fail. This ensures that the resolution is canonical, but can make proof search much more expensive.

#### Flag: Typeclasses Unique Instances

Typeclass declarations introduced when this flag is set have a more efficient resolution behavior (the flag is off by default). When a solution to the typeclass goal of this class is found, we never backtrack on it, assuming that it is canonical.

#### Flag: Typeclasses Iterative Deepening

When this flag is set, the proof search strategy is breadth-first search. Otherwise, the search strategy is depth-first search. The default is off. *Typeclasses eauto* is another way to set this flag.

#### Option: Typeclasses Depth num

Sets the maximum proof search depth. The default is unbounded. *Typeclasses eauto* is another way to set this option.

#### Flag: Typeclasses Debug

Controls whether typeclass resolution steps are shown during search. Setting this flag also sets *Typeclasses Debug Verbosity* to 1. *Typeclasses eauto* is another way to set this flag.

#### Option: Typeclasses Debug Verbosity num

Determines how much information is shown for typeclass resolution steps during search. 1 is the default level. 2 shows additional information such as tried tactics and shelving of goals. Setting this option to 1 or 2 turns on the *Typeclasses Debug* flag; setting this option to 0 turns that flag off.

#### Flag: Typeclasses Axioms Are Instances

Deprecated since version 8.10.

This flag (off by default since 8.8) automatically declares axioms whose type is a typeclass at declaration time as instances of that class.

#### Typeclasses eauto :=

## Command: Typeclasses eauto := debug (dfs) (bfs) num

This command allows more global customization of the typeclass resolution tactic. The semantics of the options are:

- debug This sets the debug mode. In debug mode, the trace of successfully applied tactics is printed. The debug mode can also be set with *Typeclasses Debug*.
- (dfs), (bfs) This sets the search strategy to depth-first search (the default) or breadth-first search. The search strategy can also be set with Typeclasses Iterative Deepening.
- num This sets the depth limit of the search. The depth limit can also be set with Typeclasses Depth.

# 8.5 Omega: a solver for quantifier-free problems in Presburger Arithmetic

Author Pierre Crégut

Warning: The *omega* tactic is about to be deprecated in favor of the *lia* tactic. The goal is to consolidate the arithmetic solving capabilities of Coq into a single engine; moreover, *lia* is in general more powerful than *omega* (it is a complete Presburger arithmetic solver while *omega* was known to be incomplete).

Work is in progress to make sure that there are no regressions (including no performance regression) when switching from omega to lia in existing projects. However, we already recommend using lia in new or refactored proof scripts. We also ask that you report (in our bug tracker<sup>313</sup>) any issue you encounter, especially if the issue was not present in omega.

Note that replacing omega with lia can break non-robust proof scripts which rely on incompleteness bugs of omega (e.g. using the pattern; try omega).

#### 8.5.1 Description of omega

#### omega

omega is a tactic for solving goals in Presburger arithmetic, i.e. for proving formulas made of equations and inequalities over the type nat of natural numbers or the type Z of binary-encoded integers. Formulas on nat are automatically injected into Z. The procedure may use any hypothesis of the current proof session to solve the goal.

Multiplication is handled by <code>omega</code> but only goals where at least one of the two multiplicands of products is a constant are solvable. This is the restriction meant by "Presburger arithmetic".

If the tactic cannot solve the goal, it fails with an error message. In any case, the computation eventually stops.

#### 8.5.2 Arithmetical goals recognized by omega

omega applies only to quantifier-free formulas built from the connectives:

on atomic formulas. Atomic formulas are built from the predicates:

```
= < <= > >=
```

on nat or Z. In expressions of type nat, omega recognizes:

```
+ - * S O pred
```

and in expressions of type Z, omega recognizes numeral constants and:

```
+ - * Z.succ Z.pred
```

All expressions of type nat or Z not built on these operators are considered abstractly as if they were arbitrary variables of type nat or Z.

<sup>313</sup> https://github.com/coq/coq/issues

#### 8.5.3 Messages from omega

When omega does not solve the goal, one of the following errors is generated:

#### Error: omega can't solve this system.

This may happen if your goal is not quantifier-free (if it is universally quantified, try *intros* first; if it contains existentials quantifiers too, *omega* is not strong enough to solve your goal). This may happen also if your goal contains arithmetical operators not recognized by *omega*. Finally, your goal may be simply not true!

Error: omega: Not a quantifier-free goal.

If your goal is universally quantified, you should first apply intro as many times as needed.

```
Error: omega: Unrecognized predicate or connective: ident.
```

Error: omega: Unrecognized atomic proposition: ...

Error: omega: Can't solve a goal with proposition variables.

Error: omega: Unrecognized proposition.

Error: omega: Can't solve a goal with non-linear products.

Error: omega: Can't solve a goal with equality on type ...

#### 8.5.4 Using omega

The omega tactic does not belong to the core system. It should be loaded by

Require Import Omega.

#### Example

```
Require Import Omega.
Open Scope Z_scope.
Goal forall m n: Z, 1 + 2 * m \Leftrightarrow 2 * n.
   1 subgoal
     _____
     forall m n : Z, 1 + 2 * m \iff 2 * n
intros; omega.
   No more subgoals.
Abort.
Goal forall z:Z, z > 0 \rightarrow 2 * z + 1 > z.
   1 subgoal
     _____
     forall z : Z, z > 0 -> 2 * z + 1 > z
intro; omega.
   No more subgoals.
Abort.
```

#### 8.5.5 Options

#### Flag: Stable Omega

Deprecated since version 8.5.

This deprecated flag (on by default) is for compatibility with Coq pre 8.5. It resets internal name counters to make executions of *omega* independent.

#### Flag: Omega UseLocalDefs

This flag (on by default) allows omega to use the bodies of local variables.

#### Flag: Omega System

This flag (off by default) activate the printing of debug information

#### Flag: Omega Action

This flag (off by default) activate the printing of debug information

#### 8.5.6 Technical data

#### Overview of the tactic

- The goal is negated twice and the first negation is introduced as a hypothesis.
- Hypotheses are decomposed in simple equations or inequalities. Multiple goals may result from this phase.
- Equations and inequalities over nat are translated over Z, multiple goals may result from the translation
  of subtraction.
- Equations and inequalities are normalized.
- Goals are solved by the OMEGA decision procedure.
- The script of the solution is replayed.

#### Overview of the OMEGA decision procedure

The OMEGA decision procedure involved in the *omega* tactic uses a small subset of the decision procedure presented in [Pug92] Here is an overview, refer to the original paper for more information.

- Equations and inequalities are normalized by division by the GCD of their coefficients.
- Equations are eliminated, using the Banerjee test to get a coefficient equal to one.
- Note that each inequality cuts the Euclidean space in half.
- Inequalities are solved by projecting on the hyperspace defined by cancelling one of the variables. They are partitioned according to the sign of the coefficient of the eliminated variable. Pairs of inequalities from different classes define a new edge in the projection.
- Redundant inequalities are eliminated or merged in new equations that can be eliminated by the Banerjee test.
- The last two steps are iterated until a contradiction is reached (success) or there is no more variable to eliminate (failure).

It may happen that there is a real solution and no integer one. The last steps of the Omega procedure are not implemented, so the decision procedure is only partial.

#### 8.5.7 Bugs

- The simplification procedure is very dumb and this results in many redundant cases to explore.
- · Much too slow.
- Certainly other bugs! You can report them to https://coq.inria.fr/bugs/.

### 8.6 Micromega: tactics for solving arithmetic goals over ordered rings

Authors Frédéric Besson and Evgeny Makarov

#### 8.6.1 Short description of the tactics

The Psatz module (Require Import Psatz.) gives access to several tactics for solving arithmetic goals over  $\mathbb{Q}$ ,  $\mathbb{R}$ , and  $\mathbb{Z}$  but also nat and N. It also possible to get the tactics for integers by a Require Import Lia, rationals Require Import Lqa and reals Require Import Lra.

- lia is a decision procedure for linear integer arithmetic;
- nia is an incomplete proof procedure for integer non-linear arithmetic;
- *lra* is a decision procedure for linear (real or rational) arithmetic;
- nra is an incomplete proof procedure for non-linear (real or rational) arithmetic;
- psatz D n where D is Z or Q or R, and n is an optional integer limiting the proof search depth, is an incomplete proof procedure for non-linear arithmetic. It is based on John Harrison's HOL Light driver to the external prover csdp<sup>314</sup>. Note that the csdp driver is generating a proof cache which makes it possible to rerun scripts even without csdp.

#### Flag: Simplex

This flag (set by default) instructs the decision procedures to use the Simplex method for solving linear goals. If it is not set, the decision procedures are using Fourier elimination.

#### Flag: Lia Cache

This flag (set by default) instructs lia to cache its results in the file .lia.cache

#### Flag: Nia Cache

This flag (set by default) instructs nia to cache its results in the file .nia.cache

#### Flag: Nra Cache

This flag (set by default) instructs nra to cache its results in the file .nra.cache

The tactics solve propositional formulas parameterized by atomic arithmetic expressions interpreted over a domain  $D \in \{\mathbb{Z}, \mathbb{Q}, \mathbb{R}\}$ . The syntax of the formulas is the following:

where c is a numeric constant,  $x \in D$  is a numeric variable, the operators  $-, +, \times$  are respectively subtraction, addition, and product;  $p^n$  is exponentiation by a constant n, P is an arbitrary proposition. For  $\mathbb{Q}$ , equality is not Leibniz equality = but the equality of rationals ==.

<sup>314</sup> Sources and binaries can be found at https://projects.coin-or.org/Csdp

For  $\mathbb{Z}$  (resp.  $\mathbb{Q}$ ), c ranges over integer constants (resp. rational constants). For  $\mathbb{R}$ , the tactic recognizes as real constants the following expressions:

```
\texttt{c} ::= \texttt{RO} \ | \ \texttt{R1} \ | \ \texttt{Rmul(c,c)} \ | \ \texttt{Rplus(c,c)} \ | \ \texttt{Rminus(c,c)} \ | \ \texttt{IZR} \ \texttt{z} \ | \ \texttt{IQR} \ \texttt{q} \ | \ \texttt{Rdiv(c,c)} \ | \ \texttt{Rinv} \ \texttt{c}
```

where z is a constant in  $\mathbb{Z}$  and q is a constant in  $\mathbb{Q}$ . This includes integer constants written using the decimal notation, *i.e.*, c%R.

#### 8.6.2 Positivstellensatz refutations

The name psatz is an abbreviation for positivs tellens atz – literally "positivity theorem" – which generalizes Hilbert's null stellens atz. It relies on the notion of Cone. Given a (finite) set of polynomials S, Cone(S) is inductively defined as the smallest set of polynomials closed under the following rules:

$$\frac{p \in S}{p \in \mathit{Cone}(S)} \quad \frac{p_1 \in \mathit{Cone}(S) \quad p_2 \in \mathit{Cone}(S) \quad \in \{+, *\}}{p_1 \ p_2 \in \mathit{Cone}(S)}$$

The following theorem provides a proof principle for checking that a set of polynomial inequalities does not have solutions<sup>315</sup>.

**Theorem (Psatz)**. Let S be a set of polynomials. If -1 belongs to Cone(S), then the conjunction  $\bigwedge_{p \in S} p \geq 0$  is unsatisfiable. A proof based on this theorem is called a *positivstellensatz* refutation. The tactics work as follows. Formulas are normalized into conjunctive normal form  $\bigwedge_i C_i$  where  $C_i$  has the general form  $(\bigwedge_{j \in S_i} p_j \ 0) \to False$  and  $\in \{>, \geq, =\}$  for  $D \in \{\mathbb{Q}, \mathbb{R}\}$  and  $\in \{\geq, =\}$  for  $\mathbb{Z}$ .

For each conjunct  $C_i$ , the tactic calls an oracle which searches for -1 within the cone. Upon success, the oracle returns a cone expression that is normalized by the ring tactic (see The ring and field tactic families) and checked to be -1.

#### 8.6.3 1ra: a decision procedure for linear real and rational arithmetic

lra

This tactic is searching for *linear* refutations. As a result, this tactic explores a subset of the *Cone* defined as

$$\mathit{LinCone}(S) = \left\{ \left. \sum_{p \in S} \alpha_p \times p \; \right| \; \alpha_p \text{ are positive constants} \right\}$$

The deductive power of lra overlaps with the one of field tactic e.g., x = 10 \* x/10 is solved by lra.

#### 8.6.4 lia: a tactic for linear integer arithmetic

lia

This tactic solves linear goals over Z by searching for *linear* refutations and cutting planes. *lia* provides support for Z, nat, positive and N by pre-processing via the *zify* tactic.

#### High level view of lia

Over  $\mathbb{R}$ , positivstellensatz refutations are a complete proof principle<sup>316</sup>. However, this is not the case over  $\mathbb{Z}$ . Actually, positivstellensatz refutations are not even sufficient to decide linear integer arithmetic. The canonical example is  $2*x = 1 - > \mathtt{False}$  which is a theorem of  $\mathbb{Z}$  but not a theorem of  $\mathbb{R}$ . To remedy this weakness, the *lia* tactic is using recursively a combination of:

<sup>&</sup>lt;sup>315</sup> Variants deal with equalities and strict inequalities.

<sup>&</sup>lt;sup>316</sup> In practice, the oracle might fail to produce such a refutation.

- linear positivstellensatz refutations;
- cutting plane proofs;
- case split.

#### **Cutting plane proofs**

are a way to take into account the discreteness of  $\mathbb{Z}$  by rounding up (rational) constants up-to the closest integer.

#### Theorem: Bound on the ceiling function

Let p be an integer and c a rational constant. Then  $p \ge c \to p \ge \lceil c \rceil$ .

For instance, from 2 x = 1 we can deduce

- $x \ge 1/2$  whose cut plane is  $x \ge \lceil 1/2 \rceil = 1$ ;
- $x \le 1/2$  whose cut plane is  $x \le |1/2| = 0$ .

By combining these two facts (in normal form)  $x-1 \ge 0$  and  $-x \ge 0$ , we conclude by exhibiting a positivstellensatz refutation:  $-1 \equiv x-1+-x \in Cone(x-1,x)$ .

Cutting plane proofs and linear *positivstellensatz* refutations are a complete proof principle for integer linear arithmetic.

#### Case split

enumerates over the possible values of an expression.

**Theorem**. Let p be an integer and  $c_1$  and  $c_2$  integer constants. Then:

$$c_1 \leq p \leq c_2 \Rightarrow \bigvee\nolimits_{x \in [c_1,c_2]} p = x$$

Our current oracle tries to find an expression e with a small range  $[c_1, c_2]$ . We generate  $c_2 - c_1$  subgoals which contexts are enriched with an equation e = i for  $i \in [c_1, c_2]$  and recursively search for a proof.

#### 8.6.5 nra: a proof procedure for non-linear arithmetic

nra

This tactic is an *experimental* proof procedure for non-linear arithmetic. The tactic performs a limited amount of non-linear reasoning before running the linear prover of *lra*. This pre-processing does the following:

- If the context contains an arithmetic expression of the form  $e[x^2]$  where x is a monomial, the context is enriched with  $x^2 \ge 0$ ;
- For all pairs of hypotheses  $e_1 \geq 0$ ,  $e_2 \geq 0$ , the context is enriched with  $e_1 \times e_2 \geq 0$ .

After this pre-processing, the linear prover of lra searches for a proof by abstracting monomials by variables.

#### 8.6.6 nia: a proof procedure for non-linear integer arithmetic

nia

This tactic is a proof procedure for non-linear integer arithmetic. It performs a pre-processing similar to nra. The obtained goal is solved using the linear integer prover lia.

#### 8.6.7 psatz: a proof procedure for non-linear arithmetic

#### psatz

This tactic explores the Cone by increasing degrees – hence the depth parameter n. In theory, such a proof search is complete – if the goal is provable the search eventually stops. Unfortunately, the external oracle is using numeric (approximate) optimization techniques that might miss a refutation.

To illustrate the working of the tactic, consider we wish to prove the following Coq goal:

```
Require Import ZArith Psatz. 
 Open Scope Z_scope. 
 Goal forall x, -x^2 >= 0 \rightarrow x - 1 >= 0 \rightarrow False. intro x. 
psatz Z 2.
```

As shown, such a goal is solved by intro x. psatz Z 2.. The oracle returns the cone expression  $2 \times (x - 1) + (\mathbf{x} - \mathbf{1}) \times (\mathbf{x} - \mathbf{1}) + -x^2$  (polynomial hypotheses are printed in bold). By construction, this expression belongs to  $Cone(-x^2, x - 1)$ . Moreover, by running ring we obtain -1. By Theorem Psatz, the goal is valid.

#### 8.6.8 zify: pre-processing of arithmetic goals

#### zify

This tactic is internally called by *lia* to support additional types e.g., nat, positive and N. By requiring the module ZifyBool, the boolean type bool and some comparison operators are also supported. zify can also be extended by rebinding the tactic Zify.zify\_post\_hook that is run immediately after zify.

- To support Z.div and Z.modulo: Ltac Zify.zify\_post\_hook ::= Z.div\_mod\_to\_equations.
- To support Z.quot and Z.rem: Ltac Zify.zify\_post\_hook ::= Z.quot\_rem\_to\_equations.
- To support Z.div, Z.modulo, Z.quot, and Z.rem: Ltac Zify.zify\_post\_hook ::= Z. to\_euclidean\_division\_equations.

#### Command: Show Zify InjTyp

This command shows the list of types that can be injected into Z.

#### Command: Show Zify BinOp

This command shows the list of binary operators processed by zify.

#### Command: Show Zify BinRel

This command shows the list of binary relations processed by zify.

#### Command: Show Zify UnOp

This command shows the list of unary operators processed by zify.

#### Command: Show Zify CstOp

This command shows the list of constants processed by zify.

#### Command: Show Zify Spec

This command shows the list of operators over Z that are compiled using their specification e.g., Z.min.

### 8.7 Extraction of programs in OCaml and Haskell

Authors Jean-Christophe Filliâtre and Pierre Letouzey

We present here the Coq extraction commands, used to build certified and relatively efficient functional programs, extracting them from either Coq functions or Coq proofs of specifications. The functional languages available as output are currently OCaml, Haskell and Scheme. In the following, "ML" will be used (abusively) to refer to any of the three.

Before using any of the commands or options described in this chapter, the extraction framework should first be loaded explicitly via Require Extraction, or via the more robust From Coq Require Extraction. Note that in earlier versions of Coq, these commands and options were directly available without any preliminary Require.

Require Extraction.

#### 8.7.1 Generating ML Code

**Note:** In the following, a qualified identifier *qualid* can be used to refer to any kind of Coq global "object": constant, inductive type, inductive constructor or module name.

The next two commands are meant to be used for rapid preview of extraction. They both display extracted term(s) inside Coq.

#### Command: Extraction qualid

Extraction of the mentioned object in the Coq toplevel.

### Command: Recursive Extraction qualid

Recursive extraction of all the mentioned objects and all their dependencies in the Coq toplevel.

All the following commands produce real ML files. User can choose to produce one monolithic file or one file per Coq library.

## Command: Extraction string qualid +

Recursive extraction of all the mentioned objects and all their dependencies in one monolithic file string. Global and local identifiers are renamed according to the chosen ML language to fulfill its syntactic conventions, keeping original names as much as possible.

#### Command: Extraction Library ident

Extraction of the whole Coq library *ident*.v to an ML module *ident*.ml. In case of name clash, identifiers are here renamed using prefixes coq\_ or Coq\_ to ensure a session-independent renaming.

#### Command: Recursive Extraction Library ident

Extraction of the Coq library ident.v and all other modules ident.v depends on.

## Command: Separate Extraction qualid

Recursive extraction of all the mentioned objects and all their dependencies, just as Extraction string qualid, but instead of producing one monolithic file, this command splits the produced code in separate ML files, one per corresponding Coq.v file. This command is hence quite similar to Recursive Extraction Library, except that only the needed parts of Coq libraries are extracted instead of the whole. The naming convention in case of name clash is the same one as Extraction Library: identifiers are here renamed using prefixes coq\_ or Coq\_.

The following command is meant to help automatic testing of the extraction, see for instance the test-suite directory in the Coq sources.

### Command: Extraction TestCompile qualid

All the mentioned objects and all their dependencies are extracted to a temporary OCaml file, just as

in Extraction "file". Then this temporary file and its signature are compiled with the same OCaml compiler used to built Coq. This command succeeds only if the extraction and the OCaml compilation succeed. It fails if the current target language of the extraction is not OCaml.

#### 8.7.2 Extraction Options

#### Setting the target language

#### Command: Extraction Language OCaml Haskell Scheme

The ability to fix target language is the first and more important of the extraction options. Default is OCaml.

#### Inlining and optimizations

Since OCaml is a strict language, the extracted code has to be optimized in order to be efficient (for instance, when using induction principles we do not want to compute all the recursive calls but only the needed ones). So the extraction mechanism provides an automatic optimization routine that will be called each time the user wants to generate an OCaml program. The optimizations can be split in two groups: the type-preserving ones (essentially constant inlining and reductions) and the non type-preserving ones (some function abstractions of dummy types are removed when it is deemed safe in order to have more elegant types). Therefore some constants may not appear in the resulting monolithic OCaml program. In the case of modular extraction, even if some inlining is done, the inlined constants are nevertheless printed, to ensure session-independent programs.

Concerning Haskell, type-preserving optimizations are less useful because of laziness. We still make some optimizations, for example in order to produce more readable code.

The type-preserving optimizations are controlled by the following Coq flags and commands:

#### Flag: Extraction Optimize

Default is on. This controls all type-preserving optimizations made on the ML terms (mostly reduction of dummy beta/iota redexes, but also simplifications on Cases, etc). Turn this flag off if you want a ML term as close as possible to the Coq term.

#### Flag: Extraction Conservative Types

Default is off. This controls the non type-preserving optimizations made on ML terms (which try to avoid function abstraction of dummy types). Turn this flag on to make sure that e:t implies that e':t' where e' and t' are the extracted code of e and t respectively.

#### Flag: Extraction KeepSingleton

Default is off. Normally, when the extraction of an inductive type produces a singleton type (i.e. a type with only one constructor, and only one argument to this constructor), the inductive structure is removed and this type is seen as an alias to the inner type. The typical example is sig. This flag allows disabling this optimization when one wishes to preserve the inductive structure of types.

#### Flag: Extraction AutoInline

Default is on. The extraction mechanism inlines the bodies of some defined constants, according to some heuristics like size of bodies, uselessness of some arguments, etc. Those heuristics are not always perfect; if you want to disable this feature, turn this flag off.

### Command: Extraction Inline qualid +

In addition to the automatic inline feature, the constants mentioned by this command will always be inlined during extraction.

## Command: Extraction NoInline qualid

Conversely, the constants mentioned by this command will never be inlined during extraction.

#### Command: Print Extraction Inline

Prints the current state of the table recording the custom inlinings declared by the two previous commands.

#### Command: Reset Extraction Inline

Empties the table recording the custom inlinings (see the previous commands).

#### Inlining and printing of a constant declaration:

The user can explicitly ask for a constant to be extracted by two means:

- by mentioning it on the extraction command line
- by extracting the whole Coq module of this constant.

In both cases, the declaration of this constant will be present in the produced file. But this same constant may or may not be inlined in the following terms, depending on the automatic/custom inlining mechanism.

For the constants non-explicitly required but needed for dependency reasons, there are two cases:

- If an inlining decision is taken, whether automatically or not, all occurrences of this constant are replaced by its extracted body, and this constant is not declared in the generated file.
- If no inlining decision is taken, the constant is normally declared in the produced file.

#### Extra elimination of useless arguments

The following command provides some extra manual control on the code elimination performed during extraction, in a way which is independent but complementary to the main elimination principles of extraction (logical parts and types).

## Command: Extraction Implicit qualid [ ident ]

This experimental command allows declaring some arguments of *qualid* as implicit, i.e. useless in extracted code and hence to be removed by extraction. Here *qualid* can be any function or inductive constructor, and the given *ident* are the names of the concerned arguments. In fact, an argument can also be referred by a number indicating its position, starting from 1.

When an actual extraction takes place, an error is normally raised if the *Extraction Implicit* declarations cannot be honored, that is if any of the implicit arguments still occurs in the final code. This behavior can be relaxed via the following flag:

#### Flag: Extraction SafeImplicits

Default is on. When this flag is off, a warning is emitted instead of an error if some implicit arguments still occur in the final code of an extraction. This way, the extracted code may be obtained nonetheless and reviewed manually to locate the source of the issue (in the code, some comments mark the location of these remaining implicit arguments). Note that this extracted code might not compile or run properly, depending of the use of these remaining implicit arguments.

#### Realizing axioms

Extraction will fail if it encounters an informative axiom not realized. A warning will be issued if it encounters a logical axiom, to remind the user that inconsistent logical axioms may lead to incorrect or non-terminating extracted terms.

It is possible to assume some axioms while developing a proof. Since these axioms can be any kind of proposition or object or type, they may perfectly well have some computational content. But a program

must be a closed term, and of course the system cannot guess the program which realizes an axiom. Therefore, it is possible to tell the system what ML term corresponds to a given axiom.

#### Command: Extract Constant qualid => string

Give an ML extraction for the given constant. The string may be an identifier or a quoted string.

#### Command: Extract Inlined Constant qualid => string

Same as the previous one, except that the given ML terms will be inlined everywhere instead of being declared via a let.

Note: This command is sugar for an *Extract Constant* followed by a *Extraction Inline*. Hence a *Reset Extraction Inline* will have an effect on the realized and inlined axiom.

Caution: It is the responsibility of the user to ensure that the ML terms given to realize the axioms do have the expected types. In fact, the strings containing realizing code are just copied to the extracted files. The extraction recognizes whether the realized axiom should become a ML type constant or a ML object declaration. For example:

```
Axiom X:Set.
Axiom x:X.
Extract Constant X => "int".
Extract Constant x => "0".
```

Notice that in the case of type scheme axiom (i.e. whose type is an arity, that is a sequence of product finished by a sort), then some type variables have to be given (as quoted strings). The syntax is then:

```
Variant: Extract Constant qualid string ... string => string
```

The number of type variables is checked by the system. For example:

```
Axiom Y : Set \rightarrow Set .
Extract Constant Y "'a" "'b" \Rightarrow " 'a * 'b ".
```

Realizing an axiom via *Extract Constant* is only useful in the case of an informative axiom (of sort Type or Set). A logical axiom has no computational content and hence will not appear in extracted terms. But a warning is nonetheless issued if extraction encounters a logical axiom. This warning reminds user that inconsistent logical axioms may lead to incorrect or non-terminating extracted terms.

If an informative axiom has not been realized before an extraction, a warning is also issued and the definition of the axiom is filled with an exception labeled AXIOM TO BE REALIZED. The user must then search these exceptions inside the extracted file and replace them by real code.

#### Realizing inductive types

The system also provides a mechanism to specify ML terms for inductive types and constructors. For instance, the user may want to use the ML native boolean type instead of the Coq one. The syntax is the following:

```
Command: Extract Inductive qualid => string [ string ]
```

Give an ML extraction for the given inductive type. You must specify extractions for the type itself (first string) and all its constructors (all the string between square brackets). In this form, the ML extraction must be an ML inductive datatype, and the native pattern matching of the language will be used.

```
Variant: Extract Inductive qualid => string [ string ] string
```

Same as before, with a final extra string that indicates how to perform pattern matching over this inductive type. In this form, the ML extraction could be an arbitrary type. For an inductive type with k constructors, the function used to emulate the pattern matching should expect k+1 arguments, first the k branches in functional form, and then the inductive element to destruct. For instance, the match branch | S n => foo gives the functional form (fun n -> foo). Note that a constructor with no arguments is considered to have one unit argument, in order to block early evaluation of the branch: | 0 => bar leads to the functional form (fun () -> bar). For instance, when extracting nat into OCaml int, the code to be provided has type: (unit->'a)->(int->'a)->int->'a.

Caution: As for Extract Constant, this command should be used with care:

- The ML code provided by the user is currently **not** checked at all by extraction, even for syntax errors.
- Extracting an inductive type to a pre-existing ML inductive type is quite sound. But extracting to a general type (by providing an ad-hoc pattern matching) will often **not** be fully rigorously correct. For instance, when extracting **nat** to OCaml **int**, it is theoretically possible to build **nat** values that are larger than OCaml **max\_int**. It is the user's responsibility to be sure that no overflow or other bad events occur in practice.
- Translating an inductive type to an arbitrary ML type does **not** magically improve the asymptotic complexity of functions, even if the ML type is an efficient representation. For instance, when extracting **nat** to OCaml **int**, the function **Nat.mul** stays quadratic. It might be interesting to associate this translation with some specific *Extract Constant* when primitive counterparts exist.

Typical examples are the following:

```
Extract Inductive unit => "unit" [ "()" ].
Extract Inductive bool => "bool" [ "true" "false" ].
Extract Inductive sumbool => "bool" [ "true" "false" ].
```

**Note:** When extracting to OCaml, if an inductive constructor or type has arity 2 and the corresponding string is enclosed by parentheses, and the string meets OCaml's lexical criteria for an infix symbol, then the rest of the string is used as an infix constructor or type.

```
Extract Inductive list => "list" [ "[]" "(::)" ].
Extract Inductive prod => "(*)" [ "(,)" ].
```

As an example of translation to a non-inductive datatype, let's turn nat into OCaml int (see caveat above):

```
Extract Inductive nat \Rightarrow int [ "0" "succ" ] "(fun f0 fS n \Rightarrow if n=0 then f0 () else fS (n-1))".
```

#### Avoiding conflicts with existing filenames

When using Extraction Library, the names of the extracted files directly depend on the names of the Coq files. It may happen that these filenames are in conflict with already existing files, either in the standard library of the target language or in other code that is meant to be linked with the extracted code. For instance the module List exists both in Coq and in OCaml. It is possible to instruct the extraction not to use particular filenames.

Command: Extraction Blacklist ident

Instruct the extraction to avoid using these names as filenames for extracted code.

#### Command: Print Extraction Blacklist

Show the current list of filenames the extraction should avoid.

#### Command: Reset Extraction Blacklist

Allow the extraction to use any filename.

For OCaml, a typical use of these commands is Extraction Blacklist String List.

#### **Additional settings**

#### Option: Extraction File Comment string

Provides a comment that is included at the beginning of the output files.

#### Option: Extraction Flag num

Controls which optimizations are used during extraction, providing a finer-grained control than *Extraction Optimize*. The bits of *num* are used as a bit mask. Keeping an option off keeps the extracted ML more similar to the Coq term. Values are:

Bit	Value	Optimization (default is on unless noted otherwise)
0	1	Remove local dummy variables
1	2	Use special treatment for fixpoints
2	4	Simplify case with iota-redux
3	8	Factor case branches as functions
4	16	(not available, default false)
5	32	Simplify case as function of one argument
6	64	Simplify case by swapping case and lambda
7	128	Some case optimization
8	256	Push arguments inside a letin
9	512	Use linear let reduction (default false)
10	1024	Use linear beta reduction (default false)

#### Flag: Extraction TypeExpand

If set, fully expand Coq types in ML. See the Coq source code to learn more.

#### 8.7.3 Differences between Coq and ML type systems

Due to differences between Coq and ML type systems, some extracted programs are not directly typable in ML. We now solve this problem (at least in OCaml) by adding when needed some unsafe casting Obj.magic, which give a generic type 'a to any term.

First, if some part of the program is *very* polymorphic, there may be no ML type for it. In that case the extraction to ML works alright but the generated code may be refused by the ML type checker. A very well known example is the distr-pair function:

Definition dp  $\{A \ B: Type\}(x:A)(y:B)(f:forall \ C: Type, \ C->C) := (f \ A \ x, f \ B \ y).$ 

In OCaml, for instance, the direct extracted term would be:

let dp x y f = Pair((f () x),(f () y))

and would have type:

```
dp : 'a -> 'a -> (unit -> 'a -> 'b) -> ('b, 'b) prod
```

which is not its original type, but a restriction.

We now produce the following correct version:

```
let dp x y f = Pair ((Obj.magic f () x), (Obj.magic f () y))
```

Secondly, some Coq definitions may have no counterpart in ML. This happens when there is a quantification over types inside the type of a constructor; for example:

```
Inductive anything : Type := dummy : forall A:Set, A -> anything.
```

which corresponds to the definition of an ML dynamic type. In OCaml, we must cast any argument of the constructor dummy (no GADT are produced yet by the extraction).

Even with those unsafe castings, you should never get error like **segmentation fault**. In fact even if your program may seem ill-typed to the OCaml type checker, it can't go wrong: it comes from a Coq well-typed terms, so for example inductive types will always have the correct number of arguments, etc. Of course, when launching manually some extracted function, you should apply it to arguments of the right shape (from the Coq point-of-view).

More details about the correctness of the extracted programs can be found in [Let 02].

We have to say, though, that in most "realistic" programs, these problems do not occur. For example all the programs of Coq library are accepted by the OCaml type checker without any Obj.magic (see examples below).

#### 8.7.4 Some examples

We present here two examples of extraction, taken from the Coq Standard Library. We choose OCaml as the target language, but everything, with slight modifications, can also be done in the other languages supported by extraction. We then indicate where to find other examples and tests of extraction.

#### A detailed example: Euclidean division

The file Euclid contains the proof of Euclidean division. The natural numbers used here are unary, represented by the type nat, which is defined by two constructors O and S. This module contains a theorem eucl\_dev, whose type is:

```
forall b:nat, b > 0 -> forall a:nat, diveucl a b
```

where diveucl is a type for the pair of the quotient and the modulo, plus some logical assertions that disappear during extraction. We can now extract this program to OCaml:

(continues on next page)

```
| Right
(** val sub : nat -> nat -> nat **)
let rec sub n m =
  match n with
  | 0 -> n
  | S k -> (match m with
            | 0 -> n
            | S 1 -> sub k 1)
(** val le_lt_dec : nat -> nat -> sumbool **)
let rec le_lt_dec n m =
  match n with
  | 0 -> Left
  | S nO -> (match m with
             | 0 -> Right
             | S m0 -> le_lt_dec n0 m0)
(** val le_gt_dec : nat -> nat -> sumbool **)
let le_gt_dec =
  le_lt_dec
type diveucl =
| Divex of nat * nat
(** val eucl_dev : nat \rightarrow nat \rightarrow diveucl **)
let rec eucl_dev n m =
  let s = le_gt_dec n m in
  (match s with
   | Left ->
     let d = let y = sub m n in eucl_dev n y in
     let Divex (q, r) = d in Divex ((S q), r)
   | Right -> Divex (0, m))
```

The inlining of gt\_wf\_rec and others is not mandatory. It only enhances readability of extracted code. You can then copy-paste the output to a file euclid.ml or let Coq do it for you with the following command:

Extraction "euclid" eucl\_dev.

Let us play the resulting program (in an OCaml toplevel):

```
#use "euclid.ml";;
type nat = 0 | S of nat
type sumbool = Left | Right
val sub : nat -> nat -> nat = <fun>
val le_lt_dec : nat -> nat -> sumbool = <fun>
val le_gt_dec : nat -> nat -> sumbool = <fun>
type diveucl = Divex of nat * nat
val eucl_dev : nat -> nat -> diveucl = <fun>
# eucl_dev (S (S 0)) (S (S (S (S 0)))));;
- : diveucl = Divex (S (S 0), S 0)
```

It is easier to test on OCaml integers:
# let rec nat\_of\_int = function 0 -> 0 | n -> S (nat\_of\_int (n-1));;
val nat\_of\_int : int -> nat = <fun>
# let rec int\_of\_nat = function 0 -> 0 | S p -> 1+(int\_of\_nat p);;
val int\_of\_nat : nat -> int = <fun>
# let div a b =
 let Divex (q,r) = eucl\_dev (nat\_of\_int b) (nat\_of\_int a)
 in (int\_of\_nat q, int\_of\_nat r);;
val div : int -> int -> int \* int = <fun>
# div 173 15;;
- : int \* int = (11, 8)

Note that these nat\_of\_int and int\_of\_nat are now available via a mere Require Import ExtrOcamlIntConv and then adding these functions to the list of functions to extract. This file ExtrOcamlIntConv.v and some others in plugins/extraction/ are meant to help building concrete program via extraction.

#### Extraction's horror museum

Some pathological examples of extraction are grouped in the file test-suite/success/extraction.v of the sources of Coq.

#### **Users' Contributions**

Several of the Coq Users' Contributions use extraction to produce certified programs. In particular the following ones have an automatic extraction test:

- additions : https://github.com/coq-contribs/additions
- bdds: https://github.com/coq-contribs/bdds
- canon-bdds: https://github.com/coq-contribs/canon-bdds
- chinese: https://github.com/coq-contribs/chinese
- continuations : https://github.com/coq-contribs/continuations
- coq-in-coq : https://github.com/coq-contribs/coq-in-coq
- exceptions : https://github.com/coq-contribs/exceptions
- firing-squad : https://github.com/coq-contribs/firing-squad
- founify: https://github.com/coq-contribs/founify
- graphs : https://github.com/coq-contribs/graphs
- higman-cf: https://github.com/coq-contribs/higman-cf
- higman-nw: https://github.com/coq-contribs/higman-nw
- hardware : https://github.com/coq-contribs/hardware
- multiplier: https://github.com/coq-contribs/multiplier
- search-trees: https://github.com/coq-contribs/search-trees
- stalmarck: https://github.com/coq-contribs/stalmarck

Note that continuations and multiplier are a bit particular. They are examples of developments where Obj.magic is needed. This is probably due to a heavy use of impredicativity. After compilation, those two examples run nonetheless, thanks to the correction of the extraction [Let02].

### 8.8 Program

#### Author Matthieu Sozeau

We present here the **Program** tactic commands, used to build certified Coq programs, elaborating them from their algorithmic skeleton and a rich specification [Soz07]. It can be thought of as a dual of Extraction. The goal of **Program** is to program as in a regular functional programming language whilst using as rich a specification as desired and proving that the code meets the specification using the whole Coq proof apparatus. This is done using a technique originating from the "Predicate subtyping" mechanism of PVS [ROS98], which generates type checking conditions while typing a term constrained to a particular type. Here we insert existential variables in the term, which must be filled with proofs to get a complete Coq term. **Program** replaces the **Program** tactic by Catherine Parent [Par95] which had a similar goal but is no longer maintained.

The languages available as input are currently restricted to Coq's term language, but may be extended to OCaml, Haskell and others in the future. We use the same syntax as Coq and permit to use implicit arguments and the existing coercion mechanism. Input terms and types are typed in an extended system (Russell) and interpreted into Coq terms. The interpretation process may produce some proof obligations which need to be resolved to create the final term.

#### 8.8.1 Elaborating programs

The main difference from Coq is that an object in a type T: Set can be considered as an object of type  $\{x:T\mid P\}$  for any well-formed P: Prop. If we go from T to the subset of T verifying property P, we must prove that the object under consideration verifies it. Russell will generate an obligation for every such coercion. In the other direction, Russell will automatically insert a projection.

Another distinction is the treatment of pattern matching. Apart from the following differences, it is equivalent to the standard match operation (see *Extended pattern matching*).

• Generation of equalities. A match expression is always generalized by the corresponding equality. As an example, the expression:

This permits to get the proper equalities in the context of proof obligations inside clauses, without which reasoning is very limited.

• Generation of disequalities. If a pattern intersects with a previous one, a disequality is added in the context of the second branch. See for example the definition of div2 below, where the second branch is typed in a context where p, \_ <> S (S p).

8.8. Program 605

• Coercion. If the object being matched is coercible to an inductive type, the corresponding coercion will be automatically inserted. This also works with the previous mechanism.

There are flags to control the generation of equalities and coercions.

#### Flag: Program Cases

This controls the special treatment of pattern matching generating equalities and disequalities when using **Program** (it is on by default). All pattern-matches and let-patterns are handled using the standard algorithm of Coq (see *Extended pattern matching*) when this flag is deactivated.

#### Flag: Program Generalized Coercion

This controls the coercion of general inductive types when using **Program** (the flag is on by default). Coercion of subset types and pairs is still active in this case.

#### Flag: Program Mode

Enables the program mode, in which 1) typechecking allows subset coercions and 2) the elaboration of pattern matching of *Fixpoint* and *Definition* act respectively like *Program Fixpoint* and *Program Definition*, generating obligations if there are unresolved holes after typechecking.

#### Syntactic control over equalities

To give more control over the generation of equalities, the type checker will fall back directly to Coq's usual typing of dependent pattern matching if a return or in clause is specified. Likewise, the if construct is not treated specially by **Program** so boolean tests in the code are not automatically reflected in the obligations. One can use the dec combinator to get the correct hypotheses as in:

Require Import Program Arith.

```
Program Definition id (n : nat) : { x : nat | x = n } :=
  if dec (leb n 0) then 0
  else S (pred n).
   id has type-checked, generating 2 obligations
   Solving obligations automatically...
  2 obligations remaining
  Obligation 1 of id:
   (forall n : nat, (n <=? 0) = true -> (fun x : nat => x = n) 0).

Obligation 2 of id:
  (forall n : nat,
   (n <=? 0) = false -> (fun x : nat => x = n) (S (Init.Nat.pred n))).
```

The let tupling construct let (x1, ..., xn) := t in b does not produce an equality, contrary to the let pattern construct let (x1, ..., xn) := t in b. Also, term :> explicitly asks the system to coerce term to its support type. It can be useful in notations, for example:

```
Notation " x = y " := (@eq (x :>) (y :>)) (only parsing).
```

This notation denotes equality on subset types using equality on their support types, avoiding uses of proofirrelevance that would come up when reasoning with equality on the subset types themselves.

The next two commands are similar to their standard counterparts *Definition* and *Fixpoint* in that they define constants. However, they may require the user to prove some goals to construct the final definitions.

#### **Program Definition**

#### Command: Program Definition ident := term

This command types the value term in Russell and generates proof obligations. Once solved using the

commands shown below, it binds the final Coq term to the name ident in the environment.

Error: ident already exists.

```
Variant: Program Definition ident : type := term
```

It interprets the type type, potentially generating proof obligations to be resolved. Once done with them, we have a Coq type  $type_0$ . It then elaborates the preterm term into a Coq term  $term_0$ , checking that the type of  $term_0$  is coercible to  $type_0$ , and registers ident as being of type  $type_0$  once the set of obligations generated during the interpretation of  $term_0$  and the aforementioned coercion derivation are solved.

Error: In environment ... the term: term does not have type type. Actually, it has type ...

```
Variant: Program Definition ident binders : type := term
```

This is equivalent to:

```
Program Definition ident : forall binders, type := fun binders => term.
```

#### See also:

Sections Controlling the reduction strategies and the conversion algorithm, unfold

#### **Program Fixpoint**

```
Command: Program Fixpoint ident binders {order} : type := term

The optional order annotation follows the grammar:
```

```
order ::= measure term [ term ] | wf term ident
```

- measure f R where f is a value of type X computed on any subset of the arguments and the optional term R is a relation on X. X defaults to nat and R to lt.
- wf R x which is equivalent to measure x R.

The structural fixpoint operator behaves just like the one of Coq (see *Fixpoint*), except it may also generate obligations. It works with mutually recursive definitions too.

Require Import Program Arith.

```
Program Fixpoint div2 (n : nat) : { x : nat | n = 2 * x \/ n = 2 * x + 1 } := match n with 
 | S (S p) => S (div2 p) 
 | _ => 0 
 end. 
 Solving obligations automatically... 
 4 obligations remaining
```

Here we have one obligation for each branch (branches for 0 and (S 0) are automatically generated by the pattern matching compilation algorithm).

8.8. Program 607

```
S (S p) = S (x + S (x + 0)) \setminus S (S p) = S (x + S (x + 0) + 1)
```

One can use a well-founded order or a measure as termination orders using the syntax:

```
Program Fixpoint div2 (n : nat) {measure n} : { x : nat | n = 2 * x \ / n = 2 * x + 1 } := match n with 
 | S (S p) => S (div2 p) 
 | _ => 0 
 end.
```

Caution: When defining structurally recursive functions, the generated obligations should have the prototype of the currently defined functional in their context. In this case, the obligations should be transparent (e.g. defined using Defined) so that the guardedness condition on recursive calls can be checked by the kernel's type- checker. There is an optimization in the generation of obligations which gets rid of the hypothesis corresponding to the functional when it is not necessary, so that the obligation can be declared opaque (e.g. using Qed). However, as soon as it appears in the context, the proof of the obligation is required to be declared transparent.

No such problems arise when using measures or well-founded recursion.

#### **Program Lemma**

#### Command: Program Lemma ident : type

The Russell language can also be used to type statements of logical properties. It will generate obligations, try to solve them automatically and fail if some unsolved obligations remain. In this case, one can first define the lemma's statement using Program Definition and use it as the goal afterwards. Otherwise the proof will be started with the elaborated version as a goal. The Program prefix can similarly be used as a prefix for Variable, Hypothesis, Axiom etc.

#### 8.8.2 Solving obligations

The following commands are available to manipulate obligations. The optional identifier is used when multiple functions have unsolved obligations (e.g. when defining mutually recursive blocks). The optional tactic is replaced by the default one if not specified.

```
Command: Local Global Obligation Tactic := tactic
```

Sets the default obligation solving tactic applied to all obligations automatically, whether to solve them or when starting to prove one, e.g. using Next. Local makes the setting last only for the current module. Inside sections, local is the default.

#### Command: Show Obligation Tactic

Displays the current default tactic.

## Command: Obligations of ident

Displays all remaining obligations.

```
Command: Obligation num of ident ?
Start the proof of obligation num.
```

### Command: Next Obligation of ident?

Start the proof of the next unsolved obligation.

## Command: Solve Obligations of ident with tactic

Tries to solve each obligation of ident using the given tactic or the default one.

## Command: Solve All Obligations with tactic

Tries to solve each obligation of every program using the given tactic or the default one (useful for mutually recursive definitions).

## Command: Admit Obligations of ident?

Admits all obligations (of ident).

Note: Does not work with structurally recursive programs.

### Command: Preterm of ident

Shows the term that will be fed to the kernel once the obligations are solved. Useful for debugging.

#### Flag: Transparent Obligations

Controls whether all obligations should be declared as transparent (the default), or if the system should infer which obligations can be declared opaque.

#### Flag: Hide Obligations

Controls whether obligations appearing in the term should be hidden as implicit arguments of the special constantProgram. Tactics. obligation.

#### Flag: Shrink Obligations

Deprecated since version 8.7.

This flag (on by default) controls whether obligations should have their context minimized to the set of variables used in the proof of the obligation, to avoid unnecessary dependencies.

The module Coq.Program.Tactics defines the default tactic for solving obligations called program\_simpl. Importing Coq.Program.Program also adds some useful notations, as documented in the file itself.

#### 8.8.3 Frequently Asked Questions

#### Error: Ill-formed recursive definition.

This error can happen when one tries to define a function by structural recursion on a subset object, which means the Coq function looks like:

```
Program Fixpoint f(x : A \mid P) := match x with A b => f b end.
```

Supposing b:A, the argument at the recursive call to f is not a direct subterm of x as b is wrapped inside an exist constructor to build an object of type  $\{x:A\mid P\}$ . Hence the definition is rejected by the guardedness condition checker. However one can use wellfounded recursion on subset objects like this:

```
Program Fixpoint f (x : A | P) { measure (size x) } := match x with A b => f b end.
```

One will then just have to prove that the measure decreases at each recursive call. There are three drawbacks though:

1. A measure function has to be defined;

8.8. Program 609

- 2. The reduction is a little more involved, although it works well using lazy evaluation;
- 3. Mutual recursion on the underlying inductive type isn't possible anymore, but nested mutual recursion is always possible.

# 8.9 The ring and field tactic families

Author Bruno Barras, Benjamin Grégoire, Assia Mahboubi, Laurent Théry<sup>317</sup>

This chapter presents the tactics dedicated to dealing with ring and field equations.

#### 8.9.1 What does this tactic do?

ring does associative-commutative rewriting in ring and semiring structures. Assume you have two binary functions  $\oplus$  and  $\otimes$  that are associative and commutative, with  $\oplus$  distributive on  $\otimes$ , and two constants 0 and 1 that are unities for  $\oplus$  and  $\otimes$ . A polynomial is an expression built on variables  $V_0, V_1, \ldots$  and constants by application of  $\oplus$  and  $\otimes$ .

Let an ordered product be a product of variables  $V_{i_1} \otimes \cdots \otimes V_{i_n}$  verifying  $i_1 \leq i_2 \leq \cdots \leq i_n$ . Let a monomial be the product of a constant and an ordered product. We can order the monomials by the lexicographic order on products of variables. Let a canonical sum be an ordered sum of monomials that are all different, i.e. each monomial in the sum is strictly less than the following monomial according to the lexicographic order. It is an easy theorem to show that every polynomial is equivalent (modulo the ring properties) to exactly one canonical sum. This canonical sum is called the normal form of the polynomial. In fact, the actual representation shares monomials with same prefixes. So what does the ring tactic do? It normalizes polynomials over any ring or semiring structure. The basic use of ring is to simplify ring expressions, so that the user does not have to deal manually with the theorems of associativity and commutativity.

#### Example

In the ring of integers, the normal form of x(3+yx+25(1-z))+zx

is 
$$28x + (-24)xz + xxy$$
.

ring is also able to compute a normal form modulo monomial equalities. For example, under the hypothesis that  $2x^2 = yz + 1$ , the normal form of 2(x + 1)x - x - zy is x + 1.

### 8.9.2 The variables map

It is frequent to have an expression built with + and  $\times$ , but rarely on variables only. Let us associate a number to each subterm of a ring expression in the Gallina language. For example, consider this expression in the semiring nat:

```
(plus (mult (plus (f (5)) x) x)
(mult (if b then (4) else (f (3))) (2)))
```

As a ring expression, it has 3 subterms. Give each subterm a number in an arbitrary order:

0	$\mapsto$	if b then $(4)$ else $(f(3))$
1	$\mapsto$	(f(5))
2	$\mapsto$	X

 $<sup>^{317}</sup>$  based on previous work from Patrick Loiseleur and Samuel Boutin

Then normalize the "abstract" polynomial  $((V_1 \oplus V_2) \otimes V_2) \oplus (V_0 \otimes 2)$  In our example the normal form is:  $(2 \otimes V_0) \oplus (V_1 \otimes V_2) \oplus (V_2 \otimes V_2)$ . Then substitute the variables by their values in the variables map to get the concrete normal polynomial:

```
(plus (mult (2) (if b then (4) else (f (3))))
            (plus (mult (f (5)) x) (mult x x)))
```

#### 8.9.3 Is it automatic?

Yes, building the variables map and doing the substitution after normalizing is automatically done by the tactic. So you can just forget this paragraph and use the tactic according to your intuition.

# 8.9.4 Concrete usage in Coq

#### ring

This tactic solves equations upon polynomial expressions of a ring (or semiring) structure. It proceeds by normalizing both sides of the equation (w.r.t. associativity, commutativity and distributivity, constant propagation, rewriting of monomials) and comparing syntactically the results.

#### ring\_simplify

This tactic applies the normalization procedure described above to the given terms. The tactic then replaces all occurrences of the terms given in the conclusion of the goal by their normal forms. If no term is given, then the conclusion should be an equation and both sides are normalized. The tactic can also be applied in a hypothesis.

The tactic must be loaded by Require Import Ring. The ring structures must be declared with the Add Ring command (see below). The ring of booleans is predefined; if one wants to use the tactic on nat one must first require the module ArithRing exported by Arith); for Z, do Require Import ZArithRing or simply Require Import ZArith; for N, do Require Import NArithRing or Require Import NArith.

#### Example

```
Require Import ZArith.
    [Loading ML file newring_plugin.cmxs ... done]
    [Loading ML file zify_plugin.cmxs ... done]
    [Loading ML file omega_plugin.cmxs ... done]
Open Scope Z_scope.
Goal forall a b c:Z,
    (a + b + c) ^2 =
     a * a + b ^ 2 + c * c + 2 * a * b + 2 * a * c + 2 * b * c.
    1 subgoal
      _____
      forall a b c : Z,
      (a + b + c) \hat{2} = a * a + b \hat{2} + c * c + 2 * a * b + 2 * a * c + 2 * b * c
intros; ring.
    No more subgoals.
Abort.
Goal forall a b:Z,
     2 * a * b = 30 \rightarrow (a + b) ^ 2 = a ^ 2 + b ^ 2 + 30.
                                                                                  (continues on next page)
```

(continued from previous page)

```
1 subgoal
```

```
forall a b : Z, 2 * a * b = 30 -> (a + b) ^ 2 = a ^ 2 + b ^ 2 + 30

intros a b H; ring [H].

No more subgoals.
```

Abort.

Variant: ring [term \*]

This tactic decides the equality of two terms modulo ring operations and the equalities defined by the *terms*. Each *term* has to be a proof of some equality m = p, where m is a monomial (after "abstraction"), p a polynomial and p the corresponding equality of the ring structure.

Variant: ring\_simplify [ term \* ] term \* in ident

This tactic performs the simplification in the hypothesis named ident.

Note: ring\_simplify term; ring\_simplify term; is not equivalent to ring\_simplify term, term.

In the latter case the variables map is shared between the two terms, and common subterm t of  $term_1$  and  $term_2$  will have the same associated variable number. So the first alternative should be avoided for terms belonging to the same ring theory.

Error messages:

Error: Not a valid ring equation.

The conclusion of the goal is not provable in the corresponding ring theory.

Error: Arguments of ring\_simplify do not have all the same type.

ring\_simplify cannot simplify terms of several rings at the same time. Invoke the tactic once per ring structure.

Error: Cannot find a declared ring structure over term.

No ring has been declared for the type of the terms to be simplified. Use Add Ring first.

Error: Cannot find a declared ring structure for equality term.

Same as above in the case of the *ring* tactic.

# 8.9.5 Adding a ring structure

Declaring a new ring consists in proving that a ring signature (a carrier set, an equality, and ring operations: Ring\_theory.ring\_theory and Ring\_theory.semi\_ring\_theory) satisfies the ring axioms. Semi-rings (rings without + inverse) are also supported. The equality can be either Leibniz equality, or any relation declared as a setoid (see *Tactics enabled on user provided relations*). The definitions of ring and semiring (see module Ring theory) are:

(continues on next page)

(continued from previous page)

```
Rmul_assoc : forall x y z, x * (y * z) == (x * y) * z;
             : forall x y z, (x + y) * z == (x * z) + (y * z);
 Rdistr_l
             : forall x y, x - y == x + -y;
 Rsub_def
             : forall x, x + (-x) == 0
 Ropp_def
Record semi_ring_theory : Prop := mk_srt {
  SRadd_0_1 : forall n, 0 + n == n;
            : forall n m, n + m == m + n;
 SRadd_sym
 SRadd_assoc : forall n m p, n + (m + p) == (n + m) + p;
 SRmul_1l : forall n, 1*n == n;
 SRmul_0_1
            : forall n, 0*n == 0;
 SRmul_sym
            : forall n m, n*m == m*n;
 SRmul_assoc : forall n m p, n*(m*p) == (n*m)*p;
 SRdistr_1 : forall n m p, (n + m)*p == n*p + m*p
}.
```

This implementation of ring also features a notion of constant that can be parameterized. This can be used to improve the handling of closed expressions when operations are effective. It consists in introducing a type of *coefficients* and an implementation of the ring operations, and a morphism from the coefficient type to the ring carrier type. The morphism needs not be injective, nor surjective.

As an example, one can consider the real numbers. The set of coefficients could be the rational numbers, upon which the ring operations can be implemented. The fact that there exists a morphism is defined by the following properties:

```
Record ring_morph : Prop := mkmorph {
          : [c0] == 0;
 morph0
 morph1
            : [cI] == 1;
 morph_add : forall x y, [x +! y] == [x]+[y];
 morph\_sub : forall x y, [x -! y] == [x]-[y];
 morph_mul : forall x y, [x *! y] == [x]*[y];
 morph_opp : forall x, [-!x] == -[x];
 morph_eq : forall x y, x?=!y = true -> [x] == [y]
}.
Record semi_morph : Prop := mkRmorph {
  Smorph0 : [c0] == 0;
 Smorph1 : [cI] == 1;
 Smorph_add : forall x y, [x +! y] == [x]+[y];
 Smorph_mul : forall x y, [x *! y] == [x]*[y];
 Smorph_eq : forall x y, x?=!y = true \rightarrow [x] == [y]
}.
```

where c0 and cI denote the 0 and 1 of the coefficient set, +!, \*!, -! are the implementations of the ring operations, == is the equality of the coefficients, ?+! is an implementation of this equality, and [x] is a notation for the image of x by the ring morphism.

Since Z is an initial ring (and N is an initial semiring), it can always be considered as a set of coefficients. There are basically three kinds of (semi-)rings:

abstract rings to be used when operations are not effective. The set of coefficients is Z (or N for semirings).

**computational rings** to be used when operations are effective. The set of coefficients is the ring itself. The user only has to provide an implementation for the equality.

customized ring for other cases. The user has to provide the coefficient set and the morphism.

This implementation of ring can also recognize simple power expressions as ring expressions. A power function is specified by the following property:

```
Require Import Reals.
Section POWER.
Variable Cpow : Set.
Variable Cp_phi : N -> Cpow.
Variable rpow : R -> Cpow -> R.
Record power_theory : Prop := mkpow_th {
    rpow_pow_N : forall r n, rpow r (Cp_phi n) = pow_N 1%R Rmult r n
}.
End POWER.
```

The syntax for adding a new ring is

# Command: Add Ring ident: term (ring\_mod, ring\_mod)

The *ident* is not relevant. It is used just for error messages. The *term* is a proof that the ring signature satisfies the (semi-)ring axioms. The optional list of modifiers is used to tailor the behavior of the tactic. The following list describes their syntax and effects:

abstract declares the ring as abstract. This is the default.

decidable term declares the ring as computational. The expression term is the correctness proof of an equality test ?=! (which should be evaluable). Its type should be of the form forall x y, x ?=! y = true  $\rightarrow x$  == y.

morphism term declares the ring as a customized one. The expression term is a proof that there exists a morphism between a set of coefficient and the ring carrier (see Ring\_theory.ring\_morph and Ring\_theory.semi\_morph).

setoid term term forces the use of given setoid. The first term is a proof that the equality is indeed a setoid (see Setoid.Setoid\_Theory), and the second term a proof that the ring operations are morphisms (see Ring\_theory.ring\_eq\_ext and Ring\_theory.sring\_eq\_ext). This modifier needs not be used if the setoid and morphisms have been declared.

constants [ tactic ] specifies a tactic expression tactic that, given a term, returns either an object of the coefficient set that is mapped to the expression via the morphism, or returns InitialRing. NotConstant. The default behavior is to map only 0 and 1 to their counterpart in the coefficient set. This is generally not desirable for non trivial computational rings.

preprocess [ tactic ] specifies a tactic tactic that is applied as a preliminary step for ring and
ring\_simplify. It can be used to transform a goal so that it is better recognized. For instance,
S n can be changed to plus 1 n.

**postprocess** [ tactic ] specifies a tactic tactic that is applied as a final step for ring\_simplify. For instance, it can be used to undo modifications of the preprocessor.

power\_tac term [ tactic ] allows ring and  $ring\_simplify$  to recognize power expressions with a constant positive integer exponent (example:  $x^2$ ). The term term is a proof that a given power function satisfies the specification of a power function (term has to be a proof of Ring\_theory. power\_theory) and tactic specifies a tactic expression that, given a term, "abstracts" it into an object of type N whose interpretation via Cp\_phi (the evaluation function of power coefficient) is the original term, or returns InitialRing.NotConstant if not a constant coefficient (i.e.  $L_{tac}$  is the inverse function of Cp\_phi). See files plugins/setoid\_ring/ZArithRing.v and plugins/setoid\_ring/RealField.v for examples. By default the tactic does not recognize power expressions as ring expressions.

sign term allows ring\_simplify to use a minus operation when outputting its normal form, i.e writing
x - y instead of x + (- y). The term term is a proof that a given sign function indicates
expressions that are signed (term has to be a proof of Ring\_theory.get\_sign). See plugins/
setoid\_ring/InitialRing.v for examples of sign function.

div term allows ring and ring\_simplify to use monomials with coefficients other than 1 in the rewriting. The term term is a proof that a given division function satisfies the specification of an euclidean division function (term has to be a proof of Ring\_theory.div\_theory). For example, this function is called when trying to rewrite 7x by 2x = z to tell that  $7 = 3 \times 2 + 1$ . See plugins/setoid\_ring/InitialRing.v for examples of div function.

Error messages:

#### Error: Bad ring structure.

The proof of the ring structure provided is not of the expected type.

#### Error: Bad lemma for decidability of equality.

The equality function provided in the case of a computational ring has not the expected type.

#### Error: Ring operation should be declared as a morphism.

A setoid associated to the carrier of the ring structure has been found, but the ring operation should be declared as morphism. See *Tactics enabled on user provided relations*.

#### 8.9.6 How does it work?

The code of ring is a good example of a tactic written using reflection. What is reflection? Basically, using it means that a part of a tactic is written in Gallina, Coq's language of terms, rather than  $L_{tac}$  or OCaml. From the philosophical point of view, reflection is using the ability of the Calculus of Constructions to speak and reason about itself. For the ring tactic we used Coq as a programming language and also as a proof environment to build a tactic and to prove its correctness.

The interested reader is strongly advised to have a look at the file Ring\_polynom.v. Here a type for polynomials is defined:

```
Inductive PExpr : Type :=
    | PEc : C -> PExpr
    | PEX : positive -> PExpr
    | PEadd : PExpr -> PExpr -> PExpr
    | PEsub : PExpr -> PExpr -> PExpr
    | PEmul : PExpr -> PExpr -> PExpr
    | PEopp : PExpr -> PExpr
    | PEpow : PExpr -> N -> PExpr.
```

Polynomials in normal form are defined as:

```
Inductive Pol : Type :=
    | Pc : C -> Pol
    | Pinj : positive -> Pol -> Pol
    | PX : Pol -> positive -> Pol -> Pol.
```

where Pinj n P denotes P in which  $V_i$  is replaced by  $V_{i+n}$ , and PX P n Q denotes  $P \otimes V_1^n \oplus Q'$ , Q' being Q where  $V_i$  is replaced by  $V_{i+1}$ .

Variable maps are represented by lists of ring elements, and two interpretation functions, one that maps a variables map and a polynomial to an element of the concrete ring, and the second one that does the same for normal forms:

```
Definition PEeval : list R \rightarrow PExpr \rightarrow R := [...]. Definition Pphi_dev : list R \rightarrow Pol \rightarrow R := [...].
```

A function to normalize polynomials is defined, and the big theorem is its correctness w.r.t interpretation, that is:

```
Definition norm : PExpr -> Pol := [...].
Lemma Pphi_dev_ok :
   forall 1 pe npe, norm pe = npe -> PEeval 1 pe == Pphi_dev 1 npe.
```

So now, what is the scheme for a normalization proof? Let p be the polynomial expression that the user wants to normalize. First a little piece of ML code guesses the type of p, the ring theory T to use, an abstract polynomial ap and a variables map v such that p is  $\beta\delta\iota$ - equivalent to (PEeval v ap). Then we replace it by (Pphi\_dev v (norm ap)), using the main correctness theorem and we reduce it to a concrete expression p', which is the concrete normal form of p. This is summarized in this diagram:

р	$\rightarrow_{\beta\delta\iota}$	(PEeval v ap)
	=(by the main correctness theorem)	
p'	$\leftarrow_{\beta\delta\iota}$	(Pphi_dev v (norm ap))

The user does not see the right part of the diagram. From outside, the tactic behaves like a  $\beta\delta\iota$  simplification extended with rewriting rules for associativity and commutativity. Basically, the proof is only the application of the main correctness theorem to well-chosen arguments.

# 8.9.7 Dealing with fields

#### field

This tactic is an extension of the ring tactic that deals with rational expressions. Given a rational expression F=0. It first reduces the expression F to a common denominator N/D=0 where N and D are two ring expressions. For example, if we take F=(1-1/x)x-x+1, this gives  $N=(x-1)x-x^2+x$  and D=x. It then calls ring to solve N=0.

Note that field also generates nonzero conditions for all the denominators it encounters in the reduction. In our example, it generates the condition  $x \neq 0$ . These conditions appear as one subgoal which is a conjunction if there are several denominators. Nonzero conditions are always polynomial expressions. For example when reducing the expression 1/(1+1/x), two side conditions are generated:  $x \neq 0$  and  $x + 1 \neq 0$ . Factorized expressions are broken since a field is an integral domain, and when the equality test on coefficients is complete w.r.t. the equality of the target field, constants can be proven different from zero automatically.

The tactic must be loaded by Require Import Field. New field structures can be declared to the system with the Add Field command (see below). The field of real numbers is defined in module RealField (in plugins/setoid\_ring). It is exported by module Rbase, so that requiring Rbase or

Reals is enough to use the field tactics on real numbers. Rational numbers in canonical form are also declared as a field in the module Qcanon.

### Example

```
Require Import Reals.
Open Scope R_scope.
Goal forall x,
      x <> 0 -> (1 - 1 / x) * x - x + 1 = 0.
   1 subgoal
     forall x : R, x <> 0 -> (1 - 1 / x) * x - x + 1 = 0
intros; field; auto.
   No more subgoals.
Abort.
Goal forall x y,
      y <> 0 -> y = x -> x / y = 1.
   1 subgoal
     _____
     forall x y : R, y <> 0 -> y = x -> x / y = 1
intros x y H H1; field [H1]; auto.
   No more subgoals.
Abort.
```

# Variant: field [term \*]

This tactic decides the equality of two terms modulo field operations and the equalities defined by the terms. Each term has to be a proof of some equality m = p, where m is a monomial (after "abstraction"), p a polynomial and = the corresponding equality of the field structure.

**Note:** Rewriting works with the equality m = p only if p is a polynomial since rewriting is handled by the underlying ring tactic.

# Variant: field\_simplify

performs the simplification in the conclusion of the goal,  $F_1 = F_2$  becomes  $N_1/D_1 = N_2/D_2$ . A normalization step (the same as the one for rings) is then applied to  $N_1$ ,  $D_1$ ,  $N_2$  and  $D_2$ . This way, polynomials remain in factorized form during fraction simplification. This yields smaller expressions when reducing to the same denominator since common factors can be canceled.

# Variant: field\_simplify [ \* | \* |

This variant performs the simplification in the conclusion of the goal using the equalities defined by the terms.

# Variant: field\_simplify [term \*] term \*

This variant performs the simplification in the terms *terms* of the conclusion of the goal using the equalities defined by *terms* inside the brackets.

#### Variant: field\_simplify in ident

This variant performs the simplification in the assumption *ident*.

Variant: field\_simplify [term \*] in ident

This variant performs the simplification in the assumption ident using the equalities defined by the terms.

Variant: field\_simplify [term \*] term \* in ident

This variant performs the simplification in the *terms* of the assumption *ident* using the equalities defined by the *terms* inside the brackets.

Variant: field simplify eq

performs the simplification in the conclusion of the goal removing the denominator.  $F_1 = F_2$  becomes  $N_1D_2 = N_2D_1$ .

Variant: field\_simplify\_eq [ term ]

This variant performs the simplification in the conclusion of the goal using the equalities defined by terms.

Variant: field\_simplify\_eq in ident

This variant performs the simplification in the assumption *ident*.

Variant: field\_simplify\_eq [ term \* ] in ident

This variant performs the simplification in the assumption ident using the equalities defined by terms and removing the denominator.

# 8.9.8 Adding a new field structure

Declaring a new field consists in proving that a field signature (a carrier set, an equality, and field operations: Field\_theory.field\_theory and Field\_theory.semi\_field\_theory) satisfies the field axioms. Semi-fields (fields without + inverse) are also supported. The equality can be either Leibniz equality, or any relation declared as a setoid (see *Tactics enabled on user provided relations*). The definition of fields and semifields is:

```
Record field_theory : Prop := mk_field {
   F_R : ring_theory r0 rI radd rmul rsub ropp req;
   F_1_neq_0 : ~ 1 == 0;
   Fdiv_def : forall p q, p / q == p * / q;
   Finv_l : forall p, ~ p == 0 -> / p * p == 1
}.

Record semi_field_theory : Prop := mk_sfield {
   SF_SR : semi_ring_theory r0 rI radd rmul req;
   SF_1_neq_0 : ~ 1 == 0;
   SFdiv_def : forall p q, p / q == p * / q;
   SFinv_l : forall p, ~ p == 0 -> / p * p == 1
}.
```

The result of the normalization process is a fraction represented by the following type:

```
Record linear : Type := mk_linear {
  num : PExpr C;
  denum : PExpr C;
  condition : list (PExpr C)
}.
```

where num and denum are the numerator and denominator; condition is a list of expressions that have appeared as a denominator during the normalization process. These expressions must be proven different from zero for the correctness of the algorithm.

The syntax for adding a new field is

```
Command: Add Field ident: term (field_mod, field_mod))
```

The *ident* is not relevant. It is used just for error messages. *term* is a proof that the field signature satisfies the (semi-)field axioms. The optional list of modifiers is used to tailor the behavior of the tactic.

```
field_mod ::= ring_mod \mid completeness term
```

Since field tactics are built upon ring tactics, all modifiers of the Add Ring apply. There is only one specific modifier:

completeness term allows the field tactic to prove automatically that the image of nonzero coefficients are mapped to nonzero elements of the field. term is a proof of forall x y, [x] == [y] -> x ?=! y = true, which is the completeness of equality on coefficients w.r.t. the field equality.

# 8.9.9 History of ring

First Samuel Boutin designed the tactic ACDSimpl. This tactic did lot of rewriting. But the proofs terms generated by rewriting were too big for Coq's type checker. Let us see why:

```
Require Import ZArith.
Open Scope Z_scope.
Goal forall x y z : Z,
      x + 3 + y + y * z = x + 3 + y + z * y.
   1 subgoal
      _____
     forall x y z : Z, x + 3 + y + y * z = x + 3 + y + z * y
intros; rewrite (Zmult_comm y z); reflexivity.
   No more subgoals.
Save foo.
Print foo.
   foo =
   fun x y z : Z =>
   eq_ind_r (fun z0 : Z \Rightarrow x + 3 + y + z0 = x + 3 + y + z * y) eq_refl
      (Z.mul_comm y z)
         : forall x y z : Z, x + 3 + y + y * z = x + 3 + y + z * y
   Arguments foo (_ _ _)%Z_scope
```

At each step of rewriting, the whole context is duplicated in the proof term. Then, a tactic that does hundreds of rewriting generates huge proof terms. Since ACDSimpl was too slow, Samuel Boutin rewrote it using reflection (see [Bou97]). Later, it was rewritten by Patrick Loiseleur: the new tactic does not any more require ACDSimpl to compile and it makes use of  $\beta\delta\iota$ -reduction not only to replace the rewriting steps, but also to achieve the interleaving of computation and reasoning (see Discussion). He also wrote some ML code for the Add Ring command that allows registering new rings dynamically.

Proofs terms generated by ring are quite small, they are linear in the number of  $\oplus$  and  $\otimes$  operations in the normalized terms. Type checking those terms requires some time because it makes a large use of the conversion rule, but memory requirements are much smaller.

### 8.9.10 Discussion

Efficiency is not the only motivation to use reflection here. ring also deals with constants, it rewrites for example the expression 34 + 2 \* x - x + 12 to the expected result x + 46. For the tactic ACDSimpl, the only constants were 0 and 1. So the expression 34 + 2 \* (x - 1) + 12 is interpreted as  $V_0 \oplus V_1 \otimes (V_2 \oplus 1) \oplus V_3$ , with the variables mapping  $\{V_0 \mapsto 34; V_1 \mapsto 2; V_2 \mapsto x; V_3 \mapsto 12\}$ . Then it is rewritten to 34 - x + 2 \* x + 12, very far from the expected result. Here rewriting is not sufficient: you have to do some kind of reduction (some kind of computation) to achieve the normalization.

The tactic **ring** is not only faster than the old one: by using reflection, we get for free the integration of computation and reasoning that would be very difficult to implement without it.

Is it the ultimate way to write tactics? The answer is: yes and no. The ring tactic intensively uses the conversion rules of the Calculus of Inductive Constructions, i.e. it replaces proofs by computations as much as possible. It can be useful in all situations where a classical tactic generates huge proof terms, like symbolic processing and tautologies. But there are also tactics like auto or linear that do many complex computations, using side-effects and backtracking, and generate a small proof term. Clearly, it would be significantly less efficient to replace them by tactics using reflection.

Another idea suggested by Benjamin Werner: reflection could be used to couple an external tool (a rewriting program or a model checker) with Coq. We define (in Coq) a type of terms, a type of traces, and prove a correctness theorem that states that replaying traces is safe with respect to some interpretation. Then we let the external tool do every computation (using side-effects, backtracking, exception, or others features that are not available in pure lambda calculus) to produce the trace. Now we can check in Coq that the trace has the expected semantics by applying the correctness theorem.

# 8.10 Nsatz: tactics for proving equalities in integral domains

Author Loïc Pottier

nsatz

This tactic is for solving goals of the form

$$\begin{array}{l} \forall X_1,\ldots,X_n\in A,\\ P_1(X_1,\ldots,X_n)=Q_1(X_1,\ldots,X_n),\ldots,P_s(X_1,\ldots,X_n)=Q_s(X_1,\ldots,X_n)\\ \vdash P(X_1,\ldots,X_n)=Q(X_1,\ldots,X_n) \end{array}$$

where  $P, Q, P_1, Q_1, \dots, P_s, Q_s$  are polynomials and A is an integral domain, i.e. a commutative ring with no zero divisors. For example, A can be  $\mathbb{R}$ ,  $\mathbb{Z}$ , or  $\mathbb{Q}$ . Note that the equality = used in these goals can be any setoid equality (see *Tactics enabled on user provided relations*), not only Leibniz equality.

It also proves formulas

$$\begin{array}{l} \forall X_1,\ldots,X_n \in A, \\ P_1(X_1,\ldots,X_n) = Q_1(X_1,\ldots,X_n) \wedge \ldots \wedge P_s(X_1,\ldots,X_n) = Q_s(X_1,\ldots,X_n) \\ \rightarrow P(X_1,\ldots,X_n) = Q(X_1,\ldots,X_n) \end{array}$$

doing automatic introductions.

You can load the Nsatz module with the command Require Import Nsatz.

#### 8.10.1 More about nsatz

Hilbert's Nullstellensatz theorem shows how to reduce proofs of equalities on polynomials on a commutative ring A with no zero divisors to algebraic computations: it is easy to see that if a polynomial P in  $A[X_1, \ldots, X_n]$  verifies  $cP^r = \sum_{i=1}^s S_i P_i$ , with  $c \in A$ ,  $c \neq 0$ , r a positive integer, and the  $S_i$  s in  $A[X_1, \ldots, X_n]$ , then P is

zero whenever polynomials  $P_1, \dots, P_s$  are zero (the converse is also true when A is an algebraically closed field: the method is complete).

So, solving our initial problem reduces to finding  $S_1, \dots, S_s$ , c and r such that  $c(P-Q)^r = \sum_i S_i(P_i-Q_i)$ , which will be proved by the tactic ring.

This is achieved by the computation of a Gröbner basis of the ideal generated by  $P_1 - Q_1, ..., P_s - Q_s$ , with an adapted version of the Buchberger algorithm.

This computation is done after a step of reification, which is performed using Typeclasses.

Variant: nsatz with radicalmax:=num%N strategy:=num%Z parameters:=[ident\*,] variables:=[ident\*,]

Most complete syntax for nsatz.

- radical max is a bound when searching for r such that  $c(P-Q)r = \sum_{i=1..s} S_i(Pi-Qi)$
- strategy gives the order on variables  $X_1, \dots, X_n$  and the strategy used in Buchberger algorithm (see  $\lceil GMN + 91 \rceil$  for details):
  - strategy = 0: reverse lexicographic order and newest s-polynomial.
  - strategy = 1: reverse lexicographic order and sugar strategy.
  - strategy = 2: pure lexicographic order and newest s-polynomial.
  - strategy = 3: pure lexicographic order and sugar strategy.
- parameters is the list of variables  $X_{i_1},\dots,X_{i_k}$  among  $X_1,\dots,X_n$  which are considered as parameters: computation will be performed with rational fractions in these variables, i.e. polynomials are considered with coefficients in  $R(X_{i_1},\dots,X_{i_k})$ . In this case, the coefficient c can be a non constant polynomial in  $X_{i_1},\dots,X_{i_k}$ , and the tactic produces a goal which states that c is not zero.
- variables is the list of the variables in the decreasing order in which they will be used in the Buchberger algorithm. If variables = (@nil R), then lvar is replaced by all the variables which are not in parameters.

See the file Nsatz.v for many examples, especially in geometry.

# 8.11 Generalized rewriting

#### Author Matthieu Sozeau

This chapter presents the extension of several equality related tactics to work over user-defined structures (called setoids) that are equipped with ad-hoc equivalence relations meant to behave as equalities. Actually, the tactics have also been generalized to relations weaker than equivalences (e.g. rewriting systems). The toolbox also extends the automatic rewriting capabilities of the system, allowing the specification of custom strategies for rewriting.

This documentation is adapted from the previous setoid documentation by Claudio Sacerdoti Coen (based on previous work by Clément Renard). The new implementation is a drop-in replacement for the old one<sup>318</sup>, hence most of the documentation still applies.

The work is a complete rewrite of the previous implementation, based on the typeclass infrastructure. It also improves on and generalizes the previous implementation in several ways:

• User-extensible algorithm. The algorithm is separated into two parts: generation of the rewriting constraints (written in ML) and solving these constraints using typeclass resolution. As typeclass resolution is extensible using tactics, this allows users to define general ways to solve morphism constraints.

<sup>&</sup>lt;sup>318</sup> Nicolas Tabareau helped with the gluing.

- Subrelations. An example extension to the base algorithm is the ability to define one relation as a subrelation of another so that morphism declarations on one relation can be used automatically for the other. This is done purely using tactics and typeclass search.
- Rewriting under binders. It is possible to rewrite under binders in the new implementation, if one provides the proper morphisms. Again, most of the work is handled in the tactics.
- First-class morphisms and signatures. Signatures and morphisms are ordinary Coq terms, hence they can be manipulated inside Coq, put inside structures and lemmas about them can be proved inside the system. Higher-order morphisms are also allowed.
- Performance. The implementation is based on a depth-first search for the first solution to a set of constraints which can be as fast as linear in the size of the term, and the size of the proof term is linear in the size of the original term. Besides, the extensibility allows the user to customize the proof search if necessary.

# 8.11.1 Introduction to generalized rewriting

#### Relations and morphisms

A parametric relation R is any term of type forall  $(x1 : T1) \dots (xn : Tn)$ , relation A. The expression A, which depends on  $x1 \dots xn$ , is called the *carrier* of the relation and R is said to be a relation over A; the list  $x1, \dots, xn$  is the (possibly empty) list of parameters of the relation.

#### **Example: Parametric relation**

It is possible to implement finite sets of elements of type A as unordered lists of elements of type A. The function set\_eq: forall (A : Type), relation (list A) satisfied by two lists with the same elements is a parametric relation over (list A) with one parameter A. The type of set\_eq is convertible with forall (A : Type), list A -> list A -> Prop.

An instance of a parametric relation R with n parameters is any term (R t1 ... tn).

Let R be a relation over A with n parameters. A term is a parametric proof of reflexivity for R if it has type forall (x1 : T1) ... (xn : Tn), reflexive (R x1 ... xn). Similar definitions are given for parametric proofs of symmetry and transitivity.

### Example: Parametric relation (continued)

The  $set\_eq$  relation of the previous example can be proved to be reflexive, symmetric and transitive. A parametric unary function f of type forall (x1:T1)...(xn:Tn), A1 -> A2 covariantly respects two parametric relation instances R1 and R2 if, whenever x, y satisfy R1 x y, their images (f x) and (f y) satisfy R2 (f x) (f y). An f that respects its input and output relations will be called a unary covariant morphism. We can also say that f is a monotone function with respect to R1 and R2. The sequence x1 ... xn represents the parameters of the morphism.

Let R1 and R2 be two parametric relations. The *signature* of a parametric morphism of type forall (x1: T1)... (xn: Tn), A1 -> A2 that covariantly respects two instances  $I_{R_1}$  and  $I_{R_2}$  of R1 and R2 is written  $I_{R_1} ++> I_{R_2}$ . Notice that the special arrow ++>, which reminds the reader of covariance, is placed between the two relation instances, not between the two carriers. The signature relation instances and morphism will be typed in a context introducing variables for the parameters.

The previous definitions are extended straightforwardly to n-ary morphisms, that are required to be simultaneously monotone on every argument.

Morphisms can also be contravariant in one or more of their arguments. A morphism is contravariant on an argument associated to the relation instance R if it is covariant on the same argument when the inverse relation  $R^{-1}$  (inverse R in Coq) is considered. The special arrow --> is used in signatures for contravariant morphisms.

Functions having arguments related by symmetric relations instances are both covariant and contravariant in those arguments. The special arrow ==> is used in signatures for morphisms that are both covariant and contravariant.

An instance of a parametric morphism f with n parameters is any term  $f t_1 \dots t_n$ .

#### Example: Morphisms

Continuing the previous example, let union: forall (A : Type), list A -> list A -> list A perform the union of two sets by appending one list to the other. union is a binary morphism parametric over A that respects the relation instance (set\_eq A). The latter condition is proved by showing:

```
forall (A: Type) (S1 S1' S2 S2': list A),
  set_eq A S1 S1' ->
  set_eq A S2 S2' ->
  set_eq A (union A S1 S2) (union A S1' S2').
```

The signature of the function union A is set\_eq A ==> set\_eq A ==> set\_eq A for all A.

# **Example: Contravariant morphisms**

The division function Rdiv: R -> R is a morphism of signature le ++> le --> le where le is the usual order relation over real numbers. Notice that division is covariant in its first argument and contravariant in its second argument.

Leibniz equality is a relation and every function is a morphism that respects Leibniz equality. Unfortunately, Leibniz equality is not always the intended equality for a given structure.

In the next section we will describe the commands to register terms as parametric relations and morphisms. Several tactics that deal with equality in Coq can also work with the registered relations. The exact list of tactics will be given in this section. For instance, the tactic reflexivity can be used to solve a goal R n n whenever R is an instance of a registered reflexive relation. However, the tactics that replace in a context C[] one term with another one related by R must verify that C[] is a morphism that respects the intended relation. Currently the verification consists of checking whether C[] is a syntactic composition of morphism instances that respects some obvious compatibility constraints.

# Example: Rewriting

Continuing the previous examples, suppose that the user must prove set\_eq int (union int S1 S2) S2) (f S1 S2) under the hypothesis H: set\_eq int S2 (@nil int). It is possible to use the rewrite tactic to replace the first two occurrences of S2 with @nil int in the goal since the context set\_eq int (union int (union int S1 nil) nil) (f S1 S2), being a composition of morphisms instances, is a morphism. However the tactic will fail replacing the third occurrence of S2 unless f has also been declared as a morphism.

#### Adding new relations and morphisms

```
Command: Add Parametric Relation binders: (A t1 ... tn) (Aeq t1 ... tm) reflexivity proved by term This command declares a parametric relation Aeq: forall (y1 : \beta1 ... ym : \betam), relation (A t1 ... tn) over (A : \alphai -> ... \alphan -> Type).
```

The final *ident* gives a unique name to the morphism and it is used by the command to generate fresh names for automatically provided lemmas used internally.

Notice that the carrier and relation parameters may refer to the context of variables introduced at the beginning of the declaration, but the instances need not be made only of variables. Also notice that A is *not* required to be a term having the same parameters as Aeq, although that is often the case in practice (this departs from the previous implementation).

To use this command, you need to first import the module Setoid using the command Require Import Setoid.

#### Command: Add Relation

In case the carrier and relations are not parametric, one can use this command instead, whose syntax is the same except there is no local context.

The proofs of reflexivity, symmetry and transitivity can be omitted if the relation is not an equivalence relation. The proofs must be instances of the corresponding relation definitions: e.g. the proof of reflexivity must have a type convertible to reflexive (A t1 ... tn) (Aeq t 1 ... tn). Each proof may refer to the introduced variables as well.

### **Example: Parametric relation**

For Leibniz equality, we may declare:

```
Add Parametric Relation (A : Type) : A (@eq A)
    [reflexivity proved by @refl_equal A]
...
```

Some tactics (reflexivity, symmetry, transitivity) work only on relations that respect the expected properties. The remaining tactics (replace, rewrite and derived tactics such as autorewrite) do not require any properties over the relation. However, they are able to replace terms with related ones only in contexts that are syntactic compositions of parametric morphism instances declared with the following command.

Command: Add Parametric Morphism binders: (ident term, ) with signature term, as ident

This command declares a parametric morphism *ident* term<sub>1</sub> of signature term<sub>2</sub>. The final identifier *ident* gives a unique name to the morphism and it is used as the base name of the typeclass instance definition and as the name of the lemma that proves the well-definedness of the morphism. The parameters of the morphism as well as the signature may refer to the context of variables. The command asks the user to prove interactively that the function denoted by the first *ident* respects the relations identified from the signature.

#### Example

We start the example by assuming a small theory over homogeneous sets and we declare set equality as a parametric equivalence relation and union of two sets as a parametric morphism.

```
Require Export Setoid.
Require Export Relation_Definitions.
Set Implicit Arguments.
Parameter set : Type -> Type.
Parameter empty : forall A, set A.
Parameter eq_set : forall A, set A -> set A -> Prop.
Parameter union : forall A, set A -> set A -> set A.
Axiom eq_set_refl : forall A, reflexive _ (eq_set (A:=A)).
Axiom eq_set_sym : forall A, symmetric _ (eq_set (A:=A)).
Axiom eq_set_trans : forall A, transitive _ (eq_set (A:=A)).
Axiom empty_neutral : forall A (S : set A), eq_set (union S (empty A)) S.
Axiom union_compat :
  forall (A : Type),
    forall x x' : set A, eq_set x x' ->
    forall y y' : set A, eq_set y y' ->
      eq_set (union x y) (union x' y').
Add Parametric Relation A : (set A) (@eq_set A)
 reflexivity proved by (eq_set_refl (A:=A))
 symmetry proved by (eq_set_sym (A:=A))
 transitivity proved by (eq_set_trans (A:=A))
 as eq_set_rel.
Add Parametric Morphism A : (@union A)
 with signature (@eq_set A) ==> (@eq_set A) ==> (@eq_set A) as union_mor.
Proof.
exact (@union_compat A).
Qed.
```

It is possible to reduce the burden of specifying parameters using (maximally inserted) implicit arguments. If A is always set as maximally implicit in the previous example, one can write:

```
Add Parametric Relation A : (set A) eq_set
reflexivity proved by eq_set_refl
symmetry proved by eq_set_sym
transitivity proved by eq_set_trans
as eq_set_rel.

Add Parametric Morphism A : (@union A) with
signature eq_set ==> eq_set ==> eq_set as union_mor.

Proof. exact (@union_compat A). Qed.
```

We proceed now by proving a simple lemma performing a rewrite step and then applying reflexivity, as we would do working with Leibniz equality. Both tactic applications are accepted since the required properties over eq\_set and union can be established from the two declarations above.

```
Goal forall (S : set nat),
   eq_set (union (union S (empty nat)) S) (union S S).
Proof.
intros.
rewrite empty_neutral.
reflexivity.
Qed.
```

The tables of relations and morphisms are managed by the typeclass instance mechanism. The behavior on section close is to generalize the instances by the variables of the section (and possibly hypotheses used in the proofs of instance declarations) but not to export them in the rest of the development for proof search. One can use the cmd:Existing Instance command to do so outside the section, using the name of the

declared morphism suffixed by \_Morphism, or use the Global modifier for the corresponding class instance declaration (see *First Class Setoids and Morphisms*) at definition time. When loading a compiled file or importing a module, all the declarations of this module will be loaded.

#### Rewriting and non reflexive relations

To replace only one argument of an n-ary morphism it is necessary to prove that all the other arguments are related to themselves by the respective relation instances.

#### Example

To replace (union S empty) with S in (union (union S empty) S) (union S S) the rewrite tactic must exploit the monotony of union (axiom union\_compat in the previous example). Applying union\_compat by hand we are left with the goal eq\_set (union S S) (union S S).

When the relations associated to some arguments are not reflexive, the tactic cannot automatically prove the reflexivity goals, that are left to the user.

Setoids whose relations are partial equivalence relations (PER) are useful for dealing with partial functions. Let R be a PER. We say that an element x is defined if R x x. A partial function whose domain comprises all the defined elements is declared as a morphism that respects R. Every time a rewriting step is performed the user must prove that the argument of the morphism is defined.

#### Example

Let eq0 be fun x y => x = y /\ x <> 0 (the smallest PER over nonzero elements). Division can be declared as a morphism of signature eq ==> eq0 ==> eq. Replacing x with y in div x n = div y n opens an additional goal eq0 n n which is equivalent to n = n /\ n <> 0.

### Rewriting and non symmetric relations

When the user works up to relations that are not symmetric, it is no longer the case that any covariant morphism argument is also contravariant. As a result it is no longer possible to replace a term with a related one in every context, since the obtained goal implies the previous one if and only if the replacement has been performed in a contravariant position. In a similar way, replacement in an hypothesis can be performed only if the replaced term occurs in a covariant position.

# Example: Covariance and contravariance

Suppose that division over real numbers has been defined as a morphism of signature Z.div: Z.lt ++> Z.lt --> Z.lt (i.e. Z.div is increasing in its first argument, but decreasing on the second one). Let < denote Z.lt. Under the hypothesis H: x < y we have k < x / y -> k < x / x, but not k < y / x -> k < x / x. Dually, under the same hypothesis k < x / y -> k < y / y holds, but k < y / x -> k < y / y does not. Thus, if the current goal is k < x / x, it is possible to replace only the second occurrence of x (in contravariant position) with y since the obtained goal must imply the current one. On the contrary, if k < x / x is an hypothesis, it is possible to replace only the first occurrence of x (in covariant position) with y since the current hypothesis must imply the obtained one.

Contrary to the previous implementation, no specific error message will be raised when trying to replace a term that occurs in the wrong position. It will only fail because the rewriting constraints are not satisfiable. However it is possible to use the at modifier to specify which occurrences should be rewritten.

As expected, composing morphisms together propagates the variance annotations by switching the variance every time a contravariant position is traversed.

### Example

Let us continue the previous example and let us consider the goal x / (x / x) < k. The first and third occurrences of x are in a contravariant position, while the second one is in covariant position. More in detail, the second occurrence of x occurs covariantly in (x / x) (since division is covariant in its first argument), and thus contravariantly in x / (x / x) (since division is contravariant in its second argument), and finally covariantly in x / (x / x) < k (since <, as every transitive relation, is contravariant in its first argument with respect to the relation itself).

#### Rewriting in ambiguous setoid contexts

One function can respect several different relations and thus it can be declared as a morphism having multiple signatures.

#### Example

Union over homogeneous lists can be given all the following signatures: eq ==> eq (eq being the equality over ordered lists) set\_eq ==> set\_eq (set\_eq being the equality over unordered lists up to duplicates), multiset\_eq ==> multiset\_eq ==> multiset\_eq (multiset\_eq being the equality over unordered lists).

To declare multiple signatures for a morphism, repeat the Add Morphism command.

When morphisms have multiple signatures it can be the case that a rewrite request is ambiguous, since it is unclear what relations should be used to perform the rewriting. Contrary to the previous implementation, the tactic will always choose the first possible solution to the set of constraints generated by a rewrite and will not try to find all the possible solutions to warn the user about them.

# 8.11.2 Commands and tactics

#### First class setoids and morphisms

The implementation is based on a first-class representation of properties of relations and morphisms as typeclasses. That is, the various combinations of properties on relations and morphisms are represented as records and instances of these classes are put in a hint database. For example, the declaration:

```
Add Parametric Relation (x1 : T1) ... (xn : Tn) : (A t1 ... tn) (Aeq t1 ... tm)

[reflexivity proved by ref1]
[symmetry proved by sym]
[transitivity proved by trans]
as id.

is equivalent to an instance declaration:

Instance (x1 : T1) ... (xn : Tn) => id : @Equivalence (A t1 ... tn) (Aeq t1 ... tm) :=

[Equivalence_Reflexive := ref1]
[Equivalence_Symmetric := sym]
[Equivalence_Transitive := trans].
```

The declaration itself amounts to the definition of an object of the record type Coq.Classes. RelationClasses. Equivalence and a hint added to the typeclass\_instances hint database. Morphism declarations are also instances of a typeclass defined in Classes. Morphisms. See the documentation on Typeclasses and the theories files in Classes for further explanations.

One can inform the rewrite tactic about morphisms and relations just by using the typeclass mechanism to declare them using Instance and Context vernacular commands. Any object of type Proper (the type of morphism declarations) in the local context will also be automatically used by the rewriting tactic to solve constraints.

Other representations of first class setoids and morphisms can also be handled by encoding them as records. In the following example, the projections of the setoid relation and of the morphism function can be registered as parametric relations and morphisms.

#### Example: First class setoids

```
Require Import Relation_Definitions Setoid.
Record Setoid : Type :=
{ car: Type;
 eq: car -> car -> Prop;
 refl: reflexive _ eq;
 sym: symmetric _ eq;
 trans: transitive _ eq
Add Parametric Relation (s : Setoid) : (@car s) (@eq s)
 reflexivity proved by (refl s)
 symmetry proved by (sym s)
 transitivity proved by (trans s) as eq_rel.
Record Morphism (S1 S2 : Setoid) : Type :=
{ f: car S1 -> car S2;
 compat: forall (x1 x2 : car S1), eq S1 x1 x2 \rightarrow eq S2 (f x1) (f x2)
Add Parametric Morphism (S1 S2 : Setoid) (M : Morphism S1 S2) :
  (@f S1 S2 M) with signature (@eq S1 ==> @eq S2) as apply_mor.
Proof.
apply (compat S1 S2 M).
Lemma test : forall (S1 S2 : Setoid) (m : Morphism S1 S2)
  (x y : car S1), eq S1 x y \rightarrow eq S2 (f _ m x) (f _ m y).
Proof.
intros.
rewrite H.
reflexivity.
Qed.
```

#### Tactics enabled on user provided relations

The following tactics, all prefixed by setoid\_, deal with arbitrary registered relations and morphisms. Moreover, all the corresponding unprefixed tactics (i.e. reflexivity, symmetry, transitivity, replace, rewrite) have been extended to fall back to their prefixed counterparts when the relation involved is not Leibniz equality. Notice, however, that using the prefixed tactics it is possible to pass additional arguments such as using relation.

```
Variant: setoid_reflexivity

Variant: setoid_symmetry in ident
```

```
Variant: setoid_transitivity

Variant: setoid_rewrite orientation | term at occurrences | in ident |

Variant: setoid_replace term with term using relation term | in ident | by tactic |
```

The using relation arguments cannot be passed to the unprefixed form. The latter argument tells the tactic what parametric relation should be used to replace the first tactic argument with the second one. If omitted, it defaults to the DefaultRelation instance on the type of the objects. By default, it means the most recent Equivalence instance in the environment, but it can be customized by declaring new DefaultRelation instances. As Leibniz equality is a declared equivalence, it will fall back to it if no other relation is declared on a given type.

Every derived tactic that is based on the unprefixed forms of the tactics considered above will also work up to user defined relations. For instance, it is possible to register hints for *autorewrite* that are not proofs of Leibniz equalities. In particular it is possible to exploit *autorewrite* to simulate normalization in a term rewriting system up to user defined equalities.

#### Printing relations and morphisms

#### Command: Print Instances

This command can be used to show the list of currently registered Reflexive (using Print Instances Reflexive), Symmetric or Transitive relations, Equivalences, PreOrders, PERs, and Morphisms (implemented as Proper instances). When the rewriting tactics refuse to replace a term in a context because the latter is not a composition of morphisms, the *Print Instances* command can be useful to understand what additional morphisms should be registered.

#### Deprecated syntax and backward incompatibilities

#### Command: Add Setoid qualid, qualid, qualid, as ident

This command for declaring setoids and morphisms is also accepted due to backward compatibility reasons.

Here  $qualid_2$  is a congruence relation without parameters,  $qualid_1$  is its carrier and  $qualid_3$  is an object of type (Setoid\_Theory  $qualid_1$   $qualid_2$ ) (i.e. a record packing together the reflexivity, symmetry and transitivity lemmas). Notice that the syntax is not completely backward compatible since the identifier was not required.

#### Command: Add Morphism ident : ident

This command is restricted to the declaration of morphisms without parameters. It is not fully backward compatible since the property the user is asked to prove is slightly different: for n-ary morphisms the hypotheses of the property are permuted; moreover, when the morphism returns a proposition, the property is now stated using a bi-implication in place of a simple implication. In practice, porting an old development to the new semantics is usually quite simple.

#### Command: Declare Morphism ident : ident

This commands is to be used in a module type to declare a parameter that is a morphism.

Notice that several limitations of the old implementation have been lifted. In particular, it is now possible to declare several relations with the same carrier and several signatures for the same morphism. Moreover, it is now also possible to declare several morphisms having the same signature. Finally, the *replace* and *rewrite* tactics can be used to replace terms in contexts that were refused by the old implementation. As discussed in the next section, the semantics of the new *setoid\_rewrite* tactic differs slightly from the old one and *rewrite*.

# 8.11.3 Extensions

#### Rewriting under binders

Warning: Due to compatibility issues, this feature is enabled only when calling the <code>setoid\_rewrite</code> tactic directly and not <code>rewrite</code>.

To be able to rewrite under binding constructs, one must declare morphisms with respect to pointwise (setoid) equivalence of functions. Example of such morphisms are the standard all and ex combinators for universal and existential quantification respectively. They are declared as morphisms in the Classes.Morphisms\_Prop module. For example, to declare that universal quantification is a morphism for logical equivalence:

One then has to show that if two predicates are equivalent at every point, their universal quantifications are equivalent. Once we have declared such a morphism, it will be used by the setoid rewriting tactic each time we try to rewrite under an all application (products in Prop are implicitly translated to such applications).

Indeed, when rewriting under a lambda, binding variable x, say from P x to Q x using the relation iff, the tactic will generate a proof of pointwise\_relation A iff (fun x => P x) (fun x => Q x) from the proof of iff (P x) (Q x) and a constraint of the form Proper (pointwise\_relation A iff ==> ?) m will be generated for the surrounding morphism m.

Hence, one can add higher-order combinators as morphisms by providing signatures using pointwise extension for the relations on the functional arguments (or whatever subrelation of the pointwise extension). For example, one could declare the map combinator on lists as a morphism:

```
Instance map_morphism `{Equivalence A eqA, Equivalence B eqB} : 
 Proper ((eqA ==> eqB) ==> list_equiv eqA ==> list_equiv eqB) (@map A B).
```

where list\_equiv implements an equivalence on lists parameterized by an equivalence on the elements.

Note that when one does rewriting with a lemma under a binder using <code>setoid\_rewrite</code>, the application of the lemma may capture the bound variable, as the semantics are different from rewrite where the lemma is first matched on the whole term. With the new <code>setoid\_rewrite</code>, matching is done on each subterm separately and in its local environment, and all matches are rewritten <code>simultaneously</code> by default. The semantics of the previous <code>setoid\_rewrite</code> implementation can almost be recovered using the <code>at 1</code> modifier.

#### **Subrelations**

Subrelations can be used to specify that one relation is included in another, so that morphism signatures for one can be used for the other. If a signature mentions a relation R on the left of an arrow ==>, then the signature also applies for any relation S that is smaller than R, and the inverse applies on the right of an

arrow. One can then declare only a few morphisms instances that generate the complete set of signatures for a particular constant. By default, the only declared subrelation is iff, which is a subrelation of impl and inverse impl (the dual of implication). That's why we can declare only two morphisms for conjunction: Proper (impl ==> impl ==> impl) and and Proper (iff ==> iff ==> iff) and. This is sufficient to satisfy any rewriting constraints arising from a rewrite using iff, impl or inverse impl through and.

Subrelations are implemented in Classes.Morphisms and are a prime example of a mostly user-space extension of the algorithm.

## **Constant unfolding**

The resolution tactic is based on typeclasses and hence regards user- defined constants as transparent by default. This may slow down the resolution due to a lot of unifications (all the declared Proper instances are tried at each node of the search tree). To speed it up, declare your constant as rigid for proof search using the command *Typeclasses Opaque*.

# 8.11.4 Strategies for rewriting

#### **Definitions**

The generalized rewriting tactic is based on a set of strategies that can be combined to obtain custom rewriting procedures. Its set of strategies is based on the programmable rewriting strategies with generic traversals by Visser et al. [LV97] [VBT98], which formed the core of the Stratego transformation language [Vis01]. Rewriting strategies are applied using the tactic rewrite\_strat strategy where strategy is a strategy expression. Strategies are defined inductively as described by the following grammar:

```
strategy
                qualid (lemma, left to right)
                <- qualid (lemma, right to left)
                fail (failure)
                id (identity)
                refl (reflexivity)
                progress strategy (progress)
                try strategy (try catch)
                strategy ; strategy (composition)
                choice strategy strategy (left_biased_choice)
                repeat strategy (one or more)
                any strategy (zero or more)
                subterm strategy (one subterm)
                subterms strategy (all subterms)
                innermost strategy (innermost first)
                outermost strategy (outermost first)
                bottomup strategy (bottom-up)
                topdown strategy (top-down)
                hints ident (apply hints from hint database)
                terms term ... term (any of the terms)
                eval redexpr (apply reduction)
                fold term (unify)
                ( strategy )
```

Actually a few of these are defined in term of the others using a primitive fixpoint operator:

```
• try strategy := choice strategy id
```

```
any strategy := fix ident. try (strategy; ident)
repeat strategy := strategy; any strategy
bottomup strategy := fix ident. (choice (progress (subterms ident)) strategy); try ident
topdown strategy := fix ident. (choice strategy (progress (subterms ident))); try ident
innermost strategy := fix ident. (choice (subterm ident) strategy)
outermost strategy := fix ident. (choice strategy (subterm ident))
```

The basic control strategy semantics are straightforward: strategies are applied to subterms of the term to rewrite, starting from the root of the term. The lemma strategies unify the left-hand-side of the lemma with the current subterm and on success rewrite it to the right- hand-side. Composition can be used to continue rewriting on the current subterm. The fail strategy always fails while the identity strategy succeeds without making progress. The reflexivity strategy succeeds, making progress using a reflexivity proof of rewriting. progress tests progress of the argument strategy and fails if no progress was made, while try always succeeds, catching failures. choice is left-biased: it will launch the first strategy and fall back on the second one in case of failure. One can iterate a strategy at least 1 time using repeat and at least 0 times using any.

The subterm and subterms strategies apply their argument strategy to respectively one or all subterms of the current term under consideration, left-to-right. subterm stops at the first subterm for which strategy made progress. The composite strategies innermost and outermost perform a single innermost or outermost rewrite using their argument strategy. Their counterparts bottomup and topdown perform as many rewritings as possible, starting from the bottom or the top of the term.

Hint databases created for *autorewrite* can also be used by *rewrite\_strat* using the hints strategy that applies any of the lemmas at the current subterm. The terms strategy takes the lemma names directly as arguments. The eval strategy expects a reduction expression (see *Performing computations*) and succeeds if it reduces the subterm under consideration. The fold strategy takes a *term* and tries to *unify* it to the current subterm, converting it to *term* on success. It is stronger than the tactic fold.

#### **Usage**

```
rewrite_strat strategy in ident ?
```

Rewrite using the strategy s in hypothesis ident or the conclusion.

 ${\bf Error:}$  Nothing to rewrite.

If the strategy failed.

Error: No progress made.

If the strategy succeeded but made no progress.

Error: Unable to satisfy the rewriting constraints.

If the strategy succeeded and made progress but the corresponding rewriting constraints are not satisfied.

The setoid rewrite c tactic is basically equivalent to rewrite strat (outermost c).

# 8.12 Asynchronous and Parallel Proof Processing

Author Enrico Tassi

This chapter explains how proofs can be asynchronously processed by Coq. This feature improves the reactivity of the system when used in interactive mode via CoqIDE. In addition, it allows Coq to take advantage of parallel hardware when used as a batch compiler by decoupling the checking of statements and definitions from the construction and checking of proofs objects.

This feature is designed to help dealing with huge libraries of theorems characterized by long proofs. In the current state, it may not be beneficial on small sets of short files.

This feature has some technical limitations that may make it unsuitable for some use cases.

For example, in interactive mode, some errors coming from the kernel of Coq are signaled late. The type of errors belonging to this category are universe inconsistencies.

At the time of writing, only opaque proofs (ending with Qed or Admitted) can be processed asynchronously.

Finally, asynchronous processing is disabled when running CoqIDE in Windows. The current implementation of the feature is not stable on Windows. It can be enabled, as described below at *Interactive mode*, though doing so is not recommended.

#### 8.12.1 Proof annotations

To process a proof asynchronously Coq needs to know the precise statement of the theorem without looking at the proof. This requires some annotations if the theorem is proved inside a Section (see Section Section mechanism).

When a section ends, Coq looks at the proof object to decide which section variables are actually used and hence have to be quantified in the statement of the theorem. To avoid making the construction of proofs mandatory when ending a section, one can start each proof with the Proof using command (Section Switching on/off the proof editing mode) that declares which section variables the theorem uses.

The presence of **Proof** using is needed to process proofs asynchronously in interactive mode.

It is not strictly mandatory in batch mode if it is not the first time the file is compiled and if the file itself did not change. When the proof does not begin with Proof using, the system records in an auxiliary file, produced along with the .vo file, the list of section variables used.

#### Automatic suggestion of proof annotations

The Suggest Proof Using flag makes Coq suggest, when a Qed command is processed, a correct proof annotation. It is up to the user to modify the proof script accordingly.

#### 8.12.2 Proof blocks and error resilience

Coq 8.6 introduced a mechanism for error resilience: in interactive mode Coq is able to completely check a document containing errors instead of bailing out at the first failure.

Two kind of errors are supported: errors occurring in vernacular commands and errors occurring in proofs.

To properly recover from a failing tactic, Coq needs to recognize the structure of the proof in order to confine the error to a sub proof. Proof block detection is performed by looking at the syntax of the proof script (i.e. also looking at indentation). Coq comes with four kind of proof blocks, and an ML API to add new ones.

**curly** blocks are delimited by { and }, see Chapter *Proof handling* 

par blocks are atomic, i.e. just one tactic introduced by the par: goal selector

**indent** blocks end with a tactic indented less than the previous one

bullet blocks are delimited by two equal bullet signs at the same indentation level

#### **Caveats**

When a vernacular command fails the subsequent error messages may be bogus, i.e. caused by the first error. Error resilience for vernacular commands can be switched off by passing -async-proofs-command-error-resilience off to CoqIDE.

An incorrect proof block detection can result into an incorrect error recovery and hence in bogus errors. Proof block detection cannot be precise for bullets or any other non well parenthesized proof structure. Error resilience can be turned off or selectively activated for any set of block kind passing to CoqIDE one of the following options:

- -async-proofs-tactic-error-resilience off
- -async-proofs-tactic-error-resilience all
- -async-proofs-tactic-error-resilience blocktype

Valid proof block types are: "curly", "par", "indent", and "bullet".

#### 8.12.3 Interactive mode

At the time of writing the only user interface supporting asynchronous proof processing is CoqIDE.

When CoqIDE is started, two Coq processes are created. The master one follows the user, giving feedback as soon as possible by skipping proofs, which are delegated to the worker process. The worker process, whose state can be seen by clicking on the button in the lower right corner of the main CoqIDE window, asynchronously processes the proofs. If a proof contains an error, it is reported in red in the label of the very same button, that can also be used to see the list of errors and jump to the corresponding line.

If a proof is processed asynchronously the corresponding Qed command is colored using a lighter color than usual. This signals that the proof has been delegated to a worker process (or will be processed lazily if the -async-proofs lazy option is used). Once finished, the worker process will provide the proof object, but this will not be automatically checked by the kernel of the main process. To force the kernel to check all the proof objects, one has to click the button with the gears (Fully check the document) on the top bar. Only then all the universe constraints are checked.

#### **Caveats**

634

The number of worker processes can be increased by passing CoqIDE the <code>-async-proofs-j</code> n flag. Note that the memory consumption increases too, since each worker requires the same amount of memory as the master process. Also note that increasing the number of workers may reduce the reactivity of the master process to user commands.

To disable this feature, one can pass the <code>-async-proofs</code> off flag to CoqIDE. Conversely, on Windows, where the feature is disabled by default, pass the <code>-async-proofs</code> on flag to enable it.

Proofs that are known to take little time to process are not delegated to a worker process. The threshold can be configured with -async-proofs-delegation-threshold. Default is 0.03 seconds.

# 8.12.4 Batch mode

Warning: The -vio flag is subsumed, for most practical usage, by the the more recent -vos flag. See Compiled interfaces (produced using -vos).

Warning: When working with .vio files, do not use the -vos option at the same time, otherwise stale files might get loaded when executing a Require. Indeed, the loading of a nonempty .vos file is assigned higher priority than the loading of a .vio file.

When Coq is used as a batch compiler by running coqc, it produces a .vo file for each .v file. A .vo file contains, among other things, theorem statements and proofs. Hence to produce a .vo Coq need to process all the proofs of the .v file.

The asynchronous processing of proofs can decouple the generation of a compiled file (like the .vo one) that can be loaded by Require from the generation and checking of the proof objects. The -vio flag can be passed to coqc to produce, quickly, .vio files. Alternatively, when using a Makefile produced by coq\_makefile, the vio target can be used to compile all files using the -vio flag.

A .vio file can be loaded using Require exactly as a .vo file but proofs will not be available (the Print command produces an error). Moreover, some universe constraints might be missing, so universes inconsistencies might go unnoticed. A .vio file does not contain proof objects, but proof tasks, i.e. what a worker process can transform into a proof object.

Compiling a set of files with the -vio flag allows one to work, interactively, on any file without waiting for all the proofs to be checked.

When working interactively, one can fully check all the .v files by running coqc as usual.

Alternatively one can turn each .vio into the corresponding .vo. All .vio files can be processed in parallel, hence this alternative might be faster. The command coqc -schedule-vio2vo 2 a b c can be used to obtain a good scheduling for two workers to produce a.vo, b.vo, and c.vo. When using a Makefile produced by coq\_makefile, the vio2vo target can be used for that purpose. Variable J should be set to the number of workers, e.g. make vio2vo J=2. The only caveat is that, while the .vo files obtained from .vio files are complete (they contain all proof terms and universe constraints), the satisfiability of all universe constraints has not been checked globally (they are checked to be consistent for every single proof). Constraints will be checked when these .vo files are (recursively) loaded with Require.

There is an extra, possibly even faster, alternative: just check the proof tasks stored in .vio files without producing the .vo files. This is possibly faster because all the proof tasks are independent, hence one can further partition the job to be done between workers. The coqc -schedule-vio-checking 6 a b c command can be used to obtain a good scheduling for 6 workers to check all the proof tasks of a.vio, b.vio, and c.vio. Auxiliary files are used to predict how long a proof task will take, assuming it will take the same amount of time it took last time. When using a Makefile produced by coq\_makefile, the checkproofs target can be used to check all .vio files. Variable J should be set to the number of workers, e.g. make checkproofs J=6. As when converting .vio files to .vo files, universe constraints are not checked to be globally consistent. Hence this compilation mode is only useful for quick regression testing and on developments not making heavy use of the Type hierarchy.

#### 8.12.5 Limiting the number of parallel workers

Many Coq processes may run on the same computer, and each of them may start many additional worker processes. The coqworkmgr utility lets one limit the number of workers, globally.

The utility accepts the -j argument to specify the maximum number of workers (defaults to 2). coqworkmgr automatically starts in the background and prints an environment variable assignment like

COQWORKMGR\_SOCKET=localhost:45634. The user must set this variable in all the shells from which Coq processes will be started. If one uses just one terminal running the bash shell, then export 'coqworkmgr-j 4' will do the job.

After that, all Coq processes, e.g. coqide and coqc, will respect the limit, globally.

# 8.13 Miscellaneous extensions

# 8.13.1 Program derivation

Coq comes with an extension called Derive, which supports program derivation. Typically in the style of Bird and Meertens or derivations of program refinements. To use the Derive extension it must first be required with Require Coq.derive.Derive. When the extension is loaded, it provides the following command:

Command: Derive ident, SuchThat type As ident,

 $ident_1$  can appear in type. This command opens a new proof presenting the user with a goal for type in which the name  $ident_1$  is bound to an existential variable ?x (formally, there are other goals standing for the existential variables but they are shelved, as described in shelve).

When the proof ends two constants are defined:

- The first one is named  $ident_1$  and is defined as the proof of the shelved goal (which is also the value of ?x). It is always transparent.
- The second one is named *ident*<sub>2</sub>. It has type *type*, and its body is the proof of the initially visible goal. It is opaque if the proof ends with *Qed*, and transparent if the proof ends with *Defined*.

# Example

```
Require Coq.derive.Derive.
    [Loading ML file derive_plugin.cmxs ... done]
Require Import Coq.Numbers.Natural.Peano.NPeano.
Section P.
Variables (n m k:nat).
   n is declared
   m is declared
   k is declared
Derive p SuchThat ((k*n)+(k*m) = p) As h.
   1 focused subgoal
    (shelved: 1)
     n, m, k : nat
     p := ?Goal : nat
     _____
     k * n + k * m = p
Proof.
rewrite <- Nat.mul_add_distr_1.
   1 focused subgoal
    (shelved: 1)
     n, m, k : nat
```

(continues on next page)

(continued from previous page)

```
p := ?Goal : nat
      _____
      k * (n + m) = p
subst p.
    1 focused subgoal
    (shelved: 1)
     \mathtt{n}\,,\;\mathtt{m}\,,\;\mathtt{k}\;:\;\mathtt{nat}
      _____
      k * (n + m) = ?Goal
reflexivity.
    No more subgoals.
Qed.
End P.
Print p.
   p = fun n m k : nat => k * (n + m)
         : nat -> nat -> nat -> nat
    Arguments p (_ _ _)%nat_scope
Check h.
   h
         : forall n m k : nat, k * n + k * m = p n m k
```

Any property can be used as term, not only an equation. In particular, it could be an order relation specifying some form of program refinement or a non-executable property from which deriving a program is convenient.

# 8.14 Polymorphic Universes

Author Matthieu Sozeau

# 8.14.1 General Presentation

Warning: The status of Universe Polymorphism is experimental.

This section describes the universe polymorphic extension of Coq. Universe polymorphism makes it possible to write generic definitions making use of universes and reuse them at different and sometimes incompatible universe levels.

A standard example of the difference between universe *polymorphic* and *monomorphic* definitions is given by the identity function:

```
Definition identity \{A : Type\} (a : A) := a.
```

By default, constant declarations are monomorphic, hence the identity function declares a global universe (say Top.1) for its domain. Subsequently, if we try to self-apply the identity, we will get an error:

```
Fail Definition selfid := identity (@identity).
   The command has indeed failed with message:
   The term "@identity" has type "forall A : Type, A -> A"
   while it is expected to have type "?A"
   (unable to find a well-typed instantiation for "?A": cannot ensure that
   "Type@{identity.u0+1}" is a subtype of "Type@{identity.u0}").
```

Indeed, the global level Top.1 would have to be strictly smaller than itself for this self-application to type check, as the type of (@identity) is forall (A : Type@{Top.1}), A -> A whose type is itself Type@{Top.1+1}.

A universe polymorphic identity function binds its domain universe level at the definition level instead of making it global.

```
Polymorphic Definition pidentity {A : Type} (a : A) := a.
About pidentity.
  pidentity@{Top.2} : forall A : Type, A -> A

  pidentity is universe polymorphic
  Arguments pidentity {A}%type_scope
  pidentity is transparent
  Expands to: Constant Top.pidentity
```

It is then possible to reuse the constant at different levels, like so:

```
Definition selfpid := pidentity (@pidentity).
```

Of course, the two instances of pidentity in this definition are different. This can be seen when the *Printing Universes* flag is on:

```
Print selfpid.
    selfpid =
    pidentity@{selfpid.u0} (@pidentity@{selfpid.u1})
        : forall A : Type@{selfpid.u1}, A -> A
    (* {selfpid.u1 selfpid.u0} /= selfpid.u1 < selfpid.u0 *)
Arguments selfpid _%type_scope</pre>
```

Now pidentity is used at two different levels: at the head of the application it is instantiated at Top.3 while in the argument position it is instantiated at Top.4. This definition is only valid as long as Top.4 is strictly smaller than Top.3, as shown by the constraints. Note that this definition is monomorphic (not universe polymorphic), so the two universes (in this case Top.3 and Top.4) are actually global levels.

When printing pidentity, we can see the universes it binds in the annotation <code>@{Top.2}</code>. Additionally, when *Printing Universes* is on we print the "universe context" of pidentity consisting of the bound universes and the constraints they must verify (for pidentity there are no constraints).

Inductive types can also be declared universes polymorphic on universes appearing in their parameters or fields. A typical example is given by monoids:

```
Polymorphic Record Monoid := { mon_car :> Type; mon_unit : mon_car;
  mon_op : mon_car -> mon_car -> mon_car }.
```

Print Monoid.

The Monoid's carrier universe is polymorphic, hence it is possible to instantiate it for example with Monoid itself. First we build the trivial unit monoid in Set:

```
Definition unit_monoid : Monoid :=
  {| mon_car := unit; mon_unit := tt; mon_op x y := tt |}.
```

From this we can build a definition for the monoid of Set-monoids (where multiplication would be given by the product of monoids).

As one can see from the constraints, this monoid is "large", it lives in a universe strictly higher than Set.

# 8.14.2 Polymorphic, Monomorphic

#### Command: Polymorphic definition

As shown in the examples, polymorphic definitions and inductives can be declared using the Polymorphic prefix.

#### Flag: Universe Polymorphism

Once enabled, this flag will implicitly prepend Polymorphic to any definition of the user.

# Command: Monomorphic definition

When the *Universe Polymorphism* flag is set, to make a definition producing global universe constraints, one can use the Monomorphic prefix.

Many other commands support the Polymorphic flag, including:

- Lemma, Axiom, and all the other "definition" keywords support polymorphism.
- Section will locally set the polymorphism flag inside the section.
- Variables, Context, Universe and Constraint in a section support polymorphism. See *Universe* polymorphism and sections for more details.
- Hint Resolve and Hint Rewrite will use the auto/rewrite hint polymorphically, not at a single instance.

# 8.14.3 Cumulative, NonCumulative

Polymorphic inductive types, coinductive types, variants and records can be declared cumulative using the Cumulative prefix.

#### Command: Cumulative inductive

Declares the inductive as cumulative

Alternatively, there is a *Polymorphic Inductive Cumulativity* flag which when set, makes all subsequent *polymorphic* inductive definitions cumulative. When set, inductive types and the like can be enforced to be non-cumulative using the NonCumulative prefix.

#### Command: NonCumulative inductive

Declares the inductive as non-cumulative

#### Flag: Polymorphic Inductive Cumulativity

When this flag is on, it sets all following polymorphic inductive types as cumulative (it is off by default).

Consider the examples below.

```
Polymorphic Cumulative Inductive list {A : Type} :=
| nil : list
| cons : A -> list -> list.

Print list.
    Inductive list@{Top.12} (A : Type@{Top.12}) : Type@{max(Set,Top.12)} :=
        nil : list@{Top.12} | cons : A -> list@{Top.12} -> list@{Top.12}
    (* *Top.12 /= *)

Arguments list {A}%type_scope
Arguments nil {A}%type_scope
Arguments cons {A}%type_scope
```

When printing list, the universe context indicates the subtyping constraints by prefixing the level names with symbols.

Because inductive subtypings are only produced by comparing inductives to themselves with universes changed, they amount to variance information: each universe is either invariant, covariant or irrelevant (there are no contravariant subtypings in Coq), respectively represented by the symbols =, + and \*.

Here we see that list binds an irrelevant universe, so any two instances of list are convertible:  $E[\Gamma] \vdash \text{list}@\{i\}$   $A =_{\beta\delta\iota\zeta\eta} \text{list}@\{j\}$  B whenever  $E[\Gamma] \vdash A =_{\beta\delta\iota\zeta\eta} B$  and this applies also to their corresponding constructors, when they are comparable at the same type.

See *Conversion rules* for more details on convertibility and subtyping. The following is an example of a record with non-trivial subtyping relation:

```
Polymorphic Cumulative Record packType := {pk : Type}.

packType is defined

pk is defined
```

packType binds a covariant universe, i.e.

```
E[\Gamma] \vdash \mathsf{packType}@\{i\} =_{\beta\delta\iota\zeta\eta} \mathsf{packType}@\{j\} \text{ whenever } i \leq j
```

Cumulative inductive types, coinductive types, variants and records only make sense when they are universe polymorphic. Therefore, an error is issued whenever the user uses the Cumulative or NonCumulative prefix in a monomorphic context. Notice that this is not the case for the *Polymorphic Inductive Cumulativity* flag. That is, this flag, when set, makes all subsequent *polymorphic* inductive declarations cumulative (unless, of course the NonCumulative prefix is used) but has no effect on *monomorphic* inductive declarations.

Consider the following examples.

```
Fail Monomorphic Cumulative Inductive Unit := unit.
   The command has indeed failed with message:
   The Cumulative prefix can only be used in a polymorphic context.

Fail Monomorphic NonCumulative Inductive Unit := unit.
   The command has indeed failed with message:
   The NonCumulative prefix can only be used in a polymorphic context.
```

```
Set Polymorphic Inductive Cumulativity.
Inductive Unit := unit.
   Unit is defined
   Unit_rect is defined
   Unit_ind is defined
   Unit_rec is defined
   Unit_rec is defined
   Unit_sind is defined
```

# An example of a proof using cumulativity

```
Set Universe Polymorphism.
Set Polymorphic Inductive Cumulativity.
\label{localized inductive eq0} \mbox{Inductive eq0{i} $\{A : Type0{i}\} \ (x : A) : A \rightarrow Type0{i} := eq_refl : eq x x. $$}
\label{lem:definition funext_type} $$ \end{a} \ b \ e \ (A : Type0{a}) \ (B : A \rightarrow Type0{b}) $$
:= forall f g : (forall a, B a),
                   (forall x, eq@{e} (f x) (g x))
                   -> eq@{e} f g.
Section down.
Universes a b e e'.
Constraint e' < e.
Lemma funext_down {A B}
      (H : @funext_type@{a b e} A B) : @funext_type@{a b e'} A B.
Proof.
exact H.
Defined.
End down.
```

# 8.14.4 Cumulativity Weak Constraints

#### Flag: Cumulativity Weak Constraints

When set, which is the default, causes "weak" constraints to be produced when comparing universes in an irrelevant position. Processing weak constraints is delayed until minimization time. A weak constraint between  ${\tt u}$  and  ${\tt v}$  when neither is smaller than the other and one is flexible causes them to be unified. Otherwise the constraint is silently discarded.

This heuristic is experimental and may change in future versions. Disabling weak constraints is more predictable but may produce arbitrary numbers of universes.

# 8.14.5 Global and local universes

Each universe is declared in a global or local environment before it can be used. To ensure compatibility, every *global* universe is set to be strictly greater than Set when it is introduced, while every *local* (i.e. polymorphically quantified) universe is introduced as greater or equal to Set.

#### 8.14.6 Conversion and unification

The semantics of conversion and unification have to be modified a little to account for the new universe instance arguments to polymorphic references. The semantics respect the fact that definitions are transparent, so indistinguishable from their bodies during conversion.

This is accomplished by changing one rule of unification, the first- order approximation rule, which applies when two applicative terms with the same head are compared. It tries to short-cut unfolding by comparing the arguments directly. In case the constant is universe polymorphic, we allow this rule to fire only when unifying the universes results in instantiating a so-called flexible universe variables (not given by the user). Similarly for conversion, if such an equation of applicative terms fail due to a universe comparison not being satisfied, the terms are unfolded. This change implies that conversion and unification can have different unfolding behaviors on the same development with universe polymorphism switched on or off.

#### 8.14.7 Minimization

Universe polymorphism with cumulativity tends to generate many useless inclusion constraints in general. Typically at each application of a polymorphic constant f, if an argument has expected type TypeO{i} and is given a term of type TypeO{j}, a  $j \leq i$  constraint will be generated. It is however often the case that an equation j = i would be more appropriate, when f's universes are fresh for example. Consider the following example:

```
Definition id0 := @pidentity nat 0.
Print id0.
   id0@{} = pidentity@{Set} 0
      : nat
```

This definition is elaborated by minimizing the universe of id0 to level Set while the more general definition would keep the fresh level i generated at the application of id and a constraint that  $Set \leq i$ . This minimization process is applied only to fresh universe variables. It simply adds an equation between the variable and its lower bound if it is an atomic universe (i.e. not an algebraic max() universe).

#### Flag: Universe Minimization ToSet

Turning this flag off (it is on by default) disallows minimization to the sort Set and only collapses floating universes between themselves.

# 8.14.8 Explicit Universes

The syntax has been extended to allow users to explicitly bind names to universes and explicitly instantiate polymorphic definitions.

#### Command: Universe ident

#### Command: Polymorphic Universe ident

In the monorphic case, this command declares a new global universe named ident, which can be referred to using its qualified name as well. Global universe names live in a separate namespace. The command supports the Polymorphic flag only in sections, meaning the universe quantification will be discharged on each section definition independently.

### Command: Constraint universe\_constraint

# Command: Polymorphic Constraint universe\_constraint

This command declares a new constraint between named universes.

```
\begin{array}{ll} \text{universe\_constraint} & ::= & qualid < qualid \\ & qualid <= qualid \\ & qualid = qualid \end{array}
```

If consistent, the constraint is then enforced in the global environment. Like *Universe*, it can be used with the Polymorphic prefix in sections only to declare constraints discharged at section closing time. One cannot declare a global constraint on polymorphic universes.

Error: Undeclared universe *ident*. Error: Universe inconsistency.

#### Polymorphic definitions

For polymorphic definitions, the declaration of (all) universe levels introduced by a definition uses the following syntax:

```
Polymorphic Definition le@{i j} (A : Type@{i}) : Type@{j} := A.

Print le.
    le@{i j} =
    fun A : Type@{i} => A
        : Type@{i} -> Type@{j}
    (* i j |= i <= j *)

Arguments le _%type_scope</pre>
```

During refinement we find that j must be larger or equal than i, as we are using A: Type@{i} <= Type@{j}, hence the generated constraint. At the end of a definition or proof, we check that the only remaining universes are the ones declared. In the term and in general in proof mode, introduced universe names can be referred to in terms. Note that local universe names shadow global universe names. During a proof, one can use Show Universes to display the current context of universes.

It is possible to provide only some universe levels and let Coq infer the others by adding a + in the list of bound universe levels:

```
Fail Definition foobar@{u} : Type@{u} := Type.
    The command has indeed failed with message:
    Universe {Top.50} is unbound.

Definition foobar@{u +} : Type@{u} := Type.
    foobar is defined

Set Printing Universes.
Print foobar.
    foobar@{u Top.52} = Type@{Top.52}
        : Type@{u}
        (* u Top.52 /= Top.52 < u *)</pre>
```

This can be used to find which universes need to be explicitly bound in a given definition.

Definitions can also be instantiated explicitly, giving their full instance:

User-named universes and the anonymous universe implicitly attached to an explicit **Type** are considered rigid for unification and are never minimized. Flexible anonymous universes can be produced with an underscore or by omitting the annotation to a polymorphic definition.

#### Flag: Strict Universe Declaration

Turning this flag off allows one to freely use identifiers for universes without declaring them first, with the semantics that the first use declares it. In this mode, the universe names are not associated with the definition or proof once it has been defined. This is meant mainly for debugging purposes.

#### Flag: Private Polymorphic Universes

This flag, on by default, removes universes which appear only in the body of an opaque polymorphic definition from the definition's universe arguments. As such, no value needs to be provided for these universes when instantiating the definition. Universe constraints are automatically adjusted.

Consider the following definition:

```
Lemma foo@{i} : Type@{i}.
   1 subgoal
     _____
     Type@{i}
Proof.
exact Type.
   No more subgoals.
Qed.
Print foo.
   foo@{i} =
   Type@{Top.63}
        : Type@{i}
    (* Public universes:
    i /= Set < i
    Private universes:
    \{Top.63\} \mid = Top.63 < i * \}
```

The universe Top.xxx for the Type in the body cannot be accessed, we only care that one exists for any instantiation of the universes appearing in the type of foo. This is guaranteed when the transitive constraint Set <= Top.xxx < i is verified. Then when using the constant we don't need to put a value for the inner universe:

```
Check foo@{_}.
   foo@{Top.64}
        : Type@{Top.64}
    (* {Top.64} |= Set < Top.64 *)
and when not looking at the body we don't mention the private universe:
About foo.
   foo@{i} : Type@{i}
    (* i |= Set < i *)
   foo is universe polymorphic
   foo is opaque
   Expands to: Constant Top.foo
To recover the same behaviour with regard to universes as Defined, the Private Polymorphic
Universes flag may be unset:
Unset Private Polymorphic Universes.
Lemma bar : Type.
   1 subgoal
     _____
     Type@{Top.65}
Proof.
exact Type.
   No more subgoals.
Qed.
About bar.
   bar@{Top.65 Top.66} : Type@{Top.65}
    (* Top.65 Top.66 |= Top.66 < Top.65 *)
   bar is universe polymorphic
   bar is opaque
   Expands to: Constant Top.bar
Fail Check bar@{_}.
   The command has indeed failed with message:
   Universe instance should have length 2.
Check bar@\{\_ _\}.
   bar@{Top.68
   Top.69}
         : Type@{Top.68}
    (* {Top.69 Top.68} |= Top.69 < Top.68 *)
Note that named universes are always public.
Set Private Polymorphic Universes.
Unset Strict Universe Declaration.
Lemma baz : Type@{outer}.
   1 subgoal
     _____
     Type@{outer}
```

(continues on next page)

(continued from previous page)

```
Proof.
exact Type@{inner}.
    No more subgoals.

Qed.
About baz.
    baz@{outer inner} : Type@{outer}
    (* outer inner /= inner < outer *)

baz is universe polymorphic
baz is opaque
Expands to: Constant Top.baz</pre>
```

### 8.14.9 Universe polymorphism and sections

Variables, Context, Universe and Constraint in a section support polymorphism. This means that the universe variables and their associated constraints are discharged polymorphically over definitions that use them. In other words, two definitions in the section sharing a common variable will both get parameterized by the universes produced by the variable declaration. This is in contrast to a "mononorphic" variable which introduces global universes and constraints, making the two definitions depend on the same global universes associated to the variable.

It is possible to mix universe polymorphism and monomorphism in sections, except in the following ways:

• no monomorphic constraint may refer to a polymorphic universe:

```
Section Foo.
Polymorphic Universe i.
Fail Constraint i = i.
   The command has indeed failed with message:
   Cannot add monomorphic constraints which refer to section polymorphic universes.
```

This includes constraints implicitly declared by commands such as *Variable*, which may need to be used with universe polymorphism activated (locally by attribute or globally by option):

```
Fail Variable A : (Type@{i} : Type).
   The command has indeed failed with message:
    Cannot add monomorphic constraints which refer to section polymorphic universes.
Polymorphic Variable A : (Type@{i} : Type).
   A is declared
```

(in the above example the anonymous Type constrains polymorphic universe i to be strictly smaller.)

• no monomorphic constant or inductive may be declared if polymorphic universes or universe constraints are present.

These restrictions are required in order to produce a sensible result when closing the section (the requirement on constants and inductives is stricter than the one on constraints, because constants and inductives are abstracted by *all* the section's polymorphic universes and constraints).

### 8.15 SProp (proof irrelevant propositions)

Warning: The status of strict propositions is experimental.

This section describes the extension of Coq with definitionally proof irrelevant propositions (types in the sort SProp, also known as strict propositions) as described in [GCST19].

Using SProp may be prevented by passing -disallow-sprop to the Coq program or using Allow StrictProp.

#### Flag: Allow StrictProp

Allows using SProp when set and forbids it when unset. The initial value depends on whether you used the command line -disallow-sprop and -allow-sprop.

Error: SProp not allowed, you need to Set Allow StrictProp or to use the -allow-sprop command-line-flag Some of the definitions described in this document are available through Coq.Logic.StrictProp, which see.

#### 8.15.1 Basic constructs

The purpose of SProp is to provide types where all elements are convertible:

```
Definition irrelevance (A:SProp) (P:A \rightarrow Prop) (x:A) (v:P x) (y:A) : P y := v.
```

Since we have definitional  $\eta$ -expansion for functions, the property of being a type of definitionally irrelevant values is impredicative, and so is SProp:

```
Check fun (A:Type) (B:A \rightarrow SProp) \Rightarrow (forall x:A, B x) : SProp.
```

Warning: Conversion checking through bytecode or native code compilation currently does not understand proof irrelevance.

In order to keep conversion tractable, cumulativity for SProp is forbidden:

```
Fail Check (fun (A:SProp) => A : Type).
   The command has indeed failed with message:
   In environment
   A : SProp
   The term "A" has type "SProp" while it is expected to have type "Type".
```

We can explicitly lift strict propositions into the relevant world by using a wrapping inductive type. The inductive stops definitional proof irrelevance from escaping.

```
Inductive Box (A:SProp) : Prop := box : A -> Box A.
Arguments box {_} _.

Fail Check fun (A:SProp) (x y : Box A) => eq_refl : x = y.
    The command has indeed failed with message:
    In environment
    A : SProp
    x : Box A
    y : Box A
```

(continues on next page)

(continued from previous page)

```
The term "eq_refl" has type "x = x" while it is expected to have type
"x = y" (cannot unify "x" and "y").

Definition box_irrelevant (A:SProp) (x y : Box A) : x = y
:= match x, y with box x, box y => eq_refl end.
```

In the other direction, we can use impredicativity to "squash" a relevant type, making an irrelevant approximation.

```
Definition iSquash (A:Type) : SProp
  := forall P : SProp, (A -> P) -> P.
Definition isquash A : A -> iSquash A
  := fun a P f => f a.
Definition iSquash_sind A (P : iSquash A -> SProp) (H : forall x : A, P (isquash A x))
  : forall x : iSquash A, P x
  := fun x => x (P x) (H : A -> P x).
```

Or more conveniently (but equivalently)

```
Inductive Squash (A:Type) : SProp := squash : A -> Squash A.
```

Most inductives types defined in SProp are squashed types, i.e. they can only be eliminated to construct proofs of other strict propositions. Empty types are the only exception.

```
Inductive sEmpty : SProp := .
Check sEmpty_rect.
    sEmpty_rect
    : forall (P : sEmpty -> Type) (s : sEmpty), P s
```

**Note:** Eliminators to strict propositions are called **foo\_sind**, in the same way that eliminators to propositions are called **foo\_ind**.

Primitive records in SProp are allowed when fields are strict propositions, for instance:

```
Set Primitive Projections.
Record sProd (A B : SProp) : SProp := { sfst : A; ssnd : B }.
```

On the other hand, to avoid having definitionally irrelevant types in non-SProp sorts (through record  $\eta$ -extensionality), primitive records in relevant sorts must have at least one relevant field.

```
Set Warnings "+non-primitive-record".
Fail Record rBox (A:SProp) : Prop := rbox { runbox : A }.
   The command has indeed failed with message:
   The record rBox could not be defined as a primitive record

Record ssig (A:Type) (P:A -> SProp) : Type := { spr1 : A; spr2 : P spr1 }.
```

Note that rBox works as an emulated record, which is equivalent to the Box inductive.

### 8.15.2 Encodings for strict propositions

The elimination for unit types can be encoded by a trivial function thanks to proof irrelevance:

### 8.15.3 Issues with non-cumulativity

Inductive sUnit : SProp := stt.

During normal term elaboration, we don't always know that a type is a strict proposition early enough. For instance:

```
Definition constant_0 : ?[T] \rightarrow nat := fun_ : sUnit => 0.
```

While checking the type of the constant, we only know that ?[T] must inhabit some sort. Putting it in some floating universe u would disallow instantiating it by sUnit: SProp.

In order to make the system usable without having to annotate every instance of SProp, we consider SProp to be a subtype of every universe during elaboration (i.e. outside the kernel). Then once we have a fully elaborated term it is sent to the kernel which will check that we didn't actually need cumulativity of SProp (in the example above, u doesn't appear in the final term).

This means that some errors will be delayed until Qed:

```
Lemma foo : Prop.
Proof.
pose (fun A : SProp => A : Type); exact True.

Fail Qed.
    The command has indeed failed with message:
    In environment
    A : SProp
    The term "A" has type "SProp" while it is expected to have type "Type".

Abort.
```

#### Flag: Elaboration StrictProp Cumulativity

Unset this flag (it is on by default) to be strict with regard to SProp cumulativity during elaboration.

The implementation of proof irrelevance uses inferred "relevance" marks on binders to determine which variables are irrelevant. Together with non-cumulativity this allows us to avoid retyping during conversion. However during elaboration cumulativity is allowed and so the algorithm may miss some irrelevance:

```
Fail Definition late_mark := fun (A:SProp) (P:A \rightarrow Prop) x y (v:P x) => v : P y.

The command has indeed failed with message:

In environment

(continues on next page)
```

(continued from previous page)

```
A : SProp P : A \rightarrow Prop \\ x : A \\ y : A \\ v : P x The term "v" has type "P x" while it is expected to have type "P y".
```

The binders for x and y are created before their type is known to be A, so they're not marked irrelevant. This can be avoided with sufficient annotation of binders (see irrelevance at the beginning of this chapter) or by bypassing the conversion check in tactics.

```
Definition late_mark := fun (A:SProp) (P:A \rightarrow Prop) x y (v:P x) => ltac:(exact_no_check v) : P y.
```

The kernel will re-infer the marks on the fully elaborated term, and so correctly converts x and y.

#### Warning: Bad relevance

This is a developer warning, disabled by default. It is emitted by the kernel when it is passed a term with incorrect relevance marks. To avoid conversion issues as in late\_mark you may wish to use it to find when your tactics are producing incorrect marks.

### **BIBLIOGRAPHY**

- [Asp00] David Aspinall. Proof general: a generic tool for proof development. In Susanne Graf and Michael Schwartzbach, editors, *Tools and Algorithms for the Construction and Analysis of Systems, TACAS 2000*, volume 1785 of Lecture Notes in Computer Science, pages 38–43. Springer Berlin Heidelberg, 2000. doi:10.1007/3-540-46419-0\_3<sup>319</sup>.
- [Bar81] H.P. Barendregt. The Lambda Calculus its Syntax and Semantics. North-Holland, 1981.
- [BDenesGregoire11] Mathieu Boespflug, Maxime Dénès, and Benjamin Grégoire. Full reduction at full throttle. In Jean-Pierre Jouannaud and Zhong Shao, editors, Certified Programs and Proofs First International Conference, CPP 2011, Kenting, Taiwan, December 7-9, 2011. Proceedings, volume 7086 of Lecture Notes in Computer Science, 362–377. Springer, 2011. URL: http://dx.doi.org/10.1007/978-3-642-25379-9 26, doi:10.1007/978-3-642-25379-9 26<sup>320</sup>.
- [Bou97] S. Boutin. Using reflection to build efficient and certified decision procedure s. In Martin Abadi and Takahashi Ito, editors, *TACS'97*, volume 1281 of Lecture Notes in Computer Science. Springer-Verlag, 1997.
- [Coq89] T. Coquand. Metamathematical investigations of a calculus of constructions. Technical Report RR-1088, INRIA, September 1989. URL: https://hal.inria.fr/inria-00075471.
- [CH86a] T. Coquand and Gérard Huet. Concepts mathematiques et informatiques formalises dans le calcul des constructions. Technical Report RR-0515, INRIA, April 1986. URL: https://hal.inria.fr/ inria-00076039.
- [CH86b] T. Coquand and Gérard Huet. The calculus of constructions. Technical Report RR-0530, INRIA, May 1986. URL: https://hal.inria.fr/inria-00076024.
- [Coq85] Th. Coquand. Une Théorie des Constructions. PhD thesis, Université Paris 7, January 1985.
- [Coq86] Th. Coquand. An Analysis of Girard's Paradox. In Symposium on Logic in Computer Science. Cambridge, MA, 1986. IEEE Computer Society Press.
- [Coq92] Th. Coquand. Pattern Matching with Dependent Types. In *Proceedings of the 1992 Workshop on Types for Proofs and Programs*. 1992.
- [CH85] Thierry Coquand and Gérard Huet. Constructions: a higher order proof system for mechanizing mathematics. In *European Conference on Computer Algebra*, 151–184. Springer Berlin Heidelberg, 1985. URL: http://dx.doi.org/10.1007/3-540-15983-5\_13, doi:10.1007/3-540-15983-5\_13<sup>321</sup>.

 $<sup>^{319}~\</sup>rm{https://doi.org/10.1007/3-540-46419-0\_3}$ 

 $<sup>^{320}</sup>$  https://doi.org/10.1007/978-3-642-25379-9\_26

<sup>&</sup>lt;sup>321</sup> https://doi.org/10.1007/3-540-15983-5\_13

- [CP90] Thierry Coquand and Christine Paulin. Inductively defined types. In COLOG-88, 50–66. Springer Berlin Heidelberg, 1990. URL: http://dx.doi.org/10.1007/3-540-52335-9\_47, doi:10.1007/3-540-52335-9\_47<sup>322</sup>.
- [CT95] Cristina Cornes and Delphine Terrasse. Automating inversion of inductive predicates in coq. In TYPES, 85–104, 1995.
- [CFC58] Haskell B. Curry, Robert Feys, and William Craig. Combinatory Logic. Volume 1. North-Holland, 1958. §9E.
- [DM82] Luis Damas and Robin Milner. Principal type-schemes for functional programs. In Proceedings of the 9th ACM SIGPLAN-SIGACT Symposium on Principles of Programming Languages, POPL '82, 207–212. New York, NY, USA, 1982. ACM. URL: http://doi.acm.org/10.1145/582153.582176, doi:10.1145/582153.582176<sup>323</sup>.
- [dB72] N.J. de Bruijn. Lambda-Calculus Notation with Nameless Dummies, a Tool for Automatic Formula Manipulation, with Application to the Church-Rosser Theorem. *Indag. Math.*, 1972.
- [Del00] D. Delahaye. A Tactic Language for the System Coq. In Proceedings of Logic for Programming and Automated Reasoning (LPAR), Reunion Island, volume 1955 of Lecture Notes in Computer Science, 85– 95. Springer-Verlag, November 2000. URL: http://www.lirmm.fr/%7Edelahaye/papers/ltac%20(LPAR% 2700).pdf.
- [dC95] R. di Cosmo. Isomorphisms of Types: from  $\lambda$ -calculus to information retrieval and language design. Progress in Theoretical Computer Science. Birkhauser, 1995. ISBN-0-8176-3763-X.
- [Dyc92] Roy Dyckhoff. Contraction-free sequent calculi for intuitionistic logic. *The Journal of Symbolic Logic*, September 1992.
- [GCST19] Gaëtan Gilbert, Jesper Cockx, Matthieu Sozeau, and Nicolas Tabareau. Definitional Proof Irrelevance Without K. Proc. ACM Program. Lang., 3(POPL):3:1–3:28, 2019. URL: http://doi.acm.org/10.1145/3290316.
- [Gimenez94] E. Giménez. Codifying guarded definitions with recursive schemes. In *Types'94: Types for Proofs and Programs*, volume 996 of Lecture Notes in Computer Science. Springer-Verlag, 1994. Extended version in LIP research report 95-07, ENS Lyon.
- [Gimenez95] E. Giménez. An application of co-inductive types in coq: verification of the alternating bit protocol. In *Workshop on Types for Proofs and Programs*, number 1158 in Lecture Notes in Computer Science, 135–152. Springer-Verlag, 1995.
- [Gimenez98] E. Giménez. A tutorial on recursive types in coq. Technical Report, INRIA, March 1998.
- [GimenezCasteran05] E. Giménez and P. Castéran. A tutorial on [co-]inductive types in coq. available at http://coq.inria.fr/doc, January 2005.
- [GMN+91] Alessandro Giovini, Teo Mora, Gianfranco Niesi, Lorenzo Robbiano, and Carlo Traverso. "one sugar cube, please" or selection strategies in the buchberger algorithm. In *Proceedings of the ISSAC'91*, ACM Press, 5–4. 1991.
- [GLT89] J.-Y. Girard, Y. Lafont, and P. Taylor. *Proofs and Types*. Cambridge Tracts in Theoretical Computer Science 7. Cambridge University Press, 1989.
- [GZND11] Georges Gonthier, Beta Ziliani, Aleksandar Nanevski, and Derek Dreyer. How to make ad hoc proof automation less ad hoc. SIGPLAN Not., 46(9):163–175, September 2011. URL: http://doi.acm.org/10.1145/2034574.2034798, doi:10.1145/2034574.2034798<sup>324</sup>.

652 Bibliography

<sup>322</sup> https://doi.org/10.1007/3-540-52335-9\_47

<sup>&</sup>lt;sup>323</sup> https://doi.org/10.1145/582153.582176

 $<sup>^{324}</sup>$  https://doi.org/10.1145/2034574.2034798

- [GregoireL02] Benjamin Grégoire and Xavier Leroy. A compiled implementation of strong reduction. In Mitchell Wand and Simon L. Peyton Jones, editors, *Proceedings of the Seventh ACM SIG-PLAN International Conference on Functional Programming (ICFP '02)*, *Pittsburgh*, *Pennsylvania*, *USA*, *October 4-6*, 2002., 235–246. ACM, 2002. URL: http://doi.acm.org/10.1145/581478.581501, doi:10.1145/581478.581501<sup>325</sup>.
- [How80] W.A. Howard. The formulae-as-types notion of constructions. In J.P. Seldin and J.R. Hindley, editors, to H.B. Curry: Essays on Combinatory Logic, Lambda Calculus and Formalism. Academic Press, 1980.
- [Hue89] G. Huet. The Constructive Engine. In R. Narasimhan, editor, A perspective in Theoretical Computer Science. Commemorative Volume for Gift Siromoney. World Scientific Publishing, 1989.
- [Hue88] Gérard Huet. Induction principles formalized in the calculus of constructions. In *Programming of Future Generation Computers*. *Elsevier Science*. Springer Berlin Heidelberg, 1988. URL: http://dx.doi.org/10.1007/3-540-17660-8\_62, doi:10.1007/3-540-17660-8\_62<sup>326</sup>.
- [LW11] Gyesik Lee and Benjamin Werner. Proof-irrelevant model of CC with predicative induction and judgmental equality. *Logical Methods in Computer Science*, 2011.
- [Ler90] X. Leroy. The ZINC experiment: an economical implementation of the ML language. Technical Report 117, INRIA, 1990.
- [Let02] P. Letouzey. A new extraction for coq. In TYPES. 2002. URL: http://www.irif.fr/~letouzey/download/extraction2002.pdf.
- [LV97] Sebastiaan P. Luttik and Eelco Visser. Specification of rewriting strategies. In 2nd International Workshop on the Theory and Practice of Algebraic Specifications (ASF+SDF'97), Electronic Workshops in Computing. Springer-Verlag, 1997.
- [MT13] Assia Mahboubi and Enrico Tassi. Canonical Structures for the working Coq user. In Sandrine Blazy, Christine Paulin, and David Pichardie, editors, ITP 2013, 4th Conference on Interactive Theorem Proving, volume 7998 of LNCS, 19–34. Rennes, France, 2013. Springer. URL: http://hal.inria.fr/hal-00816703, doi:10.1007/978-3-642-39634-2\_5<sup>327</sup>.
- [McB00] Conor McBride. Elimination with a motive. In TYPES, 197–216. 2000.
- [Moh86] Christine Mohring. Algorithm development in the calculus of constructions. In LICS, 84–91. 1986.
- [Mun94] C. Muñoz. Démonstration automatique dans la logique propositionnelle intuitionniste. Master's thesis, DEA d'Informatique Fondamentale, Université Paris 7, September 1994.
- [Mye86] Eugene Myers. An O(ND) difference algorithm and its variations. *Algorithmica*, 1986. URL: http://www.xmailserver.org/diff2.pdf.
- [Par95] C. Parent. Synthesizing proofs from programs in the Calculus of Inductive Constructions. In *Mathematics of Program Construction'95*, volume 947 of LNCS. Springer-Verlag, 1995.
- [PM93a] C. Paulin-Mohring. Inductive Definitions in the System Coq Rules and Properties. In M. Bezem and J.-F. Groote, editors, *Proceedings of the conference Typed Lambda Calculi and Applications*, number 664 in LNCS. Springer-Verlag, 1993. Also LIP research report 92-49, ENS Lyon.
- [PM89] Christine Paulin-Mohring. Extracting  $\omega$ 's programs from proofs in the calculus of constructions. In *Proceedings of the 16th ACM SIGPLAN-SIGACT symposium on Principles of programming languages*, 89–104. ACM Press, 1989. URL: http://dx.doi.org/10.1145/75277.75285, doi:10.1145/75277.75285<sup>328</sup>.

Bibliography 653

<sup>&</sup>lt;sup>325</sup> https://doi.org/10.1145/581478.581501

<sup>326</sup> https://doi.org/10.1007/3-540-17660-8\_62

 $<sup>^{327}~\</sup>rm{https://doi.org/10.1007/978\text{-}3\text{-}642\text{-}39634\text{-}2\_5}$ 

 $<sup>^{328}</sup>$  https://doi.org/10.1145/75277.75285

- [PM93b] Christine Paulin-Mohring. Inductive definitions in the system coq rules and properties. In *International Conference on Typed Lambda Calculi and Applications*, 328–345. Springer-Verlag, 1993. URL: http://dx.doi.org/10.1007/bfb0037116, doi:10.1007/bfb0037116<sup>329</sup>.
- [PPM89] Frank Pfenning and Christine Paulin-Mohring. Inductively defined types in the calculus of constructions. In *International Conference on Mathematical Foundations of Programming Semantics*, 209–228. Springer-Verlag, 1989. URL: http://dx.doi.org/10.1007/bfb0040259, doi:10.1007/bfb0040259<sup>330</sup>.
- [PCC16] Clément Pit-Claudel and Pierre Courtieu. Company-coq: taking proof general one step closer to a real ide. In *CoqPL'16: The Second International Workshop on Coq for PL*. January 2016. doi:10.5281/zenodo.44331<sup>331</sup>.
- [Pug92] W. Pugh. The omega test: a fast and practical integer programming algorithm for dependence analysis. *Communication of the ACM*, pages 102–114, 1992.
- [ROS98] John Rushby, Sam Owre, and N. Shankar. Subtypes for specifications: predicate subtyping in PVS. *IEEE Transactions on Software Engineering*, 24(9):709–720, September 1998.
- [Soz07] Matthieu Sozeau. Subset coercions in Coq. In TYPES'06, volume 4502 of LNCS, 237–252. Springer, 2007.
- [SO08] Matthieu Sozeau and Nicolas Oury. First-Class Type Classes. In TPHOLs'08. 2008.
- [Vis01] Eelco Visser. Stratego: A language for program transformation based on rewriting strategies. In RTA, volume 2051 of LNCS, 357–362. 2001.
- [VBT98] Eelco Visser, Zine-El-Abidine Benaissa, and Andrew P. Tolmach. Building program optimizers with rewriting strategies. In *ICFP*, 13–26. 1998.
- [Wer94] B. Werner. Une théorie des constructions inductives. PhD thesis, Université Paris 7, 1994.

654 Bibliography

<sup>&</sup>lt;sup>329</sup> https://doi.org/10.1007/bfb0037116

 $<sup>^{330}</sup>$  https://doi.org/10.1007/bfb0040259

 $<sup>^{331}~\</sup>rm{https://doi.org/10.5281/zenodo.44331}$ 

## **COMMAND INDEX**

a	Combined Scheme, 518
Abort, 254	Compute, 238
About, 236	Conjecture, $132$
Add @table, 237	Conjectures, $132$
Add Field, 619	Constraint, 642
Add LoadPath, 246	Context, 160
Add ML Path, 246	Corollary, 144
Add Morphism, 629	Create HintDb, $324$
Add Parametric Morphism, 624	Cumulative, 639
Add Parametric Relation, 624	1
Add Rec LoadPath, 246	d
Add Rec ML Path, 246	Declare Custom Entry, $501$
Add Relation, $624$	Declare Instance, 585
Add Ring, 614	Declare Left Step, $313$
Add Setoid, 629	Declare ML Module, $245$
Admit Obligations, 609	Declare Module, 162
Admitted, 254	Declare Morphism, 629
Arguments (assert), 177	Declare Reduction, $250$
Arguments (bidirectionality hints), 186	Declare Right Step, $313$
Arguments (clear implicits), 172	Declare Scope, $505$
Arguments (default implicits), 174	Defined, $254$
Arguments (implicits), 172	Definition, $133$
Alguments (implicits), 1/2	,
Arguments (rename), 177	Delimit Scope, 506
Arguments (rename), 177	Delimit Scope, 506
Arguments (rename), $177$ Arguments (scopes), $507$	Delimit Scope, 506 Derive, 636
Arguments (rename), 177 Arguments (scopes), 507 Axiom, 132 Axioms, 132	Delimit Scope, 506 Derive, 636 Derive Inversion, 524 Drop, 247
Arguments (rename), 177 Arguments (scopes), 507 Axiom, 132 Axioms, 132 b	Delimit Scope, 506 Derive, 636 Derive Inversion, 524 Drop, 247 e
Arguments (rename), 177 Arguments (scopes), 507 Axiom, 132 Axioms, 132  b Back, 247	Delimit Scope, 506 Derive, 636 Derive Inversion, 524 Drop, 247  e End, 159
Arguments (rename), 177 Arguments (scopes), 507 Axiom, 132 Axioms, 132  b  Back, 247 BackTo, 247	Delimit Scope, 506 Derive, 636 Derive Inversion, 524 Drop, 247  e End, 159 Eval, 238
Arguments (rename), 177 Arguments (scopes), 507 Axiom, 132 Axioms, 132  b Back, 247	Delimit Scope, 506 Derive, 636 Derive Inversion, 524 Drop, 247  e End, 159 Eval, 238 Example, 133
Arguments (rename), 177 Arguments (scopes), 507 Axiom, 132 Axioms, 132  b Back, 247 BackTo, 247 Bind Scope, 508	Delimit Scope, 506 Derive, 636 Derive Inversion, 524 Drop, 247  e End, 159 Eval, 238 Example, 133 Existential, 256
Arguments (rename), 177 Arguments (scopes), 507 Axiom, 132 Axioms, 132  b Back, 247 BackTo, 247 Bind Scope, 508  C	Delimit Scope, 506 Derive, 636 Derive Inversion, 524 Drop, 247  e End, 159 Eval, 238 Example, 133 Existential, 256 Existing Instance, 586
Arguments (rename), 177 Arguments (scopes), 507 Axiom, 132 Axioms, 132  b Back, 247 BackTo, 247 Bind Scope, 508  C Canonical, 178	Delimit Scope, 506 Derive, 636 Derive Inversion, 524 Drop, 247  e End, 159 Eval, 238 Example, 133 Existential, 256 Existing Instance, 586 Export, 167
Arguments (rename), 177 Arguments (scopes), 507 Axiom, 132 Axioms, 132  b Back, 247 BackTo, 247 Bind Scope, 508  C Canonical, 178 Cd, 245	Delimit Scope, 506 Derive, 636 Derive Inversion, 524 Drop, 247  e End, 159 Eval, 238 Example, 133 Existential, 256 Existing Instance, 586 Export, 167 Extract Constant, 599
Arguments (rename), 177 Arguments (scopes), 507 Axiom, 132 Axioms, 132  b Back, 247 BackTo, 247 Bind Scope, 508  C Canonical, 178 Cd, 245 Check, 238	Delimit Scope, 506 Derive, 636 Derive Inversion, 524 Drop, 247  e End, 159 Eval, 238 Example, 133 Existential, 256 Existing Instance, 586 Export, 167 Extract Constant, 599 Extract Inductive, 599
Arguments (rename), 177 Arguments (scopes), 507 Axiom, 132 Axioms, 132  b Back, 247 BackTo, 247 Bind Scope, 508  C Canonical, 178 Cd, 245 Check, 238 Class, 585	Delimit Scope, 506 Derive, 636 Derive Inversion, 524 Drop, 247  e End, 159 Eval, 238 Example, 133 Existential, 256 Existing Instance, 586 Export, 167 Extract Constant, 599 Extract Inductive, 599 Extract Inlined Constant, 599
Arguments (rename), 177 Arguments (scopes), 507 Axiom, 132 Axioms, 132  b Back, 247 BackTo, 247 Bind Scope, 508  C Canonical, 178 Cd, 245 Check, 238 Class, 585 Close Scope, 506	Delimit Scope, 506 Derive, 636 Derive Inversion, 524 Drop, 247  e End, 159 Eval, 238 Example, 133 Existential, 256 Existing Instance, 586 Export, 167 Extract Constant, 599 Extract Inductive, 599 Extract Inlined Constant, 599 Extraction, 596
Arguments (rename), 177 Arguments (scopes), 507 Axiom, 132 Axioms, 132  b  Back, 247 BackTo, 247 Bind Scope, 508  C  Canonical, 178 Cd, 245 Check, 238 Class, 585 Close Scope, 506 Coercion, 565	Delimit Scope, 506 Derive, 636 Derive Inversion, 524 Drop, 247  e End, 159 Eval, 238 Example, 133 Existential, 256 Existing Instance, 586 Export, 167 Extract Constant, 599 Extract Inductive, 599 Extract Inlined Constant, 599 Extraction, 596 Extraction Blacklist, 600
Arguments (rename), 177 Arguments (scopes), 507 Axiom, 132 Axioms, 132  b  Back, 247 BackTo, 247 Bind Scope, 508  C  Canonical, 178 Cd, 245 Check, 238 Class, 585 Close Scope, 506 Coercion, 565 CoFixpoint, 143	Delimit Scope, 506 Derive, 636 Derive Inversion, 524 Drop, 247  e End, 159 Eval, 238 Example, 133 Existential, 256 Existing Instance, 586 Export, 167 Extract Constant, 599 Extract Inductive, 599 Extract Inlined Constant, 599 Extraction, 596 Extraction Blacklist, 600 Extraction Implicit, 598
Arguments (rename), 177 Arguments (scopes), 507 Axiom, 132 Axioms, 132  b  Back, 247 BackTo, 247 Bind Scope, 508  C  Canonical, 178 Cd, 245 Check, 238 Class, 585 Close Scope, 506 Coercion, 565	Delimit Scope, 506 Derive, 636 Derive Inversion, 524 Drop, 247  e End, 159 Eval, 238 Example, 133 Existential, 256 Existing Instance, 586 Export, 167 Extract Constant, 599 Extract Inductive, 599 Extract Inlined Constant, 599 Extraction, 596 Extraction Blacklist, 600

Extraction Library, $596$	Include, 161
Extraction NoInline, 597	Inductive, $134$
Extraction TestCompile, 596	Infix, $496$
f	Info, $370$ Inline, $162$
Fact, 144	Inspect, $236$
Fail, 248	Instance, $585$
Fixpoint, 141	1
Focus, $257$	I
From Require, 244	$\mathtt{Lemma},\ 144$
Function, 156	$\mathtt{Let},160$
Functional Scheme, $519$	Let (outside a section), $133$ Let CoFixpoint, $160$
g	Let Fixpoint, 160
Generalizable, 182	Load, 243 Local, 250
Generalizable All Variables, 182	,
Generalizable No Variables, 182	Local Close Scope, 506 Local Declare Custom Entry, 505
Global, 250	Local Definition, 133
Global Close Scope, 506	Local Notation, 505
Global Generalizable, 182	Local Open Scope, 506
Global Instance, 585	
Global Opaque, 249	Local Parameter, $132$ Locate, $242$
Global Open Scope, 506	Locate File, 246
Global Transparent, 249	
Goal, 253	Locate Library, 246
Grab Existential Variables, 256	Ltac, 363 Ltac2, 377
Guarded, 265	Ltac2 Eval, 386
h	Ltac2 Notation, 386
	Ltac2 Set, 377
Hint, 325	Ltac2 Type, 376
Hint Constants, 326	Eddez Type, 810
Hint Constructors, 326	m
Hint Cut, 327	Module, $161$
Hint Extern, 326	Module Type, 162
Hint Immediate, 325	Monomorphic, 639
Hint Mode, 327	Honomorphic, 000
Hint Opaque, 326	n
Hint Resolve, 325	
Hint Rewrite, 329	Next Obligation, 608 NonCumulative, 639
Hint Transparent, 326	Notation, 492
Hint Unfold, 326	•
Hint Variables, 326	Numeral Notation, 511
Hint View for, 490	0
Hint View for apply, 484	
Hint View for move, 484	Obligation, 608
Hypotheses, 160	Obligation Tactic, 608
Hypotheses (outside a section), 132	Obligations, 608
Hypothesis, 160	Opaque, 249
Hypothesis (outside a section), $132$	Open Scope, 506
i	Optimize Heap, $267$ Optimize Proof, $267$
Identity Coercion, 566	GF
Implicit Types, 180	p
Import, 166	Parameter, $132$

656 Command Index

Parameters, 132 Polymorphic, 639	$\begin{array}{c} {\tt Proof \ `term`},254 \\ {\tt Proof \ using},255 \end{array}$
Polymorphic Constraint, 642	Proof with, $330$
Polymorphic Universe, 642	Proposition, $144$
Prenex Implicits, 402	Pwd, 245
Preterm, 609	
Primitive, 253	q
Print, 236	$\mathtt{Qed},254$
Print All, 236	$\mathtt{Quit},247$
Print All Dependencies, 238	
Print Assumptions, 238	r
Print Canonical Projections, 179	Record, $147$
Print Classes, 566	Recursive Extraction, 596
Print Coercion Paths, 566	Recursive Extraction Library, 596
Print Coercions, 566	Redirect, 247
Print Custom Grammar, 503	Register, 252
Print Extraction Blacklist, 601	Register Inline, 253
Print Extraction Inline, 598	Remark, 144
Print Firstorder Solver, 332	Remove @table, 237
Print Grammar constr, 494	Remove Hints, 328
Print Grammar pattern, 494	Remove LoadPath, 246
Print Grammar tactic, 515	Require, 244
Print Graph, 566	Require Export, 244
Print Hint, 324	Require Import, 244
Print HintDb, 329	Reserved Notation, 496
Print Implicit, 177	Reset, 246
Print Instances, 629	Reset Extraction Blacklist, 601
Print Libraries, 245	Reset Extraction Inline, 598
Print LoadPath, 246	Reset Ltac Profile, 372
Print Ltac, 364	Restart, 257
Print Ltac Signatures, 364	10050010, 201
Print ML Modules, 245	S
Print ML Path, 246	Save, $254$
Print Module, 167	
Print Module Type, 167	Scheme, 516
Print Opaque Dependencies, 238	Scheme Equality, 516 Search, 238
Print Options, 237	Search (ssreflect), 486
Print Rewrite HintDb, 329	SearchAbout, 239
Print Scope, 510	•
Print Scopes, 510	SearchHead, 240 SearchPattern, 240
Print Strategy, 250	•
Print Table @table, 237	SearchRewrite, 241
Print Tables, 237	Section, 159
Print Term, 236	Separate Extraction, 596
Print Transparent Dependencies, 238	Set, 237
Print Typing Flags, 251	Set Coption, 237
Print Universes, 183	Show, 264
Print Universes Subgraph, 183	Show Conjectures, 265
Print Visibility, 510	Show Existentials, 265
Program Definition, 606	Show Goal, 265
Program Fixpoint, 607	Show Intro, 265
Program Instance, 585	Show Intros, 265
Program Lemma, 608	Show Ltac Profile, 372
Proof, 254	Show Obligation Tactic, 608
,	Show Proof, $264$

Command Index 657

```
Show Universes, 265
Show Zify BinOp, 595
Show Zify BinRel, 595
Show Zify CstOp, 595
Show Zify InjTyp, 595
Show Zify Spec, 595
Show Zify UnOp, 595
Solve All Obligations, 609
Solve Obligations, 609
Strategy, 249
String Notation, 513
Structure, 567
SubClass, 566
t
Tactic Notation, 515
Test, 237
Test Otable for, 237
Theorem, 144
Time, 247
Timeout, 248
Transparent, 249
Typeclasses eauto, 588
Typeclasses Opaque, 587
Typeclasses Transparent, 587
Undelimit Scope, 506
Undo, 257
Unfocus, 257
Unfocused, 257
Universe, 642
Unset, 237
Unset Coption, 237
Unshelve, 342
٧
Variable, 159
Variable (outside a section), 132
Variables, 160
Variables (outside a section), 132
Variant, 138
```

658 Command Index

## **TACTIC INDEX**

+	change_no_check, 343
+ (backtracking branching), $351$	classical_left, 337
	classical_right, 337
•	clear, 285
$\dots$ : (goal selector), $349$	clearbody, 285
$\dots$ : $\dots$ (ssreflect), $416$	cofix, 310
	compare, 335
=	compute, 315
=>, 419	congr, 463
r	congruence, 332
	congruence with, 334
[>   ] (dispatch), 349	constr_eq, 334
	constr_eq_strict, 334
a	constructor, 282
abstract, 362	contradict, 293
abstract (ssreflect), 419	contradiction, 293
absurd, 292	convert_concl_no_check, 344
admit, 292	cut, 291
all:, 349	cutrewrite, 312
apply, 278	cycle, 339
apply (ssreflect), 415	_1
apply in, 281	d
apply in as, 282	debug auto, $322$
assert, 289	debug trivial, $322$
assert_fails, 352	decide equality, $335$
assert_succeeds, 352	decompose, 288
assumption, 276	dependent destruction, 299
auto, 321	dependent induction, 298
autoapply, 586	dependent inversion, $305$
autorewrite, 323	dependent inversion with, $305$
autounfold, 323	dependent rewrite $\rightarrow$ , 336
dabbanioia, ozo	dependent rewrite <-, $336$
b	destruct, 293
btauto, 337	destruct eqn:, 294
by, 428	dintuition, 332
<b>by</b> , <del>12</del> 0	${\tt discriminate},301$
С	discrR, 198
	do, 350
case, 294	do (ssreflect), $431$
case (ssreflect), 414	done, 428
cbn, 316	double induction, 298
cbv, 314	dtauto, 331
change, 313	

e	g
eapply, 278	generalize, 291
eassert, 290	generally have, 489
eassumption, 276	gfail, 353
easy, 324	give_up, 342
eauto, 323	guard, 362
ecase, 294	
econstructor, 283	h
edestruct, 294	has_evar, 335
ediscriminate, 301	
eelim, 297	have, 433
eenough, 290	hnf, 316
eexact, 276	i
eexists, 283	
einduction, 296	idtac, 353
einjection, 303	in, 431
eintros, 284	induction, 295
eleft, 283	induction using, 296
elim, 297	info_trivial, 322
elim (ssreflect), 415	injection, 301
	instantiate, 292
elim with, 297	intro, 283
elimtype, 298	intros, 284
enough, 290	intros, $284$
epose, 288	intuition, 331
epose proof, 290	inversion, 304
eremember, 288	inversion using, $306$
erewrite, 312	inversion_clear, 304
eright, 283	inversion_sigma, 306
eset, 288	is_evar, 335
esimplify_eq, 336	is_var, 335
esplit, 283	1
evar, 292	1
exact, 276	lapply, 279
exact_no_check, 344	last, 429
exactly_once, 352	last first, 430
exfalso, 293	lazy, 314
exists, $282$	left, 283
r	let :=, 357
f	lia, 593
f_equal, 335	lra, 593
fail, 353	ltac-seq, 348
field, 338	-
field_simplify, $338$	m
field_simplify_eq, 338	match goal, 359
finish_timing, 357	move, 414
first, 351	move after, 285
first (ssreflect), 429	move at bottom, 286
first last, 430	move at top, 286
firstorder, 332	move before, 285
fix, 310	mo. o Dollolo , 200
fold, 319	n
function induction, 299	
functional inversion, 336	native_cast_no_check, 345
	native_compute, 315

660 Tactic Index

$\mathtt{nia},594$	$\mathtt{simpl},316$
notypeclasses refine, 278	simple apply, 279
now, 324	simple destruct, $294$
nra, 594	$\mathtt{simple}$ eapply, $279$
nsatz, 620	simple induction, 298
	simple inversion, $306$
0	simple notypeclasses refine, $278$
omega, 337	simple refine, $277$
once, 352	$simplify_eq, 336$
only :, 349	$\mathtt{solve},353$
optimize_heap, 374	${\tt solve\_constraints},342$
over, 459	${ t specialize},291$
	$\mathtt{split},282$
p	${\tt split\_Rabs},198$
par:, 350	${\tt split\_Rmult},198$
pattern, $320$	start ltac profiling, $373$
pose, 288	$\mathtt{stepl},313$
pose (ssreflect), 403	$\mathtt{stepr},313$
pose proof, 290	stop ltac profiling, $373$
progress, $350$	$\mathtt{subst},312$
psatz, 595	$\mathtt{suff}, 489$
,	suffices, 489
r	swap, $340$
red, 316	symmetry, 335
refine, 277	• •
reflexivity, 335	t
remember, 288	tauto, 330
rename, 287	$\texttt{time}, \overset{'}{3}56$
repeat, 350	time_constr, 356
replace, 312	timeout, 356
reset ltac profile, 373	transitivity, 335
restart_timer, 356	transparent_abstract, 363
revert, 285	trivial, 322
revert dependent, 285	try, 350
revgoals, 341	tryif, 352
rewrite, 310	typeclasses eauto, 586
rewrite (ssreflect), 444	31
rewrite_strat, 632	u
right, 283	under, $457$
ring, 337	unfold, 318
ring_simplify, 337	unify, 334
rtauto, 332	unlock, $462$
104400, 902	unshelve, 342
S	undiret 10, 612
set, 288	V
set, 200 set (ssreflect), 404	vm_cast_no_check, 344
setoid_reflexivity, 628	vm_compute, 315
_ · · · · · · · · · · · · · · · · · · ·	vm_compate, 919
setoid_replace, 629	W
setoid_rewrite, 629	
setoid_symmetry, 628	without loss, 441
setoid_transitivity, 628	wlog, 441
shelve, 341	Z
shelve_unifiable, 342	
show ltac profile, 373	$\mathtt{zify}, 595$

Tactic Index 661

| | (left-biased branching), 351

662 Tactic Index

# FLAGS, OPTIONS AND TABLES INDEX

a Allow StrictProp, $647$ Asymmetric Patterns, $558$ Auto Template Polymorphism, $218$	Extraction Optimize, 597 Extraction SafeImplicits, 598 Extraction TypeExpand, 601 f
b Boolean Equality Schemes, 518 Bracketing Last Introduction Pattern, 271 Bullet Behavior, 264  C Case Analysis Schemes, 518 Congruence Verbose, 334 Contextual Implicit, 176 Coqtop Exit On Error, 526 Cumulativity Weak Constraints, 641	Fast Name Printing, 243 Firstorder Depth, 332 Firstorder Solver, 332  g Guard Checking, 251  h Hide Obligations, 609 Hyps Limit, 267
Debug Auto, 322 Debug Cbv, 316 Debug Eauto, 323 Debug RAKAM, 318 Debug Ssreflect, 490 Debug SsrMatching, 490 Debug Tactic Unification, 283 Debug Trivial, 322 Debug Unification, 278 Decidable Equality Schemes, 518 Default Goal Selector, 268 Default Proof Mode, 256 Default Proof Using, 255 Default Timeout, 248	Implicit Arguments, 175 Info Auto, 322 Info Eauto, 323 Info Level, 371 Info Trivial, 322 Intuition Negation Unfolding, 332  k Keep Proof Equalities, 303 Keyed Unification, 312  Lia Cache, 592 Loose Hint Behavior, 329  Lace Packtrone 270
Diffs, 266  e Elaboration StrictProp Cumulativity, 649 Elimination Schemes, 518 Extraction AutoInline, 597 Extraction Conservative Types, 597 Extraction File Comment, 601 Extraction Flag, 601 Extraction KeepSingleton, 597	Ltac Backtrace, 370 Ltac Batch Debug, 371 Ltac Debug, 371 Ltac Profiling, 372 Ltac2 Backtrace, 387  m  Mangle Names, 343 Mangle Names Prefix, 343 Maximal Implicit Insertion, 176

n	S
NativeCompute Profile Filename, 316	Search Blacklist, 242
NativeCompute Profiling, 315	Search Output Name Only, 248
Nested Proofs Allowed, 267	Short Module Printing, 167
Nia Cache, 592	Shrink Obligations, 609
Nonrecursive Elimination Schemes, 518	Silent, 248
Nra Cache, 592	Simplex, 592
,	Solve Unification Constraints, 342
0	SsrHave NoTCResolution, 440
Omega Action, 591	SsrIdents, 399
Omega System, 591	SsrOldRewriteGoalsOrder, 446
Omega UseLocalDefs, 591	SsrRewrite, 399
,	Stable Omega, 591
p	Strict Implicit, 176
Parsing Explicit, 178	Strict Universe Declaration, 644
Polymorphic Inductive Cumulativity, 640	Strongly Strict Implicit, 176
Positivity Checking, 251	Structural Injection, 303
Primitive Projections, 150	Suggest Proof Using, 255
Printing All, 183	-
Printing Allow Match Default Clause, 154	t
Printing Coercion, 566	Template Check, 218
Printing Coercions, 566	Transparent Obligations, 609
Printing Compact Contexts, 248	Typeclass Resolution For Conversion, 587
Printing Constructor, 149	Typeclasses Axioms Are Instances, 588
Printing Dependent Evars Line, 248	Typeclasses Debug, 588
Printing Depth, 248	Typeclasses Debug Verbosity, 588
Printing Existential Instances, 184	Typeclasses Dependency Order, 587
Printing Factorizable Match Patterns, 154	Typeclasses Depth, 588
Printing If, 155	Typeclasses Filtered Unification, 587
Printing Implicit, 177	Typeclasses Iterative Deepening, 588
Printing Implicit Defensive, 177	Typeclasses Limit Intros, 587
Printing Let, 155	Typeclasses Strict Resolution, 588
Printing Matching, 154	Typeclasses Unique Instances, 588
Printing Notations, 497	Typeclasses Unique Solutions, $588$
Printing Primitive Projection Parameters,	
151	u
Printing Projections, 149	Uniform Inductive Parameters, $137$
Printing Record, 149	Universal Lemma Under Conjunction, 281
Printing Records, 148	Universe Checking, $251$
Printing Synth, 154	Universe Minimization ToSet, 642
Printing Unfocused, 248	Universe Polymorphism, 639
Printing Universes, 183	
Printing Width, 248	W
Printing Wildcard, 154	Warnings, 248
Private Polymorphic Universes, 644	
Program Cases, 606	
Program Generalized Coercion, $606$	
Program Mode, 606	
r	
Regular Subst Tactic, 313	
Reversible Pattern Implicit, 176	
Rewriting Schemes, 518	
· · · · · · · · · · · · · · · · · · ·	

## **ERRORS AND WARNINGS INDEX**

Q	Cannot find inversion information for
@ident already exists. (Axiom), 132	hypothesis 'ident', $336$
Cident already exists. (Definition), 133	Cannot find library foo in loadpath, $244$
@ident already exists. (Let), 160	Cannot find the source class of 'qualid',
@ident already exists. (Program Definition),	565
607	Cannot handle mutually (co)inductive
Oident already exists. (Theorem), 144	records, $150$ Cannot infer a term for this placeholder.
@ident already exists. (Variable), $159$	(Casual use of implicit arguments),
a	171
Argument number 'num' is a trailing	Cannot infer a term for this placeholder.
implicit so must be maximal, 174	(refine), 277
Argument of match does not evaluate to a	Cannot interpret in 'scope' because 'ident'
term, 358	could not be found in the current
Arguments of ring_simplify do not have all	environment, $512$ Cannot interpret this number as a value of
the same type, 612	type 'type', 512
Attempt to save an incomplete proof, $254$ Automatically declaring 'ident' as template	Cannot interpret this string as a value of
polymorphic, 218	type'type', 514
polymorphio, 210	Cannot load qualid: no physical path bound
b	to dirpath, 244
Bad lemma for decidability of equality, 615	Cannot move 'ident' after 'ident': it
Bad magic number, 245	depends on 'ident', 286 Cannot move 'ident' after 'ident': it
Bad occurrence number of 'qualid', 319	occurs in the type of 'ident', 286
Bad relevance, 650	Cannot recognize a boolean equality, 337
Bad ring structure, 615	Cannot recognize 'class' as a source class
Brackets do not support multi-goal selectors, 259	of 'qualid', $565$
50100015, 200	Cannot solve the goal, 353
С	Cannot use mutual definition with
Cannot build functional inversion principle,	well-founded recursion or measure, 157
157	Can't find file 'ident' on loadpath, 244
Cannot coerce 'qualid' to an evaluable	Compiled library 'ident'.vo makes
reference, 318	inconsistent assumptions over
Cannot define graph for 'ident', 157 Cannot define principle(s) for 'ident', 157	library qualid, $245$
Cannot find a declared ring structure for	Condition not satisfied, $362$
equality 'term', 612	d
Cannot find a declared ring structure over 'term', 612	Debug mode not available in the IDE, $371$
Cannot find induction information on	е
'qualid', $301$	Either there is a type incompatibility or

the problem involves dependencies,	No applicable tactic, $351$
563	No argument name 'ident', $157$
r	No discriminable equalities, $301$
f	No evars, $335$
Failed to progress, $350$	No focused proof, $253$
File not found on loadpath: 'string', $245$	No focused proof (No proof-editing in
Files processed by Load cannot leave open	progress), 254
proofs, 244	No focused proof to restart, $257$
Found target class instead of, $565$	No head constant to reduce, 316
Funclass cannot be a source class, $565$	No matching clauses for match, 358
ď	No matching clauses for match goal, 360
g	No primitive equality found, 301
goal does not satisfy the expected	No product even after head-reduction, 283
preconditions, 303	No progress made, 632
Goal is solvable by congruence but	No such assumption, 276
some arguments are missing. Try	No such binder, 269
congruence with 'term''term',	No such goal, 264
replacing metavariables by arbitrary	No such goal ('ident'), 259
terms, 334	No such goal ('num'), 259 No such goal. (fail), 354
h	No such goal. (Goal selector), 350
	No such goal. Focus next goal with bullet
Hypothesis 'ident' must contain at least	'bullet', 263
one Function, 336	No such hypothesis, 285
i	No such hypothesis in current goal, 284
	No such hypothesis: 'ident', 284
I don't know how to handle dependent	No such label 'ident', 161
equality, 334 Ignored instance declaration for "'ident'":	Non exhaustive pattern matching, 563
"'term'" is not a class, 584	Non strictly positive occurrence of 'ident'
Ill-formed recursive definition, 609	in 'type', 134
In environment the term: 'term' does not	Not a context variable, 360
have type 'type'. Actually, it has	Not a discriminable equality, 301
type, 607	Not a primitive equality, 302
Incorrect number of tactics (expected N	Not a projectable equality but a
tactics, was given M), 458	discriminable one, 302
Inductive 'ident' cannot be made template	Not a proposition or a type, 289
polymorphic, 218	Not a valid ring equation, $612$
Invalid argument, 277	Not a variable or hypothesis, $335$
Invalid backtrack, 247	Not an evar, $335$
	Not an exact proof, 276
	Not an inductive goal with 1 constructor,
Load is not supported inside proofs, 244	283
Loading of ML object file forbidden in a	Not an inductive goal with 2 constructors,
native Coq, 245	283
-	Not an inductive product, $282$
m	Not convertible, 313
Module/section 'qualid' not found, 240	Not enough constructors, 282
-	Not equal, 334
n	Not equal (due to universes), 334
Nested proofs are not allowed unless you	Not reducible, 316
turn the Nested Proofs Allowed flag	Not the right number of induction arguments
on, 144	301
New coercion path $\dots$ is ambiguous with existing $\dots, 565$	Not the right number of missing arguments, 269

Notation 'string' is deprecated since	t
'string'. 'string', $146$	Tactic Failure message (level 'num'), 354
Nothing to do, it is an equality between	Tactic generated a subgoal identical to
convertible terms, $302$	the original goal. This happens if
Nothing to inject, $303$	'term' does not occur in the goal,
Nothing to rewrite, 632	311
,	Tactic Notation 'qualid' is deprecated
0	since 'string'. 'string', 146
omega can't solve this system, 590	
omega: Can't solve a goal with equality on	Tactic 'qualid' is deprecated since
	'string'. 'string', 146
type, 590	Terms do not have convertible types, 312
omega: Can't solve a goal with non-linear	The 'abstract after' directive has no
products, 590	effect when the parsing function
omega: Can't solve a goal with proposition	('ident') targets an option type, $513$
variables, 590	The command has not failed!, $248$
omega: Not a quantifier-free goal, $590$	The conclusion is not a substitutive
omega: Unrecognized atomic proposition:	equation, $335$
$\dots$ , 590	The conclusion of 'type' is not valid; it
omega: Unrecognized predicate or	must be built from 'ident', $134$
connective: 'ident', $590$	The constant 'numeral' is not a
omega: Unrecognized proposition, $590$	binary64 floating-point value. A
	closest value will be used and
p	unambiguously printed 'numeral'.
Proof is not complete. (abstract), $363$	[inexact-float,parsing], 201
Proof is not complete. (assert), 290	The constructor 'ident' expects 'num'
1	arguments, 563
r	The elimination predicate term should be of
Records declared with the keyword Record or	arity 'num' (for non dependent case)
Structure cannot be recursive, 150	or 'num' (for dependent case), 563
Refine passed ill-formed term, 277	The file :n: 'ident'.vo' contains library
Require is not allowed inside a module or a	·
	dirpath and not library dirpath', 245
module type, 245	The recursive argument must be specified,
Ring operation should be declared as a	157
morphism, 615	The reference is not unfoldable, 250
S	The reference X was not found in the
	current environment, 390
Signature components for label 'ident' do	The reference 'ident' was not found in the
$\mathtt{not}\ \mathtt{match},161$	$\verb current  environment , 513$
SProp not allowed, you need to Set	The reference 'qualid' was not found in the
Allow StrictProp or to use the	current environment, $238$
-allow-sprop command-line-flag, $647$	The term 'term' has type 'type' which
Stack overflow or segmentation fault	should be Set, Prop or Type, $144$
happens when working with large	The term 'term' has type 'type' while it is
numbers in 'type' (threshold may	expected to have type 'type', $133$
vary depending on your system limits	The variable 'ident' is already defined, 288
and on the command executed), $513$	The 'num' th argument of 'ident' must be
Statement without assumptions, 281	'ident' in 'type', 138
Syntax error: [prim:reference]	The 'term' provided does not end with an
expected after 'Notation' (in	equation, 311
[vernac:command]), 513	This is not the last opened module, 161
Syntax error: [prim:reference] expected	This is not the last opened module type, 162
after [prim:reference] (in	This is not the last opened section, 159
[vernac:command]), 513	This object does not support universe names
[vermac.command]), 010	236

```
This proof is focused, but cannot be
                                                       enable skipping this proof which is
       unfocused this way, 259
                                                      located inside a section. Give as
                                                      argument to "Proof using" the list
This tactic has more than one success, 352
To avoid stack overflow, large numbers
                                                      of section variables that are not
       in 'type' are interpreted as
                                                      needed to typecheck the statement
       applications of 'ident', 513
                                                      but that are required by the proof,
Too few occurrences, 314
Trying to mask the absolute name 'qualid'!,
                                               'class' must be a transparent constant, 566
                                               'ident' cannot be defined, 150
Unable to apply, 281
                                               'ident' is already declared as a typeclass,
Unable to find an instance for the
       variables 'ident'...'ident', 278
                                               'ident' is already used, 283
Unable to infer a match predicate, 563
                                               'ident' is bound to a notation that does not
Unable to satisfy the rewriting constraints,
                                                       denote a reference, 513
                                               'ident' is declared as a local axiom
Unable to unify ... with ..., 335
                                                       [local-declaration, scope], 133
Unable to unify 'term' with 'term', 278
                                               'ident' is declared as a local definition
Unbound [value|constructor] X, 389
                                                       [local-declaration, scope], 133
Unbound context identifier 'ident', 360
                                               'ident' is not a local definition, 285
Undeclared universe 'ident', 642
                                               'ident' is used in conclusion, 291
Unexpected non-option term 'term' while
                                               'ident' is used in hypothesis 'ident', 291
       parsing a numeral notation, 512
                                               'ident' is used in the conclusion, 285
Unexpected non-option term 'term' while
                                               'ident' is used in the hypothesis 'ident',
       parsing a string notation, 514
Unexpected term 'term' while parsing a
                                               'ident' should go from Byte.byte or (list
       numeral notation, 512
                                                      Byte.byte) to 'type' or (option
Unexpected term 'term' while parsing a
                                                       'type'), 514
       string notation, 514
                                               'ident' should go from Decimal.int to 'type'
Universe inconsistency, 643
                                                       or (option 'type'). Instead of
Universe instance should have length 'num',
                                                       Decimal.int, the types Decimal.uint
                                                       or Z or Int63.int or Decimal.decimal
Unknown inductive type, 265
                                                       could be used (you may need to
Unsupported attribute, 147
                                                       require BinNums or Decimal or Int63
Use of 'string' Notation is deprecated as
                                                       first), 512
       it is inconsistent with pattern
                                               'ident' should go from 'type' to Byte.byte
       syntax, 505
                                                       or (option Byte.byte) or (list
                                                       Byte.byte) or (option (list
                                                      Byte.byte)), 514
Variable 'ident' is already declared, 290
                                               'ident' should go from 'type' to Decimal.int
                                                       or (option Decimal.int). Instead of
W
                                                       Decimal.int, the types Decimal.uint
When 'term' contains more than one non
                                                       or Z or Int63.int or Decimal.decimal
       dependent product the tactic lapply
                                                       could be used (you may need to
       only takes into account the first
                                                       require BinNums or Decimal or Int63
       product, 279
                                                       first), 512
Wrong bullet 'bullet': Bullet 'bullet' is
                                               'ident': no such entry, 246
       mandatory here, 263
                                               'qualid' does not occur, 319
Wrong bullet 'bullet': Current bullet
                                               'qualid' does not respect the uniform
       'bullet' is not finished, 263
                                                       inheritance condition, 565
                                               'qualid' is already a coercion, 565
                                               'qualid' is not a function, 565
You should use the "Proof using [...]."
                                               'qualid' is not a module, 167
       syntax instead of "Proof." to
```

```
'qualid' is not an inductive type, 326 'qualid' not a defined object, 236 'qualid' not declared, 565 'term' cannot be used as a hint, 325 'type' is not an inductive type, 512
```

## **INDEX**

Symbols	Abort (cmd), $254$
* (term), 191, 196	About (cmd), 236
+ (backtracking branching) (tacn), 351	abstract (ssreflect) (tacn), 419
+ (term), 191, 196	abstract (tacn), 362
- (term), 196	absurd (tacn), 292
: (goal selector) (tacn), 349	absurd (term), 190
: (ssreflect) (tacn), 416	absurd_set (term), 192
: (type cast), 128	Acc (term), 194
<:, 128	Acc_inv (term), 194
<<:, 128	Acc_rect (term), 194
:> (coercion), 567	Add @table (cmd), 237
:> (substructure), 584	Add Field (cmd), 619
=> (tacn), 419	Add LoadPath (cmd), 246
?= (term), 196	Add ML Path (cmd), 246
@ident already exists. (Axiom) (err), 132	Add Morphism (cmd), 629
@ident already exists. (Definition) (err), 133	Add Parametric Morphism (cmd), 624
@ident already exists. (Let) (err), 160	Add Parametric Relation (cmd), 624
@ident already exists. (Program Definition) (err),	Add Rec LoadPath (cmd), 246
607	Add Rec ML Path (cmd), 246
@ident already exists. (Theorem) (err), 144	Add Relation (cmd), 624
@ident already exists. (Variable) (err), 159	Add Ring (cmd), 614
	Add Setoid (cmd), 629
	admit (tacn), 292
}, 257	Admit Obligations (cmd), 609
(left-biased branching) (tacn), 351	Admitted (cmd), 254
> (term), 196	all (term), 189
>= (term), 196	all: (tacnv), 349
< (term), 196	Allow StrictProp (flag), 647
<= (term), 196	and (term), 189
[>     (dispatch) (tacn), 349	and_rect (term), 192
$\{A\}+\{B\} \text{ (term)}, 192$	app (term), 199
{x:A & P x} (term), 191	apply (ssreflect) (tacn), 415
{x:A   P x} (term), 191	apply (tacn), 278
'( ), 181	apply in (tacn), 281
(!), 181	apply in as (tacnv), 282
`{ }, 181	Argument number 'num' is a trailing implicit so must
`{!}, 181	be maximal (warn), 174
( ),	Argument of match does not evaluate to a term (err),
A	358
A*B (term), 191	Arguments (assert) (cmd), 177
A+B (term), 191 A+B (term), 191	Arguments (bidirectionality hints) (cmd), 186
A+{B} (term), 191 A+{B} (term), 192	Arguments (clear implicits) (cmd), 172
$A+\{D\}$ (will), 192	

Arguments (default implicits) (cmd), 174	Cannot find induction information on 'qualid' (err)
Arguments (implicits) (cmd), 172	301
Arguments (rename) (cmd), 177	Cannot find inversion information for hypothesis
Arguments (scopes) (cmd), 507	'ident' (err), 336
Arguments of ring_simplify do not have all the same	Cannot find library foo in loadpath (err), 244
type (err), 612	Cannot find the source class of 'qualid' (err), 565
Arithmetical notations, 196	Cannot handle mutually (co)inductive records (err),
assert (tacn), 289	150
assert_fails (tacn), 352	Cannot infer a term for this placeholder. (Casual use
assert_succeeds (tacn), 352	of implicit arguments) (err), 171
assumption (tacn), 276	Cannot infer a term for this placeholder. (refine)
Asymmetric Patterns (flag), 558	(err), 277
Attempt to save an incomplete proof (err), 254	Cannot interpret in 'scope' because 'ident' could not
auto (tacn), 321	be found in the current environment (err),
Auto Template Polymorphism (flag), 218	512, 514
autoapply (tacn), 586	Cannot interpret this number as a value of type 'type'
Automatically declaring 'ident' as template polymor-	(err), 512
phic (warn), 218	Cannot interpret this string as a value of type 'type'
autorewrite (tacn), 323	(err), 514
autounfold (tacn), 323	Cannot load qualid: no physical path bound to
Axiom (cmdv), 132	dirpath (err), 244
Axioms (cmdv), 132	Cannot move 'ident' after 'ident': it depends on
В	'ident' (err), 286
	Cannot move 'ident' after 'ident': it occurs in the
Back (cmd), 247	type of 'ident' (err), 286
BackTo (cmd), 247	Cannot recognize a boolean equality (err), 337
Bad lemma for decidability of equality (err), 615	Cannot recognize 'class' as a source class of 'qualid'
Bad magic number (err), 245	(err), 565
Bad occurrence number of 'qualid' (err), 319	Cannot solve the goal (err), 353
Bad relevance (warn), 650	Cannot use mutual definition with well-founded re-
Bad ring structure (err), 615	cursion or measure (err), 157
Bind Scope (cmd), 508	Canonical (cmd), 178
bool (term), 190	Can't find file 'ident' on loadpath (err), 244
bool_choice (term), 192	case (ssreflect) (tacn), 414
Boolean Equality Schemes (flag), 518	case (tacn), 294
Bracketing Last Introduction Pattern (flag), 271	Case Analysis Schemes (flag), 518
Brackets do not support multi-goal selectors (err),	cbn (tacn), 316
259	cbv (tacn), 314
btauto (tacn), 337	Cd (cmd), 245
Bullet Behavior (opt), 264	change (tacn), 313
by (tacn), 428	change_no_check (tacn), 343
<i>C</i>	Check (cmd), 238
C	Choice (term), 192
Cannot build functional inversion principle (warn),	Choice2 (term), 192
157	Class (cmd), 585
Cannot coerce 'qualid' to an evaluable reference (err),	classical_left (tacn), 337 classical_right (tacn), 337
318	clear (tacn), 285
Cannot define graph for 'ident' (warn), 157	clear (tach), 285 clearbody (tachy), 285
Cannot define principle(s) for 'ident' (warn), 157	
Cannot find a declared ring structure for equality	Close Scope (cmd), 506
'term' (err), 612	Coercion (cmd), 565
Cannot find a declared ring structure over 'term'	cofix, 130
(err), 612	cofix (tacn), 310 CoFixpoint (cmd), 143
	COLIMPOLII (CHIU), 140

CoInductive (cmd), 139 Collection (cmd), 256 Combined Scheme (cmd), 518 compare (tacn), 335 Compiled library 'ident'.vo makes inconsistent assumptions over library qualid (err), 245 Compute (cmd), 238 compute (tacnv), 315 Condition not satisfied (err), 362 congr (tacn), 463 congruence (tacn), 332 Congruence Verbose (flag), 334 congruence with (tacnv), 334 conj (term), 189 Conjecture (cmdv), 132 Conjectures (cmdv), 132 Connectives, 189 constr_eq_(tacn), 334 constr_eq_strict (tacn), 334 Constraint (cmd), 642 constructor (tacn), 282 Context (cmd), 160 Contextual Implicit (flag), 176 contradict (tacn), 293 contradiction (tacn), 293 convert_concl_no_check (tacnv), 344 Coqtop Exit On Error (flag), 526 Corollary (cmdv), 144 Create HintDb (cmd), 324 Cumulative (cmd), 639 Cumulativity Weak Constraints (flag), 641 cut (tacnv), 291 cutrewrite (tacnv), 312	Declare ML Module (cmd), 245 Declare Module (cmd), 162 Declare Morphism (cmd), 629 Declare Reduction (cmd), 250 Declare Right Step (cmd), 313 Declare Scope (cmd), 505 decompose (tacn), 288 Default Goal Selector (opt), 268 Default Proof Mode (opt), 256 Default Proof Using (opt), 255 Default Timeout (opt), 248 Defined (cmdv), 254 Definition (cmd), 133 Delimit Scope (cmd), 506 dependent destruction (tacnv), 299 dependent induction (tacn), 298 dependent inversion with (tacnv), 305 dependent rewrite -> (tacn), 336 Derive (cmd), 636 Derive Inversion (cmd), 524 destruct (tacn), 293 destruct eqn: (tacnv), 294 Diffs (opt), 266 dintuition (tacnv), 332 discriminate (tacn), 301 discrR (tacn), 198 do (ssreflect) (tacn), 431 do (tacn), 350 done (tacn), 428 double induction (tacn), 298 Drop (cmd), 247
cycle (tacn), 339	dtauto (tacnv), 331
Datatypes, 190 Debug Auto (flag), 322 debug auto (tacnv), 322 Debug Cbv (flag), 316 Debug Eauto (flag), 323 Debug mode not available in the IDE (err), 371 Debug RAKAM (flag), 318 Debug Ssreflect (flag), 490 Debug SsrMatching (flag), 490 Debug Tactic Unification (flag), 283 Debug Trivial (flag), 322 debug trivial (tacnv), 322 Debug Unification (flag), 278 Decidable Equality Schemes (flag), 518 decide equality (tacn), 335 Declare Custom Entry (cmd), 501 Declare Instance (cmdv), 585	eapply (tacnv), 278 eassert (tacnv), 290 eassumption (tacnv), 276 easy (tacn), 324 eauto (tacn), 323 ecase (tacnv), 294 econstructor (tacnv), 283 edestruct (tacnv), 294 ediscriminate (tacnv), 301 eelim (tacnv), 297 eenough (tacnv), 290 eexact (tacnv), 276 eexists (tacnv), 283 einduction (tacnv), 296 einjection (tacnv), 303 eintros (tacn), 284 Either there is a type incompatibility or the problem
Declare Left Step (cmd), 313	involves dependencies (err), 563

Elaboration StrictProp Cumulativity (flag), 649	Extraction (cmd), 596
eleft (tacny), 283	Extraction AutoInline (flag), 597
elim (ssreflect) (tacn), 415	Extraction Blacklist (cmd), 600
elim (tacny), 297	Extraction Conservative Types (flag), 597
elim with (tacnv), 297	Extraction File Comment (opt), 601
Elimination Schemes (flag), 518	Extraction Flag (opt), 601
elimtype (tacnv), 298	Extraction Implicit (cmd), 598
End (cmd), 159, 161, 162	Extraction Inline (cmd), 597
enough (tacnv), 290	Extraction KeepSingleton (flag), 597
epose (tacny), 288	Extraction Language (cmd), 597
epose proof (tacnv), 290	Extraction Library (cmd), 596
eq (term), 189	Extraction NoInline (cmd), 597
eq_add_S (term), 193	Extraction Optimize (flag), 597
eq_ind_r (term), 190	Extraction SafeImplicits (flag), 598
eq_rec_r (term), 190	Extraction TestCompile (cmd), 596
eq_rect (term), 190, 192	Extraction TypeExpand (flag), 601
eq_rect_r (term), 190	г
eq_refl (term), 189	F
eq_S (term), 193	f_equal (tacn), 335
eq_sym (term), 190	f_equal (term), 190
eq_trans (term), 190	f_equal2 f_equal5 (term), 190
Equality, 189	Fact (cmdv), 144
eremember (tacnv), 288	Fail (cmd), 248
erewrite (tacny), 312	fail (tacn), 353
eright (tacnv), 283	Failed to progress (err), 350
error (term), 192	False (term), 189
eset (tacnv), 288	false (term), 190
esimplify_eq (tacnv), 336	False_rec (term), 192
esplit (tacnv), 283	False_rect (term), 192
Eval (cmd), 238	Fast Name Printing (flag), 243
evar (tacn), 292	field (tacn), 338
ex (term), 189	field_simplify (tacn), 338
ex2 (term), 189	field_simplify_eq (tacn), 338
ex_intro (term), 189	File not found on loadpath: 'string' (err), 245
ex_intro2 (term), 189	Files processed by Load cannot leave open proofs
exact (tacn), 276	(err), 244
exact_no_check (tacn), 344	finish_timing (tacn), 357
exactly_once (tacn), 352	first (ssreflect) (tacn), 429
Example (cmdv), 133	first (tacn), 351
Exc (term), 192	first last (tacny), 430
exfalso (tacn), 293	firstorder (tacn), 332
exist (term), 191	Firstorder Depth (opt), 332
exist2 (term), 191	Firstorder Solver (opt), 332
Existential (cmd), 256	fix, 130
Existing Instance (cmd), 586	fix (tacn), 310
exists (tacnv), 282	fix_eq (term), 194
exists (term), 189	Fix_F (term), 194
exists2 (term), 189	Fix_F_eq (term), 194
existT (term), 191	Fix_F_inv (term), 194
existT2 (term), 191	Fix_r_mv (term), 194 Fixpoint (cmd), 141
Export (cmdv), 167	flat_map (term), 199
Extract Constant (cmd), 599	Focus (cmd), 257
Extract Inductive (cmd), 599	fold (tacn), 319
Extract Inlined Constant (cmd), 599	fold_left (term), 199
( )	1014_1010 (001111), 100

fold_right (term), 199	Hint Opaque (cmdv), 326
forall, 128	Hint Resolve (cmdv), 325
Found target class instead of (err), 565	Hint Rewrite (cmd), 329
From Require (cmdv), 244	Hint Transparent (cmdv), 326
fst (term), 191	Hint Unfold (cmdv), 326
fun =>, 128	Hint Variables (cmdv), 326
Funclass cannot be a source class (err), 565	Hint View for (cmd), 490
Function (cmd), 156	Hint View for apply (cmd), 484, 490
function induction (tacn), 299	Hint View for move (cmd), 484
function_scope, 509	hnf (tacn), 316
functional inversion (tacn), 336	Hypotheses (cmdv), 160
Functional Scheme (cmd), 519	Hypotheses (outside a section) (cmdv), 132
	Hypothesis (cmdv), 160
G	Hypothesis (outside a section) (cmdv), 132
ge (term), 193	Hypothesis 'ident' must contain at least one Function
Generalizable (cmd), 182	(err), 336
Generalizable All Variables (cmd), 182	Hyps Limit (opt), 267
Generalizable No Variables (cmd), 182	
generalize (tacn), 291	
generally have (tacn), 489	I (term), 189
gfail (tacnv), 353	I don't know how to handle dependent equality (err).
give_up (tacn), 342	334
Global (cmd), 250	identity (term), 190, 194
Global Close Scope (cmd), 506	Identity Coercion (cmd), 566
Global Generalizable (cmd), 182	idtac (tacn), 353
Global Instance (cmdv), 585	IF_then_else (term), 189
Global Opaque (cmdv), 249	iff (term), 189
Global Open Scope (cmd), 506	Ignored instance declaration for "ident'": "'term'" is
Global Transparent (cmdv), 249	not a class (warn), 584
Goal (cmd), 253	Ill-formed recursive definition (err), 609
goal does not satisfy the expected preconditions (err),	Implicit Arguments (flag), 175
303	
	Implicit Types (cmd), 180
Goal is solvable by congruence but some argu-	Import (cmd), 166 in (tacn), 431
ments are missing. Try congruence with 'term''term', replacing metavariables by ar-	
bitrary terms (err), 334	In environment the term: 'term' does not have type
Grab Existential Variables (cmd), 256	'type'. Actually, it has type (err), 607
\ //	Include (cmd), 161, 162
gt (term), 193	Incorrect number of tactics (expected N tactics, was
guard (tacn), 362	given M) (err), 458
Guard Checking (flag), 251	induction (tacn), 295
Guarded (cmd), 265	induction using (tacnv), 296
Н	Inductive (cmd), 134
	Inductive 'ident' cannot be made template polymor-
has_evar (tacn), 335	phic (err), 218
have (tacn), 433	Infix (cmd), 496
head (term), 199	Info (cmd), 370
Hide Obligations (flag), 609	Info Auto (flag), 322
Hint (cmd), 325	Info Eauto (flag), 323
Hint Constants (cmdv), 326	Info Level (opt), 371
Hint Constructors (cmdv), 326	Info Trivial (flag), 322
Hint Cut (cmdv), 327	info_trivial (tacny), 322
Hint Extern (cmdv), 326	injection (tacn), 301
Hint Immediate (cmdv), 325	inl (term), 191
Hint Mode (cmdv), 327	inleft (term), 192

Inline (cmd), $162$	Local Open Scope (cmd), 506
inr (term), 191	Local Parameter (cmdv), 132
inright (term), 192	Locate (cmd), 242
Inspect (cmdv), 236	Locate File (cmd), 246
Instance (cmd), 585	Locate Library (cmd), 246
instantiate (tacn), 292	Loose Hint Behavior (opt), 329
intro (tacn), 283	lra (tacn), 593
intros (tacnv), 284	lt (term), 193
intros (tacn), 284	Ltac (cmd), 363
intuition (tacn), 331	Ltac Backtrace (flag), 370
Intuition Negation Unfolding (flag), 332	Ltac Batch Debug (flag), 371
Invalid argument (err), 277	Ltac Debug (flag), 371
Invalid backtrack (err), 247	Ltac Profiling (flag), 372
inversion (tacn), 304	ltac-seq (tacn), 348
inversion using (tacnv), 306	Ltac2 (cmd), 377
inversion_clear (tacnv), 304	Ltac2 Backtrace (flag), 387
inversion_sigma (tacny), 306	Ltac2 Eval (cmd), 386
is_evar (tacn), 335	Ltac2 Notation (cmd), 386
is_var (tach), 335	
	Ltac2 Set (cmd), 377
IsSucc (term), 193	Ltac2 Type (cmd), 376
K	M
Keep Proof Equalities (flag), 303	Mangle Names (flag), 343
Keyed Unification (flag), 312	Mangle Names Prefix (opt), 343
1	map (term), 199
L	match with, 129
lapply (tacnv), 279	match goal (tacn), 359
last (tacn), 429	Maximal Implicit Insertion (flag), 176
last first (tacnv), 430	mod (term), 196
lazy (tacn), 314	Module (cmd), 161
le (term), 193	Module Type (cmd), 162
le_n (term), 193	Module/section 'qualid' not found (err), 240
le_S (term), 193	Monomorphic (cmd), 639
left (tacny), 283	move (tacn), 414
left (term), 192	move after (tacn), 285
Lemma (cmdv), 144	move at bottom (tacnv), 286
length (term), 199	move at top (tacnv), 286
Let (cmd), 160	move before (tacnv), 285
Let (outside a section) (cmdv), 133	mult (term), 193
let := (tacn), 357	mult_n_O (term), 193
let := (term), 129	mult_n_Sm (term), 193
Let CoFixpoint (cmdv), 160	, , , , , , , , , , , , , , , , , , ,
Let Fixpoint (cmdv), 160	N
lia (tacn), 593	n_Sn (term), 193
Lia Cache (flag), 592	nat (term), 190
	1120 (001111), 190
Load (cmd) 243	
Load (cmd), 243 Load is not supported inside proofs (err.) 244	nat_case (term), 193
Load is not supported inside proofs (err), 244	nat_case (term), 193 nat_double_ind (term), 193
Load is not supported inside proofs (err), 244 Loading of ML object file forbidden in a native Coq	nat_case (term), 193 nat_double_ind (term), 193 nat_scope, 196
Load is not supported inside proofs (err), 244 Loading of ML object file forbidden in a native Coq (err), 245	nat_case (term), 193 nat_double_ind (term), 193 nat_scope, 196 native_cast_no_check (tacnv), 345
Load is not supported inside proofs (err), 244 Loading of ML object file forbidden in a native Coq (err), 245 Local (cmd), 250	nat_case (term), 193 nat_double_ind (term), 193 nat_scope, 196 native_cast_no_check (tacnv), 345 native_compute (tacnv), 315
Load is not supported inside proofs (err), 244 Loading of ML object file forbidden in a native Coq (err), 245 Local (cmd), 250 Local Close Scope (cmd), 506	nat_case (term), 193 nat_double_ind (term), 193 nat_scope, 196 native_cast_no_check (tacnv), 345 native_compute (tacnv), 315 NativeCompute Profile Filename (opt), 316
Load is not supported inside proofs (err), 244 Loading of ML object file forbidden in a native Coq	nat_case (term), 193 nat_double_ind (term), 193 nat_scope, 196 native_cast_no_check (tacnv), 345 native_compute (tacnv), 315 NativeCompute Profile Filename (opt), 316 NativeCompute Profiling (flag), 315
Load is not supported inside proofs (err), 244 Loading of ML object file forbidden in a native Coq	nat_case (term), 193 nat_double_ind (term), 193 nat_scope, 196 native_cast_no_check (tacnv), 345 native_compute (tacnv), 315 NativeCompute Profile Filename (opt), 316

Nested proofs are not allowed unless you turn the Nested Proofs Allowed flag on (err), 144	Not convertible (err), 313 Not enough constructors (err), 282
New coercion path $\dots$ is ambiguous with existing $\dots$	Not equal (due to universes) (err), 334
(warn), 565	Not equal (err), 334
Next Obligation (cmd), 608	Not reducible (err), 316
nia (tacn), 594	Not the right number of induction arguments (err),
Nia Cache (flag), 592	301
No applicable tactic (err), 351	Not the right number of missing arguments (err), 269,
No argument name 'ident' (err), 157	278
No discriminable equalities (err), 301	not_eq_S (term), 193
No evars (err), 335	Notation (cmd), 492
No focused proof (err), 253, 264	Notation 'string' is deprecated since 'string'. 'string'
No focused proof (No proof-editing in progress) (err),	(warn), 146
254	Notations for lists, 199
No focused proof to restart (err), 257	Nothing to do, it is an equality between convertible
No head constant to reduce (err), 316	terms (err), $302$
No matching clauses for match (err), 358	Nothing to inject (err), 303
No matching clauses for match goal (err), 360	Nothing to rewrite (err), 632
No primitive equality found (err), 301	notT (term), 195
No product even after head-reduction (err), 283	notypeclasses refine (tacnv), 278
No progress made (err), 632	now (tacnv), 324
No such assumption (err), 276, 293	nra (tacn), 594
No such binder (err), 269	Nra Cache (flag), 592
No such goal (err), 264	nsatz (tacn), 620
No such goal ('ident') (err), 259	nth (term), 199
No such goal ('num') (err), 259	Numeral Notation (cmd), 511
No such goal. (fail) (err), 354	· /·
No such goal. (Goal selector) (err), 350	0
No such goal. Focus next goal with bullet 'bullet'	O (term), 190
(err), 263	O_S (term), 193
No such hypothesis (err), 285–287	Obligation (cmd), 608
No such hypothesis in current goal (err), 284	Obligation Tactic (cmd), 608
No such hypothesis: 'ident' (err), 284, 321	Obligations (cmd), 608
No such label 'ident' (err), 161	omega (tacn), 337
Non exhaustive pattern matching (err), 563	Omega Action (flag), 591
Non strictly positive occurrence of 'ident' in 'type'	omega can't solve this system (err), 590
(err), 134	Omega System (flag), 591
NonCumulative (cmd), 639	Omega UseLocalDefs (flag), 591
None (term), 190	omega: Can't solve a goal with equality on type
Nonrecursive Elimination Schemes (flag), 518	(err), 590
not (term), 189	omega: Can't solve a goal with non-linear products
Not a context variable (err), 360	(err), 590
Not a discriminable equality (err), 301	omega: Can't solve a goal with proposition variables
Not a primitive equality (err), 302	(err), 590
Not a projectable equality but a discriminable one	omega: Not a quantifier-free goal (err), 590
(err), 302	omega: Unrecognized atomic proposition: (err),
Not a proposition or a type (err), 289	590
Not a valid ring equation (err), 612	omega: Unrecognized predicate or connective: 'ident'
Not a variable or hypothesis (err), 335	
Not an evar (err), 335	(err), 590
Not an exact proof (err), 276	omega: Unrecognized proposition (err), 590
Not an inductive goal with 1 constructor (err), 283	once (tacn), 352
Not an inductive goal with 2 constructors (err), 283	only: (tacnv), 349 Opaque (cmd), 249
Not an inductive groduct (err), 282, 296	Open Scope (cmd), 506
• ( )/ - /	open scope (ema), out

Optimize Heap (cmd), 267	Print Libraries (cmd), 245
Optimize Proof (cmd), 267	Print LoadPath (cmd), 246
optimize_heap (tacn), 374	Print Ltac (cmd), 364
option (term), 190	Print Ltac Signatures (cmd), 364
or (term), 189	Print ML Modules (cmd), 245
or_introl (term), 189	Print ML Path (cmd), 246
or_intror (term), 189	Print Module (cmd), 167
over (tacn), 459	Print Module Type (cmd), 167
5	Print Opaque Dependencies (cmdv), 238
P	Print Options (cmd), 237
pair (term), 191	Print Rewrite HintDb (cmd), 329
par: (tacnv), 350	Print Scope (cmdv), 510
Parameter (cmd), 132	Print Scopes (cmd), 510
Parameters (cmdv), 132	Print Strategy (cmd), 250
Parsing Explicit (flag), 178	Print Table @table (cmd), 237
pattern (tacn), 320	Print Tables (cmd), 237
Peano's arithmetic, 196	Print Term (cmdv), 236
plus (term), 193	Print Transparent Dependencies (cmdv), 238
plus_n_O (term), 193	Print Typing Flags (cmd), 251
plus_n_Sm (term), 193	Print Universes (cmd), 183
Polymorphic (cmd), 639	Print Universes Subgraph (cmdv), 183
Polymorphic Constraint (cmd), 642	Print Visibility (cmd), 510
Polymorphic Inductive Cumulativity (flag), 640	Printing All (flag), 183
Polymorphic Universe (cmd), 642	Printing Allow Match Default Clause (flag), 154
pose (ssreflect) (tacn), 403	Printing Coercion (table), 566
pose (tacn), 288	Printing Coercions (flag), 566
pose proof (tacnv), 290	Printing Compact Contexts (flag), 248
Positivity Checking (flag), 251	Printing Constructor (table), 149
pred (term), 193	Printing Dependent Evars Line (flag), 248
pred_Sn (term), 193	Printing Depth (opt), 248
Prenex Implicits (cmd), 402, 490	Printing Existential Instances (flag), 184
Preterm (cmd), 609	Printing Factorizable Match Patterns (flag), 154
Primitive (cmd), 253	Printing If (table), 155
Primitive Projections (flag), 150	Printing Implicit (flag), 177
Print (cmd), 236	Printing Implicit Defensive (flag), 177
Print All (cmd), 236	Printing Let (table), 155
Print All Dependencies (cmdv), 238	Printing Matching (flag), 154
Print Assumptions (cmd), 238	Printing Notations (flag), 497
Print Canonical Projections (cmd), 179	Printing Primitive Projection Parameters (flag), 151
Print Classes (cmd), 566	Printing Projections (flag), 149
Print Coercion Paths (cmd), 566	Printing Record (table), 149
Print Coercions (cmd), 566	Printing Records (flag), 148
Print Custom Grammar (cmd), 503	Printing Synth (flag), 154
Print Extraction Blacklist (cmd), 601	Printing Unfocused (flag), 248
Print Extraction Inline (cmd), 598	Printing Universes (flag), 183
Print Firstorder Solver (cmd), 332	Printing Width (opt), 248
Print Grammar constr (cmd), 494	Printing Wildcard (flag), 154
Print Grammar pattern (cmd), 494	Private Polymorphic Universes (flag), 644
Print Grammar tactic (cmd), 515	prod (term), 191
Print Graph (cmd), 566	Program Cases (flag), 606
Print Hint (cmd), 324, 328, 329	Program Definition (cmd), 606
Print HintDb (cmd), 329	Program Fixpoint (cmd), 607
Print Implicit (cmd), 177	Program Generalized Coercion (flag), 606
Print Instances (cmd), 629	Program Instance (cmdv), 585

Program Lemma (cmd), 608 Program Mode (flag), 606 Programming, 190 progress (tacn), 350 proj1 (term), 189 proj2 (term), 189 projT1 (term), 191 projT2 (term), 191 Proof (cmd), 254 Proof is not complete. (abstract) (err), 363 Proof is not complete. (assert) (err), 290 Proof voing (cmd), 255	Reset (cmd), 246 Reset Extraction Blacklist (cmd), 601 Reset Extraction Inline (cmd), 598 Reset Ltac Profile (cmd), 372 reset ltac profile (tacn), 373 Restart (cmdv), 257 restart_timer (tacn), 356 rev (term), 199 Reversible Pattern Implicit (flag), 176 revert (tacn), 285 revert dependent (tacnv), 285
Proof using (cmd), 255 Proof with (cmd), 330	revgoals (tacn), 341 rewrite (ssreflect) (tacn), 444
Proof 'term' (cmd), 254	rewrite (tacn), 310
Prop, 127	rewrite_strat (tacn), 632
Proposition (cmdv), 144	Rewriting Schemes (flag), 518
psatz (tacn), 595	right (tacnv), 283
Pwd (cmd), 245	right (term), 192
_	ring (tacn), 337
Q	Ring operation should be declared as a morphism
Qed (cmd), 254	(err), 615
Quantifiers, 189	ring_simplify (tacn), 337
Quit (cmd), 247	rtauto (tacn), 332
R	S
Record (cmd), 147	S (term), 190
Records declared with the keyword Record or Struc-	Save (cmdv), 254
ture cannot be recursive (err), 150	Scheme (cmd), 516
Recursion, 194	Scheme Equality (cmdv), 516
Recursive Extraction (cmd), 596	Search (cmd), 238
Recursive Extraction Library (cmd), 596	Search (ssreflect) (cmd), 486
red (tacn), 316	Search Blacklist (table), 242
Redirect (cmd), 247	Search Output Name Only (flag), 248
refine (tacn), 277	SearchAbout (cmdv), 239
Refine passed ill-formed term (err), 277	SearchHead (cmd), 240
refl_identity (term), 190	SearchPattern (cmd), 240
reflexivity (tacn), 335	SearchRewrite (cmd), 241
Register (cmd), 252	Section (cmd), 159
Register Inline (cmd), 253	Separate Extraction (cmd), 596
Regular Subst Tactic (flag), 313	Set (cmd), 237
Remark (cmdv), 144	Set (sort), 127
remember (tacn), 288	set (ssreflect) (tacn), 404
Remove @table (cmd), 237	set (tacn), 288
Remove Hints (cmd), 328	Set @option (cmd), 237
Remove LoadPath (cmd), 246	setoid_reflexivity (tacny), 628
rename (tacn), 287	setoid_replace (tacnv), 628
repeat (tacn), 350	setoid_rewrite (tacny), 628
replace (tacn), 312	setoid_symmetry (tacny), 628
Require (cmd), 244	setoid_transitivity (tacnv), 628
Require Export (cmdv), 244	shelve (tacn), 341
Require Import (cmdv), 244	shelve_unifiable (tacny), 342 Short Module Printing (flag), 167
Require is not allowed inside a module or a module	Short Module Printing (flag), 167
type (err), 245	Show (cmd), 264 Show Conjectures (cmdv), 265
Reserved Notation (cmd), 496	bhow Conjectures (Chiav), 200

Show Existentials (cmdv), 265	Stack overflow or segmentation fault happens when
Show Goal (cmdv), 265	working with large numbers in 'type'
Show Intro (cmdv), 265	(threshold may vary depending on your sys-
Show Intros (cmdv), 265	tem limits and on the command executed)
Show Ltac Profile (cmd), 372	(warn), 513
show ltac profile (tacn), 373	start ltac profiling (tacn), 373
Show Obligation Tactic (cmd), 608	Statement without assumptions (err), 281
Show Proof (cmdv), 264	stepl (tacn), 313
Show Universes (cmdv), 265	stepr (tacnv), 313
Show Zify BinOp (cmd), 595	stop ltac profiling (tacn), 373
Show Zify BinRel (cmd), 595	Strategy (cmd), 249
Show Zify CstOp (cmd), 595	Strict Implicit (flag), 176
Show Zify InjTyp (cmd), 595	Strict Universe Declaration (flag), 644
Show Zify Spec (cmd), 595	String Notation (cmd), 513
Show Zify UnOp (cmd), 595	Strongly Strict Implicit (flag), 176
Shrink Obligations (flag), 609	Structural Injection (flag), 303
sig (term), 191	Structure (cmdv), 567
sig2  (term), 191	SubClass (cmdv), 566
Signature components for label 'ident' do not match	subst (tacn), 312
(err), 161	suff (tacn), 489
sigT (term), 191	suffices (tacn), 489
sigT2 (term), 191	Suggest Proof Using (flag), 255
Silent (flag), 248	sum (term), 191
simpl (tacn), 316	sumbool (term), 192
simple apply (tacnv), 279	sumor (term), 192
simple destruct (tacnv), 294	swap (tacn), 340
simple destruct (tachv), 254 simple eapply (tachv), 279	sym_not_eq (term), 190
simple cappy (tachy), 273 simple induction (tachy), 298	symmetry (tacn), 335
simple induction (tachv), 298 simple inversion (tachv), 306	Syntax error: [prim:reference] expected after 'Nota-
simple inversion (tachy), 500 simple notypeclasses refine (tachy), 278	tion' (in [vernac:command]) (err), 513, 514
simple refine (tacny), 277	
Simplex (flag), 592	[prim:reference] (in [vernac:command])
simplify_eq (tacn), 336	(err), 513, 514
singel: / (term), 196	T
snd (term), 191	
solve (tacn), 353	Tactic Failure message (level 'num') (err), 354
Solve All Obligations (cmd), 609	Tactic generated a subgoal identical to the original
Solve Obligations (cmd), 609	goal. This happens if 'term' does not occur
Solve Unification Constraints (flag), 342	in the goal (err), 311
solve_constraints (tacn), 342	Tactic Notation (cmd), 515
Some (term), 190	Tactic Notation 'qualid' is deprecated since 'string'.
specialize (tacny), 291	'string' (warn), 146
split (tacnv), 282	Tactic 'qualid' is deprecated since 'string'. 'string'
split_Rabs (tacn), 198	(warn), 146
split_Rmult (tacn), 198	tail (term), 199
SProp, 127	tauto (tacn), 330
SProp not allowed, you need to Set Allow Strict-	Template Check (flag), 218
Prop or to use the -allow-sprop command-	Terms do not have convertible types (err), 312
line-flag (err), 647	Test (cmd), 237
SsrHave NoTCResolution (flag), 440	Test @table for (cmd), 237
SsrIdents (flag), 399	The 'abstract after' directive has no effect when the
SsrOldRewriteGoalsOrder (flag), 446	parsing function ('ident') targets an option
SsrRewrite (flag), 399	type (warn), 513
Stable Omega (flag), 591	The command has not failed! (err), 248

The conclusion is not a substitutive equation (err), 335	transparent_abstract (tacnv), 363 trivial (tacnv), 322
The conclusion of 'type' is not valid	True (term), 189
it must be built from 'ident' (err), 134	true (term), 190
The constant 'numeral' is not a binary64 floating-	try (tacn), 350
point value. A closest value will be used and	tryif (tacn), 352
unambiguously printed 'numeral'. [inexact-	Trying to mask the absolute name 'qualid'! (warn),
float,parsing] (warn), 201	167
The constructor 'ident' expects 'num' arguments	tt (term), 190
(err), 563	Type, 127
The elimination predicate term should be of arity	type_scope, 509
'num' (for non dependent case) or 'num' (for	Typeclass Resolution For Conversion (flag), 587
dependent case) (err), 563	Typeclasses Axioms Are Instances (flag), 588
The file :n:"ident'.vo' contains library dirpath and not	Typeclasses Debug (flag), 588
library dirpath' (err), 245	Typeclasses Debug Verbosity (opt), 588
The recursive argument must be specified (err), 157	Typeclasses Dependency Order (flag), 587
The reference is not unfoldable (err), 250	Typeclasses Depth (opt), 588
The reference X was not found in the current envi-	Typeclasses eauto (cmd), 588
ronment (err), 390	typeclasses eauto (tacn), 586
The reference 'ident' was not found in the current	Typeclasses Filtered Unification (flag), 587
environment (err), 513, 514	Typeclasses Iterative Deepening (flag), 588
The reference 'qualid' was not found in the current	Typeclasses Limit Intros (flag), 587
environment (err), 238, 249  The term 'term' has type 'type' which should be Set	Typeclasses Opaque (cmd), 587 Typeclasses Strict Possilytion (flow) 588
The term 'term' has type 'type' which should be Set, Prop or Type (err), 144	Typeclasses Strict Resolution (flag), 588 Typeclasses Transparent (cmd), 587
The term 'term' has type 'type' while it is expected	Typeclasses Unique Instances (flag), 588
to have type 'type' (err), 133	Typeclasses Unique Solutions (flag), 588
The variable 'ident' is already defined (err), 288	Typeciasses offique solutions (mag), see
The 'num' th argument of 'ident' must be 'ident' in	U
'type' (err), 138	Unable to apply (err), 281
The 'term' provided does not end with an equation	Unable to find an instance for the variables 'ident'
(err), 311	'ident' (err), 296
Theorem (cmd), 144	Unable to find an instance for the variables
Theories, 187	'ident''ident' (err), 278
This is not the last opened module (err), 161	Unable to infer a match predicate (err), 563
This is not the last opened module type (err), 162	Unable to satisfy the rewriting constraints (err), 632
This is not the last opened section (err), 159	Unable to unify with (err), 335
This object does not support universe names (err),	Unable to unify 'term' with 'term' (err), 278, 334
236	Unbound context identifier 'ident' (err), 360
This proof is focused, but cannot be unfocused this	Unbound [value constructor] X (err), 389
way (err), 259	Undeclared universe 'ident' (err), 642
This tactic has more than one success (err), 352	Undelimit Scope (cmd), 506
Time (cmd), 247 time (tacn), 356	under (tacn), 457
time_constr (tacn), 356	Undo (cmd), 257
Timeout (cmd), 248	Unexpected non-option term 'term' while parsing a
timeout (tacn), 356	numeral notation (err), 512
To avoid stack overflow, large numbers in 'type' are	Unexpected non-option term 'term' while parsing a string notation (err), 514
interpreted as applications of 'ident' (warn),	Unexpected term 'term' while parsing a numeral no-
513	tation (err), 512
Too few occurrences (err), 314, 318	Unexpected term 'term' while parsing a string nota-
transitivity (tacn), 335	tion (err), 514
Transparent (cmd), 249	Unfocus (cmd), 257
Transparent Obligations (flag), 609	Unfocused (cmd), 257

unfold (tacn), 318	the statement but that are required by the
Uniform Inductive Parameters (flag), 137	proof (warn), 531
unify (tacn), 334	7
unit (term), 190	Z
Universal Lemma Under Conjunction (flag), 281	zify (tacn), 595
Universe (cmd), 642	V ( ),
Universe Checking (flag), 251	
Universe inconsistency (err), 643	'class' must be a transparent constant (err), 566
Universe instance should have length 'num' (err), 236	'ident' cannot be defined (warn), 150
Universe Minimization ToSet (flag), 642	'ident' is already declared as a typeclass (warn), 585
Universe Polymorphism (flag), 639	'ident' is already used (err), 283, 287
Unknown inductive type (err), 265	'ident' is bound to a notation that does not denote a
unlock (tacn), 462	reference (err), 513, 514
Unset (cmd), 237	'ident' is declared as a local axiom [local-
Unset @option (cmd), 237	declaration, scope (warn), 133
Unshelve (cmd), 342	'ident' is declared as a local definition [local-
unshelve (tacn), 342	declaration, scope (warn), 133
Unsupported attribute (warn), 147	'ident' is not a local definition (err), 285
Use of 'string' Notation is deprecated as it is incon-	'ident' is used in conclusion (err), 291
sistent with pattern syntax (warn), 505	'ident' is used in hypothesis 'ident' (err), 291
	'ident' is used in the conclusion (err), 285
V	'ident' is used in the hypothesis 'ident' (err), 285
value (term), 192	'ident' should go from Byte.byte or (list Byte.byte) to
Variable (cmd), 159	'type' or (option 'type') (err), 514
Variable (cutside a section) (cmdv), 132	'ident' should go from Decimal.int to 'type' or (op-
Variable 'ident' is already declared (err), 290	tion 'type'). Instead of Decimal.int, the
Variables (cmdv), 160	types Decimal.uint or Z or Int63.int or Deci-
Variables (cmdv), 100 Variables (outside a section) (cmdv), 132	mal.decimal could be used (you may need to
Variant (cmd), 138	require BinNums or Decimal or Int63 first)
vm_cast_no_check (tacnv), 344	- /
vm_compute (tacnv), 315	(err), 512
viii_compute (taciiv), 515	'ident' should go from 'type' to Byte.byte or (option Byte.byte) or (list Byte.byte) or (option (list
W	Byte.byte) (err), 514
	'ident' should go from 'type' to Decimal.int or (option
Warnings (opt), 248	Decimal.int). Instead of Decimal.int, the
Well founded induction, 194	types Decimal.uint or Z or Int63.int or Deci-
Well foundedness, 194	mal.decimal could be used (you may need to
well_founded (term), 194	require BinNums or Decimal or Int63 first)
When 'term' contains more than one non dependent	(err), 512
product the tactic lapply only takes into ac-	'ident': no such entry (err), 246
count the first product (warn), 279	'qualid' does not occur (err), 319
without loss (tacn), 441	'qualid' does not respect the uniform inheritance con-
wlog (tacn), 441	dition (warn), 565
Wrong bullet 'bullet': Bullet 'bullet' is mandatory	'qualid' is already a coercion (err), 565
here (err), 263	
Wrong bullet 'bullet': Current bullet 'bullet' is not	'qualid' is not a function (err), 565
finished (err), 263	'qualid' is not a module (err), 167
Υ	'qualid' is not an inductive type (err), 326
	'qualid' not a defined object (err), 236
You should use the "Proof using []." syntax instead	'qualid' not declared (err), 565 'torm' cannot be used as a hint (err), 325, 326
of "Proof." to enable skipping this proof	'term' cannot be used as a hint (err), 325, 326
which is located inside a section. Give as ar-	'type' is not an inductive type (err), 512, 514
gument to "Proof using" the list of section	
variables that are not needed to typecheck	