

## Contents

<b>1 Misc</b>	<b>1</b>
1.1 Contest . . . . .	1
1.1.1 Makefile . . . . .	1
1.1.2 Default Code . . . . .	1
1.2 How Did We Get Here? . . . . .	1
1.2.1 Macros . . . . .	1
1.2.2 Constexpr . . . . .	1
1.2.3 Bump Allocator . . . . .	1
1.3 Tools . . . . .	1
1.3.1 Floating Point Binary Search . . . . .	1
1.3.2 SplitMix64 . . . . .	1
1.3.3 <random> . . . . .	1
1.4 Algorithms . . . . .	2
1.4.1 Bit Hacks . . . . .	2
1.4.2 Aliens Trick . . . . .	2
1.4.3 Hilbert Curve . . . . .	2

## 1. Misc

### 1.1. Contest

#### 1.1.1. Makefile

```
1 .PRECIOUS: ./p%
3
3 %: p%
    ulimit -s unlimited && ./${%}
5 p%: p%.cpp
    g++ -o $@ $< -std=c++17 -Wall -Wextra -Wshadow \
7         -fsanitize=address,undefined
```

#### 1.1.2. Default Code

```
1 #include <bits/stdc++.h>
3
3 #define pb          push_back
3 #define eb          emplace_back
5 #define F          first
5 #define S          second
7 #define SZ(v)       ((int)(v).size())
7 #define ALL(v)       (v).begin(), (v).end()
9 #define MEM(a, b)   memset(a, b, sizeof a)
9 #define unpair(p)   (p).F[(p).S
11
13 using namespace std;
13 using ll = long long;
13 using ld = long double;
15 using LL = __int128;
15 using pii = pair<int, int>;
17 using pll = pair<ll, ll>;
19
19 int main() { ios::sync_with_stdio(0), cin.tie(0); }
```

### 1.2. How Did We Get Here?

#### 1.2.1. Macros

```
1 #define _GLIBCXX_DEBUG          1 // for debug mode
1 #define _GLIBCXX_SANITIZE_VECTOR 1 // for asan on vectors
3 #pragma GCC optimize("O3", "unroll-loops")
3 #pragma GCC optimize("fast-math")
5 #pragma GCC target("avx,avx2,abm,bmi,bmi2") // tip: `lscpu`
5 // before a loop
7 #pragma GCC unroll 16 // 0 or 1 -> no unrolling
7 #pragma GCC ivdep // use with caution
9 // gcc>=9 has [[likely]] [[unlikely]]
9 // more gcc opt info: -fopt-info-optimized-missed-optall
```

#### 1.2.2. Constexpr

```
1 constexpr array<int, 10> fibonacci{[] {
3     array<int, 10> a{};
3     a[0] = a[1] = 1;
3     for (int i = 2; i < 10; i++) a[i] = a[i - 1] + a[i - 2];
5     return a;
5 }()};
7 static_assert(fibonacci[9] == 55, "CE");
9
9 template <typename F, typename INT, INT... S>
9 constexpr void for_constexpr(integer_sequence<INT, S...,
11                             F &&func) {
11     int _[] = {(func(integral_constant<INT, S>{}), 0)...};
13 }
13 // example
```

```
15 template <typename... T> void print_tuple(tuple<T...> t) {
17     for_constexpr(make_index_sequence<sizeof...(T)>{}),
17         [&](auto i) { cout << get<i>(t) << '\n'; });
19 }
19 // some default limits in g++ (7.x - trunk):
19 // constexpr recursion depth: 512
21 // constexpr loop iteration (per function): 262144
21 // constexpr operation count (per function): 33554432
23 // template recursion depth: 900 (g++ might segfault)
```

#### 1.2.3. Bump Allocator

```
1 // global bump allocator
1 char mem[256 << 20]; // 256 MB
3 size_t rsp = sizeof mem;
3 void *operator new(size_t s) {
5     assert(s < rsp); // MLE
5     return (void *)&mem[rsp -= s];
7 }
7 void operator delete(void *) {}
9
9 // bump allocator for STL / pbds containers
11 char mem[256 << 20];
11 size_t rsp = sizeof mem;
13 template <typename T> struct bump {
13     typedef T value_type;
15     bump() {}
15     template <typename U> bump(U, ...) {}
17     T *allocate(size_t n) {
17         rsp -= n * sizeof(T);
19         rsp &= 0 - alignof(T);
19         return (T *)(&mem + rsp);
21     }
21     void deallocate(T *, size_t n) {}
23 };
23
```

### 1.3. Tools

#### 1.3.1. Floating Point Binary Search

```
1 union di {
3     double d;
3     ull i;
3 };
5 bool check(double);
5 // binary search in [L, R] with relative error 2^-eps
7 double binary_search(double L, double R, int eps) {
7     di l = {L}, r = {R}, m;
9     while (r.i - l.i > 1LL << (52 - eps)) {
9         m.i = (l.i + r.i) >> 1;
11         if (check(m.d)) r = m;
11         else l = m;
13     }
13     return l.d;
15 }
15
```

#### 1.3.2. SplitMix64

```
1 using ull = unsigned long long;
1 inline ull splitmix64(ull x) {
3     // static ull x = seed;
3     ull z = (x += 0x9E3779B97F4A7C15);
5     z = (z ^ (z >> 30)) * 0xBF58476D1CE4E5B9;
5     z = (z ^ (z >> 27)) * 0x94D049BB133111EB;
7     return z ^ (z >> 31);
7 }
7
```

#### 1.3.3. <random>

```
1 #ifdef __unix__
1 random_device rd;
3 mt19937_64 RNG(rd());
3 #else
5 const auto SEED = chrono::high_resolution_clock::now()
5     .time_since_epoch()
5     .count();
7 mt19937_64 RNG(SEED);
7 #endif
9 // random long long: RNG();
9 // uniformly random type T (int, double, ...) in [l, r]:
11 // uniform_int_distribution<T> dist(l, r); dist(RNG);
11
```

## 1.4. Algorithms

### 1.4.1. Bit Hacks

```
1 ull next_permutation(ull x) {  
    ull c = __builtin_ctzll(x), r = x + (1 << c);  
3     return (r ^ x) >> (c + 2) | r;  
    }  
5 // iterate over all (proper) subsets of bitset s  
void subsets(ull s) {  
7     for (ull x = s; x;) { --x &= s; /* do stuff */ }  
    }
```

### 1.4.2. Aliens Trick

```
1 // min dp[i] value and its i (smallest one)  
pll get_dp(int n);  
3 ll aliens(int n) {  
    int l = 0, r = 1000000;  
5     while (l != r) {  
        int m = (l + r) / 2;  
7         auto [f, s] = get_dp(m);  
        if (s == n) return f - m * n;  
9         if (s < n) r = m;  
        else l = m + 1;  
11    }  
    return get_dp(--l).first - l * n;  
13 }
```

### 1.4.3. Hilbert Curve

```
1 ll hilbert(ll n, int x, int y) {  
    ll res = 0;  
3     for (ll s = n / 2; s; s >>= 1) {  
        int rx = (x & s) > 0;  
5        int ry = (y & s) > 0;  
        res += s * s * ((3 * rx) ^ ry);  
7        if (ry == 0) {  
            if (rx == 1) x = s - 1 - x, y = s - 1 - y;  
9            swap(x, y);  
        }  
11    }  
    return res;  
13 }
```