```
b22040617@HONORmagic14R7:~/exp3_1$ nano exp3_1.c
b22040617@HONORmagic14R7:~/exp3_1$ nano makefile
b22040617@HONORmagic14R7:~/exp3_1$ make
gcc -c exp3_1.c
gcc -o exp3_1 exp3_1.o
b22040617@HONORmagic14R7:~/exp3_1$ make clean
rm -rf *.o
b22040617@HONORmagic14R7:~/exp3_1$ touch test1.txt
b22040617@HONORmagic14R7:~/exp3_1$ echo "asdfgchxdsVfzxgchgmnfbg" >> test1.txt
b22040617@HONORmagic14R7:~/exp3_1$ ./exp3_1 test1.txt
asdfgchxdsVfzxgchgmnfbg

b22040617@HONORmagic14R7:~/exp3_1$
```

```
b22040617@HONORmagic14R7:~/exp3_2$ nano exp3_2.c
b22040617@HONORmagic14R7:~/exp3_2$ nano makefile
b22040617@HONORmagic14R7:~/exp3_2$ make
gcc -c exp3_2.c
gcc -o exp3_2 exp3_2.o
b22040617@HONORmagic14R7:~/exp3_2$ make clean
rm -rf *.o
b22040617@HONORmagic14R7:~/exp3_2$ ./exp3_2 ~

.
.local
.profile
..
.bashrc
.bash_logout
exp3_2
exp3_1
.bash_history
b22040617@HONORmagic14R7:~/exp3_2$
```

```
b22040617@HONORmagic14R7:~/exp3_3$ nano exp3_3.c
b22040617@HONORmagic14R7:~/exp3_3$ nano makefile
b22040617@HONORmagic14R7:~/exp3_3$ make
gcc -c exp3_3.c
gcc -o exp3_3 exp3_3.o
b22040617@HONORmagic14R7:~/exp3_3$ make clean
rm -rf *.o
b22040617@HONORmagic14R7:~/exp3_3$ ./exp3_3 ~
/home/b22040617/exp3_3
success
/home
b22040617@HONORmagic14R7:~/exp3_3$ |
```