

---

## Automation

---

April 2, 2019

<b>1 Module Documentation</b>	<b>1</b>
1.1 Entities	1
1.1.0.1 ogit/Forum/KnowledgeBundle	1
1.1.0.2 ogit/Organization	2
1.1.0.3 ogit/Forum/KnowledgeItemHistory	2
1.1.0.4 ogit/Forum/Reply	3
1.1.0.5 ogit/Forum/ShortId	4
1.1.0.6 ogit/Question	4
1.1.0.7 ogit/Automation/MARSNodeTemplate	5
1.1.0.8 ogit/Automation/KIRanking	6
1.1.0.9 ogit/Forum/Workflow	6
1.1.0.10 ogit/Forum/Topic	7
1.1.0.11 ogit/ServiceManagement/ChangeRequest	7
1.1.0.12 ogit/Automation/MARSNode	8
1.1.0.13 ogit/Attachment	12
1.1.0.14 ogit/ServiceManagement/SubTask	13
1.1.0.15 ogit/Automation/MAID	14
1.1.0.16 ogit/ServiceManagement/Problem	15
1.1.0.17 ogit/Comment	15
1.1.0.18 ogit/Region	16
1.1.0.19 ogit/ServiceManagement/Order	16
1.1.0.20 ogit/ConfigurationItem	17
1.1.0.21 ogit/OSLC-crtv/ServiceInstance	19
1.1.0.22 ogit/Automation/KnowledgeItem	20
1.1.0.23 ogit/Hyperlink	22
1.1.0.24 ogit/ServiceManagement/Incident	22
1.1.0.25 ogit/Cost/PlanningTemplate	23
1.1.0.26 ogit/Automation/Item	23
1.1.0.27 ogit/Software/Application	24
1.1.0.28 ogit/Forum/Rating	24
1.1.0.29 ogit/Automation/KnowledgeBundle	25
1.1.0.30 ogit/Forum/WorkflowStep	26
1.1.0.31 ogit/Data/Log	26
1.1.0.32 ogit/Network/NetworkInterface	27
1.1.0.33 ogit/ServiceManagement/Report	27
1.1.0.34 ogit/ServiceManagement/Offering	28
1.1.0.35 ogit/Automation/MARSModelTemplate	28
1.1.0.36 ogit/Environment	29
1.1.0.37 ogit/MARS/Resource	29
1.1.0.38 ogit/Person	30
1.1.0.39 ogit/Location	31
1.1.0.40 ogit/Automation/History	31

1.1.0.41	ogit/Asset	32
1.1.0.42	ogit/Knowledge/AcquisitionSession	32
1.1.0.43	ogit/Task	33
1.1.0.44	ogit/Event	33
1.1.0.45	ogit/Forum/KnowledgeBundleHistory	34
1.1.0.46	ogit/Forum/Profile	35
1.1.0.47	ogit/Software/SoftwareComponent	36
1.1.0.48	ogit/Forum/Post	36
1.1.0.49	ogit/Automation/DynamicEngineData	37
1.1.0.50	ogit/Automation/AutomationIssue	37
1.1.0.51	ogit/Automation/MARSMODEL	39
1.1.0.52	ogit/Automation/KnowledgeItemAttribute	39
1.1.0.53	ogit/Automation/Variable	40
1.1.0.54	ogit/Forum/Tag	40
1.1.0.55	ogit/Automation/KnowledgePool	41
1.1.0.56	ogit/Automation/Configuration	41
1.1.0.57	ogit/Automation/Trigger	42
1.1.0.58	ogit/ServiceManagement/Service	42
1.1.0.59	ogit/ServiceManagement/Ticket	43
1.1.0.60	ogit/License	44
1.1.0.61	ogit/Cost/CostElement	44
1.1.0.62	ogit/Timeseries	45
1.1.0.63	ogit/Forum/FeedEntry	45
1.2	Verbs	46
1.2.0.1	ogit/contains	46
1.2.0.2	ogit/defines	46
1.2.0.3	ogit/hosts	47
1.2.0.4	ogit/runsOn	47
1.2.0.5	ogit/worksOn	47
1.2.0.6	ogit/assignedTo	48
1.2.0.7	ogit/generates	48
1.2.0.8	ogit/specifies	48
1.2.0.9	ogit/solves	49
1.2.0.10	ogit/forks	49
1.2.0.11	ogit/derivesFrom	49
1.2.0.12	ogit/describes	50
1.2.0.13	ogit/creates	50
1.2.0.14	ogit/associates	50
1.2.0.15	ogit/connects	51
1.2.0.16	ogit/deployedTo	51
1.2.0.17	ogit/locatedIn	52
1.2.0.18	ogit/versions	52

1.2.0.19 ogit/corresponds	52
1.2.0.20 ogit/Forum/rates	53
1.2.0.21 ogit/affects	53
1.2.0.22 ogit/OSLC-crtv/runsOn	53
1.2.0.23 ogit/implements	54
1.2.0.24 ogit/provides	54
1.2.0.25 ogit/owns	54
1.2.0.26 ogit/dependsOn	55
1.2.0.27 ogit/belongs	55
1.2.0.28 ogit/uses	55
1.2.0.29 ogit/plans	56
1.2.0.30 ogit/reportedOn	56
1.2.0.31 ogit/Forum/downloads	56
1.2.0.32 ogit/consistsOf	57
1.2.0.33 ogit/relates	57
1.3 Attributes	58
1.3.0.1 ogit/_modified-by	58
1.3.0.2 ogit/Automation/serviceType	58
1.3.0.3 ogit/ciType	58
1.3.0.4 ogit/reviewedAt	59
1.3.0.5 ogit/Automation/serialNumber	59
1.3.0.6 ogit/Automation/servletName	59
1.3.0.7 ogit/Automation/deployToEngine	60
1.3.0.8 ogit/Automation/cpuCoreCount	60
1.3.0.9 ogit/Automation/serviceId	60
1.3.0.10 ogit/manufacture	61
1.3.0.11 ogit/ServiceManagement/testPlan	61
1.3.0.12 ogit/Data/timeToLive	61
1.3.0.13 ogit/certainty	62
1.3.0.14 ogit/currency	62
1.3.0.15 ogit/category	62
1.3.0.16 ogit/_id	63
1.3.0.17 ogit/comment	63
1.3.0.18 ogit/Automation/osVersion	63
1.3.0.19 ogit/assignedAt	64
1.3.0.20 ogit/endOfWarranty	64
1.3.0.21 ogit/postalCode	64
1.3.0.22 ogit/Automation/buildType	65
1.3.0.23 ogit/Automation/cpuManufacturer	65
1.3.0.24 ogit/Automation/virtualMachineName	65
1.3.0.25 ogit/productOrderNumber	66
1.3.0.26 ogit/Automation/maidFormalRepresentation	66

1.3.0.27 ogit/checkedOutAt . . . . .	66
1.3.0.28 ogit/email . . . . .	67
1.3.0.29 ogit/Automation/moveToProductionAt . . . . .	67
1.3.0.30 ogit/ServiceManagement/resolvedAt . . . . .	67
1.3.0.31 ogit/urgency . . . . .	68
1.3.0.32 ogit/deliveredAt . . . . .	68
1.3.0.33 ogit/Automation/osServicePack . . . . .	68
1.3.0.34 ogit/Automation/rankingType . . . . .	69
1.3.0.35 ogit/alternativeName . . . . .	69
1.3.0.36 ogit/isCritical . . . . .	69
1.3.0.37 ogit/asset . . . . .	70
1.3.0.38 ogit/Automation/portNumberListener . . . . .	70
1.3.0.39 ogit/function . . . . .	70
1.3.0.40 ogit/positionNumber . . . . .	71
1.3.0.41 ogit/ServiceManagement/customer . . . . .	71
1.3.0.42 ogit/isValid . . . . .	71
1.3.0.43 ogit/Automation/memory . . . . .	72
1.3.0.44 ogit/integrity . . . . .	72
1.3.0.45 ogit/Automation/companyName . . . . .	72
1.3.0.46 ogit/ServiceManagement/scheduledStartAt . . . . .	73
1.3.0.47 ogit/country . . . . .	73
1.3.0.48 ogit/businessCategory . . . . .	73
1.3.0.49 ogit/Automation/middlewareType . . . . .	74
1.3.0.50 ogit/Automation/serviceName . . . . .	74
1.3.0.51 ogit/project . . . . .	74
1.3.0.52 ogit/Automation/licenseAvailability . . . . .	75
1.3.0.53 ogit/question . . . . .	75
1.3.0.54 ogit/maintenanceState . . . . .	75
1.3.0.55 ogit/_creator . . . . .	76
1.3.0.56 ogit/notification . . . . .	76
1.3.0.57 ogit/changeLog . . . . .	76
1.3.0.58 ogit/ServiceManagement/externalTicketId . . . . .	77
1.3.0.59 ogit/sourceId . . . . .	77
1.3.0.60 ogit/url . . . . .	77
1.3.0.61 ogit/licenseKey . . . . .	78
1.3.0.62 ogit/uri . . . . .	78
1.3.0.63 ogit/purchasedAt . . . . .	79
1.3.0.64 ogit/Automation/cpuCount . . . . .	79
1.3.0.65 ogit/timestamp . . . . .	79
1.3.0.66 ogit/Automation/databaseSchema . . . . .	80
1.3.0.67 ogit/mobilePhone . . . . .	80
1.3.0.68 ogit/Automation/additionalMacAddress . . . . .	80

1.3.0.69 ogit/severity	81
1.3.0.70 ogit/Automation/knowledgeItemTier	81
1.3.0.71 ogit/connectorId	81
1.3.0.72 ogit/Automation/dataClassification	82
1.3.0.73 ogit/Automation/firmwareVersion	82
1.3.0.74 ogit/effort	82
1.3.0.75 ogit/startedAt	83
1.3.0.76 ogit/value	83
1.3.0.77 ogit/assetTag	83
1.3.0.78 ogit/ipAddress	84
1.3.0.79 ogit/licenseType	84
1.3.0.80 ogit/unit	84
1.3.0.81 ogit/Automation/todo	85
1.3.0.82 ogit/Automation/knowledgeItemFormalRepresentation	85
1.3.0.83 ogit/Automation/installCount	85
1.3.0.84 ogit/installedAt	86
1.3.0.85 ogit/Automation/knowledgeItemId	86
1.3.0.86 ogit/Automation/marsNodeFormalRepresentation	86
1.3.0.87 ogit/updateCount	87
1.3.0.88 ogit/installStatus	87
1.3.0.89 ogit/city	87
1.3.0.90 ogit/Automation/systemClass	88
1.3.0.91 ogit/Automation/diskCount	88
1.3.0.92 ogit/mode	88
1.3.0.93 ogit/Automation/automationState	89
1.3.0.94 ogit/ServiceManagement/incidentStatus	89
1.3.0.95 ogit/taskLog	89
1.3.0.96 ogit/status	90
1.3.0.97 ogit/createdAt	90
1.3.0.98 ogit/ServiceManagement/workAround	91
1.3.0.99 ogit/ServiceManagement/rootCause	91
1.3.0.100 ogit/Forum/username	91
1.3.0.101 ogit/model	92
1.3.0.102 ogit/Automation/domain	92
1.3.0.103 ogit/Automation/lifecycle	92
1.3.0.104 ogit/lastName	93
1.3.0.105 ogit/Automation/cpuModel	93
1.3.0.106 ogit/Automation/buildName	93
1.3.0.107 ogit/Automation/appInstanceType	94
1.3.0.108 ogit/modificationTime	94
1.3.0.109 ogit/ServiceManagement/problemStatus	94
1.3.0.110 ogit/Automation/knowledgeItemSyntaxVersion	95

1.3.0.111 ogit/priority . . . . .	95
1.3.0.112 ogit/shortDescription . . . . .	95
1.3.0.113 ogit/Automation/serviceClass . . . . .	96
1.3.0.114 ogit/middleName . . . . .	96
1.3.0.115 ogit/resource . . . . .	96
1.3.0.116 ogit/ServiceManagement/targetFinishAt . . . . .	96
1.3.0.117 ogit/accessControl . . . . .	97
1.3.0.118 ogit/ServiceManagement/ticketId . . . . .	97
1.3.0.119 ogit/justification . . . . .	97
1.3.0.120 ogit/invoiceNumber . . . . .	98
1.3.0.121 ogit/response . . . . .	98
1.3.0.122 ogit/ServiceManagement/externalTicketSource . . . . .	98
1.3.0.123 ogit/Automation/diskSpace . . . . .	99
1.3.0.124 ogit/soxClass . . . . .	99
1.3.0.125 ogit/closedAt . . . . .	99
1.3.0.126 ogit/ServiceManagement/taskStatus . . . . .	100
1.3.0.127 ogit/ServiceManagement/resolutionCode . . . . .	100
1.3.0.128 ogit/expiresAt . . . . .	100
1.3.0.129 ogit/streetAddress . . . . .	101
1.3.0.130 ogit/businessCriticality . . . . .	101
1.3.0.131 ogit/leaseContract . . . . .	101
1.3.0.132 ogit/_owner . . . . .	102
1.3.0.133 ogit/securityClass . . . . .	102
1.3.0.134 ogit/serialNumber . . . . .	102
1.3.0.135 ogit/firstName . . . . .	103
1.3.0.136 ogit/assignedGroup . . . . .	103
1.3.0.137 ogit/macAddress . . . . .	103
1.3.0.138 ogit/Automation/osName . . . . .	104
1.3.0.139 ogit/version . . . . .	104
1.3.0.140 ogit/title . . . . .	104
1.3.0.141 ogit/Automation/appServer . . . . .	105
1.3.0.142 ogit/class . . . . .	105
1.3.0.143 ogit/Automation/sendHistory . . . . .	105
1.3.0.144 ogit/content . . . . .	106
1.3.0.145 ogit/confidentiality . . . . .	106
1.3.0.146 ogit/Automation/deployStatus . . . . .	106
1.3.0.147 ogit/Automation/rankMap . . . . .	107
1.3.0.148 ogit/lastOccurredAt . . . . .	107
1.3.0.149 ogit/Automation/isDeployed . . . . .	107
1.3.0.150 ogit/Automation/processingNode . . . . .	108
1.3.0.151 ogit/Automation/issueFormalRepresentation . . . . .	108
1.3.0.152 ogit/_tags . . . . .	108

1.3.0.153 ogit/ServiceManagement/scheduledFinishAt	109
1.3.0.154 ogit/name	109
1.3.0.155 ogit/Automation/software	110
1.3.0.156 ogit/Automation/originNode	110
1.3.0.157 ogit/description	111
1.3.0.158 ogit/finishedAt	111
1.3.0.159 ogit/Automation/host	112
1.3.0.160 ogit/Automation/weightMap	112
1.3.0.161 ogit/externalId	112
1.3.0.162 ogit/impact	113
1.3.0.163 ogit/contact	113
1.3.0.164 ogit/Automation/defaultSigma	113
1.3.0.165 ogit/Automation/appInfrastructureType	114
1.3.0.166 ogit/revision	114
1.3.0.167 ogit/Automation/issueType	114
1.3.0.168 ogit/orderedAt	115
1.3.0.169 ogit/faultCount	115
1.3.0.170 ogit/risk	115
1.3.0.171 ogit/lastUpdatedBy	116
1.3.0.172 ogit/ServiceManagement/fallbackPlan	116
1.3.0.173 ogit/Automation/defaultRank	116
1.3.0.174 ogit/isRoot	117
1.3.0.175 ogit/openedAt	117
1.3.0.176 ogit/Automation/virtualSystemName	117
1.3.0.177 ogit/expirationDate	118
1.3.0.178 ogit/officePhone	118
1.3.0.179 ogit/phone	118
1.3.0.180 ogit/acknowledgeState	119
1.3.0.181 ogit/deadline	119
1.3.0.182 ogit/Automation/osLicense	119
1.3.0.183 ogit/fax	120
1.3.0.184 ogit/Automation/databaseServer	120
1.3.0.185 ogit/Automation/portNumber	120
1.3.0.186 ogit/Automation/webServer	121
1.3.0.187 ogit/type	121
1.3.0.188 ogit/Automation/softwareKey	121
1.3.0.189 ogit/Automation/installPath	122
1.3.0.190 ogit/Automation/licenseName	122
1.3.0.191 ogit/capacity	122
1.3.0.192 ogit/Automation/contextPath	123
1.3.0.193 ogit/Automation/cpuSpeed	123
1.3.0.194 ogit/Automation/processingTimestamp	123



1.3.0.195 ogit/otherPhone . . . . .	124
1.3.0.196 ogit/subCategory . . . . .	124
1.3.0.197 ogit/Automation/servletClass . . . . .	124
1.3.0.198 ogit/sourceTable . . . . .	125
1.3.0.199 ogit/creator . . . . .	125
1.3.0.200 ogit/ServiceManagement/implementationPlan . . . . .	125
1.3.0.201 ogit/Datacenter/rackUnit . . . . .	126
1.3.0.202 ogit/availability . . . . .	126
1.3.0.203 ogit/ServiceManagement/allowedForNewBusiness . . . . .	126
1.3.0.204 ogit/Automation/firewallStatus . . . . .	127
1.3.0.205 ogit/lastScannedAt . . . . .	127
1.3.0.206 ogit/capacityAvailable . . . . .	127
1.3.0.207 ogit/subType . . . . .	128
1.3.0.208 ogit/pendingChange . . . . .	128
1.3.0.209 ogit/Automation/exchangeRate . . . . .	128
1.3.0.210 ogit/ServiceManagement/sourceStatus . . . . .	129
1.3.0.211 ogit/Automation/patchNumber . . . . .	129
1.3.0.212 ogit/Automation/cpuType . . . . .	129
1.3.0.213 ogit/Automation/dataPrivacy . . . . .	130
1.3.0.214 ogit/inventoryNumber . . . . .	130
1.3.0.215 ogit/message . . . . .	130
1.3.0.216 ogit/webPage . . . . .	131
1.3.0.217 ogit/Automation/objectIdentifier . . . . .	131
1.3.0.218 ogit/lastUpdatedAt . . . . .	131
1.3.0.219 ogit/modelNumber . . . . .	132
1.3.0.220 ogit/Automation/fqdn . . . . .	132
1.3.0.221 ogit/Automation/osKey . . . . .	132
1.3.0.222 ogit/Automation/brand . . . . .	133
1.3.0.223 ogit/Automation/licenseType . . . . .	133
1.3.0.224 ogit/market . . . . .	133
1.3.0.225 ogit/Automation/virtualSystemType . . . . .	134
1.3.0.226 ogit/Automation/affectedNodeId . . . . .	134
1.3.0.227 ogit/Automation/osManufacturer . . . . .	134
1.3.0.228 ogit/id . . . . .	135
1.3.0.229 ogit/occurenceCount . . . . .	135
1.3.0.230 ogit/ServiceManagement/solution . . . . .	136
1.3.0.231 ogit/creationTime . . . . .	136
1.3.0.232 ogit/subject . . . . .	136
1.3.0.233 ogit/checkedInAt . . . . .	137
1.3.0.234 ogit/summary . . . . .	137
1.3.0.235 ogit/lastClearedAt . . . . .	137
1.3.0.236 ogit/Automation/adminUrl . . . . .	138

---

1.3.0.237 ogit/MARS/Resource/class . . . . .	138
1.3.0.238 ogit/Automation/marsNodeType . . . . .	138
1.3.0.239 ogit/Automation/command . . . . .	139
1.3.0.240 ogit/Automation/basicConfigId . . . . .	139
1.3.0.241 ogit/size . . . . .	139
1.3.0.242 ogit/serviceContract . . . . .	140
1.3.0.243 ogit/Automation/serviceStatus . . . . .	140
1.3.0.244 ogit/vendor . . . . .	140
1.3.0.245 ogit/firstOccurredAt . . . . .	141
1.3.0.246 ogit/validFrom . . . . .	141
1.3.0.247 ogit/Automation/governingContract . . . . .	141
1.3.0.248 ogit/Automation/systemType . . . . .	142
1.3.0.249 ogit/Automation/tcpPort . . . . .	142
1.3.0.250 ogit/position . . . . .	142
1.3.0.251 ogit/reportedAt . . . . .	143
1.3.0.252 ogit/Automation/logLevel . . . . .	143
1.3.0.253 ogit/ServiceManagement/targetStartAt . . . . .	143
1.3.0.254 ogit/ServiceManagement/reportedSource . . . . .	144
1.3.0.255 ogit/ServiceManagement/task . . . . .	144
1.3.0.256 ogit/instance . . . . .	144
1.3.0.257 ogit/Automation/sendData . . . . .	145
1.3.0.258 ogit/isSupported . . . . .	145
1.3.0.259 ogit/operationalStatus . . . . .	145
1.3.0.260 ogit/validTo . . . . .	146
1.3.0.261 ogit/ServiceManagement/changeStatus . . . . .	146
1.3.0.262 ogit/Automation/projectName . . . . .	146

# Chapter 1

## Module Documentation

### 1.1 Entities

#### 1.1.0.1 ogit/Forum/KnowledgeBundle

Deprecated in favor of ogit/Automation/KnowledgeBundle. A grouping of ogit/Automation/↔ KnowledgeItems into a package.

- id: <http://www.purl.org/ogit/Forum/KnowledgeBundle>
- valid-from: Mon Apr 27 00:00:00 UTC 2015
- creator: [cwalker@arago.de](mailto:cwalker@arago.de)
- scope: NTO
- parent: ogit/Node

#### attributes

- mandatory:
  - [ogit/name](#)
- optional:
  - [ogit/accessControl](#)

#### incoming edges

- [ogit/connects](#) ≤ [ogit/Automation/KnowledgeItem](#)

#### outgoing edges

- [ogit/connects](#) ⇒ [ogit/Automation/KnowledgeItem](#)
- [ogit/contains](#) ⇒ [ogit/Automation/AutomationIssue](#)
- [ogit/contains](#) ⇒ [ogit/Automation/KnowledgeItem](#)

### 1.1.0.2 ogit/Organization

An identity that represents an organization, company, or some other grouping of Person objects. Entities of this type should be created with a predefined ID. Those IDs should be named like a domain name, i.e. a concatenation of some strings separated with a dot. If organization data is created from a LDAP then a mapping like "cn=John Doe,dc=example,dc=com" => "john\_doe.example.com" should be employed. The ogit/function attribute should be used to tell what kind of grouping an entity of type Organization is: company, department, group, ...

- id: <http://www.purl.org/ogit/Organization>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: SGO
- parent: ogit/Node

#### attributes

- mandatory:
  - [ogit/name](#)
- optional:
  - [ogit/businessCategory](#)
  - [ogit/city](#)
  - [ogit/country](#)
  - [ogit/description](#)
  - [ogit/email](#)
  - [ogit/function](#)
  - [ogit/phone](#)
  - [ogit/postalCode](#)
  - [ogit/sourceId](#)
  - [ogit/status](#)
  - [ogit/streetAddress](#)
  - [ogit/webPage](#)

#### outgoing edges

- [ogit/owns](#) => [ogit/Automation/MARSNode](#)

### 1.1.0.3 ogit/Forum/KnowledgeItemHistory

Deprecated in favor of [ogit/VersioningData](#). A data container of [ogit/Automation/KnowledgeItems](#) changes.

- id: <http://www.purl.org/ogit/Forum/KnowledgeItemHistory>
- valid-from: Fri Nov 13 00:00:00 UTC 2015
- creator: [bmmore@arago.de](mailto:bmmore@arago.de)
- scope: NTO
- parent: ogit/Node

**attributes**

- mandatory:
  - [ogit/Automation/deployToEngine](#)
  - [ogit/Automation/knowledgeItemFormalRepresentation](#)
- optional:
  - [ogit/Automation/knowledgeItemTier](#)
  - [ogit/accessControl](#)
  - [ogit/changeLog](#)
  - [ogit/creationTime](#)
  - [ogit/description](#)
  - [ogit/isValid](#)
  - [ogit/modificationTime](#)
  - [ogit/name](#)

**incoming edges**

- [ogit/connects](#) <= [ogit/Automation/KnowledgeItem](#)

**outgoing edges**

- [ogit/connects](#) => [ogit/Automation/KnowledgeItem](#)
- [ogit/relates](#) => [ogit/Automation/KnowledgeItem](#)

**1.1.0.4 ogit/Forum/Reply**

A response to a some other entity

- id: <http://www.purl.org/ogit/Forum/Reply>
- valid-from: Mon Apr 27 00:00:00 UTC 2015
- creator: [cwalker@arago.de](mailto:cwalker@arago.de)
- scope: NTO
- parent: ogit/Node

**attributes**

- mandatory:
  - [ogit/content](#)

**incoming edges**

- [ogit/connects](#) <= [ogit/Automation/KnowledgeItem](#)

## outgoing edges

- [ogit/connects](#) => [ogit/Automation/KnowledgeItem](#)

1.1.0.5 [ogit/Forum/ShortId](#)

A Reference to another Entity, used to track access via a specific channel/referrer. For example in TabTab, a Post has many shortIds which relate to different sharing methods, e.g. one for Twitter, one for Yammer, one for Email, etc... TabTab uses them as 'short urls' in the App and redirect the user to the correct content after tracking the access by the channel ([ogit/function](#)) attribute. The [ogit/function](#) attribute is used for this as the function of this shortId is to track a specific channel of inbound traffic. The ShortId can be used without this channel/referrer data, albeit to more limited use. The [ogit/id](#) attribute in this instance would be a short URL safe string.

- id: <http://www.purl.org/ogit/Forum/ShortId>
- valid-from: Thu Apr 23 00:00:00 UTC 2015
- creator: [cwalker@arago.de](mailto:cwalker@arago.de)
- scope: NTO
- parent: [ogit/Node](#)

## attributes

- mandatory:
  - [ogit/id](#)
- optional:
  - [ogit/function](#)

## outgoing edges

- [ogit/specifies](#) => [ogit/Automation/KnowledgeItem](#)

1.1.0.6 [ogit/Question](#)

This structure allows an automation engine to create data requests for existing Issues which should be filled by human user. Additionally could be used to create new Issue from some form.

- id: <http://www.purl.org/ogit/Question>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: SGO
- parent: [ogit/Node](#)

**attributes**

- optional:
  - [ogit/capacity](#)
  - [ogit/question](#)
  - [ogit/response](#)
  - [ogit/status](#)

**incoming edges**

- [ogit/associates](#) <= [ogit/Automation/AutomationIssue](#)

**1.1.0.7 [ogit/Automation/MARSNodeTemplate](#)**

Entity similar to MARSNode but used to create [ogit/Automation/MARSTemplate](#)'s, which are used to define a vendor implementation template of an ordered service offering and to enable definition of cost elements ([ogit/Cost/Cost↔Element](#)) attached to it. [Automation/MarsNode](#) can not be reused for template reasons.

- id: <http://www.purl.org/ogit/Automation/MARSNodeTemplate>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: NTO
- parent: [ogit/Node](#)

**attributes**

- mandatory:
  - [ogit/Automation/marsNodeFormalRepresentation](#)
- optional:
  - [ogit/Automation/marsNodeType](#)
  - [ogit/status](#)

**incoming edges**

- [ogit/contains](#) <= [ogit/Automation/MARSModelTemplate](#)
- [ogit/describes](#) <= [ogit/Asset](#)
- [ogit/relates](#) <= [ogit/Automation/KnowledgeItem](#)
- [ogit/relates](#) <= [ogit/Automation/MARSNode](#)
- [ogit/relates](#) <= [ogit/Automation/MARSNodeTemplate](#)

## outgoing edges

- [ogit/associates](#) => [ogit/Cost/CostElement](#)
- [ogit/relates](#) => [ogit/Automation/MARSNodeTemplate](#)
- [ogit/relates](#) => [ogit/Automation/MARSNodeTemplate](#)
- [ogit/relates](#) => [ogit/Automation/MARSNode](#)

1.1.0.8 [ogit/Automation/KIRanking](#)

A specific knowledge ranking configuration for HIRO.

- id: <http://www.purl.org/ogit/Automation/KIRanking>
- valid-from: Wed Apr 25 00:00:00 UTC 2018
- creator: [cy@arago.de](mailto:cy@arago.de)
- scope: NTO
- parent: [ogit/Node](#)

## attributes

- mandatory:
  - [ogit/Automation/rankingType](#)
  - [ogit/Automation/weightMap](#)
  - [ogit/name](#)
- optional:
  - [ogit/Automation/defaultRank](#)
  - [ogit/Automation/defaultSigma](#)
  - [ogit/Automation/rankMap](#)
  - [ogit/Automation/sendData](#)
  - [ogit/Automation/sendHistory](#)
  - [ogit/url](#)

## incoming edges

- [ogit/uses](#) <= [ogit/Automation/Configuration](#)

1.1.0.9 [ogit/Forum/Workflow](#)

A Workflow defines a series of steps that must be completed in order.

- id: <http://www.purl.org/ogit/Forum/Workflow>
- valid-from: Mon Sep 18 00:00:00 UTC 2017
- creator: [cwalker@arago.de](mailto:cwalker@arago.de)
- scope: NTO
- parent: [ogit/Node](#)



## attributes

- mandatory:
  - [ogit/title](#)

## outgoing edges

- [ogit/connects](#) => [ogit/Automation/AutomationIssue](#)

1.1.0.10 [ogit/Forum/Topic](#)

A Topic is a SubForum with a specific topic associated. Use to divide forums into sub-forums. However the entity is general enough to be used for anything that has a given subject.

- id: <http://www.purl.org/ogit/Forum/Topic>
- valid-from: Mon Apr 27 00:00:00 UTC 2015
- creator: [cwalker@arago.de](mailto:cwalker@arago.de)
- scope: NTO
- parent: [ogit/Node](#)

## attributes

- mandatory:
  - [ogit/description](#)
  - [ogit/title](#)
- optional:
  - [ogit/accessControl](#)

## incoming edges

- [ogit/connects](#) <= [ogit/Automation/KnowledgeItem](#)

1.1.0.11 [ogit/ServiceManagement/ChangeRequest](#)

This entity type defines a change request ticket

- id: <http://www.purl.org/ogit/ServiceManagement/ChangeRequest>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: NTO
- parent: [ogit/Node](#)

**attributes**

- mandatory:
  - [ogit/id](#)
- optional:
  - [ogit/ServiceManagement/changeStatus](#)
  - [ogit/ServiceManagement/customer](#)
  - [ogit/ServiceManagement/fallbackPlan](#)
  - [ogit/ServiceManagement/implementationPlan](#)
  - [ogit/ServiceManagement/resolutionCode](#)
  - [ogit/ServiceManagement/scheduledFinishAt](#)
  - [ogit/ServiceManagement/scheduledStartAt](#)
  - [ogit/ServiceManagement/solution](#)
  - [ogit/ServiceManagement/sourceStatus](#)
  - [ogit/ServiceManagement/targetFinishAt](#)
  - [ogit/ServiceManagement/targetStartAt](#)
  - [ogit/ServiceManagement/testPlan](#)
  - [ogit/assignedGroup](#)
  - [ogit/category](#)
  - [ogit/effort](#)
  - [ogit/finishedAt](#)
  - [ogit/justification](#)
  - [ogit/reportedAt](#)
  - [ogit/reviewedAt](#)
  - [ogit/risk](#)
  - [ogit/startedAt](#)

**outgoing edges**

- [ogit/affects](#) => [ogit/Automation/MARSNode](#)
- [ogit/corresponds](#) => [ogit/Automation/AutomationIssue](#)
- [ogit/relates](#) => [ogit/Automation/MARSNode](#)
- [ogit/reportedOn](#) => [ogit/Automation/MARSNode](#)

**1.1.0.12 ogit/Automation/MARSNode**

Using this entity type to represent MARS nodes is deprecated. New applications should prefer the entity types from ogit/MARS NTO.

IT Objects will be represented in MARS Modell with MARS nodes. The MARS model builds upon four basic types of objects with a single type of relationship. Basically the objects which are in fact called "nodes" represent both views - the business perspective and the technical view. The technical components are modeled in the machine and software layers while the application and resource layers describe the business view of the IT environment.

- id: <http://www.purl.org/ogit/Automation/MARSNode>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: NTO
- parent: ogit/Node

## attributes

- optional:
  - [ogit/Automation/additionalMacAddress](#)
  - [ogit/Automation/adminUrl](#)
  - [ogit/Automation/appInfrastructureType](#)
  - [ogit/Automation/appInstanceType](#)
  - [ogit/Automation/appServer](#)
  - [ogit/Automation/basicConfigId](#)
  - [ogit/Automation/brand](#)
  - [ogit/Automation/buildName](#)
  - [ogit/Automation/buildType](#)
  - [ogit/Automation/companyName](#)
  - [ogit/Automation/contextPath](#)
  - [ogit/Automation/cpuCoreCount](#)
  - [ogit/Automation/cpuCount](#)
  - [ogit/Automation/cpuManufacturer](#)
  - [ogit/Automation/cpuModel](#)
  - [ogit/Automation/cpuSpeed](#)
  - [ogit/Automation/cpuType](#)
  - [ogit/Automation/dataClassification](#)
  - [ogit/Automation/dataPrivacy](#)
  - [ogit/Automation/databaseSchema](#)
  - [ogit/Automation/databaseServer](#)
  - [ogit/Automation/deployStatus](#)
  - [ogit/Automation/diskCount](#)
  - [ogit/Automation/diskSpace](#)
  - [ogit/Automation/domain](#)
  - [ogit/Automation/exchangeRate](#)
  - [ogit/Automation/firewallStatus](#)
  - [ogit/Automation/firmwareVersion](#)
  - [ogit/Automation/fqdn](#)
  - [ogit/Automation/host](#)
  - [ogit/Automation/installCount](#)
  - [ogit/Automation/installPath](#)
  - [ogit/Automation/isDeployed](#)
  - [ogit/Automation/licenseAvailability](#)
  - [ogit/Automation/licenseName](#)
  - [ogit/Automation/licenseType](#)
  - [ogit/Automation/lifecycle](#)
  - [ogit/Automation/marsNodeFormalRepresentation](#)
  - [ogit/Automation/marsNodeType](#)
  - [ogit/Automation/memory](#)
  - [ogit/Automation/middlewareType](#)
  - [ogit/Automation/moveToProductionAt](#)

- [ogit/Automation/objectIdentifier](#)
- [ogit/Automation/osKey](#)
- [ogit/Automation/osLicense](#)
- [ogit/Automation/osManufacturer](#)
- [ogit/Automation/osName](#)
- [ogit/Automation/osServicePack](#)
- [ogit/Automation/osVersion](#)
- [ogit/Automation/patchNumber](#)
- [ogit/Automation/portNumber](#)
- [ogit/Automation/portNumberListener](#)
- [ogit/Automation/projectName](#)
- [ogit/Automation/serialNumber](#)
- [ogit/Automation/serviceId](#)
- [ogit/Automation/serviceName](#)
- [ogit/Automation/serviceStatus](#)
- [ogit/Automation/serviceType](#)
- [ogit/Automation/servletClass](#)
- [ogit/Automation/servletName](#)
- [ogit/Automation/software](#)
- [ogit/Automation/softwareKey](#)
- [ogit/Automation/systemClass](#)
- [ogit/Automation/systemType](#)
- [ogit/Automation/tcpPort](#)
- [ogit/Automation/virtualMachineName](#)
- [ogit/Automation/virtualSystemName](#)
- [ogit/Automation/virtualSystemType](#)
- [ogit/Automation/webServer](#)
- [ogit/Datacenter/rackUnit](#)
- [ogit/connectorId](#)
- [ogit/creationTime](#)
- [ogit/endOfWarranty](#)
- [ogit/id](#)
- [ogit/ipAddress](#)
- [ogit/macAddress](#)
- [ogit/manufacturer](#)
- [ogit/modificationTime](#)
- [ogit/name](#)
- [ogit/serialNumber](#)

#### incoming edges

- [ogit/OSLC-crtv/runsOn](#) <= [ogit/OSLC-crtv/ServiceInstance](#)
- [ogit/affects](#) <= [ogit/Automation/MARSNode](#)
- [ogit/affects](#) <= [ogit/ServiceManagement/ChangeRequest](#)

- `ogit/affects`  $\leq$  `ogit/ServiceManagement/Incident`
- `ogit/affects`  $\leq$  `ogit/ServiceManagement/Order`
- `ogit/affects`  $\leq$  `ogit/ServiceManagement/Problem`
- `ogit/affects`  $\leq$  `ogit/ServiceManagement/Ticket`
- `ogit/affects`  $\leq$  `ogit/Event`
- `ogit/belongs`  $\leq$  `ogit/Attachment`
- `ogit/consistsOf`  $\leq$  `ogit/Environment`
- `ogit/contains`  $\leq$  `ogit/Automation/MARSModel`
- `ogit/contains`  $\leq$  `ogit/Automation/MARSNode`
- `ogit/corresponds`  $\leq$  `ogit/ConfigurationItem`
- `ogit/dependsOn`  $\leq$  `ogit/Automation/MARSNode`
- `ogit/deployedTo`  $\leq$  `ogit/Automation/MARSNode`
- `ogit/describes`  $\leq$  `ogit/Asset`
- `ogit/hosts`  $\leq$  `ogit/Automation/MARSNode`
- `ogit/owns`  $\leq$  `ogit/Organization`
- `ogit/provides`  $\leq$  `ogit/Automation/MARSNode`
- `ogit/relates`  $\leq$  `ogit/Automation/AutomationIssue`
- `ogit/relates`  $\leq$  `ogit/Automation/MARSNode`
- `ogit/relates`  $\leq$  `ogit/Automation/MARSNodeTemplate`
- `ogit/relates`  $\leq$  `ogit/ServiceManagement/ChangeRequest`
- `ogit/relates`  $\leq$  `ogit/ServiceManagement/Report`
- `ogit/relates`  $\leq$  `ogit/ConfigurationItem`
- `ogit/relates`  $\leq$  `ogit/Event`
- `ogit/reportedOn`  $\leq$  `ogit/ServiceManagement/ChangeRequest`
- `ogit/reportedOn`  $\leq$  `ogit/ServiceManagement/Incident`
- `ogit/reportedOn`  $\leq$  `ogit/ServiceManagement/Order`
- `ogit/reportedOn`  $\leq$  `ogit/ServiceManagement/Problem`
- `ogit/reportedOn`  $\leq$  `ogit/ServiceManagement/Ticket`
- `ogit/runsOn`  $\leq$  `ogit/Automation/MARSNode`
- `ogit/uses`  $\leq$  `ogit/Software/SoftwareComponent`
- `ogit/worksOn`  $\leq$  `ogit/Automation/AutomationIssue`

## outgoing edges

- `ogit/affects => ogit/ServiceManagement/Service`
- `ogit/affects => ogit/Automation/MARSNode`
- `ogit/assignedTo => ogit/Person`
- `ogit/associates => ogit/Cost/CostElement`
- `ogit/contains => ogit/Network/NetworkInterface`
- `ogit/contains => ogit/Automation/MARSNode`
- `ogit/contains => ogit/Automation/DynamicEngineData`
- `ogit/corresponds => ogit/Software/Application`
- `ogit/dependsOn => ogit/Automation/MARSNode`
- `ogit/deployedTo => ogit/Automation/MARSNode`
- `ogit/generates => ogit/Data/Log`
- `ogit/generates => ogit/Timeseries`
- `ogit/hosts => ogit/Automation/MARSNode`
- `ogit/locatedIn => ogit/Location`
- `ogit/locatedIn => ogit/Region`
- `ogit/provides => ogit/Automation/MARSNode`
- `ogit/relates => ogit/Automation/MARSNodeTemplate`
- `ogit/relates => ogit/Automation/MARSNode`
- `ogit/relates => ogit/License`
- `ogit/relates => ogit/Automation/KnowledgeItem`
- `ogit/runsOn => ogit/Automation/MARSNode`
- `ogit/uses => ogit/Automation/Configuration`

## 1.1.0.13 ogit/Attachment

This entity defines a file attachment that an IT service, issue, task or a ticket might have. The attachment itself is not saved in GraphIT, instead it contains an external url link for it.

- `id: http://www.purl.org/ogit/Attachment`
- `valid-from: Thu May 21 00:00:00 UTC 2015`
- `creator: Peter Larem`
- `scope: SGO`
- `parent: ogit/Node`

**attributes**

- optional:
  - [ogit/accessControl](#)
  - [ogit/content](#)
  - [ogit/createdAt](#)
  - [ogit/creator](#)
  - [ogit/id](#)
  - [ogit/lastUpdatedAt](#)
  - [ogit/lastUpdatedBy](#)
  - [ogit/name](#)
  - [ogit/size](#)
  - [ogit/sourceTable](#)
  - [ogit/type](#)
  - [ogit/url](#)

**outgoing edges**

- [ogit/belongs](#) => [ogit/Automation/MARSNode](#)

**1.1.0.14 ogit/ServiceManagement/SubTask**

This entity type defines sub-tasks for a ticket. Mostly used for ChangeRequest. Common alternative names with same meaning are: task, activity, work order.

- id: <http://www.purl.org/ogit/ServiceManagement/SubTask>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: NTO
- parent: [ogit/Node](#)

**attributes**

- mandatory:
  - [ogit/id](#)
- optional:
  - [ogit/ServiceManagement/customer](#)
  - [ogit/ServiceManagement/resolutionCode](#)
  - [ogit/ServiceManagement/scheduledFinishAt](#)
  - [ogit/ServiceManagement/scheduledStartAt](#)
  - [ogit/ServiceManagement/sourceStatus](#)
  - [ogit/ServiceManagement/targetFinishAt](#)
  - [ogit/ServiceManagement/targetStartAt](#)

- [ogit/ServiceManagement/taskStatus](#)
- [ogit/assignedGroup](#)
- [ogit/description](#)
- [ogit/effort](#)
- [ogit/finishedAt](#)
- [ogit/lastUpdatedAt](#)
- [ogit/name](#)
- [ogit/startedAt](#)
- [ogit/taskLog](#)
- [ogit/type](#)

#### outgoing edges

- [ogit/corresponds](#) => [ogit/Automation/AutomationIssue](#)

#### 1.1.0.15 [ogit/Automation/MAID](#)

The Monitoring-Automation Interface Description (MAID) is an abstract definition of

1. a timeseries to be monitored
2. desired normalizations of that timeseries
3. a set of condition->event mappings to apply to the timeseries or its normalizations

These time series definitions can be parameterized for more flexibility. Usually each MAID should describe exactly one raw timeseries. Depending of the type of monitoring or event management system connected to the engine, the corresponding adapter may choose to either supply the raw timeseries itself or directly create issues using the contained Event structures if it the raw data is not available.

The abstract MAID definitions are then mapped to the MARS model within the engine using so-called "Binding Blocks".

Thus MAID ensures that the arago Automation Engine is compatible to any monitoring system and can fully interact with them. By formalizing the interface the information verification process and definition of required add-ons to the monitoring systems becomes possible.

- id: <http://www.purl.org/ogit/Automation/MAID>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: NTO
- parent: [ogit/Node](#)

#### attributes

- mandatory:
  - [ogit/Automation/maidFormalRepresentation](#)



## outgoing edges

- [ogit/defines](#) => [ogit/Timeseries](#)
- [ogit/generates](#) => [ogit/Timeseries](#)

1.1.0.16 [ogit/ServiceManagement/Problem](#)

This entity type defines a problem ticket.

- id: <http://www.purl.org/ogit/ServiceManagement/Problem>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: NTO
- parent: [ogit/Node](#)

## attributes

- mandatory:
  - [ogit/id](#)
- optional:
  - [ogit/ServiceManagement/problemStatus](#)
  - [ogit/ServiceManagement/resolutionCode](#)
  - [ogit/ServiceManagement/rootCause](#)
  - [ogit/ServiceManagement/solution](#)
  - [ogit/ServiceManagement/workAround](#)
  - [ogit/reportedAt](#)

## outgoing edges

- [ogit/affects](#) => [ogit/Automation/MARSNode](#)
- [ogit/corresponds](#) => [ogit/Automation/AutomationIssue](#)
- [ogit/reportedOn](#) => [ogit/Automation/MARSNode](#)

1.1.0.17 [ogit/Comment](#)

Defines comments for a ticket, issue or another type of entity. Also known as WorkLog, ChangeLog or HistoryEntry.

- id: <http://www.purl.org/ogit/Comment>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: SGO
- parent: [ogit/Node](#)

**attributes**

- optional:
  - [ogit/content](#)
  - [ogit/creator](#)
  - [ogit/id](#)

**incoming edges**

- [ogit/connects](#) <= [ogit/Automation/KnowledgeItem](#)

**outgoing edges**

- [ogit/connects](#) => [ogit/Automation/KnowledgeItem](#)

**1.1.0.18 ogit/Region**

A region is always something that has a certain geographic extension (a country, a county, ) whereas ogit/Location usually refers to specific place usually having an address

- id: <http://www.purl.org/ogit/Region>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: SGO
- parent: ogit/Node

**attributes**

- optional:
  - [ogit/description](#)
  - [ogit/name](#)

**incoming edges**

- [ogit/locatedIn](#) <= [ogit/Automation/MARSNode](#)

**1.1.0.19 ogit/ServiceManagement/Order**

Defines an order.

- id: <http://www.purl.org/ogit/ServiceManagement/Order>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: NTO
- parent: ogit/Node

**attributes**

- mandatory:
  - [ogit/id](#)
- optional:
  - [ogit/ServiceManagement/externalTicketId](#)
  - [ogit/ServiceManagement/externalTicketSource](#)
  - [ogit/ServiceManagement/reportedSource](#)
  - [ogit/ServiceManagement/sourceStatus](#)
  - [ogit/closedAt](#)
  - [ogit/createdAt](#)
  - [ogit/description](#)
  - [ogit/impact](#)
  - [ogit/lastUpdatedAt](#)
  - [ogit/openedAt](#)
  - [ogit/priority](#)
  - [ogit/project](#)
  - [ogit/summary](#)
  - [ogit/urgency](#)

**incoming edges**

- [ogit/implements](#) <= [ogit/Automation/MARSModel](#)

**outgoing edges**

- [ogit/affects](#) => [ogit/Automation/MARSNode](#)
- [ogit/reportedOn](#) => [ogit/Automation/MARSNode](#)

**1.1.0.20 ogit/ConfigurationItem**

A configuration item.

- id: <http://www.purl.org/ogit/ConfigurationItem>
- valid-from: Thu Jun 11 00:00:00 UTC 2015
- creator: Aymen Ayoub
- scope: SGO
- parent: [ogit/Node](#)

**attributes**

- mandatory:
  - [ogit/id](#)
- optional:
  - [ogit/Automation/governingContract](#)
  - [ogit/asset](#)
  - [ogit/assetTag](#)
  - [ogit/assignedAt](#)
  - [ogit/availability](#)
  - [ogit/businessCriticality](#)
  - [ogit/category](#)
  - [ogit/checkedInAt](#)
  - [ogit/checkedOutAt](#)
  - [ogit/ciType](#)
  - [ogit/class](#)
  - [ogit/comment](#)
  - [ogit/confidentiality](#)
  - [ogit/contact](#)
  - [ogit/content](#)
  - [ogit/createdAt](#)
  - [ogit/deliveredAt](#)
  - [ogit/description](#)
  - [ogit/endOfWarranty](#)
  - [ogit/externalId](#)
  - [ogit/faultCount](#)
  - [ogit/impact](#)
  - [ogit/installStatus](#)
  - [ogit/installedAt](#)
  - [ogit/integrity](#)
  - [ogit/inventoryNumber](#)
  - [ogit/invoiceNumber](#)
  - [ogit/isCritical](#)
  - [ogit/isSupported](#)
  - [ogit/lastScannedAt](#)
  - [ogit/lastUpdatedAt](#)
  - [ogit/leaseContract](#)
  - [ogit/model](#)
  - [ogit/modelNumber](#)
  - [ogit/name](#)
  - [ogit/operationalStatus](#)
  - [ogit/orderedAt](#)
  - [ogit/pendingChange](#)
  - [ogit/priority](#)

- [ogit/productOrderNumber](#)
- [ogit/purchasedAt](#)
- [ogit/securityClass](#)
- [ogit/serviceContract](#)
- [ogit/shortDescription](#)
- [ogit/soxClass](#)
- [ogit/startedAt](#)
- [ogit/status](#)
- [ogit/subCategory](#)
- [ogit/subType](#)
- [ogit/type](#)
- [ogit/updateCount](#)
- [ogit/vendor](#)
- [ogit/version](#)

#### outgoing edges

- [ogit/corresponds](#) => [ogit/Automation/MARSNode](#)
- [ogit/relates](#) => [ogit/Automation/MARSNode](#)

#### 1.1.0.21 [ogit/OSLC-crtv/ServiceInstance](#)

A Service Instance is the representation of a service offering that was selected by the customer and then instantiated for that specific customer. Service Instances are supported by definite and measurable warranties or guarantees that the expected level of service/value will be met. Instances of the resource carry exposure from the group that is responsible for supporting the offering externally to the group that is utilizing the offering. It is common to group or nest instances together to form a service instance hierarchy. This resource definition does not represent the individual processes and/or activities that comprise an overall service except in the case where such processes are viewed as an independent service. In this condition, an instance of ServiceInstance would be created to represent the ServiceInstance of the process, then creating a hierarchy of ServiceInstances (to the containing ServiceInstance).

- id: <http://www.purl.org/ogit/OSLC-crtv/ServiceInstance>
- valid-from: Thu Sep 22 00:00:00 UTC 2016
- creator: OGIT Importer
- scope: NTO
- parent: [ogit/Node](#)

#### incoming edges

- [ogit/deployedTo](#) <= [ogit/Automation/KnowledgeItem](#)

#### outgoing edges

- [ogit/OSLC-crtv/runsOn](#) => [ogit/Automation/MARSNode](#)
- [ogit/uses](#) => [ogit/Automation/KnowledgePool](#)

## 1.1.0.22 ogit/Automation/KnowledgeItem

Formalized Knowledge stored in XML format. Serves as the building block for automation solutions.

A KnowledgeItem is a knowledge module, which is applied for execution of an issue. A KnowledgeItem checks therefor the information and decides if it will be executed. In that case, the KnowledgeItem executes operations, which serves the exploitation of information.

- id: <http://www.purl.org/ogit/Automation/KnowledgeItem>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: NTO
- parent: ogit/Node

## attributes

- mandatory:
  - [ogit/Automation/knowledgeItemFormalRepresentation](#)
- optional:
  - [ogit/Automation/deployStatus](#)
  - [ogit/Automation/deployToEngine](#)
  - [ogit/Automation/isDeployed](#)
  - [ogit/Automation/knowledgeItemSyntaxVersion](#)
  - [ogit/Automation/knowledgeItemTier](#)
  - [ogit/accessControl](#)
  - [ogit/changeLog](#)
  - [ogit/creationTime](#)
  - [ogit/description](#)
  - [ogit/isValid](#)
  - [ogit/modificationTime](#)
  - [ogit/name](#)

## incoming edges

- [ogit/Forum/downloads](#) <= [ogit/Forum/Profile](#)
- [ogit/Forum/rates](#) <= [ogit/Forum/Rating](#)
- [ogit/assignedTo](#) <= [ogit/Forum/Tag](#)
- [ogit/connects](#) <= [ogit/Automation/KnowledgeItem](#)
- [ogit/connects](#) <= [ogit/Forum/KnowledgeBundle](#)
- [ogit/connects](#) <= [ogit/Forum/KnowledgeItemHistory](#)
- [ogit/connects](#) <= [ogit/Forum/Post](#)
- [ogit/connects](#) <= [ogit/Forum/Reply](#)

- `ogit/connects`  $\leq$  `ogit/Forum/WorkflowStep`
- `ogit/connects`  $\leq$  `ogit/Comment`
- `ogit/contains`  $\leq$  `ogit/Automation/KnowledgeBundle`
- `ogit/contains`  $\leq$  `ogit/Automation/KnowledgePool`
- `ogit/contains`  $\leq$  `ogit/Forum/KnowledgeBundle`
- `ogit/contains`  $\leq$  `ogit/Forum/KnowledgeBundleHistory`
- `ogit/creates`  $\leq$  `ogit/Forum/Profile`
- `ogit/defines`  $\leq$  `ogit/Knowledge/AcquisitionSession`
- `ogit/derivesFrom`  $\leq$  `ogit/Automation/KnowledgeItem`
- `ogit/forks`  $\leq$  `ogit/Automation/KnowledgeItem`
- `ogit/relates`  $\leq$  `ogit/Automation/MARSNode`
- `ogit/relates`  $\leq$  `ogit/Forum/KnowledgeItemHistory`
- `ogit/specifies`  $\leq$  `ogit/Forum/ShortId`
- `ogit/uses`  $\leq$  `ogit/Automation/KnowledgePool`

#### outgoing edges

- `ogit/connects`  $\Rightarrow$  `ogit/Forum/WorkflowStep`
- `ogit/connects`  $\Rightarrow$  `ogit/Forum/KnowledgeItemHistory`
- `ogit/connects`  $\Rightarrow$  `ogit/Forum/Profile`
- `ogit/connects`  $\Rightarrow$  `ogit/Forum/Topic`
- `ogit/connects`  $\Rightarrow$  `ogit/Comment`
- `ogit/connects`  $\Rightarrow$  `ogit/Forum/Reply`
- `ogit/connects`  $\Rightarrow$  `ogit/Forum/KnowledgeBundle`
- `ogit/connects`  $\Rightarrow$  `ogit/Automation/KnowledgeItem`
- `ogit/connects`  $\Rightarrow$  `ogit/Forum/Post`
- `ogit/connects`  $\Rightarrow$  `ogit/Hyperlink`
- `ogit/contains`  $\Rightarrow$  `ogit/Automation/Trigger`
- `ogit/deployedTo`  $\Rightarrow$  `ogit/OSLC-crtv/ServiceInstance`
- `ogit/derivesFrom`  $\Rightarrow$  `ogit/Automation/KnowledgeItem`
- `ogit/forks`  $\Rightarrow$  `ogit/Automation/KnowledgeItem`
- `ogit/generates`  $\Rightarrow$  `ogit/Timeseries`
- `ogit/relates`  $\Rightarrow$  `ogit/Automation/MARSNodeTemplate`
- `ogit/solves`  $\Rightarrow$  `ogit/Task`
- `ogit/worksOn`  $\Rightarrow$  `ogit/Automation/AutomationIssue`

## 1.1.0.23 ogit/Hyperlink

A representation of an (optionally) titled Hyperlink to some media. No protocol restrictions imposed.

- id: <http://www.purl.org/ogit/Hyperlink>
- valid-from: Tue Jun 09 00:00:00 UTC 2015
- creator: [cwalker@arago.de](mailto:cwalker@arago.de)
- scope: SGO
- parent: ogit/Node

## attributes

- mandatory:
  - [ogit/url](#)
- optional:
  - [ogit/title](#)

## incoming edges

- [ogit/connects](#) <= [ogit/Automation/KnowledgeItem](#)

## 1.1.0.24 ogit/ServiceManagement/Incident

This entity type defines an incident ticket.

- id: <http://www.purl.org/ogit/ServiceManagement/Incident>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: NTO
- parent: ogit/Node

## attributes

- optional:
  - [ogit/ServiceManagement/customer](#)
  - [ogit/ServiceManagement/incidentStatus](#)
  - [ogit/ServiceManagement/reportedSource](#)
  - [ogit/ServiceManagement/resolutionCode](#)
  - [ogit/ServiceManagement/resolvedAt](#)
  - [ogit/ServiceManagement/solution](#)
  - [ogit/ServiceManagement/sourceStatus](#)
  - [ogit/ServiceManagement/task](#)
  - [ogit/assignedGroup](#)
  - [ogit/category](#)
  - [ogit/id](#)
  - [ogit/reportedAt](#)



## outgoing edges

- [ogit/affects](#) => [ogit/Automation/MARSNode](#)
- [ogit/corresponds](#) => [ogit/Automation/AutomationIssue](#)
- [ogit/reportedOn](#) => [ogit/Automation/MARSNode](#)

1.1.0.25 [ogit/Cost/PlanningTemplate](#)

A Planning Template is an estimated planning of cost elements referring to an Implementation Template and a Planning Parameter. It will consist of a recursive set of sub-templates, connected through an edge, where each one of them will represent a service. For a general overview: see the NTO description on github.

- id: <http://www.purl.org/ogit/Cost/PlanningTemplate>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: NTO
- parent: [ogit/Node](#)

## outgoing edges

- [ogit/plans](#) => [ogit/Automation/MARSModelTemplate](#)

1.1.0.26 [ogit/Automation/Item](#)

Item describing a condition for an automation issue (e.g. Request) that would correspond to a technical characteristic, which would activate the automation Trigger.

- id: <http://www.purl.org/ogit/Automation/Item>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: NTO
- parent: [ogit/Node](#)

## attributes

- mandatory:
  - [ogit/name](#)

## incoming edges

- [ogit/contains](#) <= [ogit/Automation/AutomationIssue](#)
- [ogit/contains](#) <= [ogit/Automation/Item](#)
- [ogit/contains](#) <= [ogit/Automation/Trigger](#)

## outgoing edges

- `ogit/contains => ogit/Automation/KnowledgeItemAttribute`
- `ogit/contains => ogit/Automation/Item`

## 1.1.0.27 ogit/Software/Application

Represents any type of software application

- id: `http://www.purl.org/ogit/Software/Application`
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: NTO
- parent: ogit/Node

## attributes

- mandatory:
  - `ogit/name`
- optional:
  - `ogit/description`
  - `ogit/url`
  - `ogit/version`

## incoming edges

- `ogit/corresponds <= ogit/Automation/MARSNode`

## 1.1.0.28 ogit/Forum/Rating

Rating is used to rank nodes based on an arbitrary integer value

- id: `http://www.purl.org/ogit/Forum/Rating`
- valid-from: Wed Aug 12 00:00:00 UTC 2015
- creator: `bneal@arago.de`
- scope: NTO
- parent: ogit/Node

## attributes

- mandatory:
  - [ogit/value](#)
- optional:
  - [ogit/content](#)

## outgoing edges

- [ogit/Forum/rates](#) => [ogit/Automation/KnowledgeItem](#)

1.1.0.29 [ogit/Automation/KnowledgeBundle](#)

A grouping of [ogit/Automation/KnowledgeItems](#) into a package.

- id: <http://www.purl.org/ogit/Automation/KnowledgeBundle>
- valid-from: Tue Oct 31 00:00:00 UTC 2017
- creator: [druss@arago.de](mailto:druss@arago.de)
- scope: NTO
- parent: [ogit/Node](#)

## attributes

- mandatory:
  - [ogit/name](#)
- optional:
  - [ogit/accessControl](#)

## incoming edges

- [ogit/contains](#) <= [ogit/Automation/KnowledgePool](#)
- [ogit/derivesFrom](#) <= [ogit/Automation/KnowledgeBundle](#)

## outgoing edges

- [ogit/contains](#) => [ogit/Automation/KnowledgeItem](#)
- [ogit/derivesFrom](#) => [ogit/Automation/KnowledgeBundle](#)

## 1.1.0.30 ogit/Forum/WorkflowStep

A Workflow Step defines part of a workflow

- id: <http://www.purl.org/ogit/Forum/WorkflowStep>
- valid-from: Mon Sep 18 00:00:00 UTC 2017
- creator: [cwalker@arago.de](mailto:cwalker@arago.de)
- scope: NTO
- parent: ogit/Node

## attributes

- mandatory:
  - [ogit/title](#)

## incoming edges

- [ogit/connects](#) <= [ogit/Automation/KnowledgeItem](#)

## outgoing edges

- [ogit/connects](#) => [ogit/Automation/KnowledgeItem](#)

## 1.1.0.31 ogit/Data/Log

This entity defines a log. It used to store a sequence of log records

- id: <http://www.purl.org/ogit/Data/Log>
- valid-from: Wed Jun 14 00:00:00 UTC 2017
- creator: [stravlos@arago.de](mailto:stravlos@arago.de)
- scope: NTO
- parent: ogit/Node

## attributes

- optional:
  - [ogit/Data/timeToLive](#)
  - [ogit/description](#)
  - [ogit/name](#)

## incoming edges

- [ogit/generates](#) <= [ogit/Automation/MARSNode](#)

1.1.0.32 [ogit/Network/NetworkInterface](#)

Logical or physical network interface.

- id: <http://www.purl.org/ogit/Network/NetworkInterface>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: NTO
- parent: [ogit/Node](#)

## attributes

- optional:
  - [ogit/id](#)

## incoming edges

- [ogit/contains](#) <= [ogit/Automation/MARSNode](#)

1.1.0.33 [ogit/ServiceManagement/Report](#)

Reporting about IT service delivery

- id: <http://www.purl.org/ogit/ServiceManagement/Report>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: NTO
- parent: [ogit/Node](#)

## attributes

- optional:
  - [ogit/id](#)
  - [ogit/name](#)
  - [ogit/version](#)

## outgoing edges

- [ogit/relates](#) => [ogit/Automation/MARSNode](#)

1.1.0.34 [ogit/ServiceManagement/Offering](#)

This is a concrete offering from a vendor including one or more combined services from a catalog/collection/offering book.

- id: <http://www.purl.org/ogit/ServiceManagement/Offering>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: NTO
- parent: [ogit/Node](#)

## attributes

- mandatory:
  - [ogit/id](#)
  - [ogit/name](#)
- optional:
  - [ogit/ServiceManagement/allowedForNewBusiness](#)
  - [ogit/capacityAvailable](#)
  - [ogit/category](#)
  - [ogit/currency](#)
  - [ogit/description](#)
  - [ogit/expirationDate](#)
  - [ogit/market](#)
  - [ogit/serialNumber](#)
  - [ogit/validFrom](#)

## outgoing edges

- [ogit/specifies](#) => [ogit/Automation/MARSModelTemplate](#)

1.1.0.35 [ogit/Automation/MARSModelTemplate](#)

Represents a set of interconnected MARSNodes, which will be used to define a vendor implementation template of an ordered service offering.

- id: <http://www.purl.org/ogit/Automation/MARSModelTemplate>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: NTO
- parent: [ogit/Node](#)

## attributes

- mandatory:
  - [ogit/name](#)
- optional:
  - [ogit/description](#)

## incoming edges

- [ogit/plans](#) <= [ogit/Cost/PlanningTemplate](#)
- [ogit/specifies](#) <= [ogit/ServiceManagement/Offering](#)

## outgoing edges

- [ogit/contains](#) => [ogit/Automation/MARSNodeTemplate](#)

1.1.0.36 [ogit/Environment](#)

An environment describes the overall structure a user, computer or program operates in.

- id: <http://www.purl.org/ogit/Environment>
- valid-from: Thu Feb 08 00:00:00 UTC 2018
- creator: Viktor Voss
- scope: SGO
- parent: [ogit/Node](#)

## attributes

- optional:
  - [ogit/name](#)

## outgoing edges

- [ogit/consistsOf](#) => [ogit/Automation/MARSNode](#)

1.1.0.37 [ogit/MARS/Resource](#)

Vertices of this type are the 'R'-nodes in the MARS model. 'R' stands for 'Resource' and those nodes form the second highest layer in the A-R-S-M layer model. A 'Resource' node groups 'Software' nodes. It's up to the user whether this grouping is used to group software instance of the same software (e.g. all instances of an Oracle RAC) or software instance of different softwares (functional grouping, e.g. 'persistence')

- id: <http://www.purl.org/ogit/MARS/Resource>
- valid-from: Fri Jun 01 00:00:00 UTC 2018
- creator: FCO
- scope: NTO
- parent: [ogit/Node](#)

**attributes**

- mandatory:
  - [ogit/MARS/Resource/class](#)
  - [ogit/name](#)
- optional:
  - [ogit/Automation/automationState](#)
  - [ogit/Automation/lifecycle](#)
  - [ogit/Automation/marsNodeType](#)
  - [ogit/Automation/serviceStatus](#)
  - [ogit/url](#)

**outgoing edges**

- [ogit/uses](#) => [ogit/Automation/Configuration](#)

**1.1.0.38 ogit/Person**

A Person represents a human identity.

- id: <http://www.purl.org/ogit/Person>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: SGO
- parent: ogit/Node

**attributes**

- optional:
  - [ogit/alternativeName](#)
  - [ogit/email](#)
  - [ogit/fax](#)
  - [ogit/firstName](#)
  - [ogit/lastName](#)
  - [ogit/middleName](#)
  - [ogit/mobilePhone](#)
  - [ogit/notification](#)
  - [ogit/officePhone](#)
  - [ogit/otherPhone](#)
  - [ogit/position](#)
  - [ogit/sourceId](#)
  - [ogit/status](#)
  - [ogit/title](#)
  - [ogit/webPage](#)



## incoming edges

- [ogit/assignedTo](#) <= [ogit/Automation/MARSNode](#)

1.1.0.39 [ogit/Location](#)

A place where some service is offered or requested. In many cases this will be related to an address of an Organization. Similar to <http://purl.org/goodrelations/v1#Location>

- id: <http://www.purl.org/ogit/Location>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: SGO
- parent: [ogit/Node](#)

## attributes

- mandatory:
  - [ogit/name](#)
- optional:
  - [ogit/description](#)

## incoming edges

- [ogit/locatedIn](#) <= [ogit/Automation/MARSNode](#)

1.1.0.40 [ogit/Automation/History](#)

IssueHistoryEntry corresponds to element <HistoryEntry> from IssueOutputSchema.

- id: <http://www.purl.org/ogit/Automation/History>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: NTO
- parent: [ogit/Node](#)

## attributes

- mandatory:
  - [ogit/Automation/affectedNodeid](#)
  - [ogit/Automation/command](#)
  - [ogit/Automation/knowledgeItemId](#)
  - [ogit/Automation/logLevel](#)
  - [ogit/message](#)
  - [ogit/timestamp](#)

## incoming edges

- [ogit/generates](#) <= [ogit/Automation/AutomationIssue](#)

## outgoing edges

- [ogit/generates](#) => [ogit/Timeseries](#)

## 1.1.0.41 ogit/Asset

Assets represent a physical hold of a value and are situated in a location. Assets could correspond to one or more ogit/Automation/MARSNode's and can be physical or virtual. Assets of a Service Provider include anything that could contribute to the delivery of a Service. Assets can have a type, for example: Management, Organisation, Process, Knowledge, People, Information, Applications, Infrastructure, Financial Capital.

- id: <http://www.purl.org/ogit/Asset>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: SGO
- parent: ogit/Node

## attributes

- optional:
  - [ogit/id](#)
  - [ogit/name](#)

## outgoing edges

- [ogit/describes](#) => [ogit/Automation/MARSNodeTemplate](#)
- [ogit/describes](#) => [ogit/Automation/MARSNode](#)

## 1.1.0.42 ogit/Knowledge/AcquisitionSession

Entity to describe a Knowledge Acquisition Session, linking to Conversation, Structured Task Steps and the Knowledge

- id: <http://www.purl.org/ogit/Knowledge/AcquisitionSession>
- valid-from: Tue Mar 14 00:00:00 UTC 2017
- creator: [cwalker@arago.de](mailto:cwalker@arago.de)
- scope: NTO
- parent: ogit/Node

## incoming edges

- [ogit/relates](#) <= [ogit/Automation/AutomationIssue](#)

## outgoing edges

- [ogit/defines](#) => [ogit/Automation/KnowledgeItem](#)

## 1.1.0.43 ogit/Task

A task is a unit of execution.

- id: <http://www.purl.org/ogit/Task>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: SGO
- parent: ogit/Node

## attributes

- optional:
  - [ogit/description](#)
  - [ogit/id](#)
  - [ogit/name](#)
  - [ogit/positionNumber](#)
  - [ogit/question](#)
  - [ogit/response](#)
  - [ogit/status](#)
  - [ogit/type](#)

## incoming edges

- [ogit/contains](#) <= [ogit/Automation/AutomationIssue](#)
- [ogit/solves](#) <= [ogit/Automation/KnowledgeItem](#)

## 1.1.0.44 ogit/Event

This entity defines any type of event records, e.g. ITSM/produced by event management systems, Business Process etc.

- id: <http://www.purl.org/ogit/Event>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: SGO
- parent: ogit/Node

**attributes**

- mandatory:
  - [ogit/id](#)
  - [ogit/name](#)
- optional:
  - [ogit/ServiceManagement/reportedSource](#)
  - [ogit/acknowledgeState](#)
  - [ogit/category](#)
  - [ogit/certainty](#)
  - [ogit/description](#)
  - [ogit/expiresAt](#)
  - [ogit/firstOccurredAt](#)
  - [ogit/impact](#)
  - [ogit/instance](#)
  - [ogit/isRoot](#)
  - [ogit/lastClearedAt](#)
  - [ogit/lastOccurredAt](#)
  - [ogit/lastUpdatedAt](#)
  - [ogit/maintenanceState](#)
  - [ogit/occurenceCount](#)
  - [ogit/openedAt](#)
  - [ogit/priority](#)
  - [ogit/resource](#)
  - [ogit/severity](#)
  - [ogit/sourceId](#)
  - [ogit/status](#)
  - [ogit/summary](#)
  - [ogit/type](#)

**outgoing edges**

- [ogit/affects](#) => [ogit/Automation/MARSNode](#)
- [ogit/corresponds](#) => [ogit/Automation/AutomationIssue](#)
- [ogit/relates](#) => [ogit/Automation/MARSNode](#)

**1.1.0.45 ogit/Forum/KnowledgeBundleHistory**

A point-in-time snapshot of an [ogit/Forum/KnowledgeBundle](#)

- id: <http://www.purl.org/ogit/Forum/KnowledgeBundleHistory>
- valid-from: Mon Apr 27 00:00:00 UTC 2015
- creator: [cwalker@arago.de](mailto:cwalker@arago.de)
- scope: NTO
- parent: [ogit/Node](#)

## attributes

- mandatory:
  - [ogit/name](#)
- optional:
  - [ogit/accessControl](#)

## outgoing edges

- [ogit/contains](#) => [ogit/Automation/AutomationIssue](#)
- [ogit/contains](#) => [ogit/Automation/KnowledgeItem](#)

1.1.0.46 [ogit/Forum/Profile](#)

A User's persona within a forum. Linked to an [ogit/Identity](#) but separate, the Profile is the root node for most operations with a Forum.

- id: <http://www.purl.org/ogit/Forum/Profile>
- valid-from: Mon Apr 27 00:00:00 UTC 2015
- creator: [cwalker@arago.de](mailto:cwalker@arago.de)
- scope: NTO
- parent: [ogit/Node](#)

## attributes

- mandatory:
  - [ogit/Forum/username](#)
  - [ogit/name](#)

## incoming edges

- [ogit/connects](#) <= [ogit/Automation/KnowledgeItem](#)

## outgoing edges

- [ogit/Forum/downloads](#) => [ogit/Automation/KnowledgeItem](#)
- [ogit/creates](#) => [ogit/Automation/AutomationIssue](#)
- [ogit/creates](#) => [ogit/Automation/KnowledgeItem](#)

## 1.1.0.47 ogit/Software/SoftwareComponent

Any type of Software Component

- id: <http://www.purl.org/ogit/Software/SoftwareComponent>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: NTO
- parent: ogit/Node

## attributes

- optional:
  - [ogit/id](#)

## outgoing edges

- [ogit/uses](#) => [ogit/Automation/MARSNode](#)

## 1.1.0.48 ogit/Forum/Post

A Post is an online publication. Could be a blog post, or a posting on a forum/messageboard.

- id: <http://www.purl.org/ogit/Forum/Post>
- valid-from: Mon Apr 27 00:00:00 UTC 2015
- creator: [cwalker@arago.de](mailto:cwalker@arago.de)
- scope: NTO
- parent: ogit/Node

## attributes

- mandatory:
  - [ogit/content](#)

## incoming edges

- [ogit/connects](#) <= [ogit/Automation/KnowledgeItem](#)

## outgoing edges

- [ogit/connects](#) => [ogit/Automation/KnowledgeItem](#)

#### 1.1.0.49 ogit/Automation/DynamicEngineData

Dynamic information exists within the arago Automation Engine (aAE) used to store volatile data about current state of MARSNode or AutomationIssue.

- id: <http://www.purl.org/ogit/Automation/DynamicEngineData>
- valid-from: Thu Jun 25 00:00:00 UTC 2015
- creator: Mirosław Glusiuk
- scope: NTO
- parent: ogit/Node

##### attributes

- optional:
  - [ogit/creationTime](#)
  - [ogit/modificationTime](#)
  - [ogit/name](#)

##### incoming edges

- [ogit/contains](#) ≤ [ogit/Automation/AutomationIssue](#)
- [ogit/contains](#) ≤ [ogit/Automation/DynamicEngineData](#)
- [ogit/contains](#) ≤ [ogit/Automation/MARSNode](#)

##### outgoing edges

- [ogit/contains](#) ⇒ [ogit/Automation/DynamicEngineData](#)

#### 1.1.0.50 ogit/Automation/AutomationIssue

Dynamic information exists within an automation engine in the form of Issues otherwise referred to as Task or Situational Data. From the technical perspective an Issue is a number of attributes (Key/Value tuples) with unique names. From the logical point of view Issues contain information about the change of states on a system. Issues can be injected into an automation engine from external systems e.g. Monitoring or result from the execution of a Knowledge Item. By comparing an Issue with the Issue Condition of a Knowledge Item an automation engine decides which Knowledge Items are processed in which order. If multiple Knowledge Items can be applied to an Issue the KI with the more precisely defined IssueCondition is processed first.

- id: <http://www.purl.org/ogit/Automation/AutomationIssue>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: NTO
- parent: ogit/Node

**attributes**

- optional:
  - [ogit/Automation/deployStatus](#)
  - [ogit/Automation/isDeployed](#)
  - [ogit/Automation/issueFormalRepresentation](#)
  - [ogit/Automation/issueType](#)
  - [ogit/Automation/originNode](#)
  - [ogit/Automation/processingNode](#)
  - [ogit/Automation/processingTimestamp](#)
  - [ogit/creationTime](#)
  - [ogit/modificationTime](#)
  - [ogit/status](#)
  - [ogit/subject](#)

**incoming edges**

- [ogit/connects](#) <= [ogit/Forum/Workflow](#)
- [ogit/contains](#) <= [ogit/Forum/KnowledgeBundle](#)
- [ogit/contains](#) <= [ogit/Forum/KnowledgeBundleHistory](#)
- [ogit/corresponds](#) <= [ogit/ServiceManagement/ChangeRequest](#)
- [ogit/corresponds](#) <= [ogit/ServiceManagement/Incident](#)
- [ogit/corresponds](#) <= [ogit/ServiceManagement/Problem](#)
- [ogit/corresponds](#) <= [ogit/ServiceManagement/SubTask](#)
- [ogit/corresponds](#) <= [ogit/ServiceManagement/Ticket](#)
- [ogit/corresponds](#) <= [ogit/Event](#)
- [ogit/creates](#) <= [ogit/Forum/Profile](#)
- [ogit/relates](#) <= [ogit/Forum/FeedEntry](#)
- [ogit/worksOn](#) <= [ogit/Automation/KnowledgeItem](#)

**outgoing edges**

- [ogit/associates](#) => [ogit/Question](#)
- [ogit/contains](#) => [ogit/Task](#)
- [ogit/contains](#) => [ogit/Automation/DynamicEngineData](#)
- [ogit/contains](#) => [ogit/Automation/Item](#)
- [ogit/generates](#) => [ogit/Timeseries](#)
- [ogit/generates](#) => [ogit/Automation/History](#)
- [ogit/relates](#) => [ogit/Knowledge/AcquisitionSession](#)
- [ogit/relates](#) => [ogit/Automation/MARSNode](#)
- [ogit/worksOn](#) => [ogit/Automation/MARSNode](#)



## 1.1.0.51 ogit/Automation/MARSModel

A collection of MARSNodes allows to address all MARS nodes belonging together in a certain way at once the relationship from MARSModel to MARSNode is 'ogit/contains'. examples are: All MARS nodes describing the IT of one data center, or all MARS nodes associated with the same contract. In such cases you would connect the other entity (data center, contract) with the MARSModel node instead creating links to any MARSNode being part of that model.

- id: <http://www.purl.org/ogit/Automation/MARSModel>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: NTO
- parent: ogit/Node

## attributes

- optional:
  - [ogit/description](#)
  - [ogit/name](#)

## outgoing edges

- [ogit/contains](#) => [ogit/Automation/MARSNode](#)
- [ogit/generates](#) => [ogit/Timeseries](#)
- [ogit/implements](#) => [ogit/ServiceManagement/Order](#)

## 1.1.0.52 ogit/Automation/KnowledgeItemAttribute

Contains key-value pairs (together with mode) found inside Issue subitems.

- id: <http://www.purl.org/ogit/Automation/KnowledgeItemAttribute>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: NTO
- parent: ogit/Node

## attributes

- mandatory:
  - [ogit/name](#)
  - [ogit/value](#)
- optional:
  - [ogit/mode](#)

## incoming edges

- [ogit/contains](#) ≤ [ogit/Automation/Item](#)

1.1.0.53 [ogit/Automation/Variable](#)

Variable definition to be used in KnowledgeItem

- id: <http://www.purl.org/ogit/Automation/Variable>
- valid-from: Mon Feb 09 00:00:00 UTC 2015
- creator: Kaushik Gondaliya
- scope: NTO
- parent: [ogit/Node](#)

## attributes

- mandatory:
  - [ogit/Automation/todo](#)
  - [ogit/\\_id](#)
  - [ogit/accessControl](#)
  - [ogit/creator](#)
  - [ogit/description](#)
  - [ogit/name](#)
- optional:
  - [ogit/\\_tags](#)

1.1.0.54 [ogit/Forum/Tag](#)

A Tag used to categorise content. The required `key` attribute should be used as the unique identifier, and the `name` considered a display name.

- id: <http://www.purl.org/ogit/Forum/Tag>
- valid-from: Mon Apr 27 00:00:00 UTC 2015
- creator: [cwalker@arago.de](mailto:cwalker@arago.de)
- scope: NTO
- parent: [ogit/Node](#)

## attributes

- mandatory:
  - [ogit/name](#)

## outgoing edges

- [ogit/assignedTo](#) => [ogit/Automation/KnowledgeItem](#)

1.1.0.55 [ogit/Automation/KnowledgePool](#)

A grouping of [ogit/Automation/KnowledgeItems](#) and [ogit/Automation/KnowledgeBundles](#) for user or automation engine.

- id: <http://www.purl.org/ogit/Automation/KnowledgePool>
- valid-from: Mon Apr 27 00:00:00 UTC 2015
- creator: [druss@arago.de](mailto:druss@arago.de)
- scope: NTO
- parent: [ogit/Node](#)

## attributes

- mandatory:
  - [ogit/name](#)

## incoming edges

- [ogit/uses](#) <= [ogit/Automation/Configuration](#)
- [ogit/uses](#) <= [ogit/OSLC-crtv/ServiceInstance](#)

## outgoing edges

- [ogit/contains](#) => [ogit/Automation/KnowledgeBundle](#)
- [ogit/contains](#) => [ogit/Automation/KnowledgeItem](#)
- [ogit/uses](#) => [ogit/Automation/KnowledgeItem](#)

1.1.0.56 [ogit/Automation/Configuration](#)

Configuration node to dynamically connect Knowledge Pools or Rankings to a HIRO installation.

- id: <http://www.purl.org/ogit/Automation/Configuration>
- valid-from: Wed Apr 25 00:00:00 UTC 2018
- creator: [cy@arago.de](mailto:cy@arago.de)
- scope: NTO
- parent: [ogit/Node](#)

## incoming edges

- [ogit/uses](#) <= [ogit/Automation/MARSNode](#)
- [ogit/uses](#) <= [ogit/MARS/Resource](#)

## outgoing edges

- [ogit/uses](#) => [ogit/Automation/KIRanking](#)
- [ogit/uses](#) => [ogit/Automation/KnowledgePool](#)

1.1.0.57 [ogit/Automation/Trigger](#)

Trigger of a KI having a set of Subitems.

- id: <http://www.purl.org/ogit/Automation/Trigger>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: NTO
- parent: [ogit/Node](#)

## attributes

- mandatory:
  - [ogit/description](#)

## incoming edges

- [ogit/contains](#) <= [ogit/Automation/KnowledgeItem](#)

## outgoing edges

- [ogit/contains](#) => [ogit/Automation/Item](#)

1.1.0.58 [ogit/ServiceManagement/Service](#)

A technology service item, which combined or not with other technology services can constitute a service offering ([ogit/ServiceManagement/Offering](#)).

- id: <http://www.purl.org/ogit/ServiceManagement/Service>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: NTO
- parent: [ogit/Node](#)

**attributes**

- mandatory:
  - [ogit/id](#)
- optional:
  - [ogit/description](#)
  - [ogit/name](#)
  - [ogit/uri](#)

**incoming edges**

- [ogit/affects](#) <= [ogit/Automation/MARSNode](#)

**1.1.0.59 ogit/ServiceManagement/Ticket**

This entity defines any type of tickets. For specific behaviour of tickets, please check specific entities (e.g. [ogit/ServiceManagement/Incident](#)).

- id: <http://www.purl.org/ogit/ServiceManagement/Ticket>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: NTO
- parent: [ogit/Node](#)

**attributes**

- mandatory:
  - [ogit/id](#)
- optional:
  - [ogit/ServiceManagement/externalTicketId](#)
  - [ogit/ServiceManagement/reportedSource](#)
  - [ogit/ServiceManagement/sourceStatus](#)
  - [ogit/ServiceManagement/ticketId](#)
  - [ogit/closedAt](#)
  - [ogit/createdAt](#)
  - [ogit/description](#)
  - [ogit/impact](#)
  - [ogit/lastUpdatedAt](#)
  - [ogit/openedAt](#)
  - [ogit/priority](#)
  - [ogit/project](#)
  - [ogit/summary](#)
  - [ogit/urgency](#)

## outgoing edges

- [ogit/affects](#) => [ogit/Automation/MARSNode](#)
- [ogit/corresponds](#) => [ogit/Automation/AutomationIssue](#)
- [ogit/reportedOn](#) => [ogit/Automation/MARSNode](#)

## 1.1.0.60 ogit/License

This entity type allows to store license information or actual licenses.

- id: <http://www.purl.org/ogit/License>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: SGO
- parent: ogit/Node

## attributes

- optional:
  - [ogit/createdAt](#)
  - [ogit/creator](#)
  - [ogit/deadline](#)
  - [ogit/expirationDate](#)
  - [ogit/id](#)
  - [ogit/licenseKey](#)
  - [ogit/licenseType](#)
  - [ogit/subject](#)
  - [ogit/validFrom](#)
  - [ogit/validTo](#)

## incoming edges

- [ogit/relates](#) <= [ogit/Automation/MARSNode](#)

## 1.1.0.61 ogit/Cost/CostElement

The cost element is a type of cost for an activity, an ordered service or a business unit or budget. There are 3 levels of cost elements: Top Level, Middle Level, Bottom Level. Between the different levels, for each cost element there could be two types of edges: Incoming and Outgoing. Each type of edge could have two types of connections: [consistsOf](#) and [contributesTo](#). E.g. a cost element CPU consists in 30% of a HR cost element. The HR cost element contributes in 40% to the cost of the CPU cost element. This percentage values will then be saved in the entity Distribution, which will be connected to the cost element. For a general overview: see the NTO description on github.

- id: <http://www.purl.org/ogit/Cost/CostElement>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: NTO
- parent: ogit/Node

## incoming edges

- [ogit/associates](#) <= [ogit/Automation/MARSNode](#)
- [ogit/associates](#) <= [ogit/Automation/MARSNodeTemplate](#)

1.1.0.62 [ogit/Timeseries](#)

A time series is a sequence of data points, measured typically at successive points in time spaced at uniform time intervals.

- id: <http://www.purl.org/ogit/Timeseries>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: SGO
- parent: [ogit/Node](#)

## attributes

- optional:
  - [ogit/description](#)
  - [ogit/instance](#)
  - [ogit/name](#)
  - [ogit/unit](#)

## incoming edges

- [ogit/defines](#) <= [ogit/Automation/MAID](#)
- [ogit/generates](#) <= [ogit/Automation/AutomationIssue](#)
- [ogit/generates](#) <= [ogit/Automation/History](#)
- [ogit/generates](#) <= [ogit/Automation/KnowledgeItem](#)
- [ogit/generates](#) <= [ogit/Automation/MAID](#)
- [ogit/generates](#) <= [ogit/Automation/MARSModel](#)
- [ogit/generates](#) <= [ogit/Automation/MARSNode](#)

1.1.0.63 [ogit/Forum/FeedEntry](#)

A single entry in a newsfeed or other stream of items. Unlikely to contain many attributes of its own, more likely to link users with items describing the event.

- id: <http://www.purl.org/ogit/Forum/FeedEntry>
- valid-from: Mon Apr 27 00:00:00 UTC 2015
- creator: [cwalker@arago.de](mailto:cwalker@arago.de)
- scope: NTO
- parent: [ogit/Node](#)

## outgoing edges

- [ogit/relates](#) => [ogit/Automation/AutomationIssue](#)

## 1.2 Verbs

### 1.2.0.1 ogit/contains

This relationship indicates that something is part of something else. see also "includes"

- id: <http://www.purl.org/ogit/contains>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

#### Allowed Connection

- [ogit/Automation/AutomationIssue](#) => [ogit/Task](#)
- [ogit/Automation/AutomationIssue](#) => [ogit/Automation/DynamicEngineData](#)
- [ogit/Automation/AutomationIssue](#) => [ogit/Automation/Item](#)
- [ogit/Automation/DynamicEngineData](#) => [ogit/Automation/DynamicEngineData](#)
- [ogit/Automation/Item](#) => [ogit/Automation/KnowledgeItemAttribute](#)
- [ogit/Automation/Item](#) => [ogit/Automation/Item](#)
- [ogit/Automation/KnowledgeBundle](#) => [ogit/Automation/KnowledgeItem](#)
- [ogit/Automation/KnowledgeItem](#) => [ogit/Automation/Trigger](#)
- [ogit/Automation/KnowledgePool](#) => [ogit/Automation/KnowledgeBundle](#)
- [ogit/Automation/KnowledgePool](#) => [ogit/Automation/KnowledgeItem](#)
- [ogit/Automation/MARSModel](#) => [ogit/Automation/MARSNode](#)
- [ogit/Automation/MARSModelTemplate](#) => [ogit/Automation/MARSNodeTemplate](#)
- [ogit/Automation/MARSNode](#) => [ogit/Network/NetworkInterface](#)
- [ogit/Automation/MARSNode](#) => [ogit/Automation/MARSNode](#)
- [ogit/Automation/MARSNode](#) => [ogit/Automation/DynamicEngineData](#)
- [ogit/Automation/Trigger](#) => [ogit/Automation/Item](#)
- [ogit/Forum/KnowledgeBundle](#) => [ogit/Automation/AutomationIssue](#)
- [ogit/Forum/KnowledgeBundle](#) => [ogit/Automation/KnowledgeItem](#)
- [ogit/Forum/KnowledgeBundleHistory](#) => [ogit/Automation/AutomationIssue](#)
- [ogit/Forum/KnowledgeBundleHistory](#) => [ogit/Automation/KnowledgeItem](#)

### 1.2.0.2 ogit/defines

General relationship indicating that some entity defines some other.

- id: <http://www.purl.org/ogit/defines>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem



**Allowed Connection**

- [ogit/Automation/MAID](#) => [ogit/Timeseries](#)
- [ogit/Knowledge/AcquisitionSession](#) => [ogit/Automation/KnowledgeItem](#)

**1.2.0.3 ogit/hosts**

verb which shows that an entity is hosted in another entity.

- id: <http://www.purl.org/ogit/hosts>
- valid-from: Thu Oct 15 00:00:00 UTC 2015
- creator: Aymen Ayoub

**Allowed Connection**

- [ogit/Automation/MARSNode](#) => [ogit/Automation/MARSNode](#)

**1.2.0.4 ogit/runsOn**

Shows if a certain component is running on another component.

- id: <http://www.purl.org/ogit/runsOn>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

**Allowed Connection**

- [ogit/Automation/MARSNode](#) => [ogit/Automation/MARSNode](#)

**1.2.0.5 ogit/worksOn**

Indicates if one entity is currently working on another entity.

- id: <http://www.purl.org/ogit/worksOn>
- valid-from: Wed Jun 24 00:00:00 UTC 2015
- creator: Peter Larem

**Allowed Connection**

- [ogit/Automation/AutomationIssue](#) => [ogit/Automation/MARSNode](#)
- [ogit/Automation/KnowledgeItem](#) => [ogit/Automation/AutomationIssue](#)

### 1.2.0.6 ogit/assignedTo

Verb expressing which entity could be assigned to which another entity.

- id: <http://www.purl.org/ogit/assignedTo>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

#### Allowed Connection

- [ogit/Automation/MARSNode](#) => [ogit/Person](#)
- [ogit/Forum/Tag](#) => [ogit/Automation/KnowledgeItem](#)

### 1.2.0.7 ogit/generates

Verb indicating if an entity generates another entity.

- id: <http://www.purl.org/ogit/generates>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

#### Allowed Connection

- [ogit/Automation/AutomationIssue](#) => [ogit/Timeseries](#)
- [ogit/Automation/AutomationIssue](#) => [ogit/Automation/History](#)
- [ogit/Automation/History](#) => [ogit/Timeseries](#)
- [ogit/Automation/KnowledgeItem](#) => [ogit/Timeseries](#)
- [ogit/Automation/MAID](#) => [ogit/Timeseries](#)
- [ogit/Automation/MARSModel](#) => [ogit/Timeseries](#)
- [ogit/Automation/MARSNode](#) => [ogit/Data/Log](#)
- [ogit/Automation/MARSNode](#) => [ogit/Timeseries](#)

### 1.2.0.8 ogit/specifies

One entity "specifies" another.

- id: <http://www.purl.org/ogit/specifies>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

**Allowed Connection**

- [ogit/Forum/ShortId](#) => [ogit/Automation/KnowledgeItem](#)
- [ogit/ServiceManagement/Offering](#) => [ogit/Automation/MARSModelTemplate](#)

**1.2.0.9 ogit/solves**

One entity can "solve" another.

- id: <http://www.purl.org/ogit/solves>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

**Allowed Connection**

- [ogit/Automation/KnowledgeItem](#) => [ogit/Task](#)

**1.2.0.10 ogit/forks**

General relationship indicating that some entity forks some other, assuming the same type.

- id: <http://www.purl.org/ogit/forks>
- valid-from: Tue Jun 12 00:00:00 UTC 2018
- creator: Vitaly Teremasov

**Allowed Connection**

- [ogit/Automation/KnowledgeItem](#) => [ogit/Automation/KnowledgeItem](#)

**1.2.0.11 ogit/derivesFrom**

The derivesFrom of a version. This verb could be generated internally.

- id: <http://www.purl.org/ogit/derivesFrom>
- valid-from: Tue Oct 31 00:00:00 UTC 2017
- creator: [druss@arago.de](mailto:druss@arago.de)

**Allowed Connection**

- [ogit/Automation/KnowledgeBundle](#) => [ogit/Automation/KnowledgeBundle](#)
- [ogit/Automation/KnowledgeItem](#) => [ogit/Automation/KnowledgeItem](#)

## 1.2.0.12 ogit/describes

This relationship allows to associate additional information with an entity. The "described" node can have many "describing" nodes.

- id: <http://www.purl.org/ogit/describes>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

## Allowed Connection

- [ogit/Asset](#) => [ogit/Automation/MARSNodeTemplate](#)
- [ogit/Asset](#) => [ogit/Automation/MARSNode](#)

## 1.2.0.13 ogit/creates

Indicates if one entity creates another one.

- id: <http://www.purl.org/ogit/creates>
- valid-from: Tue May 19 00:00:00 UTC 2015
- creator: Peter Larem

## Allowed Connection

- [ogit/Forum/Profile](#) => [ogit/Automation/AutomationIssue](#)
- [ogit/Forum/Profile](#) => [ogit/Automation/KnowledgeItem](#)

## 1.2.0.14 ogit/associates

Verb indicating if an entity associates with another entity.

- id: <http://www.purl.org/ogit/associates>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

## Allowed Connection

- [ogit/Automation/AutomationIssue](#) => [ogit/Question](#)
- [ogit/Automation/MARSNode](#) => [ogit/Cost/CostElement](#)
- [ogit/Automation/MARSNodeTemplate](#) => [ogit/Cost/CostElement](#)

## 1.2.0.15 ogit/connects

Verb showing that an entity is physically/virtually connecting to another entity.

- id: <http://www.purl.org/ogit/connects>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

## Allowed Connection

- [ogit/Automation/KnowledgeItem](#) => [ogit/Forum/WorkflowStep](#)
- [ogit/Automation/KnowledgeItem](#) => [ogit/Forum/KnowledgeItemHistory](#)
- [ogit/Automation/KnowledgeItem](#) => [ogit/Forum/Profile](#)
- [ogit/Automation/KnowledgeItem](#) => [ogit/Forum/Topic](#)
- [ogit/Automation/KnowledgeItem](#) => [ogit/Comment](#)
- [ogit/Automation/KnowledgeItem](#) => [ogit/Forum/Reply](#)
- [ogit/Automation/KnowledgeItem](#) => [ogit/Forum/KnowledgeBundle](#)
- [ogit/Automation/KnowledgeItem](#) => [ogit/Automation/KnowledgeItem](#)
- [ogit/Automation/KnowledgeItem](#) => [ogit/Forum/Post](#)
- [ogit/Automation/KnowledgeItem](#) => [ogit/Hyperlink](#)
- [ogit/Forum/KnowledgeBundle](#) => [ogit/Automation/KnowledgeItem](#)
- [ogit/Forum/KnowledgeItemHistory](#) => [ogit/Automation/KnowledgeItem](#)
- [ogit/Forum/Post](#) => [ogit/Automation/KnowledgeItem](#)
- [ogit/Forum/Reply](#) => [ogit/Automation/KnowledgeItem](#)
- [ogit/Forum/Workflow](#) => [ogit/Automation/AutomationIssue](#)
- [ogit/Forum/WorkflowStep](#) => [ogit/Automation/KnowledgeItem](#)
- [ogit/Comment](#) => [ogit/Automation/KnowledgeItem](#)

## 1.2.0.16 ogit/deployedTo

Verb associates if something was deployed to another entity/component.

- id: <http://www.purl.org/ogit/deployedTo>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

## Allowed Connection

- [ogit/Automation/KnowledgeItem](#) => [ogit/OSLC-crtv/ServiceInstance](#)
- [ogit/Automation/MARSNode](#) => [ogit/Automation/MARSNode](#)

## 1.2.0.17 ogit/locatedIn

indicate that something has its place somewhere

- id: <http://www.purl.org/ogit/locatedIn>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

## Allowed Connection

- [ogit/Automation/MARSNode](#) => [ogit/Location](#)
- [ogit/Automation/MARSNode](#) => [ogit/Region](#)

## 1.2.0.18 ogit/versions

The version of a node. This verb is generated internally.

- id: <http://www.purl.org/ogit/versions>
- valid-from: Tue Oct 31 00:00:00 UTC 2017
- creator: [druss@arago.de](mailto:druss@arago.de)

## Allowed Connection

- [ogit/VersioningData](#) => [ogit/Automation/KnowledgeBundle](#)
- [ogit/VersioningData](#) => [ogit/Automation/KnowledgeItem](#)

## 1.2.0.19 ogit/corresponds

Indicates whether one entity could correspond to a more general one, e.g. an Incident could correspond to a Ticket

- id: <http://www.purl.org/ogit/corresponds>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

## Allowed Connection

- [ogit/Automation/MARSNode](#) => [ogit/Software/Application](#)
- [ogit/ServiceManagement/ChangeRequest](#) => [ogit/Automation/AutomationIssue](#)
- [ogit/ServiceManagement/Incident](#) => [ogit/Automation/AutomationIssue](#)
- [ogit/ServiceManagement/Problem](#) => [ogit/Automation/AutomationIssue](#)
- [ogit/ServiceManagement/SubTask](#) => [ogit/Automation/AutomationIssue](#)
- [ogit/ServiceManagement/Ticket](#) => [ogit/Automation/AutomationIssue](#)
- [ogit/ConfigurationItem](#) => [ogit/Automation/MARSNode](#)
- [ogit/Event](#) => [ogit/Automation/AutomationIssue](#)

## 1.2.0.20 ogit/Forum/rates

This verb represents the `Rating` between two nodes

- id: <http://www.purl.org/ogit/Forum/rates>
- valid-from: Wed Aug 12 00:00:00 UTC 2015
- creator: [bneal@arago.de](mailto:bneal@arago.de)

## Allowed Connection

- [ogit/Forum/Rating](#) => [ogit/Automation/KnowledgeItem](#)

## 1.2.0.21 ogit/affects

The relationship indicates that one entity affects some other entity.

- id: <http://www.purl.org/ogit/affects>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

## Allowed Connection

- [ogit/Automation/MARSNode](#) => [ogit/ServiceManagement/Service](#)
- [ogit/Automation/MARSNode](#) => [ogit/Automation/MARSNode](#)
- [ogit/ServiceManagement/ChangeRequest](#) => [ogit/Automation/MARSNode](#)
- [ogit/ServiceManagement/Incident](#) => [ogit/Automation/MARSNode](#)
- [ogit/ServiceManagement/Order](#) => [ogit/Automation/MARSNode](#)
- [ogit/ServiceManagement/Problem](#) => [ogit/Automation/MARSNode](#)
- [ogit/ServiceManagement/Ticket](#) => [ogit/Automation/MARSNode](#)
- [ogit/Event](#) => [ogit/Automation/MARSNode](#)

## 1.2.0.22 ogit/OSLC-crtv/runsOn

The ComputerSystem this SoftwareServer instance is running on.

- id: <http://www.purl.org/ogit/OSLC-crtv/runsOn>
- valid-from: Thu Sep 22 00:00:00 UTC 2016
- creator: OGIT Importer
- cardinality: many2many

**Allowed Connection**

- [ogit/OSLC-crtv/ServiceInstance](#) => [ogit/Automation/MARSNode](#)

**1.2.0.23 ogit/implements**

Defines that an entity provides the implementation for another entity.

- id: <http://www.purl.org/ogit/implements>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

**Allowed Connection**

- [ogit/Automation/MARSModel](#) => [ogit/ServiceManagement/Order](#)

**1.2.0.24 ogit/provides**

Verb showing if one entity provides something to another.

- id: <http://www.purl.org/ogit/provides>
- valid-from: Fri Jul 24 00:00:00 UTC 2015
- creator: Aymen Ayoub

**Allowed Connection**

- [ogit/Automation/MARSNode](#) => [ogit/Automation/MARSNode](#)

**1.2.0.25 ogit/owns**

This relationship indicates that one entity owns some other.

- id: <http://www.purl.org/ogit/owns>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

**Allowed Connection**

- [ogit/Organization](#) => [ogit/Automation/MARSNode](#)



## 1.2.0.26 ogit/dependsOn

This relationship indicates that some entity is depending on some other. E.g. machine hosts software.

- id: <http://www.purl.org/ogit/dependsOn>
- valid-from: Thu Oct 15 00:00:00 UTC 2015
- creator: Aymen Ayoub

## Allowed Connection

- [ogit/Automation/MARSNode](#) => [ogit/Automation/MARSNode](#)

## 1.2.0.27 ogit/belongs

Verb showing if one entity belongs to another.

- id: <http://www.purl.org/ogit/belongs>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

## Allowed Connection

- [ogit/Attachment](#) => [ogit/Automation/MARSNode](#)

## 1.2.0.28 ogit/uses

This relationship indicates that some entity is used by some other.

- id: <http://www.purl.org/ogit/uses>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

## Allowed Connection

- [ogit/Automation/Configuration](#) => [ogit/Automation/KIRanking](#)
- [ogit/Automation/Configuration](#) => [ogit/Automation/KnowledgePool](#)
- [ogit/Automation/KnowledgePool](#) => [ogit/Automation/KnowledgeItem](#)
- [ogit/Automation/MARSNode](#) => [ogit/Automation/Configuration](#)
- [ogit/MARS/Resource](#) => [ogit/Automation/Configuration](#)
- [ogit/OSLC-crtv/ServiceInstance](#) => [ogit/Automation/KnowledgePool](#)
- [ogit/Software/SoftwareComponent](#) => [ogit/Automation/MARSNode](#)

## 1.2.0.29 ogit/plans

Verb showing how one entity plans/predicts on the content of another entity

- id: <http://www.purl.org/ogit/plans>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

## Allowed Connection

- [ogit/Cost/PlanningTemplate](#) => [ogit/Automation/MARSModelTemplate](#)

## 1.2.0.30 ogit/reportedOn

Indicates where a failure situation was initially observed. In case an incident record is created from an event management system this relationship points to the entity that represents the monitored device/endpoint. We call it "reportedOn" instead of "observedOn" to account for the close relation to "reportedAt", "reportedBy"

- id: <http://www.purl.org/ogit/reportedOn>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

## Allowed Connection

- [ogit/ServiceManagement/ChangeRequest](#) => [ogit/Automation/MARSNode](#)
- [ogit/ServiceManagement/Incident](#) => [ogit/Automation/MARSNode](#)
- [ogit/ServiceManagement/Order](#) => [ogit/Automation/MARSNode](#)
- [ogit/ServiceManagement/Problem](#) => [ogit/Automation/MARSNode](#)
- [ogit/ServiceManagement/Ticket](#) => [ogit/Automation/MARSNode](#)

## 1.2.0.31 ogit/Forum/downloads

This verb represents that a "User" has downloaded a given Bundle

- id: <http://www.purl.org/ogit/Forum/downloads>
- valid-from: Thu Feb 25 00:00:00 UTC 2016
- creator: [bneal@arago.de](mailto:bneal@arago.de)

## Allowed Connection

- [ogit/Forum/Profile](#) => [ogit/Automation/KnowledgeItem](#)

## 1.2.0.32 ogit/consistsOf

It shows, that the destination entity is a non-exclusive part of the source.

- id: <http://www.purl.org/ogit/consistsOf>
- valid-from: Tue Feb 13 00:00:00 UTC 2018
- creator: Aymen Ayoub

## Allowed Connection

- [ogit/Environment](#) => [ogit/Automation/MARSNode](#)

## 1.2.0.33 ogit/relates

General relationship indicating that one entity is related to another one.

- id: <http://www.purl.org/ogit/relates>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

## Allowed Connection

- [ogit/Automation/AutomationIssue](#) => [ogit/Knowledge/AcquisitionSession](#)
- [ogit/Automation/AutomationIssue](#) => [ogit/Automation/MARSNode](#)
- [ogit/Automation/KnowledgeItem](#) => [ogit/Automation/MARSNodeTemplate](#)
- [ogit/Automation/MARSNode](#) => [ogit/Automation/MARSNodeTemplate](#)
- [ogit/Automation/MARSNode](#) => [ogit/Automation/MARSNode](#)
- [ogit/Automation/MARSNode](#) => [ogit/License](#)
- [ogit/Automation/MARSNode](#) => [ogit/Automation/KnowledgeItem](#)
- [ogit/Automation/MARSNodeTemplate](#) => [ogit/Automation/MARSNodeTemplate](#)
- [ogit/Automation/MARSNodeTemplate](#) => [ogit/Automation/MARSNode](#)
- [ogit/Forum/FeedEntry](#) => [ogit/Automation/AutomationIssue](#)
- [ogit/Forum/KnowledgeItemHistory](#) => [ogit/Automation/KnowledgeItem](#)
- [ogit/ServiceManagement/ChangeRequest](#) => [ogit/Automation/MARSNode](#)
- [ogit/ServiceManagement/Report](#) => [ogit/Automation/MARSNode](#)
- [ogit/ConfigurationItem](#) => [ogit/Automation/MARSNode](#)
- [ogit/Event](#) => [ogit/Automation/MARSNode](#)

## 1.3 Attributes

### 1.3.0.1 ogit/\_modified-by

[internally generated] The id of the identity who did the modification

- id: [http://www.purl.org/ogit/\\_modified-by](http://www.purl.org/ogit/_modified-by)
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

### 1.3.0.2 ogit/Automation/serviceType

Contains the Type of a service.

- id: <http://www.purl.org/ogit/Automation/serviceType>
- valid-from: Fri Jul 24 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

### 1.3.0.3 ogit/ciType

Type of a configuration item. For example: VM, Server or Device.

- id: <http://www.purl.org/ogit/ciType>
- valid-from: Thu Aug 20 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

#### 1.3.0.4 ogit/reviewedAt

Defines the time when something was actually reviewed. The values can combin date and time with time zone designator according to ISO 8601. Reviewed time is used in incident management.

- id: <http://www.purl.org/ogit/reviewedAt>
- valid-from: Wed Jul 01 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ServiceManagement/ChangeRequest](#)

#### 1.3.0.5 ogit/Automation/serialNumber

Contains a the serial number of a device/component.

- id: <http://www.purl.org/ogit/Automation/serialNumber>
- valid-from: Fri Jul 24 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

#### 1.3.0.6 ogit/Automation/servletName

Contains the name if the servlet.

- id: <http://www.purl.org/ogit/Automation/servletName>
- valid-from: Fri Jul 24 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

#### 1.3.0.7 ogit/Automation/deployToEngine

Boolean value, true if an automation Knowledge Item can deploy into an Automation Engine.

- id: <http://www.purl.org/ogit/Automation/deployToEngine>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- mandatory:
  - [ogit/Forum/KnowledgeItemHistory](#)
- optional:
  - [ogit/Automation/KnowledgeItem](#)

#### 1.3.0.8 ogit/Automation/cpuCoreCount

Contains the number of cpu cores.

- id: <http://www.purl.org/ogit/Automation/cpuCoreCount>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

#### 1.3.0.9 ogit/Automation/serviceId

Contains the Id of the service.

- id: <http://www.purl.org/ogit/Automation/serviceId>
- valid-from: Fri Jul 24 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

#### 1.3.0.10 ogit/manufacturere

Manufacturer of a device or component.

- id: <http://www.purl.org/ogit/manufacturere>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

#### 1.3.0.11 ogit/ServiceManagement/testPlan

Contains a test plan used in change management to define how a successful change implementation can be verified.

- id: <http://www.purl.org/ogit/ServiceManagement/testPlan>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ServiceManagement/ChangeRequest](#)

#### 1.3.0.12 ogit/Data/timeToLive

Defines how many seconds data will be kept before expire.

- id: <http://www.purl.org/ogit/Data/timeToLive>
- valid-from: Fri Feb 09 00:00:00 UTC 2018
- creator: [mglusiuk@arago.de](mailto:mglusiuk@arago.de)

used

- optional:
  - [ogit/Data/Log](#)

#### 1.3.0.13 ogit/certainty

Defines the certainty of an event

- id: <http://www.purl.org/ogit/certainty>
- valid-from: Wed Aug 03 00:00:00 UTC 2016
- creator: Philipp Pelchmann

used

- optional:
  - [ogit/Event](#)

#### 1.3.0.14 ogit/currency

A currency code, possibly according to ISO 4217.

- id: <http://www.purl.org/ogit/currency>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ServiceManagement/Offering](#)

#### 1.3.0.15 ogit/category

Used to categorize things.

- id: <http://www.purl.org/ogit/category>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ConfigurationItem](#)
  - [ogit/Event](#)
  - [ogit/ServiceManagement/ChangeRequest](#)
  - [ogit/ServiceManagement/Incident](#)
  - [ogit/ServiceManagement/Offering](#)



## 1.3.0.16 ogit/\_id

[internally generated] The unique identifier. The id is automatically generated by GraphIT.

- id: [http://www.purl.org/ogit/\\_id](http://www.purl.org/ogit/_id)
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- mandatory:
  - [ogit/Automation/Variable](#)

## 1.3.0.17 ogit/comment

Contains a comment.

- id: <http://www.purl.org/ogit/comment>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

## 1.3.0.18 ogit/Automation/osVersion

Version of the Operating System.

- id: <http://www.purl.org/ogit/Automation/osVersion>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Philipp Pelchmann

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.19 ogit/assignedAt**

Defines the time when something was actually assigned to a person/organization for example. The values can combine date and time with time zone designator according to ISO 8601.

- id: <http://www.purl.org/ogit/assignedAt>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

**1.3.0.20 ogit/endOfWarranty**

End of warranty phase of a component

- id: <http://www.purl.org/ogit/endOfWarranty>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Automation/MARSNode](#)
  - [ogit/ConfigurationItem](#)

**1.3.0.21 ogit/postalCode**

The postal code. For example, 60433.

- id: <http://www.purl.org/ogit/postalCode>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Organization](#)

#### 1.3.0.22 `ogit/Automation/buildType`

Contains the build type of a component.

- id: <http://www.purl.org/ogit/Automation/buildType>
- valid-from: Wed Aug 19 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

#### 1.3.0.23 `ogit/Automation/cpuManufacturer`

Contains the manufacturer of the cpu of a device.

- id: <http://www.purl.org/ogit/Automation/cpuManufacturer>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

#### 1.3.0.24 `ogit/Automation/virtualMachineName`

Contains the name of the virtual machine.

- id: <http://www.purl.org/ogit/Automation/virtualMachineName>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

#### 1.3.0.25 ogit/productOrderNumber

An integer, which displays the order number of a product.

- id: <http://www.purl.org/ogit/productOrderNumber>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

#### 1.3.0.26 ogit/Automation/maidFormalRepresentation

Contains a MAID in XML representation defined by MAIDSchema.

- id: <http://www.purl.org/ogit/Automation/maidFormalRepresentation>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- mandatory:
  - [ogit/Automation/MAID](#)

#### 1.3.0.27 ogit/checkedOutAt

Defines the time when something was actually checked out. The values can combine date and time with time zone designator according to ISO 8601.

- id: <http://www.purl.org/ogit/checkedOutAt>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

**1.3.0.28** ogit/email

An email address.

- id: <http://www.purl.org/ogit/email>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Organization](#)
  - [ogit/Person](#)

**1.3.0.29** ogit/Automation/moveToProductionAt

Defines the time when something was actually moved to production. The values can combine date and time with time zone designator according to ISO 8601.

- id: <http://www.purl.org/ogit/Automation/moveToProductionAt>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.30** ogit/ServiceManagement/resolvedAt

Datetime indicating when a ticket was resolved. Can be used for incident or problem tickets when it is necessary to distinguish between the ticket resolving and ticket closure (closedAt). The values must be combined date and time with time zone designator according to ISO 8601

- id: <http://www.purl.org/ogit/ServiceManagement/resolvedAt>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ServiceManagement/Incident](#)

#### 1.3.0.31 ogit/urgency

Contains the urgency which could be applied to a ticket, incident etc.

- id: <http://www.purl.org/ogit/urgency>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ServiceManagement/Order](#)
  - [ogit/ServiceManagement/Ticket](#)

#### 1.3.0.32 ogit/deliveredAt

Defines a point in time when a component/device was actually delivered. The values must be combined date and time with time zone designator according to ISO 8601

- id: <http://www.purl.org/ogit/deliveredAt>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

#### 1.3.0.33 ogit/Automation/osServicePack

Contains the service pack for the operating system.

- id: <http://www.purl.org/ogit/Automation/osServicePack>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Philipp Pelchmann

used

- optional:
  - [ogit/Automation/MARSNode](#)

#### 1.3.0.34 ogit/Automation/rankingType

Contains the type of KI ranking algorithm.

- id: <http://www.purl.org/ogit/Automation/rankingType>
- valid-from: Tue May 01 00:00:00 UTC 2018
- creator: [cy@arago.de](mailto:cy@arago.de)

used

- mandatory:
  - [ogit/Automation/KIRanking](#)

#### 1.3.0.35 ogit/alternativeName

Alternative name of something. In context of a Person this can be the full name or an alias/nick name.

- id: <http://www.purl.org/ogit/alternativeName>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Person](#)

#### 1.3.0.36 ogit/isCritical

This field specifies if the CI is critical for day-to-day operation, such as an E-mail server or RDBMS server. If you open an incident on a critical CI, the incident indicates that this is a critical CI. This field contains a boolean value.

- id: <http://www.purl.org/ogit/isCritical>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

#### 1.3.0.37 ogit/asset

This field represents an asset (device or component).

- id: <http://www.purl.org/ogit/asset>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

#### 1.3.0.38 ogit/Automation/portNumberListener

Contains a port number listener.

- id: <http://www.purl.org/ogit/Automation/portNumberListener>
- valid-from: Fri Jul 24 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

#### 1.3.0.39 ogit/function

Attribute used to specify a function that some entity does/provides. This is more specific than 'description'. Should contain a short string. At this level of specification it is still a free from string. However, unlike 'description', it is expected to contain some list of fixed values.

- id: <http://www.purl.org/ogit/function>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Forum/ShortId](#)
  - [ogit/Organization](#)



**1.3.0.40** `ogit/positionNumber`

An integer, which displays a position of numbering.

- id: <http://www.purl.org/ogit/positionNumber>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Task](#)

**1.3.0.41** `ogit/ServiceManagement/customer`

The customer related to a Service Management process.

- id: <http://www.purl.org/ogit/ServiceManagement/customer>
- valid-from: Fri Jul 03 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ServiceManagement/ChangeRequest](#)
  - [ogit/ServiceManagement/Incident](#)
  - [ogit/ServiceManagement/SubTask](#)

**1.3.0.42** `ogit/isValid`

Boolean value, true if the object is valid.

- id: <http://www.purl.org/ogit/isValid>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Automation/KnowledgeItem](#)
  - [ogit/Forum/KnowledgeItemHistory](#)

**1.3.0.43 ogit/Automation/memory**

Contains a the total physical memory (RAM) in MB.

- id: <http://www.purl.org/ogit/Automation/memory>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.44 ogit/integrity**

A security pricipale that ensures data and Configuration Items are only modified by authorized personnel and Activities

- id: <http://www.purl.org/ogit/integrity>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

**1.3.0.45 ogit/Automation/companyName**

Contains the company name of a component.

- id: <http://www.purl.org/ogit/Automation/companyName>
- valid-from: Mon Nov 02 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.46** `ogit/ServiceManagement/scheduledStartAt`

Defines a point in time when the work on a change is planned/scheduled to start. This date time is usually defined during change planning and/or approval. This datetime is set by change coordinator (e.g it is planned to be done at 7:30PM) The values must be combined date and time with time zone designator according to ISO 8601.

- id: <http://www.purl.org/ogit/ServiceManagement/scheduledStartAt>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ServiceManagement/ChangeRequest](#)
  - [ogit/ServiceManagement/SubTask](#)

**1.3.0.47** `ogit/country`

Name of a country.

- id: <http://www.purl.org/ogit/country>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Philipp Pelchmann

used

- optional:
  - [ogit/Organization](#)

**1.3.0.48** `ogit/businessCategory`

The category of a business.

- id: <http://www.purl.org/ogit/businessCategory>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Philipp Pelchmann

used

- optional:
  - [ogit/Organization](#)

**1.3.0.49** `ogit/Automation/middlewareType`

Contains information about the type of middleware. For example it database middleware, application server middleware or a message-oriented middleware.

- id: <http://www.purl.org/ogit/Automation/middlewareType>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.50** `ogit/Automation/serviceName`

Contains the name of a service.

- id: <http://www.purl.org/ogit/Automation/serviceName>
- valid-from: Fri Jul 24 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.51** `ogit/project`

Project name, for which the entity is being used.

- id: <http://www.purl.org/ogit/project>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ServiceManagement/Order](#)
  - [ogit/ServiceManagement/Ticket](#)

**1.3.0.52 ogit/Automation/licenseAvailability**

The availability of the license of a component.

- id: <http://www.purl.org/ogit/Automation/licenseAvailability>
- valid-from: Fri Jul 24 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.53 ogit/question**

Contains a question.

- id: <http://www.purl.org/ogit/question>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Question](#)
  - [ogit/Task](#)

**1.3.0.54 ogit/maintenanceState**

Defines the state of maintenance.

- id: <http://www.purl.org/ogit/maintenanceState>
- valid-from: Wed Aug 03 00:00:00 UTC 2016
- creator: Philipp Pelchmann

used

- optional:
  - [ogit/Event](#)

1.3.0.55 `ogit/_creator`

[internally generated] The id of the identity who created the node or edge

- id: [http://www.purl.org/ogit/\\_creator](http://www.purl.org/ogit/_creator)
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

1.3.0.56 `ogit/notification`

A notification.

- id: <http://www.purl.org/ogit/notification>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Philipp Pelchmann

used

- optional:
  - [ogit/Person](#)

1.3.0.57 `ogit/changeLog`

String value describing a changelog of an entity.

- id: <http://www.purl.org/ogit/changeLog>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Automation/KnowledgeItem](#)
  - [ogit/Forum/KnowledgeItemHistory](#)

**1.3.0.58** `ogit/ServiceManagement/externalTicketId`

If a ticket was imported/duplicated from another system this attribute will define the ticket ID from the source system.

- id: <http://www.purl.org/ogit/ServiceManagement/externalTicketId>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ServiceManagement/Order](#)
  - [ogit/ServiceManagement/Ticket](#)

**1.3.0.59** `ogit/sourceId`

The Id of the source system.

- id: <http://www.purl.org/ogit/sourceId>
- valid-from: Thu Jun 11 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Event](#)
  - [ogit/Organization](#)
  - [ogit/Person](#)

**1.3.0.60** `ogit/url`

Contains an URL (unified resource locator)

- id: <http://www.purl.org/ogit/url>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- mandatory:
  - [ogit/Hyperlink](#)
- optional:
  - [ogit/Attachment](#)
  - [ogit/Automation/KIRanking](#)
  - [ogit/MARS/Resource](#)
  - [ogit/Software/Application](#)

#### 1.3.0.61 [ogit/licenseKey](#)

A string containing a license key.

- id: <http://www.purl.org/ogit/licenseKey>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/License](#)

#### 1.3.0.62 [ogit/uri](#)

Unified resource identifier

- id: <http://www.purl.org/ogit/uri>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ServiceManagement/Service](#)



**1.3.0.63** ogit/purchasedAt

Defines a point in time when a component/device was actually purchased. The values must be combined date and time with time zone designator according to ISO 8601

- id: <http://www.purl.org/ogit/purchasedAt>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

**1.3.0.64** ogit/Automation/cpuCount

An integer which shows the number of cps of a component.

- id: <http://www.purl.org/ogit/Automation/cpuCount>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.65** ogit/timestamp

Contains the timestamp in milliseconds.

- id: <http://www.purl.org/ogit/timestamp>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- mandatory:
  - [ogit/Automation/History](#)

**1.3.0.66** `ogit/Automation/databaseSchema`

Contains information about the database schema. The schema is the skeleton structure that represents the logical view of the entire database

- id: <http://www.purl.org/ogit/Automation/databaseSchema>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.67** `ogit/mobilePhone`

A mobile phone number.

- id: <http://www.purl.org/ogit/mobilePhone>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Person](#)

**1.3.0.68** `ogit/Automation/additionalMacAddress`

Contains an additional MAC address

- id: <http://www.purl.org/ogit/Automation/additionalMacAddress>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.69** ogit/severity

Stores a severity. E.g. Some event management systems might store a severity field.

- id: <http://www.purl.org/ogit/severity>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Event](#)

**1.3.0.70** ogit/Automation/knowledgeItemTier

Numeric value describing KnowledgeItem Tier.

- id: <http://www.purl.org/ogit/Automation/knowledgeItemTier>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Automation/KnowledgeItem](#)
  - [ogit/Forum/KnowledgeItemHistory](#)

**1.3.0.71** ogit/connectorId

The Id of the connector.

- id: <http://www.purl.org/ogit/connectorId>
- valid-from: Thu Jun 11 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

#### 1.3.0.72 ogit/Automation/dataClassification

Data classification of a component.

- id: <http://www.purl.org/ogit/Automation/dataClassification>
- valid-from: Fri Jul 24 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

#### 1.3.0.73 ogit/Automation/firmwareVersion

Version of the firmware.

- id: <http://www.purl.org/ogit/Automation/firmwareVersion>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

#### 1.3.0.74 ogit/effort

Defines how much time was spent on the actual work for a change, task, or similar entity. The values is expected to be in format HH:MM, e.g. 1:00 for 1 hour effort.

- id: <http://www.purl.org/ogit/effort>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ServiceManagement/ChangeRequest](#)
  - [ogit/ServiceManagement/SubTask](#)

**1.3.0.75 ogit/startedAt**

Defines a point in time when the work on a change, task, or similar entity was actually started. The values must be combined date and time with time zone designator according to ISO 8601

- id: <http://www.purl.org/ogit/startedAt>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ConfigurationItem](#)
  - [ogit/ServiceManagement/ChangeRequest](#)
  - [ogit/ServiceManagement/SubTask](#)

**1.3.0.76 ogit/value**

Contains a value of a key / value pair.

- id: <http://www.purl.org/ogit/value>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- mandatory:
  - [ogit/Automation/KnowledgeItemAttribute](#)
  - [ogit/Forum/Rating](#)

**1.3.0.77 ogit/assetTag**

This field specifies the asset tag number/code.

- id: <http://www.purl.org/ogit/assetTag>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

**1.3.0.78 ogit/ipAddress**

The IP address of a component/hardware device.

- id: <http://www.purl.org/ogit/ipAddress>
- valid-from: Wed May 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.79 ogit/licenseType**

Type of the License e.g. community/enterprise.

- id: <http://www.purl.org/ogit/licenseType>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/License](#)

**1.3.0.80 ogit/unit**

Unit of measurement of some value.

- id: <http://www.purl.org/ogit/unit>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Timeseries](#)

**1.3.0.81 ogit/Automation/todo**

Boolean value, true if variable is todo variable.

- id: <http://www.purl.org/ogit/Automation/todo>
- valid-from: Mon Feb 09 00:00:00 UTC 2015
- creator: Kaushik Gondaliya

used

- mandatory:
  - [ogit/Automation/Variable](#)

**1.3.0.82 ogit/Automation/knowledgeItemFormalRepresentation**

Contains an automation Knowledge Item (KI) in XML representation defined by KiSchema.

- id: <http://www.purl.org/ogit/Automation/knowledgeItemFormalRepresentation>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- mandatory:
  - [ogit/Automation/KnowledgeItem](#)
  - [ogit/Forum/KnowledgeItemHistory](#)

**1.3.0.83 ogit/Automation/installCount**

Contains an integer. This integer can be adjust automatically when software is added to or deleted from configuration items (CIs).

- id: <http://www.purl.org/ogit/Automation/installCount>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.84** `ogit/installedAt`

Defines a point in time when a component/device was actually installed. The values must be combined date and time with time zone designator according to ISO 8601

- id: <http://www.purl.org/ogit/installedAt>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

**1.3.0.85** `ogit/Automation/knowledgeItemId`

Contains a KnowledgeItemId in string representation.

- id: <http://www.purl.org/ogit/Automation/knowledgeItemId>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- mandatory:
  - [ogit/Automation/History](#)

**1.3.0.86** `ogit/Automation/marsNodeFormalRepresentation`

Contains MARS in XML representation defined by MARSSchema2013.

- id: <http://www.purl.org/ogit/Automation/marsNodeFormalRepresentation>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- mandatory:
  - [ogit/Automation/MARSNodeTemplate](#)
- optional:
  - [ogit/Automation/MARSNode](#)



**1.3.0.87 ogit/updateCount**

Contains the count of the records updated.

- id: <http://www.purl.org/ogit/updateCount>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

**1.3.0.88 ogit/installStatus**

An installation status for an entity. At this level of specification no list of values is specified. However, applications using this attribute are expected to allow only a fixed list of values that seems useful in the application's semantic context.

- id: <http://www.purl.org/ogit/installStatus>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

**1.3.0.89 ogit/city**

Name of a city.

- id: <http://www.purl.org/ogit/city>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Philipp Pelchmann

used

- optional:
  - [ogit/Organization](#)

**1.3.0.90 ogit/Automation/systemClass**

Contains the class of the system.

- id: <http://www.purl.org/ogit/Automation/systemClass>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.91 ogit/Automation/diskCount**

An integer which shows the number of disks of a component.

- id: <http://www.purl.org/ogit/Automation/diskCount>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.92 ogit/mode**

Contains the type of filter for the value contained in the entity "Attribute" and corresponding to one of the following strings: eq, ne, lt, le, gt, ge, exists, notexists, string, notstring, regex, notregex

- id: <http://www.purl.org/ogit/mode>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Automation/KnowledgeItemAttribute](#)

**1.3.0.93** `ogit/Automation/automationState`

A value of 'Manual' will mark a node as not eligible for Issue processing

- id: <http://www.purl.org/ogit/Automation/automationState>
- valid-from: Fri Jun 01 00:00:00 UTC 2018
- creator: [fotto@arago.de](mailto:fotto@arago.de)

used

- optional:
  - [ogit/MARS/Resource](#)

**1.3.0.94** `ogit/ServiceManagement/incidentStatus`

Defines the status of an incident record/ticket.

- id: <http://www.purl.org/ogit/ServiceManagement/incidentStatus>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ServiceManagement/Incident](#)

**1.3.0.95** `ogit/taskLog`

In cases where the log for a Task is maintained as a single string it will be stored in taskLog. In all other case consider using ogit/Timeseries.

- id: <http://www.purl.org/ogit/taskLog>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ServiceManagement/SubTask](#)

## 1.3.0.96 ogit/status

A status for an entity. At this level of specification no list of values is specified. However, applications using this attribute are expected to allow only a fixed list of values that seems useful in the application's semantic context.

- id: <http://www.purl.org/ogit/status>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Automation/AutomationIssue](#)
  - [ogit/Automation/MARSNodeTemplate](#)
  - [ogit/ConfigurationItem](#)
  - [ogit/Event](#)
  - [ogit/Organization](#)
  - [ogit/Person](#)
  - [ogit/Question](#)
  - [ogit/Task](#)

## 1.3.0.97 ogit/createdAt

Defines a point in time when a ticket/incident/event etc was created or recorded.

- id: <http://www.purl.org/ogit/createdAt>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Attachment](#)
  - [ogit/ConfigurationItem](#)
  - [ogit/License](#)
  - [ogit/ServiceManagement/Order](#)
  - [ogit/ServiceManagement/Ticket](#)

**1.3.0.98** `ogit/ServiceManagement/workAround`

Defines a work around for a known problem until a permanent solution is defined.

- id: <http://www.purl.org/ogit/ServiceManagement/workAround>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ServiceManagement/Problem](#)

**1.3.0.99** `ogit/ServiceManagement/rootCause`

Root cause for example of a problem ticket.

- id: <http://www.purl.org/ogit/ServiceManagement/rootCause>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ServiceManagement/Problem](#)

**1.3.0.100** `ogit/Forum/username`

A unique username for a member of a Forum

- id: <http://www.purl.org/ogit/Forum/username>
- valid-from: Mon Apr 27 00:00:00 UTC 2015
- creator: Chris Walker

used

- mandatory:
  - [ogit/Forum/Profile](#)

## 1.3.0.101 ogit/model

Model of a device.

- id: <http://www.purl.org/ogit/model>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ConfigurationItem](#)

## 1.3.0.102 ogit/Automation/domain

Contains the domain name.

- id: <http://www.purl.org/ogit/Automation/domain>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

## 1.3.0.103 ogit/Automation/lifecycle

Contains the lifecycle state of a MARSNode. If value is 'decommissioned' this node is ignored by engine, graph and UI.

- id: <http://www.purl.org/ogit/Automation/lifecycle>
- valid-from: Thu May 11 00:00:00 UTC 2017
- creator: Philipp Kähltz

used

- optional:
  - [ogit/Automation/MARSNode](#)
  - [ogit/MARS/Resource](#)

**1.3.0.104 ogit/lastName**

Last name of a person.

- id: <http://www.purl.org/ogit/lastName>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Person](#)

**1.3.0.105 ogit/Automation/cpuModel**

Contains the model of the cpu.

- id: <http://www.purl.org/ogit/Automation/cpuModel>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.106 ogit/Automation/buildName**

Contains the build name of a component.

- id: <http://www.purl.org/ogit/Automation/buildName>
- valid-from: Fri Jul 24 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.107 ogit/Automation/appInstanceType**

Contains the instance type.

- id: <http://www.purl.org/ogit/Automation/appInstanceType>
- valid-from: Fri Jul 24 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.108 ogit/modificationTime**

Modification time.

- id: <http://www.purl.org/ogit/modificationTime>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Automation/AutomationIssue](#)
  - [ogit/Automation/DynamicEngineData](#)
  - [ogit/Automation/KnowledgeItem](#)
  - [ogit/Automation/MARSNode](#)
  - [ogit/Forum/KnowledgeItemHistory](#)

**1.3.0.109 ogit/ServiceManagement/problemStatus**

defines the status of a problem record

- id: <http://www.purl.org/ogit/ServiceManagement/problemStatus>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ServiceManagement/Problem](#)



**1.3.0.110 ogit/Automation/knowledgeItemSyntaxVersion**

Contains an automation Knowledge Item (KI) syntax version.

- id: <http://www.purl.org/ogit/Automation/knowledgeItemSyntaxVersion>
- valid-from: Tue Oct 31 00:00:00 UTC 2017
- creator: [druss@arago.de](mailto:druss@arago.de)

used

- optional:
  - [ogit/Automation/KnowledgeItem](#)

**1.3.0.111 ogit/priority**

Priority of a ticket. The actual semantics might depend on the ticket type (Incident, Service Request, ...)

- id: <http://www.purl.org/ogit/priority>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ConfigurationItem](#)
  - [ogit/Event](#)
  - [ogit/ServiceManagement/Order](#)
  - [ogit/ServiceManagement/Ticket](#)

**1.3.0.112 ogit/shortDescription**

Contains a short description.

- id: <http://www.purl.org/ogit/shortDescription>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

**1.3.0.113 ogit/Automation/serviceClass**

Contains the class of the service.

- id: <http://www.purl.org/ogit/Automation/serviceClass>
- valid-from: Fri Jul 24 00:00:00 UTC 2015
- creator: Aymen Ayoub

**1.3.0.114 ogit/middleName**

Middle name of a person.

- id: <http://www.purl.org/ogit/middleName>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Philipp Pelchmann

used

- optional:
  - [ogit/Person](#)

**1.3.0.115 ogit/resource**

Defines the name of an resource on an instance e.g. disk or database.

- id: <http://www.purl.org/ogit/resource>
- valid-from: Wed Aug 03 00:00:00 UTC 2016
- creator: Philipp Pelchmann

used

- optional:
  - [ogit/Event](#)

**1.3.0.116 ogit/ServiceManagement/targetFinishAt**

Defines a point in time when the work on a change should be finished. This date time is defined by the requester. The values must be combined date and time with time zone designator according to ISO 8601

- id: <http://www.purl.org/ogit/ServiceManagement/targetFinishAt>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ServiceManagement/ChangeRequest](#)
  - [ogit/ServiceManagement/SubTask](#)

**1.3.0.117 ogit/accessControl**

The access control level of this Node. Value could mean different things to different applications / policies. Initial intent is that policies would treat "public-read" (inspired by Amazon AWS S3 ACLs) to mean anyone would have read-only access to this node.

- id: <http://www.purl.org/ogit/accessControl>
- valid-from: Thu Mar 26 00:00:00 UTC 2015
- creator: Chris Walker

used

- mandatory:
  - [ogit/Automation/Variable](#)
- optional:
  - [ogit/Attachment](#)
  - [ogit/Automation/KnowledgeBundle](#)
  - [ogit/Automation/KnowledgeItem](#)
  - [ogit/Forum/KnowledgeBundle](#)
  - [ogit/Forum/KnowledgeBundleHistory](#)
  - [ogit/Forum/KnowledgeItemHistory](#)
  - [ogit/Forum/Topic](#)

**1.3.0.118 ogit/ServiceManagement/ticketId**

ID of the ticket in the source system, e.g. the ID of the ticket in BMC.

- id: <http://www.purl.org/ogit/ServiceManagement/ticketId>
- valid-from: Tue May 26 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ServiceManagement/Ticket](#)

**1.3.0.119 ogit/justification**

Justification for a ChangeRequest

- id: <http://www.purl.org/ogit/justification>
- valid-from: Wed Jul 01 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ServiceManagement/ChangeRequest](#)

**1.3.0.120 ogit/invoiceNumber**

Contains an invoice number. This number is used as identifier for security purposes.

- id: <http://www.purl.org/ogit/invoiceNumber>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

**1.3.0.121 ogit/response**

Contains the response for a question.

- id: <http://www.purl.org/ogit/response>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Question](#)
  - [ogit/Task](#)

**1.3.0.122 ogit/ServiceManagement/externalTicketSource**

If a ticket was imported/duplicated from another system this will contain a string indentifying the source system.

- id: <http://www.purl.org/ogit/ServiceManagement/externalTicketSource>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ServiceManagement/Order](#)

**1.3.0.123 ogit/Automation/diskSpace**

An integer which contains the disk space in GB.

- id: <http://www.purl.org/ogit/Automation/diskSpace>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.124 ogit/soxClass**

This attribute specifies, if an entity has a Sarbanes Oxley (SOX) classification that applies to it. The out-of-box data is: Critical or Non Critical

- id: <http://www.purl.org/ogit/soxClass>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

**1.3.0.125 ogit/closedAt**

Will defined the time when a ticket was closed. The values must be combined date and time with time zone designator according to ISO 8601

- id: <http://www.purl.org/ogit/closedAt>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ServiceManagement/Order](#)
  - [ogit/ServiceManagement/Ticket](#)

**1.3.0.126** `ogit/ServiceManagement/taskStatus`

Defines the status of a task.

- id: <http://www.purl.org/ogit/ServiceManagement/taskStatus>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ServiceManagement/SubTask](#)

**1.3.0.127** `ogit/ServiceManagement/resolutionCode`

Optional resolution code that may be provided during an incident or problem along with the solution description.

- id: <http://www.purl.org/ogit/ServiceManagement/resolutionCode>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ServiceManagement/ChangeRequest](#)
  - [ogit/ServiceManagement/Incident](#)
  - [ogit/ServiceManagement/Problem](#)
  - [ogit/ServiceManagement/SubTask](#)

**1.3.0.128** `ogit/expiresAt`

Defines the date something expires.

- id: <http://www.purl.org/ogit/expiresAt>
- valid-from: Wed Aug 03 00:00:00 UTC 2016
- creator: Philipp Pelchmann

used

- optional:
  - [ogit/Event](#)

**1.3.0.129** ogit/streetAddress

The street address. For example, Eschersheimer Landstr. 526-532

- id: <http://www.purl.org/ogit/streetAddress>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Organization](#)

**1.3.0.130** ogit/businessCriticality

The business criticality of a process/service/CI.

- id: <http://www.purl.org/ogit/businessCriticality>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

**1.3.0.131** ogit/leaseContract

This field specifies the lease contract covering a service.

- id: <http://www.purl.org/ogit/leaseContract>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

## 1.3.0.132 ogit/\_owner

[internally generated] The id of the identity who owns the node

- id: [http://www.purl.org/ogit/\\_owner](http://www.purl.org/ogit/_owner)
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

## 1.3.0.133 ogit/securityClass

Contains the security class of an entity/device.

- id: <http://www.purl.org/ogit/securityClass>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

## 1.3.0.134 ogit/serialNumber

A string representing a any kind of serial number. see <http://purl.org/goodrelations/v1#serialNumber>

- id: <http://www.purl.org/ogit/serialNumber>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Automation/MARSNode](#)
  - [ogit/ServiceManagement/Offering](#)



**1.3.0.135 ogit/firstName**

First name of a person

- id: <http://www.purl.org/ogit/firstName>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Person](#)

**1.3.0.136 ogit/assignedGroup**

Assigned Group to a Service Management process.

- id: <http://www.purl.org/ogit/assignedGroup>
- valid-from: Wed Jul 01 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ServiceManagement/ChangeRequest](#)
  - [ogit/ServiceManagement/Incident](#)
  - [ogit/ServiceManagement/SubTask](#)

**1.3.0.137 ogit/macAddress**

The mac address of a component.

- id: <http://www.purl.org/ogit/macAddress>
- valid-from: Wed May 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.138 ogit/Automation/osName**

Contains operating system name.

- id: <http://www.purl.org/ogit/Automation/osName>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Philipp Pelchmann

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.139 ogit/version**

Any string representation of version information. no restrictions are imposed on that base attribute

- id: <http://www.purl.org/ogit/version>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ConfigurationItem](#)
  - [ogit/ServiceManagement/Report](#)
  - [ogit/Software/Application](#)

**1.3.0.140 ogit/title**

Title of any kind. In the context of a Person this can be a courtesy title, an academic title, or a job title.

- id: <http://www.purl.org/ogit/title>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- mandatory:
  - [ogit/Forum/Topic](#)
  - [ogit/Forum/Workflow](#)
  - [ogit/Forum/WorkflowStep](#)
- optional:
  - [ogit/Hyperlink](#)
  - [ogit/Person](#)

**1.3.0.141** `ogit/Automation/appServer`

Contains application server.

- id: <http://www.purl.org/ogit/Automation/appServer>
- valid-from: Fri Jul 24 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.142** `ogit/class`

Class of a component/device.

- id: <http://www.purl.org/ogit/class>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

**1.3.0.143** `ogit/Automation/sendHistory`

Boolean flag whether issue history should be sent to decision service.

- id: <http://www.purl.org/ogit/Automation/sendHistory>
- valid-from: Tue May 01 00:00:00 UTC 2018
- creator: [cy@arago.de](mailto:cy@arago.de)

used

- optional:
  - [ogit/Automation/KIRanking](#)

**1.3.0.144 ogit/content**

A string holding any type of content: plain string, XML fragments, RDF documents, ...

- id: <http://www.purl.org/ogit/content>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

**used**

- mandatory:
  - [ogit/Forum/Post](#)
  - [ogit/Forum/Reply](#)
- optional:
  - [ogit/Attachment](#)
  - [ogit/Comment](#)
  - [ogit/ConfigurationItem](#)
  - [ogit/Forum/Rating](#)

**1.3.0.145 ogit/confidentiality**

Contains information about the confidentiality related to a device or an entity.

- id: <http://www.purl.org/ogit/confidentiality>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

**used**

- optional:
  - [ogit/ConfigurationItem](#)

**1.3.0.146 ogit/Automation/deployStatus**

String value, represents the status if an automation Knowledge Item is not deployed into an Automation Engine.

- id: <http://www.purl.org/ogit/Automation/deployStatus>
- valid-from: Mon Jan 25 00:00:00 UTC 2016
- creator: Peter Larem

**used**

- optional:
  - [ogit/Automation/AutomationIssue](#)
  - [ogit/Automation/KnowledgeItem](#)
  - [ogit/Automation/MARSNode](#)

**1.3.0.147** `ogit/Automation/rankMap`

Contains KI ranking values.

- id: <http://www.purl.org/ogit/Automation/rankMap>
- valid-from: Tue May 01 00:00:00 UTC 2018
- creator: [cy@arago.de](mailto:cy@arago.de)

used

- optional:
  - [ogit/Automation/KIRanking](#)

**1.3.0.148** `ogit/lastOccurredAt`

Defines the date of last occurrence of an event

- id: <http://www.purl.org/ogit/lastOccurredAt>
- valid-from: Wed Aug 03 00:00:00 UTC 2016
- creator: Philipp Pelchmann

used

- optional:
  - [ogit/Event](#)

**1.3.0.149** `ogit/Automation/isDeployed`

Boolean value, true if an automation Knowledge Item is deployed into an Automation Engine.

- id: <http://www.purl.org/ogit/Automation/isDeployed>
- valid-from: Mon Jan 25 00:00:00 UTC 2016
- creator: Peter Larem

used

- optional:
  - [ogit/Automation/AutomationIssue](#)
  - [ogit/Automation/KnowledgeItem](#)
  - [ogit/Automation/MARSNode](#)

**1.3.0.150** `ogit/Automation/processingNode`

Defines where an AutomationIssue is currently being processed or was being processed last. Must contain a valid vertex id. Replaces the free attribute '/CurrentNodeID'

- id: <http://www.purl.org/ogit/Automation/processingNode>
- valid-from: Fri Jun 01 00:00:00 UTC 2018
- creator: [fotto@arago.de](mailto:fotto@arago.de)

used

- optional:
  - [ogit/Automation/AutomationIssue](#)

**1.3.0.151** `ogit/Automation/issueFormalRepresentation`

Contains an issue in XML representation defined by IssueSchema.

- id: <http://www.purl.org/ogit/Automation/issueFormalRepresentation>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Automation/AutomationIssue](#)

**1.3.0.152** `ogit/_tags`

[internally generated] Used for individual search.

- id: [http://www.purl.org/ogit/\\_tags](http://www.purl.org/ogit/_tags)
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Automation/Variable](#)

**1.3.0.153** `ogit/ServiceManagement/scheduledFinishAt`

Defines a point in time when the work on a change is planned/scheduled to be finished. This date time is usually defined during change planning and/or approval. The values must be combined date and time with time zone designator according to ISO 8601

- id: <http://www.purl.org/ogit/ServiceManagement/scheduledFinishAt>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ServiceManagement/ChangeRequest](#)
  - [ogit/ServiceManagement/SubTask](#)

**1.3.0.154** `ogit/name`

Contains a name.

- id: <http://www.purl.org/ogit/name>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- mandatory:
  - [ogit/Automation/Item](#)
  - [ogit/Automation/KIRanking](#)
  - [ogit/Automation/KnowledgeBundle](#)
  - [ogit/Automation/KnowledgeItemAttribute](#)
  - [ogit/Automation/KnowledgePool](#)
  - [ogit/Automation/MARSModelTemplate](#)
  - [ogit/Automation/Variable](#)
  - [ogit/Event](#)
  - [ogit/Forum/KnowledgeBundle](#)
  - [ogit/Forum/KnowledgeBundleHistory](#)
  - [ogit/Forum/Profile](#)
  - [ogit/Forum/Tag](#)
  - [ogit/Location](#)
  - [ogit/MARS/Resource](#)
  - [ogit/Organization](#)
  - [ogit/ServiceManagement/Offering](#)

- [ogit/Software/Application](#)
- optional:
  - [ogit/Asset](#)
  - [ogit/Attachment](#)
  - [ogit/Automation/DynamicEngineData](#)
  - [ogit/Automation/KnowledgeItem](#)
  - [ogit/Automation/MARSModel](#)
  - [ogit/Automation/MARSNode](#)
  - [ogit/ConfigurationItem](#)
  - [ogit/Data/Log](#)
  - [ogit/Environment](#)
  - [ogit/Forum/KnowledgeItemHistory](#)
  - [ogit/Region](#)
  - [ogit/ServiceManagement/Report](#)
  - [ogit/ServiceManagement/Service](#)
  - [ogit/ServiceManagement/SubTask](#)
  - [ogit/Task](#)
  - [ogit/Timeseries](#)

#### 1.3.0.155 [ogit/Automation/software](#)

A software component.

- id: <http://www.purl.org/ogit/Automation/software>
- valid-from: Fri Jul 24 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

#### 1.3.0.156 [ogit/Automation/originNode](#)

Defines where an AutomationIssue starts/started its lifecycle. Must contain a valid vertex id. Replaces the free attribute 'NodeID'

- id: <http://www.purl.org/ogit/Automation/originNode>
- valid-from: Fri Jun 01 00:00:00 UTC 2018
- creator: [fotto@arago.de](mailto:fotto@arago.de)

used

- optional:
  - [ogit/Automation/AutomationIssue](#)



## 1.3.0.157 ogit/description

Contains a description.

- id: <http://www.purl.org/ogit/description>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- mandatory:
  - [ogit/Automation/Trigger](#)
  - [ogit/Automation/Variable](#)
  - [ogit/Forum/Topic](#)
- optional:
  - [ogit/Automation/KnowledgeItem](#)
  - [ogit/Automation/MARSModel](#)
  - [ogit/Automation/MARSModelTemplate](#)
  - [ogit/ConfigurationItem](#)
  - [ogit/Data/Log](#)
  - [ogit/Event](#)
  - [ogit/Forum/KnowledgeItemHistory](#)
  - [ogit/Location](#)
  - [ogit/Organization](#)
  - [ogit/Region](#)
  - [ogit/ServiceManagement/Offering](#)
  - [ogit/ServiceManagement/Order](#)
  - [ogit/ServiceManagement/Service](#)
  - [ogit/ServiceManagement/SubTask](#)
  - [ogit/ServiceManagement/Ticket](#)
  - [ogit/Software/Application](#)
  - [ogit/Task](#)
  - [ogit/Timeseries](#)

## 1.3.0.158 ogit/finishedAt

Defines a point in time when the work on a change, task, or similar entity was actually finished. The values must be combined date and time with time zone designator according to ISO 8601

- id: <http://www.purl.org/ogit/finishedAt>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ServiceManagement/ChangeRequest](#)
  - [ogit/ServiceManagement/SubTask](#)

**1.3.0.159** ogit/Automation/host

Contains the host name.

- id: <http://www.purl.org/ogit/Automation/host>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.160** ogit/Automation/weightMap

Contains fingerprint weight values for a KI ranking.

- id: <http://www.purl.org/ogit/Automation/weightMap>
- valid-from: Tue May 01 00:00:00 UTC 2018
- creator: [cy@arago.de](mailto:cy@arago.de)

used

- mandatory:
  - [ogit/Automation/KIRanking](#)

**1.3.0.161** ogit/externalId

The External Id of a component.

- id: <http://www.purl.org/ogit/externalId>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

## 1.3.0.162 ogit/impact

Will contain the impact, for example of a ticket. In this case the actual semantics would depend on the ticket type, which could correspond to an Incident, Service Request, etc.

- id: <http://www.purl.org/ogit/impact>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ConfigurationItem](#)
  - [ogit/Event](#)
  - [ogit/ServiceManagement/Order](#)
  - [ogit/ServiceManagement/Ticket](#)

## 1.3.0.163 ogit/contact

This field displays the device/CI/component owner who is the person assigned to the device/CI/component and uses it on a day-to-day basis. Support contacts are secondary contacts who may have access to a CI for example.

- id: <http://www.purl.org/ogit/contact>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

## 1.3.0.164 ogit/Automation/defaultSigma

Contains the default sigma value for a KI ranking.

- id: <http://www.purl.org/ogit/Automation/defaultSigma>
- valid-from: Tue May 01 00:00:00 UTC 2018
- creator: [cy@arago.de](mailto:cy@arago.de)

used

- optional:
  - [ogit/Automation/KIRanking](#)

**1.3.0.165 ogit/Automation/appInfrastructureType**

Contains the application infrastructure type.

- id: <http://www.purl.org/ogit/Automation/appInfrastructureType>
- valid-from: Fri Jul 24 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.166 ogit/revision**

Contains the revision of versioned data.

- id: <http://www.purl.org/ogit/revision>
- valid-from: Tue Oct 31 00:00:00 UTC 2017
- creator: [druss@arago.de](mailto:druss@arago.de)

used

- mandatory:
  - [ogit/VersioningData](#)

**1.3.0.167 ogit/Automation/issueType**

Contains the type of the issue.

- id: <http://www.purl.org/ogit/Automation/issueType>
- valid-from: Thu Nov 01 00:00:00 UTC 2018
- creator: [cy@arago.de](mailto:cy@arago.de)

used

- optional:
  - [ogit/Automation/AutomationIssue](#)

**1.3.0.168 ogit/orderedAt**

Defines a point in time when a component/device was actually ordered. The values must be combined date and time with time zone designator according to ISO 8601

- id: <http://www.purl.org/ogit/orderedAt>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

**1.3.0.169 ogit/faultCount**

Contains fault count related to a component

- id: <http://www.purl.org/ogit/faultCount>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

**1.3.0.170 ogit/risk**

Used to store the result of a risk analysis.

- id: <http://www.purl.org/ogit/risk>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ServiceManagement/ChangeRequest](#)

**1.3.0.171** `ogit/lastUpdatedBy`

Defines the last person or process who updated an entity.

- id: <http://www.purl.org/ogit/lastUpdatedBy>
- valid-from: Mon Jul 20 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Attachment](#)

**1.3.0.172** `ogit/ServiceManagement/fallbackPlan`

Defines instructions of how to revert in case a change fails.

- id: <http://www.purl.org/ogit/ServiceManagement/fallbackPlan>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ServiceManagement/ChangeRequest](#)

**1.3.0.173** `ogit/Automation/defaultRank`

Contains the default rank for a KI ranking.

- id: <http://www.purl.org/ogit/Automation/defaultRank>
- valid-from: Tue May 01 00:00:00 UTC 2018
- creator: [cy@arago.de](mailto:cy@arago.de)

used

- optional:
  - [ogit/Automation/KIRanking](#)

**1.3.0.174 ogit/isRoot**

Defines if an event is root.

- id: <http://www.purl.org/ogit/isRoot>
- valid-from: Wed Aug 03 00:00:00 UTC 2016
- creator: Philipp Pelchmann

used

- optional:
  - [ogit/Event](#)

**1.3.0.175 ogit/openedAt**

Time when a ticket or task was created/opened. The values could combine date and time with time zone designator according to ISO 8601 for service management tickets. For most tickets there is no real difference between creation and opened time. In case such a distinction is relevant the "createdAt" attribute can be used.

- id: <http://www.purl.org/ogit/openedAt>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Event](#)
  - [ogit/ServiceManagement/Order](#)
  - [ogit/ServiceManagement/Ticket](#)

**1.3.0.176 ogit/Automation/virtualSystemName**

Contains the name of the virtual system.

- id: <http://www.purl.org/ogit/Automation/virtualSystemName>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.177 ogit/expirationDate**

Defines a point in time when something becomes invalid the format is described at <http://purl.org/goodrelations/v1#validThrough>

- id: <http://www.purl.org/ogit/expirationDate>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/License](#)
  - [ogit/ServiceManagement/Offering](#)

**1.3.0.178 ogit/officePhone**

The phone number in the office.

- id: <http://www.purl.org/ogit/officePhone>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Philipp Pelchmann

used

- optional:
  - [ogit/Person](#)

**1.3.0.179 ogit/phone**

a phone number

- id: <http://www.purl.org/ogit/phone>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Organization](#)



**1.3.0.180 ogit/acknowledgeState**

Defines the state of acknowledgement.

- id: <http://www.purl.org/ogit/acknowledgeState>
- valid-from: Wed Aug 03 00:00:00 UTC 2016
- creator: Philipp Pelchmann

used

- optional:
  - [ogit/Event](#)

**1.3.0.181 ogit/deadline**

Defines a point in time when a deadline is reached.

- id: <http://www.purl.org/ogit/deadline>
- valid-from: Mon Dec 19 00:00:00 UTC 2016
- creator: [stravlos@arago.co](mailto:stravlos@arago.co)

used

- optional:
  - [ogit/License](#)

**1.3.0.182 ogit/Automation/osLicense**

License of the Operating System.

- id: <http://www.purl.org/ogit/Automation/osLicense>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Philipp Pelchmann

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.183** ogit/fax

The number of a fax.

- id: <http://www.purl.org/ogit/fax>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Philipp Pelchmann

used

- optional:
  - [ogit/Person](#)

**1.3.0.184** ogit/Automation/databaseServer

Contains information about the database server.

- id: <http://www.purl.org/ogit/Automation/databaseServer>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.185** ogit/Automation/portNumber

Contains a port number.

- id: <http://www.purl.org/ogit/Automation/portNumber>
- valid-from: Fri Jul 24 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.186** ogit/Automation/webServer

Contains an webServer.

- id: <http://www.purl.org/ogit/Automation/webServer>
- valid-from: Fri Jul 24 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.187** ogit/type

Type of an an entity.

- id: <http://www.purl.org/ogit/type>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Attachment](#)
  - [ogit/ConfigurationItem](#)
  - [ogit/Event](#)
  - [ogit/ServiceManagement/SubTask](#)
  - [ogit/Task](#)

**1.3.0.188** ogit/Automation/softwareKey

Contains the key of a software.

- id: <http://www.purl.org/ogit/Automation/softwareKey>
- valid-from: Fri Jul 24 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.189 ogit/Automation/installPath**

Contains the installation path of a component.

- id: <http://www.purl.org/ogit/Automation/installPath>
- valid-from: Fri Jul 24 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.190 ogit/Automation/licenseName**

Contains the license name of a component.

- id: <http://www.purl.org/ogit/Automation/licenseName>
- valid-from: Fri Jul 24 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.191 ogit/capacity**

General Capacity

- id: <http://www.purl.org/ogit/capacity>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Question](#)

**1.3.0.192** `ogit/Automation/contextPath`

Contains the context path of a component.

- id: <http://www.purl.org/ogit/Automation/contextPath>
- valid-from: Fri Jul 24 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.193** `ogit/Automation/cpuSpeed`

An floating point number which shows the cpu speed in GHZ.

- id: <http://www.purl.org/ogit/Automation/cpuSpeed>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.194** `ogit/Automation/processingTimestamp`

Contains the timestamp indicating last time an aumation issue was processed.

- id: <http://www.purl.org/ogit/Automation/processingTimestamp>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Automation/AutomationIssue](#)

**1.3.0.195** ogit/otherPhone

The number of an other phone.

- id: <http://www.purl.org/ogit/otherPhone>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Philipp Pelchmann

used

- optional:
  - [ogit/Person](#)

**1.3.0.196** ogit/subCategory

Used to give a subcategory to things.

- id: <http://www.purl.org/ogit/subCategory>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

**1.3.0.197** ogit/Automation/servletClass

Contains the class of the servlet.

- id: <http://www.purl.org/ogit/Automation/servletClass>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.198 ogit/sourceTable**

Contains the source table, that stores where the data are coming from.

- id: <http://www.purl.org/ogit/sourceTable>
- valid-from: Thu Aug 20 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Attachment](#)

**1.3.0.199 ogit/creator**

Creator of an entity.

- id: <http://www.purl.org/ogit/creator>
- valid-from: Thu Aug 20 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- mandatory:
  - [ogit/Automation/Variable](#)
- optional:
  - [ogit/Attachment](#)
  - [ogit/Comment](#)
  - [ogit/License](#)

**1.3.0.200 ogit/ServiceManagement/implementationPlan**

Used to define detail implementation instructions.

- id: <http://www.purl.org/ogit/ServiceManagement/implementationPlan>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ServiceManagement/ChangeRequest](#)

**1.3.0.201 ogit/Datacenter/rackUnit**

The name of the RackUnit within a datacenter.

- id: <http://www.purl.org/ogit/Datacenter/rackUnit>
- valid-from: Thu Oct 15 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.202 ogit/availability**

Contains information about the availability of a service/device.

- id: <http://www.purl.org/ogit/availability>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

**1.3.0.203 ogit/ServiceManagement/allowedForNewBusiness**

If the value of this flag is true, the service could be offered in a store to new users for order. If flag is false, the service will only be available to users with already existing instances/entities of a specific service.

- id: <http://www.purl.org/ogit/ServiceManagement/allowedForNewBusiness>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ServiceManagement/Offering](#)



**1.3.0.204 ogit/Automation/firewallStatus**

Contains information about the firewall status.

- id: <http://www.purl.org/ogit/Automation/firewallStatus>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.205 ogit/lastScannedAt**

Defines a point in time when a component/device was actually scanned last time. The values must be combined date and time with time zone designator according to ISO 8601

- id: <http://www.purl.org/ogit/lastScannedAt>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

**1.3.0.206 ogit/capacityAvailable**

If the flag is true, then service can be ordered by new instance. If the flag is false, the service cannot temporarily be ordered due to capacity reasons.

- id: <http://www.purl.org/ogit/capacityAvailable>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ServiceManagement/Offering](#)

**1.3.0.207 ogit/subType**

A subtype of an an entity.

- id: <http://www.purl.org/ogit/subType>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

**1.3.0.208 ogit/pendingChange**

This field indicates whether or not there are any changes pending against a component/device. When you close or open a change for this component/device, this action sets or clears the flag..

- id: <http://www.purl.org/ogit/pendingChange>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

**1.3.0.209 ogit/Automation/exchangeRate**

Contains the data rate exchanged.

- id: <http://www.purl.org/ogit/Automation/exchangeRate>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.210 ogit/ServiceManagement/sourceStatus**

It can be used to define application specific status values, which are not allowed by a normalized status, e.g. incidentStatus, changeStatus etc.

- id: <http://www.purl.org/ogit/ServiceManagement/sourceStatus>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ServiceManagement/ChangeRequest](#)
  - [ogit/ServiceManagement/Incident](#)
  - [ogit/ServiceManagement/Order](#)
  - [ogit/ServiceManagement/SubTask](#)
  - [ogit/ServiceManagement/Ticket](#)

**1.3.0.211 ogit/Automation/patchNumber**

Contains a patch number.

- id: <http://www.purl.org/ogit/Automation/patchNumber>
- valid-from: Fri Jul 24 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.212 ogit/Automation/cpuType**

Contains the cpu type of a device.

- id: <http://www.purl.org/ogit/Automation/cpuType>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.213 ogit/Automation/dataPrivacy**

Data privacy of a component.

- id: <http://www.purl.org/ogit/Automation/dataPrivacy>
- valid-from: Fri Jul 24 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.214 ogit/inventoryNumber**

This field specifies the inventory component number for the a device as defined by the company-defined device inventory number in the model table. The system uses this number to provide data on the Manufacturer, Model, and Version fields if available.

- id: <http://www.purl.org/ogit/inventoryNumber>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

**1.3.0.215 ogit/message**

Contains a message.

- id: <http://www.purl.org/ogit/message>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- mandatory:
  - [ogit/Automation/History](#)

**1.3.0.216 ogit/webPage**

A web page.

- id: <http://www.purl.org/ogit/webPage>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Philipp Pelchmann

used

- optional:
  - [ogit/Organization](#)
  - [ogit/Person](#)

**1.3.0.217 ogit/Automation/objectIdentifier**

Contains a system object identifier.

- id: <http://www.purl.org/ogit/Automation/objectIdentifier>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.218 ogit/lastUpdatedAt**

Defines latest date and time when a ticket or it's comment was updated. The format of this value could be according to ISO 8601.

- id: <http://www.purl.org/ogit/lastUpdatedAt>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Attachment](#)
  - [ogit/ConfigurationItem](#)
  - [ogit/Event](#)
  - [ogit/ServiceManagement/Order](#)
  - [ogit/ServiceManagement/SubTask](#)
  - [ogit/ServiceManagement/Ticket](#)

**1.3.0.219** ogit/modelNumber

ModelNumber of a device.

- id: <http://www.purl.org/ogit/modelNumber>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

**1.3.0.220** ogit/Automation/fqdn

Contains a fully qualified domain name.

- id: <http://www.purl.org/ogit/Automation/fqdn>
- valid-from: Tue Jan 15 00:00:00 UTC 2019
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.221** ogit/Automation/osKey

Product key for the Operating System.

- id: <http://www.purl.org/ogit/Automation/osKey>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Philipp Pelchmann

used

- optional:
  - [ogit/Automation/MARSNode](#)

## 1.3.0.222 ogit/Automation/brand

Contains the brand of a component/device.

- id: <http://www.purl.org/ogit/Automation/brand>
- valid-from: Tue Jan 15 00:00:00 UTC 2019
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

## 1.3.0.223 ogit/Automation/licenseType

Contains the license type of a component.

- id: <http://www.purl.org/ogit/Automation/licenseType>
- valid-from: Sun May 24 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

## 1.3.0.224 ogit/market

Indicates market, for which an entity may be applicable.

- id: <http://www.purl.org/ogit/market>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ServiceManagement/Offering](#)

**1.3.0.225** `ogit/Automation/virtualSystemType`

Contains the type of the virtual system.

- id: <http://www.purl.org/ogit/Automation/virtualSystemType>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.226** `ogit/Automation/affectedNodeId`

Contains the ID of the node which is affected by this entity.

- id: <http://www.purl.org/ogit/Automation/affectedNodeId>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- mandatory:
  - [ogit/Automation/History](#)

**1.3.0.227** `ogit/Automation/osManufacturer`

Contains the manufacturer of the operating system.

- id: <http://www.purl.org/ogit/Automation/osManufacturer>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)



## 1.3.0.228 ogit/id

General id.

- id: <http://www.purl.org/ogit/id>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- mandatory:
  - [ogit/ConfigurationItem](#)
  - [ogit/Event](#)
  - [ogit/Forum/ShortId](#)
  - [ogit/ServiceManagement/ChangeRequest](#)
  - [ogit/ServiceManagement/Offering](#)
  - [ogit/ServiceManagement/Order](#)
  - [ogit/ServiceManagement/Problem](#)
  - [ogit/ServiceManagement/Service](#)
  - [ogit/ServiceManagement/SubTask](#)
  - [ogit/ServiceManagement/Ticket](#)
- optional:
  - [ogit/Asset](#)
  - [ogit/Attachment](#)
  - [ogit/Automation/MARSNode](#)
  - [ogit/Comment](#)
  - [ogit/License](#)
  - [ogit/Network/NetworkInterface](#)
  - [ogit/ServiceManagement/Incident](#)
  - [ogit/ServiceManagement/Report](#)
  - [ogit/Software/SoftwareComponent](#)
  - [ogit/Task](#)

## 1.3.0.229 ogit/occurenceCount

Defines the number an event occurred.

- id: <http://www.purl.org/ogit/occurenceCount>
- valid-from: Wed Aug 03 00:00:00 UTC 2016
- creator: Philipp Pelchmann

used

- optional:
  - [ogit/Event](#)

**1.3.0.230 ogit/ServiceManagement/solution**

Solution description, for example that is usually provided during incident resolving. This field is also use for problem tickets. There is defines the permanent solution desription for a problem.

- id: <http://www.purl.org/ogit/ServiceManagement/solution>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ServiceManagement/ChangeRequest](#)
  - [ogit/ServiceManagement/Incident](#)
  - [ogit/ServiceManagement/Problem](#)

**1.3.0.231 ogit/creationTime**

Creation time of an entity.

- id: <http://www.purl.org/ogit/creationTime>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Automation/AutomationIssue](#)
  - [ogit/Automation/DynamicEngineData](#)
  - [ogit/Automation/KnowledgeItem](#)
  - [ogit/Automation/MARSNode](#)
  - [ogit/Forum/KnowledgeItemHistory](#)

**1.3.0.232 ogit/subject**

Contains the subject.

- id: <http://www.purl.org/ogit/subject>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Automation/AutomationIssue](#)
  - [ogit/License](#)

**1.3.0.233** ogit/checkedInAt

Defines the time when something was actually checked in. The values can combine date and time with time zone designator according to ISO 8601.

- id: <http://www.purl.org/ogit/checkedInAt>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

**1.3.0.234** ogit/summary

A summary/short description, for example of a ticket.

- id: <http://www.purl.org/ogit/summary>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Event](#)
  - [ogit/ServiceManagement/Order](#)
  - [ogit/ServiceManagement/Ticket](#)

**1.3.0.235** ogit/lastClearedAt

Defines the date an event has been cleared.

- id: <http://www.purl.org/ogit/lastClearedAt>
- valid-from: Wed Aug 03 00:00:00 UTC 2016
- creator: Philipp Pelchmann

used

- optional:
  - [ogit/Event](#)

**1.3.0.236** `ogit/Automation/adminUrl`

Contains an URL (unified resource locator)

- id: <http://www.purl.org/ogit/Automation/adminUrl>
- valid-from: Fri Jul 24 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.237** `ogit/MARS/Resource/class`

Used to classifiy Resource nodes. Will contain values like: 'Backend', 'Database', and so on. Replaces 'Resource↔ Class' from MARS-Schema

- id: <http://www.purl.org/ogit/MARS/Resource/class>
- valid-from: Fri Jun 01 00:00:00 UTC 2018
- creator: [fotto@arago.de](mailto:fotto@arago.de)

used

- mandatory:
  - [ogit/MARS/Resource](#)

**1.3.0.238** `ogit/Automation/marsNodeType`

Contains The Type of the Mars Node. Should be one of Application, Machine, Software, Resource.

- id: <http://www.purl.org/ogit/Automation/marsNodeType>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Automation/MARSNode](#)
  - [ogit/Automation/MARSNodeTemplate](#)
  - [ogit/MARS/Resource](#)

**1.3.0.239** `ogit/Automation/command`

Contains an automation command.

- id: <http://www.purl.org/ogit/Automation/command>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- mandatory:
  - [ogit/Automation/History](#)

**1.3.0.240** `ogit/Automation/basicConfigId`

Contains the internal identifier of the basic configuration of a component .

- id: <http://www.purl.org/ogit/Automation/basicConfigId>
- valid-from: Wed May 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.241** `ogit/size`

The size, e.g. of a file.

- id: <http://www.purl.org/ogit/size>
- valid-from: Thu Mar 26 00:00:00 UTC 2015
- creator: arago Technologies

used

- optional:
  - [ogit/Attachment](#)

**1.3.0.242** ogit/serviceContract

This field specifies the contract covering a service.

- id: <http://www.purl.org/ogit/serviceContract>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

**1.3.0.243** ogit/Automation/serviceStatus

Contains the status of a service.

- id: <http://www.purl.org/ogit/Automation/serviceStatus>
- valid-from: Fri Jul 24 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)
  - [ogit/MARS/Resource](#)

**1.3.0.244** ogit/vendor

Contains the vendor of a device or software/hardware component.

- id: <http://www.purl.org/ogit/vendor>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

**1.3.0.245 ogit/firstOccurredAt**

Defines the date of first occurrence of an event

- id: <http://www.purl.org/ogit/firstOccurredAt>
- valid-from: Wed Aug 03 00:00:00 UTC 2016
- creator: Philipp Pelchmann

used

- optional:
  - [ogit/Event](#)

**1.3.0.246 ogit/validFrom**

Defines a point in time when something becomes valid.

- id: <http://www.purl.org/ogit/validFrom>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/License](#)
  - [ogit/ServiceManagement/Offering](#)

**1.3.0.247 ogit/Automation/governingContract**

Contains information about the governing contract.

- id: <http://www.purl.org/ogit/Automation/governingContract>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

**1.3.0.248** ogit/Automation/systemType

Contains the type of the system.

- id: <http://www.purl.org/ogit/Automation/systemType>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.249** ogit/Automation/tcpPort

The tcp port.

- id: <http://www.purl.org/ogit/Automation/tcpPort>
- valid-from: Fri Jul 24 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.250** ogit/position

Indicates user's position. This field contains a string value.

- id: <http://www.purl.org/ogit/position>
- valid-from: Tue Oct 18 00:00:00 UTC 2016
- creator: Arthur Shoba

used

- optional:
  - [ogit/Person](#)



**1.3.0.251** ogit/reportedAt

Defines the time when something was actually reported. The values can combine date and time with time zone designator according to ISO 8601. Reported time is used in incident management in the following manner: in most cases the reported time equals the time when the incident is created. In some cases, e.g. the incident is created after the helpdesk has already worked on some request before it was decided to create an incident, the reported time might differ from ticket creation/opening time.

- id: <http://www.purl.org/ogit/reportedAt>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ServiceManagement/ChangeRequest](#)
  - [ogit/ServiceManagement/Incident](#)
  - [ogit/ServiceManagement/Problem](#)

**1.3.0.252** ogit/Automation/logLevel

Contains the numeric log level of the history entry.

- id: <http://www.purl.org/ogit/Automation/logLevel>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- mandatory:
  - [ogit/Automation/History](#)

**1.3.0.253** ogit/ServiceManagement/targetStartAt

Defines a point in time when the work on a change should start. This date time is defined by the requester. The values must be combined date and time with time zone designator according to ISO 8601

- id: <http://www.purl.org/ogit/ServiceManagement/targetStartAt>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ServiceManagement/ChangeRequest](#)
  - [ogit/ServiceManagement/SubTask](#)

**1.3.0.254** `ogit/ServiceManagement/reportedSource`

Can be used to define how a ticket was communicated. It could define some kind of communication channel ("← ServiceDesk", "Email") or, e.g. for Incident records, it might define that the ticket was produced automatically from an event management system.

- id: <http://www.purl.org/ogit/ServiceManagement/reportedSource>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Event](#)
  - [ogit/ServiceManagement/Incident](#)
  - [ogit/ServiceManagement/Order](#)
  - [ogit/ServiceManagement/Ticket](#)

**1.3.0.255** `ogit/ServiceManagement/task`

A task related to a Service Management process.

- id: <http://www.purl.org/ogit/ServiceManagement/task>
- valid-from: Mon Jul 06 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ServiceManagement/Incident](#)

**1.3.0.256** `ogit/instance`

Defines the name of an instance.

- id: <http://www.purl.org/ogit/instance>
- valid-from: Wed Aug 03 00:00:00 UTC 2016
- creator: Philipp Pelchmann

used

- optional:
  - [ogit/Event](#)
  - [ogit/Timeseries](#)

**1.3.0.257 ogit/Automation/sendData**

Boolean flag whether issue data should be sent to decision service.

- id: <http://www.purl.org/ogit/Automation/sendData>
- valid-from: Tue May 01 00:00:00 UTC 2018
- creator: [cy@arago.de](mailto:cy@arago.de)

used

- optional:
  - [ogit/Automation/KIRanking](#)

**1.3.0.258 ogit/isSupported**

Indicates whether the service currently is supported. This field contains a boolean value.

- id: <http://www.purl.org/ogit/isSupported>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

**1.3.0.259 ogit/operationalStatus**

An operational status for an entity. At this level of specification no list of values is specified. However, applications using this attribute are expected to allow only a fixed list of values that seems useful in the application's semantic context.

- id: <http://www.purl.org/ogit/operationalStatus>
- valid-from: Wed May 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

**1.3.0.260** ogit/validTo

Defines a point in time when something stops being valid.

- id: <http://www.purl.org/ogit/validTo>
- valid-from: Tue Nov 29 00:00:00 UTC 2016
- creator: [stravlos@arago.co](mailto:stravlos@arago.co)

used

- optional:
  - [ogit/License](#)

**1.3.0.261** ogit/ServiceManagement/changeStatus

Defines the status of a change record within the service management.

- id: <http://www.purl.org/ogit/ServiceManagement/changeStatus>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ServiceManagement/ChangeRequest](#)

**1.3.0.262** ogit/Automation/projectName

Contains the project name of a component.

- id: <http://www.purl.org/ogit/Automation/projectName>
- valid-from: Mon Nov 02 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Automation/MARSNode](#)