

---

## ServiceManagement

---

April 4, 2019

<b>1 Module Documentation</b>	<b>1</b>
1.1 Entities	1
1.1.0.1 ogit/Penalty	1
1.1.0.2 ogit/Organization	1
1.1.0.3 ogit/MARS/Software	3
1.1.0.4 ogit/Role	4
1.1.0.5 ogit/Price/Invoice	5
1.1.0.6 ogit/ServiceManagement/ChangeRequest	5
1.1.0.7 ogit/Automation/MARSNode	8
1.1.0.8 ogit/Attachment	11
1.1.0.9 ogit/ServiceManagement/SubTask	11
1.1.0.10 ogit/ServiceManagement/Problem	13
1.1.0.11 ogit/Comment	15
1.1.0.12 ogit/Region	15
1.1.0.13 ogit/Software/Connector	16
1.1.0.14 ogit/ServiceManagement/ApprovalTask	16
1.1.0.15 ogit/ServiceManagement/Order	17
1.1.0.16 ogit/ConfigurationItem	19
1.1.0.17 ogit/ServiceManagement/Incident	21
1.1.0.18 ogit/MARS/Application	23
1.1.0.19 ogit/Software/Application	24
1.1.0.20 ogit/ServiceManagement/Report	25
1.1.0.21 ogit/ServiceManagement/Offering	25
1.1.0.22 ogit/Automation/MARSModelTemplate	26
1.1.0.23 ogit/CatalogItem	27
1.1.0.24 ogit/Contract	28
1.1.0.25 ogit/MARS/Machine	28
1.1.0.26 ogit/ServiceManagement/SLA	30
1.1.0.27 ogit/MARS/Resource	30
1.1.0.28 ogit/Person	31
1.1.0.29 ogit/Location	33
1.1.0.30 ogit/Task	34
1.1.0.31 ogit/ServiceManagement/Action	35
1.1.0.32 ogit/Event	35
1.1.0.33 ogit/Automation/AutomationIssue	37
1.1.0.34 ogit/Automation/MARSModel	38
1.1.0.35 ogit/Parameter	38
1.1.0.36 ogit/ServiceManagement/Service	39
1.1.0.37 ogit/Policy	40
1.1.0.38 ogit/ServiceManagement/Ticket	41
1.1.0.39 ogit/Cost/CostElement	42
1.1.0.40 ogit/Timeseries	43

1.2 Verbs	44
1.2.0.1 ogit/bills	44
1.2.0.2 ogit/contains	44
1.2.0.3 ogit/manages	44
1.2.0.4 ogit/defines	45
1.2.0.5 ogit/triggers	45
1.2.0.6 ogit/supports	45
1.2.0.7 ogit/supervises	45
1.2.0.8 ogit/assignedTo	46
1.2.0.9 ogit/generates	47
1.2.0.10 ogit/specifies	47
1.2.0.11 ogit/calls	47
1.2.0.12 ogit/opens	47
1.2.0.13 ogit/describes	48
1.2.0.14 ogit/precedes	48
1.2.0.15 ogit/creates	49
1.2.0.16 ogit/complies	49
1.2.0.17 ogit/locatedIn	49
1.2.0.18 ogit/corresponds	50
1.2.0.19 ogit/affects	50
1.2.0.20 ogit/requires	52
1.2.0.21 ogit/implements	52
1.2.0.22 ogit/requests	52
1.2.0.23 ogit/updates	53
1.2.0.24 ogit/causes	53
1.2.0.25 ogit/owns	54
1.2.0.26 ogit/closes	54
1.2.0.27 ogit/belongs	54
1.2.0.28 ogit/reports	55
1.2.0.29 ogit/uses	55
1.2.0.30 ogit/reportedOn	56
1.2.0.31 ogit/governs	57
1.2.0.32 ogit/relates	57
1.2.0.33 ogit/availableIn	58
1.3 Attributes	59
1.3.0.1 ogit/MARS/Network/fqdn	59
1.3.0.2 ogit/Automation/serviceType	59
1.3.0.3 ogit/ciType	59
1.3.0.4 ogit/MARS/Software/installPath	60
1.3.0.5 ogit/ServiceManagement/requirementId	60
1.3.0.6 ogit/reviewedAt	60
1.3.0.7 ogit/MARS/Network/interfaceMAC	61

1.3.0.8 ogit/Automation/serialNumber . . . . .	61
1.3.0.9 ogit/Automation/servletName . . . . .	61
1.3.0.10 ogit/Automation/cpuCoreCount . . . . .	62
1.3.0.11 ogit/Automation/serviceId . . . . .	62
1.3.0.12 ogit/manufacture . . . . .	62
1.3.0.13 ogit/ServiceManagement/testPlan . . . . .	63
1.3.0.14 ogit/certainty . . . . .	63
1.3.0.15 ogit/reason . . . . .	63
1.3.0.16 ogit/currency . . . . .	64
1.3.0.17 ogit/category . . . . .	64
1.3.0.18 ogit/ServiceManagement/isRequired . . . . .	64
1.3.0.19 ogit/comment . . . . .	65
1.3.0.20 ogit/Automation/osVersion . . . . .	65
1.3.0.21 ogit/assignedAt . . . . .	65
1.3.0.22 ogit/endOfWarranty . . . . .	66
1.3.0.23 ogit/postalCode . . . . .	66
1.3.0.24 ogit/Automation/buildType . . . . .	66
1.3.0.25 ogit/Automation/cpuManufacturer . . . . .	67
1.3.0.26 ogit/Automation/virtualMachineName . . . . .	67
1.3.0.27 ogit/productOrderNumber . . . . .	67
1.3.0.28 ogit/MARS/Network/bindAddress . . . . .	68
1.3.0.29 ogit/ServiceManagement/approvalStatus . . . . .	68
1.3.0.30 ogit/MARS/Machine/class . . . . .	68
1.3.0.31 ogit/MARS/Machine/cpuArch . . . . .	69
1.3.0.32 ogit/checkedOutAt . . . . .	69
1.3.0.33 ogit/email . . . . .	69
1.3.0.34 ogit/Automation/moveToProductionAt . . . . .	70
1.3.0.35 ogit/MARS/Software/logPath . . . . .	70
1.3.0.36 ogit/ServiceManagement/resolvedAt . . . . .	70
1.3.0.37 ogit/urgency . . . . .	71
1.3.0.38 ogit/deliveredAt . . . . .	71
1.3.0.39 ogit/Automation/osServicePack . . . . .	71
1.3.0.40 ogit/alternativeName . . . . .	72
1.3.0.41 ogit/isCritical . . . . .	72
1.3.0.42 ogit/asset . . . . .	72
1.3.0.43 ogit/Automation/portNumberListener . . . . .	73
1.3.0.44 ogit/function . . . . .	73
1.3.0.45 ogit/positionNumber . . . . .	73
1.3.0.46 ogit/ServiceManagement/customer . . . . .	74
1.3.0.47 ogit/Version/major . . . . .	74
1.3.0.48 ogit/Automation/memory . . . . .	74
1.3.0.49 ogit/integrity . . . . .	75

1.3.0.50 ogit/Automation/companyName . . . . .	75
1.3.0.51 ogit/ServiceManagement/scheduledStartAt . . . . .	75
1.3.0.52 ogit/country . . . . .	76
1.3.0.53 ogit/businessCategory . . . . .	76
1.3.0.54 ogit/Automation/middlewareType . . . . .	76
1.3.0.55 ogit/Automation/serviceName . . . . .	77
1.3.0.56 ogit/project . . . . .	77
1.3.0.57 ogit/Automation/licenseAvailability . . . . .	77
1.3.0.58 ogit/ServiceManagement/granularity . . . . .	78
1.3.0.59 ogit/question . . . . .	78
1.3.0.60 ogit/maintenanceState . . . . .	78
1.3.0.61 ogit/notification . . . . .	79
1.3.0.62 ogit/ServiceManagement/externalTicketId . . . . .	79
1.3.0.63 ogit/sourceId . . . . .	79
1.3.0.64 ogit/url . . . . .	80
1.3.0.65 ogit/uri . . . . .	80
1.3.0.66 ogit/purchasedAt . . . . .	80
1.3.0.67 ogit/Automation/cpuCount . . . . .	81
1.3.0.68 ogit/Automation/databaseSchema . . . . .	81
1.3.0.69 ogit/mobilePhone . . . . .	81
1.3.0.70 ogit/Automation/additionalMacAddress . . . . .	82
1.3.0.71 ogit/severity . . . . .	82
1.3.0.72 ogit/connectorId . . . . .	82
1.3.0.73 ogit/Automation/dataClassification . . . . .	83
1.3.0.74 ogit/Automation/firmwareVersion . . . . .	83
1.3.0.75 ogit/effort . . . . .	83
1.3.0.76 ogit/startedAt . . . . .	84
1.3.0.77 ogit/ServiceManagement/taskName . . . . .	84
1.3.0.78 ogit/assetTag . . . . .	84
1.3.0.79 ogit/ipAddress . . . . .	85
1.3.0.80 ogit/unit . . . . .	85
1.3.0.81 ogit/Automation/installCount . . . . .	85
1.3.0.82 ogit/installedAt . . . . .	86
1.3.0.83 ogit/Automation/marsNodeFormalRepresentation . . . . .	86
1.3.0.84 ogit/updateCount . . . . .	86
1.3.0.85 ogit/installStatus . . . . .	87
1.3.0.86 ogit/city . . . . .	87
1.3.0.87 ogit/Automation/systemClass . . . . .	87
1.3.0.88 ogit/Automation/diskCount . . . . .	88
1.3.0.89 ogit/Automation/automationState . . . . .	88
1.3.0.90 ogit/ServiceManagement/resolvedInTime . . . . .	88
1.3.0.91 ogit/ServiceManagement/incidentStatus . . . . .	89

1.3.0.92 ogit/taskLog . . . . .	89
1.3.0.93 ogit/status . . . . .	89
1.3.0.94 ogit/createdAt . . . . .	90
1.3.0.95 ogit/ServiceManagement/workAround . . . . .	90
1.3.0.96 ogit/ServiceManagement/rootCause . . . . .	90
1.3.0.97 ogit/model . . . . .	91
1.3.0.98 ogit/Automation/domain . . . . .	91
1.3.0.99 ogit/Automation/lifecycle . . . . .	91
1.3.0.100 ogit/lastName . . . . .	92
1.3.0.101 ogit/Automation/cpuModel . . . . .	92
1.3.0.102 ogit/Automation/buildName . . . . .	92
1.3.0.103 ogit/Automation/applInstanceType . . . . .	93
1.3.0.104 ogit/modificationTime . . . . .	93
1.3.0.105 ogit/ServiceManagement/problemStatus . . . . .	93
1.3.0.106 ogit/priority . . . . .	94
1.3.0.107 ogit/shortDescription . . . . .	94
1.3.0.108 ogit/middleName . . . . .	94
1.3.0.109 ogit/resource . . . . .	95
1.3.0.110 ogit/ServiceManagement/targetFinishAt . . . . .	95
1.3.0.111 ogit/MARS/Software/instanceId . . . . .	95
1.3.0.112 ogit/accessControl . . . . .	96
1.3.0.113 ogit/ServiceManagement/ticketId . . . . .	96
1.3.0.114 ogit/justification . . . . .	96
1.3.0.115 ogit/invoiceNumber . . . . .	97
1.3.0.116 ogit/response . . . . .	97
1.3.0.117 ogit/ServiceManagement/externalTicketSource . . . . .	97
1.3.0.118 ogit/Automation/diskSpace . . . . .	98
1.3.0.119 ogit/soxClass . . . . .	98
1.3.0.120 ogit/closedAt . . . . .	98
1.3.0.121 ogit/ServiceManagement/taskStatus . . . . .	99
1.3.0.122 ogit/ServiceManagement/resolutionCode . . . . .	99
1.3.0.123 ogit/expiresAt . . . . .	99
1.3.0.124 ogit/streetAddress . . . . .	100
1.3.0.125 ogit/businessCriticality . . . . .	100
1.3.0.126 ogit/leaseContract . . . . .	100
1.3.0.127 ogit/MARS/Application/subClass . . . . .	101
1.3.0.128 ogit/securityClass . . . . .	101
1.3.0.129 ogit/serialNumber . . . . .	101
1.3.0.130 ogit/firstName . . . . .	102
1.3.0.131 ogit/MARS/Network/defaultGateway . . . . .	102
1.3.0.132 ogit/Price/priceAmount . . . . .	102
1.3.0.133 ogit/assignedGroup . . . . .	103

1.3.0.134 ogit/macAddress . . . . .	103
1.3.0.135 ogit/Automation/osName . . . . .	103
1.3.0.136 ogit/version . . . . .	104
1.3.0.137 ogit/title . . . . .	104
1.3.0.138 ogit/ServiceManagement/elapsedTime . . . . .	104
1.3.0.139 ogit/Automation/appServer . . . . .	105
1.3.0.140 ogit/MARS/Machine/ram . . . . .	105
1.3.0.141 ogit/MARS/Network/port . . . . .	105
1.3.0.142 ogit/class . . . . .	106
1.3.0.143 ogit/lengthOfReportingPeriod . . . . .	106
1.3.0.144 ogit/Version/patch . . . . .	106
1.3.0.145 ogit/content . . . . .	107
1.3.0.146 ogit/confidentiality . . . . .	107
1.3.0.147 ogit/Automation/deployStatus . . . . .	107
1.3.0.148 ogit/MARS/Machine/kernel . . . . .	108
1.3.0.149 ogit/lastOccurredAt . . . . .	108
1.3.0.150 ogit/Automation/isDeployed . . . . .	108
1.3.0.151 ogit/Automation/processingNode . . . . .	109
1.3.0.152 ogit/Automation/issueFormalRepresentation . . . . .	109
1.3.0.153 ogit/MARS/Network/protocol . . . . .	109
1.3.0.154 ogit/ServiceManagement/scheduledFinishAt . . . . .	110
1.3.0.155 ogit/MARS/Network/ipVersion . . . . .	110
1.3.0.156 ogit/name . . . . .	110
1.3.0.157 ogit/Automation/software . . . . .	111
1.3.0.158 ogit/Automation/originNode . . . . .	112
1.3.0.159 ogit/description . . . . .	112
1.3.0.160 ogit/ServiceManagement/slaStage . . . . .	113
1.3.0.161 ogit/finishedAt . . . . .	113
1.3.0.162 ogit/Automation/host . . . . .	113
1.3.0.163 ogit/externalId . . . . .	114
1.3.0.164 ogit/impact . . . . .	114
1.3.0.165 ogit/contact . . . . .	114
1.3.0.166 ogit/Automation/applInfrastructureType . . . . .	115
1.3.0.167 ogit/Automation/issueType . . . . .	115
1.3.0.168 ogit/MARS/Software/subClass . . . . .	115
1.3.0.169 ogit/Version/minor . . . . .	116
1.3.0.170 ogit/orderedAt . . . . .	116
1.3.0.171 ogit/faultCount . . . . .	116
1.3.0.172 ogit/risk . . . . .	117
1.3.0.173 ogit/lastUpdatedBy . . . . .	117
1.3.0.174 ogit/ServiceManagement/fallbackPlan . . . . .	117
1.3.0.175 ogit/isRoot . . . . .	118

1.3.0.176 ogit/openedAt	118
1.3.0.177 ogit/Automation/virtualSystemName	118
1.3.0.178 ogit/expirationDate	119
1.3.0.179 ogit/officePhone	119
1.3.0.180 ogit/phone	119
1.3.0.181 ogit/acknowledgeState	120
1.3.0.182 ogit/deadline	120
1.3.0.183 ogit/Automation/osLicense	120
1.3.0.184 ogit/fax	121
1.3.0.185 ogit/Automation/databaseServer	121
1.3.0.186 ogit/Automation/portNumber	121
1.3.0.187 ogit/Automation/webServer	122
1.3.0.188 ogit/type	122
1.3.0.189 ogit/Automation/softwareKey	122
1.3.0.190 ogit/Automation/installPath	123
1.3.0.191 ogit/Automation/licenseName	123
1.3.0.192 ogit/Automation/contextPath	123
1.3.0.193 ogit/Automation/cpuSpeed	124
1.3.0.194 ogit/Automation/processingTimestamp	124
1.3.0.195 ogit/otherPhone	124
1.3.0.196 ogit/subCategory	125
1.3.0.197 ogit/MARS/Network/interfacePrefixLength	125
1.3.0.198 ogit/isMutable	125
1.3.0.199 ogit/Automation/servletClass	126
1.3.0.200 ogit/ServiceManagement/leftTime	126
1.3.0.201 ogit/sourceTable	126
1.3.0.202 ogit/creator	127
1.3.0.203 ogit/ServiceManagement/implementationPlan	127
1.3.0.204 ogit/Datacenter/rackUnit	127
1.3.0.205 ogit/availability	128
1.3.0.206 ogit/ServiceManagement/allowedForNewBusiness	128
1.3.0.207 ogit/Automation/firewallStatus	128
1.3.0.208 ogit/MARS/Network/interfaceIP	129
1.3.0.209 ogit/lastScannedAt	129
1.3.0.210 ogit/capacityAvailable	129
1.3.0.211 ogit/subType	130
1.3.0.212 ogit/ServiceManagement/eventMessage	130
1.3.0.213 ogit/MARS/Application/class	130
1.3.0.214 ogit/pendingChange	130
1.3.0.215 ogit/Automation/exchangeRate	131
1.3.0.216 ogit/ServiceManagement/sourceStatus	131
1.3.0.217 ogit/Automation/patchNumber	131



1.3.0.218 ogit/Automation/cpuType . . . . .	132
1.3.0.219 ogit/Automation/dataPrivacy . . . . .	132
1.3.0.220 ogit/inventoryNumber . . . . .	132
1.3.0.221 ogit/webPage . . . . .	133
1.3.0.222 ogit/Automation/objectIdentifier . . . . .	133
1.3.0.223 ogit/lastUpdatedAt . . . . .	133
1.3.0.224 ogit/modelNumber . . . . .	134
1.3.0.225 ogit/Automation/fqdn . . . . .	134
1.3.0.226 ogit/Automation/osKey . . . . .	134
1.3.0.227 ogit/Automation/brand . . . . .	135
1.3.0.228 ogit/Automation/licenseType . . . . .	135
1.3.0.229 ogit/market . . . . .	135
1.3.0.230 ogit/Automation/virtualSystemType . . . . .	136
1.3.0.231 ogit/MARS/Machine/distroName . . . . .	136
1.3.0.232 ogit/MARS/Network/interfaceName . . . . .	136
1.3.0.233 ogit/Automation/osManufacturer . . . . .	137
1.3.0.234 ogit/ServiceManagement/licenseTokenStatus . . . . .	137
1.3.0.235 ogit/id . . . . .	137
1.3.0.236 ogit/MARS/Software/class . . . . .	138
1.3.0.237 ogit/occurenceCount . . . . .	138
1.3.0.238 ogit/ServiceManagement/eventNodeId . . . . .	138
1.3.0.239 ogit/ServiceManagement/solution . . . . .	139
1.3.0.240 ogit/creationTime . . . . .	139
1.3.0.241 ogit/subject . . . . .	139
1.3.0.242 ogit/checkedInAt . . . . .	140
1.3.0.243 ogit/summary . . . . .	140
1.3.0.244 ogit/lastClearedAt . . . . .	140
1.3.0.245 ogit/Automation/adminUrl . . . . .	141
1.3.0.246 ogit/MARS/Resource/class . . . . .	141
1.3.0.247 ogit/Automation/marsNodeType . . . . .	141
1.3.0.248 ogit/Automation/basicConfigId . . . . .	142
1.3.0.249 ogit/size . . . . .	142
1.3.0.250 ogit/serviceContract . . . . .	142
1.3.0.251 ogit/Automation/serviceStatus . . . . .	143
1.3.0.252 ogit/values . . . . .	143
1.3.0.253 ogit/vendor . . . . .	143
1.3.0.254 ogit/firstOccurredAt . . . . .	144
1.3.0.255 ogit/validFrom . . . . .	144
1.3.0.256 ogit/Automation/governingContract . . . . .	144
1.3.0.257 ogit/Automation/systemType . . . . .	145
1.3.0.258 ogit/Automation/tcpPort . . . . .	145
1.3.0.259 ogit/MARS/Software/serviceName . . . . .	145

---

1.3.0.260 ogit/position . . . . .	146
1.3.0.261 ogit/reportedAt . . . . .	146
1.3.0.262 ogit/ServiceManagement/targetStartAt . . . . .	146
1.3.0.263 ogit/ServiceManagement/reportedSource . . . . .	147
1.3.0.264 ogit/ServiceManagement/task . . . . .	147
1.3.0.265 ogit/instance . . . . .	147
1.3.0.266 ogit/isSupported . . . . .	148
1.3.0.267 ogit/operationalStatus . . . . .	148
1.3.0.268 ogit/validTo . . . . .	148
1.3.0.269 ogit/ServiceManagement/changeStatus . . . . .	149
1.3.0.270 ogit/Automation/projectName . . . . .	149

# Chapter 1

## Module Documentation

### 1.1 Entities

#### 1.1.0.1 ogit/Penalty

Defines the penalty that has to be paid in certain circumstances

- id: <http://www.purl.org/ogit/Penalty>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: SGO
- parent: ogit/Node

#### attributes

- optional:
  - [ogit/description](#)

#### incoming edges

- [ogit/triggers](#) <= [ogit/ServiceManagement/SLA](#)

#### 1.1.0.2 ogit/Organization

An identity that represents an organization, company, or some other grouping of Person objects. Entities of this type should be created with a predefined ID. Those IDs should be named like a domain name, i.e. a concatenation of some strings separated with a dot. if organization data is created from a LDAP then a mapping like "cn=John Doe,dc=example,dc=com" => "john\_doe.example.com" should be employed. The ogit/function attribute should be used to tell what kind of grouping an entity of type Organization is: company, department, group, ...

- id: <http://www.purl.org/ogit/Organization>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: SGO
- parent: ogit/Node

**attributes**

- mandatory:
  - [ogit/name](#)
- optional:
  - [ogit/businessCategory](#)
  - [ogit/city](#)
  - [ogit/country](#)
  - [ogit/description](#)
  - [ogit/email](#)
  - [ogit/function](#)
  - [ogit/phone](#)
  - [ogit/postalCode](#)
  - [ogit/sourceId](#)
  - [ogit/status](#)
  - [ogit/streetAddress](#)
  - [ogit/webPage](#)

**incoming edges**

- [ogit/assignedTo](#) <= [ogit/ServiceManagement/ApprovalTask](#)
- [ogit/assignedTo](#) <= [ogit/ServiceManagement/ChangeRequest](#)
- [ogit/assignedTo](#) <= [ogit/ServiceManagement/Incident](#)
- [ogit/assignedTo](#) <= [ogit/ServiceManagement/Order](#)
- [ogit/assignedTo](#) <= [ogit/ServiceManagement/Problem](#)
- [ogit/assignedTo](#) <= [ogit/ServiceManagement/SubTask](#)
- [ogit/assignedTo](#) <= [ogit/ServiceManagement/Ticket](#)

**outgoing edges**

- [ogit/defines](#) => [ogit/ServiceManagement/Offering](#)
- [ogit/supervises](#) => [ogit/ServiceManagement/SubTask](#)
- [ogit/supervises](#) => [ogit/ServiceManagement/ChangeRequest](#)
- [ogit/supervises](#) => [ogit/ServiceManagement/Order](#)
- [ogit/supervises](#) => [ogit/ServiceManagement/Ticket](#)
- [ogit/supervises](#) => [ogit/ServiceManagement/Problem](#)
- [ogit/supervises](#) => [ogit/ServiceManagement/Incident](#)

## 1.1.0.3 ogit/MARS/Software

Vertices of this type are the 'S'-nodes in the MARS model. 'S' stands for 'Software' and those nodes form the second lowest layer in the A-R-S-M layer model. It's up to the user whether it will model a specific instance of a software (linked to just one 'Machine' node) or several identical instances (then the 'Software' node will be linked to several 'Machine' nodes)

- id: <http://www.purl.org/ogit/MARS/Software>
- valid-from: Fri Jun 01 00:00:00 UTC 2018
- creator: FCO
- scope: NTO
- parent: ogit/Node

## attributes

- mandatory:
  - [ogit/MARS/Software/class](#)
  - [ogit/MARS/Software/subClass](#)
  - [ogit/name](#)
- optional:
  - [ogit/Automation/automationState](#)
  - [ogit/Automation/lifecycle](#)
  - [ogit/Automation/marsNodeType](#)
  - [ogit/Automation/serviceStatus](#)
  - [ogit/MARS/Network/bindAddress](#)
  - [ogit/MARS/Network/port](#)
  - [ogit/MARS/Network/protocol](#)
  - [ogit/MARS/Software/installPath](#)
  - [ogit/MARS/Software/installPath](#)
  - [ogit/MARS/Software/instanceId](#)
  - [ogit/MARS/Software/logPath](#)
  - [ogit/MARS/Software/serviceName](#)
  - [ogit/Version/major](#)
  - [ogit/Version/minor](#)
  - [ogit/Version/patch](#)
  - [ogit/endTimeOfWarranty](#)
  - [ogit/serialNumber](#)
  - [ogit/url](#)
  - [ogit/vendor](#)

**incoming edges**

- [ogit/affects](#) <= [ogit/ServiceManagement/ChangeRequest](#)
- [ogit/affects](#) <= [ogit/ServiceManagement/Incident](#)
- [ogit/affects](#) <= [ogit/ServiceManagement/Problem](#)
- [ogit/affects](#) <= [ogit/ServiceManagement/Ticket](#)
- [ogit/relates](#) <= [ogit/ServiceManagement/ChangeRequest](#)
- [ogit/relates](#) <= [ogit/ServiceManagement/Report](#)
- [ogit/reportedOn](#) <= [ogit/ServiceManagement/ChangeRequest](#)
- [ogit/reportedOn](#) <= [ogit/ServiceManagement/Incident](#)
- [ogit/reportedOn](#) <= [ogit/ServiceManagement/Order](#)
- [ogit/reportedOn](#) <= [ogit/ServiceManagement/Problem](#)
- [ogit/reportedOn](#) <= [ogit/ServiceManagement/Ticket](#)

**1.1.0.4 ogit/Role**

In contrast to [ogit/Organization](#), which is mainly a collection of persons and/or other organizations, [ogit/Role](#) defines behavior of an actor along with necessary privileges.

- id: <http://www.purl.org/ogit/Role>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: SGO
- parent: [ogit/Node](#)

**attributes**

- mandatory:
  - [ogit/name](#)
- optional:
  - [ogit/description](#)
  - [ogit/status](#)

**outgoing edges**

- [ogit/manages](#) => [ogit/ServiceManagement/Service](#)

## 1.1.0.5 ogit/Price/Invoice

Models any type of invoice

- id: <http://www.purl.org/ogit/Price/Invoice>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: NTO
- parent: ogit/Node

## attributes

- mandatory:
  - [ogit/Price/priceAmount](#)
  - [ogit/currency](#)
- optional:
  - [ogit/description](#)
  - [ogit/name](#)

## incoming edges

- [ogit/generates](#) <= [ogit/ServiceManagement/Report](#)

## outgoing edges

- [ogit/bills](#) => [ogit/ServiceManagement/Order](#)

## 1.1.0.6 ogit/ServiceManagement/ChangeRequest

This entity type defines a change request ticket

- id: <http://www.purl.org/ogit/ServiceManagement/ChangeRequest>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: NTO
- parent: ogit/Node

**attributes**

- mandatory:
  - [ogit/id](#)
- optional:
  - [ogit/ServiceManagement/changeStatus](#)
  - [ogit/ServiceManagement/customer](#)
  - [ogit/ServiceManagement/fallbackPlan](#)
  - [ogit/ServiceManagement/implementationPlan](#)
  - [ogit/ServiceManagement/resolutionCode](#)
  - [ogit/ServiceManagement/scheduledFinishAt](#)
  - [ogit/ServiceManagement/scheduledStartAt](#)
  - [ogit/ServiceManagement/solution](#)
  - [ogit/ServiceManagement/sourceStatus](#)
  - [ogit/ServiceManagement/targetFinishAt](#)
  - [ogit/ServiceManagement/targetStartAt](#)
  - [ogit/ServiceManagement/testPlan](#)
  - [ogit/assignedGroup](#)
  - [ogit/category](#)
  - [ogit/effort](#)
  - [ogit/finishedAt](#)
  - [ogit/justification](#)
  - [ogit/reportedAt](#)
  - [ogit/reviewedAt](#)
  - [ogit/risk](#)
  - [ogit/startedAt](#)

**incoming edges**

- [ogit/belongs](#) <= [ogit/ServiceManagement/ApprovalTask](#)
- [ogit/belongs](#) <= [ogit/ServiceManagement/SubTask](#)
- [ogit/belongs](#) <= [ogit/Attachment](#)
- [ogit/causes](#) <= [ogit/ServiceManagement/ChangeRequest](#)
- [ogit/causes](#) <= [ogit/ServiceManagement/Incident](#)
- [ogit/causes](#) <= [ogit/ServiceManagement/Order](#)
- [ogit/causes](#) <= [ogit/ServiceManagement/Problem](#)
- [ogit/closes](#) <= [ogit/Person](#)
- [ogit/creates](#) <= [ogit/Software/Connector](#)
- [ogit/opens](#) <= [ogit/Person](#)
- [ogit/relates](#) <= [ogit/ServiceManagement/ChangeRequest](#)
- [ogit/relates](#) <= [ogit/ServiceManagement/Incident](#)



- `ogit/relates`  $\leq$  `ogit/ServiceManagement/Order`
- `ogit/relates`  $\leq$  `ogit/ServiceManagement/Problem`
- `ogit/requests`  $\leq$  `ogit/Person`
- `ogit/supervises`  $\leq$  `ogit/Organization`
- `ogit/supervises`  $\leq$  `ogit/Person`
- `ogit/updates`  $\leq$  `ogit/Person`
- `ogit/uses`  $\leq$  `ogit/ServiceManagement/ChangeRequest`

#### outgoing edges

- `ogit/affects`  $\Rightarrow$  `ogit/Location`
- `ogit/affects`  $\Rightarrow$  `ogit/ConfigurationItem`
- `ogit/affects`  $\Rightarrow$  `ogit/ServiceManagement/Service`
- `ogit/affects`  $\Rightarrow$  `ogit/Person`
- `ogit/affects`  $\Rightarrow$  `ogit/MARS/Application`
- `ogit/affects`  $\Rightarrow$  `ogit/MARS/Resource`
- `ogit/affects`  $\Rightarrow$  `ogit/MARS/Software`
- `ogit/affects`  $\Rightarrow$  `ogit/MARS/Machine`
- `ogit/affects`  $\Rightarrow$  `ogit/Automation/MARSNode`
- `ogit/assignedTo`  $\Rightarrow$  `ogit/Person`
- `ogit/assignedTo`  $\Rightarrow$  `ogit/Organization`
- `ogit/assignedTo`  $\Rightarrow$  `ogit/ServiceManagement/Service`
- `ogit/causes`  $\Rightarrow$  `ogit/ServiceManagement/ChangeRequest`
- `ogit/causes`  $\Rightarrow$  `ogit/ServiceManagement/Order`
- `ogit/complies`  $\Rightarrow$  `ogit/ServiceManagement/SLA`
- `ogit/corresponds`  $\Rightarrow$  `ogit/ServiceManagement/Ticket`
- `ogit/corresponds`  $\Rightarrow$  `ogit/Automation/AutomationIssue`
- `ogit/locatedIn`  $\Rightarrow$  `ogit/Location`
- `ogit/relates`  $\Rightarrow$  `ogit/ServiceManagement/Problem`
- `ogit/relates`  $\Rightarrow$  `ogit/ServiceManagement/Incident`
- `ogit/relates`  $\Rightarrow$  `ogit/ServiceManagement/ChangeRequest`
- `ogit/relates`  $\Rightarrow$  `ogit/ServiceManagement/Order`
- `ogit/relates`  $\Rightarrow$  `ogit/MARS/Machine`
- `ogit/relates`  $\Rightarrow$  `ogit/MARS/Software`
- `ogit/relates`  $\Rightarrow$  `ogit/MARS/Resource`
- `ogit/relates`  $\Rightarrow$  `ogit/MARS/Application`
- `ogit/relates`  $\Rightarrow$  `ogit/Automation/MARSNode`

- `ogit/reportedOn => ogit/MARS/Machine`
- `ogit/reportedOn => ogit/MARS/Software`
- `ogit/reportedOn => ogit/MARS/Resource`
- `ogit/reportedOn => ogit/MARS/Application`
- `ogit/reportedOn => ogit/Automation/MARSNode`
- `ogit/uses => ogit/ServiceManagement/ChangeRequest`

#### 1.1.0.7 ogit/Automation/MARSNode

Using this entity type to represent MARS nodes is deprecated. New applications should prefer the entity types from ogit/MARS NTO.

IT Objects will be represented in MARS Modell with MARS nodes. The MARS model builds upon four basic types of objects with a single type of relationship. Basically the objects which are in fact called "nodes" represent both views - the business perspective and the technical view. The technical components are modeled in the machine and software layers while the application and resource layers describe the business view of the IT environment.

- id: <http://www.purl.org/ogit/Automation/MARSNode>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: NTO
- parent: ogit/Node

#### attributes

- optional:
  - `ogit/Automation/additionalMacAddress`
  - `ogit/Automation/adminUrl`
  - `ogit/Automation/appInfrastructureType`
  - `ogit/Automation/appInstanceType`
  - `ogit/Automation/appServer`
  - `ogit/Automation/basicConfigId`
  - `ogit/Automation/brand`
  - `ogit/Automation/buildName`
  - `ogit/Automation/buildType`
  - `ogit/Automation/companyName`
  - `ogit/Automation/contextPath`
  - `ogit/Automation/cpuCoreCount`
  - `ogit/Automation/cpuCount`
  - `ogit/Automation/cpuManufacturer`
  - `ogit/Automation/cpuModel`
  - `ogit/Automation/cpuSpeed`
  - `ogit/Automation/cpuType`

- [ogit/Automation/dataClassification](#)
- [ogit/Automation/dataPrivacy](#)
- [ogit/Automation/databaseSchema](#)
- [ogit/Automation/databaseServer](#)
- [ogit/Automation/deployStatus](#)
- [ogit/Automation/diskCount](#)
- [ogit/Automation/diskSpace](#)
- [ogit/Automation/domain](#)
- [ogit/Automation/exchangeRate](#)
- [ogit/Automation/firewallStatus](#)
- [ogit/Automation/firmwareVersion](#)
- [ogit/Automation/fqdn](#)
- [ogit/Automation/host](#)
- [ogit/Automation/installCount](#)
- [ogit/Automation/installPath](#)
- [ogit/Automation/isDeployed](#)
- [ogit/Automation/licenseAvailability](#)
- [ogit/Automation/licenseName](#)
- [ogit/Automation/licenseType](#)
- [ogit/Automation/lifecycle](#)
- [ogit/Automation/marsNodeFormalRepresentation](#)
- [ogit/Automation/marsNodeType](#)
- [ogit/Automation/memory](#)
- [ogit/Automation/middlewareType](#)
- [ogit/Automation/moveToProductionAt](#)
- [ogit/Automation/objectIdentifier](#)
- [ogit/Automation/osKey](#)
- [ogit/Automation/osLicense](#)
- [ogit/Automation/osManufacturer](#)
- [ogit/Automation/osName](#)
- [ogit/Automation/osServicePack](#)
- [ogit/Automation/osVersion](#)
- [ogit/Automation/patchNumber](#)
- [ogit/Automation/portNumber](#)
- [ogit/Automation/portNumberListener](#)
- [ogit/Automation/projectName](#)
- [ogit/Automation/serialNumber](#)
- [ogit/Automation/serviceId](#)
- [ogit/Automation/serviceName](#)
- [ogit/Automation/serviceStatus](#)
- [ogit/Automation/serviceType](#)
- [ogit/Automation/servletClass](#)
- [ogit/Automation/servletName](#)
- [ogit/Automation/software](#)
- [ogit/Automation/softwareKey](#)

- ogit/Automation/systemClass
- ogit/Automation/systemType
- ogit/Automation/tcpPort
- ogit/Automation/virtualMachineName
- ogit/Automation/virtualSystemName
- ogit/Automation/virtualSystemType
- ogit/Automation/webServer
- ogit/Datacenter/rackUnit
- ogit/connectorId
- ogit/creationTime
- ogit/endOfWarranty
- ogit/id
- ogit/ipAddress
- ogit/macAddress
- ogit/manufacturer
- ogit/modificationTime
- ogit/name
- ogit/serialNumber

#### incoming edges

- ogit/affects <= ogit/ServiceManagement/ChangeRequest
- ogit/affects <= ogit/ServiceManagement/Incident
- ogit/affects <= ogit/ServiceManagement/Order
- ogit/affects <= ogit/ServiceManagement/Problem
- ogit/affects <= ogit/ServiceManagement/Ticket
- ogit/relates <= ogit/ServiceManagement/ChangeRequest
- ogit/relates <= ogit/ServiceManagement/Report
- ogit/reportedOn <= ogit/ServiceManagement/ChangeRequest
- ogit/reportedOn <= ogit/ServiceManagement/Incident
- ogit/reportedOn <= ogit/ServiceManagement/Order
- ogit/reportedOn <= ogit/ServiceManagement/Problem
- ogit/reportedOn <= ogit/ServiceManagement/Ticket

#### outgoing edges

- ogit/affects => ogit/ServiceManagement/Service

### 1.1.0.8 ogit/Attachment

This entity defines a file attachment that an IT service, issue, task or a ticket might have. The attachment itself is not saved in GraphIT, instead it contains an external url link for it.

- id: <http://www.purl.org/ogit/Attachment>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: SGO
- parent: ogit/Node

#### attributes

- optional:
  - [ogit/accessControl](#)
  - [ogit/content](#)
  - [ogit/createdAt](#)
  - [ogit/creator](#)
  - [ogit/id](#)
  - [ogit/lastUpdatedAt](#)
  - [ogit/lastUpdatedBy](#)
  - [ogit/name](#)
  - [ogit/size](#)
  - [ogit/sourceTable](#)
  - [ogit/type](#)
  - [ogit/url](#)

#### outgoing edges

- [ogit/belongs](#) => [ogit/ServiceManagement/SubTask](#)
- [ogit/belongs](#) => [ogit/ServiceManagement/Ticket](#)
- [ogit/belongs](#) => [ogit/ServiceManagement/Problem](#)
- [ogit/belongs](#) => [ogit/ServiceManagement/Incident](#)
- [ogit/belongs](#) => [ogit/ServiceManagement/ChangeRequest](#)
- [ogit/belongs](#) => [ogit/ServiceManagement/Order](#)

### 1.1.0.9 ogit/ServiceManagement/SubTask

This entity type defines sub-tasks for a ticket. Mostly used for ChangeRequest. Common alternative names with same meaning are: task, activity, work order.

- id: <http://www.purl.org/ogit/ServiceManagement/SubTask>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: NTO
- parent: ogit/Node

**attributes**

- mandatory:
  - `ogit/id`
- optional:
  - `ogit/ServiceManagement/customer`
  - `ogit/ServiceManagement/resolutionCode`
  - `ogit/ServiceManagement/scheduledFinishAt`
  - `ogit/ServiceManagement/scheduledStartAt`
  - `ogit/ServiceManagement/sourceStatus`
  - `ogit/ServiceManagement/targetFinishAt`
  - `ogit/ServiceManagement/targetStartAt`
  - `ogit/ServiceManagement/taskStatus`
  - `ogit/assignedGroup`
  - `ogit/description`
  - `ogit/effort`
  - `ogit/finishedAt`
  - `ogit/lastUpdatedAt`
  - `ogit/name`
  - `ogit/startedAt`
  - `ogit/taskLog`
  - `ogit/type`

**incoming edges**

- `ogit/belongs`  $\leq$  `ogit/Attachment`
- `ogit/belongs`  $\leq$  `ogit/Comment`
- `ogit/closes`  $\leq$  `ogit/Person`
- `ogit/opens`  $\leq$  `ogit/Person`
- `ogit/precedes`  $\leq$  `ogit/ServiceManagement/SubTask`
- `ogit/requests`  $\leq$  `ogit/Person`
- `ogit/supervises`  $\leq$  `ogit/Organization`
- `ogit/supervises`  $\leq$  `ogit/Person`
- `ogit/updates`  $\leq$  `ogit/Person`

## outgoing edges

- [ogit/affects => ogit/ConfigurationItem](#)
- [ogit/assignedTo => ogit/Person](#)
- [ogit/assignedTo => ogit/Organization](#)
- [ogit/belongs => ogit/ServiceManagement/Ticket](#)
- [ogit/belongs => ogit/ServiceManagement/Problem](#)
- [ogit/belongs => ogit/ServiceManagement/Incident](#)
- [ogit/belongs => ogit/ServiceManagement/ChangeRequest](#)
- [ogit/belongs => ogit/ServiceManagement/Order](#)
- [ogit/corresponds => ogit/Task](#)
- [ogit/corresponds => ogit/Automation/AutomationIssue](#)
- [ogit/locatedIn => ogit/Location](#)
- [ogit/precedes => ogit/ServiceManagement/SubTask](#)

## 1.1.0.10 ogit/ServiceManagement/Problem

This entity type defines a problem ticket.

- id: <http://www.purl.org/ogit/ServiceManagement/Problem>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: NTO
- parent: ogit/Node

## attributes

- mandatory:
  - [ogit/id](#)
- optional:
  - [ogit/ServiceManagement/problemStatus](#)
  - [ogit/ServiceManagement/resolutionCode](#)
  - [ogit/ServiceManagement/rootCause](#)
  - [ogit/ServiceManagement/solution](#)
  - [ogit/ServiceManagement/workAround](#)
  - [ogit/reportedAt](#)

## incoming edges

- `ogit/belongs`  $\leq$  `ogit/ServiceManagement/SubTask`
- `ogit/belongs`  $\leq$  `ogit/Attachment`
- `ogit/causes`  $\leq$  `ogit/ServiceManagement/Incident`
- `ogit/causes`  $\leq$  `ogit/ServiceManagement/Problem`
- `ogit/closes`  $\leq$  `ogit/Person`
- `ogit/opens`  $\leq$  `ogit/ServiceManagement/Problem`
- `ogit/opens`  $\leq$  `ogit/Person`
- `ogit/relates`  $\leq$  `ogit/ServiceManagement/ChangeRequest`
- `ogit/relates`  $\leq$  `ogit/ServiceManagement/Incident`
- `ogit/relates`  $\leq$  `ogit/ServiceManagement/Order`
- `ogit/relates`  $\leq$  `ogit/ServiceManagement/Problem`
- `ogit/reports`  $\leq$  `ogit/Person`
- `ogit/supervises`  $\leq$  `ogit/Organization`
- `ogit/supervises`  $\leq$  `ogit/Person`
- `ogit/updates`  $\leq$  `ogit/Person`

## outgoing edges

- `ogit/affects`  $\Rightarrow$  `ogit/Person`
- `ogit/affects`  $\Rightarrow$  `ogit/MARS/Application`
- `ogit/affects`  $\Rightarrow$  `ogit/MARS/Resource`
- `ogit/affects`  $\Rightarrow$  `ogit/MARS/Software`
- `ogit/affects`  $\Rightarrow$  `ogit/MARS/Machine`
- `ogit/affects`  $\Rightarrow$  `ogit/Automation/MARSNode`
- `ogit/assignedTo`  $\Rightarrow$  `ogit/Person`
- `ogit/assignedTo`  $\Rightarrow$  `ogit/Organization`
- `ogit/assignedTo`  $\Rightarrow$  `ogit/ServiceManagement/Service`
- `ogit/causes`  $\Rightarrow$  `ogit/ServiceManagement/Problem`
- `ogit/causes`  $\Rightarrow$  `ogit/ServiceManagement/ChangeRequest`
- `ogit/complies`  $\Rightarrow$  `ogit/ServiceManagement/SLA`
- `ogit/corresponds`  $\Rightarrow$  `ogit/ServiceManagement/Ticket`
- `ogit/corresponds`  $\Rightarrow$  `ogit/Automation/AutomationIssue`
- `ogit/opens`  $\Rightarrow$  `ogit/ServiceManagement/Problem`
- `ogit/relates`  $\Rightarrow$  `ogit/ServiceManagement/Problem`
- `ogit/relates`  $\Rightarrow$  `ogit/ServiceManagement/Incident`



- `ogit/relates => ogit/ServiceManagement/ChangeRequest`
- `ogit/relates => ogit/ServiceManagement/Order`
- `ogit/reportedOn => ogit/MARS/Machine`
- `ogit/reportedOn => ogit/MARS/Software`
- `ogit/reportedOn => ogit/MARS/Resource`
- `ogit/reportedOn => ogit/MARS/Application`
- `ogit/reportedOn => ogit/Automation/MARSNode`

#### 1.1.0.11 ogit/Comment

Defines comments for a ticket, issue or another type of entity. Also known as WorkLog, ChangeLog or HistoryEntry.

- id: <http://www.purl.org/ogit/Comment>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: SGO
- parent: ogit/Node

#### attributes

- optional:
  - `ogit/content`
  - `ogit/creator`
  - `ogit/id`

#### outgoing edges

- `ogit/belongs => ogit/ServiceManagement/SubTask`
- `ogit/belongs => ogit/ServiceManagement/Ticket`

#### 1.1.0.12 ogit/Region

A region is always something that has a certain geographic extension (a country, a county, ) whereas ogit/Location usually refers to specific place usually having an address

- id: <http://www.purl.org/ogit/Region>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: SGO
- parent: ogit/Node

**attributes**

- optional:
  - [ogit/description](#)
  - [ogit/name](#)

**incoming edges**

- [ogit/availableIn](#) <= [ogit/ServiceManagement/Offering](#)

**1.1.0.13 ogit/Software/Connector**

Represents any type of software connector

- id: <http://www.purl.org/ogit/Software/Connector>
- valid-from: Thu Jun 11 00:00:00 UTC 2015
- creator: Aymen Ayoub
- scope: NTO
- parent: ogit/Node

**attributes**

- optional:
  - [ogit/connectorId](#)
  - [ogit/name](#)

**outgoing edges**

- [ogit/creates](#) => [ogit/ServiceManagement/ChangeRequest](#)
- [ogit/creates](#) => [ogit/ServiceManagement/Incident](#)

**1.1.0.14 ogit/ServiceManagement/ApprovalTask**

This entity type defines approval tasks for a ticket. Used for example at [ogit/ServiceManagement/ChangeRequest](#).

- id: <http://www.purl.org/ogit/ServiceManagement/ApprovalTask>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: NTO
- parent: ogit/Node

**attributes**

- optional:
  - [ogit/ServiceManagement/approvalStatus](#)
  - [ogit/ServiceManagement/sourceStatus](#)
  - [ogit/id](#)
  - [ogit/lastUpdatedAt](#)
  - [ogit/name](#)
  - [ogit/reason](#)

**incoming edges**

- [ogit/precedes](#) <= [ogit/ServiceManagement/ApprovalTask](#)

**outgoing edges**

- [ogit/assignedTo](#) => [ogit/Person](#)
- [ogit/assignedTo](#) => [ogit/Organization](#)
- [ogit/belongs](#) => [ogit/ServiceManagement/ChangeRequest](#)
- [ogit/corresponds](#) => [ogit/Task](#)
- [ogit/precedes](#) => [ogit/ServiceManagement/ApprovalTask](#)

**1.1.0.15 [ogit/ServiceManagement/Order](#)**

Defines an order.

- id: <http://www.purl.org/ogit/ServiceManagement/Order>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: NTO
- parent: [ogit/Node](#)

**attributes**

- mandatory:
  - [ogit/id](#)
- optional:
  - [ogit/ServiceManagement/externalTicketId](#)
  - [ogit/ServiceManagement/externalTicketSource](#)
  - [ogit/ServiceManagement/reportedSource](#)
  - [ogit/ServiceManagement/sourceStatus](#)
  - [ogit/closedAt](#)
  - [ogit/createdAt](#)
  - [ogit/description](#)
  - [ogit/impact](#)
  - [ogit/lastUpdatedAt](#)
  - [ogit/openedAt](#)
  - [ogit/priority](#)
  - [ogit/project](#)
  - [ogit/summary](#)
  - [ogit/urgency](#)

**incoming edges**

- [ogit/belongs](#) <= [ogit/ServiceManagement/SubTask](#)
- [ogit/belongs](#) <= [ogit/Attachment](#)
- [ogit/bills](#) <= [ogit/Price/Invoice](#)
- [ogit/causes](#) <= [ogit/ServiceManagement/ChangeRequest](#)
- [ogit/causes](#) <= [ogit/ServiceManagement/Incident](#)
- [ogit/causes](#) <= [ogit/ServiceManagement/Order](#)
- [ogit/closes](#) <= [ogit/Person](#)
- [ogit/contains](#) <= [ogit/ServiceManagement/Offering](#)
- [ogit/implements](#) <= [ogit/Automation/MARSMModel](#)
- [ogit/opens](#) <= [ogit/Person](#)
- [ogit/relates](#) <= [ogit/ServiceManagement/ChangeRequest](#)
- [ogit/relates](#) <= [ogit/ServiceManagement/Order](#)
- [ogit/relates](#) <= [ogit/ServiceManagement/Problem](#)
- [ogit/relates](#) <= [ogit/Event](#)
- [ogit/supervises](#) <= [ogit/Organization](#)
- [ogit/supervises](#) <= [ogit/Person](#)
- [ogit/updates](#) <= [ogit/Person](#)

## outgoing edges

- `ogit/affects => ogit/Person`
- `ogit/affects => ogit/Automation/MARSNode`
- `ogit/assignedTo => ogit/Person`
- `ogit/assignedTo => ogit/Organization`
- `ogit/causes => ogit/ServiceManagement/Ticket`
- `ogit/causes => ogit/ServiceManagement/ChangeRequest`
- `ogit/causes => ogit/ServiceManagement/Order`
- `ogit/corresponds => ogit/ServiceManagement/Service`
- `ogit/relates => ogit/ServiceManagement/Ticket`
- `ogit/relates => ogit/ServiceManagement/Problem`
- `ogit/relates => ogit/ServiceManagement/Incident`
- `ogit/relates => ogit/ServiceManagement/ChangeRequest`
- `ogit/relates => ogit/ServiceManagement/Order`
- `ogit/relates => ogit/Contract`
- `ogit/reportedOn => ogit/MARS/Machine`
- `ogit/reportedOn => ogit/MARS/Software`
- `ogit/reportedOn => ogit/MARS/Resource`
- `ogit/reportedOn => ogit/MARS/Application`
- `ogit/reportedOn => ogit/Automation/MARSNode`

## 1.1.0.16 ogit/ConfigurationItem

A configuration item.

- id: <http://www.purl.org/ogit/ConfigurationItem>
- valid-from: Thu Jun 11 00:00:00 UTC 2015
- creator: Aymen Ayoub
- scope: SGO
- parent: ogit/Node

**attributes**

- mandatory:
  - [ogit/id](#)
- optional:
  - [ogit/Automation/governingContract](#)
  - [ogit/asset](#)
  - [ogit/assetTag](#)
  - [ogit/assignedAt](#)
  - [ogit/availability](#)
  - [ogit/businessCriticality](#)
  - [ogit/category](#)
  - [ogit/checkedInAt](#)
  - [ogit/checkedOutAt](#)
  - [ogit/ciType](#)
  - [ogit/class](#)
  - [ogit/comment](#)
  - [ogit/confidentiality](#)
  - [ogit/contact](#)
  - [ogit/content](#)
  - [ogit/createdAt](#)
  - [ogit/deliveredAt](#)
  - [ogit/description](#)
  - [ogit/endOfWarranty](#)
  - [ogit/externalId](#)
  - [ogit/faultCount](#)
  - [ogit/impact](#)
  - [ogit/installStatus](#)
  - [ogit/installedAt](#)
  - [ogit/integrity](#)
  - [ogit/inventoryNumber](#)
  - [ogit/invoiceNumber](#)
  - [ogit/isCritical](#)
  - [ogit/isSupported](#)
  - [ogit/lastScannedAt](#)
  - [ogit/lastUpdatedAt](#)
  - [ogit/leaseContract](#)
  - [ogit/model](#)
  - [ogit/modelNumber](#)
  - [ogit/name](#)
  - [ogit/operationalStatus](#)
  - [ogit/orderedAt](#)
  - [ogit/pendingChange](#)
  - [ogit/priority](#)

- [ogit/productOrderNumber](#)
- [ogit/purchasedAt](#)
- [ogit/securityClass](#)
- [ogit/serviceContract](#)
- [ogit/shortDescription](#)
- [ogit/soxClass](#)
- [ogit/startedAt](#)
- [ogit/status](#)
- [ogit/subCategory](#)
- [ogit/subType](#)
- [ogit/type](#)
- [ogit/updateCount](#)
- [ogit/vendor](#)
- [ogit/version](#)

#### incoming edges

- [ogit/affects](#) ≤ [ogit/ServiceManagement/ChangeRequest](#)
- [ogit/affects](#) ≤ [ogit/ServiceManagement/Incident](#)
- [ogit/affects](#) ≤ [ogit/ServiceManagement/SubTask](#)

#### 1.1.0.17 [ogit/ServiceManagement/Incident](#)

This entity type defines an incident ticket.

- id: <http://www.purl.org/ogit/ServiceManagement/Incident>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: NTO
- parent: [ogit/Node](#)

#### attributes

- optional:
  - [ogit/ServiceManagement/customer](#)
  - [ogit/ServiceManagement/incidentStatus](#)
  - [ogit/ServiceManagement/reportedSource](#)
  - [ogit/ServiceManagement/resolutionCode](#)
  - [ogit/ServiceManagement/resolvedAt](#)
  - [ogit/ServiceManagement/solution](#)
  - [ogit/ServiceManagement/sourceStatus](#)
  - [ogit/ServiceManagement/task](#)
  - [ogit/assignedGroup](#)
  - [ogit/category](#)
  - [ogit/id](#)
  - [ogit/reportedAt](#)

## incoming edges

- `ogit/belongs`  $\leq$  `ogit/ServiceManagement/SubTask`
- `ogit/belongs`  $\leq$  `ogit/Attachment`
- `ogit/causes`  $\leq$  `ogit/ServiceManagement/Incident`
- `ogit/closes`  $\leq$  `ogit/Person`
- `ogit/creates`  $\leq$  `ogit/Software/Connector`
- `ogit/opens`  $\leq$  `ogit/ServiceManagement/Service`
- `ogit/opens`  $\leq$  `ogit/Person`
- `ogit/relates`  $\leq$  `ogit/ServiceManagement/ChangeRequest`
- `ogit/relates`  $\leq$  `ogit/ServiceManagement/Incident`
- `ogit/relates`  $\leq$  `ogit/ServiceManagement/Order`
- `ogit/relates`  $\leq$  `ogit/ServiceManagement/Problem`
- `ogit/relates`  $\leq$  `ogit/Event`
- `ogit/reports`  $\leq$  `ogit/Person`
- `ogit/supervises`  $\leq$  `ogit/Organization`
- `ogit/supervises`  $\leq$  `ogit/Person`
- `ogit/updates`  $\leq$  `ogit/Person`

## outgoing edges

- `ogit/affects`  $\Rightarrow$  `ogit/ServiceManagement/Service`
- `ogit/affects`  $\Rightarrow$  `ogit/ConfigurationItem`
- `ogit/affects`  $\Rightarrow$  `ogit/Person`
- `ogit/affects`  $\Rightarrow$  `ogit/MARS/Application`
- `ogit/affects`  $\Rightarrow$  `ogit/MARS/Resource`
- `ogit/affects`  $\Rightarrow$  `ogit/MARS/Software`
- `ogit/affects`  $\Rightarrow$  `ogit/MARS/Machine`
- `ogit/affects`  $\Rightarrow$  `ogit/Automation/MARSNode`
- `ogit/assignedTo`  $\Rightarrow$  `ogit/Person`
- `ogit/assignedTo`  $\Rightarrow$  `ogit/Organization`
- `ogit/assignedTo`  $\Rightarrow$  `ogit/ServiceManagement/Service`
- `ogit/causes`  $\Rightarrow$  `ogit/ServiceManagement/Problem`
- `ogit/causes`  $\Rightarrow$  `ogit/ServiceManagement/Incident`
- `ogit/causes`  $\Rightarrow$  `ogit/Event`
- `ogit/causes`  $\Rightarrow$  `ogit/ServiceManagement/ChangeRequest`
- `ogit/causes`  $\Rightarrow$  `ogit/ServiceManagement/Order`



- `ogit/complies => ogit/ServiceManagement/SLA`
- `ogit/corresponds => ogit/ServiceManagement/Ticket`
- `ogit/corresponds => ogit/Automation/AutomationIssue`
- `ogit/locatedIn => ogit/Location`
- `ogit/opens => ogit/Task`
- `ogit/relates => ogit/ServiceManagement/Problem`
- `ogit/relates => ogit/ServiceManagement/Incident`
- `ogit/relates => ogit/ServiceManagement/ChangeRequest`
- `ogit/reportedOn => ogit/MARS/Machine`
- `ogit/reportedOn => ogit/MARS/Software`
- `ogit/reportedOn => ogit/MARS/Resource`
- `ogit/reportedOn => ogit/MARS/Application`
- `ogit/reportedOn => ogit/Automation/MARSNode`

#### 1.1.0.18 ogit/MARS/Application

Vertices of this type are the 'A'-nodes in the MARS model. 'A' stands for 'Application' and those nodes form the highest layer in the A-R-S-M layer model. An 'Application' node groups 'Resource' nodes which form one business application.

- `id: http://www.purl.org/ogit/MARS/Application`
- `valid-from: Fri Jun 01 00:00:00 UTC 2018`
- `creator: FCO`
- `scope: NTO`
- `parent: ogit/Node`

#### attributes

- `mandatory:`
  - `ogit/MARS/Application/class`
  - `ogit/MARS/Application/subClass`
  - `ogit/name`
- `optional:`
  - `ogit/Automation/automationState`
  - `ogit/Automation/lifecycle`
  - `ogit/Automation/marsNodeType`
  - `ogit/Automation/serviceStatus`

## incoming edges

- `ogit/affects`  $\leq$  `ogit/ServiceManagement/ChangeRequest`
- `ogit/affects`  $\leq$  `ogit/ServiceManagement/Incident`
- `ogit/affects`  $\leq$  `ogit/ServiceManagement/Problem`
- `ogit/affects`  $\leq$  `ogit/ServiceManagement/Ticket`
- `ogit/relates`  $\leq$  `ogit/ServiceManagement/ChangeRequest`
- `ogit/relates`  $\leq$  `ogit/ServiceManagement/Report`
- `ogit/reportedOn`  $\leq$  `ogit/ServiceManagement/ChangeRequest`
- `ogit/reportedOn`  $\leq$  `ogit/ServiceManagement/Incident`
- `ogit/reportedOn`  $\leq$  `ogit/ServiceManagement/Order`
- `ogit/reportedOn`  $\leq$  `ogit/ServiceManagement/Problem`
- `ogit/reportedOn`  $\leq$  `ogit/ServiceManagement/Ticket`

1.1.0.19 `ogit/Software/Application`

Represents any type of software application

- id: <http://www.purl.org/ogit/Software/Application>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: NTO
- parent: `ogit/Node`

## attributes

- mandatory:
  - `ogit/name`
- optional:
  - `ogit/description`
  - `ogit/url`
  - `ogit/version`

## incoming edges

- `ogit/implements`  $\leq$  `ogit/ServiceManagement/Service`

## outgoing edges

- `ogit/complies`  $\Rightarrow$  `ogit/ServiceManagement/SLA`

## 1.1.0.20 ogit/ServiceManagement/Report

Reporting about IT service delivery

- id: <http://www.purl.org/ogit/ServiceManagement/Report>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: NTO
- parent: ogit/Node

## attributes

- optional:
  - [ogit/id](#)
  - [ogit/name](#)
  - [ogit/version](#)

## incoming edges

- [ogit/generates](#) <= [ogit/ServiceManagement/Service](#)

## outgoing edges

- [ogit/creates](#) => [ogit/ServiceManagement/Service](#)
- [ogit/generates](#) => [ogit/Price/Invoice](#)
- [ogit/relates](#) => [ogit/MARS/Machine](#)
- [ogit/relates](#) => [ogit/MARS/Software](#)
- [ogit/relates](#) => [ogit/MARS/Resource](#)
- [ogit/relates](#) => [ogit/MARS/Application](#)
- [ogit/relates](#) => [ogit/Automation/MARSNode](#)
- [ogit/uses](#) => [ogit/Timeseries](#)

## 1.1.0.21 ogit/ServiceManagement/Offering

This is a concrete offering from a vendor including one or more combined services from a catalog/collection/offering book.

- id: <http://www.purl.org/ogit/ServiceManagement/Offering>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: NTO
- parent: ogit/Node

## attributes

- mandatory:
  - [ogit/id](#)
  - [ogit/name](#)
- optional:
  - [ogit/ServiceManagement/allowedForNewBusiness](#)
  - [ogit/capacityAvailable](#)
  - [ogit/category](#)
  - [ogit/currency](#)
  - [ogit/description](#)
  - [ogit/expirationDate](#)
  - [ogit/market](#)
  - [ogit/serialNumber](#)
  - [ogit/validFrom](#)

## incoming edges

- [ogit/defines](#) <= [ogit/Organization](#)
- [ogit/describes](#) <= [ogit/Parameter](#)

## outgoing edges

- [ogit/availableIn](#) => [ogit/Region](#)
- [ogit/contains](#) => [ogit/ServiceManagement/Order](#)
- [ogit/contains](#) => [ogit/ServiceManagement/Service](#)
- [ogit/contains](#) => [ogit/CatalogItem](#)
- [ogit/contains](#) => [ogit/Cost/CostElement](#)
- [ogit/locatedIn](#) => [ogit/Location](#)
- [ogit/specifies](#) => [ogit/Automation/MARSModelTemplate](#)

1.1.0.22 [ogit/Automation/MARSModelTemplate](#)

Represents a set of interconnected MARSNodes, which will be used to define a vendor implementation template of an ordered service offering.

- id: <http://www.purl.org/ogit/Automation/MARSModelTemplate>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: NTO
- parent: [ogit/Node](#)

**attributes**

- mandatory:
  - [ogit/name](#)
- optional:
  - [ogit/description](#)

**incoming edges**

- [ogit/specifies](#) <= [ogit/ServiceManagement/Offering](#)

**1.1.0.23 ogit/CatalogItem**

An entry within a Catalog. the semantics of Item is more general than that of <http://purl.org/goodrelations/v1#ProductOrService>

- id: <http://www.purl.org/ogit/CatalogItem>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: SGO
- parent: ogit/Node

**attributes**

- mandatory:
  - [ogit/name](#)
- optional:
  - [ogit/description](#)

**incoming edges**

- [ogit/contains](#) <= [ogit/ServiceManagement/Offering](#)
- [ogit/corresponds](#) <= [ogit/ServiceManagement/Action](#)
- [ogit/corresponds](#) <= [ogit/ServiceManagement/Service](#)
- [ogit/requires](#) <= [ogit/ServiceManagement/Action](#)

**outgoing edges**

- [ogit/requires](#) => [ogit/ServiceManagement/Service](#)
- [ogit/requires](#) => [ogit/ServiceManagement/Action](#)

## 1.1.0.24 ogit/Contract

General definition of a contract. Usually used for IT service related contracts but at this level of detail it is not restricted to those.

- id: <http://www.purl.org/ogit/Contract>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: SGO
- parent: ogit/Node

## attributes

- mandatory:
  - [ogit/name](#)
- optional:
  - [ogit/deadline](#)
  - [ogit/description](#)
  - [ogit/expirationDate](#)
  - [ogit/status](#)
  - [ogit/type](#)
  - [ogit/validFrom](#)
  - [ogit/validTo](#)

## incoming edges

- [ogit/relates](#) <= [ogit/ServiceManagement/Order](#)

## outgoing edges

- [ogit/contains](#) => [ogit/ServiceManagement/SLA](#)

## 1.1.0.25 ogit/MARS/Machine

Vertices of this type are the 'M'-nodes in the MARS model. 'M' stands for 'Machine' and those nodes form the bottom layer in the A-R-S-M layer model. But to be precise a 'Machine' node models any operation system instance (regardless whether running on bare metal or in some virtualized environment)

- id: <http://www.purl.org/ogit/MARS/Machine>
- valid-from: Fri Jun 01 00:00:00 UTC 2018
- creator: FCO
- scope: NTO
- parent: ogit/Node

**attributes**

- mandatory:
  - [ogit/MARS/Machine/class](#)
  - [ogit/name](#)
- optional:
  - [ogit/Automation/automationState](#)
  - [ogit/Automation/lifecycle](#)
  - [ogit/Automation/marsNodeType](#)
  - [ogit/Automation/serviceStatus](#)
  - [ogit/MARS/Machine/cpuArch](#)
  - [ogit/MARS/Machine/distroName](#)
  - [ogit/MARS/Machine/kernel](#)
  - [ogit/MARS/Machine/ram](#)
  - [ogit/MARS/Network/defaultGateway](#)
  - [ogit/MARS/Network/fqdn](#)
  - [ogit/MARS/Network/interfaceIP](#)
  - [ogit/MARS/Network/interfaceMAC](#)
  - [ogit/MARS/Network/interfaceName](#)
  - [ogit/MARS/Network/interfacePrefixLength](#)
  - [ogit/MARS/Network/ipVersion](#)
  - [ogit/Version/major](#)
  - [ogit/Version/minor](#)
  - [ogit/Version/patch](#)
  - [ogit/endOfWarranty](#)
  - [ogit/serialNumber](#)
  - [ogit/vendor](#)

**incoming edges**

- [ogit/affects](#) <= [ogit/ServiceManagement/ChangeRequest](#)
- [ogit/affects](#) <= [ogit/ServiceManagement/Incident](#)
- [ogit/affects](#) <= [ogit/ServiceManagement/Problem](#)
- [ogit/affects](#) <= [ogit/ServiceManagement/Ticket](#)
- [ogit/relates](#) <= [ogit/ServiceManagement/ChangeRequest](#)
- [ogit/relates](#) <= [ogit/ServiceManagement/Report](#)
- [ogit/reportedOn](#) <= [ogit/ServiceManagement/ChangeRequest](#)
- [ogit/reportedOn](#) <= [ogit/ServiceManagement/Incident](#)
- [ogit/reportedOn](#) <= [ogit/ServiceManagement/Order](#)
- [ogit/reportedOn](#) <= [ogit/ServiceManagement/Problem](#)
- [ogit/reportedOn](#) <= [ogit/ServiceManagement/Ticket](#)

## 1.1.0.26 ogit/ServiceManagement/SLA

A service level agreement.

- id: <http://www.purl.org/ogit/ServiceManagement/SLA>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: NTO
- parent: ogit/Node

## attributes

- optional:
  - [ogit/ServiceManagement/elapsedTime](#)
  - [ogit/ServiceManagement/leftTime](#)
  - [ogit/ServiceManagement/resolvedInTime](#)
  - [ogit/ServiceManagement/scheduledFinishAt](#)
  - [ogit/ServiceManagement/slaStage](#)
  - [ogit/name](#)
  - [ogit/startedAt](#)

## incoming edges

- [ogit/complies](#) <= [ogit/ServiceManagement/ChangeRequest](#)
- [ogit/complies](#) <= [ogit/ServiceManagement/Incident](#)
- [ogit/complies](#) <= [ogit/ServiceManagement/Problem](#)
- [ogit/complies](#) <= [ogit/ServiceManagement/Service](#)
- [ogit/complies](#) <= [ogit/Software/Application](#)
- [ogit/contains](#) <= [ogit/Contract](#)
- [ogit/describes](#) <= [ogit/Parameter](#)

## outgoing edges

- [ogit/triggers](#) => [ogit/Penalty](#)

## 1.1.0.27 ogit/MARS/Resource

Vertices of this type are the 'R'-nodes in the MARS model. 'R' stands for 'Resource' and those nodes form the second highest layer in the A-R-S-M layer model. A 'Resource' node groups 'Software' nodes. It's up to the user whether this grouping is used to group software instance of the same software (e.g. all instances of an Oracle RAC) or software instance of different softwares (functional grouping, e.g. 'persistence')

- id: <http://www.purl.org/ogit/MARS/Resource>
- valid-from: Fri Jun 01 00:00:00 UTC 2018
- creator: FCO
- scope: NTO
- parent: ogit/Node



**attributes**

- mandatory:
  - [ogit/MARS/Resource/class](#)
  - [ogit/name](#)
- optional:
  - [ogit/Automation/automationState](#)
  - [ogit/Automation/lifecycle](#)
  - [ogit/Automation/marsNodeType](#)
  - [ogit/Automation/serviceStatus](#)
  - [ogit/url](#)

**incoming edges**

- [ogit/affects](#) <= [ogit/ServiceManagement/ChangeRequest](#)
- [ogit/affects](#) <= [ogit/ServiceManagement/Incident](#)
- [ogit/affects](#) <= [ogit/ServiceManagement/Problem](#)
- [ogit/affects](#) <= [ogit/ServiceManagement/Ticket](#)
- [ogit/relates](#) <= [ogit/ServiceManagement/ChangeRequest](#)
- [ogit/relates](#) <= [ogit/ServiceManagement/Report](#)
- [ogit/reportedOn](#) <= [ogit/ServiceManagement/ChangeRequest](#)
- [ogit/reportedOn](#) <= [ogit/ServiceManagement/Incident](#)
- [ogit/reportedOn](#) <= [ogit/ServiceManagement/Order](#)
- [ogit/reportedOn](#) <= [ogit/ServiceManagement/Problem](#)
- [ogit/reportedOn](#) <= [ogit/ServiceManagement/Ticket](#)

**1.1.0.28 ogit/Person**

A Person represents a human identity.

- id: <http://www.purl.org/ogit/Person>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: SGO
- parent: ogit/Node

**attributes**

- optional:
  - `ogit/alternativeName`
  - `ogit/email`
  - `ogit/fax`
  - `ogit/firstName`
  - `ogit/lastName`
  - `ogit/middleName`
  - `ogit/mobilePhone`
  - `ogit/notification`
  - `ogit/officePhone`
  - `ogit/otherPhone`
  - `ogit/position`
  - `ogit/sourceld`
  - `ogit/status`
  - `ogit/title`
  - `ogit/webPage`

**incoming edges**

- `ogit/affects`  $\leq$  `ogit/ServiceManagement/ChangeRequest`
- `ogit/affects`  $\leq$  `ogit/ServiceManagement/Incident`
- `ogit/affects`  $\leq$  `ogit/ServiceManagement/Order`
- `ogit/affects`  $\leq$  `ogit/ServiceManagement/Problem`
- `ogit/affects`  $\leq$  `ogit/ServiceManagement/Service`
- `ogit/affects`  $\leq$  `ogit/ServiceManagement/Ticket`
- `ogit/assignedTo`  $\leq$  `ogit/ServiceManagement/ApprovalTask`
- `ogit/assignedTo`  $\leq$  `ogit/ServiceManagement/ChangeRequest`
- `ogit/assignedTo`  $\leq$  `ogit/ServiceManagement/Incident`
- `ogit/assignedTo`  $\leq$  `ogit/ServiceManagement/Order`
- `ogit/assignedTo`  $\leq$  `ogit/ServiceManagement/Problem`
- `ogit/assignedTo`  $\leq$  `ogit/ServiceManagement/SubTask`
- `ogit/assignedTo`  $\leq$  `ogit/ServiceManagement/Ticket`

## outgoing edges

- `ogit/closes => ogit/ServiceManagement/ChangeRequest`
- `ogit/closes => ogit/ServiceManagement/Order`
- `ogit/closes => ogit/ServiceManagement/Ticket`
- `ogit/closes => ogit/ServiceManagement/Problem`
- `ogit/closes => ogit/ServiceManagement/Incident`
- `ogit/closes => ogit/ServiceManagement/SubTask`
- `ogit/opens => ogit/ServiceManagement/SubTask`
- `ogit/opens => ogit/ServiceManagement/ChangeRequest`
- `ogit/opens => ogit/ServiceManagement/Order`
- `ogit/opens => ogit/ServiceManagement/Ticket`
- `ogit/opens => ogit/ServiceManagement/Problem`
- `ogit/opens => ogit/ServiceManagement/Incident`
- `ogit/owns => ogit/ServiceManagement/Service`
- `ogit/reports => ogit/ServiceManagement/Problem`
- `ogit/reports => ogit/ServiceManagement/Incident`
- `ogit/requests => ogit/ServiceManagement/SubTask`
- `ogit/requests => ogit/ServiceManagement/ChangeRequest`
- `ogit/supervises => ogit/ServiceManagement/SubTask`
- `ogit/supervises => ogit/ServiceManagement/ChangeRequest`
- `ogit/supervises => ogit/ServiceManagement/Order`
- `ogit/supervises => ogit/ServiceManagement/Ticket`
- `ogit/supervises => ogit/ServiceManagement/Problem`
- `ogit/supervises => ogit/ServiceManagement/Incident`
- `ogit/updates => ogit/ServiceManagement/ChangeRequest`
- `ogit/updates => ogit/ServiceManagement/Order`
- `ogit/updates => ogit/ServiceManagement/Ticket`
- `ogit/updates => ogit/ServiceManagement/Problem`
- `ogit/updates => ogit/ServiceManagement/Incident`
- `ogit/updates => ogit/ServiceManagement/SubTask`

## 1.1.0.29 ogit/Location

A place where some service is offered or requested. In many cases this will be related to an address of an Organization. Similar to <http://purl.org/goodrelations/v1#Location>

- id: <http://www.purl.org/ogit/Location>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: SGO
- parent: ogit/Node

**attributes**

- mandatory:
  - [ogit/name](#)
- optional:
  - [ogit/description](#)

**incoming edges**

- [ogit/affects](#) <= [ogit/ServiceManagement/ChangeRequest](#)
- [ogit/locatedIn](#) <= [ogit/ServiceManagement/ChangeRequest](#)
- [ogit/locatedIn](#) <= [ogit/ServiceManagement/Incident](#)
- [ogit/locatedIn](#) <= [ogit/ServiceManagement/Offering](#)
- [ogit/locatedIn](#) <= [ogit/ServiceManagement/SubTask](#)

**1.1.0.30 ogit/Task**

A task is a unit of execution.

- id: <http://www.purl.org/ogit/Task>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: SGO
- parent: ogit/Node

**attributes**

- optional:
  - [ogit/description](#)
  - [ogit/id](#)
  - [ogit/name](#)
  - [ogit/positionNumber](#)
  - [ogit/question](#)
  - [ogit/response](#)
  - [ogit/status](#)
  - [ogit/type](#)

**incoming edges**

- [ogit/corresponds](#) <= [ogit/ServiceManagement/ApprovalTask](#)
- [ogit/corresponds](#) <= [ogit/ServiceManagement/SubTask](#)
- [ogit/opens](#) <= [ogit/ServiceManagement/Incident](#)

#### 1.1.0.31 ogit/ServiceManagement/Action

Defines Actions on it Services. A Service is connected to the available Actions by the "supports" relationship.

- id: <http://www.purl.org/ogit/ServiceManagement/Action>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: NTO
- parent: ogit/Node

##### attributes

- mandatory:
  - [ogit/name](#)
- optional:
  - [ogit/description](#)
  - [ogit/id](#)

##### incoming edges

- [ogit/requires](#) <= [ogit/ServiceManagement/Action](#)
- [ogit/requires](#) <= [ogit/ServiceManagement/Service](#)
- [ogit/requires](#) <= [ogit/CatalogItem](#)
- [ogit/supports](#) <= [ogit/ServiceManagement/Service](#)

##### outgoing edges

- [ogit/corresponds](#) => [ogit/CatalogItem](#)
- [ogit/requires](#) => [ogit/ServiceManagement/Service](#)
- [ogit/requires](#) => [ogit/ServiceManagement/Action](#)
- [ogit/requires](#) => [ogit/CatalogItem](#)

#### 1.1.0.32 ogit/Event

This entity defines any type of event records, e.g. ITSM/produced by event management systems, Business Process etc.

- id: <http://www.purl.org/ogit/Event>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: SGO
- parent: ogit/Node

**attributes**

- mandatory:
  - [ogit/id](#)
  - [ogit/name](#)
- optional:
  - [ogit/ServiceManagement/reportedSource](#)
  - [ogit/acknowledgeState](#)
  - [ogit/category](#)
  - [ogit/certainty](#)
  - [ogit/description](#)
  - [ogit/expiresAt](#)
  - [ogit/firstOccurredAt](#)
  - [ogit/impact](#)
  - [ogit/instance](#)
  - [ogit/isRoot](#)
  - [ogit/lastClearedAt](#)
  - [ogit/lastOccurredAt](#)
  - [ogit/lastUpdatedAt](#)
  - [ogit/maintenanceState](#)
  - [ogit/occurenceCount](#)
  - [ogit/openedAt](#)
  - [ogit/priority](#)
  - [ogit/resource](#)
  - [ogit/severity](#)
  - [ogit/sourceId](#)
  - [ogit/status](#)
  - [ogit/summary](#)
  - [ogit/type](#)

**incoming edges**

- [ogit/causes](#) <= [ogit/ServiceManagement/Incident](#)

**outgoing edges**

- [ogit/relates](#) => [ogit/ServiceManagement/Order](#)
- [ogit/relates](#) => [ogit/ServiceManagement/Incident](#)

## 1.1.0.33 ogit/Automation/AutomationIssue

Dynamic information exists within an automation engine in the form of Issues otherwise referred to as Task or Situational Data. From the technical perspective an Issue is a number of attributes (Key/Value tuples) with unique names. From the logical point of view Issues contain information about the change of states on a system. Issues can be injected into an automation engine from external systems e.g. Monitoring or result from the execution of a Knowledge Item. By comparing an Issue with the Issue Condition of a Knowledge Item an automation engine decides which Knowledge Items are processed in which order. If multiple Knowledge Items can be applied to an Issue the KI with the more precisely defined IssueCondition is processed first.

- id: <http://www.purl.org/ogit/Automation/AutomationIssue>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: NTO
- parent: ogit/Node

## attributes

- optional:
  - [ogit/Automation/deployStatus](#)
  - [ogit/Automation/isDeployed](#)
  - [ogit/Automation/issueFormalRepresentation](#)
  - [ogit/Automation/issueType](#)
  - [ogit/Automation/originNode](#)
  - [ogit/Automation/processingNode](#)
  - [ogit/Automation/processingTimestamp](#)
  - [ogit/creationTime](#)
  - [ogit/modificationTime](#)
  - [ogit/status](#)
  - [ogit/subject](#)

## incoming edges

- [ogit/corresponds](#) <= [ogit/ServiceManagement/ChangeRequest](#)
- [ogit/corresponds](#) <= [ogit/ServiceManagement/Incident](#)
- [ogit/corresponds](#) <= [ogit/ServiceManagement/Problem](#)
- [ogit/corresponds](#) <= [ogit/ServiceManagement/SubTask](#)
- [ogit/corresponds](#) <= [ogit/ServiceManagement/Ticket](#)

## 1.1.0.34 ogit/Automation/MARSModel

A collection of MARSNodes allows to address all MARS nodes belonging together in a certain way at once the relationship from MARSModel to MARSNode is 'ogit/contains'. examples are: All MARS nodes describing the IT of one data center, or all MARS nodes associated with the same contract. In such cases you would connect the other entity (data center, contract) with the MARSModel node instead creating links to any MARSNode being part of that model.

- id: <http://www.purl.org/ogit/Automation/MARSModel>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: NTO
- parent: ogit/Node

## attributes

- optional:
  - [ogit/description](#)
  - [ogit/name](#)

## outgoing edges

- [ogit/implements](#) => [ogit/ServiceManagement/Order](#)

## 1.1.0.35 ogit/Parameter

Defines a parameter of an entity, for example: service, action, ticket, sla, etc.

- id: <http://www.purl.org/ogit/Parameter>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: SGO
- parent: ogit/Node

## attributes

- mandatory:
  - [ogit/name](#)
- optional:
  - [ogit/ServiceManagement/granularity](#)
  - [ogit/ServiceManagement/isRequired](#)
  - [ogit/ServiceManagement/requirementId](#)
  - [ogit/category](#)
  - [ogit/description](#)
  - [ogit/isMutable](#)
  - [ogit/lengthOfReportingPeriod](#)
  - [ogit/unit](#)
  - [ogit/uri](#)
  - [ogit/values](#)



## outgoing edges

- [ogit/describes](#) => [ogit/ServiceManagement/SLA](#)
- [ogit/describes](#) => [ogit/ServiceManagement/Service](#)
- [ogit/describes](#) => [ogit/ServiceManagement/Offering](#)

1.1.0.36 [ogit/ServiceManagement/Service](#)

A technology service item, which combined or not with other technology services can constitute a service offering ([ogit/ServiceManagement/Offering](#)).

- id: <http://www.purl.org/ogit/ServiceManagement/Service>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: NTO
- parent: [ogit/Node](#)

## attributes

- mandatory:
  - [ogit/id](#)
- optional:
  - [ogit/description](#)
  - [ogit/name](#)
  - [ogit/uri](#)

## incoming edges

- [ogit/affects](#) <= [ogit/Automation/MARSNode](#)
- [ogit/affects](#) <= [ogit/ServiceManagement/ChangeRequest](#)
- [ogit/affects](#) <= [ogit/ServiceManagement/Incident](#)
- [ogit/assignedTo](#) <= [ogit/ServiceManagement/ChangeRequest](#)
- [ogit/assignedTo](#) <= [ogit/ServiceManagement/Incident](#)
- [ogit/assignedTo](#) <= [ogit/ServiceManagement/Problem](#)
- [ogit/assignedTo](#) <= [ogit/ServiceManagement/Ticket](#)
- [ogit/calls](#) <= [ogit/ServiceManagement/Service](#)
- [ogit/contains](#) <= [ogit/ServiceManagement/Offering](#)
- [ogit/corresponds](#) <= [ogit/ServiceManagement/Order](#)
- [ogit/creates](#) <= [ogit/ServiceManagement/Report](#)
- [ogit/describes](#) <= [ogit/Parameter](#)

- `ogit/governs`  $\leq$  `ogit/Policy`
- `ogit/manages`  $\leq$  `ogit/Role`
- `ogit/owns`  $\leq$  `ogit/Person`
- `ogit/requires`  $\leq$  `ogit/ServiceManagement/Action`
- `ogit/requires`  $\leq$  `ogit/ServiceManagement/Service`
- `ogit/requires`  $\leq$  `ogit/CatalogItem`

#### outgoing edges

- `ogit/affects`  $\Rightarrow$  `ogit/Person`
- `ogit/calls`  $\Rightarrow$  `ogit/ServiceManagement/Service`
- `ogit/complies`  $\Rightarrow$  `ogit/ServiceManagement/SLA`
- `ogit/corresponds`  $\Rightarrow$  `ogit/CatalogItem`
- `ogit/generates`  $\Rightarrow$  `ogit/ServiceManagement/Report`
- `ogit/implements`  $\Rightarrow$  `ogit/Software/Application`
- `ogit/opens`  $\Rightarrow$  `ogit/ServiceManagement/Ticket`
- `ogit/opens`  $\Rightarrow$  `ogit/ServiceManagement/Incident`
- `ogit/requires`  $\Rightarrow$  `ogit/ServiceManagement/Service`
- `ogit/requires`  $\Rightarrow$  `ogit/ServiceManagement/Action`
- `ogit/supports`  $\Rightarrow$  `ogit/ServiceManagement/Action`

#### 1.1.0.37 ogit/Policy

A policy is a deliberate system of principles to guide decisions and achieve rational outcomes. It is connected and applied to Organizations

- id: <http://www.purl.org/ogit/Policy>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: SGO
- parent: ogit/Node

#### attributes

- mandatory:
  - `ogit/content`

#### outgoing edges

- `ogit/governs`  $\Rightarrow$  `ogit/ServiceManagement/Service`

## 1.1.0.38 ogit/ServiceManagement/Ticket

This entity defines any type of tickets. For specific behaviour of tickets, please check specific entities (e.g. ogit/↔ServiceManagement/Incident).

- id: <http://www.purl.org/ogit/ServiceManagement/Ticket>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: NTO
- parent: ogit/Node

## attributes

- mandatory:
  - [ogit/id](#)
- optional:
  - [ogit/ServiceManagement/externalTicketId](#)
  - [ogit/ServiceManagement/reportedSource](#)
  - [ogit/ServiceManagement/sourceStatus](#)
  - [ogit/ServiceManagement/ticketId](#)
  - [ogit/closedAt](#)
  - [ogit/createdAt](#)
  - [ogit/description](#)
  - [ogit/impact](#)
  - [ogit/lastUpdatedAt](#)
  - [ogit/openedAt](#)
  - [ogit/priority](#)
  - [ogit/project](#)
  - [ogit/summary](#)
  - [ogit/urgency](#)

## incoming edges

- [ogit/belongs](#) <= [ogit/ServiceManagement/SubTask](#)
- [ogit/belongs](#) <= [ogit/Attachment](#)
- [ogit/belongs](#) <= [ogit/Comment](#)
- [ogit/causes](#) <= [ogit/ServiceManagement/Order](#)
- [ogit/causes](#) <= [ogit/ServiceManagement/Ticket](#)
- [ogit/closes](#) <= [ogit/Person](#)
- [ogit/corresponds](#) <= [ogit/ServiceManagement/ChangeRequest](#)
- [ogit/corresponds](#) <= [ogit/ServiceManagement/Incident](#)

- `ogit/corresponds`  $\leq$  `ogit/ServiceManagement/Problem`
- `ogit/opens`  $\leq$  `ogit/ServiceManagement/Service`
- `ogit/opens`  $\leq$  `ogit/Person`
- `ogit/relates`  $\leq$  `ogit/ServiceManagement/Order`
- `ogit/relates`  $\leq$  `ogit/ServiceManagement/Ticket`
- `ogit/supervises`  $\leq$  `ogit/Organization`
- `ogit/supervises`  $\leq$  `ogit/Person`
- `ogit/updates`  $\leq$  `ogit/Person`

#### outgoing edges

- `ogit/affects`  $\Rightarrow$  `ogit/Person`
- `ogit/affects`  $\Rightarrow$  `ogit/MARS/Application`
- `ogit/affects`  $\Rightarrow$  `ogit/MARS/Resource`
- `ogit/affects`  $\Rightarrow$  `ogit/MARS/Software`
- `ogit/affects`  $\Rightarrow$  `ogit/MARS/Machine`
- `ogit/affects`  $\Rightarrow$  `ogit/Automation/MARSNode`
- `ogit/assignedTo`  $\Rightarrow$  `ogit/Person`
- `ogit/assignedTo`  $\Rightarrow$  `ogit/Organization`
- `ogit/assignedTo`  $\Rightarrow$  `ogit/ServiceManagement/Service`
- `ogit/causes`  $\Rightarrow$  `ogit/ServiceManagement/Ticket`
- `ogit/corresponds`  $\Rightarrow$  `ogit/Automation/AutomationIssue`
- `ogit/relates`  $\Rightarrow$  `ogit/ServiceManagement/Ticket`
- `ogit/reportedOn`  $\Rightarrow$  `ogit/MARS/Machine`
- `ogit/reportedOn`  $\Rightarrow$  `ogit/MARS/Software`
- `ogit/reportedOn`  $\Rightarrow$  `ogit/MARS/Resource`
- `ogit/reportedOn`  $\Rightarrow$  `ogit/MARS/Application`
- `ogit/reportedOn`  $\Rightarrow$  `ogit/Automation/MARSNode`

#### 1.1.0.39 ogit/Cost/CostElement

The cost element is a type of cost for an activity, an ordered service or a business unit or budget. There are 3 levels of cost elements: Top Level, Middle Level, Bottom Level. Between the different levels, for each cost element there could be two types of edges: Incoming and Outgoing. Each type of edge could have two types of connections  $\leftrightarrow$ : `consistsOf` and `contributesTo`. E.g. a cost element CPU consists in 30% of a HR cost element. The HR cost element contributes in 40% to the cost of the CPU cost element. This percentage values will then be saved in the entity Distribution, which will be connected to the cost element. For a general overview: see the NTO description on github.

- id: <http://www.purl.org/ogit/Cost/CostElement>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: NTO
- parent: `ogit/Node`

**incoming edges**

- [ogit/contains](#) <= [ogit/ServiceManagement/Offering](#)

**1.1.0.40 ogit/Timeseries**

A time series is a sequence of data points, measured typically at successive points in time spaced at uniform time intervals.

- id: <http://www.purl.org/ogit/Timeseries>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: SGO
- parent: [ogit/Node](#)

**attributes**

- optional:
  - [ogit/description](#)
  - [ogit/instance](#)
  - [ogit/name](#)
  - [ogit/unit](#)

**incoming edges**

- [ogit/uses](#) <= [ogit/ServiceManagement/Report](#)

## 1.2 Verbs

### 1.2.0.1 ogit/bills

Indicates if one entity bills another one, e.g. an Invoice bills an Order

- id: <http://www.purl.org/ogit/bills>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

#### Allowed Connection

- [ogit/Price/Invoice](#) => [ogit/ServiceManagement/Order](#)

### 1.2.0.2 ogit/contains

This relationship indicates that something is part of something else. see also "includes"

- id: <http://www.purl.org/ogit/contains>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

#### Allowed Connection

- [ogit/ServiceManagement/Offering](#) => [ogit/ServiceManagement/Order](#)
- [ogit/ServiceManagement/Offering](#) => [ogit/ServiceManagement/Service](#)
- [ogit/ServiceManagement/Offering](#) => [ogit/CatalogItem](#)
- [ogit/ServiceManagement/Offering](#) => [ogit/Cost/CostElement](#)
- [ogit/Contract](#) => [ogit/ServiceManagement/SLA](#)

### 1.2.0.3 ogit/manages

This relationship indicates that one entity manages some other.

- id: <http://www.purl.org/ogit/manages>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

#### Allowed Connection

- [ogit/Role](#) => [ogit/ServiceManagement/Service](#)

#### 1.2.0.4 ogit/defines

General relationship indicating that some entity defines some other.

- id: <http://www.purl.org/ogit/defines>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

##### Allowed Connection

- [ogit/Organization](#) => [ogit/ServiceManagement/Offering](#)

#### 1.2.0.5 ogit/triggers

This relationship indicates that one entity triggers some other.

- id: <http://www.purl.org/ogit/triggers>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

##### Allowed Connection

- [ogit/ServiceManagement/SLA](#) => [ogit/Penalty](#)

#### 1.2.0.6 ogit/supports

This relationship defines that one entity provides/supports another entity.

- id: <http://www.purl.org/ogit/supports>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

##### Allowed Connection

- [ogit/ServiceManagement/Service](#) => [ogit/ServiceManagement/Action](#)

#### 1.2.0.7 ogit/supervises

Indicates if an entity supervises another entity. E.g. a Person supervises a Ticket or a Task.

- id: <http://www.purl.org/ogit/supervises>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

**Allowed Connection**

- [ogit/Organization](#) => [ogit/ServiceManagement/SubTask](#)
- [ogit/Organization](#) => [ogit/ServiceManagement/ChangeRequest](#)
- [ogit/Organization](#) => [ogit/ServiceManagement/Order](#)
- [ogit/Organization](#) => [ogit/ServiceManagement/Ticket](#)
- [ogit/Organization](#) => [ogit/ServiceManagement/Problem](#)
- [ogit/Organization](#) => [ogit/ServiceManagement/Incident](#)
- [ogit/Person](#) => [ogit/ServiceManagement/SubTask](#)
- [ogit/Person](#) => [ogit/ServiceManagement/ChangeRequest](#)
- [ogit/Person](#) => [ogit/ServiceManagement/Order](#)
- [ogit/Person](#) => [ogit/ServiceManagement/Ticket](#)
- [ogit/Person](#) => [ogit/ServiceManagement/Problem](#)
- [ogit/Person](#) => [ogit/ServiceManagement/Incident](#)

**1.2.0.8 ogit/assignedTo**

Verb expressing which entity could be assigned to which another entity.

- id: <http://www.purl.org/ogit/assignedTo>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

**Allowed Connection**

- [ogit/ServiceManagement/ApprovalTask](#) => [ogit/Person](#)
- [ogit/ServiceManagement/ApprovalTask](#) => [ogit/Organization](#)
- [ogit/ServiceManagement/ChangeRequest](#) => [ogit/Person](#)
- [ogit/ServiceManagement/ChangeRequest](#) => [ogit/Organization](#)
- [ogit/ServiceManagement/ChangeRequest](#) => [ogit/ServiceManagement/Service](#)
- [ogit/ServiceManagement/Incident](#) => [ogit/Person](#)
- [ogit/ServiceManagement/Incident](#) => [ogit/Organization](#)
- [ogit/ServiceManagement/Incident](#) => [ogit/ServiceManagement/Service](#)
- [ogit/ServiceManagement/Order](#) => [ogit/Person](#)
- [ogit/ServiceManagement/Order](#) => [ogit/Organization](#)
- [ogit/ServiceManagement/Problem](#) => [ogit/Person](#)
- [ogit/ServiceManagement/Problem](#) => [ogit/Organization](#)
- [ogit/ServiceManagement/Problem](#) => [ogit/ServiceManagement/Service](#)
- [ogit/ServiceManagement/SubTask](#) => [ogit/Person](#)
- [ogit/ServiceManagement/SubTask](#) => [ogit/Organization](#)
- [ogit/ServiceManagement/Ticket](#) => [ogit/Person](#)
- [ogit/ServiceManagement/Ticket](#) => [ogit/Organization](#)
- [ogit/ServiceManagement/Ticket](#) => [ogit/ServiceManagement/Service](#)



### 1.2.0.9 ogit/generates

Verb indicating if an entity generates another entity.

- id: <http://www.purl.org/ogit/generates>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

#### Allowed Connection

- [ogit/ServiceManagement/Report](#) => [ogit/Price/Invoice](#)
- [ogit/ServiceManagement/Service](#) => [ogit/ServiceManagement/Report](#)

### 1.2.0.10 ogit/specifies

One entity "specifies" another.

- id: <http://www.purl.org/ogit/specifies>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

#### Allowed Connection

- [ogit/ServiceManagement/Offering](#) => [ogit/Automation/MARSModelTemplate](#)

### 1.2.0.11 ogit/calls

Verb showing which entity calls which another entity.

- id: <http://www.purl.org/ogit/calls>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

#### Allowed Connection

- [ogit/ServiceManagement/Service](#) => [ogit/ServiceManagement/Service](#)

### 1.2.0.12 ogit/opens

Indicates an entity which creates/opens another entity (e.g. Person opens Ticket).

- id: <http://www.purl.org/ogit/opens>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

**Allowed Connection**

- [ogit/ServiceManagement/Incident](#) => [ogit/Task](#)
- [ogit/ServiceManagement/Problem](#) => [ogit/ServiceManagement/Problem](#)
- [ogit/ServiceManagement/Service](#) => [ogit/ServiceManagement/Ticket](#)
- [ogit/ServiceManagement/Service](#) => [ogit/ServiceManagement/Incident](#)
- [ogit/Person](#) => [ogit/ServiceManagement/SubTask](#)
- [ogit/Person](#) => [ogit/ServiceManagement/ChangeRequest](#)
- [ogit/Person](#) => [ogit/ServiceManagement/Order](#)
- [ogit/Person](#) => [ogit/ServiceManagement/Ticket](#)
- [ogit/Person](#) => [ogit/ServiceManagement/Problem](#)
- [ogit/Person](#) => [ogit/ServiceManagement/Incident](#)

**1.2.0.13 ogit/describes**

This relationship allows to associate additional information with an entity. The "described" node can have many "describing" nodes.

- id: <http://www.purl.org/ogit/describes>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

**Allowed Connection**

- [ogit/Parameter](#) => [ogit/ServiceManagement/SLA](#)
- [ogit/Parameter](#) => [ogit/ServiceManagement/Service](#)
- [ogit/Parameter](#) => [ogit/ServiceManagement/Offering](#)

**1.2.0.14 ogit/precedes**

Describes the relation between a predecessor and a successor entity. This can be use in two ways: Either do define some temporal order of things. Or to define some dependency of actions to be done. The application managing such dependency graphs is responsible to prevent cyclic dependencies.

- id: <http://www.purl.org/ogit/precedes>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

**Allowed Connection**

- [ogit/ServiceManagement/ApprovalTask](#) => [ogit/ServiceManagement/ApprovalTask](#)
- [ogit/ServiceManagement/SubTask](#) => [ogit/ServiceManagement/SubTask](#)

## 1.2.0.15 ogit/creates

Indicates if one entity creates another one.

- id: <http://www.purl.org/ogit/creates>
- valid-from: Tue May 19 00:00:00 UTC 2015
- creator: Peter Larem

## Allowed Connection

- [ogit/ServiceManagement/Report](#) => [ogit/ServiceManagement/Service](#)
- [ogit/Software/Connector](#) => [ogit/ServiceManagement/ChangeRequest](#)
- [ogit/Software/Connector](#) => [ogit/ServiceManagement/Incident](#)

## 1.2.0.16 ogit/complies

Indicates whether one entity should comply to another.

- id: <http://www.purl.org/ogit/complies>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

## Allowed Connection

- [ogit/ServiceManagement/ChangeRequest](#) => [ogit/ServiceManagement/SLA](#)
- [ogit/ServiceManagement/Incident](#) => [ogit/ServiceManagement/SLA](#)
- [ogit/ServiceManagement/Problem](#) => [ogit/ServiceManagement/SLA](#)
- [ogit/ServiceManagement/Service](#) => [ogit/ServiceManagement/SLA](#)
- [ogit/Software/Application](#) => [ogit/ServiceManagement/SLA](#)

## 1.2.0.17 ogit/locatedIn

indicate that something has its place somewhere

- id: <http://www.purl.org/ogit/locatedIn>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

**Allowed Connection**

- [ogit/ServiceManagement/ChangeRequest](#) => [ogit/Location](#)
- [ogit/ServiceManagement/Incident](#) => [ogit/Location](#)
- [ogit/ServiceManagement/Offering](#) => [ogit/Location](#)
- [ogit/ServiceManagement/SubTask](#) => [ogit/Location](#)

**1.2.0.18 ogit/corresponds**

Indicates whether one entity could correspond to a more general one, e.g. an Incident could correspond to a Ticket

- id: <http://www.purl.org/ogit/corresponds>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

**Allowed Connection**

- [ogit/ServiceManagement/Action](#) => [ogit/CatalogItem](#)
- [ogit/ServiceManagement/ApprovalTask](#) => [ogit/Task](#)
- [ogit/ServiceManagement/ChangeRequest](#) => [ogit/ServiceManagement/Ticket](#)
- [ogit/ServiceManagement/ChangeRequest](#) => [ogit/Automation/AutomationIssue](#)
- [ogit/ServiceManagement/Incident](#) => [ogit/ServiceManagement/Ticket](#)
- [ogit/ServiceManagement/Incident](#) => [ogit/Automation/AutomationIssue](#)
- [ogit/ServiceManagement/Order](#) => [ogit/ServiceManagement/Service](#)
- [ogit/ServiceManagement/Problem](#) => [ogit/ServiceManagement/Ticket](#)
- [ogit/ServiceManagement/Problem](#) => [ogit/Automation/AutomationIssue](#)
- [ogit/ServiceManagement/Service](#) => [ogit/CatalogItem](#)
- [ogit/ServiceManagement/SubTask](#) => [ogit/Task](#)
- [ogit/ServiceManagement/SubTask](#) => [ogit/Automation/AutomationIssue](#)
- [ogit/ServiceManagement/Ticket](#) => [ogit/Automation/AutomationIssue](#)

**1.2.0.19 ogit/affects**

The relationship indicates that one entity affects some other entity.

- id: <http://www.purl.org/ogit/affects>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

**Allowed Connection**

- [ogit/Automation/MARSNode](#) => [ogit/ServiceManagement/Service](#)
- [ogit/ServiceManagement/ChangeRequest](#) => [ogit/Location](#)
- [ogit/ServiceManagement/ChangeRequest](#) => [ogit/ConfigurationItem](#)
- [ogit/ServiceManagement/ChangeRequest](#) => [ogit/ServiceManagement/Service](#)
- [ogit/ServiceManagement/ChangeRequest](#) => [ogit/Person](#)
- [ogit/ServiceManagement/ChangeRequest](#) => [ogit/MARS/Application](#)
- [ogit/ServiceManagement/ChangeRequest](#) => [ogit/MARS/Resource](#)
- [ogit/ServiceManagement/ChangeRequest](#) => [ogit/MARS/Software](#)
- [ogit/ServiceManagement/ChangeRequest](#) => [ogit/MARS/Machine](#)
- [ogit/ServiceManagement/ChangeRequest](#) => [ogit/Automation/MARSNode](#)
- [ogit/ServiceManagement/Incident](#) => [ogit/ServiceManagement/Service](#)
- [ogit/ServiceManagement/Incident](#) => [ogit/ConfigurationItem](#)
- [ogit/ServiceManagement/Incident](#) => [ogit/Person](#)
- [ogit/ServiceManagement/Incident](#) => [ogit/MARS/Application](#)
- [ogit/ServiceManagement/Incident](#) => [ogit/MARS/Resource](#)
- [ogit/ServiceManagement/Incident](#) => [ogit/MARS/Software](#)
- [ogit/ServiceManagement/Incident](#) => [ogit/MARS/Machine](#)
- [ogit/ServiceManagement/Incident](#) => [ogit/Automation/MARSNode](#)
- [ogit/ServiceManagement/Order](#) => [ogit/Person](#)
- [ogit/ServiceManagement/Order](#) => [ogit/Automation/MARSNode](#)
- [ogit/ServiceManagement/Problem](#) => [ogit/Person](#)
- [ogit/ServiceManagement/Problem](#) => [ogit/MARS/Application](#)
- [ogit/ServiceManagement/Problem](#) => [ogit/MARS/Resource](#)
- [ogit/ServiceManagement/Problem](#) => [ogit/MARS/Software](#)
- [ogit/ServiceManagement/Problem](#) => [ogit/MARS/Machine](#)
- [ogit/ServiceManagement/Problem](#) => [ogit/Automation/MARSNode](#)
- [ogit/ServiceManagement/Service](#) => [ogit/Person](#)
- [ogit/ServiceManagement/SubTask](#) => [ogit/ConfigurationItem](#)
- [ogit/ServiceManagement/Ticket](#) => [ogit/Person](#)
- [ogit/ServiceManagement/Ticket](#) => [ogit/MARS/Application](#)
- [ogit/ServiceManagement/Ticket](#) => [ogit/MARS/Resource](#)
- [ogit/ServiceManagement/Ticket](#) => [ogit/MARS/Software](#)
- [ogit/ServiceManagement/Ticket](#) => [ogit/MARS/Machine](#)
- [ogit/ServiceManagement/Ticket](#) => [ogit/Automation/MARSNode](#)

### 1.2.0.20 ogit/requires

Indicates dependencies between entities in the sense of "necessary condition".

- id: <http://www.purl.org/ogit/requires>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

#### Allowed Connection

- [ogit/ServiceManagement/Action](#) => [ogit/ServiceManagement/Service](#)
- [ogit/ServiceManagement/Action](#) => [ogit/ServiceManagement/Action](#)
- [ogit/ServiceManagement/Action](#) => [ogit/CatalogItem](#)
- [ogit/ServiceManagement/Service](#) => [ogit/ServiceManagement/Service](#)
- [ogit/ServiceManagement/Service](#) => [ogit/ServiceManagement/Action](#)
- [ogit/CatalogItem](#) => [ogit/ServiceManagement/Service](#)
- [ogit/CatalogItem](#) => [ogit/ServiceManagement/Action](#)

### 1.2.0.21 ogit/implements

Defines that an entity provides the implementation for another entity.

- id: <http://www.purl.org/ogit/implements>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

#### Allowed Connection

- [ogit/Automation/MARSModel](#) => [ogit/ServiceManagement/Order](#)
- [ogit/ServiceManagement/Service](#) => [ogit/Software/Application](#)

### 1.2.0.22 ogit/requests

Indicates if one entity requests another, e.g. Person requests a ChangeRequest. This might be different from the person who created the ticket (ogit/ITSM/openedBy) in case the reporter is calling a service desk and the ticket will be opened by help desk staff. Sometimes also named as "caller". This Person or entity must be kept informed about relevant updates of the ticket.

- id: <http://www.purl.org/ogit/requests>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

**Allowed Connection**

- [ogit/Person](#) => [ogit/ServiceManagement/SubTask](#)
- [ogit/Person](#) => [ogit/ServiceManagement/ChangeRequest](#)

**1.2.0.23 ogit/updates**

Indicates which entity (e.g. Person) updated each another entity (e.g. Ticket).

- id: <http://www.purl.org/ogit/updates>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

**Allowed Connection**

- [ogit/Person](#) => [ogit/ServiceManagement/ChangeRequest](#)
- [ogit/Person](#) => [ogit/ServiceManagement/Order](#)
- [ogit/Person](#) => [ogit/ServiceManagement/Ticket](#)
- [ogit/Person](#) => [ogit/ServiceManagement/Problem](#)
- [ogit/Person](#) => [ogit/ServiceManagement/Incident](#)
- [ogit/Person](#) => [ogit/ServiceManagement/SubTask](#)

**1.2.0.24 ogit/causes**

Indicates that one entity causes the creation of another one. E.g. an error situation during change execution might lead to a new incident ticket.

- id: <http://www.purl.org/ogit/causes>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

**Allowed Connection**

- [ogit/ServiceManagement/ChangeRequest](#) => [ogit/ServiceManagement/ChangeRequest](#)
- [ogit/ServiceManagement/ChangeRequest](#) => [ogit/ServiceManagement/Order](#)
- [ogit/ServiceManagement/Incident](#) => [ogit/ServiceManagement/Problem](#)
- [ogit/ServiceManagement/Incident](#) => [ogit/ServiceManagement/Incident](#)
- [ogit/ServiceManagement/Incident](#) => [ogit/Event](#)
- [ogit/ServiceManagement/Incident](#) => [ogit/ServiceManagement/ChangeRequest](#)
- [ogit/ServiceManagement/Incident](#) => [ogit/ServiceManagement/Order](#)
- [ogit/ServiceManagement/Order](#) => [ogit/ServiceManagement/Ticket](#)
- [ogit/ServiceManagement/Order](#) => [ogit/ServiceManagement/ChangeRequest](#)
- [ogit/ServiceManagement/Order](#) => [ogit/ServiceManagement/Order](#)
- [ogit/ServiceManagement/Problem](#) => [ogit/ServiceManagement/Problem](#)
- [ogit/ServiceManagement/Problem](#) => [ogit/ServiceManagement/ChangeRequest](#)
- [ogit/ServiceManagement/Ticket](#) => [ogit/ServiceManagement/Ticket](#)

## 1.2.0.25 ogit/owns

This relationship indicates that one entity owns some other.

- id: <http://www.purl.org/ogit/owns>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

## Allowed Connection

- [ogit/Person](#) => [ogit/ServiceManagement/Service](#)

## 1.2.0.26 ogit/closes

Indicates if one entity closes another one, e.g. a Person might close a Ticket

- id: <http://www.purl.org/ogit/closes>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

## Allowed Connection

- [ogit/Person](#) => [ogit/ServiceManagement/ChangeRequest](#)
- [ogit/Person](#) => [ogit/ServiceManagement/Order](#)
- [ogit/Person](#) => [ogit/ServiceManagement/Ticket](#)
- [ogit/Person](#) => [ogit/ServiceManagement/Problem](#)
- [ogit/Person](#) => [ogit/ServiceManagement/Incident](#)
- [ogit/Person](#) => [ogit/ServiceManagement/SubTask](#)

## 1.2.0.27 ogit/belongs

Verb showing if one entity belongs to another.

- id: <http://www.purl.org/ogit/belongs>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem



**Allowed Connection**

- [ogit/ServiceManagement/ApprovalTask](#) => [ogit/ServiceManagement/ChangeRequest](#)
- [ogit/ServiceManagement/SubTask](#) => [ogit/ServiceManagement/Ticket](#)
- [ogit/ServiceManagement/SubTask](#) => [ogit/ServiceManagement/Problem](#)
- [ogit/ServiceManagement/SubTask](#) => [ogit/ServiceManagement/Incident](#)
- [ogit/ServiceManagement/SubTask](#) => [ogit/ServiceManagement/ChangeRequest](#)
- [ogit/ServiceManagement/SubTask](#) => [ogit/ServiceManagement/Order](#)
- [ogit/Attachment](#) => [ogit/ServiceManagement/SubTask](#)
- [ogit/Attachment](#) => [ogit/ServiceManagement/Ticket](#)
- [ogit/Attachment](#) => [ogit/ServiceManagement/Problem](#)
- [ogit/Attachment](#) => [ogit/ServiceManagement/Incident](#)
- [ogit/Attachment](#) => [ogit/ServiceManagement/ChangeRequest](#)
- [ogit/Attachment](#) => [ogit/ServiceManagement/Order](#)
- [ogit/Comment](#) => [ogit/ServiceManagement/SubTask](#)
- [ogit/Comment](#) => [ogit/ServiceManagement/Ticket](#)

**1.2.0.28 ogit/reports**

Verb showing which entity reports to which another entity.

- id: <http://www.purl.org/ogit/reports>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

**Allowed Connection**

- [ogit/Person](#) => [ogit/ServiceManagement/Problem](#)
- [ogit/Person](#) => [ogit/ServiceManagement/Incident](#)

**1.2.0.29 ogit/uses**

This relationship indicates that some entity is used by some other.

- id: <http://www.purl.org/ogit/uses>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

**Allowed Connection**

- [ogit/ServiceManagement/ChangeRequest](#) => [ogit/ServiceManagement/ChangeRequest](#)
- [ogit/ServiceManagement/Report](#) => [ogit/Timeseries](#)

**1.2.0.30 ogit/reportedOn**

Indicates where a failure situation was initially observed. In case an incident record is created from an event management system this relationship points to the entity that represents the monitored device/endpoint. We call it "reportedOn" instead of "observedOn" to account for the close relation to "reportedAt", "reportedBy"

- id: <http://www.purl.org/ogit/reportedOn>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

**Allowed Connection**

- [ogit/ServiceManagement/ChangeRequest](#) => [ogit/MARS/Machine](#)
- [ogit/ServiceManagement/ChangeRequest](#) => [ogit/MARS/Software](#)
- [ogit/ServiceManagement/ChangeRequest](#) => [ogit/MARS/Resource](#)
- [ogit/ServiceManagement/ChangeRequest](#) => [ogit/MARS/Application](#)
- [ogit/ServiceManagement/ChangeRequest](#) => [ogit/Automation/MARSNode](#)
- [ogit/ServiceManagement/Incident](#) => [ogit/MARS/Machine](#)
- [ogit/ServiceManagement/Incident](#) => [ogit/MARS/Software](#)
- [ogit/ServiceManagement/Incident](#) => [ogit/MARS/Resource](#)
- [ogit/ServiceManagement/Incident](#) => [ogit/MARS/Application](#)
- [ogit/ServiceManagement/Incident](#) => [ogit/Automation/MARSNode](#)
- [ogit/ServiceManagement/Order](#) => [ogit/MARS/Machine](#)
- [ogit/ServiceManagement/Order](#) => [ogit/MARS/Software](#)
- [ogit/ServiceManagement/Order](#) => [ogit/MARS/Resource](#)
- [ogit/ServiceManagement/Order](#) => [ogit/MARS/Application](#)
- [ogit/ServiceManagement/Order](#) => [ogit/Automation/MARSNode](#)
- [ogit/ServiceManagement/Problem](#) => [ogit/MARS/Machine](#)
- [ogit/ServiceManagement/Problem](#) => [ogit/MARS/Software](#)
- [ogit/ServiceManagement/Problem](#) => [ogit/MARS/Resource](#)
- [ogit/ServiceManagement/Problem](#) => [ogit/MARS/Application](#)
- [ogit/ServiceManagement/Problem](#) => [ogit/Automation/MARSNode](#)
- [ogit/ServiceManagement/Ticket](#) => [ogit/MARS/Machine](#)
- [ogit/ServiceManagement/Ticket](#) => [ogit/MARS/Software](#)
- [ogit/ServiceManagement/Ticket](#) => [ogit/MARS/Resource](#)
- [ogit/ServiceManagement/Ticket](#) => [ogit/MARS/Application](#)
- [ogit/ServiceManagement/Ticket](#) => [ogit/Automation/MARSNode](#)

## 1.2.0.31 ogit/governs

Verb showing if an entity governs/enforces another one.

- id: <http://www.purl.org/ogit/governs>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

## Allowed Connection

- [ogit/Policy](#) => [ogit/ServiceManagement/Service](#)

## 1.2.0.32 ogit/relates

General relationship indicating that one entity is related to another one.

- id: <http://www.purl.org/ogit/relates>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

## Allowed Connection

- [ogit/ServiceManagement/ChangeRequest](#) => [ogit/ServiceManagement/Problem](#)
- [ogit/ServiceManagement/ChangeRequest](#) => [ogit/ServiceManagement/Incident](#)
- [ogit/ServiceManagement/ChangeRequest](#) => [ogit/ServiceManagement/ChangeRequest](#)
- [ogit/ServiceManagement/ChangeRequest](#) => [ogit/ServiceManagement/Order](#)
- [ogit/ServiceManagement/ChangeRequest](#) => [ogit/MARS/Machine](#)
- [ogit/ServiceManagement/ChangeRequest](#) => [ogit/MARS/Software](#)
- [ogit/ServiceManagement/ChangeRequest](#) => [ogit/MARS/Resource](#)
- [ogit/ServiceManagement/ChangeRequest](#) => [ogit/MARS/Application](#)
- [ogit/ServiceManagement/ChangeRequest](#) => [ogit/Automation/MARSNode](#)
- [ogit/ServiceManagement/Incident](#) => [ogit/ServiceManagement/Problem](#)
- [ogit/ServiceManagement/Incident](#) => [ogit/ServiceManagement/Incident](#)
- [ogit/ServiceManagement/Incident](#) => [ogit/ServiceManagement/ChangeRequest](#)
- [ogit/ServiceManagement/Order](#) => [ogit/ServiceManagement/Ticket](#)
- [ogit/ServiceManagement/Order](#) => [ogit/ServiceManagement/Problem](#)
- [ogit/ServiceManagement/Order](#) => [ogit/ServiceManagement/Incident](#)
- [ogit/ServiceManagement/Order](#) => [ogit/ServiceManagement/ChangeRequest](#)
- [ogit/ServiceManagement/Order](#) => [ogit/ServiceManagement/Order](#)

- [ogit/ServiceManagement/Order](#) => [ogit/Contract](#)
- [ogit/ServiceManagement/Problem](#) => [ogit/ServiceManagement/Problem](#)
- [ogit/ServiceManagement/Problem](#) => [ogit/ServiceManagement/Incident](#)
- [ogit/ServiceManagement/Problem](#) => [ogit/ServiceManagement/ChangeRequest](#)
- [ogit/ServiceManagement/Problem](#) => [ogit/ServiceManagement/Order](#)
- [ogit/ServiceManagement/Report](#) => [ogit/MARS/Machine](#)
- [ogit/ServiceManagement/Report](#) => [ogit/MARS/Software](#)
- [ogit/ServiceManagement/Report](#) => [ogit/MARS/Resource](#)
- [ogit/ServiceManagement/Report](#) => [ogit/MARS/Application](#)
- [ogit/ServiceManagement/Report](#) => [ogit/Automation/MARSNode](#)
- [ogit/ServiceManagement/Ticket](#) => [ogit/ServiceManagement/Ticket](#)
- [ogit/Event](#) => [ogit/ServiceManagement/Order](#)
- [ogit/Event](#) => [ogit/ServiceManagement/Incident](#)

#### 1.2.0.33 [ogit/availableIn](#)

Indicates that something can be found from somewhere.

- id: <http://www.purl.org/ogit/availableIn>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

#### Allowed Connection

- [ogit/ServiceManagement/Offering](#) => [ogit/Region](#)

## 1.3 Attributes

### 1.3.0.1 ogit/MARS/Network/fqdn

A FQDN according to RFC 1035. Replaces 'FQDN' from MARS-Schema

- id: <http://www.purl.org/ogit/MARS/Network/fqdn>
- valid-from: Fri Jun 01 00:00:00 UTC 2018
- creator: [fotto@arago.de](mailto:fotto@arago.de)

used

- optional:
  - [ogit/MARS/Machine](#)

### 1.3.0.2 ogit/Automation/serviceType

Contains the Type of a service.

- id: <http://www.purl.org/ogit/Automation/serviceType>
- valid-from: Fri Jul 24 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

### 1.3.0.3 ogit/ciType

Type of a configuration item. For example: VM, Server or Device.

- id: <http://www.purl.org/ogit/ciType>
- valid-from: Thu Aug 20 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

#### 1.3.0.4 ogit/MARS/Software/installPath

Defines where a software is installed. Replaces 'SWInstallPath' and 'BasePath' from MARS-Schema

- id: <http://www.purl.org/ogit/MARS/Software/installPath>
- valid-from: Fri Jun 01 00:00:00 UTC 2018
- creator: [fotto@arago.de](mailto:fotto@arago.de)

used

- optional:
  - [ogit/MARS/Software](#)
  - [ogit/MARS/Software](#)

#### 1.3.0.5 ogit/ServiceManagement/requirementId

IDs of the corresponding requirements that lead to the entity creation.

- id: <http://www.purl.org/ogit/ServiceManagement/requirementId>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Parameter](#)

#### 1.3.0.6 ogit/reviewedAt

Defines the time when something was actually reviewed. The values can combin date and time with time zone designator according to ISO 8601. Reviewed time is used in incident management.

- id: <http://www.purl.org/ogit/reviewedAt>
- valid-from: Wed Jul 01 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ServiceManagement/ChangeRequest](#)

#### 1.3.0.7 ogit/MARS/Network/interfaceMAC

Alloes to specifies the MAC address of all defined interfaces. It's a key'ed list with the key to be defined in attribute ogit/MARS/Network/interfaceName of the same Machine node. Replaces 'NetworkInterfaceMAC' from MARS-↔ Schema

- id: <http://www.purl.org/ogit/MARS/Network/interfaceMAC>
- valid-from: Fri Jun 01 00:00:00 UTC 2018
- creator: [fotto@arago.de](mailto:fotto@arago.de)

used

- optional:
  - [ogit/MARS/Machine](#)

#### 1.3.0.8 ogit/Automation/serialNumber

Contains a the serial number of a device/component.

- id: <http://www.purl.org/ogit/Automation/serialNumber>
- valid-from: Fri Jul 24 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

#### 1.3.0.9 ogit/Automation/servletName

Contains the name if the servlet.

- id: <http://www.purl.org/ogit/Automation/servletName>
- valid-from: Fri Jul 24 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

#### 1.3.0.10 ogit/Automation/cpuCoreCount

Contains the number of cpu cores.

- id: <http://www.purl.org/ogit/Automation/cpuCoreCount>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

#### 1.3.0.11 ogit/Automation/serviceId

Contains the Id of the service.

- id: <http://www.purl.org/ogit/Automation/serviceId>
- valid-from: Fri Jul 24 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

#### 1.3.0.12 ogit/manufacture

Manufacturer of a device or component.

- id: <http://www.purl.org/ogit/manufacture>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)



#### 1.3.0.13 [ogit/ServiceManagement/testPlan](#)

Contains a test plan used in change management to define how a successful change implementation can be verified.

- id: <http://www.purl.org/ogit/ServiceManagement/testPlan>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ServiceManagement/ChangeRequest](#)

#### 1.3.0.14 [ogit/certainty](#)

Defines the certainty of an event

- id: <http://www.purl.org/ogit/certainty>
- valid-from: Wed Aug 03 00:00:00 UTC 2016
- creator: Philipp Pelchmann

used

- optional:
  - [ogit/Event](#)

#### 1.3.0.15 [ogit/reason](#)

Describes the reason for a decision.

- id: <http://www.purl.org/ogit/reason>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ServiceManagement/ApprovalTask](#)

**1.3.0.16** ogit/currency

A currency code, possibly according to ISO 4217.

- id: <http://www.purl.org/ogit/currency>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- mandatory:
  - [ogit/Price/Invoice](#)
- optional:
  - [ogit/ServiceManagement/Offering](#)

**1.3.0.17** ogit/category

Used to categorize things.

- id: <http://www.purl.org/ogit/category>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ConfigurationItem](#)
  - [ogit/Event](#)
  - [ogit/Parameter](#)
  - [ogit/ServiceManagement/ChangeRequest](#)
  - [ogit/ServiceManagement/Incident](#)
  - [ogit/ServiceManagement/Offering](#)

**1.3.0.18** ogit/ServiceManagement/isRequired

True if the value has to be specified for the Service to be provisioned. False otherwise.

- id: <http://www.purl.org/ogit/ServiceManagement/isRequired>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Parameter](#)

**1.3.0.19 ogit/comment**

Contains a comment.

- id: <http://www.purl.org/ogit/comment>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

**1.3.0.20 ogit/Automation/osVersion**

Version of the Operating System.

- id: <http://www.purl.org/ogit/Automation/osVersion>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Philipp Pelchmann

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.21 ogit/assignedAt**

Defines the time when something was actually assigned to a person/organization for example. The values can combine date and time with time zone designator according to ISO 8601.

- id: <http://www.purl.org/ogit/assignedAt>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

## 1.3.0.22 ogit/endOfWarranty

End of warranty phase of a component

- id: <http://www.purl.org/ogit/endOfWarranty>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Automation/MARSNode](#)
  - [ogit/ConfigurationItem](#)
  - [ogit/MARS/Machine](#)
  - [ogit/MARS/Software](#)

## 1.3.0.23 ogit/postalCode

The postal code. For example, 60433.

- id: <http://www.purl.org/ogit/postalCode>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Organization](#)

## 1.3.0.24 ogit/Automation/buildType

Contains the build type of a component.

- id: <http://www.purl.org/ogit/Automation/buildType>
- valid-from: Wed Aug 19 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.25** `ogit/Automation/cpuManufacturer`

Contains the manufacturer of the cpu of a device.

- id: <http://www.purl.org/ogit/Automation/cpuManufacturer>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.26** `ogit/Automation/virtualMachineName`

Contains the name of the virtual machine.

- id: <http://www.purl.org/ogit/Automation/virtualMachineName>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.27** `ogit/productOrderNumber`

An integer, which displays the order number of a product.

- id: <http://www.purl.org/ogit/productOrderNumber>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

**1.3.0.28** `ogit/MARS/Network/bindAddress`

Usually an IP address. Defines the listening address for a software (server). Replaces 'NetworkIP' from MARS-Schema

- id: <http://www.purl.org/ogit/MARS/Network/bindAddress>
- valid-from: Fri Jun 01 00:00:00 UTC 2018
- creator: [fotto@arago.de](mailto:fotto@arago.de)

used

- optional:
  - [ogit/MARS/Software](#)

**1.3.0.29** `ogit/ServiceManagement/approvalStatus`

Status of an ApprovalTask containing one of the following values: New|PendingApproval|Approved|Rejected|Cancelled|Closed.

- id: <http://www.purl.org/ogit/ServiceManagement/approvalStatus>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ServiceManagement/ApprovalTask](#)

**1.3.0.30** `ogit/MARS/Machine/class`

Defines the 'class' of a Machine MARS node. This is basically the Operation System name. Replaces 'MachineClass' from MARS-Schema

- id: <http://www.purl.org/ogit/MARS/Machine/class>
- valid-from: Fri Jun 01 00:00:00 UTC 2018
- creator: [fotto@arago.de](mailto:fotto@arago.de)

used

- mandatory:
  - [ogit/MARS/Machine](#)

#### 1.3.0.31 [ogit/MARS/Machine/cpuArch](#)

CPU architecture. On UNIX like systems it will be the output of 'uname -m'. Replaces 'MachineArchitecture' from MARS-Schema

- id: <http://www.purl.org/ogit/MARS/Machine/cpuArch>
- valid-from: Fri Jun 01 00:00:00 UTC 2018
- creator: [fotto@arago.de](mailto:fotto@arago.de)

used

- optional:
  - [ogit/MARS/Machine](#)

#### 1.3.0.32 [ogit/checkedOutAt](#)

Defines the time when something was actually checked out. The values can combine date and time with time zone designator according to ISO 8601.

- id: <http://www.purl.org/ogit/checkedOutAt>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

#### 1.3.0.33 [ogit/email](#)

An email address.

- id: <http://www.purl.org/ogit/email>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Organization](#)
  - [ogit/Person](#)

**1.3.0.34** `ogit/Automation/moveToProductionAt`

Defines the time when something was actually moved to production. The values can combine date and time with time zone designator according to ISO 8601.

- id: <http://www.purl.org/ogit/Automation/moveToProductionAt>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.35** `ogit/MARS/Software/logPath`

Defines where a software writes its logfiles. Replaces 'LogPath' from MARS-Schema

- id: <http://www.purl.org/ogit/MARS/Software/logPath>
- valid-from: Fri Jun 01 00:00:00 UTC 2018
- creator: [fotto@arago.de](mailto:fotto@arago.de)

used

- optional:
  - [ogit/MARS/Software](#)

**1.3.0.36** `ogit/ServiceManagement/resolvedAt`

Datetime indicating when a ticket was resolved. Can be used for incident or problem tickets when it is necessary to distinguish between the ticket resolving and ticket closure (`closedAt`). The values must be combined date and time with time zone designator according to ISO 8601

- id: <http://www.purl.org/ogit/ServiceManagement/resolvedAt>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ServiceManagement/Incident](#)



**1.3.0.37 ogit/urgency**

Contains the urgency which could be applied to a ticket, incident etc.

- id: <http://www.purl.org/ogit/urgency>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ServiceManagement/Order](#)
  - [ogit/ServiceManagement/Ticket](#)

**1.3.0.38 ogit/deliveredAt**

Defines a point in time when a component/device was actually delivered. The values must be combined date and time with time zone designator according to ISO 8601

- id: <http://www.purl.org/ogit/deliveredAt>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

**1.3.0.39 ogit/Automation/osServicePack**

Contains the service pack for the operating system.

- id: <http://www.purl.org/ogit/Automation/osServicePack>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Philipp Pelchmann

used

- optional:
  - [ogit/Automation/MARSNode](#)

1.3.0.40 `ogit/alternativeName`

Alternative name of something. In context of a Person this can be the full name or an alias/nick name.

- id: <http://www.purl.org/ogit/alternativeName>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Person](#)

1.3.0.41 `ogit/isCritical`

This field specifies if the CI is critical for day-to-day operation, such as an E-mail server or RDBMS server. If you open an incident on a critical CI, the incident indicates that this is a critical CI. This field contains a boolean value.

- id: <http://www.purl.org/ogit/isCritical>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

1.3.0.42 `ogit/asset`

This field represents an asset (device or component).

- id: <http://www.purl.org/ogit/asset>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

#### 1.3.0.43 `ogit/Automation/portNumberListener`

Contains a port number listener.

- id: <http://www.purl.org/ogit/Automation/portNumberListener>
- valid-from: Fri Jul 24 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

#### 1.3.0.44 `ogit/function`

Attribute used to specify a function that some entity does/provides. This is more specific than 'description'. Should contain a short string. At this level of specification it is still a free from string. However, unlike 'description', it is expected to contain some list of fixed values.

- id: <http://www.purl.org/ogit/function>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Organization](#)

#### 1.3.0.45 `ogit/positionNumber`

An integer, which displays a position of numbering.

- id: <http://www.purl.org/ogit/positionNumber>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Task](#)

**1.3.0.46** `ogit/ServiceManagement/customer`

The customer related to a Service Management process.

- id: <http://www.purl.org/ogit/ServiceManagement/customer>
- valid-from: Fri Jul 03 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ServiceManagement/ChangeRequest](#)
  - [ogit/ServiceManagement/Incident](#)
  - [ogit/ServiceManagement/SubTask](#)

**1.3.0.47** `ogit/Version/major`

major version according to <https://semver.org/>

- id: <http://www.purl.org/ogit/Version/major>
- valid-from: Fri May 25 00:00:00 UTC 2018
- creator: [fotto@arago.de](mailto:fotto@arago.de)

used

- optional:
  - [ogit/MARS/Machine](#)
  - [ogit/MARS/Software](#)

**1.3.0.48** `ogit/Automation/memory`

Contains a the total physical memory (RAM) in MB.

- id: <http://www.purl.org/ogit/Automation/memory>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.49 ogit/integrity**

A security principle that ensures data and Configuration Items are only modified by authorized personnel and Activities

- id: <http://www.purl.org/ogit/integrity>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

**1.3.0.50 ogit/Automation/companyName**

Contains the company name of a component.

- id: <http://www.purl.org/ogit/Automation/companyName>
- valid-from: Mon Nov 02 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.51 ogit/ServiceManagement/scheduledStartAt**

Defines a point in time when the work on a change is planned/scheduled to start. This date time is usually defined during change planning and/or approval. This datetime is set by change coordinator (e.g it is planned to be done at 7:30PM) The values must be combined date and time with time zone designator according to ISO 8601.

- id: <http://www.purl.org/ogit/ServiceManagement/scheduledStartAt>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ServiceManagement/ChangeRequest](#)
  - [ogit/ServiceManagement/SubTask](#)

## 1.3.0.52 ogit/country

Name of a country.

- id: <http://www.purl.org/ogit/country>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Philipp Pelchmann

used

- optional:
  - [ogit/Organization](#)

## 1.3.0.53 ogit/businessCategory

The category of a business.

- id: <http://www.purl.org/ogit/businessCategory>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Philipp Pelchmann

used

- optional:
  - [ogit/Organization](#)

## 1.3.0.54 ogit/Automation/middlewareType

Contains information about the type of middleware. For example it database middleware, application server middleware or a message-oriented middleware.

- id: <http://www.purl.org/ogit/Automation/middlewareType>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.55** `ogit/Automation/serviceName`

Contains the name of a service.

- id: <http://www.purl.org/ogit/Automation/serviceName>
- valid-from: Fri Jul 24 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.56** `ogit/project`

Project name, for which the entity is being used.

- id: <http://www.purl.org/ogit/project>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ServiceManagement/Order](#)
  - [ogit/ServiceManagement/Ticket](#)

**1.3.0.57** `ogit/Automation/licenseAvailability`

The availability of the license of a component.

- id: <http://www.purl.org/ogit/Automation/licenseAvailability>
- valid-from: Fri Jul 24 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.58** `ogit/ServiceManagement/granularity`

Smallest value increment of a Parameter

- id: <http://www.purl.org/ogit/ServiceManagement/granularity>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Parameter](#)

**1.3.0.59** `ogit/question`

Contains a question.

- id: <http://www.purl.org/ogit/question>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Task](#)

**1.3.0.60** `ogit/maintenanceState`

Defines the state of maintenance.

- id: <http://www.purl.org/ogit/maintenanceState>
- valid-from: Wed Aug 03 00:00:00 UTC 2016
- creator: Philipp Pelchmann

used

- optional:
  - [ogit/Event](#)



**1.3.0.61 ogit/notification**

A notification.

- id: <http://www.purl.org/ogit/notification>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Philipp Pelchmann

used

- optional:
  - [ogit/Person](#)

**1.3.0.62 ogit/ServiceManagement/externalTicketId**

If a ticket was imported/duplicated from another system this attribute will define the ticket ID from the source system.

- id: <http://www.purl.org/ogit/ServiceManagement/externalTicketId>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ServiceManagement/Order](#)
  - [ogit/ServiceManagement/Ticket](#)

**1.3.0.63 ogit/sourceId**

The Id of the source system.

- id: <http://www.purl.org/ogit/sourceId>
- valid-from: Thu Jun 11 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Event](#)
  - [ogit/Organization](#)
  - [ogit/Person](#)

**1.3.0.64** ogit/url

Contains an URL (unified resource locator)

- id: <http://www.purl.org/ogit/url>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Attachment](#)
  - [ogit/MARS/Resource](#)
  - [ogit/MARS/Software](#)
  - [ogit/Software/Application](#)

**1.3.0.65** ogit/uri

Unified resource identifier

- id: <http://www.purl.org/ogit/uri>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Parameter](#)
  - [ogit/ServiceManagement/Service](#)

**1.3.0.66** ogit/purchasedAt

Defines a point in time when a component/device was actually purchased. The values must be combined date and time with time zone designator according to ISO 8601

- id: <http://www.purl.org/ogit/purchasedAt>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

**1.3.0.67** `ogit/Automation/cpuCount`

An integer which shows the number of cps of a component.

- id: <http://www.purl.org/ogit/Automation/cpuCount>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.68** `ogit/Automation/databaseSchema`

Contains information about the database schema. The schema is the skeleton structure that represents the logical view of the entire database

- id: <http://www.purl.org/ogit/Automation/databaseSchema>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.69** `ogit/mobilePhone`

A mobile phone number.

- id: <http://www.purl.org/ogit/mobilePhone>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Person](#)

#### 1.3.0.70 [ogit/Automation/additionalMacAddress](#)

Contains an additional MAC address

- id: <http://www.purl.org/ogit/Automation/additionalMacAddress>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

#### 1.3.0.71 [ogit/severity](#)

Stores a severity. E.g. Some event management systems might store a severity field.

- id: <http://www.purl.org/ogit/severity>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Event](#)

#### 1.3.0.72 [ogit/connectorId](#)

The Id of the connector.

- id: <http://www.purl.org/ogit/connectorId>
- valid-from: Thu Jun 11 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)
  - [ogit/Software/Connector](#)

**1.3.0.73 ogit/Automation/dataClassification**

Data classification of a component.

- id: <http://www.purl.org/ogit/Automation/dataClassification>
- valid-from: Fri Jul 24 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.74 ogit/Automation/firmwareVersion**

Version of the firmware.

- id: <http://www.purl.org/ogit/Automation/firmwareVersion>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.75 ogit/effort**

Defines how much time was spent on the actual work for a change, task, or similar entity. The values is expected to be in format HH:MM, e.g. 1:00 for 1 hour effort.

- id: <http://www.purl.org/ogit/effort>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ServiceManagement/ChangeRequest](#)
  - [ogit/ServiceManagement/SubTask](#)

**1.3.0.76** ogit/startedAt

Defines a point in time when the work on a change, task, or similar entity was actually started. The values must be combined date and time with time zone designator according to ISO 8601

- id: <http://www.purl.org/ogit/startedAt>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ConfigurationItem](#)
  - [ogit/ServiceManagement/ChangeRequest](#)
  - [ogit/ServiceManagement/SLA](#)
  - [ogit/ServiceManagement/SubTask](#)

**1.3.0.77** ogit/ServiceManagement/taskName

Contains the task name. In some cases it might be equal to taskID or to some short description (summary) of the task.

- id: <http://www.purl.org/ogit/ServiceManagement/taskName>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

**1.3.0.78** ogit/assetTag

This field specifies the asset tag number/code.

- id: <http://www.purl.org/ogit/assetTag>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

**1.3.0.79 ogit/ipAddress**

The IP address of a component/hardware device.

- id: <http://www.purl.org/ogit/ipAddress>
- valid-from: Wed May 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.80 ogit/unit**

Unit of measurement of some value.

- id: <http://www.purl.org/ogit/unit>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Parameter](#)
  - [ogit/Timeseries](#)

**1.3.0.81 ogit/Automation/installCount**

Contains an integer. This integer can be adjust automatically when software is added to or deleted from configuration items (CIs).

- id: <http://www.purl.org/ogit/Automation/installCount>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.82 ogit/installedAt**

Defines a point in time when a component/device was actually installed. The values must be combined date and time with time zone designator according to ISO 8601

- id: <http://www.purl.org/ogit/installedAt>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

**1.3.0.83 ogit/Automation/marsNodeFormalRepresentation**

Contains MARS in XML representation defined by MARSSchema2013.

- id: <http://www.purl.org/ogit/Automation/marsNodeFormalRepresentation>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.84 ogit/updateCount**

Contains the count of the records updated.

- id: <http://www.purl.org/ogit/updateCount>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)



**1.3.0.85 ogit/installStatus**

An installation status for an entity. At this level of specification no list of values is specified. However, applications using this attribute are expected to allow only a fixed list of values that seems useful in the application's semantic context.

- id: <http://www.purl.org/ogit/installStatus>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

**1.3.0.86 ogit/city**

Name of a city.

- id: <http://www.purl.org/ogit/city>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Philipp Pelchmann

used

- optional:
  - [ogit/Organization](#)

**1.3.0.87 ogit/Automation/systemClass**

Contains the class of the system.

- id: <http://www.purl.org/ogit/Automation/systemClass>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.88** `ogit/Automation/diskCount`

An integer which shows the number of disks of a component.

- id: <http://www.purl.org/ogit/Automation/diskCount>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.89** `ogit/Automation/automationState`

A value of 'Manual' will mark a node as not eligible for Issue processing

- id: <http://www.purl.org/ogit/Automation/automationState>
- valid-from: Fri Jun 01 00:00:00 UTC 2018
- creator: [fotto@arago.de](mailto:fotto@arago.de)

used

- optional:
  - [ogit/MARS/Application](#)
  - [ogit/MARS/Machine](#)
  - [ogit/MARS/Resource](#)
  - [ogit/MARS/Software](#)

**1.3.0.90** `ogit/ServiceManagement/resolvedInTime`

Information about a ticket being solved in the time excepted.

- id: <http://www.purl.org/ogit/ServiceManagement/resolvedInTime>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Philipp Pelchmann

used

- optional:
  - [ogit/ServiceManagement/SLA](#)

#### 1.3.0.91 `ogit/ServiceManagement/incidentStatus`

Defines the status of an incident record/ticket.

- id: <http://www.purl.org/ogit/ServiceManagement/incidentStatus>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ServiceManagement/Incident](#)

#### 1.3.0.92 `ogit/taskLog`

In cases where the log for a Task is maintained as a single string it will be stored in taskLog. In all other case consider using `ogit/Timeseries`.

- id: <http://www.purl.org/ogit/taskLog>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ServiceManagement/SubTask](#)

#### 1.3.0.93 `ogit/status`

A status for an entity. At this level of specification no list of values is specified. However, applications using this attribute are expected to allow only a fixed list of values that seems usefual in the application's semantic context.

- id: <http://www.purl.org/ogit/status>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Automation/AutomationIssue](#)
  - [ogit/ConfigurationItem](#)
  - [ogit/Contract](#)
  - [ogit/Event](#)
  - [ogit/Organization](#)
  - [ogit/Person](#)
  - [ogit/Role](#)
  - [ogit/Task](#)

**1.3.0.94** ogit/createdAt

Defines a point in time when a ticket/incident/event etc was created or recorded.

- id: <http://www.purl.org/ogit/createdAt>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Attachment](#)
  - [ogit/ConfigurationItem](#)
  - [ogit/ServiceManagement/Order](#)
  - [ogit/ServiceManagement/Ticket](#)

**1.3.0.95** ogit/ServiceManagement/workAround

Defines a work around for a known problem until a permanent solution is defined.

- id: <http://www.purl.org/ogit/ServiceManagement/workAround>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ServiceManagement/Problem](#)

**1.3.0.96** ogit/ServiceManagement/rootCause

Root cause for example of a problem ticket.

- id: <http://www.purl.org/ogit/ServiceManagement/rootCause>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ServiceManagement/Problem](#)

## 1.3.0.97 ogit/model

Model of a device.

- id: <http://www.purl.org/ogit/model>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ConfigurationItem](#)

## 1.3.0.98 ogit/Automation/domain

Contains the domain name.

- id: <http://www.purl.org/ogit/Automation/domain>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

## 1.3.0.99 ogit/Automation/lifecycle

Contains the lifecycle state of a MARSNode. If value is 'decommissioned' this node is ignored by engine, graph and UI.

- id: <http://www.purl.org/ogit/Automation/lifecycle>
- valid-from: Thu May 11 00:00:00 UTC 2017
- creator: Philipp Kählitz

used

- optional:
  - [ogit/Automation/MARSNode](#)
  - [ogit/MARS/Application](#)
  - [ogit/MARS/Machine](#)
  - [ogit/MARS/Resource](#)
  - [ogit/MARS/Software](#)

**1.3.0.100 ogit/lastName**

Last name of a person.

- id: <http://www.purl.org/ogit/lastName>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Person](#)

**1.3.0.101 ogit/Automation/cpuModel**

Contains the model of the cpu.

- id: <http://www.purl.org/ogit/Automation/cpuModel>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.102 ogit/Automation/buildName**

Contains the build name of a component.

- id: <http://www.purl.org/ogit/Automation/buildName>
- valid-from: Fri Jul 24 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.103 ogit/Automation/appInstanceType**

Contains the instance type.

- id: <http://www.purl.org/ogit/Automation/appInstanceType>
- valid-from: Fri Jul 24 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.104 ogit/modificationTime**

Modification time.

- id: <http://www.purl.org/ogit/modificationTime>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Automation/AutomationIssue](#)
  - [ogit/Automation/MARSNode](#)

**1.3.0.105 ogit/ServiceManagement/problemStatus**

defines the status of a problem record

- id: <http://www.purl.org/ogit/ServiceManagement/problemStatus>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ServiceManagement/Problem](#)

**1.3.0.106 ogit/priority**

Priority of a ticket. The actual semantics might depend on the ticket type (Incident, Service Request, ...)

- id: <http://www.purl.org/ogit/priority>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ConfigurationItem](#)
  - [ogit/Event](#)
  - [ogit/ServiceManagement/Order](#)
  - [ogit/ServiceManagement/Ticket](#)

**1.3.0.107 ogit/shortDescription**

Contains a short description.

- id: <http://www.purl.org/ogit/shortDescription>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

**1.3.0.108 ogit/middleName**

Middle name of a person.

- id: <http://www.purl.org/ogit/middleName>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Philipp Pelchmann

used

- optional:
  - [ogit/Person](#)



1.3.0.109 `ogit/resource`

Defines the name of an resource on an instance e.g. disk or database.

- id: <http://www.purl.org/ogit/resource>
- valid-from: Wed Aug 03 00:00:00 UTC 2016
- creator: Philipp Pelchmann

used

- optional:
  - [ogit/Event](#)

1.3.0.110 `ogit/ServiceManagement/targetFinishAt`

Defines a point in time when the work on a change should be finished. This date time is defined by the requester. The values must be combined date and time with time zone designator according to ISO 8601

- id: <http://www.purl.org/ogit/ServiceManagement/targetFinishAt>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ServiceManagement/ChangeRequest](#)
  - [ogit/ServiceManagement/SubTask](#)

1.3.0.111 `ogit/MARS/Software/instanceId`

Allow to define some instance identifier for a Software node. Usually this is used to uniquely identify a cluster member. The value might be a composition of several attributes, e.g. `<data-center-id>:<rack-id>`. Replaces 'Instance' from MARS-Schema

- id: <http://www.purl.org/ogit/MARS/Software/instanceId>
- valid-from: Fri Jun 01 00:00:00 UTC 2018
- creator: [fotto@arago.de](mailto:fotto@arago.de)

used

- optional:
  - [ogit/MARS/Software](#)

**1.3.0.112** `ogit/accessControl`

The access control level of this Node. Value could mean different things to different applications / policies. Initial intent is that policies would treat "public-read" (inspired by Amazon AWS S3 ACLs) to mean anyone would have read-only access to this node.

- id: <http://www.purl.org/ogit/accessControl>
- valid-from: Thu Mar 26 00:00:00 UTC 2015
- creator: Chris Walker

used

- optional:
  - [ogit/Attachment](#)

**1.3.0.113** `ogit/ServiceManagement/ticketId`

ID of the ticket in the source system, e.g. the ID of the ticket in BMC.

- id: <http://www.purl.org/ogit/ServiceManagement/ticketId>
- valid-from: Tue May 26 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ServiceManagement/Ticket](#)

**1.3.0.114** `ogit/justification`

Justification for a ChangeRequest

- id: <http://www.purl.org/ogit/justification>
- valid-from: Wed Jul 01 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ServiceManagement/ChangeRequest](#)

**1.3.0.115 ogit/invoiceNumber**

Contains an invoice number. This number is used as identifier for security purposes.

- id: <http://www.purl.org/ogit/invoiceNumber>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

**1.3.0.116 ogit/response**

Contains the response for a question.

- id: <http://www.purl.org/ogit/response>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Task](#)

**1.3.0.117 ogit/ServiceManagement/externalTicketSource**

If a ticket was imported/duplicated from another system this will contain a string indentifying the source system.

- id: <http://www.purl.org/ogit/ServiceManagement/externalTicketSource>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ServiceManagement/Order](#)

**1.3.0.118** ogit/Automation/diskSpace

An integer which contains the disk space in GB.

- id: <http://www.purl.org/ogit/Automation/diskSpace>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.119** ogit/soxClass

This attribute specifies, if an entity has a Sarbanes Oxley (SOX) classification that applies to it. The out-of-box data is: Critical or Non Critical

- id: <http://www.purl.org/ogit/soxClass>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

**1.3.0.120** ogit/closedAt

Will defined the time when a ticket was closed. The values must be combined date and time with time zone designator according to ISO 8601

- id: <http://www.purl.org/ogit/closedAt>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ServiceManagement/Order](#)
  - [ogit/ServiceManagement/Ticket](#)

**1.3.0.121 ogit/ServiceManagement/taskStatus**

Defines the status of a task.

- id: <http://www.purl.org/ogit/ServiceManagement/taskStatus>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ServiceManagement/SubTask](#)

**1.3.0.122 ogit/ServiceManagement/resolutionCode**

Optional resolution code that may be provided during an incident or problem along with the solution description.

- id: <http://www.purl.org/ogit/ServiceManagement/resolutionCode>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ServiceManagement/ChangeRequest](#)
  - [ogit/ServiceManagement/Incident](#)
  - [ogit/ServiceManagement/Problem](#)
  - [ogit/ServiceManagement/SubTask](#)

**1.3.0.123 ogit/expiresAt**

Defines the date something expires.

- id: <http://www.purl.org/ogit/expiresAt>
- valid-from: Wed Aug 03 00:00:00 UTC 2016
- creator: Philipp Pelchmann

used

- optional:
  - [ogit/Event](#)

**1.3.0.124 ogit/streetAddress**

The street address. For example, Eschersheimer Landstr. 526-532

- id: <http://www.purl.org/ogit/streetAddress>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Organization](#)

**1.3.0.125 ogit/businessCriticality**

The business criticality of a process/service/CI.

- id: <http://www.purl.org/ogit/businessCriticality>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

**1.3.0.126 ogit/leaseContract**

This field specifies the lease contract covering a service.

- id: <http://www.purl.org/ogit/leaseContract>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

**1.3.0.127 ogit/MARS/Application/subClass**

Allows to further classify applications. This can be used to match KnowledgeItems specific to a certain business domain. Replaces 'ApplicationSubClass' from MARS-Schema

- id: <http://www.purl.org/ogit/MARS/Application/subClass>
- valid-from: Fri Jun 01 00:00:00 UTC 2018
- creator: [fotto@arago.de](mailto:fotto@arago.de)

used

- mandatory:
  - [ogit/MARS/Application](#)

**1.3.0.128 ogit/securityClass**

Contains the security class of an entity/device.

- id: <http://www.purl.org/ogit/securityClass>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

**1.3.0.129 ogit/serialNumber**

A string representing a any kind of serial number. see <http://purl.org/goodrelations/v1#serialNumber>

- id: <http://www.purl.org/ogit/serialNumber>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Automation/MARSNode](#)
  - [ogit/MARS/Machine](#)
  - [ogit/MARS/Software](#)
  - [ogit/ServiceManagement/Offering](#)

## 1.3.0.130 ogit/firstName

First name of a person

- id: <http://www.purl.org/ogit/firstName>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Person](#)

## 1.3.0.131 ogit/MARS/Network/defaultGateway

Defines the default gateway. In case of IPv4 dot-decimal notation shall be used. Replaces 'NetworkDefaultGW' from MARS-Schema

- id: <http://www.purl.org/ogit/MARS/Network/defaultGateway>
- valid-from: Fri Jun 01 00:00:00 UTC 2018
- creator: [fotto@arago.de](mailto:fotto@arago.de)

used

- optional:
  - [ogit/MARS/Machine](#)

## 1.3.0.132 ogit/Price/priceAmount

Amount to pay for example for an invoice.

- id: <http://www.purl.org/ogit/Price/priceAmount>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- mandatory:
  - [ogit/Price/Invoice](#)



**1.3.0.133 ogit/assignedGroup**

Assigned Group to a Service Management process.

- id: <http://www.purl.org/ogit/assignedGroup>
- valid-from: Wed Jul 01 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ServiceManagement/ChangeRequest](#)
  - [ogit/ServiceManagement/Incident](#)
  - [ogit/ServiceManagement/SubTask](#)

**1.3.0.134 ogit/macAddress**

The mac address of a component.

- id: <http://www.purl.org/ogit/macAddress>
- valid-from: Wed May 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.135 ogit/Automation/osName**

Contains operating system name.

- id: <http://www.purl.org/ogit/Automation/osName>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Philipp Pelchmann

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.136** ogit/version

Any string representation of version information. no restrictions are imposed on that base attribute

- id: <http://www.purl.org/ogit/version>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ConfigurationItem](#)
  - [ogit/ServiceManagement/Report](#)
  - [ogit/Software/Application](#)

**1.3.0.137** ogit/title

Title of any kind. In the context of a Person this can be a courtesy title, an academic title, or a job title.

- id: <http://www.purl.org/ogit/title>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Person](#)

**1.3.0.138** ogit/ServiceManagement/elapsedTime

Time between start time and now (minus pause duration).

- id: <http://www.purl.org/ogit/ServiceManagement/elapsedTime>
- valid-from: Mon Jun 08 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ServiceManagement/SLA](#)

**1.3.0.139** `ogit/Automation/appServer`

Contains application server.

- id: <http://www.purl.org/ogit/Automation/appServer>
- valid-from: Fri Jul 24 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.140** `ogit/MARS/Machine/ram`

The available system memory in a machine. It starts with a number following by an optional unit character ('M' or 'G'). If unit character is omitted then 'M' shall be assumed. This is . Replaces 'HWRAM' from MARS-Schema

- id: <http://www.purl.org/ogit/MARS/Machine/ram>
- valid-from: Fri Jun 01 00:00:00 UTC 2018
- creator: [fotto@arago.de](mailto:fotto@arago.de)

used

- optional:
  - [ogit/MARS/Machine](#)

**1.3.0.141** `ogit/MARS/Network/port`

A number indicating a network port (0..65535). Usually used define the listening port for a software (server). Replaces 'NetworkPort' from MARS-Schema

- id: <http://www.purl.org/ogit/MARS/Network/port>
- valid-from: Fri Jun 01 00:00:00 UTC 2018
- creator: [fotto@arago.de](mailto:fotto@arago.de)

used

- optional:
  - [ogit/MARS/Software](#)

## 1.3.0.142 ogit/class

Class of a component/device.

- id: <http://www.purl.org/ogit/class>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

## 1.3.0.143 ogit/lengthOfReportingPeriod

Period in which the attribute is reported.

- id: <http://www.purl.org/ogit/lengthOfReportingPeriod>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Parameter](#)

## 1.3.0.144 ogit/Version/patch

patch version according to <https://semver.org/>

- id: <http://www.purl.org/ogit/Version/patch>
- valid-from: Fri May 25 00:00:00 UTC 2018
- creator: [fotto@arago.de](mailto:fotto@arago.de)

used

- optional:
  - [ogit/MARS/Machine](#)
  - [ogit/MARS/Software](#)

**1.3.0.145 ogit/content**

A string holding any type of content: plain string, XML fragments, RDF documents, ...

- id: <http://www.purl.org/ogit/content>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- mandatory:
  - [ogit/Policy](#)
- optional:
  - [ogit/Attachment](#)
  - [ogit/Comment](#)
  - [ogit/ConfigurationItem](#)

**1.3.0.146 ogit/confidentiality**

Contains information about the confidentiality related to a device or an entity.

- id: <http://www.purl.org/ogit/confidentiality>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

**1.3.0.147 ogit/Automation/deployStatus**

String value, represents the status if an automation Knowledge Item is not deployed into an Automation Engine.

- id: <http://www.purl.org/ogit/Automation/deployStatus>
- valid-from: Mon Jan 25 00:00:00 UTC 2016
- creator: Peter Larem

used

- optional:
  - [ogit/Automation/AutomationIssue](#)
  - [ogit/Automation/MARSNode](#)

**1.3.0.148** ogit/MARS/Machine/kernel

Describes the running Operating System kernel. For Linux systems this is usually the output of 'uname -s -v -r'. Replaces 'OSKernel' from MARS-Schema

- id: <http://www.purl.org/ogit/MARS/Machine/kernel>
- valid-from: Fri Jun 01 00:00:00 UTC 2018
- creator: [fotto@arago.de](mailto:fotto@arago.de)

used

- optional:
  - [ogit/MARS/Machine](#)

**1.3.0.149** ogit/lastOccurredAt

Defines the date of last occurrence of an event

- id: <http://www.purl.org/ogit/lastOccurredAt>
- valid-from: Wed Aug 03 00:00:00 UTC 2016
- creator: Philipp Pelchmann

used

- optional:
  - [ogit/Event](#)

**1.3.0.150** ogit/Automation/isDeployed

Boolean value, true if an automation Knowledge Item is deployed into an Automation Engine.

- id: <http://www.purl.org/ogit/Automation/isDeployed>
- valid-from: Mon Jan 25 00:00:00 UTC 2016
- creator: Peter Larem

used

- optional:
  - [ogit/Automation/AutomationIssue](#)
  - [ogit/Automation/MARSNode](#)

**1.3.0.151** [ogit/Automation/processingNode](#)

Defines where an AutomationIssue is currently being processed or was being processed last. Must contain a valid vertex id. Replaces the free attribute '/CurrentNodeID'

- id: <http://www.purl.org/ogit/Automation/processingNode>
- valid-from: Fri Jun 01 00:00:00 UTC 2018
- creator: [fotto@arago.de](mailto:fotto@arago.de)

used

- optional:
  - [ogit/Automation/AutomationIssue](#)

**1.3.0.152** [ogit/Automation/issueFormalRepresentation](#)

Contains an issue in XML representation defined by IssueSchema.

- id: <http://www.purl.org/ogit/Automation/issueFormalRepresentation>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Automation/AutomationIssue](#)

**1.3.0.153** [ogit/MARS/Network/protocol](#)

Can be used to define the network protocol a service (software) is using. Typical values: 'tcp', 'udp'. Replaces 'NetworkProtocol' from MARS-Schema

- id: <http://www.purl.org/ogit/MARS/Network/protocol>
- valid-from: Fri Jun 01 00:00:00 UTC 2018
- creator: [fotto@arago.de](mailto:fotto@arago.de)

used

- optional:
  - [ogit/MARS/Software](#)

**1.3.0.154** `ogit/ServiceManagement/scheduledFinishAt`

Defines a point in time when the work on a change is planned/scheduled to be finished. This date time is usually defined during change planning and/or approval. The values must be combined date and time with time zone designator according to ISO 8601

- id: <http://www.purl.org/ogit/ServiceManagement/scheduledFinishAt>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ServiceManagement/ChangeRequest](#)
  - [ogit/ServiceManagement/SLA](#)
  - [ogit/ServiceManagement/SubTask](#)

**1.3.0.155** `ogit/MARS/Network/ipVersion`

Allows to specify the IP version for defined interfaces. It's a key'ed list with the key to be defined in attribute `ogit/MARS/Network/interfaceName` of the same Machine node. It can be used to indicate what to expectd in the corresponding entries of other network related attributes, e.g 'ogit/MARS/Network/interfacelP'. Replaces 'Network↔InterfaceType' from MARS-Schema

- id: <http://www.purl.org/ogit/MARS/Network/ipVersion>
- valid-from: Fri Jun 01 00:00:00 UTC 2018
- creator: [fotto@arago.de](mailto:fotto@arago.de)

used

- optional:
  - [ogit/MARS/Machine](#)

**1.3.0.156** `ogit/name`

Contains a name.

- id: <http://www.purl.org/ogit/name>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem



used

- mandatory:
  - [ogit/Automation/MARSModelTemplate](#)
  - [ogit/CatalogItem](#)
  - [ogit/Contract](#)
  - [ogit/Event](#)
  - [ogit/Location](#)
  - [ogit/MARS/Application](#)
  - [ogit/MARS/Machine](#)
  - [ogit/MARS/Resource](#)
  - [ogit/MARS/Software](#)
  - [ogit/Organization](#)
  - [ogit/Parameter](#)
  - [ogit/Role](#)
  - [ogit/ServiceManagement/Action](#)
  - [ogit/ServiceManagement/Offering](#)
  - [ogit/Software/Application](#)
- optional:
  - [ogit/Attachment](#)
  - [ogit/Automation/MARSModel](#)
  - [ogit/Automation/MARSNode](#)
  - [ogit/ConfigurationItem](#)
  - [ogit/Price/Invoice](#)
  - [ogit/Region](#)
  - [ogit/ServiceManagement/ApprovalTask](#)
  - [ogit/ServiceManagement/Report](#)
  - [ogit/ServiceManagement/SLA](#)
  - [ogit/ServiceManagement/Service](#)
  - [ogit/ServiceManagement/SubTask](#)
  - [ogit/Software/Connector](#)
  - [ogit/Task](#)
  - [ogit/Timeseries](#)

#### 1.3.0.157 [ogit/Automation/software](#)

A software component.

- id: <http://www.purl.org/ogit/Automation/software>
- valid-from: Fri Jul 24 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

## 1.3.0.158 ogit/Automation/originNode

Defines where an AutomationIssue starts/started its lifecycle. Must contain a valid vertex id. Replaces the free attribute 'NodeID'

- id: <http://www.purl.org/ogit/Automation/originNode>
- valid-from: Fri Jun 01 00:00:00 UTC 2018
- creator: [fotto@arago.de](mailto:fotto@arago.de)

used

- optional:
  - [ogit/Automation/AutomationIssue](#)

## 1.3.0.159 ogit/description

Contains a description.

- id: <http://www.purl.org/ogit/description>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Automation/MARSModel](#)
  - [ogit/Automation/MARSModelTemplate](#)
  - [ogit/CatalogItem](#)
  - [ogit/ConfigurationItem](#)
  - [ogit/Contract](#)
  - [ogit/Event](#)
  - [ogit/Location](#)
  - [ogit/Organization](#)
  - [ogit/Parameter](#)
  - [ogit/Penalty](#)
  - [ogit/Price/Invoice](#)
  - [ogit/Region](#)
  - [ogit/Role](#)
  - [ogit/ServiceManagement/Action](#)
  - [ogit/ServiceManagement/Offering](#)
  - [ogit/ServiceManagement/Order](#)
  - [ogit/ServiceManagement/Service](#)
  - [ogit/ServiceManagement/SubTask](#)
  - [ogit/ServiceManagement/Ticket](#)
  - [ogit/Software/Application](#)
  - [ogit/Task](#)
  - [ogit/Timeseries](#)

**1.3.0.160** `ogit/ServiceManagement/slaStage`

Stage of an SLA.

- id: <http://www.purl.org/ogit/ServiceManagement/slaStage>
- valid-from: Mon Jun 08 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ServiceManagement/SLA](#)

**1.3.0.161** `ogit/finishedAt`

Defines a point in time when the work on a change, task, or similar entity was actually finished. The values must be combined date and time with time zone designator according to ISO 8601

- id: <http://www.purl.org/ogit/finishedAt>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ServiceManagement/ChangeRequest](#)
  - [ogit/ServiceManagement/SubTask](#)

**1.3.0.162** `ogit/Automation/host`

Contains the host name.

- id: <http://www.purl.org/ogit/Automation/host>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.163 ogit/externalId**

The External Id of a component.

- id: <http://www.purl.org/ogit/externalId>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

**1.3.0.164 ogit/impact**

Will contain the impact, for example of a ticket. In this case the actual semantics would depend on the ticket type, which could correspond to an Incident, Service Request, etc.

- id: <http://www.purl.org/ogit/impact>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ConfigurationItem](#)
  - [ogit/Event](#)
  - [ogit/ServiceManagement/Order](#)
  - [ogit/ServiceManagement/Ticket](#)

**1.3.0.165 ogit/contact**

This field displays the device/CI/component owner who is the person assigned to the device/CI/component and uses it on a day-to-day basis. Support contacts are secondary contacts who may have access to a CI for example.

- id: <http://www.purl.org/ogit/contact>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

**1.3.0.166 ogit/Automation/appInfrastructureType**

Contains the application infrastructure type.

- id: <http://www.purl.org/ogit/Automation/appInfrastructureType>
- valid-from: Fri Jul 24 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.167 ogit/Automation/issueType**

Contains the type of the issue.

- id: <http://www.purl.org/ogit/Automation/issueType>
- valid-from: Thu Nov 01 00:00:00 UTC 2018
- creator: [cy@arago.de](mailto:cy@arago.de)

used

- optional:
  - [ogit/Automation/AutomationIssue](#)

**1.3.0.168 ogit/MARS/Software/subClass**

Give each type of Software a unique name, e.g 'OpenLDAP' or 'MSSharePointServer'. This should be the primary matching variable for software specific automation (using KnowledgeItems). Replaces 'SoftwareSubClass' from MARS-Schema

- id: <http://www.purl.org/ogit/MARS/Software/subClass>
- valid-from: Fri Jun 01 00:00:00 UTC 2018
- creator: [fotto@arago.de](mailto:fotto@arago.de)

used

- mandatory:
  - [ogit/MARS/Software](#)

**1.3.0.169** ogit/Version/minor

minor version according to <https://semver.org/>

- id: <http://www.purl.org/ogit/Version/minor>
- valid-from: Fri May 25 00:00:00 UTC 2018
- creator: [fotto@arago.de](mailto:fotto@arago.de)

used

- optional:
  - [ogit/MARS/Machine](#)
  - [ogit/MARS/Software](#)

**1.3.0.170** ogit/orderedAt

Defines a point in time when a component/device was actually ordered. The values must be combined date and time with time zone designator according to ISO 8601

- id: <http://www.purl.org/ogit/orderedAt>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

**1.3.0.171** ogit/faultCount

Contains fault count related to a component

- id: <http://www.purl.org/ogit/faultCount>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

**1.3.0.172 ogit/risk**

Used to store the result of a risk analysis.

- id: <http://www.purl.org/ogit/risk>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ServiceManagement/ChangeRequest](#)

**1.3.0.173 ogit/lastUpdatedBy**

Defines the last person or process who updated an entity.

- id: <http://www.purl.org/ogit/lastUpdatedBy>
- valid-from: Mon Jul 20 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Attachment](#)

**1.3.0.174 ogit/ServiceManagement/fallbackPlan**

Defines instructions of how to revert in case a change fails.

- id: <http://www.purl.org/ogit/ServiceManagement/fallbackPlan>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ServiceManagement/ChangeRequest](#)

**1.3.0.175 ogit/isRoot**

Defines if an event is root.

- id: <http://www.purl.org/ogit/isRoot>
- valid-from: Wed Aug 03 00:00:00 UTC 2016
- creator: Philipp Pelchmann

used

- optional:
  - [ogit/Event](#)

**1.3.0.176 ogit/openedAt**

Time when a ticket or task was created/opened. The values could combine date and time with time zone designator according to ISO 8601 for service management tickets. For most tickets there is no real difference between creation and opened time. In case such a distinction is relevant the "createdAt" attribute can be used.

- id: <http://www.purl.org/ogit/openedAt>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Event](#)
  - [ogit/ServiceManagement/Order](#)
  - [ogit/ServiceManagement/Ticket](#)

**1.3.0.177 ogit/Automation/virtualSystemName**

Contains the name of the virtual system.

- id: <http://www.purl.org/ogit/Automation/virtualSystemName>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)



**1.3.0.178 ogit/expirationDate**

Defines a point in time when something becomes invalid the format is described at <http://purl.org/goodrelations/v1#validThrough>

- id: <http://www.purl.org/ogit/expirationDate>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Contract](#)
  - [ogit/ServiceManagement/Offering](#)

**1.3.0.179 ogit/officePhone**

The phone number in the office.

- id: <http://www.purl.org/ogit/officePhone>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Philipp Pelchmann

used

- optional:
  - [ogit/Person](#)

**1.3.0.180 ogit/phone**

a phone number

- id: <http://www.purl.org/ogit/phone>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Organization](#)

**1.3.0.181 ogit/acknowledgeState**

Defines the state of acknowledgement.

- id: <http://www.purl.org/ogit/acknowledgeState>
- valid-from: Wed Aug 03 00:00:00 UTC 2016
- creator: Philipp Pelchmann

used

- optional:
  - [ogit/Event](#)

**1.3.0.182 ogit/deadline**

Defines a point in time when a deadline is reached.

- id: <http://www.purl.org/ogit/deadline>
- valid-from: Mon Dec 19 00:00:00 UTC 2016
- creator: [stravlos@arago.co](mailto:stravlos@arago.co)

used

- optional:
  - [ogit/Contract](#)

**1.3.0.183 ogit/Automation/osLicense**

License of the Operating System.

- id: <http://www.purl.org/ogit/Automation/osLicense>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Philipp Pelchmann

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.184** ogit/fax

The number of a fax.

- id: <http://www.purl.org/ogit/fax>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Philipp Pelchmann

used

- optional:
  - [ogit/Person](#)

**1.3.0.185** ogit/Automation/databaseServer

Contains information about the database server.

- id: <http://www.purl.org/ogit/Automation/databaseServer>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.186** ogit/Automation/portNumber

Contains a port number.

- id: <http://www.purl.org/ogit/Automation/portNumber>
- valid-from: Fri Jul 24 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.187** ogit/Automation/webServer

Contains an webServer.

- id: <http://www.purl.org/ogit/Automation/webServer>
- valid-from: Fri Jul 24 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.188** ogit/type

Type of an an entity.

- id: <http://www.purl.org/ogit/type>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Attachment](#)
  - [ogit/ConfigurationItem](#)
  - [ogit/Contract](#)
  - [ogit/Event](#)
  - [ogit/ServiceManagement/SubTask](#)
  - [ogit/Task](#)

**1.3.0.189** ogit/Automation/softwareKey

Contains the key of a software.

- id: <http://www.purl.org/ogit/Automation/softwareKey>
- valid-from: Fri Jul 24 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.190** ogit/Automation/installPath

Contains the installation path of a component.

- id: <http://www.purl.org/ogit/Automation/installPath>
- valid-from: Fri Jul 24 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.191** ogit/Automation/licenseName

Contains the license name of a component.

- id: <http://www.purl.org/ogit/Automation/licenseName>
- valid-from: Fri Jul 24 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.192** ogit/Automation/contextPath

Contains the context path of a component.

- id: <http://www.purl.org/ogit/Automation/contextPath>
- valid-from: Fri Jul 24 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.193** ogit/Automation/cpuSpeed

An floating point number which shows the cpu speed in GHZ.

- id: <http://www.purl.org/ogit/Automation/cpuSpeed>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.194** ogit/Automation/processingTimestamp

Contains the timestamp indicating last time an aumation issue was processed.

- id: <http://www.purl.org/ogit/Automation/processingTimestamp>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Automation/AutomationIssue](#)

**1.3.0.195** ogit/otherPhone

The number of an other phone.

- id: <http://www.purl.org/ogit/otherPhone>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Philipp Pelchmann

used

- optional:
  - [ogit/Person](#)

**1.3.0.196** ogit/subCategory

Used to give a subcategory to things.

- id: <http://www.purl.org/ogit/subCategory>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

**1.3.0.197** ogit/MARS/Network/interfacePrefixLength

Specifies the network prefix length (network mask) of all defined interfaces. It's a key'ed list with the key to be defined in attribute ogit/MARS/Network/interfaceName of the same Machine node. The values are always number, e.g. a value of '24' in the context of IPv4 is equivalent to 255.255.255.0 in dot-decimal notation. Replaces 'Network↔InterfacePrefixLength' and 'NetworkInterfaceNetmask' from MARS-Schema

- id: <http://www.purl.org/ogit/MARS/Network/interfacePrefixLength>
- valid-from: Fri Jun 01 00:00:00 UTC 2018
- creator: [fotto@arago.de](mailto:fotto@arago.de)

used

- optional:
  - [ogit/MARS/Machine](#)

**1.3.0.198** ogit/isMutable

True if the value can be changed. E.g. after a service is provisioned.

- id: <http://www.purl.org/ogit/isMutable>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Parameter](#)

**1.3.0.199** `ogit/Automation/servletClass`

Contains the class of the servlet.

- id: <http://www.purl.org/ogit/Automation/servletClass>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.200** `ogit/ServiceManagement/leftTime`

Time remaining until SLA breach.

- id: <http://www.purl.org/ogit/ServiceManagement/leftTime>
- valid-from: Mon Jun 08 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ServiceManagement/SLA](#)

**1.3.0.201** `ogit/sourceTable`

Contains the source table, that stores where the data are coming from.

- id: <http://www.purl.org/ogit/sourceTable>
- valid-from: Thu Aug 20 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Attachment](#)



## 1.3.0.202 ogit/creator

Creator of an entity.

- id: <http://www.purl.org/ogit/creator>
- valid-from: Thu Aug 20 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Attachment](#)
  - [ogit/Comment](#)

## 1.3.0.203 ogit/ServiceManagement/implementationPlan

Used to define detail implementation instructions.

- id: <http://www.purl.org/ogit/ServiceManagement/implementationPlan>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ServiceManagement/ChangeRequest](#)

## 1.3.0.204 ogit/Datacenter/rackUnit

The name of the RackUnit within a datacenter.

- id: <http://www.purl.org/ogit/Datacenter/rackUnit>
- valid-from: Thu Oct 15 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.205** ogit/availability

Contains information about the availability of a service/device.

- id: <http://www.purl.org/ogit/availability>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

**1.3.0.206** ogit/ServiceManagement/allowedForNewBusiness

If the value of this flag is true, the service could be offered in a store to new users for order. If flag is false, the service will only be available to users with already existing instances/entities of a specific service.

- id: <http://www.purl.org/ogit/ServiceManagement/allowedForNewBusiness>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ServiceManagement/Offering](#)

**1.3.0.207** ogit/Automation/firewallStatus

Contains information about the firewall status.

- id: <http://www.purl.org/ogit/Automation/firewallStatus>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.208** `ogit/MARS/Network/interfaceIP`

Specifies the configured IP address of all defined interfaces. It's a key'ed list with the key to be defined in attribute `ogit/MARS/Network/interfaceName` of the same Machine node. In case of IPv4 addresses dot-decimal notation shall be used. Replaces 'NetworkInterfaceIP' from MARS-Schema

- id: <http://www.purl.org/ogit/MARS/Network/interfaceIP>
- valid-from: Fri Jun 01 00:00:00 UTC 2018
- creator: [fotto@arago.de](mailto:fotto@arago.de)

used

- optional:
  - [ogit/MARS/Machine](#)

**1.3.0.209** `ogit/lastScannedAt`

Defines a point in time when a component/device was actually scanned last time. The values must be combined date and time with time zone designator according to ISO 8601

- id: <http://www.purl.org/ogit/lastScannedAt>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

**1.3.0.210** `ogit/capacityAvailable`

If the flag is true, then service can be ordered by new instance. If the flag is false, the service cannot temporarily be ordered due to capacity reasons.

- id: <http://www.purl.org/ogit/capacityAvailable>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ServiceManagement/Offering](#)

**1.3.0.211 ogit/subType**

A subtype of an an entity.

- id: <http://www.purl.org/ogit/subType>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

**1.3.0.212 ogit/ServiceManagement/eventMessage**

Defines the event message/summary/logstring.

- id: <http://www.purl.org/ogit/ServiceManagement/eventMessage>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

**1.3.0.213 ogit/MARS/Application/class**

Used to classify Application nodes. Replaces 'ResourceClass' from MARS-Schema

- id: <http://www.purl.org/ogit/MARS/Application/class>
- valid-from: Fri Jun 01 00:00:00 UTC 2018
- creator: [fotto@arago.de](mailto:fotto@arago.de)

used

- mandatory:
  - [ogit/MARS/Application](#)

**1.3.0.214 ogit/pendingChange**

This field indicates whether or not there are any changes pending against a component/device. When you close or open a change for this component/device, this action sets or clears the flag..

- id: <http://www.purl.org/ogit/pendingChange>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

**1.3.0.215 ogit/Automation/exchangeRate**

Contains the data rate exchanged.

- id: <http://www.purl.org/ogit/Automation/exchangeRate>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.216 ogit/ServiceManagement/sourceStatus**

It can be used to define application specific status values, which are not allowed by a normalized status, e.g. incidentStatus, changeStatus etc.

- id: <http://www.purl.org/ogit/ServiceManagement/sourceStatus>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ServiceManagement/ApprovalTask](#)
  - [ogit/ServiceManagement/ChangeRequest](#)
  - [ogit/ServiceManagement/Incident](#)
  - [ogit/ServiceManagement/Order](#)
  - [ogit/ServiceManagement/SubTask](#)
  - [ogit/ServiceManagement/Ticket](#)

**1.3.0.217 ogit/Automation/patchNumber**

Contains a patch number.

- id: <http://www.purl.org/ogit/Automation/patchNumber>
- valid-from: Fri Jul 24 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.218 ogit/Automation/cpuType**

Contains the cpu type of a device.

- id: <http://www.purl.org/ogit/Automation/cpuType>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.219 ogit/Automation/dataPrivacy**

Data privacy of a component.

- id: <http://www.purl.org/ogit/Automation/dataPrivacy>
- valid-from: Fri Jul 24 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.220 ogit/inventoryNumber**

This field specifies the inventory component number for the a device as defined by the company-defined device inventory number in the model table. The system uses this number to provide data on the Manufacturer, Model, and Version fields if available.

- id: <http://www.purl.org/ogit/inventoryNumber>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

**1.3.0.221 ogit/webPage**

A web page.

- id: <http://www.purl.org/ogit/webPage>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Philipp Pelchmann

used

- optional:
  - [ogit/Organization](#)
  - [ogit/Person](#)

**1.3.0.222 ogit/Automation/objectIdentifier**

Contains a system object identifier.

- id: <http://www.purl.org/ogit/Automation/objectIdentifier>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.223 ogit/lastUpdatedAt**

Defines latest date and time when a ticket or it's comment was updated. The format of this value could be according to ISO 8601.

- id: <http://www.purl.org/ogit/lastUpdatedAt>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Attachment](#)
  - [ogit/ConfigurationItem](#)
  - [ogit/Event](#)
  - [ogit/ServiceManagement/ApprovalTask](#)
  - [ogit/ServiceManagement/Order](#)
  - [ogit/ServiceManagement/SubTask](#)
  - [ogit/ServiceManagement/Ticket](#)

**1.3.0.224** ogit/modelNumber

ModelNumber of a device.

- id: <http://www.purl.org/ogit/modelNumber>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

**1.3.0.225** ogit/Automation/fqdn

Contains a fully qualified domain name.

- id: <http://www.purl.org/ogit/Automation/fqdn>
- valid-from: Tue Jan 15 00:00:00 UTC 2019
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.226** ogit/Automation/osKey

Product key for the Operating System.

- id: <http://www.purl.org/ogit/Automation/osKey>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Philipp Pelchmann

used

- optional:
  - [ogit/Automation/MARSNode](#)



**1.3.0.227** ogit/Automation/brand

Contains the brand of a component/device.

- id: <http://www.purl.org/ogit/Automation/brand>
- valid-from: Tue Jan 15 00:00:00 UTC 2019
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.228** ogit/Automation/licenseType

Contains the license type of a component.

- id: <http://www.purl.org/ogit/Automation/licenseType>
- valid-from: Sun May 24 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.229** ogit/market

Indicates market, for which an entity may be applicable.

- id: <http://www.purl.org/ogit/market>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ServiceManagement/Offering](#)

**1.3.0.230** `ogit/Automation/virtualSystemType`

Contains the type of the virtual system.

- id: <http://www.purl.org/ogit/Automation/virtualSystemType>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.231** `ogit/MARS/Machine/distroName`

The distro name of an Operation System. For Linux you will encounter things like: 'CentOS', 'RedHat', ... . Replaces 'OSName' from MARS-Schema

- id: <http://www.purl.org/ogit/MARS/Machine/distroName>
- valid-from: Fri Jun 01 00:00:00 UTC 2018
- creator: [fotto@arago.de](mailto:fotto@arago.de)

used

- optional:
  - [ogit/MARS/Machine](#)

**1.3.0.232** `ogit/MARS/Network/interfaceName`

This defines the network interface within a system. It's always a list containing all the defined interfaces, e.g. 'lo0 eth0 eth1'. Replaces 'NetworkInterface' from MARS-Schema

- id: <http://www.purl.org/ogit/MARS/Network/interfaceName>
- valid-from: Fri Jun 01 00:00:00 UTC 2018
- creator: [fotto@arago.de](mailto:fotto@arago.de)

used

- optional:
  - [ogit/MARS/Machine](#)

**1.3.0.233** `ogit/Automation/osManufacturer`

Contains the manufacturer of the operating system.

- id: <http://www.purl.org/ogit/Automation/osManufacturer>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.234** `ogit/ServiceManagement/licenseTokenStatus`

The list of valid status values a license token can have

- id: <http://www.purl.org/ogit/ServiceManagement/licenseTokenStatus>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

**1.3.0.235** `ogit/id`

General id.

- id: <http://www.purl.org/ogit/id>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- mandatory:
  - [ogit/ConfigurationItem](#)
  - [ogit/Event](#)
  - [ogit/ServiceManagement/ChangeRequest](#)
  - [ogit/ServiceManagement/Offering](#)
  - [ogit/ServiceManagement/Order](#)
  - [ogit/ServiceManagement/Problem](#)
  - [ogit/ServiceManagement/Service](#)
  - [ogit/ServiceManagement/SubTask](#)
  - [ogit/ServiceManagement/Ticket](#)
- optional:
  - [ogit/Attachment](#)
  - [ogit/Automation/MARSNode](#)
  - [ogit/Comment](#)
  - [ogit/ServiceManagement/Action](#)
  - [ogit/ServiceManagement/ApprovalTask](#)
  - [ogit/ServiceManagement/Incident](#)
  - [ogit/ServiceManagement/Report](#)
  - [ogit/Task](#)

**1.3.0.236** `ogit/MARS/Software/class`

Used to classify Software nodes. Will contain values like: 'DBMS', 'WebServer', 'DataProcessing', and so on. Replaces 'SoftwareClass' from MARS-Schema

- id: <http://www.purl.org/ogit/MARS/Software/class>
- valid-from: Fri Jun 01 00:00:00 UTC 2018
- creator: [fotto@arago.de](mailto:fotto@arago.de)

used

- mandatory:
  - [ogit/MARS/Software](#)

**1.3.0.237** `ogit/occurenceCount`

Defines the number an event occurred.

- id: <http://www.purl.org/ogit/occurenceCount>
- valid-from: Wed Aug 03 00:00:00 UTC 2016
- creator: Philipp Pelchmann

used

- optional:
  - [ogit/Event](#)

**1.3.0.238** `ogit/ServiceManagement/eventNodeId`

Identifies the source of an event, i.e. identifies the monitoring endpoint which caused the event creation. This could be an artificial identifier or some "natural" ID like hostname or IP address.

- id: <http://www.purl.org/ogit/ServiceManagement/eventNodeId>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

**1.3.0.239** ogit/ServiceManagement/solution

Solution description, for example that is usually provided during incident resolving. This field is also use for problem tickets. There is defines the permanent solution desription for a problem.

- id: <http://www.purl.org/ogit/ServiceManagement/solution>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ServiceManagement/ChangeRequest](#)
  - [ogit/ServiceManagement/Incident](#)
  - [ogit/ServiceManagement/Problem](#)

**1.3.0.240** ogit/creationTime

Creation time of an entity.

- id: <http://www.purl.org/ogit/creationTime>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Automation/AutomationIssue](#)
  - [ogit/Automation/MARSNode](#)

**1.3.0.241** ogit/subject

Contains the subject.

- id: <http://www.purl.org/ogit/subject>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Automation/AutomationIssue](#)

**1.3.0.242** ogit/checkedInAt

Defines the time when something was actually checked in. The values can combine date and time with time zone designator according to ISO 8601.

- id: <http://www.purl.org/ogit/checkedInAt>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

**1.3.0.243** ogit/summary

A summary/short description, for example of a ticket.

- id: <http://www.purl.org/ogit/summary>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Event](#)
  - [ogit/ServiceManagement/Order](#)
  - [ogit/ServiceManagement/Ticket](#)

**1.3.0.244** ogit/lastClearedAt

Defines the date an event has been cleared.

- id: <http://www.purl.org/ogit/lastClearedAt>
- valid-from: Wed Aug 03 00:00:00 UTC 2016
- creator: Philipp Pelchmann

used

- optional:
  - [ogit/Event](#)

**1.3.0.245** `ogit/Automation/adminUrl`

Contains an URL (unified resource locator)

- id: <http://www.purl.org/ogit/Automation/adminUrl>
- valid-from: Fri Jul 24 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.246** `ogit/MARS/Resource/class`

Used to classifiy Resource nodes. Will contain values like: 'Backend', 'Database', and so on. Replaces 'Resource↔ Class' from MARS-Schema

- id: <http://www.purl.org/ogit/MARS/Resource/class>
- valid-from: Fri Jun 01 00:00:00 UTC 2018
- creator: [fotto@arago.de](mailto:fotto@arago.de)

used

- mandatory:
  - [ogit/MARS/Resource](#)

**1.3.0.247** `ogit/Automation/marsNodeType`

Contains The Type of the Mars Node. Should be one of Application, Machine, Software, Resource.

- id: <http://www.purl.org/ogit/Automation/marsNodeType>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Automation/MARSNode](#)
  - [ogit/MARS/Application](#)
  - [ogit/MARS/Machine](#)
  - [ogit/MARS/Resource](#)
  - [ogit/MARS/Software](#)

**1.3.0.248** `ogit/Automation/basicConfigId`

Contains the internal identifier of the basic configuration of a component .

- id: <http://www.purl.org/ogit/Automation/basicConfigId>
- valid-from: Wed May 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.249** `ogit/size`

The size, e.g. of a file.

- id: <http://www.purl.org/ogit/size>
- valid-from: Thu Mar 26 00:00:00 UTC 2015
- creator: arago Technologies

used

- optional:
  - [ogit/Attachment](#)

**1.3.0.250** `ogit/serviceContract`

This field specifies the contract covering a service.

- id: <http://www.purl.org/ogit/serviceContract>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)



**1.3.0.251 ogit/Automation/serviceStatus**

Contains the status of a service.

- id: <http://www.purl.org/ogit/Automation/serviceStatus>
- valid-from: Fri Jul 24 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)
  - [ogit/MARS/Application](#)
  - [ogit/MARS/Machine](#)
  - [ogit/MARS/Resource](#)
  - [ogit/MARS/Software](#)

**1.3.0.252 ogit/values**

Represents a list of values. How to actually encode a list of values is left to the semantics of the entities using this attribute.

- id: <http://www.purl.org/ogit/values>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Parameter](#)

**1.3.0.253 ogit/vendor**

Contains the vendor of a device or software/hardware component.

- id: <http://www.purl.org/ogit/vendor>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)
  - [ogit/MARS/Machine](#)
  - [ogit/MARS/Software](#)

**1.3.0.254** ogit/firstOccurredAt

Defines the date of first occurrence of an event

- id: <http://www.purl.org/ogit/firstOccurredAt>
- valid-from: Wed Aug 03 00:00:00 UTC 2016
- creator: Philipp Pelchmann

used

- optional:
  - [ogit/Event](#)

**1.3.0.255** ogit/validFrom

Defines a point in time when something becomes valid.

- id: <http://www.purl.org/ogit/validFrom>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Contract](#)
  - [ogit/ServiceManagement/Offering](#)

**1.3.0.256** ogit/Automation/governingContract

Contains information about the governing contract.

- id: <http://www.purl.org/ogit/Automation/governingContract>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

**1.3.0.257 ogit/Automation/systemType**

Contains the type of the system.

- id: <http://www.purl.org/ogit/Automation/systemType>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.258 ogit/Automation/tcpPort**

The tcp port.

- id: <http://www.purl.org/ogit/Automation/tcpPort>
- valid-from: Fri Jul 24 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/Automation/MARSNode](#)

**1.3.0.259 ogit/MARS/Software/serviceName**

Defines the service name for a software which can buse for administrative operations like start, stop, or status. E.g on RedHat Linux it would be the name of the service unit (without the .service extension). Replaces 'ServiceName' from MARS-Schema

- id: <http://www.purl.org/ogit/MARS/Software/serviceName>
- valid-from: Fri Jun 01 00:00:00 UTC 2018
- creator: [fotto@arago.de](mailto:fotto@arago.de)

used

- optional:
  - [ogit/MARS/Software](#)

**1.3.0.260** `ogit/position`

Indicates user's position. This field contains a string value.

- id: <http://www.purl.org/ogit/position>
- valid-from: Tue Oct 18 00:00:00 UTC 2016
- creator: Arthur Shoba

used

- optional:
  - [ogit/Person](#)

**1.3.0.261** `ogit/reportedAt`

Defines the time when something was actually reported. The values can combine date and time with time zone designator according to ISO 8601. Reported time is used in incident management in the following manner: in most cases the reported time equals the time when the incident is created. In some cases, e.g. the incident is created after the helpdesk has already worked on some request before it was decided to create an incident, the reported time might differ from ticket creation/opening time.

- id: <http://www.purl.org/ogit/reportedAt>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ServiceManagement/ChangeRequest](#)
  - [ogit/ServiceManagement/Incident](#)
  - [ogit/ServiceManagement/Problem](#)

**1.3.0.262** `ogit/ServiceManagement/targetStartAt`

Defines a point in time when the work on a change should start. This date time is defined by the requester. The values must be combined date and time with time zone designator according to ISO 8601

- id: <http://www.purl.org/ogit/ServiceManagement/targetStartAt>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ServiceManagement/ChangeRequest](#)
  - [ogit/ServiceManagement/SubTask](#)

**1.3.0.263** `ogit/ServiceManagement/reportedSource`

Can be used to define how a ticket was communicated. It could define some kind of communication channel ("← ServiceDesk", "Email") or, e.g. for Incident records, it might define that the ticket was produced automatically from an event management system.

- id: <http://www.purl.org/ogit/ServiceManagement/reportedSource>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Event](#)
  - [ogit/ServiceManagement/Incident](#)
  - [ogit/ServiceManagement/Order](#)
  - [ogit/ServiceManagement/Ticket](#)

**1.3.0.264** `ogit/ServiceManagement/task`

A task related to a Service Management process.

- id: <http://www.purl.org/ogit/ServiceManagement/task>
- valid-from: Mon Jul 06 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ServiceManagement/Incident](#)

**1.3.0.265** `ogit/instance`

Defines the name of an instance.

- id: <http://www.purl.org/ogit/instance>
- valid-from: Wed Aug 03 00:00:00 UTC 2016
- creator: Philipp Pelchmann

used

- optional:
  - [ogit/Event](#)
  - [ogit/Timeseries](#)

**1.3.0.266** ogit/isSupported

Indicates whether the service currently is supported. This field contains a boolean value.

- id: <http://www.purl.org/ogit/isSupported>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

**1.3.0.267** ogit/operationalStatus

An operational status for an entity. At this level of specification no list of values is specified. However, applications using this attribute are expected to allow only a fixed list of values that seems useful in the application's semantic context.

- id: <http://www.purl.org/ogit/operationalStatus>
- valid-from: Wed May 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

**1.3.0.268** ogit/validTo

Defines a point in time when something stops being valid.

- id: <http://www.purl.org/ogit/validTo>
- valid-from: Tue Nov 29 00:00:00 UTC 2016
- creator: [stravlos@arago.co](mailto:stravlos@arago.co)

used

- optional:
  - [ogit/Contract](#)

**1.3.0.269** `ogit/ServiceManagement/changeStatus`

Defines the status of a change record within the service management.

- id: <http://www.purl.org/ogit/ServiceManagement/changeStatus>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ServiceManagement/ChangeRequest](#)

**1.3.0.270** `ogit/Automation/projectName`

Contains the project name of a component.

- id: <http://www.purl.org/ogit/Automation/projectName>
- valid-from: Mon Nov 02 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Automation/MARSNode](#)