
Auth

July 10, 2019

1 Auth	1
2 Module Documentation	2
2.1 Entities	2
2.1.0.1 ogit/Auth/Software	2
2.1.0.2 ogit/Auth/Configuration	3
2.1.0.3 ogit/TermsAndConditions	3
2.1.0.4 ogit/Auth/Application	4
2.1.0.5 ogit/Auth/AccountProfile	5
2.1.0.6 ogit/Auth/Team	5
2.1.0.7 ogit/Auth/DataSet	6
2.1.0.8 ogit/Schedule/Attendee	7
2.1.0.9 ogit/Contract	7
2.1.0.10 ogit/Person	8
2.1.0.11 ogit/Auth/OrgDomain	9
2.1.0.12 ogit/Subscription	9
2.1.0.13 ogit/Auth/Machine	10
2.1.0.14 ogit/Survey/Iteration	11
2.1.0.15 ogit/Survey/Reply	11
2.1.0.16 ogit/Attachment	12
2.1.0.17 ogit/Auth/DataScope	13
2.1.0.18 ogit/Auth/Account	13
2.1.0.19 ogit/Schedule/Calendar	14
2.1.0.20 ogit/HR/Recruiting/Recruiter	15
2.1.0.21 ogit/Auth/Resource	15
2.1.0.22 ogit/Auth/RoleAssignment	16
2.1.0.23 ogit/Project/Milestone	17
2.1.0.24 ogit/Rating	17
2.1.0.25 ogit/Auth/Role	18
2.1.0.26 ogit/Notification	18
2.1.0.27 ogit/UserMeta/Filter	19
2.1.0.28 ogit/Data/Log	20
2.1.0.29 ogit/Network/NetworkInterface	20
2.1.0.30 ogit/Auth/ApplicationReview	21
2.1.0.31 ogit/Auth/Organization	21
2.1.0.32 ogit/Event	22
2.1.0.33 ogit/Automation/Configuration	23
2.1.0.34 ogit/SalesDistribution/Customer	24
2.1.0.35 ogit/Project/Project	24
2.1.0.36 ogit/Timeseries	25
2.2 Verbs	26
2.2.0.1 ogit/contains	26

2.2.0.2 ogit/manages	26
2.2.0.3 ogit/defines	26
2.2.0.4 ogit/Auth/belongs	27
2.2.0.5 ogit/concludes	27
2.2.0.6 ogit/supports	27
2.2.0.7 ogit/supervises	28
2.2.0.8 ogit/generates	28
2.2.0.9 ogit/consumes	29
2.2.0.10 ogit/includes	29
2.2.0.11 ogit/Auth/assumes	29
2.2.0.12 ogit/accepts	30
2.2.0.13 ogit/creates	30
2.2.0.14 ogit/Auth/consents	30
2.2.0.15 ogit/Auth/assigns	30
2.2.0.16 ogit/rates	31
2.2.0.17 ogit/alerts	31
2.2.0.18 ogit/versions	31
2.2.0.19 ogit/reviews	32
2.2.0.20 ogit/provides	32
2.2.0.21 ogit/produces	32
2.2.0.22 ogit/dependsOn	33
2.2.0.23 ogit/belongs	33
2.2.0.24 ogit/uses	33
2.2.0.25 ogit/Auth/isMemberOf	34
2.2.0.26 ogit/Auth/uses	34
2.2.0.27 ogit/repliedWith	34
2.2.0.28 ogit/has	34
2.3 Attributes	35
2.3.0.1 ogit/MARS/Network/fqdn	35
2.3.0.2 ogit/MARS/Software/installPath	35
2.3.0.3 ogit/MARS/Network/interfaceMAC	35
2.3.0.4 ogit/operation	36
2.3.0.5 ogit/Data/timeToLive	36
2.3.0.6 ogit/certainty	36
2.3.0.7 ogit/category	37
2.3.0.8 ogit/onAttribute	37
2.3.0.9 ogit/comment	37
2.3.0.10 ogit/endOfWarranty	38
2.3.0.11 ogit/Auth/allowedTypes	38
2.3.0.12 ogit/MARS/Network/bindAddress	38
2.3.0.13 ogit/Auth/Application/urls	39
2.3.0.14 ogit/MARS/Machine/class	39

2.3.0.15 ogit/MARS/Machine/cpuArch	39
2.3.0.16 ogit/email	40
2.3.0.17 ogit/MARS/Software/logPath	40
2.3.0.18 ogit/alternativeName	40
2.3.0.19 ogit/Version/major	41
2.3.0.20 ogit/onVertex	41
2.3.0.21 ogit/question	41
2.3.0.22 ogit/maintenanceState	42
2.3.0.23 ogit/notification	42
2.3.0.24 ogit/sourceId	42
2.3.0.25 ogit/url	43
2.3.0.26 ogit/Auth/edgeRule	43
2.3.0.27 ogit/Schedule/isOrganizer	43
2.3.0.28 ogit/mobilePhone	44
2.3.0.29 ogit/severity	44
2.3.0.30 ogit/startedAt	44
2.3.0.31 ogit/value	45
2.3.0.32 ogit/unit	45
2.3.0.33 ogit/Automation/automationState	45
2.3.0.34 ogit/status	46
2.3.0.35 ogit/createdAt	46
2.3.0.36 ogit/Automation/lifecycle	47
2.3.0.37 ogit/lastName	47
2.3.0.38 ogit/priority	47
2.3.0.39 ogit/middleName	48
2.3.0.40 ogit/resource	48
2.3.0.41 ogit/MARS/Software/instanceId	48
2.3.0.42 ogit/accessControl	49
2.3.0.43 ogit/Auth/vertexRule	49
2.3.0.44 ogit/Auth/_iam-domain	49
2.3.0.45 ogit/expiresAt	50
2.3.0.46 ogit/plannedFinishDate	50
2.3.0.47 ogit/Auth/Account/statusReason	50
2.3.0.48 ogit/serialNumber	51
2.3.0.49 ogit/firstName	51
2.3.0.50 ogit/MARS/Network/defaultGateway	51
2.3.0.51 ogit/title	52
2.3.0.52 ogit/MARS/Machine/ram	52
2.3.0.53 ogit/MARS/Network/port	52
2.3.0.54 ogit/Version/patch	53
2.3.0.55 ogit/content	53
2.3.0.56 ogit/MARS/Machine/kernel	53

2.3.0.57 ogit/lastOccurredAt	54
2.3.0.58 ogit/SalesDistribution/customerId	54
2.3.0.59 ogit/isInternal	54
2.3.0.60 ogit/MARS/Network/protocol	55
2.3.0.61 ogit/Auth/Application/parent	55
2.3.0.62 ogit/Auth/Account/displayName	55
2.3.0.63 ogit/MARS/Network/ipVersion	56
2.3.0.64 ogit/Auth/Account/type	56
2.3.0.65 ogit/name	56
2.3.0.66 ogit/description	57
2.3.0.67 ogit/placement	58
2.3.0.68 ogit/condition	58
2.3.0.69 ogit/Auth/Account/acceptedProjectTerms	58
2.3.0.70 ogit/finishedAt	59
2.3.0.71 ogit/Auth/Account/acceptedTerms	59
2.3.0.72 ogit/impact	59
2.3.0.73 ogit/plannedStartDate	60
2.3.0.74 ogit/MARS/Software/subClass	60
2.3.0.75 ogit/Version/minor	60
2.3.0.76 ogit/Auth/Account/acceptedEmails	61
2.3.0.77 ogit/lastUpdatedBy	61
2.3.0.78 ogit/isRoot	61
2.3.0.79 ogit/openedAt	62
2.3.0.80 ogit/expirationDate	62
2.3.0.81 ogit/officePhone	62
2.3.0.82 ogit/acknowledgeState	63
2.3.0.83 ogit/deadline	63
2.3.0.84 ogit/fax	63
2.3.0.85 ogit/type	64
2.3.0.86 ogit/Auth/Account/allowCookies	64
2.3.0.87 ogit/otherPhone	64
2.3.0.88 ogit/Auth/Application/type	65
2.3.0.89 ogit/MARS/Network/interfacePrefixLength	65
2.3.0.90 ogit/sourceTable	65
2.3.0.91 ogit/creator	66
2.3.0.92 ogit/MARS/Network/interfaceIP	66
2.3.0.93 ogit/subType	66
2.3.0.94 ogit/message	67
2.3.0.95 ogit/webPage	67
2.3.0.96 ogit/lastUpdatedAt	67
2.3.0.97 ogit/MARS/Machine/distroName	68
2.3.0.98 ogit/MARS/Network/interfaceName	68

2.3.0.99 ogit/id	68
2.3.0.100 ogit/Auth/Account/acceptedPrivacy	69
2.3.0.101 ogit/MARS/Software/class	69
2.3.0.102 ogit/occurenceCount	69
2.3.0.103 ogit/summary	70
2.3.0.104 ogit/lastClearedAt	70
2.3.0.105 ogit/MARS/Resource/class	70
2.3.0.106 ogit/Automation/marsNodeType	71
2.3.0.107 ogit/Schedule/attendanceStatus	71
2.3.0.108 ogit/size	71
2.3.0.109 ogit/Automation/serviceStatus	72
2.3.0.110 ogit/vendor	72
2.3.0.111 ogit/firstOccurredAt	72
2.3.0.112 ogit/validFrom	73
2.3.0.113 ogit/MARS/Software/serviceName	73
2.3.0.114 ogit/position	73
2.3.0.115 ogit/ServiceManagement/reportedSource	74
2.3.0.116 ogit/instance	74
2.3.0.117 ogit/Auth/restricted	74
2.3.0.118 ogit/validTo	75
2.3.0.119 ogit/Auth/Application/status	75

Chapter 1

Auth

Overview

This is a graph system NTO governing authentication and authorization.

Chapter 2

Module Documentation

2.1 Entities

2.1.0.1 ogit/Auth/Software

Vertices of this type are the 'S'-nodes in the MARS model. 'S' stands for 'Software' and those nodes form the second lowest layer in the A-R-S-M layer model. It's up to the user whether it will model a specific instance of a software (linked to just one 'Machine' node) or several identical instances (then the 'Software' node will be linked to several 'Machine' nodes)

- id: <http://www.purl.org/ogit/Auth/Software>
- valid-from: Fri Jun 01 00:00:00 UTC 2018
- creator: FCO
- scope: NTO
- parent: ogit/Node

attributes

- mandatory:
 - [ogit/MARS/Software/class](#)
 - [ogit/MARS/Software/subClass](#)
 - [ogit/name](#)
- optional:
 - [ogit/Automation/automationState](#)
 - [ogit/Automation/lifecycle](#)
 - [ogit/Automation/marsNodeType](#)
 - [ogit/Automation/serviceStatus](#)
 - [ogit/MARS/Network/bindAddress](#)
 - [ogit/MARS/Network/port](#)
 - [ogit/MARS/Network/protocol](#)
 - [ogit/MARS/Software/installPath](#)

- [ogit/MARS/Software/installPath](#)
- [ogit/MARS/Software/instanceId](#)
- [ogit/MARS/Software/logPath](#)
- [ogit/MARS/Software/serviceName](#)
- [ogit/Version/major](#)
- [ogit/Version/minor](#)
- [ogit/Version/patch](#)
- [ogit/endOfWarranty](#)
- [ogit/serialNumber](#)
- [ogit/url](#)
- [ogit/vendor](#)

incoming edges

- [ogit/dependsOn](#) <= [ogit/Auth/Resource](#)

outgoing edges

- [ogit/dependsOn](#) => [ogit/Auth/Machine](#)
- [ogit/generates](#) => [ogit/Data/Log](#)
- [ogit/generates](#) => [ogit/Timeseries](#)

2.1.0.2 [ogit/Auth/Configuration](#)

An [ogit/Auth/Configuration](#) reflects individual configuration for an organization registered in hiro knowledge core

- id: <http://www.purl.org/ogit/Auth/Configuration>
- valid-from: Mon Jan 01 00:00:00 UTC 2018
- creator: arago GmbH
- scope: NTO
- parent: [ogit/Node](#)

outgoing edges

- [ogit/Auth/belongs](#) => [ogit/Auth/Organization](#)

2.1.0.3 [ogit/TermsAndConditions](#)

Terms and conditions contains terms of use to be accepted by users

- id: <http://www.purl.org/ogit/TermsAndConditions>
- valid-from: Wed Apr 18 00:00:00 UTC 2018
- creator: Aman Kubanychbek
- scope: SGO
- parent: [ogit/Node](#)

attributes

- mandatory:
 - [ogit/content](#)
 - [ogit/name](#)
- optional:
 - [ogit/description](#)

incoming edges

- [ogit/accepts](#) <= [ogit/Auth/Account](#)

2.1.0.4 ogit/Auth/Application

An Application is used for authorization.

- id: <http://www.purl.org/ogit/Auth/Application>
- valid-from: Mon Jan 01 00:00:00 UTC 2018
- creator: arago GmbH
- scope: NTO
- parent: [ogit/Node](#)

attributes

- mandatory:
 - [ogit/Auth/edgeRule](#)
 - [ogit/Auth/vertexRule](#)
 - [ogit/description](#)
 - [ogit/name](#)
- optional:
 - [ogit/Auth/Application/parent](#)
 - [ogit/Auth/Application/status](#)
 - [ogit/Auth/Application/type](#)
 - [ogit/Auth/Application/urls](#)
 - [ogit/Auth/allowedTypes](#)

incoming edges

- [ogit/Auth/consents](#) <= [ogit/Auth/Account](#)
- [ogit/Auth/uses](#) <= [ogit/Auth/Account](#)
- [ogit/belongs](#) <= [ogit/SalesDistribution/Customer](#)
- [ogit/rates](#) <= [ogit/Rating](#)
- [ogit/reviews](#) <= [ogit/Auth/ApplicationReview](#)
- [ogit/versions](#) <= [ogit/Auth/Application](#)

outgoing edges

- [ogit/includes](#) => [ogit/Notification](#)
- [ogit/versions](#) => [ogit/Auth/Application](#)

2.1.0.5 [ogit/Auth/AccountProfile](#)

A profile associated with an account.

- id: <http://www.purl.org/ogit/Auth/AccountProfile>
- valid-from: Mon Jan 01 00:00:00 UTC 2018
- creator: arago GmbH
- scope: NTO
- parent: [ogit/Node](#)

attributes

- optional:
 - [ogit/Auth/Account/acceptedEmails](#)
 - [ogit/Auth/Account/displayName](#)
 - [ogit/firstName](#)
 - [ogit/lastName](#)

incoming edges

- [ogit/belongs](#) <= [ogit/Attachment](#)

outgoing edges

- [ogit/Auth/belongs](#) => [ogit/Auth/Account](#)

2.1.0.6 [ogit/Auth/Team](#)

A team is used to reflect the organizational structure of an [ogit/Auth/Organization](#)

- id: <http://www.purl.org/ogit/Auth/Team>
- valid-from: Mon Jan 01 00:00:00 UTC 2018
- creator: arago GmbH
- scope: NTO
- parent: [ogit/Node](#)

attributes

- mandatory:
 - [ogit/name](#)
- optional:
 - [ogit/description](#)

incoming edges

- [ogit/Auth/assigns](#) <= [ogit/Auth/RoleAssignment](#)
- [ogit/Auth/belongs](#) <= [ogit/Auth/Team](#)
- [ogit/Auth/isMemberOf](#) <= [ogit/Auth/Account](#)

outgoing edges

- [ogit/Auth/belongs](#) => [ogit/Auth/Team](#)
- [ogit/Auth/belongs](#) => [ogit/Auth/Organization](#)

2.1.0.7 ogit/Auth/DataSet

An ogit/Auth/DataSet defines set of data for authorization purposes

- id: <http://www.purl.org/ogit/Auth/DataSet>
- valid-from: Mon Jan 01 00:00:00 UTC 2018
- creator: arago GmbH
- scope: NTO
- parent: ogit/Node

attributes

- mandatory:
 - [ogit/Auth/edgeRule](#)
 - [ogit/Auth/vertexRule](#)
 - [ogit/name](#)
- optional:
 - [ogit/Auth/restricted](#)
 - [ogit/description](#)

incoming edges

- [ogit/Auth/assigns](#) <= [ogit/Auth/RoleAssignment](#)

2.1.0.8 ogit/Schedule/Attendee

An attendee of a calendar event.

- id: <http://www.purl.org/ogit/Schedule/Attendee>
- valid-from: Tue Jul 02 00:00:00 UTC 2019
- creator: Marek Meyer
- scope: NTO
- parent: ogit/Node

attributes

- mandatory:
 - [ogit/name](#)
- optional:
 - [ogit/Schedule/attendanceStatus](#)
 - [ogit/Schedule/isOrganizer](#)
 - [ogit/email](#)

outgoing edges

- [ogit/has](#) => [ogit/Auth/Account](#)

2.1.0.9 ogit/Contract

General definition of a contract. Usually used for IT service related contracts but at this level of detail it is not restricted to those.

- id: <http://www.purl.org/ogit/Contract>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: SGO
- parent: ogit/Node

attributes

- mandatory:
 - [ogit/name](#)
- optional:
 - [ogit/deadline](#)
 - [ogit/description](#)
 - [ogit/expirationDate](#)
 - [ogit/status](#)
 - [ogit/type](#)
 - [ogit/validFrom](#)
 - [ogit/validTo](#)

incoming edges

- [ogit/concludes](#) <= [ogit/Auth/Organization](#)
- [ogit/supervises](#) <= [ogit/Auth/Account](#)

2.1.0.10 [ogit/Person](#)

A Person represents a human identity.

- id: <http://www.purl.org/ogit/Person>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: SGO
- parent: [ogit/Node](#)

attributes

- optional:
 - [ogit/alternativeName](#)
 - [ogit/email](#)
 - [ogit/fax](#)
 - [ogit/firstName](#)
 - [ogit/lastName](#)
 - [ogit/middleName](#)
 - [ogit/mobilePhone](#)
 - [ogit/notification](#)
 - [ogit/officePhone](#)
 - [ogit/otherPhone](#)
 - [ogit/position](#)
 - [ogit/sourceId](#)
 - [ogit/status](#)
 - [ogit/title](#)
 - [ogit/webPage](#)

incoming edges

- [ogit/belongs](#) <= [ogit/Auth/Account](#)

2.1.0.11 ogit/Auth/OrgDomain

Allows Customer to have multiple valid email domains

- id: <http://www.purl.org/ogit/Auth/OrgDomain>
- valid-from: Mon Jan 01 00:00:00 UTC 2018
- creator: arago GmbH
- scope: NTO
- parent: ogit/Node

attributes

- mandatory:
 - [ogit/name](#)

outgoing edges

- [ogit/Auth/belongs](#) => [ogit/Auth/Organization](#)

2.1.0.12 ogit/Subscription

A Subscription to an Event.

- id: <http://www.purl.org/ogit/Subscription>
- valid-from: Thu Mar 22 00:00:00 UTC 2018
- creator: qikram@arago.de
- scope: SGO
- parent: ogit/Node

attributes

- optional:
 - [ogit/name](#)
 - [ogit/sourceId](#)
 - [ogit/status](#)
 - [ogit/type](#)

incoming edges

- [ogit/manages](#) <= [ogit/Auth/Account](#)

2.1.0.13 ogit/Auth/Machine

Vertices of this type are the 'M'-nodes in the MARS model. 'M' stands for 'Machine' and those nodes form the bottom layer in the A-R-S-M layer model. But to be precise a 'Machine' node models any operation system instance (regardless whether running on bare metal or in some virtualized environment)

- id: <http://www.purl.org/ogit/Auth/Machine>
- valid-from: Fri Jun 01 00:00:00 UTC 2018
- creator: FCO
- scope: NTO
- parent: ogit/Node

attributes

- mandatory:
 - [ogit/MARS/Machine/class](#)
 - [ogit/name](#)
- optional:
 - [ogit/Automation/automationState](#)
 - [ogit/Automation/lifecycle](#)
 - [ogit/Automation/marsNodeType](#)
 - [ogit/Automation/serviceStatus](#)
 - [ogit/MARS/Machine/cpuArch](#)
 - [ogit/MARS/Machine/distroName](#)
 - [ogit/MARS/Machine/kernel](#)
 - [ogit/MARS/Machine/ram](#)
 - [ogit/MARS/Network/defaultGateway](#)
 - [ogit/MARS/Network/fqdn](#)
 - [ogit/MARS/Network/interfaceIP](#)
 - [ogit/MARS/Network/interfaceMAC](#)
 - [ogit/MARS/Network/interfaceName](#)
 - [ogit/MARS/Network/interfacePrefixLength](#)
 - [ogit/MARS/Network/ipVersion](#)
 - [ogit/Version/major](#)
 - [ogit/Version/minor](#)
 - [ogit/Version/patch](#)
 - [ogit/endOfWarranty](#)
 - [ogit/serialNumber](#)
 - [ogit/vendor](#)

incoming edges

- [ogit/dependsOn](#) <= [ogit/Auth/Software](#)

outgoing edges

- [ogit/contains](#) => [ogit/Network/NetworkInterface](#)
- [ogit/generates](#) => [ogit/Data/Log](#)
- [ogit/generates](#) => [ogit/Timeseries](#)

2.1.0.14 ogit/Survey/Iteration**Iteration of the same survey**

- id: <http://www.purl.org/ogit/Survey/Iteration>
- valid-from: Mon Aug 08 00:00:00 UTC 2016
- creator: Alexander Ryabtsev
- scope: NTO
- parent: ogit/Node

attributes

- optional:
 - [ogit/startedAt](#)
 - [ogit/status](#)

incoming edges

- [ogit/consumes](#) <= [ogit/Auth/Organization](#)
- [ogit/produces](#) <= [ogit/Auth/Organization](#)
- [ogit/supports](#) <= [ogit/Auth/Organization](#)

2.1.0.15 ogit/Survey/Reply**User's reply on a survey**

- id: <http://www.purl.org/ogit/Survey/Reply>
- valid-from: Mon Aug 08 00:00:00 UTC 2016
- creator: Alexander Ryabtsev
- scope: NTO
- parent: ogit/Node

attributes

- optional:
 - [ogit/comment](#)
 - [ogit/question](#)

incoming edges

- [ogit/repliedWith](#) <= [ogit/Auth/Account](#)

2.1.0.16 ogit/Attachment

This entity defines a file attachment that an IT service, issue, task or a ticket might have. The attachment itself is not saved in GraphIT, instead it contains an external url link for it.

- id: <http://www.purl.org/ogit/Attachment>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: SGO
- parent: ogit/Node

attributes

- optional:
 - [ogit/accessControl](#)
 - [ogit/content](#)
 - [ogit/createdAt](#)
 - [ogit/creator](#)
 - [ogit/id](#)
 - [ogit/lastUpdatedAt](#)
 - [ogit/lastUpdatedBy](#)
 - [ogit/name](#)
 - [ogit/size](#)
 - [ogit/sourceTable](#)
 - [ogit/type](#)
 - [ogit/url](#)

outgoing edges

- [ogit/belongs](#) => [ogit/Auth/AccountProfile](#)

2.1.0.17 ogit/Auth/DataScope

An ogit/Auth/DataScope is used to separate data between different engine instances

- id: <http://www.purl.org/ogit/Auth/DataScope>
- valid-from: Mon Jan 01 00:00:00 UTC 2018
- creator: arago GmbH
- scope: NTO
- parent: ogit/Node

attributes

- mandatory:
 - [ogit/name](#)
- optional:
 - [ogit/description](#)

outgoing edges

- [ogit/Auth/belongs](#) => [ogit/Auth/Organization](#)

2.1.0.18 ogit/Auth/Account

An account is used for authentication and authorization.

- id: <http://www.purl.org/ogit/Auth/Account>
- valid-from: Mon Jan 01 00:00:00 UTC 2018
- creator: arago GmbH
- scope: NTO
- parent: ogit/Node

attributes

- mandatory:
 - [ogit/Auth/Account/type](#)
 - [ogit/name](#)
 - [ogit/status](#)
- optional:
 - [ogit/Auth/Account/acceptedPrivacy](#)
 - [ogit/Auth/Account/acceptedProjectTerms](#)
 - [ogit/Auth/Account/acceptedTerms](#)
 - [ogit/Auth/Account/allowCookies](#)
 - [ogit/Auth/Account/statusReason](#)
 - [ogit/email](#)

incoming edges

- `ogit/Auth/belongs` <= `ogit/Auth/AccountProfile`
- `ogit/alerts` <= `ogit/Event`
- `ogit/belongs` <= `ogit/Schedule/Calendar`
- `ogit/has` <= `ogit/HR/Recruiting/Recruiter`
- `ogit/has` <= `ogit/Schedule/Attendee`

outgoing edges

- `ogit/Auth/assumes` => `ogit/Auth/Role`
- `ogit/Auth/consents` => `ogit/Auth/Application`
- `ogit/Auth/isMemberOf` => `ogit/Auth/Organization`
- `ogit/Auth/isMemberOf` => `ogit/Auth/Team`
- `ogit/Auth/uses` => `ogit/Auth/Application`
- `ogit/accepts` => `ogit/TermsAndConditions`
- `ogit/belongs` => `ogit/Person`
- `ogit/consumes` => `ogit/Project/Milestone`
- `ogit/consumes` => `ogit/Project/Project`
- `ogit/creates` => `ogit/Auth/ApplicationReview`
- `ogit/defines` => `ogit/UserMeta/Filter`
- `ogit/manages` => `ogit/Subscription`
- `ogit/produces` => `ogit/Project/Milestone`
- `ogit/produces` => `ogit/Project/Project`
- `ogit/provides` => `ogit/Rating`
- `ogit/repliedWith` => `ogit/Survey/Reply`
- `ogit/supervises` => `ogit/Project/Project`
- `ogit/supervises` => `ogit/Contract`
- `ogit/supports` => `ogit/Project/Milestone`
- `ogit/supports` => `ogit/Project/Project`

2.1.0.19 `ogit/Schedule/Calendar`

A calendar containing events.

- id: <http://www.purl.org/ogit/Schedule/Calendar>
- valid-from: Tue Jul 02 00:00:00 UTC 2019
- creator: Marek Meyer
- scope: NTO
- parent: `ogit/Node`

attributes

- optional:
 - [ogit/description](#)
 - [ogit/subType](#)
 - [ogit/title](#)

outgoing edges

- [ogit/belongs](#) => [ogit/Auth/Account](#)

2.1.0.20 [ogit/HR/Recruiting/Recruiter](#)

One who recruits

- id: <http://www.purl.org/ogit/HR/Recruiting/Recruiter>
- valid-from: Thu Mar 21 00:00:00 UTC 2019
- creator: Florian Fluegel
- scope: NTO
- parent: [ogit/Node](#)

outgoing edges

- [ogit/has](#) => [ogit/Auth/Account](#)

2.1.0.21 [ogit/Auth/Resource](#)

Vertices of this type are the 'R'-nodes in the MARS model. 'R' stands for 'Resource' and those nodes form the second highest layer in the A-R-S-M layer model. A 'Resource' node groups 'Software' nodes. It's up to the user whether this grouping is used to group software instance of the same software (e.g. all instances of an Oracle RAC) or software instance of different softwares (functional grouping, e.g. 'persistence')

- id: <http://www.purl.org/ogit/Auth/Resource>
- valid-from: Fri Jun 01 00:00:00 UTC 2018
- creator: FCO
- scope: NTO
- parent: [ogit/Node](#)

attributes

- mandatory:
 - [ogit/MARS/Resource/class](#)
 - [ogit/name](#)
- optional:
 - [ogit/Automation/automationState](#)
 - [ogit/Automation/lifecycle](#)
 - [ogit/Automation/marsNodeType](#)
 - [ogit/Automation/serviceStatus](#)
 - [ogit/url](#)

outgoing edges

- [ogit/dependsOn](#) => [ogit/Auth/Software](#)
- [ogit/generates](#) => [ogit/Data/Log](#)
- [ogit/generates](#) => [ogit/Timeseries](#)
- [ogit/uses](#) => [ogit/Automation/Configuration](#)

2.1.0.22 [ogit/Auth/RoleAssignment](#)

An [ogit/Auth/RoleAssignment](#) links team, role, and dataset to grant permissions

- id: <http://www.purl.org/ogit/Auth/RoleAssignment>
- valid-from: Mon Jan 01 00:00:00 UTC 2018
- creator: arago GmbH
- scope: NTO
- parent: [ogit/Node](#)

outgoing edges

- [ogit/Auth/assigns](#) => [ogit/Auth/Role](#)
- [ogit/Auth/assigns](#) => [ogit/Auth/Team](#)
- [ogit/Auth/assigns](#) => [ogit/Auth/DataSet](#)
- [ogit/Auth/belongs](#) => [ogit/Auth/Organization](#)

2.1.0.23 ogit/Project/Milestone

An identity that represents an important event, achievement, ...

- id: <http://www.purl.org/ogit/Project/Milestone>
- valid-from: Mon Aug 08 00:00:00 UTC 2016
- creator: Arthur Shoba
- scope: NTO
- parent: ogit/Node

attributes

- optional:
 - [ogit/category](#)
 - [ogit/finishedAt](#)
 - [ogit/plannedFinishDate](#)
 - [ogit/plannedStartDate](#)
 - [ogit/startedAt](#)
 - [ogit/status](#)
 - [ogit/title](#)

incoming edges

- [ogit/consumes](#) <= [ogit/Auth/Account](#)
- [ogit/produces](#) <= [ogit/Auth/Account](#)
- [ogit/supports](#) <= [ogit/Auth/Account](#)

2.1.0.24 ogit/Rating

Rating is used to rank nodes based on an arbitrary integer value

- id: <http://www.purl.org/ogit/Rating>
- valid-from: Wed Aug 01 00:00:00 UTC 2018
- creator: qikram@arago.de
- scope: SGO
- parent: ogit/Node

attributes

- mandatory:
 - [ogit/value](#)
- optional:
 - [ogit/comment](#)

incoming edges

- [ogit/provides](#) <= [ogit/Auth/Account](#)

outgoing edges

- [ogit/rates](#) => [ogit/Auth/Application](#)

2.1.0.25 [ogit/Auth/Role](#)

An Role is used for authorization.

- id: <http://www.purl.org/ogit/Auth/Role>
- valid-from: Mon Jan 01 00:00:00 UTC 2018
- creator: arago GmbH
- scope: NTO
- parent: [ogit/Node](#)

attributes

- mandatory:
 - [ogit/Auth/edgeRule](#)
 - [ogit/Auth/vertexRule](#)
 - [ogit/name](#)
- optional:
 - [ogit/description](#)

incoming edges

- [ogit/Auth/assigns](#) <= [ogit/Auth/RoleAssignment](#)
- [ogit/Auth/assumes](#) <= [ogit/Auth/Account](#)

2.1.0.26 [ogit/Notification](#)

A notification event

- id: <http://www.purl.org/ogit/Notification>
- valid-from: Mon Apr 27 00:00:00 UTC 2015
- creator: cwalker@arago.de
- scope: NTO
- parent: [ogit/Node](#)

attributes

- optional:
 - [ogit/category](#)
 - [ogit/condition](#)
 - [ogit/description](#)
 - [ogit/expiresAt](#)
 - [ogit/firstOccurredAt](#)
 - [ogit/lastOccurredAt](#)
 - [ogit/message](#)
 - [ogit/onAttribute](#)
 - [ogit/onVertex](#)
 - [ogit/operation](#)
 - [ogit/priority](#)
 - [ogit/severity](#)
 - [ogit/sourceId](#)
 - [ogit/type](#)

incoming edges

- [ogit/includes](#) <= [ogit/Auth/Application](#)

2.1.0.27 ogit/UserMeta/Filter

A filter set by user, indicating preferences

- id: <http://www.purl.org/ogit/UserMeta/Filter>
- valid-from: Tue Jul 19 00:00:00 UTC 2016
- creator: stravlos@arago.de
- scope: NTO
- parent: ogit/Node

attributes

- mandatory:
 - [ogit/content](#)
 - [ogit/name](#)

incoming edges

- [ogit/defines](#) <= [ogit/Auth/Account](#)

2.1.0.28 ogit/Data/Log

This entity defines a log. It used to store a sequence of log records

- id: <http://www.purl.org/ogit/Data/Log>
- valid-from: Wed Jun 14 00:00:00 UTC 2017
- creator: stravlos@arago.de
- scope: NTO
- parent: ogit/Node

attributes

- optional:
 - [ogit/Data/timeToLive](#)
 - [ogit/description](#)
 - [ogit/name](#)

incoming edges

- [ogit/generates](#) <= [ogit/Auth/Machine](#)
- [ogit/generates](#) <= [ogit/Auth/Resource](#)
- [ogit/generates](#) <= [ogit/Auth/Software](#)

2.1.0.29 ogit/Network/NetworkInterface

Logical or physical network interface.

- id: <http://www.purl.org/ogit/Network/NetworkInterface>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: NTO
- parent: ogit/Node

attributes

- optional:
 - [ogit/id](#)

incoming edges

- [ogit/contains](#) <= [ogit/Auth/Machine](#)

2.1.0.30 ogit/Auth/ApplicationReview

Represents an application review

- id: <http://www.purl.org/ogit/Auth/ApplicationReview>
- valid-from: Fri May 18 00:00:00 UTC 2018
- creator: Mikhail Osher
- scope: NTO
- parent: ogit/Node

attributes

- mandatory:
 - [ogit/status](#)
 - [ogit/title](#)
- optional:
 - [ogit/comment](#)

incoming edges

- [ogit/creates](#) <= [ogit/Auth/Account](#)

outgoing edges

- [ogit/reviews](#) => [ogit/Auth/Application](#)

2.1.0.31 ogit/Auth/Organization

An ogit/Auth/Organization reflects a real world organization registered in hiro knowledge core

- id: <http://www.purl.org/ogit/Auth/Organization>
- valid-from: Mon Jan 01 00:00:00 UTC 2018
- creator: arago GmbH
- scope: NTO
- parent: ogit/Node

attributes

- mandatory:
 - [ogit/name](#)
- optional:
 - [ogit/isInternal](#)

incoming edges

- [ogit/Auth/belongs](#) <= [ogit/Auth/Configuration](#)
- [ogit/Auth/belongs](#) <= [ogit/Auth/DataScope](#)
- [ogit/Auth/belongs](#) <= [ogit/Auth/OrgDomain](#)
- [ogit/Auth/belongs](#) <= [ogit/Auth/RoleAssignment](#)
- [ogit/Auth/belongs](#) <= [ogit/Auth/Team](#)
- [ogit/Auth/isMemberOf](#) <= [ogit/Auth/Account](#)

outgoing edges

- [ogit/concludes](#) => [ogit/Contract](#)
- [ogit/consumes](#) => [ogit/Project/Project](#)
- [ogit/consumes](#) => [ogit/Survey/Iteration](#)
- [ogit/generates](#) => [ogit/Timeseries](#)
- [ogit/produces](#) => [ogit/Project/Project](#)
- [ogit/produces](#) => [ogit/Survey/Iteration](#)
- [ogit/supports](#) => [ogit/Project/Project](#)
- [ogit/supports](#) => [ogit/Survey/Iteration](#)

2.1.0.32 ogit/Event

This entity defines any type of event records, e.g. ITSM/produced by event management systems, Business Process etc.

- id: <http://www.purl.org/ogit/Event>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: SGO
- parent: ogit/Node

attributes

- mandatory:
 - [ogit/id](#)
 - [ogit/name](#)
- optional:
 - [ogit/ServiceManagement/reportedSource](#)
 - [ogit/acknowledgeState](#)
 - [ogit/category](#)
 - [ogit/certainty](#)
 - [ogit/description](#)
 - [ogit/expiresAt](#)
 - [ogit/firstOccurredAt](#)
 - [ogit/impact](#)
 - [ogit/instance](#)
 - [ogit/isRoot](#)
 - [ogit/lastClearedAt](#)
 - [ogit/lastOccurredAt](#)
 - [ogit/lastUpdatedAt](#)
 - [ogit/maintenanceState](#)
 - [ogit/occurrenceCount](#)
 - [ogit/openedAt](#)
 - [ogit/priority](#)
 - [ogit/resource](#)
 - [ogit/severity](#)
 - [ogit/sourceId](#)
 - [ogit/status](#)
 - [ogit/summary](#)
 - [ogit/type](#)

outgoing edges

- [ogit/alerts](#) => [ogit/Auth/Account](#)

2.1.0.33 [ogit/Automation/Configuration](#)

Configuration node to dynamically connect Knowledge Pools or Rankings to a HIRO installation.

- id: <http://www.purl.org/ogit/Automation/Configuration>
- valid-from: Wed Apr 25 00:00:00 UTC 2018
- creator: cy@arago.de
- scope: NTO
- parent: [ogit/Node](#)

incoming edges

- [ogit/uses](#) <= [ogit/Auth/Resource](#)

2.1.0.34 [ogit/SalesDistribution/Customer](#)

A customer in the sales and distribution process.

- id: <http://www.purl.org/ogit/SalesDistribution/Customer>
- valid-from: Wed Jul 10 00:00:00 UTC 2019
- creator: Marek Meyer
- scope: NTO
- parent: [ogit/Node](#)

attributes

- mandatory:
 - [ogit/name](#)
- optional:
 - [ogit/SalesDistribution/customerId](#)
 - [ogit/description](#)

outgoing edges

- [ogit/belongs](#) => [ogit/Auth/Application](#)

2.1.0.35 [ogit/Project/Project](#)

An identity that represents a grouping of Person, Milestone objects.

- id: <http://www.purl.org/ogit/Project/Project>
- valid-from: Mon Aug 08 00:00:00 UTC 2016
- creator: Arthur Shoba
- scope: NTO
- parent: [ogit/Node](#)

attributes

- optional:
 - [ogit/category](#)
 - [ogit/finishedAt](#)
 - [ogit/placement](#)
 - [ogit/plannedFinishDate](#)
 - [ogit/plannedStartDate](#)
 - [ogit/startedAt](#)
 - [ogit/status](#)
 - [ogit/title](#)

incoming edges

- [ogit/consumes](#) <= [ogit/Auth/Account](#)
- [ogit/consumes](#) <= [ogit/Auth/Organization](#)
- [ogit/produces](#) <= [ogit/Auth/Account](#)
- [ogit/produces](#) <= [ogit/Auth/Organization](#)
- [ogit/supervises](#) <= [ogit/Auth/Account](#)
- [ogit/supports](#) <= [ogit/Auth/Account](#)
- [ogit/supports](#) <= [ogit/Auth/Organization](#)

2.1.0.36 ogit/Timeseries

A time series is a sequence of data points, measured typically at successive points in time spaced at uniform time intervals.

- id: <http://www.purl.org/ogit/Timeseries>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: SGO
- parent: [ogit/Node](#)

attributes

- optional:
 - [ogit/description](#)
 - [ogit/instance](#)
 - [ogit/name](#)
 - [ogit/unit](#)

incoming edges

- [ogit/generates](#) <= [ogit/Auth/Organization](#)
- [ogit/generates](#) <= [ogit/Auth/Machine](#)
- [ogit/generates](#) <= [ogit/Auth/Resource](#)
- [ogit/generates](#) <= [ogit/Auth/Software](#)

2.2 Verbs

2.2.0.1 ogit/contains

This relationship indicates that something is part of something else. see also "includes"

- id: <http://www.purl.org/ogit/contains>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

Allowed Connection

- [ogit/Auth/Machine](#) => [ogit/Network/NetworkInterface](#)

2.2.0.2 ogit/manages

This relationship indicates that one entity manages some other.

- id: <http://www.purl.org/ogit/manages>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

Allowed Connection

- [ogit/Auth/Account](#) => [ogit/Subscription](#)

2.2.0.3 ogit/defines

General relationship indicating that some entity defines some other.

- id: <http://www.purl.org/ogit/defines>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

Allowed Connection

- [ogit/Auth/Account](#) => [ogit/UserMeta/Filter](#)

2.2.0.4 ogit/Auth/belongs

Denotes a relationship between two vertices in the Auth domain.

- id: <http://www.purl.org/ogit/Auth/belongs>
- valid-from: Mon Jan 01 00:00:00 UTC 2018
- creator: arago GmbH

Allowed Connection

- [ogit/Auth/AccountProfile](#) => [ogit/Auth/Account](#)
- [ogit/Auth/Configuration](#) => [ogit/Auth/Organization](#)
- [ogit/Auth/DataScope](#) => [ogit/Auth/Organization](#)
- [ogit/Auth/OrgDomain](#) => [ogit/Auth/Organization](#)
- [ogit/Auth/RoleAssignment](#) => [ogit/Auth/Organization](#)
- [ogit/Auth/Team](#) => [ogit/Auth/Team](#)
- [ogit/Auth/Team](#) => [ogit/Auth/Organization](#)

2.2.0.5 ogit/concludes

Verb showing if a legal entity concludes something (e.g. Contract).

- id: <http://www.purl.org/ogit/concludes>
- valid-from: Thu Jun 18 00:00:00 UTC 2015
- creator: Peter Larem

Allowed Connection

- [ogit/Auth/Organization](#) => [ogit/Contract](#)

2.2.0.6 ogit/supports

This relationship defines that one entity provides/supports another entity.

- id: <http://www.purl.org/ogit/supports>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

Allowed Connection

- [ogit/Auth/Account](#) => [ogit/Project/Milestone](#)
- [ogit/Auth/Account](#) => [ogit/Project/Project](#)
- [ogit/Auth/Organization](#) => [ogit/Project/Project](#)
- [ogit/Auth/Organization](#) => [ogit/Survey/Iteration](#)

2.2.0.7 ogit/supervises

Indicates if an entity supervises another entity. E.g. a Person supervises a Ticket or a Task.

- id: <http://www.purl.org/ogit/supervises>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

Allowed Connection

- [ogit/Auth/Account](#) => [ogit/Project/Project](#)
- [ogit/Auth/Account](#) => [ogit/Contract](#)

2.2.0.8 ogit/generates

Verb indicating if an entity generates another entity.

- id: <http://www.purl.org/ogit/generates>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

Allowed Connection

- [ogit/Auth/Organization](#) => [ogit/Timeseries](#)
- [ogit/Auth/Machine](#) => [ogit/Data/Log](#)
- [ogit/Auth/Machine](#) => [ogit/Timeseries](#)
- [ogit/Auth/Resource](#) => [ogit/Data/Log](#)
- [ogit/Auth/Resource](#) => [ogit/Timeseries](#)
- [ogit/Auth/Software](#) => [ogit/Data/Log](#)
- [ogit/Auth/Software](#) => [ogit/Timeseries](#)

2.2.0.9 ogit/consumes

This relationship indicates that one consumes result of work from another.

- id: <http://www.purl.org/ogit/consumes>
- valid-from: Mon Aug 08 00:00:00 UTC 2016
- creator: Alexander Ryabtsev

Allowed Connection

- [ogit/Auth/Account](#) => [ogit/Project/Milestone](#)
- [ogit/Auth/Account](#) => [ogit/Project/Project](#)
- [ogit/Auth/Organization](#) => [ogit/Project/Project](#)
- [ogit/Auth/Organization](#) => [ogit/Survey/Iteration](#)

2.2.0.10 ogit/includes

Indicates if an entity includes something else.

- id: <http://www.purl.org/ogit/includes>
- valid-from: Thu Jul 05 00:00:00 UTC 2018
- creator: qikram@arago.de

Allowed Connection

- [ogit/Auth/Application](#) => [ogit/Notification](#)

2.2.0.11 ogit/Auth/assumes

Denotes membership of an account in a group.

- id: <http://www.purl.org/ogit/Auth/assumes>
- valid-from: Mon Jan 01 00:00:00 UTC 2018
- creator: arago GmbH

Allowed Connection

- [ogit/Auth/Account](#) => [ogit/Auth/Role](#)

2.2.0.12 ogit/accepts

Indicates if an entity accepts something else.

- id: <http://www.purl.org/ogit/accepts>
- valid-from: Wed Sep 02 00:00:00 UTC 2015
- creator: bmoore@arago.de

Allowed Connection

- [ogit/Auth/Account](#) => [ogit/TermsAndConditions](#)

2.2.0.13 ogit/creates

Indicates if one entity creates another one.

- id: <http://www.purl.org/ogit/creates>
- valid-from: Tue May 19 00:00:00 UTC 2015
- creator: Peter Larem

Allowed Connection

- [ogit/Auth/Account](#) => [ogit/Auth/ApplicationReview](#)

2.2.0.14 ogit/Auth/consents

Denotes consent to an Application.

- id: <http://www.purl.org/ogit/Auth/consents>
- valid-from: Mon Jan 01 00:00:00 UTC 2018
- creator: arago GmbH

Allowed Connection

- [ogit/Auth/Account](#) => [ogit/Auth/Application](#)

2.2.0.15 ogit/Auth/assigns

Denotes assignments to a RoleAssignment.

- id: <http://www.purl.org/ogit/Auth/assigns>
- valid-from: Mon Jan 01 00:00:00 UTC 2018
- creator: arago GmbH

Allowed Connection

- [ogit/Auth/RoleAssignment](#) => [ogit/Auth/Role](#)
- [ogit/Auth/RoleAssignment](#) => [ogit/Auth/Team](#)
- [ogit/Auth/RoleAssignment](#) => [ogit/Auth/DataSet](#)

2.2.0.16 ogit/rates

This verb represents the `Rating` between two nodes

- id: <http://www.purl.org/ogit/rates>
- valid-from: Wed Aug 01 00:00:00 UTC 2018
- creator: qikram@arago.de

Allowed Connection

- [ogit/Rating](#) => [ogit/Auth/Application](#)

2.2.0.17 ogit/alerts

Verb showing if one entity alerts another.

- id: <http://www.purl.org/ogit/alerts>
- valid-from: Wed Oct 26 00:00:00 UTC 2016
- creator: stravlos@arago.co

Allowed Connection

- [ogit/Event](#) => [ogit/Auth/Account](#)

2.2.0.18 ogit/versions

The version of a node. This verb is generated internally.

- id: <http://www.purl.org/ogit/versions>
- valid-from: Tue Oct 31 00:00:00 UTC 2017
- creator: druss@arago.de

Allowed Connection

- [ogit/Auth/Application](#) => [ogit/Auth/Application](#)

2.2.0.19 ogit/reviews

One entity reviews another

- id: <http://www.purl.org/ogit/reviews>
- valid-from: Fri Jul 13 00:00:00 UTC 2018
- creator: Mikhail Osher

Allowed Connection

- [ogit/Auth/ApplicationReview](#) => [ogit/Auth/Application](#)

2.2.0.20 ogit/provides

Verb showing if one entity provides something to another.

- id: <http://www.purl.org/ogit/provides>
- valid-from: Fri Jul 24 00:00:00 UTC 2015
- creator: Aymen Ayoub

Allowed Connection

- [ogit/Auth/Account](#) => [ogit/Rating](#)

2.2.0.21 ogit/produces

This relationship indicates that one produces some work for another.

- id: <http://www.purl.org/ogit/produces>
- valid-from: Mon Aug 08 00:00:00 UTC 2016
- creator: Alexander Ryabtsev

Allowed Connection

- [ogit/Auth/Account](#) => [ogit/Project/Milestone](#)
- [ogit/Auth/Account](#) => [ogit/Project/Project](#)
- [ogit/Auth/Organization](#) => [ogit/Project/Project](#)
- [ogit/Auth/Organization](#) => [ogit/Survey/Iteration](#)

2.2.0.22 ogit/dependsOn

This relationship indicates that some entity is depending on some other. E.g. machine hosts software.

- id: <http://www.purl.org/ogit/dependsOn>
- valid-from: Thu Oct 15 00:00:00 UTC 2015
- creator: Aymen Ayoub

Allowed Connection

- [ogit/Auth/Resource](#) => [ogit/Auth/Software](#)
- [ogit/Auth/Software](#) => [ogit/Auth/Machine](#)

2.2.0.23 ogit/belongs

Verb showing if one entity belongs to another.

- id: <http://www.purl.org/ogit/belongs>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

Allowed Connection

- [ogit/Auth/Account](#) => [ogit/Person](#)
- [ogit/SalesDistribution/Customer](#) => [ogit/Auth/Application](#)
- [ogit/Schedule/Calendar](#) => [ogit/Auth/Account](#)
- [ogit/Attachment](#) => [ogit/Auth/AccountProfile](#)

2.2.0.24 ogit/uses

This relationship indicates that some entity is used by some other.

- id: <http://www.purl.org/ogit/uses>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

Allowed Connection

- [ogit/Auth/Resource](#) => [ogit/Automation/Configuration](#)

2.2.0.25 `ogit/Auth/isMemberOf`

Denotes membership of an account in a group.

- id: <http://www.purl.org/ogit/Auth/isMemberOf>
- valid-from: Mon Jan 01 00:00:00 UTC 2018
- creator: arago GmbH

Allowed Connection

- [ogit/Auth/Account](#) => [ogit/Auth/Organization](#)
- [ogit/Auth/Account](#) => [ogit/Auth/Team](#)

2.2.0.26 `ogit/Auth/uses`

Denotes use of an Application.

- id: <http://www.purl.org/ogit/Auth/uses>
- valid-from: Mon Jan 01 00:00:00 UTC 2018
- creator: arago GmbH

Allowed Connection

- [ogit/Auth/Account](#) => [ogit/Auth/Application](#)

2.2.0.27 `ogit/repliedWith`

This relationship indicates that user replied with something.

- id: <http://www.purl.org/ogit/repliedWith>
- valid-from: Mon Aug 08 00:00:00 UTC 2016
- creator: Alexander Ryabtsev

Allowed Connection

- [ogit/Auth/Account](#) => [ogit/Survey/Reply](#)

2.2.0.28 `ogit/has`

Indicates if an entity has another entity.

- id: <http://www.purl.org/ogit/has>
- valid-from: Thu Mar 28 00:00:00 UTC 2019
- creator: Kaushik Gondaliya

Allowed Connection

- [ogit/HR/Recruiting/Recruiter](#) => [ogit/Auth/Account](#)
- [ogit/Schedule/Attendee](#) => [ogit/Auth/Account](#)

2.3 Attributes

2.3.0.1 ogit/MARS/Network/fqdn

A FQDN according to RFC 1035. Replaces 'FQDN' from MARS-Schema

- id: <http://www.purl.org/ogit/MARS/Network/fqdn>
- valid-from: Fri Jun 01 00:00:00 UTC 2018
- creator: fotto@arago.de

used

- optional:
 - [ogit/Auth/Machine](#)

2.3.0.2 ogit/MARS/Software/installPath

Defines where a software is installed. Replaces 'SWInstallPath' and 'BasePath' from MARS-Schema

- id: <http://www.purl.org/ogit/MARS/Software/installPath>
- valid-from: Fri Jun 01 00:00:00 UTC 2018
- creator: fotto@arago.de

used

- optional:
 - [ogit/Auth/Software](#)
 - [ogit/Auth/Software](#)

2.3.0.3 ogit/MARS/Network/interfaceMAC

Alloes to specifies the MAC address of all defined interfaces. It's a key'ed list with the key to be defined in attribute ogit/MARS/Network/interfaceName of the same Machine node. Replaces 'NetworkInterfaceMAC' from MARS-Schema

- id: <http://www.purl.org/ogit/MARS/Network/interfaceMAC>
- valid-from: Fri Jun 01 00:00:00 UTC 2018
- creator: fotto@arago.de

used

- optional:
 - [ogit/Auth/Machine](#)

2.3.0.4 ogit/operation

This field represents operation type.

- id: <http://www.purl.org/ogit/operation>
- valid-from: Thu Mar 22 00:00:00 UTC 2018
- creator: qikram@arago.de

used

- optional:
 - [ogit/Notification](#)

2.3.0.5 ogit/Data/timeToLive

Defines how many seconds data will be kept before expire.

- id: <http://www.purl.org/ogit/Data/timeToLive>
- valid-from: Fri Feb 09 00:00:00 UTC 2018
- creator: mglusiuk@arago.de

used

- optional:
 - [ogit/Data/Log](#)

2.3.0.6 ogit/certainty

Defines the certainty of an event

- id: <http://www.purl.org/ogit/certainty>
- valid-from: Wed Aug 03 00:00:00 UTC 2016
- creator: Philipp Pelchmann

used

- optional:
 - [ogit/Event](#)

2.3.0.7 ogit/category

Used to categorize things.

- id: <http://www.purl.org/ogit/category>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
 - [ogit/Event](#)
 - [ogit/Notification](#)
 - [ogit/Project/Milestone](#)
 - [ogit/Project/Project](#)

2.3.0.8 ogit/onAttribute

This field represents an attribute on which an event occurred.

- id: <http://www.purl.org/ogit/onAttribute>
- valid-from: Thu Mar 22 00:00:00 UTC 2018
- creator: qikram@arago.de

used

- optional:
 - [ogit/Notification](#)

2.3.0.9 ogit/comment

Contains a comment.

- id: <http://www.purl.org/ogit/comment>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
 - [ogit/Auth/ApplicationReview](#)
 - [ogit/Rating](#)
 - [ogit/Survey/Reply](#)

2.3.0.10 ogit/endOfWarranty

End of warranty phase of a component

- id: <http://www.purl.org/ogit/endOfWarranty>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
 - [ogit/Auth/Machine](#)
 - [ogit/Auth/Software](#)

2.3.0.11 ogit/Auth/allowedTypes


Allowed types for authorization

- id: <http://www.purl.org/ogit/Auth/allowedTypes>
- valid-from: Mon Jan 01 00:00:00 UTC 2018
- creator: arago GmbH

used

- optional:
 - [ogit/Auth/Application](#)

2.3.0.12 ogit/MARS/Network/bindAddress

Usually an IP address. Defines the listening address for a software (server). Replaces 'NetworkIP' from MARS- Schema

- id: <http://www.purl.org/ogit/MARS/Network/bindAddress>
- valid-from: Fri Jun 01 00:00:00 UTC 2018
- creator: fotto@arago.de

used

- optional:
 - [ogit/Auth/Software](#)

2.3.0.13 ogit/Auth/Application/urls

URL of an application

- id: <http://www.purl.org/ogit/Auth/Application/urls>
- valid-from: Mon Jan 01 00:00:00 UTC 2018
- creator: arago GmbH

used

- optional:
 - [ogit/Auth/Application](#)

2.3.0.14 ogit/MARS/Machine/class

Defines the 'class' of a Machine MARS node. This is basically the Operation System name. Replaces 'Machine↔ Class' from MARS-Schema

- id: <http://www.purl.org/ogit/MARS/Machine/class>
- valid-from: Fri Jun 01 00:00:00 UTC 2018
- creator: fotto@arago.de

used

- mandatory:
 - [ogit/Auth/Machine](#)

2.3.0.15 ogit/MARS/Machine/cpuArch

CPU architecture. On UNIX like systems it will be the output of 'uname -m'. Replaces 'MachineArchitecture' from MARS-Schema

- id: <http://www.purl.org/ogit/MARS/Machine/cpuArch>
- valid-from: Fri Jun 01 00:00:00 UTC 2018
- creator: fotto@arago.de

used

- optional:
 - [ogit/Auth/Machine](#)

2.3.0.16 ogit/email

An email address.

- id: <http://www.purl.org/ogit/email>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
 - [ogit/Auth/Account](#)
 - [ogit/Person](#)
 - [ogit/Schedule/Attendee](#)

2.3.0.17 ogit/MARS/Software/logPath

Defines where a software writes its logfiles. Replaces 'LogPath' from MARS-Schema

- id: <http://www.purl.org/ogit/MARS/Software/logPath>
- valid-from: Fri Jun 01 00:00:00 UTC 2018
- creator: fotto@arago.de

used

- optional:
 - [ogit/Auth/Software](#)

2.3.0.18 ogit/alternativeName

Alternative name of something. In context of a Person this can be the full name or an alias/nick name.

- id: <http://www.purl.org/ogit/alternativeName>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
 - [ogit/Person](#)

2.3.0.19 ogit/Version/major

major version according to <https://semver.org/>

- id: <http://www.purl.org/ogit/Version/major>
- valid-from: Fri May 25 00:00:00 UTC 2018
- creator: fotto@arago.de

used

- optional:
 - [ogit/Auth/Machine](#)
 - [ogit/Auth/Software](#)

2.3.0.20 ogit/onVertex

This field represents a vertex on which an event occurred.

- id: <http://www.purl.org/ogit/onVertex>
- valid-from: Thu Mar 22 00:00:00 UTC 2018
- creator: qikram@arago.de

used

- optional:
 - [ogit/Notification](#)

2.3.0.21 ogit/question

Contains a question.

- id: <http://www.purl.org/ogit/question>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
 - [ogit/Survey/Reply](#)

2.3.0.22 ogit/maintenanceState

Defines the state of maintenance.

- id: <http://www.purl.org/ogit/maintenanceState>
- valid-from: Wed Aug 03 00:00:00 UTC 2016
- creator: Philipp Pelchmann

used

- optional:
 - [ogit/Event](#)

2.3.0.23 ogit/notification

A notification.

- id: <http://www.purl.org/ogit/notification>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Philipp Pelchmann

used

- optional:
 - [ogit/Person](#)

2.3.0.24 ogit/sourceId

The Id of the source system.

- id: <http://www.purl.org/ogit/sourceId>
- valid-from: Thu Jun 11 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
 - [ogit/Event](#)
 - [ogit/Notification](#)
 - [ogit/Person](#)
 - [ogit/Subscription](#)

2.3.0.25 ogit/url

Contains an URL (unified resource locator)

- id: <http://www.purl.org/ogit/url>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
 - [ogit/Attachment](#)
 - [ogit/Auth/Resource](#)
 - [ogit/Auth/Software](#)

2.3.0.26 ogit/Auth/edgeRule

Contains jfilter expression for the allowed edge operations

- id: <http://www.purl.org/ogit/Auth/edgeRule>
- valid-from: Mon Jan 01 00:00:00 UTC 2018
- creator: arago GmbH

used

- mandatory:
 - [ogit/Auth/Application](#)
 - [ogit/Auth/DataSet](#)
 - [ogit/Auth/Role](#)

2.3.0.27 ogit/Schedule/isOrganizer

Boolean indicating whether an attendee is the organizer of a calendar event.

- id: <http://www.purl.org/ogit/Schedule/isOrganizer>
- valid-from: Tue Jul 02 00:00:00 UTC 2019
- creator: Marek Meyer

used

- optional:
 - [ogit/Schedule/Attendee](#)

2.3.0.28 ogit/mobilePhone

A mobile phone number.

- id: <http://www.purl.org/ogit/mobilePhone>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
 - [ogit/Person](#)

2.3.0.29 ogit/severity

Stores a severity. E.g. Some event management systems might store a severity field.

- id: <http://www.purl.org/ogit/severity>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
 - [ogit/Event](#)
 - [ogit/Notification](#)

2.3.0.30 ogit/startedAt

Defines a point in time when the work on a change, task, or similar entity was actually started. The values must be combined date and time with time zone designator according to ISO 8601

- id: <http://www.purl.org/ogit/startedAt>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
 - [ogit/Project/Milestone](#)
 - [ogit/Project/Project](#)
 - [ogit/Survey/Iteration](#)

2.3.0.31 ogit/value

Contains a value of a key / value pair.

- id: <http://www.purl.org/ogit/value>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- mandatory:
 - [ogit/Rating](#)

2.3.0.32 ogit/unit

Unit of measurement of some value.

- id: <http://www.purl.org/ogit/unit>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
 - [ogit/Timeseries](#)

2.3.0.33 ogit/Automation/automationState

A value of 'Manual' will mark a node as not eligible for Issue processing

- id: <http://www.purl.org/ogit/Automation/automationState>
- valid-from: Fri Jun 01 00:00:00 UTC 2018
- creator: fotto@arago.de

used

- optional:
 - [ogit/Auth/Machine](#)
 - [ogit/Auth/Resource](#)
 - [ogit/Auth/Software](#)

2.3.0.34 ogit/status

A status for an entity. At this level of specification no list of values is specified. However, applications using this attribute are expected to allow only a fixed list of values that seems useful in the application's semantic context.

- id: <http://www.purl.org/ogit/status>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- mandatory:
 - [ogit/Auth/Account](#)
 - [ogit/Auth/ApplicationReview](#)
- optional:
 - [ogit/Contract](#)
 - [ogit/Event](#)
 - [ogit/Person](#)
 - [ogit/Project/Milestone](#)
 - [ogit/Project/Project](#)
 - [ogit/Subscription](#)
 - [ogit/Survey/Iteration](#)

2.3.0.35 ogit/createdAt

Defines a point in time when a ticket/incident/event etc was created or recorded.

- id: <http://www.purl.org/ogit/createdAt>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
 - [ogit/Attachment](#)

2.3.0.36 ogit/Automation/lifecycle

Contains the lifecycle state of a MARSNode. If value is 'decommissioned' this node is ignored by engine, graph and UI.

- id: <http://www.purl.org/ogit/Automation/lifecycle>
- valid-from: Thu May 11 00:00:00 UTC 2017
- creator: Philipp Kählitz

used

- optional:
 - [ogit/Auth/Machine](#)
 - [ogit/Auth/Resource](#)
 - [ogit/Auth/Software](#)

2.3.0.37 ogit/lastName

Last name of a person.

- id: <http://www.purl.org/ogit/lastName>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
 - [ogit/Auth/AccountProfile](#)
 - [ogit/Person](#)

2.3.0.38 ogit/priority

Priority of a ticket. The actual semantics might depend on the ticket type (Incident, Service Request, ...)

- id: <http://www.purl.org/ogit/priority>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
 - [ogit/Event](#)
 - [ogit/Notification](#)

2.3.0.39 ogit/middleName

Middle name of a person.

- id: <http://www.purl.org/ogit/middleName>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Philipp Pelchmann

used

- optional:
 - [ogit/Person](#)

2.3.0.40 ogit/resource

Defines the name of an resource on an instance e.g. disk or database.

- id: <http://www.purl.org/ogit/resource>
- valid-from: Wed Aug 03 00:00:00 UTC 2016
- creator: Philipp Pelchmann

used

- optional:
 - [ogit/Event](#)

2.3.0.41 ogit/MARS/Software/instanceId

Allow to define some instance identifier for a Software node. Usually this is used to uniquely identify a cluster member. The value might be a composition of several attributes, e.g. <data-center-id>:<rack-id>. Replaces 'Instance' from MARS-Schema

- id: <http://www.purl.org/ogit/MARS/Software/instanceId>
- valid-from: Fri Jun 01 00:00:00 UTC 2018
- creator: fotto@arago.de

used

- optional:
 - [ogit/Auth/Software](#)

2.3.0.42 ogit/accessControl

The access control level of this Node. Value could mean different things to different applications / policies. Initial intent is that policies would treat "public-read" (inspired by Amazon AWS S3 ACLs) to mean anyone would have read-only access to this node.

- id: <http://www.purl.org/ogit/accessControl>
- valid-from: Thu Mar 26 00:00:00 UTC 2015
- creator: Chris Walker

used

- optional:
 - [ogit/Attachment](#)

2.3.0.43 ogit/Auth/vertexRule

Contains jfilter expression for the allowed vertex operations

- id: <http://www.purl.org/ogit/Auth/vertexRule>
- valid-from: Mon Jan 01 00:00:00 UTC 2018
- creator: arago GmbH

used

- mandatory:
 - [ogit/Auth/Application](#)
 - [ogit/Auth/DataSet](#)
 - [ogit/Auth/Role](#)

2.3.0.44 ogit/Auth/_iam-domain

IAM Domain of an entity

- id: http://www.purl.org/ogit/Auth/_iam-domain
- valid-from: Mon Jan 01 00:00:00 UTC 2018
- creator: arago GmbH

2.3.0.45 ogit/expiresAt

Defines the date something expires.

- id: <http://www.purl.org/ogit/expiresAt>
- valid-from: Wed Aug 03 00:00:00 UTC 2016
- creator: Philipp Pelchmann

used

- optional:
 - [ogit/Event](#)
 - [ogit/Notification](#)

2.3.0.46 ogit/plannedFinishDate

Defines the date when something will be finished.

- id: <http://www.purl.org/ogit/plannedFinishDate>
- valid-from: Mon Aug 08 00:00:00 UTC 2016
- creator: Alexander Ryabtsev

used

- optional:
 - [ogit/Project/Milestone](#)
 - [ogit/Project/Project](#)

2.3.0.47 ogit/Auth/Account/statusReason

Status Reason of an ogit/Auth/Account

- id: <http://www.purl.org/ogit/Auth/Account/statusReason>
- valid-from: Mon Jan 01 00:00:00 UTC 2018
- creator: arago GmbH

used

- optional:
 - [ogit/Auth/Account](#)

2.3.0.48 ogit/serialNumber

A string representing a any kind of serial number. see <http://purl.org/goodrelations/v1#serialNumber>

- id: <http://www.purl.org/ogit/serialNumber>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
 - [ogit/Auth/Machine](#)
 - [ogit/Auth/Software](#)

2.3.0.49 ogit/firstName

First name of a person

- id: <http://www.purl.org/ogit/firstName>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
 - [ogit/Auth/AccountProfile](#)
 - [ogit/Person](#)

2.3.0.50 ogit/MARS/Network/defaultGateway

Defines the default gateway. In case of IPv4 dot-decimal notation shall be used. Replaces 'NetworkDefaultGW' from MARS-Schema

- id: <http://www.purl.org/ogit/MARS/Network/defaultGateway>
- valid-from: Fri Jun 01 00:00:00 UTC 2018
- creator: fotto@arago.de

used

- optional:
 - [ogit/Auth/Machine](#)

2.3.0.51 ogit/title

Title of any kind. In the context of a Person this can be a courtesy title, an academic title, or a job title.

- id: <http://www.purl.org/ogit/title>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- mandatory:
 - [ogit/Auth/ApplicationReview](#)
- optional:
 - [ogit/Person](#)
 - [ogit/Project/Milestone](#)
 - [ogit/Project/Project](#)
 - [ogit/Schedule/Calendar](#)

2.3.0.52 ogit/MARS/Machine/ram

The available system memory in a machine. It starts with a number following by an optional unit character ('M' or 'G'). If unit character is omitted then 'M' shall be assumed. This is . Replaces 'HWRAM' from MARS-Schema

- id: <http://www.purl.org/ogit/MARS/Machine/ram>
- valid-from: Fri Jun 01 00:00:00 UTC 2018
- creator: fotto@arago.de

used

- optional:
 - [ogit/Auth/Machine](#)

2.3.0.53 ogit/MARS/Network/port

A number indicating a network port (0..65535). Usually used define the listening port for a software (server). Replaces 'NetworkPort' from MARS-Schema

- id: <http://www.purl.org/ogit/MARS/Network/port>
- valid-from: Fri Jun 01 00:00:00 UTC 2018
- creator: fotto@arago.de

used

- optional:
 - [ogit/Auth/Software](#)

2.3.0.54 ogit/Version/patch

patch version according to <https://semver.org/>

- id: <http://www.purl.org/ogit/Version/patch>
- valid-from: Fri May 25 00:00:00 UTC 2018
- creator: fotto@arago.de

used

- optional:
 - [ogit/Auth/Machine](#)
 - [ogit/Auth/Software](#)

2.3.0.55 ogit/content

A string holding any type of content: plain string, XML fragments, RDF documents, ...

- id: <http://www.purl.org/ogit/content>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- mandatory:
 - [ogit/TermsAndConditions](#)
 - [ogit/UserMeta/Filter](#)
- optional:
 - [ogit/Attachment](#)

2.3.0.56 ogit/MARS/Machine/kernel

Describes the running Operating System kernel. For Linux systems this is usually the output of 'uname -s -v -r'. Replaces 'OSKernel' from MARS-Schema

- id: <http://www.purl.org/ogit/MARS/Machine/kernel>
- valid-from: Fri Jun 01 00:00:00 UTC 2018
- creator: fotto@arago.de

used

- optional:
 - [ogit/Auth/Machine](#)

2.3.0.57 `ogit/lastOccurredAt`

Defines the date of last occurrence of an event

- id: <http://www.purl.org/ogit/lastOccurredAt>
- valid-from: Wed Aug 03 00:00:00 UTC 2016
- creator: Philipp Pelchmann

used

- optional:
 - [ogit/Event](#)
 - [ogit/Notification](#)

2.3.0.58 `ogit/SalesDistribution/customerId`

Customer identifier.

- id: <http://www.purl.org/ogit/SalesDistribution/customerId>
- valid-from: Wed Jul 10 00:00:00 UTC 2019
- creator: Marek Meyer

used

- optional:
 - [ogit/SalesDistribution/Customer](#)

2.3.0.59 `ogit/isInternal`

Boolean which can define internal data. The actual semantics depends on the usage context

- id: <http://www.purl.org/ogit/isInternal>
- valid-from: Fri Feb 01 00:00:00 UTC 2019
- creator: FCO

used

- optional:
 - [ogit/Auth/Organization](#)

2.3.0.60 `ogit/MARS/Network/protocol`

Can be used to define the network protocol a service (software) is using. Typical values: 'tcp', 'udp'. Replaces 'NetworkProtocol' from MARS-Schema

- id: <http://www.purl.org/ogit/MARS/Network/protocol>
- valid-from: Fri Jun 01 00:00:00 UTC 2018
- creator: fotto@arago.de

used

- optional:
 - [ogit/Auth/Software](#)

2.3.0.61 `ogit/Auth/Application/parent`

Parent of an application

- id: <http://www.purl.org/ogit/Auth/Application/parent>
- valid-from: Mon Jan 01 00:00:00 UTC 2018
- creator: arago GmbH

used

- optional:
 - [ogit/Auth/Application](#)

2.3.0.62 `ogit/Auth/Account/displayName`

Display name of an account

- id: <http://www.purl.org/ogit/Auth/Account/displayName>
- valid-from: Mon Jan 01 00:00:00 UTC 2018
- creator: arago GmbH

used

- optional:
 - [ogit/Auth/AccountProfile](#)

2.3.0.63 ogit/MARS/Network/ipVersion

Allows to specify the IP version for defined interfaces. It's a key'ed list with the key to be defined in attribute ogit/MARS/Network/interfaceName of the same Machine node. It can be used to indicate what to expectd in the corresponding entries of other network related attributes, e.g 'ogit/MARS/Network/interfaceIP'. Replaces 'Network↔InterfaceType' from MARS-Schema

- id: <http://www.purl.org/ogit/MARS/Network/ipVersion>
- valid-from: Fri Jun 01 00:00:00 UTC 2018
- creator: fotto@arago.de

used

- optional:
 - [ogit/Auth/Machine](#)

2.3.0.64 ogit/Auth/Account/type

Type of an account. Values: person, application

- id: <http://www.purl.org/ogit/Auth/Account/type>
- valid-from: Mon Jan 01 00:00:00 UTC 2018
- creator: arago GmbH

used

- mandatory:
 - [ogit/Auth/Account](#)

2.3.0.65 ogit/name

Contains a name.

- id: <http://www.purl.org/ogit/name>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- mandatory:
 - [ogit/Auth/Account](#)
 - [ogit/Auth/Application](#)
 - [ogit/Auth/DataScope](#)
 - [ogit/Auth/DataSet](#)
 - [ogit/Auth/Machine](#)
 - [ogit/Auth/OrgDomain](#)
 - [ogit/Auth/Organization](#)
 - [ogit/Auth/Resource](#)
 - [ogit/Auth/Role](#)
 - [ogit/Auth/Software](#)
 - [ogit/Auth/Team](#)
 - [ogit/Contract](#)
 - [ogit/Event](#)
 - [ogit/SalesDistribution/Customer](#)
 - [ogit/Schedule/Attendee](#)
 - [ogit/TermsAndConditions](#)
 - [ogit/UserMeta/Filter](#)
- optional:
 - [ogit/Attachment](#)
 - [ogit/Data/Log](#)
 - [ogit/Subscription](#)
 - [ogit/Timeseries](#)

2.3.0.66 [ogit/description](#)

Contains a description.

- id: <http://www.purl.org/ogit/description>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- mandatory:
 - [ogit/Auth/Application](#)
- optional:
 - [ogit/Auth/DataScope](#)
 - [ogit/Auth/DataSet](#)
 - [ogit/Auth/Role](#)
 - [ogit/Auth/Team](#)

- [ogit/Contract](#)
- [ogit/Data/Log](#)
- [ogit/Event](#)
- [ogit/Notification](#)
- [ogit/SalesDistribution/Customer](#)
- [ogit/Schedule/Calendar](#)
- [ogit/TermsAndConditions](#)
- [ogit/Timeseries](#)

2.3.0.67 [ogit/placement](#)

A place where the object is placed.

- id: <http://www.purl.org/ogit/placement>
- valid-from: Mon Aug 08 00:00:00 UTC 2016
- creator: Alexander Ryabtsev

used

- optional:
 - [ogit/Project/Project](#)

2.3.0.68 [ogit/condition](#)

This field represents condition type.

- id: <http://www.purl.org/ogit/condition>
- valid-from: Thu Mar 22 00:00:00 UTC 2018
- creator: qikram@arago.de

used

- optional:
 - [ogit/Notification](#)

2.3.0.69 [ogit/Auth/Account/acceptedProjectTerms](#)

Flag about whether HIRO Project terms were accepted

- id: <http://www.purl.org/ogit/Auth/Account/acceptedProjectTerms>
- valid-from: Mon Jan 01 00:00:00 UTC 2018
- creator: arago GmbH

used

- optional:
 - [ogit/Auth/Account](#)

2.3.0.70 ogit/finishedAt

Defines a point in time when the work on a change, task, or similar entity was actually finished. The values must be combined date and time with time zone designator according to ISO 8601

- id: <http://www.purl.org/ogit/finishedAt>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
 - [ogit/Project/Milestone](#)
 - [ogit/Project/Project](#)

2.3.0.71 ogit/Auth/Account/acceptedTerms

Flag about whether usage terms were accepted

- id: <http://www.purl.org/ogit/Auth/Account/acceptedTerms>
- valid-from: Mon Jan 01 00:00:00 UTC 2018
- creator: arago GmbH

used

- optional:
 - [ogit/Auth/Account](#)

2.3.0.72 ogit/impact

Will contain the impact, for example of a ticket. In this case the actual semantics would depend on the ticket type, which could correspond to an Incident, Service Request, etc.

- id: <http://www.purl.org/ogit/impact>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
 - [ogit/Event](#)

2.3.0.73 ogit/plannedStartDate

Defines the date when something will be started.

- id: <http://www.purl.org/ogit/plannedStartDate>
- valid-from: Mon Aug 08 00:00:00 UTC 2016
- creator: Alexander Ryabtsev

used

- optional:
 - [ogit/Project/Milestone](#)
 - [ogit/Project/Project](#)

2.3.0.74 ogit/MARS/Software/subClass

Give each type of Software a unique name, e.g 'OpenLDAP' or 'MSSharePointServer'. This should be the primary matching variable for software specific automation (using KnowledgeItems). Replaces 'SoftwareSubClass' from MARS-Schema

- id: <http://www.purl.org/ogit/MARS/Software/subClass>
- valid-from: Fri Jun 01 00:00:00 UTC 2018
- creator: fotto@arago.de

used

- mandatory:
 - [ogit/Auth/Software](#)

2.3.0.75 ogit/Version/minor

minor version according to <https://semver.org/>

- id: <http://www.purl.org/ogit/Version/minor>
- valid-from: Fri May 25 00:00:00 UTC 2018
- creator: fotto@arago.de

used

- optional:
 - [ogit/Auth/Machine](#)
 - [ogit/Auth/Software](#)

2.3.0.76 `ogit/Auth/Account/acceptedEmails`

Flag about whether emails were accepted

- id: <http://www.purl.org/ogit/Auth/Account/acceptedEmails>
- valid-from: Mon Jan 01 00:00:00 UTC 2018
- creator: arago GmbH

used

- optional:
 - [ogit/Auth/AccountProfile](#)

2.3.0.77 `ogit/lastUpdatedBy`

Defines the last person or process who updated an entity.

- id: <http://www.purl.org/ogit/lastUpdatedBy>
- valid-from: Mon Jul 20 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
 - [ogit/Attachment](#)

2.3.0.78 `ogit/isRoot`

Defines if an event is root.

- id: <http://www.purl.org/ogit/isRoot>
- valid-from: Wed Aug 03 00:00:00 UTC 2016
- creator: Philipp Pelchmann

used

- optional:
 - [ogit/Event](#)

2.3.0.79 ogit/openedAt

Time when a ticket or task was created/opened. The values could combine date and time with time zone designator according to ISO 8601 for service management tickets. For most tickets there is no real difference between creation and opened time. In case such a distinction is relevant the "createdAt" attribute can be used.

- id: <http://www.purl.org/ogit/openedAt>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
 - [ogit/Event](#)

2.3.0.80 ogit/expirationDate

Defines a point in time when something becomes invalid the format is described at <http://purl.org/goodrelations/v1#validThrough>

- id: <http://www.purl.org/ogit/expirationDate>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
 - [ogit/Contract](#)

2.3.0.81 ogit/officePhone

The phone number in the office.

- id: <http://www.purl.org/ogit/officePhone>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Philipp Pelchmann

used

- optional:
 - [ogit/Person](#)

2.3.0.82 ogit/acknowledgeState

Defines the state of acknowledgement.

- id: <http://www.purl.org/ogit/acknowledgeState>
- valid-from: Wed Aug 03 00:00:00 UTC 2016
- creator: Philipp Pelchmann

used

- optional:
 - [ogit/Event](#)

2.3.0.83 ogit/deadline

Defines a point in time when a deadline is reached.

- id: <http://www.purl.org/ogit/deadline>
- valid-from: Mon Dec 19 00:00:00 UTC 2016
- creator: stravlos@arago.co

used

- optional:
 - [ogit/Contract](#)

2.3.0.84 ogit/fax

The number of a fax.

- id: <http://www.purl.org/ogit/fax>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Philipp Pelchmann

used

- optional:
 - [ogit/Person](#)

2.3.0.85 ogit/type

Type of an an entity.

- id: <http://www.purl.org/ogit/type>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
 - [ogit/Attachment](#)
 - [ogit/Contract](#)
 - [ogit/Event](#)
 - [ogit/Notification](#)
 - [ogit/Subscription](#)

2.3.0.86 ogit/Auth/Account/allowCookies

Flag about whether cookies are allowed

- id: <http://www.purl.org/ogit/Auth/Account/allowCookies>
- valid-from: Mon Jan 01 00:00:00 UTC 2018
- creator: arago GmbH

used

- optional:
 - [ogit/Auth/Account](#)

2.3.0.87 ogit/otherPhone

The number of an other phone.

- id: <http://www.purl.org/ogit/otherPhone>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Philipp Pelchmann

used

- optional:
 - [ogit/Person](#)

2.3.0.88 `ogit/Auth/Application/type`

Type of an application

- id: <http://www.purl.org/ogit/Auth/Application/type>
- valid-from: Mon Jan 01 00:00:00 UTC 2018
- creator: arago GmbH

used

- optional:
 - [ogit/Auth/Application](#)

2.3.0.89 `ogit/MARS/Network/interfacePrefixLength`

Specifies the network prefix length (network mask) of all defined interfaces. It's a key'ed list with the key to be defined in attribute `ogit/MARS/Network/interfaceName` of the same Machine node. The values are always number, e.g. a value of '24' in the context of IPv4 is equivalent to 255.255.255.0 in dot-decimal notation. Replaces 'Network↔InterfacePrefixLength' and 'NetworkInterfaceNetmask' from MARS-Schema

- id: <http://www.purl.org/ogit/MARS/Network/interfacePrefixLength>
- valid-from: Fri Jun 01 00:00:00 UTC 2018
- creator: fotto@arago.de

used

- optional:
 - [ogit/Auth/Machine](#)

2.3.0.90 `ogit/sourceTable`

Contains the source table, that stores where the data are coming from.

- id: <http://www.purl.org/ogit/sourceTable>
- valid-from: Thu Aug 20 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
 - [ogit/Attachment](#)

2.3.0.91 ogit/creator

Creator of an entity.

- id: <http://www.purl.org/ogit/creator>
- valid-from: Thu Aug 20 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
 - [ogit/Attachment](#)

2.3.0.92 ogit/MARS/Network/interfaceIP

Specifies the configured IP address of all defined interfaces. It's a key'ed list with the key to be defined in attribute ogit/MARS/Network/interfaceName of the same Machine node. In case of IPv4 addresses dot-decimal notation shall be used. Replaces 'NetworkInterfaceIP' from MARS-Schema

- id: <http://www.purl.org/ogit/MARS/Network/interfaceIP>
- valid-from: Fri Jun 01 00:00:00 UTC 2018
- creator: fotto@arago.de

used

- optional:
 - [ogit/Auth/Machine](#)

2.3.0.93 ogit/subType

A subtype of an an entity.

- id: <http://www.purl.org/ogit/subType>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
 - [ogit/Schedule/Calendar](#)

2.3.0.94 ogit/message

Contains a message.

- id: <http://www.purl.org/ogit/message>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
 - [ogit/Notification](#)

2.3.0.95 ogit/webPage

A web page.

- id: <http://www.purl.org/ogit/webPage>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Philipp Pelchmann

used

- optional:
 - [ogit/Person](#)

2.3.0.96 ogit/lastUpdatedAt

Defines latest date and time when a ticket or it's comment was updated. The format of this value could be according to ISO 8601.

- id: <http://www.purl.org/ogit/lastUpdatedAt>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
 - [ogit/Attachment](#)
 - [ogit/Event](#)

2.3.0.97 `ogit/MARS/Machine/distroName`

The distro name of an Operation System. For Linux you will encounter things like: 'CentOS', 'RedHat', Replaces 'OSName' from MARS-Schema

- id: <http://www.purl.org/ogit/MARS/Machine/distroName>
- valid-from: Fri Jun 01 00:00:00 UTC 2018
- creator: fotto@arago.de

used

- optional:
 - [ogit/Auth/Machine](#)

2.3.0.98 `ogit/MARS/Network/interfaceName`

This defines the network interface within a system. It's always a list containing all the defined interfaces, e.g. 'lo0 eth0 eth1'. Replaces 'NetworkInterface' from MARS-Schema

- id: <http://www.purl.org/ogit/MARS/Network/interfaceName>
- valid-from: Fri Jun 01 00:00:00 UTC 2018
- creator: fotto@arago.de

used

- optional:
 - [ogit/Auth/Machine](#)

2.3.0.99 `ogit/id`

General id.

- id: <http://www.purl.org/ogit/id>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- mandatory:
 - [ogit/Event](#)
- optional:
 - [ogit/Attachment](#)
 - [ogit/Network/NetworkInterface](#)

2.3.0.100 `ogit/Auth/Account/acceptedPrivacy`

Flag about whether privacy terms were accepted

- id: <http://www.purl.org/ogit/Auth/Account/acceptedPrivacy>
- valid-from: Mon Jan 01 00:00:00 UTC 2018
- creator: arago GmbH

used

- optional:
 - [ogit/Auth/Account](#)

2.3.0.101 `ogit/MARS/Software/class`

Used to classify Software nodes. Will contain values like: 'DBMS', 'WebServer', 'DataProcessing', and so on. Replaces 'SoftwareClass' from MARS-Schema

- id: <http://www.purl.org/ogit/MARS/Software/class>
- valid-from: Fri Jun 01 00:00:00 UTC 2018
- creator: fotto@arago.de

used

- mandatory:
 - [ogit/Auth/Software](#)

2.3.0.102 `ogit/occurenceCount`

Defines the number an event occurred.

- id: <http://www.purl.org/ogit/occurenceCount>
- valid-from: Wed Aug 03 00:00:00 UTC 2016
- creator: Philipp Pelchmann

used

- optional:
 - [ogit/Event](#)

2.3.0.103 ogit/summary

A summary/short description, for example of a ticket.

- id: <http://www.purl.org/ogit/summary>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
 - [ogit/Event](#)

2.3.0.104 ogit/lastClearedAt

Defines the date an event has been cleared.

- id: <http://www.purl.org/ogit/lastClearedAt>
- valid-from: Wed Aug 03 00:00:00 UTC 2016
- creator: Philipp Pelchmann

used

- optional:
 - [ogit/Event](#)

2.3.0.105 ogit/MARS/Resource/class

Used to classify Resource nodes. Will contain values like: 'Backend', 'Database', and so on. Replaces 'Resource↔ Class' from MARS-Schema

- id: <http://www.purl.org/ogit/MARS/Resource/class>
- valid-from: Fri Jun 01 00:00:00 UTC 2018
- creator: fotto@arago.de

used

- mandatory:
 - [ogit/Auth/Resource](#)

2.3.0.106 ogit/Automation/marsNodeType

Contains The Type of the Mars Node. Should be one of Application, Machine, Software, Resource.

- id: <http://www.purl.org/ogit/Automation/marsNodeType>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
 - [ogit/Auth/Machine](#)
 - [ogit/Auth/Resource](#)
 - [ogit/Auth/Software](#)

2.3.0.107 ogit/Schedule/attendanceStatus

Status of event attendance.

- id: <http://www.purl.org/ogit/Schedule/attendanceStatus>
- valid-from: Tue Jul 02 00:00:00 UTC 2019
- creator: Marek Meyer

used

- optional:
 - [ogit/Schedule/Attendee](#)

2.3.0.108 ogit/size

The size, e.g. of a file.

- id: <http://www.purl.org/ogit/size>
- valid-from: Thu Mar 26 00:00:00 UTC 2015
- creator: arago Technologies

used

- optional:
 - [ogit/Attachment](#)

2.3.0.109 ogit/Automation/serviceStatus

Contains the status of a service.

- id: <http://www.purl.org/ogit/Automation/serviceStatus>
- valid-from: Fri Jul 24 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
 - [ogit/Auth/Machine](#)
 - [ogit/Auth/Resource](#)
 - [ogit/Auth/Software](#)

2.3.0.110 ogit/vendor

Contains the vendor of a device or software/hardware component.

- id: <http://www.purl.org/ogit/vendor>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
 - [ogit/Auth/Machine](#)
 - [ogit/Auth/Software](#)

2.3.0.111 ogit/firstOccurredAt

Defines the date of first occurrence of an event

- id: <http://www.purl.org/ogit/firstOccurredAt>
- valid-from: Wed Aug 03 00:00:00 UTC 2016
- creator: Philipp Pelchmann

used

- optional:
 - [ogit/Event](#)
 - [ogit/Notification](#)

2.3.0.112 ogit/validFrom

Defines a point in time when something becomes valid.

- id: <http://www.purl.org/ogit/validFrom>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
 - [ogit/Contract](#)

2.3.0.113 ogit/MARS/Software/serviceName

Defines the service name for a software which can be used for administrative operations like start, stop, or status. E.g. on RedHat Linux it would be the name of the service unit (without the .service extension). Replaces 'ServiceName' from MARS-Schema

- id: <http://www.purl.org/ogit/MARS/Software/serviceName>
- valid-from: Fri Jun 01 00:00:00 UTC 2018
- creator: fotto@arago.de

used

- optional:
 - [ogit/Auth/Software](#)

2.3.0.114 ogit/position

Indicates user's position. This field contains a string value.

- id: <http://www.purl.org/ogit/position>
- valid-from: Tue Oct 18 00:00:00 UTC 2016
- creator: Arthur Shoba

used

- optional:
 - [ogit/Person](#)

2.3.0.115 `ogit/ServiceManagement/reportedSource`

Can be used to define how a ticket was communicated. It could define some kind of communication channel ("↔ ServiceDesk", "Email") or, e.g. for Incident records, it might define that the ticket was produced automatically from an event management system.

- id: <http://www.purl.org/ogit/ServiceManagement/reportedSource>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
 - [ogit/Event](#)

2.3.0.116 `ogit/instance`

Defines the name of an instance.

- id: <http://www.purl.org/ogit/instance>
- valid-from: Wed Aug 03 00:00:00 UTC 2016
- creator: Philipp Pelchmann

used

- optional:
 - [ogit/Event](#)
 - [ogit/Timeseries](#)

2.3.0.117 `ogit/Auth/restricted`

Contains flag about whether Auth/DataSet is restricted

- id: <http://www.purl.org/ogit/Auth/restricted>
- valid-from: Mon Jan 01 00:00:00 UTC 2018
- creator: arago GmbH

used

- optional:
 - [ogit/Auth/DataSet](#)

2.3.0.118 ogit/validTo

Defines a point in time when something stops being valid.

- id: <http://www.purl.org/ogit/validTo>
- valid-from: Tue Nov 29 00:00:00 UTC 2016
- creator: stravlos@arago.co

used

- optional:
 - [ogit/Contract](#)

2.3.0.119 ogit/Auth/Application/status

Status of an application

- id: <http://www.purl.org/ogit/Auth/Application/status>
- valid-from: Mon Jan 01 00:00:00 UTC 2018
- creator: arago GmbH

used

- optional:
 - [ogit/Auth/Application](#)