

---

Datacenter

---

June 3, 2019

<b>1 Module Documentation</b>	<b>1</b>
1.1 Entities	1
1.1.0.1 ogit/Organization	1
1.1.0.2 ogit/Datacenter/UPS	2
1.1.0.3 ogit/Datacenter/Section	2
1.1.0.4 ogit/Person	3
1.1.0.5 ogit/Datacenter/Rack	4
1.1.0.6 ogit/Datacenter/Storage	5
1.1.0.7 ogit/Datacenter/Server	5
1.1.0.8 ogit/Datacenter/Datacenter	6
1.1.0.9 ogit/Datacenter/Cooling	7
1.1.0.10 ogit/ConfigurationItem	7
1.1.0.11 ogit/Location	9
1.1.0.12 ogit/Datacenter/Building	10
1.1.0.13 ogit/Asset	10
1.1.0.14 ogit/Datacenter/Sensor	11
1.1.0.15 ogit/Datacenter/PowerDistributionUnit	11
1.1.0.16 ogit/Device	12
1.1.0.17 ogit/Datacenter/Room	13
1.1.0.18 ogit/Timeseries	14
1.2 Verbs	15
1.2.0.1 ogit/contains	15
1.2.0.2 ogit/manages	15
1.2.0.3 ogit/generates	16
1.2.0.4 ogit/describes	16
1.2.0.5 ogit/connects	17
1.2.0.6 ogit/locatedIn	17
1.2.0.7 ogit/corresponds	17
1.2.0.8 ogit/relates	17
1.3 Attributes	18
1.3.0.1 ogit/ciType	18
1.3.0.2 ogit/category	18
1.3.0.3 ogit/comment	18
1.3.0.4 ogit/assignedAt	19
1.3.0.5 ogit/endOfWarranty	19
1.3.0.6 ogit/postalCode	19
1.3.0.7 ogit/productOrderNumber	20
1.3.0.8 ogit/checkedOutAt	20
1.3.0.9 ogit/email	20
1.3.0.10 ogit/deliveredAt	21
1.3.0.11 ogit/alternativeName	21
1.3.0.12 ogit/isCritical	21

1.3.0.13 ogit/asset	22
1.3.0.14 ogit/function	22
1.3.0.15 ogit/Datacenter/sectionId	22
1.3.0.16 ogit/integrity	23
1.3.0.17 ogit/Datacenter/rackId	23
1.3.0.18 ogit/country	23
1.3.0.19 ogit/Datacenter/roomId	24
1.3.0.20 ogit/businessCategory	24
1.3.0.21 ogit/Datacenter/datacenterId	24
1.3.0.22 ogit/notification	25
1.3.0.23 ogit/weight	25
1.3.0.24 ogit/sourceId	25
1.3.0.25 ogit/purchasedAt	26
1.3.0.26 ogit/mobilePhone	26
1.3.0.27 ogit/purchaseDate	26
1.3.0.28 ogit/startedAt	27
1.3.0.29 ogit/assetTag	27
1.3.0.30 ogit/unit	27
1.3.0.31 ogit/installedAt	28
1.3.0.32 ogit/updateCount	28
1.3.0.33 ogit/installStatus	28
1.3.0.34 ogit/city	29
1.3.0.35 ogit/status	29
1.3.0.36 ogit/createdAt	29
1.3.0.37 ogit/model	30
1.3.0.38 ogit/lastName	30
1.3.0.39 ogit/priority	30
1.3.0.40 ogit/shortDescription	31
1.3.0.41 ogit/middleName	31
1.3.0.42 ogit/invoiceNumber	31
1.3.0.43 ogit/soxClass	32
1.3.0.44 ogit/streetAddress	32
1.3.0.45 ogit/businessCriticality	32
1.3.0.46 ogit/brand	33
1.3.0.47 ogit/leaseContract	33
1.3.0.48 ogit/Datacenter/moveProductionDate	33
1.3.0.49 ogit/securityClass	34
1.3.0.50 ogit/firstName	34
1.3.0.51 ogit/version	34
1.3.0.52 ogit/title	35
1.3.0.53 ogit/class	35
1.3.0.54 ogit/content	35

---

1.3.0.55 ogit/confidentiality . . . . .	36
1.3.0.56 ogit/name . . . . .	36
1.3.0.57 ogit/description . . . . .	36
1.3.0.58 ogit/externalId . . . . .	37
1.3.0.59 ogit/impact . . . . .	37
1.3.0.60 ogit/contact . . . . .	37
1.3.0.61 ogit/orderedAt . . . . .	38
1.3.0.62 ogit/faultCount . . . . .	38
1.3.0.63 ogit/officePhone . . . . .	38
1.3.0.64 ogit/phone . . . . .	39
1.3.0.65 ogit/fax . . . . .	39
1.3.0.66 ogit/type . . . . .	39
1.3.0.67 ogit/capacity . . . . .	40
1.3.0.68 ogit/otherPhone . . . . .	40
1.3.0.69 ogit/subCategory . . . . .	40
1.3.0.70 ogit/Datacenter/rackUnit . . . . .	41
1.3.0.71 ogit/availability . . . . .	41
1.3.0.72 ogit/lastScannedAt . . . . .	41
1.3.0.73 ogit/subType . . . . .	41
1.3.0.74 ogit/pendingChange . . . . .	42
1.3.0.75 ogit/inventoryNumber . . . . .	42
1.3.0.76 ogit/webPage . . . . .	42
1.3.0.77 ogit/lastUpdatedAt . . . . .	43
1.3.0.78 ogit/modelNumber . . . . .	43
1.3.0.79 ogit/powerConsumption . . . . .	43
1.3.0.80 ogit/id . . . . .	44
1.3.0.81 ogit/checkedInAt . . . . .	44
1.3.0.82 ogit/serviceContract . . . . .	45
1.3.0.83 ogit/vendor . . . . .	45
1.3.0.84 ogit/Automation/governingContract . . . . .	45
1.3.0.85 ogit/position . . . . .	46
1.3.0.86 ogit/buildingId . . . . .	46
1.3.0.87 ogit/instance . . . . .	46
1.3.0.88 ogit/isSupported . . . . .	47
1.3.0.89 ogit/operationalStatus . . . . .	47

# Chapter 1

## Module Documentation

### 1.1 Entities

#### 1.1.0.1 ogit/Organization

An identity that represents an organization, company, or some other grouping of Person objects. Entities of this type should be created with a predefined ID. Those IDs should be named like a domain name, i.e. a concatenation of some strings separated with a dot. If organization data is created from a LDAP then a mapping like "cn=John Doe,dc=example,dc=com" => "john\_doe.example.com" should be employed. The ogit/function attribute should be used to tell what kind of grouping an entity of type Organization is: company, department, group, ...

- id: <http://www.purl.org/ogit/Organization>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: SGO
- parent: ogit/Node

#### attributes

- mandatory:
  - [ogit/name](#)
- optional:
  - [ogit/businessCategory](#)
  - [ogit/city](#)
  - [ogit/country](#)
  - [ogit/description](#)
  - [ogit/email](#)
  - [ogit/function](#)
  - [ogit/phone](#)
  - [ogit/postalCode](#)
  - [ogit/sourceId](#)
  - [ogit/status](#)
  - [ogit/streetAddress](#)
  - [ogit/webPage](#)

## outgoing edges

- `ogit/manages => ogit/Datacenter/Room`
- `ogit/manages => ogit/Datacenter/Rack`
- `ogit/manages => ogit/Datacenter/Datacenter`
- `ogit/manages => ogit/Datacenter/Cooling`
- `ogit/manages => ogit/Datacenter/Building`

## 1.1.0.2 ogit/Datacenter/UPS

A physical UPS device (Uninterruptible power supply)

- id: <http://www.purl.org/ogit/Datacenter/UPS>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: NTO
- parent: ogit/Node

## attributes

- optional:
  - `ogit/id`

## incoming edges

- `ogit/connects <= ogit/Device`

## outgoing edges

- `ogit/corresponds => ogit/Device`

## 1.1.0.3 ogit/Datacenter/Section

A physical/logical Section within a Room

- id: <http://www.purl.org/ogit/Datacenter/Section>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: NTO
- parent: ogit/Node

**attributes**

- optional:
  - [ogit/capacity](#)
  - [ogit/id](#)

**incoming edges**

- [ogit/contains](#) <= [ogit/Datacenter/Room](#)

**outgoing edges**

- [ogit/contains](#) => [ogit/Datacenter/Sensor](#)
- [ogit/contains](#) => [ogit/Datacenter/Rack](#)

**1.1.0.4 ogit/Person**

A Person represents a human identity.

- id: <http://www.purl.org/ogit/Person>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: SGO
- parent: [ogit/Node](#)

**attributes**

- optional:
  - [ogit/alternativeName](#)
  - [ogit/email](#)
  - [ogit/fax](#)
  - [ogit/firstName](#)
  - [ogit/lastName](#)
  - [ogit/middleName](#)
  - [ogit/mobilePhone](#)
  - [ogit/notification](#)
  - [ogit/officePhone](#)
  - [ogit/otherPhone](#)
  - [ogit/position](#)
  - [ogit/sourceId](#)
  - [ogit/status](#)
  - [ogit/title](#)
  - [ogit/webPage](#)

**outgoing edges**

- `ogit/manages => ogit/Datacenter/Room`
- `ogit/manages => ogit/Datacenter/Rack`
- `ogit/manages => ogit/Datacenter/Datacenter`
- `ogit/manages => ogit/Datacenter/Cooling`
- `ogit/manages => ogit/Datacenter/Building`

**1.1.0.5 ogit/Datacenter/Rack**

A physical rack housing datacenter equipment

- `id: http://www.purl.org/ogit/Datacenter/Rack`
- `valid-from: Thu May 21 00:00:00 UTC 2015`
- `creator: Peter Larem`
- `scope: NTO`
- `parent: ogit/Node`

**attributes**

- `optional:`
  - `ogit/Datacenter/moveProductionDate`
  - `ogit/Datacenter/roomId`
  - `ogit/brand`
  - `ogit/capacity`
  - `ogit/endOfWarranty`
  - `ogit/id`
  - `ogit/model`
  - `ogit/powerConsumption`
  - `ogit/purchaseDate`
  - `ogit/weight`

**incoming edges**

- `ogit/contains <= ogit/Datacenter/Room`
- `ogit/contains <= ogit/Datacenter/Section`
- `ogit/describes <= ogit/Asset`
- `ogit/manages <= ogit/Organization`
- `ogit/manages <= ogit/Person`



## outgoing edges

- [ogit/contains](#) => [ogit/Datacenter/Sensor](#)
- [ogit/contains](#) => [ogit/Datacenter/PowerDistributionUnit](#)
- [ogit/contains](#) => [ogit/Device](#)

1.1.0.6 [ogit/Datacenter/Storage](#)

A physical/logical Storage Unit

- id: <http://www.purl.org/ogit/Datacenter/Storage>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: NTO
- parent: [ogit/Node](#)

## attributes

- optional:
  - [ogit/Datacenter/moveProductionDate](#)
  - [ogit/brand](#)
  - [ogit/endOfWarranty](#)
  - [ogit/id](#)
  - [ogit/model](#)
  - [ogit/purchaseDate](#)

## outgoing edges

- [ogit/corresponds](#) => [ogit/Device](#)

1.1.0.7 [ogit/Datacenter/Server](#)

A physical/logical Server

- id: <http://www.purl.org/ogit/Datacenter/Server>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: NTO
- parent: [ogit/Node](#)

**attributes**

- optional:
  - [ogit/Datacenter/moveProductionDate](#)
  - [ogit/brand](#)
  - [ogit/endOfWarranty](#)
  - [ogit/id](#)
  - [ogit/model](#)
  - [ogit/purchaseDate](#)

**incoming edges**

- [ogit/relates](#) <= [ogit/ConfigurationItem](#)

**outgoing edges**

- [ogit/corresponds](#) => [ogit/Device](#)
- [ogit/generates](#) => [ogit/Timeseries](#)

**1.1.0.8 ogit/Datacenter/Datacenter**

Represents a datacenter

- id: <http://www.purl.org/ogit/Datacenter/Datacenter>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: NTO
- parent: [ogit/Node](#)

**attributes**

- optional:
  - [ogit/capacity](#)
  - [ogit/id](#)

**incoming edges**

- [ogit/contains](#) <= [ogit/Datacenter/Building](#)
- [ogit/manages](#) <= [ogit/Organization](#)
- [ogit/manages](#) <= [ogit/Person](#)

## outgoing edges

- [ogit/locatedIn](#) => [ogit/Location](#)

1.1.0.9 [ogit/Datacenter/Cooling](#)

A physical Cooling Unit used for data centers and computer rooms

- id: <http://www.purl.org/ogit/Datacenter/Cooling>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: NTO
- parent: [ogit/Node](#)

## attributes

- optional:
  - [ogit/Datacenter/roomId](#)
  - [ogit/capacity](#)
  - [ogit/id](#)
  - [ogit/powerConsumption](#)

## incoming edges

- [ogit/contains](#) <= [ogit/Datacenter/Room](#)
- [ogit/describes](#) <= [ogit/Asset](#)
- [ogit/manages](#) <= [ogit/Organization](#)
- [ogit/manages](#) <= [ogit/Person](#)

1.1.0.10 [ogit/ConfigurationItem](#)

A configuration item.

- id: <http://www.purl.org/ogit/ConfigurationItem>
- valid-from: Thu Jun 11 00:00:00 UTC 2015
- creator: Aymen Ayoub
- scope: SGO
- parent: [ogit/Node](#)

**attributes**

- mandatory:
  - [ogit/id](#)
- optional:
  - [ogit/Automation/governingContract](#)
  - [ogit/asset](#)
  - [ogit/assetTag](#)
  - [ogit/assignedAt](#)
  - [ogit/availability](#)
  - [ogit/businessCriticality](#)
  - [ogit/category](#)
  - [ogit/checkedInAt](#)
  - [ogit/checkedOutAt](#)
  - [ogit/ciType](#)
  - [ogit/class](#)
  - [ogit/comment](#)
  - [ogit/confidentiality](#)
  - [ogit/contact](#)
  - [ogit/content](#)
  - [ogit/createdAt](#)
  - [ogit/deliveredAt](#)
  - [ogit/description](#)
  - [ogit/endOfWarranty](#)
  - [ogit/externalId](#)
  - [ogit/faultCount](#)
  - [ogit/impact](#)
  - [ogit/installStatus](#)
  - [ogit/installedAt](#)
  - [ogit/integrity](#)
  - [ogit/inventoryNumber](#)
  - [ogit/invoiceNumber](#)
  - [ogit/isCritical](#)
  - [ogit/isSupported](#)
  - [ogit/lastScannedAt](#)
  - [ogit/lastUpdatedAt](#)
  - [ogit/leaseContract](#)
  - [ogit/model](#)
  - [ogit/modelNumber](#)
  - [ogit/name](#)
  - [ogit/operationalStatus](#)
  - [ogit/orderedAt](#)
  - [ogit/pendingChange](#)
  - [ogit/priority](#)

- [ogit/productOrderNumber](#)
- [ogit/purchasedAt](#)
- [ogit/securityClass](#)
- [ogit/serviceContract](#)
- [ogit/shortDescription](#)
- [ogit/soxClass](#)
- [ogit/startedAt](#)
- [ogit/status](#)
- [ogit/subCategory](#)
- [ogit/subType](#)
- [ogit/type](#)
- [ogit/updateCount](#)
- [ogit/vendor](#)
- [ogit/version](#)

#### outgoing edges

- [ogit/relates](#) => [ogit/Datacenter/Server](#)

#### 1.1.0.11 [ogit/Location](#)

A place where some service is offered or requested. In many cases this will be related to a address of an Organization. Similar to <http://purl.org/goodrelations/v1#Location>

- id: <http://www.purl.org/ogit/Location>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: SGO
- parent: [ogit/Node](#)

#### attributes

- mandatory:
  - [ogit/name](#)
- optional:
  - [ogit/description](#)

#### incoming edges

- [ogit/locatedIn](#) <= [ogit/Datacenter/Datacenter](#)

## 1.1.0.12 ogit/Datacenter/Building

A physical Building within a location

- id: <http://www.purl.org/ogit/Datacenter/Building>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: NTO
- parent: ogit/Node

## attributes

- optional:
  - [ogit/Datacenter/datacenterId](#)
  - [ogit/capacity](#)
  - [ogit/id](#)

## incoming edges

- [ogit/manages](#) <= [ogit/Organization](#)
- [ogit/manages](#) <= [ogit/Person](#)

## outgoing edges

- [ogit/contains](#) => [ogit/Datacenter/Datacenter](#)
- [ogit/contains](#) => [ogit/Datacenter/Room](#)

## 1.1.0.13 ogit/Asset

Assets represent a physical hold of a value and are situated in a location. Assets could correspond to one or more ogit/Automation/MARSNode's and can be physical or virtual. Assets of a Service Provider include anything that could contribute to the delivery of a Service. Assets can have a type, for example: Management, Organisation, Process, Knowledge, People, Information, Applications, Infrastructure, Financial Capital.

- id: <http://www.purl.org/ogit/Asset>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: SGO
- parent: ogit/Node

**attributes**

- optional:
  - [ogit/id](#)
  - [ogit/name](#)

**outgoing edges**

- [ogit/describes](#) => [ogit/Datacenter/Rack](#)
- [ogit/describes](#) => [ogit/Datacenter/PowerDistributionUnit](#)
- [ogit/describes](#) => [ogit/Datacenter/Cooling](#)

**1.1.0.14 ogit/Datacenter/Sensor**

A sensor is a device that measures a physical quantity and converts it into a 'signal' which can be read by an observer or by an instrument.

- id: <http://www.purl.org/ogit/Datacenter/Sensor>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: NTO
- parent: ogit/Node

**attributes**

- optional:
  - [ogit/Datacenter/sectionId](#)
  - [ogit/id](#)

**incoming edges**

- [ogit/contains](#) <= [ogit/Datacenter/Rack](#)
- [ogit/contains](#) <= [ogit/Datacenter/Room](#)
- [ogit/contains](#) <= [ogit/Datacenter/Section](#)
- [ogit/contains](#) <= [ogit/Device](#)

**1.1.0.15 ogit/Datacenter/PowerDistributionUnit**

A PDU is a physical device for connecting datacenter devices with power sources

- id: <http://www.purl.org/ogit/Datacenter/PowerDistributionUnit>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: NTO
- parent: ogit/Node

**attributes**

- optional:
  - [ogit/Datacenter/rackId](#)
  - [ogit/capacity](#)
  - [ogit/id](#)

**incoming edges**

- [ogit/connects](#) <= [ogit/Device](#)
- [ogit/contains](#) <= [ogit/Datacenter/Rack](#)
- [ogit/describes](#) <= [ogit/Asset](#)

**1.1.0.16 ogit/Device****Any type of device**

- id: <http://www.purl.org/ogit/Device>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: SGO
- parent: [ogit/Node](#)

**attributes**

- optional:
  - [ogit/Datacenter/moveProductionDate](#)
  - [ogit/endOfWarranty](#)
  - [ogit/id](#)
  - [ogit/name](#)
  - [ogit/powerConsumption](#)
  - [ogit/purchaseDate](#)

**incoming edges**

- [ogit/contains](#) <= [ogit/Datacenter/Rack](#)
- [ogit/corresponds](#) <= [ogit/Datacenter/Server](#)
- [ogit/corresponds](#) <= [ogit/Datacenter/Storage](#)
- [ogit/corresponds](#) <= [ogit/Datacenter/UPS](#)



## outgoing edges

- [ogit/connects](#) => [ogit/Datacenter/PowerDistributionUnit](#)
- [ogit/connects](#) => [ogit/Datacenter/UPS](#)
- [ogit/contains](#) => [ogit/Datacenter/Sensor](#)

1.1.0.17 [ogit/Datacenter/Room](#)

A physical Room within a Building

- id: <http://www.purl.org/ogit/Datacenter/Room>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: NTO
- parent: [ogit/Node](#)

## attributes

- optional:
  - [ogit/buildingId](#)
  - [ogit/capacity](#)
  - [ogit/id](#)

## incoming edges

- [ogit/contains](#) <= [ogit/Datacenter/Building](#)
- [ogit/manages](#) <= [ogit/Organization](#)
- [ogit/manages](#) <= [ogit/Person](#)

## outgoing edges

- [ogit/contains](#) => [ogit/Datacenter/Rack](#)
- [ogit/contains](#) => [ogit/Datacenter/Cooling](#)
- [ogit/contains](#) => [ogit/Datacenter/Sensor](#)
- [ogit/contains](#) => [ogit/Datacenter/Section](#)

## 1.1.0.18 ogit/Timeseries

A time series is a sequence of data points, measured typically at successive points in time spaced at uniform time intervals.

- id: <http://www.purl.org/ogit/Timeseries>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem
- scope: SGO
- parent: ogit/Node

## attributes

- optional:
  - [ogit/description](#)
  - [ogit/instance](#)
  - [ogit/name](#)
  - [ogit/unit](#)

## incoming edges

- [ogit/generates](#) <= [ogit/Datacenter/Server](#)

## 1.2 Verbs

### 1.2.0.1 ogit/contains

This relationship indicates that something is part of something else. see also "includes"

- id: <http://www.purl.org/ogit/contains>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

#### Allowed Connection

- [ogit/Datacenter/Building](#) => [ogit/Datacenter/Datacenter](#)
- [ogit/Datacenter/Building](#) => [ogit/Datacenter/Room](#)
- [ogit/Datacenter/Rack](#) => [ogit/Datacenter/Sensor](#)
- [ogit/Datacenter/Rack](#) => [ogit/Datacenter/PowerDistributionUnit](#)
- [ogit/Datacenter/Rack](#) => [ogit/Device](#)
- [ogit/Datacenter/Room](#) => [ogit/Datacenter/Rack](#)
- [ogit/Datacenter/Room](#) => [ogit/Datacenter/Cooling](#)
- [ogit/Datacenter/Room](#) => [ogit/Datacenter/Sensor](#)
- [ogit/Datacenter/Room](#) => [ogit/Datacenter/Section](#)
- [ogit/Datacenter/Section](#) => [ogit/Datacenter/Sensor](#)
- [ogit/Datacenter/Section](#) => [ogit/Datacenter/Rack](#)
- [ogit/Device](#) => [ogit/Datacenter/Sensor](#)

### 1.2.0.2 ogit/manages

This relationship indicates that one entity manages some other.

- id: <http://www.purl.org/ogit/manages>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

**Allowed Connection**

- [ogit/Organization](#) => [ogit/Datacenter/Room](#)
- [ogit/Organization](#) => [ogit/Datacenter/Rack](#)
- [ogit/Organization](#) => [ogit/Datacenter/Datacenter](#)
- [ogit/Organization](#) => [ogit/Datacenter/Cooling](#)
- [ogit/Organization](#) => [ogit/Datacenter/Building](#)
- [ogit/Person](#) => [ogit/Datacenter/Room](#)
- [ogit/Person](#) => [ogit/Datacenter/Rack](#)
- [ogit/Person](#) => [ogit/Datacenter/Datacenter](#)
- [ogit/Person](#) => [ogit/Datacenter/Cooling](#)
- [ogit/Person](#) => [ogit/Datacenter/Building](#)

**1.2.0.3 ogit/generates**

Verb indicating if an entity generates another entity.

- id: <http://www.purl.org/ogit/generates>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

**Allowed Connection**

- [ogit/Datacenter/Server](#) => [ogit/Timeseries](#)

**1.2.0.4 ogit/describes**

This relationship allows to associate additional information with an entity. The "described" node can have many "describing" nodes.

- id: <http://www.purl.org/ogit/describes>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

**Allowed Connection**

- [ogit/Asset](#) => [ogit/Datacenter/Rack](#)
- [ogit/Asset](#) => [ogit/Datacenter/PowerDistributionUnit](#)
- [ogit/Asset](#) => [ogit/Datacenter/Cooling](#)

#### 1.2.0.5 ogit/connects

Verb showing that an entity is physically/virtually connecting to another entity.

- id: <http://www.purl.org/ogit/connects>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

##### Allowed Connection

- [ogit/Device](#) => [ogit/Datacenter/PowerDistributionUnit](#)
- [ogit/Device](#) => [ogit/Datacenter/UPS](#)

#### 1.2.0.6 ogit/locatedIn

indicate that something has its place somewhere

- id: <http://www.purl.org/ogit/locatedIn>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

##### Allowed Connection

- [ogit/Datacenter/Datacenter](#) => [ogit/Location](#)

#### 1.2.0.7 ogit/corresponds

Indicates whether one entity could correspond to a more general one, e.g. an Incident could correspond to a Ticket

- id: <http://www.purl.org/ogit/corresponds>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

##### Allowed Connection

- [ogit/Datacenter/Server](#) => [ogit/Device](#)
- [ogit/Datacenter/Storage](#) => [ogit/Device](#)
- [ogit/Datacenter/UPS](#) => [ogit/Device](#)

#### 1.2.0.8 ogit/relates

General relationship indicating that one entity is related to another one.

- id: <http://www.purl.org/ogit/relates>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

##### Allowed Connection

- [ogit/ConfigurationItem](#) => [ogit/Datacenter/Server](#)

## 1.3 Attributes

### 1.3.0.1 ogit/ciType

Type of a configuration item. For example: VM, Server or Device.

- id: <http://www.purl.org/ogit/ciType>
- valid-from: Thu Aug 20 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

### 1.3.0.2 ogit/category

Used to categorize things.

- id: <http://www.purl.org/ogit/category>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ConfigurationItem](#)

### 1.3.0.3 ogit/comment

Contains a comment.

- id: <http://www.purl.org/ogit/comment>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

#### 1.3.0.4 ogit/assignedAt

Defines the time when something was actually assigned to a person/organization for example. The values can combine date and time with time zone designator according to ISO 8601.

- id: <http://www.purl.org/ogit/assignedAt>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

#### 1.3.0.5 ogit/endOfWarranty

End of warranty phase of a component

- id: <http://www.purl.org/ogit/endOfWarranty>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ConfigurationItem](#)
  - [ogit/Datacenter/Rack](#)
  - [ogit/Datacenter/Server](#)
  - [ogit/Datacenter/Storage](#)
  - [ogit/Device](#)

#### 1.3.0.6 ogit/postalCode

The postal code. For example, 60433.

- id: <http://www.purl.org/ogit/postalCode>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Organization](#)

#### 1.3.0.7 ogit/productOrderNumber

An integer, which displays the order number of a product.

- id: <http://www.purl.org/ogit/productOrderNumber>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

#### 1.3.0.8 ogit/checkedOutAt

Defines the time when something was actually checked out. The values can combine date and time with time zone designator according to ISO 8601.

- id: <http://www.purl.org/ogit/checkedOutAt>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

#### 1.3.0.9 ogit/email

An email address.

- id: <http://www.purl.org/ogit/email>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Organization](#)
  - [ogit/Person](#)



#### 1.3.0.10 ogit/deliveredAt

Defines a point in time when a component/device was actually delivered. The values must be combined date and time with time zone designator according to ISO 8601

- id: <http://www.purl.org/ogit/deliveredAt>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

#### 1.3.0.11 ogit/alternativeName

Alternative name of something. In context of a Person this can be the full name or an alias/nick name.

- id: <http://www.purl.org/ogit/alternativeName>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Person](#)

#### 1.3.0.12 ogit/isCritical

This field specifies if the CI is critical for day-to-day operation, such as an E-mail server or RDBMS server. If you open an incident on a critical CI, the incident indicates that this is a critical CI. This field contains a boolean value.

- id: <http://www.purl.org/ogit/isCritical>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

#### 1.3.0.13 ogit/asset

This field represents an asset (device or component).

- id: <http://www.purl.org/ogit/asset>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

#### 1.3.0.14 ogit/function

Attribute used to specify a function that some entity does/provides. This is more specific than 'description'. Should contain a short string. At this level of specification it is still a free from string. However, unlike 'description', it is expected to contain some list of fixed values.

- id: <http://www.purl.org/ogit/function>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Organization](#)

#### 1.3.0.15 ogit/Datacenter/sectionId

ID of a datacenter section.

- id: <http://www.purl.org/ogit/Datacenter/sectionId>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Datacenter/Sensor](#)

**1.3.0.16 ogit/integrity**

A security principle that ensures data and Configuration Items are only modified by authorized personnel and Activities

- id: <http://www.purl.org/ogit/integrity>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

**1.3.0.17 ogit/Datacenter/rackId**

ID of a rack within a datacenter.

- id: <http://www.purl.org/ogit/Datacenter/rackId>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Datacenter/PowerDistributionUnit](#)

**1.3.0.18 ogit/country**

Name of a country.

- id: <http://www.purl.org/ogit/country>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Philipp Pelchmann

used

- optional:
  - [ogit/Organization](#)

1.3.0.19 `ogit/Datacenter/roomId`

ID of a Room in a Datacenter.

- id: <http://www.purl.org/ogit/Datacenter/roomId>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Datacenter/Cooling](#)
  - [ogit/Datacenter/Rack](#)

1.3.0.20 `ogit/businessCategory`

The category of a business.

- id: <http://www.purl.org/ogit/businessCategory>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Philipp Pelchmann

used

- optional:
  - [ogit/Organization](#)

1.3.0.21 `ogit/Datacenter/datacenterId`

ID of a Datacenter

- id: <http://www.purl.org/ogit/Datacenter/datacenterId>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Datacenter/Building](#)

## 1.3.0.22 ogit/notification

A notification.

- id: <http://www.purl.org/ogit/notification>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Philipp Pelchmann

used

- optional:
  - [ogit/Person](#)

## 1.3.0.23 ogit/weight

Physical weight of an entity, e.g. device/component/rack

- id: <http://www.purl.org/ogit/weight>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Datacenter/Rack](#)

## 1.3.0.24 ogit/sourceId

The Id of the source system.

- id: <http://www.purl.org/ogit/sourceId>
- valid-from: Thu Jun 11 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Organization](#)
  - [ogit/Person](#)

#### 1.3.0.25 ogit/purchasedAt

Defines a point in time when a component/device was actually purchased. The values must be combined date and time with time zone designator according to ISO 8601

- id: <http://www.purl.org/ogit/purchasedAt>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

#### 1.3.0.26 ogit/mobilePhone

A mobile phone number.

- id: <http://www.purl.org/ogit/mobilePhone>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Person](#)

#### 1.3.0.27 ogit/purchaseDate

Date of purchase of a device.

- id: <http://www.purl.org/ogit/purchaseDate>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Datacenter/Rack](#)
  - [ogit/Datacenter/Server](#)
  - [ogit/Datacenter/Storage](#)
  - [ogit/Device](#)

**1.3.0.28** ogit/startedAt

Defines a point in time when the work on a change, task, or similar entity was actually started. The values must be combined date and time with time zone designator according to ISO 8601

- id: <http://www.purl.org/ogit/startedAt>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ConfigurationItem](#)

**1.3.0.29** ogit/assetTag

This field specifies the asset tag number/code.

- id: <http://www.purl.org/ogit/assetTag>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

**1.3.0.30** ogit/unit

Unit of measurement of some value.

- id: <http://www.purl.org/ogit/unit>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Timeseries](#)

**1.3.0.31 ogit/installedAt**

Defines a point in time when a component/device was actually installed. The values must be combined date and time with time zone designator according to ISO 8601

- id: <http://www.purl.org/ogit/installedAt>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

**1.3.0.32 ogit/updateCount**

Contains the count of the records updated.

- id: <http://www.purl.org/ogit/updateCount>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

**1.3.0.33 ogit/installStatus**

An installation status for an entity. At this level of specification no list of values is specified. However, applications using this attribute are expected to allow only a fixed list of values that seems useful in the application's semantic context.

- id: <http://www.purl.org/ogit/installStatus>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)



1.3.0.34 `ogit/city`

Name of a city.

- id: <http://www.purl.org/ogit/city>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Philipp Pelchmann

used

- optional:
  - [ogit/Organization](#)

1.3.0.35 `ogit/status`

A status for an entity. At this level of specification no list of values is specified. However, applications using this attribute are expected to allow only a fixed list of values that seems usefual in the application's semantic context.

- id: <http://www.purl.org/ogit/status>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ConfigurationItem](#)
  - [ogit/Organization](#)
  - [ogit/Person](#)

1.3.0.36 `ogit/createdAt`

Defines a point in time when a ticket/incident/event etc was created or recorded.

- id: <http://www.purl.org/ogit/createdAt>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ConfigurationItem](#)

## 1.3.0.37 ogit/model

Model of a device.

- id: <http://www.purl.org/ogit/model>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ConfigurationItem](#)
  - [ogit/Datacenter/Rack](#)
  - [ogit/Datacenter/Server](#)
  - [ogit/Datacenter/Storage](#)

## 1.3.0.38 ogit/lastName

Last name of a person.

- id: <http://www.purl.org/ogit/lastName>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Person](#)

## 1.3.0.39 ogit/priority

Priority of a ticket. The actual semantics might depend on the ticket type (Incident, Service Request, ...)

- id: <http://www.purl.org/ogit/priority>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ConfigurationItem](#)

#### 1.3.0.40 ogit/shortDescription

Contains a short description.

- id: <http://www.purl.org/ogit/shortDescription>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

#### 1.3.0.41 ogit/middleName

Middle name of a person.

- id: <http://www.purl.org/ogit/middleName>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Philipp Pelchmann

used

- optional:
  - [ogit/Person](#)

#### 1.3.0.42 ogit/invoiceNumber

Contains an invoice number. This number is used as identifier for security purposes.

- id: <http://www.purl.org/ogit/invoiceNumber>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

#### 1.3.0.43 ogit/soxClass

This attribute specifies, if an entity has a Sarbanes Oxley (SOX) classification that applies to it. The out-of-box data is: Critical or Non Critical

- id: <http://www.purl.org/ogit/soxClass>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

#### 1.3.0.44 ogit/streetAddress

The street address. For example, Eschersheimer Landstr. 526-532

- id: <http://www.purl.org/ogit/streetAddress>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Organization](#)

#### 1.3.0.45 ogit/businessCriticality

The business criticality of a process/service/CI.

- id: <http://www.purl.org/ogit/businessCriticality>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

**1.3.0.46 ogit/brand**

Brand/Manufacturer of a component/device.

- id: <http://www.purl.org/ogit/brand>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Datacenter/Rack](#)
  - [ogit/Datacenter/Server](#)
  - [ogit/Datacenter/Storage](#)

**1.3.0.47 ogit/leaseContract**

This field specifies the lease contract covering a service.

- id: <http://www.purl.org/ogit/leaseContract>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

**1.3.0.48 ogit/Datacenter/moveProductionDate**

Date when an device is moved to production use.

- id: <http://www.purl.org/ogit/Datacenter/moveProductionDate>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Datacenter/Rack](#)
  - [ogit/Datacenter/Server](#)
  - [ogit/Datacenter/Storage](#)
  - [ogit/Device](#)

#### 1.3.0.49 ogit/securityClass

Contains the security class of an entity/device.

- id: <http://www.purl.org/ogit/securityClass>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

#### 1.3.0.50 ogit/firstName

First name of a person

- id: <http://www.purl.org/ogit/firstName>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Person](#)

#### 1.3.0.51 ogit/version

Any string representation of version information. no restrictions are imposed on that base attribute

- id: <http://www.purl.org/ogit/version>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ConfigurationItem](#)

## 1.3.0.52 ogit/title

Title of any kind. In the context of a Person this can be a courtesy title, an academic title, or a job title.

- id: <http://www.purl.org/ogit/title>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Person](#)

## 1.3.0.53 ogit/class

Class of a component/device.

- id: <http://www.purl.org/ogit/class>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

## 1.3.0.54 ogit/content

A string holding any type of content: plain string, XML fragments, RDF documents, ...

- id: <http://www.purl.org/ogit/content>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ConfigurationItem](#)

**1.3.0.55 ogit/confidentiality**

Contains information about the confidentiality related to a device or an entity.

- id: <http://www.purl.org/ogit/confidentiality>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

**1.3.0.56 ogit/name**

Contains a name.

- id: <http://www.purl.org/ogit/name>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- mandatory:
  - [ogit/Location](#)
  - [ogit/Organization](#)
- optional:
  - [ogit/Asset](#)
  - [ogit/ConfigurationItem](#)
  - [ogit/Device](#)
  - [ogit/Timeseries](#)

**1.3.0.57 ogit/description**

Contains a description.

- id: <http://www.purl.org/ogit/description>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ConfigurationItem](#)
  - [ogit/Location](#)
  - [ogit/Organization](#)
  - [ogit/Timeseries](#)



**1.3.0.58 ogit/externalId**

The External Id of a component.

- id: <http://www.purl.org/ogit/externalId>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

**1.3.0.59 ogit/impact**

Will contain the impact, for example of a ticket. In this case the actual semantics would depend on the ticket type, which could correspond to an Incident, Service Request, etc.

- id: <http://www.purl.org/ogit/impact>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ConfigurationItem](#)

**1.3.0.60 ogit/contact**

This field displays the device/CI/component owner who is the person assigned to the device/CI/component and uses it on a day-to-day basis. Support contacts are secondary contacts who may have access to a CI for example.

- id: <http://www.purl.org/ogit/contact>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

**1.3.0.61 ogit/orderedAt**

Defines a point in time when a component/device was actually ordered. The values must be combined date and time with time zone designator according to ISO 8601

- id: <http://www.purl.org/ogit/orderedAt>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

**1.3.0.62 ogit/faultCount**

Contains fault count related to a component

- id: <http://www.purl.org/ogit/faultCount>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

**1.3.0.63 ogit/officePhone**

The phone number in the office.

- id: <http://www.purl.org/ogit/officePhone>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Philipp Pelchmann

used

- optional:
  - [ogit/Person](#)

#### 1.3.0.64 ogit/phone

a phone number

- id: <http://www.purl.org/ogit/phone>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Organization](#)

#### 1.3.0.65 ogit/fax

The number of a fax.

- id: <http://www.purl.org/ogit/fax>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Philipp Pelchmann

used

- optional:
  - [ogit/Person](#)

#### 1.3.0.66 ogit/type

Type of an an entity.

- id: <http://www.purl.org/ogit/type>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ConfigurationItem](#)

#### 1.3.0.67 ogit/capacity

General Capacity

- id: <http://www.purl.org/ogit/capacity>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Datacenter/Building](#)
  - [ogit/Datacenter/Cooling](#)
  - [ogit/Datacenter/Datacenter](#)
  - [ogit/Datacenter/PowerDistributionUnit](#)
  - [ogit/Datacenter/Rack](#)
  - [ogit/Datacenter/Room](#)
  - [ogit/Datacenter/Section](#)

#### 1.3.0.68 ogit/otherPhone

The number of an other phone.

- id: <http://www.purl.org/ogit/otherPhone>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Philipp Pelchmann

used

- optional:
  - [ogit/Person](#)

#### 1.3.0.69 ogit/subCategory

Used to give a subcategory to things.

- id: <http://www.purl.org/ogit/subCategory>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

#### 1.3.0.70 ogit/Datacenter/rackUnit

The name of the RackUnit within a datacenter.

- id: <http://www.purl.org/ogit/Datacenter/rackUnit>
- valid-from: Thu Oct 15 00:00:00 UTC 2015
- creator: Aymen Ayoub

#### 1.3.0.71 ogit/availability

Contains information about the availability of a service/device.

- id: <http://www.purl.org/ogit/availability>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

#### 1.3.0.72 ogit/lastScannedAt

Defines a point in time when a component/device was actually scanned last time. The values must be combined date and time with time zone designator according to ISO 8601

- id: <http://www.purl.org/ogit/lastScannedAt>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

#### 1.3.0.73 ogit/subType

A subtype of an an entity.

- id: <http://www.purl.org/ogit/subType>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

#### 1.3.0.74 ogit/pendingChange

This field indicates whether or not there are any changes pending against a component/device. When you close or open a change for this component/device, this action sets or clears the flag..

- id: <http://www.purl.org/ogit/pendingChange>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

#### 1.3.0.75 ogit/inventoryNumber

This field specifies the inventory component number for the a device as defined by the company-defined device inventory number in the model table. The system uses this number to provide data on the Manufacturer, Model, and Version fields if available.

- id: <http://www.purl.org/ogit/inventoryNumber>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

#### 1.3.0.76 ogit/webPage

A web page.

- id: <http://www.purl.org/ogit/webPage>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Philipp Pelchmann

used

- optional:
  - [ogit/Organization](#)
  - [ogit/Person](#)

**1.3.0.77** `ogit/lastUpdatedAt`

Defines latest date and time when a ticket or it's comment was updated. The format of this value could be according to ISO 8601.

- id: <http://www.purl.org/ogit/lastUpdatedAt>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/ConfigurationItem](#)

**1.3.0.78** `ogit/modelNumber`

ModelNumber of a device.

- id: <http://www.purl.org/ogit/modelNumber>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

**1.3.0.79** `ogit/powerConsumption`

Power consumption of a device.

- id: <http://www.purl.org/ogit/powerConsumption>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Datacenter/Cooling](#)
  - [ogit/Datacenter/Rack](#)
  - [ogit/Device](#)

## 1.3.0.80 ogit/id

General id.

- id: <http://www.purl.org/ogit/id>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- mandatory:
  - [ogit/ConfigurationItem](#)
- optional:
  - [ogit/Asset](#)
  - [ogit/Datacenter/Building](#)
  - [ogit/Datacenter/Cooling](#)
  - [ogit/Datacenter/Datacenter](#)
  - [ogit/Datacenter/PowerDistributionUnit](#)
  - [ogit/Datacenter/Rack](#)
  - [ogit/Datacenter/Room](#)
  - [ogit/Datacenter/Section](#)
  - [ogit/Datacenter/Sensor](#)
  - [ogit/Datacenter/Server](#)
  - [ogit/Datacenter/Storage](#)
  - [ogit/Datacenter/UPS](#)
  - [ogit/Device](#)

## 1.3.0.81 ogit/checkedInAt

Defines the time when something was actually checked in. The values can combine date and time with time zone designator according to ISO 8601.

- id: <http://www.purl.org/ogit/checkedInAt>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)



#### 1.3.0.82 ogit/serviceContract

This field specifies the contract covering a service.

- id: <http://www.purl.org/ogit/serviceContract>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

#### 1.3.0.83 ogit/vendor

Contains the vendor of a device or software/hardware component.

- id: <http://www.purl.org/ogit/vendor>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

#### 1.3.0.84 ogit/Automation/governingContract

Contains information about the governing contract.

- id: <http://www.purl.org/ogit/Automation/governingContract>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

**1.3.0.85** ogit/position

Indicates user's position. This field contains a string value.

- id: <http://www.purl.org/ogit/position>
- valid-from: Tue Oct 18 00:00:00 UTC 2016
- creator: Arthur Shoba

used

- optional:
  - [ogit/Person](#)

**1.3.0.86** ogit/buildingId

ID of a Building.

- id: <http://www.purl.org/ogit/buildingId>
- valid-from: Thu May 21 00:00:00 UTC 2015
- creator: Peter Larem

used

- optional:
  - [ogit/Datacenter/Room](#)

**1.3.0.87** ogit/instance

Defines the name of an instance.

- id: <http://www.purl.org/ogit/instance>
- valid-from: Wed Aug 03 00:00:00 UTC 2016
- creator: Philipp Pelchmann

used

- optional:
  - [ogit/Timeseries](#)

**1.3.0.88 ogit/isSupported**

Indicates whether the service currently is supported. This field contains a boolean value.

- id: <http://www.purl.org/ogit/isSupported>
- valid-from: Mon Jul 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)

**1.3.0.89 ogit/operationalStatus**

An operational status for an entity. At this level of specification no list of values is specified. However, applications using this attribute are expected to allow only a fixed list of values that seems useful in the application's semantic context.

- id: <http://www.purl.org/ogit/operationalStatus>
- valid-from: Wed May 27 00:00:00 UTC 2015
- creator: Aymen Ayoub

used

- optional:
  - [ogit/ConfigurationItem](#)