

[Skip to main content](#)

[Stack Overflow](#)

1. [About](#)

2. [Products](#)

3. [For Teams](#)

1. [Stack Internal](#) Implement a knowledge platform layer to power your enterprise and AI tools.

2. [Stack Data Licensing](#) Get access to top-class technical expertise with trusted & attributed content.

3. [Stack Ads](#) Connect your brand to the world's most trusted technologist communities.

4. [Releases](#) Keep up-to-date on features we add to Stack Overflow and Stack Internal.

5. [About the company](#) [Visit the blog](#)

Loading...

[current community](#)

[Stack Overflow](#)

[help](#) [chat](#)

- [Meta Stack Overflow](#)

your communities

[Sign up](#) or [log in](#) to customize your list.

[more stack exchange communities](#)

[company blog](#)

3. [Log in](#)

4. [Sign up](#)

[AI Assist is now on Stack Overflow](#). Start a chat to get instant answers from across the network. Sign up to save and share your chats.

[Home](#)

[Questions](#)

[AI Assist](#)

[Tags](#)

[Challenges](#)

7. [Chat](#)

[Articles](#)

[Users](#)

[Companies](#)

[Collectives](#)

Communities for your favorite technologies. [Explore all Collectives](#)

Stack Internal

Stack Overflow for Teams is now called **Stack Internal**. Bring the best of human thought and AI automation together at your work.

[Try for free](#) [Learn more](#)

[Stack Internal](#)

Bring the best of human thought and AI automation together at your work. [Learn more](#)

Collectives™ on Stack Overflow

Find centralized, trusted content and collaborate around the technologies you use most.

[Learn more about Collectives](#)

Stack Internal

Knowledge at work

Bring the best of human thought and AI automation together at your work.

[Explore Stack Internal](#)

[How can I expose a safe wrapper around an owned pointer?](#)

[Ask Question](#)

Asked 10 years, 3 months ago

Modified [10 years, 3 months ago](#)

Viewed 148 times

4

I'm wrapping a C library that has two structs: one has a pointer to the other.

```
struct StructA {
    void * some_mem;
};

struct StructB {
    void * some_mem;
    struct StructA * some_struct;
};
```

Both of these structs own memory, so my wrapper has constructors and destructors for both of them.

```
struct StructA(*mut c_void);

impl StructA {
    fn new() -> Self {
        StructA(c_constructor())
    }
}

impl Drop for StructA {
    fn drop(&mut self) {
        let StructA(ptr) = self;
        c_destructor(ptr);
    }
}
```

There's also a function that takes a pointer to `StructB` and returns its pointer to `StructA`:

```
const struct StructA * get_struct(const struct StructB * obj);
```

The user of this function should not free the returned pointer, since it will be freed when the user frees `obj`.

How can I wrap this function? The problem is that the destructor for `StructB` frees all its memory, including the one for `StructA`. So if my wrapping of `get_struct` returns an object, then the wrapped `StructA` will be freed twice (right?). It could instead return a reference to an object, but where would that object live?

I could have separate structs for `StructA` based on whether it's standalone and needs to be freed or if it's a reference, but I'm hoping that's unnecessary.

- [rust](#)

[Share](#)

[Improve this question](#)

Follow

asked Aug 28, 2015 at 21:40

[awelkie](#)

2,69222 gold badges2727 silver badges3333 bronze badges

[Add a comment](#) | .

2 Answers

Sorted by: [Reset to default](#)

Highest score (default) Trending (recent votes count more) Date modified (newest first) Date created (oldest first)

4

I could have separate structs for `StructA` based on whether it's standalone and needs to be freed or if it's a reference, but I'm hoping that's unnecessary.

It's necessary. The difference between an owned `StructA *` and a borrowed `StructA *` is precisely the same as the difference between a `Box<T>` and a `&T`. They're both "just a pointer", but the semantics are completely different.

Something along these lines is probably what you want:

```

use std::marker::PhantomData;
struct OwnedA(*mut c_void);
impl Drop for OwnedA {
    fn drop(&mut self) { }
}
impl OwnedA {
    fn deref(&self) -> RefA { RefA(self.0, PhantomData) }
}
struct RefA<'a>(*mut c_void, PhantomData<&'a u8>);

struct OwnedB(*mut c_void);

impl Drop for OwnedB {
    fn drop(&mut self) { }
}

impl OwnedB {
    fn get_a(&self) -> RefA { RefA(get_struct(self.0), PhantomData) }
}

```

In particular, it's worth noting that lifetime parameter on `RefA` lets the compiler make sure you don't use a `RefA` after the backing structure has been freed.

[Share](#)

[Improve this answer](#)

Follow

answered Aug 28, 2015 at 23:39

[Eli Friedman](#)

2,39311 gold badge1515 silver badges1111 bronze badges

Sign up to request clarification or add additional context in comments.

Comments

Add a comment

2

I could have separate structs for `StructA` based on whether it's standalone and needs to be freed or if it's a reference, but I'm hoping that's unnecessary.

I believe this would be the accepted pattern. For backup, I'd point to the fact that this is a normal pattern in the Rust library. `&str` and `String`, `&[T]` and `Vec<T>`, `Path` and `PathBuf`, and probably lots of others I can't think of.

The good news is that you can use similar patterns as these pairs, leveraging `Deref` or `DerefMut` to call down to shared implementation:

```

use std::ops::{Deref, DerefMut};

enum RawFoo {}

fn c_foo_new() -> *const RawFoo { std::ptr::null() }
fn c_foo_free(_f: *const RawFoo) {}
fn c_foo_count(_f: *const RawFoo) -> u8 { 42 }
fn c_foo_make_awesome(_f: *const RawFoo, _v: bool) { }

struct OwnedFoo(Foo);

impl OwnedFoo {
    fn new() -> OwnedFoo {
        OwnedFoo(Foo(c_foo_new()))
    }
}

impl Drop for OwnedFoo {
    fn drop(&mut self) { c_foo_free((self.0).0) }
}

impl Deref for OwnedFoo {
    type Target = Foo;
    fn deref(&self) -> &Self::Target { &self.0 }
}

```

```
impl DerefMut for OwnedFoo {
    fn deref_mut(&mut self) -> &mut Self::Target { &mut self.0 }
}

struct Foo(*const RawFoo);

impl Foo {
    fn count(&self) -> u8 { c_foo_count(self.0) }
    fn make_awesome(&mut self, v: bool) { c_foo_make_awesome(self.0, v) }
}

fn main() {
    let mut f = OwnedFoo::new();
    println!("{}", f.count());
    f.make_awesome(true);
}
```

Then, when you get a borrowed pointer from your other object, just wrap it up in a &Foo:

```
use std::mem;

fn c_bar_foo_ref() -> *const RawFoo { std::ptr::null() }

// Ignoring boilerplate for wrapping the raw Bar pointer
struct Bar;

impl Bar {
    fn new() -> Bar { Bar }

    fn foo(&self) -> &Foo {
        unsafe { mem::transmute(c_bar_foo_ref()) }
    }

    fn foo_mut(&mut self) -> &mut Foo {
        unsafe { mem::transmute(c_bar_foo_ref()) }
    }
}

fn main() {
    let mut b = Bar::new();
    println!("{}", b.foo().count());
    b.foo_mut().make_awesome(true);

    // Doesn't work - lifetime constrained to Bar
    // let nope = Bar::new().foo();
}
```

[Share](#)

[Improve this answer](#)

Follow

[edited Aug 29, 2015 at 13:44](#)

answered Aug 28, 2015 at 23:48

[Shepmaster](#)

439k116116 gold badges1.3k1.3k silver badges1.5k1.5k bronze badges

1 Comment

Add a comment

dcoles

[dcoles Jan 20 at 6:15](#)

How can you transmute a *const RawFoo to a &Foo where Foo is struct Foo(*const RawFoo)? Isn't that like trying to transmute a *const RawFoo to a & *const RawFoo? My [slightly modified example](#) causes Miri to complain about this: error: Undefined Behavior: constructing invalid value: encountered a dangling reference (going beyond the bounds of its allocation).

2025-01-20T06:15:49.913Z+00:00

0

Reply

- [Copy link](#)

Your Answer

Thanks for contributing an answer to Stack Overflow!

- Please be sure to *answer the question*. Provide details and share your research!

But *avoid* ...

- Asking for help, clarification, or responding to other answers.
- Making statements based on opinion; back them up with references or personal experience.

To learn more, see our [tips on writing great answers](#).

Sign up or [log in](#)

Sign up using Google

Sign up using Email and Password

Submit

Post as a guest

Name

Email

Required, but never shown

Post as a guest

Name

Email

Required, but never shown

Post Your Answer Discard

By clicking "Post Your Answer", you agree to our [terms of service](#) and acknowledge you have read our [privacy policy](#).

Start asking to get answers

Find the answer to your question by asking.

[Ask question](#)

Explore related questions

- [rust](#)

See similar questions with these tags.

- [The Overflow Blog](#)

[Introducing Stack Overflow AI Assist—a tool for the modern developer](#)

[Treating your agents like microservices](#)

- [Featured on Meta](#)

[Chat room owners can now establish room guidelines](#)

[AI Assist is now available on Stack Overflow](#)

[Policy: Generative AI \(e.g., ChatGPT\) is banned](#)

Related

[3](#)

[How do I manage optional owned pointers in rust?](#)

[0](#)

[Using managed and owned pointers together](#)

[3](#)

[How do you borrow a mutable pointer in rust?](#)

[3](#)

[Can you convert an unsafe pointer to an owned pointer in rust somehow?](#)

[0](#)

[How can I create an owning pointer to an unsized type?](#)

[7](#)

[How do I deal with wrapper type invariance in Rust?](#)

[3](#)

[Convenient access to members of raw pointers?](#)

[0](#)

[Dereferencing raw pointer with explicit annotation in Rust](#)

[0](#)

[Raw pointers w/o unsafe](#)

[2](#)

[How to wrap a struct in Rust?](#)

Hot Network Questions

- [Where in the world is the chicken?](#)
- [Critiques of the real vs. nominal definition distinction](#)
- [Can a 10*10 square be paved with 1*4 rectangular stone plates?](#)
- ["Creatures your opponents control" after the ability is activated](#)
- [Zero Inflated Beta Regression \(or not\)?](#)
- [Is it possible to use LaTeX to create RPG-related PDFs, such as character sheets or adventure modules?](#)
- [How can I secure a loose kitchen cabinet?](#)
- [Is there a term for forming emotional or relational bonds with AI chatbots? If not, is "cyberpomorphic" a valid neologism?](#)
- [What's the point of swapping polarity between mod slots?](#)
- [Finding real variable where a 2x2 complex matrix is singular in Mathematica](#)
- [Why does Mtt 13:34 say that Jesus always spoke in parables?](#)
- [Is my homebrew Species "Attuned" balanced for D&D 2024?](#)
- [Why is "cmd | xargs" to join lines of cmd with spaces wrong](#)
- [Download is performed unsandboxed as root - Why am I getting this message, and how do I fix it?](#)
- [Does short range teleporting end floating disk?](#)
- [Ping sweep of IP subnets](#)
- [Proportional odds logistic regression for ordered category outcome - how to convert odds ratios to probabilities in this case?](#)
- [Can I Automatically List Supported Kernel Parameters in GRUB?](#)
- [Recent time traveling TV show. The lead might have been Asian\(?\), set in San Francisco\(?\)](#)
- [Storm Sphere and Obstruction](#)
- [Is there any way to restore hearts without consuming anything, without hot springs, and without shrines?](#)
- [How to add blur inside subtracted element in Figma?](#)
- [Installing root certificates by government](#)
- [Documentation for DUSHIN software](#)

[more hot questions](#)

[Question feed](#)

Subscribe to RSS

Question feed

To subscribe to this RSS feed, copy and paste this URL into your RSS reader.

[Stack Overflow](#)

- [Questions](#)
- [Help](#)
- [Chat](#)

[Business](#)

- [Stack Internal](#)
- [Stack Data Licensing](#)
- [Stack Ads](#)

[Company](#)

- [About](#)
- [Press](#)
- [Work Here](#)
- [Legal](#)
- [Privacy Policy](#)
- [Terms of Service](#)
- [Contact Us](#)
- [Cookie Settings](#)
- [Cookie Policy](#)

[Stack Exchange Network](#)

- [Technology](#)
- [Culture & recreation](#)
- [Life & arts](#)
- [Science](#)
- [Professional](#)
- [Business](#)
- [API](#)
- [Data](#)
- [Blog](#)
- [Facebook](#)
- [Twitter](#)
- [LinkedIn](#)
- [Instagram](#)

Site design / logo © 2025 Stack Exchange Inc; user contributions licensed under [CC BY-SA](#) . rev 2025.12.4.37651