

[Skip to main content](#)

[Stack Overflow](#)

1. [About](#)

2. [Products](#)

3. [For Teams](#)

1. [Stack Internal](#) Implement a knowledge platform layer to power your enterprise and AI tools.

2. [Stack Data Licensing](#) Get access to top-class technical expertise with trusted & attributed content.

3. [Stack Ads](#) Connect your brand to the world's most trusted technologist communities.

4. [Releases](#) Keep up-to-date on features we add to Stack Overflow and Stack Internal.

5. [About the company](#) [Visit the blog](#)

Loading...

## [current community](#)

[Stack Overflow](#)

[help](#) [chat](#)

- [Meta Stack Overflow](#)

## **your communities**

[Sign up](#) or [log in](#) to customize your list.

## [more stack exchange communities](#)

[company blog](#)

3. [Log in](#)

4. [Sign up](#)

[AI Assist is now on Stack Overflow](#). Start a chat to get instant answers from across the network. Sign up to save and share your chats.

[Home](#)

[Questions](#)

[AI Assist](#)

[Tags](#)

[Challenges](#)

7. [Chat](#)

[Articles](#)

[Users](#)

[Companies](#)

[Collectives](#)

Communities for your favorite technologies. [Explore all Collectives](#)

Stack Internal

Stack Overflow for Teams is now called **Stack Internal**. Bring the best of human thought and AI automation together at your work.

[Try for free](#) [Learn more](#)

[Stack Internal](#)

Bring the best of human thought and AI automation together at your work. [Learn more](#)

## **Collectives™ on Stack Overflow**

Find centralized, trusted content and collaborate around the technologies you use most.

[Learn more about Collectives](#)

## **Stack Internal**

Knowledge at work

Bring the best of human thought and AI automation together at your work.

[Explore Stack Internal](#)

## [How to move one field out of a struct that implements Drop trait?](#)

[Ask Question](#)

Asked 10 years, 5 months ago

Modified [1 year, 9 months ago](#)

Viewed 17k times

36

Here's an invalid Rust program (Rust version 1.1) with a function that does an HTTP client request and returns only the headers, dropping all other fields in the response.

```
extern crate hyper;

fn just_the_headers() -> Result<hyper::header::Headers, hyper::error::Error> {
    let c = hyper::client::Client::new();
    let result = c.get("http://www.example.com").send();
    match result {
        Err(e) => Err(e),
        Ok(response) => Ok(response.headers),
    }
}

fn main() {
    println!("{}", just_the_headers());
}
```

Here are the compiler errors:

```
main.rs:8:28: 8:44 error: cannot move out of type `hyper::client::response::Response`, which defines the `Drop` trait
main.rs:8      Ok(response) => Ok(response.headers),
                        ^~~~~~
error: aborting due to previous error
```

I understand *why* the borrow checker doesn't accept this program—i.e., that the `drop` function will use the `response` after it has had its `headers` member moved.

My question is: How can I get around this and still have good safe Rust code? I know I can do a *copy*, via `clone()`, like so:

```
Ok(response) => Ok(response.headers.clone()),
```

But, coming from C++, that seems inefficient. Why *copy* when a *move* should suffice? I envision in C++ doing something like the following to force a call to a move constructor, if available:

```
headers_to_return = std::move(response.headers);
```

Is there any way to forgo the *copy* in Rust and instead force a *move*, similar to C++?

- [rust](#)

[Share](#)

[Improve this question](#)

Follow

[edited May 25, 2018 at 19:19](#)

[Boiethios](#)

43.7k2525 gold badges151151 silver badges198198 bronze badges

asked Jul 9, 2015 at 3:36

[Craig M. Brandenburg](#)

3,68466 gold badges2828 silver badges3939 bronze badges

1

This won't technically move the member value, but if you're OK to change your structure a bit, but you can wrap the headers by changing the type of `response.headers` to `Option<Headers>` and `take()` its value. This will reset the value to `None`, which is useful if you're unable to find a good default value for your type (e.g. a thread). This is done in [doc.rust-lang.org/stable/book/ch17-03-oo-design-patterns.html](http://doc.rust-lang.org/stable/book/ch17-03-oo-design-patterns.html) and [doc.rust-lang.org/stable/book/...](http://doc.rust-lang.org/stable/book/...)

hsandt – [hsandt](#)

2019-07-13 19:48:02 +00:00

Commented Jul 13, 2019 at 19:48

[Add a comment](#) | .

### 3 Answers

Sorted by: [Reset to default](#)

Highest score (default) Trending (recent votes count more) Date modified (newest first) Date created (oldest first)

48

You can use `std::mem::replace()` to swap the field with a new blank value in order to transfer ownership to you:

```
extern crate hyper;

fn just_the_headers() -> Result<hyper::header::Headers, hyper::error::Error> {
    let c = hyper::client::Client::new();
    let result = c.get("http://www.example.com").send();
    match result {
        Err(e) => Err(e),
        Ok(mut response) => Ok(std::mem::replace(&mut response.headers, hyper::header::Headers::new())),
    }
}

fn main() {
    println!("{}", just_the_headers());
}
```

Here, we're replacing `response.headers` with a new empty set of headers. `replace()` returns the value that was stored in the field before we replaced it.

[Share](#)

[Improve this answer](#)

Follow

answered Jul 9, 2015 at 4:44

[Francis Gagné](#)

66.7k1313 gold badges201201 silver badges172172 bronze badges

Sign up to request clarification or add additional context in comments.

## 6 Comments

Add a comment

DK.

[DK. Over a year ago](#)

It might be worth noting that `std::mem::replace` in Rust is *more or less* what `std::move` is in C++. Because the source and destination must be valid to destruct both before *and after* a move, C++ doesn't really move, it swaps.

2015-07-09T05:02:24.723Z+00:00

6

Reply

- Copy link

Francis Gagné

[Francis Gagné Over a year ago](#)

Indeed, with the difference that in C++, it is the class that decides how to implement the move (in the move constructor or move assignment operator), whereas `std::mem::replace` requires the caller to provide a suitable value. In fact, `std::mem::replace` is implemented in terms of [std::mem::swap](#).

2015-07-09T05:05:35.12Z+00:00

4

Reply

- Copy link

Matthieu M.

[Matthieu M. Over a year ago](#)

You might wish to note that Rust also places on emphasis on extremely efficient "default constructs", for example neither `String::new()` nor `Vec::new()` allocate memory, which is what makes this replace as efficient as the C++ move on top of being safer.

2015-07-09T08:04:24.277Z+00:00

5

Reply

- Copy link

Craig M. Brandenburg

[Craig M. Brandenburg Over a year ago](#)

Thanks! Is using `std::mem::replace` for this use case idiomatic? (Is what I'm trying to do — to force a *move* instead of a *copy* — idiomatic?) I ask because the call to `std::mem::replace` seems like a lot of typing to do something that could be a common use case.

2015-07-09T12:27:49.81Z+00:00

1

Reply

- Copy link

Francis Gagné

[Francis Gagné Over a year ago](#)

`std::mem::replace` seems to be the most suitable tool to use to take ownership of a value you can't take ownership of with Rust's standard ownership rules. Don't forget you can use `use` declarations to make names shorter, e.g. use `std::mem`;, then `mem::replace`, or use `std::mem::replace`, then `replace`. The preferred style is to use functions qualified on the module (`mem::replace`), but types unqualified (`Headers`).

2015-07-09T23:42:32.84Z+00:00

2

Reply

- Copy link

Add a comment | Show 1 more comment

2

As of Rust 1.40.0 (released in December 2019), `std::mem::take` should be used. [Rust docs](#) mention:

```
pub fn take<T>(dest: &mut T) -> T
where
    T: Default,
```

Replaces `dest` with the default value of `T`, returning the previous `dest` value.

This is how it will be used in your example:

```
fn just_the_headers() -> Result<hyper::header::Headers, hyper::error::Error> {
    let c = hyper::client::Client::new();
    let result = c.get("http://www.example.com").send();
    match result {
        Err(e) => Err(e),
        Ok(response) => Ok(std::mem::take(&mut response.headers)),
    }
}

fn main() {
    println!("{}", just_the_headers());
}
```

[Share](#)

[Improve this answer](#)

Follow

answered Feb 18, 2024 at 18:30

[Arpit Saxena](#)

6733 silver badges77 bronze badges

## Comments

Add a comment

1

It's worth noting that the `hyper` crate now has a different API which supports taking the headers by value. Here is the solution for `hyper` 14.2 (Rust edition 2021, version 1.69):

```
extern crate http;
extern crate hyper;

async fn just_the_headers() -> Result<http::header::HeaderMap, hyper::Error> {
    let c = hyper::client::Client::new();
    let result = c
        .get(hyper::Uri::from_static("http://www.example.com"))
        .await;
    match result {
        Err(e) => Err(e),
        Ok(response) => Ok(response.into_parts().0.headers),
    }
}
```

A lot has changed since Rust 1.1. `async/await` is now a first-class part of the language (stabilized in Rust 1.39). We also have the new `?` operator, stabilized in Rust 1.13. Using this operator, the code becomes

```
extern crate http;
extern crate hyper;

async fn just_the_headers() -> Result<http::header::HeaderMap, hyper::Error> {
    Ok(hyper::client::Client::new()
        .get(hyper::Uri::from_static("http://www.example.com"))
        .await?
        .into_parts()
        .0
        .headers)
}
```

[Share](#)  
[Improve this answer](#)

Follow  
answered May 22, 2023 at 23:13

[Mark Saving](#)  
1,81799 silver badges1212 bronze badges

### Comments

Add a comment

### Your Answer

Thanks for contributing an answer to Stack Overflow!

- Please be sure to *answer the question*. Provide details and share your research!

But *avoid* ...

- Asking for help, clarification, or responding to other answers.
- Making statements based on opinion; back them up with references or personal experience.

To learn more, see our [tips on writing great answers](#).

Sign up or [log in](#)

Sign up using Google  
Sign up using Email and Password

Submit

### Post as a guest

Name

Email

Required, but never shown

Post as a guest

Name

Email

Required, but never shown

Post Your Answer Discard

By clicking "Post Your Answer", you agree to our [terms of service](#) and acknowledge you have read our [privacy policy](#).

Start asking to get answers

Find the answer to your question by asking.

[Ask question](#)

Explore related questions

- [rust](#)

See similar questions with these tags.

- The Overflow Blog  
[Introducing Stack Overflow AI Assist—a tool for the modern developer](#)  
[Treating your agents like microservices](#)
- Featured on Meta  
[Chat room owners can now establish room guidelines](#)  
[AI Assist is now available on Stack Overflow](#)  
[Policy: Generative AI \(e.g., ChatGPT\) is banned](#)

#### Linked

[16](#)  
[How can I move a value out of the argument to Drop::drop\(\)?](#)

[8](#)  
[How do I destructure an object without dropping it?](#)

[4](#)  
[How to move a field whose type does not implement Default from a struct which implements Drop?](#)

[0](#)  
[Borrow checker problems for parser that can delegate](#)

[0](#)  
[method that mutates `self` and consumes one of the `struct` field \(err: move behind a mutable reference\)](#)

#### Related

[6](#)  
[Can not move out of type which defines the `Drop` trait \[E0509\]](#)

[2](#)  
[Maybe move field inside struct method](#)

[5](#)  
[Easy way to change one field in struct?](#)

[16](#)  
[How can I move a value out of the argument to Drop::drop\(\)?](#)

[4](#)  
[How to take away \(move out of\) a struct field that contains a big datastructure type?](#)

[4](#)  
[How to move a field whose type does not implement Default from a struct which implements Drop?](#)

[1](#)  
[Is it available to drop a variable holding a primitive value in Rust?](#)

[2](#)  
[How to remove a struct's field?](#)

[1](#)  
[how to implement "drop" on a generic struct where T itself implements a type](#)

[Do I need to specify 'drop\(item\)' if i write a custom drop implementation for a struct? Rust](#)

## [Hot Network Questions](#)

- [The first Pontrjagin class of Milnor's example of exotic 7-sphere](#)
- [Is there a website where we can find the average stipend/salary for the PhD and Postdoc for each country?](#)
- [Polygons \(and some stars\)](#)
- [Can four points in a unit square have mutual distances all larger than 1?](#)
- [How to check if two tables are identical?](#)
- [Curve has weird bumps when triangulated](#)
- [EEPROM Decoupling Capacitor](#)
- [Download is performed unsandboxed as root - Why am I getting this message, and how do I fix it?](#)
- [Generating Irregular, Separated Polygonal Cells along a Curve in Geometry Nodes](#)
- [What do the terms postponement, slip and scrub mean in the context of the space shuttle program?](#)
- [How do Buddhists interpret the Buddha's explanation of earthquakes in AN 8.70?](#)
- [Finding real variable where a 2x2 complex matrix is singular in Mathematica](#)
- [Can enemies damage each other in Breath of the Wild?](#)
- [Is the phrase "murder will out" from Chaucer?](#)
- [How many alien worlds could exist within 100 ly without us noticing?](#)
- [Obscure method of supression of transient voltage spike in CLC-circuit](#)
- [I can't add a loop cut on one face](#)
- [How can I determine whether a complex rational equation has real solutions?](#)
- [How to protect 100-year-old wooden floors for the next 100 years?](#)
- ["Us" in Hegel's "Greater Logic"](#)
- [Is my homebrew Species "Attuned" balanced for D&D 2024?](#)
- [How can I secure a loose kitchen cabinet?](#)
- [How to add blur inside subtracted element in Figma?](#)
- [Why doesn't sleep mode \(S3\) turn on in the BIOS on my Lecoo Pro 14 laptop \(N155A, Lenovo sub-brand\) with Windows 11?](#)

[more hot questions](#)

[Question feed](#)

## Subscribe to RSS

Question feed

To subscribe to this RSS feed, copy and paste this URL into your RSS reader.

## [Stack Overflow](#)

- [Questions](#)
- [Help](#)
- [Chat](#)

## [Business](#)

- [Stack Internal](#)
- [Stack Data Licensing](#)
- [Stack Ads](#)

## [Company](#)

- [About](#)
- [Press](#)
- [Work Here](#)
- [Legal](#)
- [Privacy Policy](#)
- [Terms of Service](#)
- [Contact Us](#)
- [Cookie Settings](#)
- [Cookie Policy](#)

## Stack Exchange Network

- [Technology](#)
- [Culture & recreation](#)
- [Life & arts](#)
- [Science](#)
- [Professional](#)
- [Business](#)
- [API](#)
- [Data](#)
- [Blog](#)
- [Facebook](#)
- [Twitter](#)
- [LinkedIn](#)
- [Instagram](#)

Site design / logo © 2025 Stack Exchange Inc; user contributions licensed under [CC BY-SA](#) . rev 2025.12.4.37651