

[Skip to main content](#)

[Stack Overflow](#)

1. [About](#)

2. [Products](#)

3. [For Teams](#)

1. [Stack Internal](#) Implement a knowledge platform layer to power your enterprise and AI tools.

2. [Stack Data Licensing](#) Get access to top-class technical expertise with trusted & attributed content.

3. [Stack Ads](#) Connect your brand to the world's most trusted technologist communities.

4. [Releases](#) Keep up-to-date on features we add to Stack Overflow and Stack Internal.

5. [About the company](#) [Visit the blog](#)

Loading...

[current community](#)

[Stack Overflow](#)

[help](#) [chat](#)

- [Meta Stack Overflow](#)

your communities

[Sign up](#) or [log in](#) to customize your list.

[more stack exchange communities](#)

[company blog](#)

3. [Log in](#)

4. [Sign up](#)

[AI Assist is now on Stack Overflow](#). Start a chat to get instant answers from across the network. Sign up to save and share your chats.

[Home](#)

[Questions](#)

[AI Assist](#)

[Tags](#)

[Challenges](#)

7. [Chat](#)

[Articles](#)

[Users](#)

[Companies](#)

[Collectives](#)

Communities for your favorite technologies. [Explore all Collectives](#)

Stack Internal

Stack Overflow for Teams is now called **Stack Internal**. Bring the best of human thought and AI automation together at your work.

[Try for free](#) [Learn more](#)

[Stack Internal](#)

Bring the best of human thought and AI automation together at your work. [Learn more](#)

Collectives™ on Stack Overflow

Find centralized, trusted content and collaborate around the technologies you use most.

[Learn more about Collectives](#)

Stack Internal

Knowledge at work

Bring the best of human thought and AI automation together at your work.

[Explore Stack Internal](#)

[How does automatic de-referencing work in Rust? \[duplicate\]](#)

[Ask Question](#)

Asked 2 years, 6 months ago

Modified [2 years, 6 months ago](#)

Viewed 706 times

1

This question already has answers here:

[What are Rust's exact auto-dereferencing rules?](#) (4 answers)

Closed 2 years ago.

I am trying to learn Rust and am having some trouble understanding why we need to dereference pointers in some cases and not in others. Fishing for answers online, I found out that Rust has automatic dereferencing, but I couldn't find much on the topic. Can someone explain to me how this exactly works?

To make it more specific, here is a sample code where I encountered this problem.

```
fn mode(v: &mut Vec<i32>) -> Option<i32> {
    let mut map: HashMap<i32, i32> = HashMap::new();
    let mut max = (0, 0);
    if v.is_empty() {
        return None;
    } else {
        ();
    }
    for i in v {
        let count = map.entry(*i).or_insert(0);
        *count += 1;
    }
    for (k, v) in map.iter() {
        if v > &max.1 {
            max = (*k, *v);
        } else {
            ();
        }
    }
    Some(max.0)
}
```

Here, there is apparently no need to dereference vector `v` anywhere, but we need to dereference several other variables such as `i` in line 75, and I do not understand why.

- [rust](#)

[Share](#)

[Improve this question](#)

Follow

[edited May 28, 2023 at 4:58](#)

asked May 28, 2023 at 4:48

[Keshav Gulati](#)

2144 bronze badges

3

`is_empty(&self)` needs a reference on `self`. `v` is already a reference (`&mut Vec`), so there is no need to dereference. `i in v` calls `into_iter(self)` where `self` is `&Vec`, so there is also no need to dereference. Assigning to `(i32, i32)` needs dereferencing.

Corona – [CoronaA](#)

2023-05-28 05:11:03 +00:00

Commented May 28, 2023 at 5:11

2

@CoronaA It does need to dereference, though, because the `is_empty` method comes from the slice type, not `Vec` itself. It's usable because `Vec<T>` implements `Deref<Target = [T]>`. If the compiler didn't auto-deref, you'd have to manually deref the `Vec` to get a slice.

cdhowie – [cdhowie](#)

2023-05-28 05:27:44 +00:00

Commented May 28, 2023 at 5:27

@cdhowie: I voted up your comment, because I did not check it. But after checking it I cannot find anything wrong with my statement: `is_empty(&self)` is implemented for `Vec<T>` and pasting the code into my IDE also claims that this method is called.

CoronA – [CoronA](#)

2023-05-28 19:18:16 +00:00

Commented May 28, 2023 at 19:18

[Add a comment](#) | .

1 Answer

Sorted by: [Reset to default](#)

Highest score (default) Trending (recent votes count more) Date modified (newest first) Date created (oldest first)

5

The easiest way to illustrate this is within the context of the sample code `x.foo(y)`.

`x` here is the *receiver*. Given the type of `x`, the compiler has to figure out what function `foo` is. It attempts to locate `foo` on `x`'s type, and additionally by *auto-dereferencing* `x`, which is what you are asking about. This process considers the type of `x` as well as every type that is encountered by dereferencing `x` as many times as possible. (It also considers `&` and possibly `&mut` variants of these types, depending on the mutability of `x` or its reference type.)

If exactly one `foo` is found, then the call is transformed to `T::foo(z, y)` where `T` is the type the `foo` method was located on, and `z` is whatever sequence of dereferences (plus one final, optional `&` or `&mut`) results in a `T`, `&T`, or `&mut T`, as required by `T::foo`.

What about `y`, though? Arguments undergo [coercion](#), which is a different thing altogether. The linked documentation lists all of the possible coercions, which I will omit for the sake of brevity, but notably absent are `&T` to `T` and `&mut T` to `T`, one of which would be required to make `map.entry(i)` work in your sample code. The explicit dereference is therefore required.

Note that one of the items present in the list of coercions is:

`&T` or `&mut T` to `U` if `T` implements `Deref<Target = U>`.

Observe that this *doesn't actually dereference a reference* but rather *converts the reference to another type of reference*! That is, the coercion is `&T` to `U`, *not* `&T` to `U`. This is what allows you to give `&String` to an argument that expects a `&str`, for example (`String` implements `Deref<Target = str>`), but this rule doesn't provide coercion from `&mut i32` to `i32` as would be required to make `map.entry(i)` work.

`for i in v` is a completely different scenario; this works simply because `&mut Vec<T>` implements `IntoIterator`.

So the answer as to why you don't have to dereference `v` is because you are using it in receiver position, where auto-dereference happens. Function arguments instead undergo coercion, which has an entirely different set of rules.

Now having said that, in your code `v` is already a reference to a `Vec`, and so `v.is_empty()` could be explained through coercion as well, as this method comes from slices, to which `Vec` automatically dereferences. However, the overall point still stands -- you cannot conflate auto-dereferencing with deref coercion. This is one instance where they would happen to do the same thing, but in many other cases they would not.

[Share](#)

[Improve this answer](#)

Follow

[edited May 28, 2023 at 5:34](#)

answered May 28, 2023 at 5:18

[cdhowie](#)

172k2525 gold badges303303 silver badges324324 bronze badges

Sign up to request clarification or add additional context in comments.

3 Comments

Add a comment

TaekYoung

[TaekYoung Over a year ago](#)

Isn't it dangerous to expand name space like that? Because what if Reference and Receiver have same method?

2024-04-30T19:04:44.563Z+00:00

0

Reply

- Copy link

cdhowie

[cdhowie Over a year ago](#)

@TaekYoung This is exactly why many built-in smart pointer "methods" require associated function syntax and can't be used with method-call syntax. For example, look at [Arc::downgrade](#). Note that it takes `this: &Arc` instead of `&self` -- this means you have to call this function using the syntax

`Arc::downgrade(&foo).foo.downgrade()` will not work. This is intentional so that if the `T` inside of the `Arc` has a `downgrade` method of its own, the method-call syntax will call `T`'s method instead of `Arc`'s.

2024-04-30T19:42:44.37Z+00:00

1

Reply

- [Copy link](#)

TaekYoung

[TaekYoung Over a year ago](#)

Thank you! That explains a lot for me. I think rust book should contain your explanation also.

2024-05-02T09:43:31.22Z+00:00

0

Reply

- [Copy link](#)

Add a comment

Start asking to get answers

Find the answer to your question by asking.

[Ask question](#)

Explore related questions

- [rust](#)

See similar questions with these tags.

- The Overflow Blog

[Introducing Stack Overflow AI Assist—a tool for the modern developer](#)

[Treating your agents like microservices](#)

- Featured on Meta

[Chat room owners can now establish room guidelines](#)

[AI Assist is now available on Stack Overflow](#)

[Policy: Generative AI \(e.g., ChatGPT\) is banned](#)

Linked

[357](#)

[What are Rust's exact auto-dereferencing rules?](#)

Related

[676](#)

[Why doesn't `println!` work in Rust unit tests?](#)

[509](#)

[How do I print the type of a variable in Rust?](#)

[408](#)

[How do I split a string in Rust?](#)

[560](#)

[How do you disable dead code warnings at the crate level in Rust?](#)

[390](#)

[Why are Rust executables so huge?](#)

[422](#)

[Why does the Rust compiler not optimize code assuming that two mutable references cannot alias?](#)

[3](#)

[Rust "Borrowed pointers" syntax](#)

[3](#)

[Rust lifetime for database connection bundle](#)

[302](#)

[How can a Rust program access metadata from its Cargo package?](#)

[648](#)

[How do I concatenate strings?](#)

[Hot Network Questions](#)

- [Misunderstanding the lorentz transformation](#)
- [Explain this seeming contradiction in Euclid Book 1 Proposition 16](#)
- [How does supporting "One China" work without also supporting Taiwan-China reunification?](#)
- ["Creatures your opponents control" after the ability is activated](#)
- [How to prevent a batch file call from escaping a caret character?](#)
- [Curve has weird bumps when triangulated](#)
- [Would it be plausible to have a flat eye with a moving pupil?](#)
- [Why are left and right cosets different in the non-normal case?](#)
- [Generating Irregular, Separated Polygonal Cells along a Curve in Geometry Nodes](#)
- [EEPROM Decoupling Capacitor](#)
- [What may cause any version of Microsoft Outlook to run slowly?](#)
- [Is zero-point energy a mathematical artifact?](#)
- [A very weird integral equation](#)
- [What is the difference between an ultraviolet limit and ultraviolet stability?](#)
- [variable name change causes segfault](#)
- [Does short range teleporting end floating disk?](#)
- ["Us" in Hegel's "Greater Logic"](#)
- [Can a 10*10 square be paved with 1*4 rectangular stone plates?](#)
- [Critiques of the real vs. nominal definition distinction](#)
- [Is there any way to restore hearts without consuming anything, without hot springs, and without shrines?](#)
- [How to add blur inside subtracted element in Figma?](#)
- [Could a world tree have different biomes?](#)
- [What's the point of swapping polarity between mod slots?](#)
- [Why is "cmd | xargs" to join lines of cmd with spaces wrong](#)

[more hot questions](#)

[Stack Overflow](#)

- [Questions](#)
- [Help](#)
- [Chat](#)

[Business](#)

- [Stack Internal](#)
- [Stack Data Licensing](#)
- [Stack Ads](#)

[Company](#)

- [About](#)
- [Press](#)
- [Work Here](#)
- [Legal](#)
- [Privacy Policy](#)
- [Terms of Service](#)
- [Contact Us](#)
- [Cookie Settings](#)
- [Cookie Policy](#)

[Stack Exchange Network](#)

- [Technology](#)
- [Culture & recreation](#)
- [Life & arts](#)
- [Science](#)
- [Professional](#)
- [Business](#)
- [API](#)
- [Data](#)
- [Blog](#)
- [Facebook](#)

- [Twitter](#)
- [LinkedIn](#)
- [Instagram](#)

Site design / logo © 2025 Stack Exchange Inc; user contributions licensed under [CC BY-SA](#) . rev 2025.12.4.37651