

**p0.sql**

```
drop database if exists kamalclasses;  
create database if not exists kamalclasses;  
use kamalclasses;
```

**Run:**

```
mysql> source C:\mysql_july26\L11\p0.sql
```



### p1.sql

```
use kamalclasses;
```

```
delimiter $$
```

```
drop procedure if exists p1 $$
```

```
create procedure p1()
```

```
begin
```

```
    select "welcome to pl/sql" as MSG;
```

```
end$$
```

```
delimiter ;
```

### Compile and Run:

```
mysql> source C:\mysql_july26\L11\p1.sql
```

```
mysql> call p1();
```



### p2.sql

```
use kamalclasses;
```

```
delimiter $$
```

```
drop procedure if exists p2 $$
```

```
create procedure p2(name varchar(50))
```

```
begin
```

```
    select concat("welcome ", name) as MSG;
```

```
end$$
```

```
delimiter ;
```

### Compile and Run:

```
mysql> source C:\mysql_july26\L11\p2.sql
```

```
mysql> call p2();
```

```
mysql> call p2("kamal");
```



### p3.sql

```
use kamalclasses;
```

```
delimiter $$
```

```
drop procedure if exists p3 $$
```

```
create procedure p3(name varchar(50))
```

```
begin
```

```
    if name is null then
```

```
        select "name shud not be null" as ERR_MSG;
```

```
    elseif length(name) = 0 then
```

```
        select "name shud contain min 1 character" as ERR_MSG;
```

```
    elseif trim(name) = "" then
```

```
        select "name shud not be blank spaces" as ERR_MSG;
```

```
    else
```

```
        select concat("welcome ", name) as MSG;
```

```
    end if;
```

```
end$$
```

```
delimiter ;
```

### Compile and Run:

```
mysql> source C:\mysql_july26\L11\p3.sql
```

```
mysql> call p3("sai");
```

```
mysql> call p3("");
```

```
mysql> call p3(" ");
```

```
mysql> call p3(null);
```



#### p4.sql

# wamp to find sum of two numbers supplied

#### p5.sql

# wamp to find avg of three numbers supplied

#### p6.sql

# wamp to check if given integer is even or odd

#### P7.sql

# wamp to print grade for given marks (0 to 100)

# m > 80 → Grade A, m > 60 → Grade B , m > 40 → Grade C else Grade D