

- create database kc.
- create table emp with following info:
 - id int unsigned primary key
 - name varchar(20)
 - salary decimal(10,2)
- Populate the table with following records:

id	name	salary
1	amit	4000.00
2	neha	5000.00
3	seema	3000.00
4	sumit	4500.00

- Create the following procedures:
- pr1) wamp to accept as input eid print name and salary
- pr2) wamp to accept as input id and print tax amount:
 - sal >= 4000 -> 20% else 10%

>> done

kc.sql

```
drop database if exists kc;
create database if not exists kc;
use kc;
```

```
drop table if exists emp;
create table if not exists emp
(
  id int unsigned primary key,
  name varchar(20),
  salary decimal(10,2)
);
```

```
insert into emp values
(1, 'amit', 4000),
(2, 'neha', 5000),
(3, 'seema', 3000),
(4, 'sumit', 4500);
```

```
select * from emp;
```


pr1.sql

```
use kc;
delimiter $$
drop procedure if exists pr1 $$
create procedure pr1(eid int)
begin
    declare c int default 0;

    select count(*) into c from emp where id = eid;
    if c = 0 then
        select concat(eid, " does not exists ") as MSG;
    else
        select concat("name = ", name, " salary = ", salary) as MSG from emp where id = eid;
    end if;

end $$
delimiter ;
```

pr11.sql

```
use kc;
delimiter $$
drop procedure if exists pr11 $$
create procedure pr11(eid int)
begin
    declare na varchar(50);
    declare sa double;

    select name, salary into na, sa from emp where id = eid;
    if (na is not null) and (sa is not null) then
        select concat("name = ", na, " salary = ", sa) as MSG;
    else
        select concat(eid, " does not exists ") as MSG;
    end if;

end $$
delimiter ;
```

pr2.sql u need to do it