

- create database **kit**.
- create table **student** with following info:
 - rno int unsigned primary key
 - name varchar(20)
 - marks tinyint unsigned
 - eyear enum for 'fe', 'se', 'te' 'be'
 - location varchar(30) default Mumbai
- Populate the table with following records:

rno	name	marks	eyear	location
10	amit	98	fe	thane
20	sumit	79	se	mumbai
30	rumit	63	fe	thane
40	seema	81	se	thane
50	reema	45	fe	mumbai
60	tina	95	be	thane

- Create the following procedures:
- pr1) Wamp to take as input rno and display the rno and name of student along with result.
- If marks > 60 then pass else fail.
- pr2) Wamp to take as input rno and display the rno and name of student along with result.
- If marks >= 70 then distinction, marks >= 60 then first class, marks >= 50 then second class, marks >= 40 then pass class else fail
- pr3) Wamp that takes as input rno and displays the number of holidays. Use simple case.
- fe - 5 days, se - 4 days else 2 days
- pr4) Wamp that takes as input rno and displays the grade of the student. Use searched case
- marks > 70 Grade A , marks > 60 Grade B else Grade C

pr1.sql

```
use kit;
delimiter $$
drop procedure if exists pr1 $$
create procedure pr1(r int)
begin
    declare c int default 0;
    declare na varchar(50) default "";
    declare ma int default 0;
    declare result varchar(10) default "";

    if r is null then
        select "rno shud not be null" as ERR_MSG;
    else
        select count(*) into c from student where rno = r;
        if c = 0 then
            select concat(r, " does not exists" ) as ERR_MSG;
        else
            select name, marks into na, ma from student where rno = r;
            if ma > 60 then
                set result = "Pass";
            else
                set result = "Fail";
            end if;
            select concat("rno = ", r, " name = ", na, " marks = ", ma, " result = ", result) as MSG;
        end if;
    end if;
end $$
delimiter ;
```

Compile and Run:

```
mysql> source C:\mysql_july26\L12\pr1.sql
Database changed
Query OK, 0 rows affected (0.00 sec)
```

```
Query OK, 0 rows affected (0.00 sec)
```

```
mysql> call pr1(10);
```

```
+-----+
| MSG                |
+-----+
| rno = 10 name = amit marks = 98 result = Pass |
+-----+
1 row in set (0.00 sec)
```

```
Query OK, 0 rows affected (0.00 sec)
```