Lab Exercise 3

Provisioning an EC2 Instance on AWS

1. **Create Terraform Configuration File for EC2 instance (instance.tf):**

main.tf instance.tf

instance.tf

```
resource "aws_instance" "My-instance" {
    instance_type = "t2.micro"
    ami = "ami-05fb0b8c1424f266b"
    count = 1
    tags = {
        Name = "UPES-EC2-Instnace"
        }
    }
```

2. **Review Plan:**

```
PS E:\aws-terraform-demo> terraform plan

Terraform used the selected providers to generate the following execution plan. Resource actions are indicated with the following symbols:
  + create

Terraform will perform the following actions:

  # aws_instance.My-instance[0] will be created
  + resource "aws_instance" "My-instance" {
      + ami                                  = "ami-05fb0b8c1424f266b"
      + arn                                  = (known after apply)
      + associate_public_ip_address          = (known after apply)
      + availability_zone                    = (known after apply)
      + cpu_core_count                       = (known after apply)
      + cpu_threads_per_core                 = (known after apply)
      + disable_api_stop                     = (known after apply)
      + disable_api_termination              = (known after apply)
      + ebs_optimized                        = (known after apply)
      + get_password_data                    = false
      + host_id                              = (known after apply)
      + host_resource_group_arn              = (known after apply)
      + iam_instance_profile                 = (known after apply)
      + id                                   = (known after apply)
      + instance_initiated_shutdown_behavior = (known after apply)
      + instance_lifecycle                   = (known after apply)
      + instance_state                       = (known after apply)
      + instance_type                        = "t2.micro"
      + ipv6_address_count                   = (known after apply)
      + ipv6_addresses                       = (known after apply)
      + key_name                             = (known after apply)
      + monitoring                           = (known after apply)
      + outpost_arn                          = (known after apply)
      + password_data                        = (known after apply)
      + placement_group                      = (known after apply)
      + placement_partition_number           = (known after apply)
      + primary_network_interface_id         = (known after apply)
      + private_dns                          = (known after apply)
      + private_ip                           = (known after apply)
      + public_dns                           = (known after apply)
```

3. Apply Changes:

```
PS E:\aws-terraform-demo> terraform apply

Terraform used the selected providers to generate the following execution plan. Resource actions are indicated with the following symbols:
  + create

Terraform will perform the following actions:

  # aws_instance.My-instance[0] will be created
  + resource "aws_instance" "My-instance" {
      + ami                                  = "ami-05fb0b8c1424f266b"
      + arn                                  = (known after apply)
      + associate_public_ip_address          = (known after apply)
      + availability_zone                    = (known after apply)
      + cpu_core_count                       = (known after apply)
      + cpu_threads_per_core                 = (known after apply)
      + disable_api_stop                     = (known after apply)
      + disable_api_termination              = (known after apply)
      + ebs_optimized                        = (known after apply)
      + get_password_data                    = false
      + host_id                              = (known after apply)
      + host_resource_group_arn              = (known after apply)
      + iam_instance_profile                 = (known after apply)
      + id                                   = (known after apply)
      + instance_initiated_shutdown_behavior = (known after apply)
      + instance_lifecycle                   = (known after apply)
      + instance_state                       = (known after apply)
```

```
Do you want to perform these actions?
  Terraform will perform the actions described above.
  Only 'yes' will be accepted to approve.

  Enter a value: yes

aws_instance.My-instance[0]: Creating...
aws_instance.My-instance[0]: Still creating... [10s elapsed]
aws_instance.My-instance[0]: Still creating... [20s elapsed]
aws_instance.My-instance[0]: Still creating... [30s elapsed]
aws_instance.My-instance[0]: Creation complete after 37s [id=i-05ca8f5871186f074]

Apply complete! Resources: 1 added, 0 changed, 0 destroyed.
PS E:\aws-terraform-demo>
```

4. Verify Resources:



5. Cleanup Resources:

```
Plan: 0 to add, 0 to change, 1 to destroy.

Do you really want to destroy all resources?
  Terraform will destroy all your managed infrastructure, as shown above.
  There is no undo. Only 'yes' will be accepted to confirm.

  Enter a value: yes

aws_instance.My-instance[0]: Destroying... [id=i-05ca8f5871186f074]
aws_instance.My-instance[0]: Still destroying... [id=i-05ca8f5871186f074, 10s elapsed]
aws_instance.My-instance[0]: Destruction complete after 12s

Destroy complete! Resources: 1 destroyed.
PS E:\aws-terraform-demo>
```