

Lab Exercise 9– Creating Multiple EC2 Instances with for each in Terraform

Objective:

Learn how to use for each in Terraform to create multiple AWS EC2 instances with specific settings for each instance.

Prerequisites:

- Terraform installed on your machine.
- AWS CLI configured with the necessary credentials.

Steps:

1. Create a Terraform Directory:

```
mkdir terraform-ec2-for-each
cd terraform-ec2-for-each
```

- Create Terraform Configuration Files:
- Create a file named main.tf:

main.tf

```
provider "aws" {
  region = "ap-south-1"
}

variable "instances" {
  description = "Map of EC2 instances with settings"
  default = {
    "instance1" = {
```

```
ami      = "ami-0c55b159cbfafa1fo"
instance_type = "t2.micro"
},
"instance2" = {
  ami      = "ami-0123456789abcdefo"
  instance_type = "t2. micro "
},
"instance3" = {
  ami      = "ami-987654321ofedcbao"
  instance_type = "t2. micro "
}
}

resource "aws_instance" "ec2_instances" {
  for_each = var.instances
  ami      = var.instances[each.key].ami
  instance_type = var.instances[each.key].instance_type
  tags = {
    Name = "EC2-Instance-${each.key}"
  }
}
```

- Replace "your-key-pair-name" and "your-subnet-id" with your actual key pair name and subnet ID.
- In this configuration, we define a variable instances as a map containing settings for each EC2 instance. The aws_instance resource is then used with for_each to create instances based on the map.

2. Initialize and Apply:

- Run the following Terraform commands to initialize and apply the configuration:

```
terraform init
terraform apply
```

- Terraform will prompt you to confirm the creation of EC2 instances. Type yes and press Enter.

3. Verify Instances in AWS Console:

- Log in to the AWS Management Console and navigate to the EC2 service.
- Verify that the specified EC2 instances with the specified names and settings have been created.

4. Update Instance Configuration:

- If you want to modify the EC2 instance configuration, update the main.tf file with the desired changes.
- Rerun the terraform apply command to apply the changes:

```
terraform apply
```

5. Clean Up:

- After testing, you can clean up the EC2 instances:


```
terraform destroy
```

- Confirm the destruction by typing yes.


6. Conclusion:

This lab exercise demonstrates how to use the `for_each` construct in Terraform to create multiple AWS EC2 instances with specific settings for each instance. The use of a map allows you to define and manage settings for each instance individually.

Experiment with different instance types, AMIs, and settings in the main.tf file to observe how Terraform provisions resources based on your configuration.



```
1 terraform {
2   required_providers {
3     aws = {
4       source = "hashicorp/aws"
5       version = "5.31.0"
6     }
7   }
8 }
9
```



```
1 provider "aws" {
2   region = "ap-south-1"
3   access_key = "AKIAWCHJE0QYJV3PQHM2"
4   secret_key = "3mbl8074QL9vqQXa2V270l/r9z11UeHfnAk7KfaE"
5 }
6
7 variable "instances" {
8   description = "Map of EC2 instances with settings"
9   default = {
10     "instance1" = {
11       ami = "ami-0e670eb768a5fc3d4"
12       instance_type = "t2.micro"
13     },
14     "instance2" = {
15       ami = "ami-0e670eb768a5fc3d4"
16       instance_type = "t2.micro"
17     },
18     "instance3" = {
19       ami = "ami-0e670eb768a5fc3d4"
20       instance_type = "t2.micro"
21     },
22     "instance4" = {
23       ami = "ami-0e670eb768a5fc3d4"
24       instance_type = "t2.micro"
25     },
26     "instance5" = {
27       ami = "ami-0e670eb768a5fc3d4"
28       instance_type = "t2.micro"
29     }
30   }
31 }
32 resource "aws_instance" "ec2_instances" {
33   for_each = var.instances
34   ami = var.instances[each.key].ami
35   instance_type = var.instances[each.key].instance_type
36   tags = {
37     Name = "Raghav-Instance-${each.key}"
38   }
39 }
```

```
31 }
32 resource "aws_instance" "ec2_instances" {
33   for_each = var.instances
34   ami      = var.instances[each.key].ami
35   instance_type = var.instances[each.key].instance_type
36   tags = {
37     Name = "Raghav-Instance-${each.key}"
38   }
39 }
40
```

```
PS C:\Users\anu39\Terraform-Script> terraform init
```

Initializing the backend...

Initializing provider plugins...

- Finding hashicorp/aws versions matching "5.31.0"...
- Installing hashicorp/aws v5.31.0...
- Installed hashicorp/aws v5.31.0 (signed by HashiCorp)

Terraform has created a lock file **.terraform.lock.hcl** to record the provider selections it made above. Include this file in your version control repository so that Terraform can guarantee to make the same selections by default when you run "terraform init" in the future.

Terraform has been successfully initialized!

You may now begin working with Terraform. Try running "terraform plan" to see any changes that are required for your infrastructure. All Terraform commands should now work.

If you ever set or change modules or backend configuration for Terraform, rerun this command to reinitialize your working directory. If you forget, other commands will detect it and remind you to do so if necessary.

```
PS C:\Users\anu39\Terraform-Script> terraform validate
Success! The configuration is valid.
```

```
PS C:\Users\anu39\Terraform-Script> terraform plan
```

Terraform used the selected providers to generate the following execution plan. Resource actions are indicated with the following symbols:
+ create

Terraform will perform the following actions:

```
# aws_instance.ec2_instances["instance1"] will be created
+ resource "aws_instance" "ec2_instances" {
  + ami                    = "ami-0e670eb768a5fc3d4"
  + arn                   = (known after apply)
  + associate_public_ip_address = (known after apply)
  + availability_zone       = (known after apply)
  + cpu_core_count          = (known after apply)
  + cpu_threads_per_core    = (known after apply)
  + disable_api_stop        = (known after apply)
  + disable_api_termination = (known after apply)
  + ebs_optimized           = (known after apply)
  + get_password_data       = false
  + host_id                 = (known after apply)
  + host_resource_group_arn = (known after apply)
  + iam_instance_profile    = (known after apply)
  + id                      = (known after apply)
  + instance_initiated_shutdown_behavior = (known after apply)
  + instance_lifecycle      = (known after apply)
  + instance_state          = (known after apply)
  + instance_type           = "t2.micro"
  + ipv6_address_count       = (known after apply)
  + ipv6_addresses          = (known after apply)
  + key_name                 = (known after apply)
  + monitoring               = (known after apply)
  + outpost_arn              = (known after apply)
  + password_data           = (known after apply)
  + placement_group          = (known after apply)
  + placement_partition_number = (known after apply)
  + primary_network_interface_id = (known after apply)
  + public_dns               = (known after apply)
  + public_ip               = (known after apply)
  + secondary_private_ips    = (known after apply)
  + security_groups          = (known after apply)
  + source_dest_check        = true
  + spot_instance_request_id = (known after apply)
  + subnet_id               = (known after apply)
  + tags                    = {
    + "Name" = "Raghav-Instance-instance1"
  }
  + tags_all                = {
    + "Name" = "Raghav-Instance-instance1"
  }
  + tenancy                 = (known after apply)
  + user_data               = (known after apply)
  + user_data_base64        = (known after apply)
  + user_data_replace_on_change = false
  + vpc_security_group_ids  = (known after apply)
}

# aws_instance.ec2_instances["instance2"] will be created
+ resource "aws_instance" "ec2_instances" {
  + ami                    = "ami-0e670eb768a5fc3d4"
  + arn                   = (known after apply)
  + associate_public_ip_address = (known after apply)
  + availability_zone       = (known after apply)
  + cpu_core_count          = (known after apply)
  + cpu_threads_per_core    = (known after apply)
  + disable_api_stop        = (known after apply)
  + disable_api_termination = (known after apply)
  + ebs_optimized           = (known after apply)
  + get_password_data       = false
  + host_id                 = (known after apply)
  + host_resource_group_arn = (known after apply)
  + iam_instance_profile    = (known after apply)
  + id                      = (known after apply)
```

```

+ password_data           = (known after apply)
+ placement_group         = (known after apply)
+ placement_partition_number = (known after apply)
+ primary_network_interface_id = (known after apply)
+ private_dns             = (known after apply)
+ private_ip              = (known after apply)
+ public_dns              = (known after apply)
+ public_ip               = (known after apply)
+ secondary_private_ips   = (known after apply)
+ security_groups          = (known after apply)
+ source_dest_check        = true
+ spot_instance_request_id = (known after apply)
+ subnet_id               = (known after apply)
+ tags                     = {
  + "Name" = "Raghav-Instance-instances5"
}
+ tags_all                 = {
  + "Name" = "Raghav-Instance-instances5"
}
+ tenancy                  = (known after apply)
+ user_data                = (known after apply)
+ user_data_base64         = (known after apply)
+ user_data_replace_on_change = false
+ vpc_security_group_ids   = (known after apply)
}

```

Plan: 5 to add, 0 to change, 0 to destroy.

Note: You didn't use the -out option to save this plan, so Terraform can't guarantee to take exactly these actions if you run "terraform apply" now.

PS C:\Users\anu39\Terraform-Script>

PS C:\Users\anu39\Terraform-Script> terraform apply --auto-approve

Terraform used the selected providers to generate the following execution plan. Resource actions are indicated with the following symbols:

+ create

Terraform will perform the following actions:

```

# aws_instance.ec2_instances["instance1"] will be created
+ resource "aws_instance" "ec2_instances" {
  + ami                  = "ami-0e670eb768a5fc3d4"
  + arn                  = (known after apply)
  + associate_public_ip_address = (known after apply)
  + availability_zone     = (known after apply)
  + cpu_core_count        = (known after apply)
  + cpu_threads_per_core   = (known after apply)
  + disable_api_stop       = (known after apply)
  + disable_api_termination = (known after apply)
  + ebs_optimized          = (known after apply)
  + get_password_data      = false
  + host_id                = (known after apply)
  + host_resource_group_arn = (known after apply)
  + iam_instance_profile   = (known after apply)
  + id                    = (known after apply)
  + instance_initiated_shutdown_behavior = (known after apply)
  + instance_lifecycle     = (known after apply)
  + instance_state         = (known after apply)
  + instance_type          = "t2.micro"
  + ipv6_address_count      = (known after apply)
  + ipv6_addresses         = (known after apply)
  + key_name               = (known after apply)
  + monitoring              = (known after apply)
  + outpost_arn            = (known after apply)
  + password_data          = (known after apply)
  + placement_group        = (known after apply)
  + placement_partition_number = (known after apply)
}

```

```

+ tenancy                  = (known after apply)
+ user_data                = (known after apply)
+ user_data_base64         = (known after apply)
+ user_data_replace_on_change = false
+ vpc_security_group_ids   = (known after apply)
}

```

Plan: 5 to add, 0 to change, 0 to destroy.

```

aws_instance.ec2_instances["instances5"]: Creating...
aws_instance.ec2_instances["instance3"]: Creating...
aws_instance.ec2_instances["instance4"]: Creating...
aws_instance.ec2_instances["instance1"]: Creating...
aws_instance.ec2_instances["instance2"]: Creating...
aws_instance.ec2_instances["instance1"]: Still creating... [10s elapsed]
aws_instance.ec2_instances["instance3"]: Still creating... [10s elapsed]
aws_instance.ec2_instances["instance4"]: Still creating... [10s elapsed]
aws_instance.ec2_instances["instances5"]: Still creating... [10s elapsed]
aws_instance.ec2_instances["instance2"]: Still creating... [10s elapsed]
aws_instance.ec2_instances["instance5"]: Still creating... [20s elapsed]
aws_instance.ec2_instances["instance3"]: Still creating... [20s elapsed]
aws_instance.ec2_instances["instance1"]: Still creating... [20s elapsed]
aws_instance.ec2_instances["instance4"]: Still creating... [20s elapsed]
aws_instance.ec2_instances["instance2"]: Still creating... [20s elapsed]
aws_instance.ec2_instances["instance2"]: Creation complete after 22s [id=i-0586b0a46e9fc3007]
aws_instance.ec2_instances["instance4"]: Still creating... [30s elapsed]
aws_instance.ec2_instances["instance3"]: Still creating... [30s elapsed]
aws_instance.ec2_instances["instances5"]: Still creating... [30s elapsed]
aws_instance.ec2_instances["instance1"]: Still creating... [30s elapsed]
aws_instance.ec2_instances["instance4"]: Creation complete after 32s [id=i-0f4b88dc95c1a0510]
aws_instance.ec2_instances["instance1"]: Creation complete after 32s [id=i-0d3ac4e6e5955fcc0]
aws_instance.ec2_instances["instances5"]: Creation complete after 32s [id=i-0f506c33e416a9c88]
aws_instance.ec2_instances["instance3"]: Creation complete after 32s [id=i-0c4389dd9c7efa281]

```

Apply complete! Resources: 5 added, 0 changed, 0 destroyed.

PS C:\Users\anu39\Terraform-Script>

Instances (5)

Info

🔄

Connect

Instance state ▾

Actions ▾

Launch instances

▼

🔍 Find Instance by attribute or tag (case-sensitive)

Any state ▾

Instance state = running

✕

Clear filters

< 1 > ⚙

<input type="checkbox"/>	Name <div>↗</div> ▾	Instance ID	Instance state ▾	Instance type ▾	Status check	Alarm status	Availability Zone ▾	Public IPv4 DNS
<input type="checkbox"/>	Raghav-Instan...	i-0f506c33e416a9c88	<div>✔ Running</div> <div>🔍</div> <div>🔍</div>	t2.micro	<div>🔄 Initializing</div>	<div>View alarms +</div>	ap-south-1a	ec2-13-233-97-69.a
<input type="checkbox"/>	Raghav-Instan...	i-0c4389dd9c7efa281	<div>✔ Running</div> <div>🔍</div> <div>🔍</div>	t2.micro	<div>🔄 Initializing</div>	<div>View alarms +</div>	ap-south-1a	ec2-13-234-202-10
<input type="checkbox"/>	Raghav-Instan...	i-0f4b88dc95c1a0510	<div>✔ Running</div> <div>🔍</div> <div>🔍</div>	t2.micro	<div>🔄 Initializing</div>	<div>View alarms +</div>	ap-south-1a	ec2-3-110-131-129
<input type="checkbox"/>	Raghav-Instan...	i-0d3ac4e6e5955fcc0	<div>✔ Running</div> <div>🔍</div> <div>🔍</div>	t2.micro	<div>🔄 Initializing</div>	<div>View alarms +</div>	ap-south-1a	ec2-13-233-130-23
<input type="checkbox"/>	Raghav-Instan...	i-0586b0a46e9fc3007	<div>✔ Running</div> <div>🔍</div> <div>🔍</div>	t2.micro	<div>🔄 Initializing</div>	<div>View alarms +</div>	ap-south-1a	ec2-3-108-193-217

```
PS C:\Users\anu39\Terraform-Script> terraform destroy --auto-approve
```

```
aws_instance.ec2_instances["instance1"]: Refreshing state... [id=i-0d3ac4e6e5955fcc0]
aws_instance.ec2_instances["instance5"]: Refreshing state... [id=i-0f506c33e416a9c88]
aws_instance.ec2_instances["instance3"]: Refreshing state... [id=i-0c4389dd9c7efa281]
aws_instance.ec2_instances["instance4"]: Refreshing state... [id=i-0f4b88dc95c1a0510]
aws_instance.ec2_instances["instance2"]: Refreshing state... [id=i-0586b0a46e9fc3007]
```

Terraform used the selected providers to generate the following execution plan. Resource actions are indicated with the following symbols:

- destroy

Terraform will perform the following actions:

```
}
}

Plan: 0 to add, 0 to change, 5 to destroy.
aws_instance.ec2_instances["instance1"]: Destroying... [id=i-0d3ac4e6e5955fcc0]
aws_instance.ec2_instances["instance3"]: Destroying... [id=i-0c4389dd9c7efa281]
aws_instance.ec2_instances["instance5"]: Destroying... [id=i-0f506c33e416a9c88]
aws_instance.ec2_instances["instance4"]: Destroying... [id=i-0f4b88dc95c1a0510]
aws_instance.ec2_instances["instance2"]: Destroying... [id=i-0586b0a46e9fc3007]
aws_instance.ec2_instances["instance1"]: Still destroying... [id=i-0d3ac4e6e5955fcc0, 10s elapsed]
aws_instance.ec2_instances["instance3"]: Still destroying... [id=i-0c4389dd9c7efa281, 10s elapsed]
aws_instance.ec2_instances["instance2"]: Still destroying... [id=i-0586b0a46e9fc3007, 10s elapsed]
aws_instance.ec2_instances["instance4"]: Still destroying... [id=i-0f4b88dc95c1a0510, 10s elapsed]
aws_instance.ec2_instances["instance5"]: Still destroying... [id=i-0f506c33e416a9c88, 10s elapsed]
aws_instance.ec2_instances["instance3"]: Still destroying... [id=i-0c4389dd9c7efa281, 20s elapsed]
aws_instance.ec2_instances["instance1"]: Still destroying... [id=i-0d3ac4e6e5955fcc0, 20s elapsed]
aws_instance.ec2_instances["instance2"]: Still destroying... [id=i-0586b0a46e9fc3007, 20s elapsed]
aws_instance.ec2_instances["instance4"]: Still destroying... [id=i-0f4b88dc95c1a0510, 20s elapsed]
aws_instance.ec2_instances["instance5"]: Still destroying... [id=i-0f506c33e416a9c88, 20s elapsed]
aws_instance.ec2_instances["instance1"]: Still destroying... [id=i-0d3ac4e6e5955fcc0, 30s elapsed]
aws_instance.ec2_instances["instance3"]: Still destroying... [id=i-0c4389dd9c7efa281, 30s elapsed]
aws_instance.ec2_instances["instance5"]: Still destroying... [id=i-0f506c33e416a9c88, 30s elapsed]
aws_instance.ec2_instances["instance2"]: Still destroying... [id=i-0586b0a46e9fc3007, 30s elapsed]
aws_instance.ec2_instances["instance4"]: Still destroying... [id=i-0f4b88dc95c1a0510, 30s elapsed]
aws_instance.ec2_instances["instance3"]: Destruction complete after 30s
aws_instance.ec2_instances["instance5"]: Destruction complete after 30s
aws_instance.ec2_instances["instance4"]: Destruction complete after 30s
aws_instance.ec2_instances["instance1"]: Destruction complete after 30s
aws_instance.ec2_instances["instance2"]: Still destroying... [id=i-0586b0a46e9fc3007, 40s elapsed]
aws_instance.ec2_instances["instance2"]: Destruction complete after 40s
```

Destroy complete! Resources: 5 destroyed.

```
PS C:\Users\anu39\Terraform-Script>
```


Instances (10) [info](#)

Refresh

Connect

Instance state

Actions

Launch instances

Find Instance by attribute or tag (case-sensitive)

Any state

<

1

>

<input type="checkbox"/>	Name ↗	Instance ID	Instance state <div></div>	Instance type <div></div>	Status check	Alarm status	Availability Zone <div></div>	Public IPv4 DNS
<input type="checkbox"/>	Raghav-Instan...	i-0afc6b8921201f7a0	<div></div> Terminated 🔍 🔍	t2.micro	–	View alarms +	ap-south-1a	–
<input type="checkbox"/>	Raghav-Instan...	i-044f8fcedf4f2712e	<div></div> Terminated 🔍 🔍	t2.micro	–	View alarms +	ap-south-1a	–
<input type="checkbox"/>	Raghav-Instan...	i-0f506c33e416a9c88	<div></div> Terminated 🔍 🔍	t2.micro	–	View alarms +	ap-south-1a	–
<input type="checkbox"/>	Raghav-Instan...	i-0c4389dd9c7efa281	<div></div> Terminated 🔍 🔍	t2.micro	–	View alarms +	ap-south-1a	–
<input type="checkbox"/>	Raghav-Instan...	i-0c9956a74f040f5f9	<div></div> Terminated 🔍 🔍	t2.micro	–	View alarms +	ap-south-1a	–
<input type="checkbox"/>	Raghav-Instan...	i-0c48a4677c62a4637	<div></div> Terminated 🔍 🔍	t2.micro	–	View alarms +	ap-south-1a	–
<input type="checkbox"/>	Raghav-Instan...	i-0f4b88dc95c1a0510	<div></div> Terminated 🔍 🔍	t2.micro	–	View alarms +	ap-south-1a	–
<input type="checkbox"/>	Raghav-Instan...	i-0d3ac4e6e5955fcc0	<div></div> Terminated 🔍 🔍	t2.micro	–	View alarms +	ap-south-1a	–
<input type="checkbox"/>	Raghav-Instan...	i-0586b0a46e9fc3007	<div></div> Terminated 🔍 🔍	t2.micro	–	View alarms +	ap-south-1a	–
<input type="checkbox"/>	Raghav-Instan...	i-0ab2f7c7ccbed11c7	<div></div> Terminated 🔍 🔍	t2.micro	–	View alarms +	ap-south-1a	–