

OUTPUT:

CREATING TRIGGER BEFORE INSERTING INTO TABLE

```
SQL> CREATE TABLE STUDENTS(  
2 ID NUMBER PRIMARY KEY,  
3 NAME VARCHAR(15),  
4 COURSE VARCHAR(10),  
5 SCORE NUMBER  
6 );
```

Table created.

```
SQL> CREATE OR REPLACE TRIGGER before_insert_students  
2 BEFORE INSERT ON students  
3 FOR EACH ROW  
4 BEGIN  
5   IF :NEW.score > 100 THEN  
6     :NEW.score := 100;  
7   END IF;  
8 END;  
9 /
```

Trigger created.

```
SQL> INSERT INTO students (id, name, course, score) VALUES (1, 'Alice', 'Python', 95);
```

1 row created.

```
SQL> INSERT INTO students (id, name, course, score) VALUES (2, 'Bob', 'Python', 105);
```

1 row created.

```
SQL> SELECT * FROM STUDENTS;
```

ID	NAME	COURSE	SCORE
1	Alice	Python	95
2	Bob	Python	100

CREATING TRIGGER BEFORE UPDATING DATA FROM TABLE

```
SQL> CREATE TABLE employees (  
2   employee_id NUMBER PRIMARY KEY,  
3   employee_name VARCHAR2(50),  
4   salary NUMBER(10, 2),  
5   department VARCHAR2(50)  
6 );
```

Table created.

```

SQL> CREATE OR REPLACE TRIGGER before_update_employee
2 BEFORE UPDATE ON employees
3 FOR EACH ROW
4 BEGIN
5     DBMS_OUTPUT.PUT_LINE('Updating employee ' || :OLD.employee_name || ' in department ' ||
        :OLD.department);
6 END;
7 /

```

Trigger created.

```

SQL> INSERT INTO employees (employee_id, employee_name, salary, department)
2 VALUES (1, 'John Doe', 50000, 'Engineering');

```

1 row created.

```

SQL> UPDATE employees
2 SET salary = 55000
3 WHERE employee_id = 1;

```

Updating employee John Doe in department Engineering

1 row updated.

CREATING TRIGGER BEFORE DELETING DATA FROM TABLE

```

SQL> CREATE TABLE orders (
2     order_id NUMBER PRIMARY KEY,
3     customer_name VARCHAR2(100),
4     order_date DATE,
5     total_amount NUMBER(10, 2)
6 );

```

Table created.

```

SQL> CREATE OR REPLACE TRIGGER before_delete_order
2 BEFORE DELETE ON orders
3 FOR EACH ROW
4 BEGIN
5     DBMS_OUTPUT.PUT_LINE('Deleting order ' || :OLD.order_id || ' for customer ' ||
        :OLD.customer_name);
6 END;
7 /

```

Trigger created.

```

SQL> INSERT INTO orders (order_id, customer_name, order_date, total_amount) VALUES (1, 'Jane
Smith', SYSDATE, 150.00);

```

1 row created.

```
SQL> DELETE FROM orders WHERE order_id = 1;
```

Deleting order 1 for customer Jane Smith

1 row deleted.