中国海洋大学
计算机网络
2019 秋季学期

作业 4

姓名: 秦浩　　学号:17020031051　　2019 年 11 月 8 日

1　实验环境

1 Deepin 15.11 x64
- gcc (Debian 6.3.0-18+deb9u1) 6.3.0
- g++ (Debian 6.3.0-18+deb9u1) 6.3.0

2 Windows 10 x64
- Visual C++ 6.0

2　编程作业

2.1　编程实现 PING 功能

程序代码如下 ping.c 所示。ping 命令的工作原理是：向网络上的另一个主机系统发送 ICMP 报文，如果指定系统得到了报文，它将把报文一模一样地传回给发送者。

2.1.1 IP 报头数据结构为：

```
struct ip
{
#if __BYTE_ORDER == __LITTLE_ENDIAN
    unsigned int ip_hl:4;       /* header length
       */
    unsigned int ip_v:4;        /* version */
#endif
#if __BYTE_ORDER == __BIG_ENDIAN
    unsigned int ip_v:4;        /* version */
    unsigned int ip_hl:4;       /* header length
       */
#endif
    u_int8_t ip_tos;            /* type of service
        */
    u_short ip_len;         /* total length */
```

```
    u_short ip_id;          /* identification */
    u_short ip_off;         /* fragment offset
        field */
#define IP_RF 0x8000            /* reserved
    fragment flag */
#define IP_DF 0x4000            /* dont fragment
    flag */
#define IP_MF 0x2000            /* more fragments
    flag */
#define IP_OFFMASK 0x1fff       /* mask for
    fragmenting bits */
    u_int8_t ip_ttl;            /* time to live */
    u_int8_t ip_p;          /* protocol */
    u_short ip_sum;         /* checksum */
    struct in_addr ip_src, ip_dst;  /* source and
        dest address */
};
```

2.1.2 ICMP 数据结构为:

```
struct icmp
{
u_int8_t  icmp_type;  /* type of message, see
    below */
u_int8_t  icmp_code;  /* type sub code */
u_int16_t icmp_cksum; /* ones complement checksum
    of struct */
union
{
    u_char ih_pptr;     /* ICMP_PARAMPROB */
    struct in_addr ih_gwaddr;   /* gateway address
        */
    struct ih_idseq     /* echo datagram */
    {
    u_int16_t icd_id;
    u_int16_t icd_seq;
    } ih_idseq;
```

```
        u_int32_t ih_void;
        /* ICMP_UNREACH_NEEDFRAG -- Path MTU Discovery
            (RFC1191) */
        struct ih_pmtu
        {
        u_int16_t ipm_void;
        u_int16_t ipm_nextmtu;
        } ih_pmtu;
        struct ih_rtradv
        {
        u_int8_t irt_num_addrs;
        u_int8_t irt_wpa;
        u_int16_t irt_lifetime;
        } ih_rtradv;
    } icmp_hun;
    #define icmp_pptr   icmp_hun.ih_pptr
    #define icmp_gwaddr icmp_hun.ih_gwaddr
    #define icmp_id     icmp_hun.ih_idseq.icd_id
    #define icmp_seq        icmp_hun.ih_idseq.icd_seq
    #define icmp_void   icmp_hun.ih_void
    #define icmp_pmvoid icmp_hun.ih_pmtu.ipm_void
    #define icmp_nextmtu    icmp_hun.ih_pmtu.
       ipm_nextmtu
    #define icmp_num_addrs  icmp_hun.ih_rtradv.
       irt_num_addrs
    #define icmp_wpa    icmp_hun.ih_rtradv.irt_wpa
    #define icmp_lifetime   icmp_hun.ih_rtradv.
       irt_lifetime
    union
    {
        struct
        {
        u_int32_t its_otime;
        u_int32_t its_rtime;
        u_int32_t its_ttime;
        } id_ts;
```

```
        struct
        {
        struct ip idi_ip;
        /* options and then 64 bits of data */
        } id_ip;
        struct icmp_ra_addr id_radv;
        u_int32_t    id_mask;
        u_int8_t     id_data[1];
    } icmp_dun;
    #define icmp_otime   icmp_dun.id_ts.its_otime
    #define icmp_rtime   icmp_dun.id_ts.its_rtime
    #define icmp_ttime   icmp_dun.id_ts.its_ttime
    #define icmp_ip      icmp_dun.id_ip.idi_ip
    #define icmp_radv    icmp_dun.id_radv
    #define icmp_mask    icmp_dun.id_mask
    #define icmp_data    icmp_dun.id_data
    };
```

程序运行结果如图 1 所示：



图 1: ping.c 运行结果

2.2 获取所在局域网的子网掩码，用实现的 PING 程序查询子网内所有 IP 地址的在线状态

连接的校园网为 OUC-AUTO, 本机地址为 10.115.240.252，子网掩码为 255.255.192.0。

2.3 编程实现 tracert 功能

程序源码如下 tacert.cpp 所示。程序实现是向目的主机发送一个 ICMP 回显请求报文，初始时 TTL （IP 头部生存时间（time to live））等于 1 ，这

样当该数据报抵达途中的第一个路由器时，TTL 的值就被减为 0，导致发送超时错误，因此该路由生成一份 ICMP 超时差错报文返回给源主机。随后，主机将数据报的 TTL 值递增 1 ，以便 IP 报能传送到下一个路由器，并由下一个路由器生成 ICMP 超时差错报文返回给源主机。不断重复这个过程，直到数据报达到目的主机或超过跳数限制，到达目的主机后，目的主机返回 ICMP 回显应答报文。这样，源主机只需要对返回的每一份 ICMP 报文进行解析处理，就可以掌握数据报从源主机到达目的主机途中所经过的路由信息。

用到的数据结构如下所示：

```
//IP报头
typedef struct IP_HEADER
{
    unsigned char hdr_len:4;        //4位头部长度
    unsigned char version:4;        //4位版本号
    unsigned char tos;              //8位服务类型
    unsigned short total_len;       //16位总长度
    unsigned short identifier;      //16位标识符
    unsigned short frag_and_flags; //3位标志加13位
        片偏移
    unsigned char ttl;              //8位生存时间
    unsigned char protocol;         //8位上层协议号
    unsigned short checksum;        //16位校验和
    unsigned long sourceIP;         //32位源IP地址
    unsigned long destIP;           //32位目的IP地
        址
} IP_HEADER;

//ICMP报头
typedef struct ICMP_HEADER
{
    BYTE type;     //8位类型字段
    BYTE code;     //8位代码字段
    USHORT cksum; //16位校验和
    USHORT id;     //16位标识符
    USHORT seq;    //16位序列号
} ICMP_HEADER;
```

```
//报文解码结构
typedef struct DECODE_RESULT
{
    USHORT usSeqNo;         //序列号
    DWORD dwRoundTripTime; //往返时间
    in_addr dwIPaddr;       //返回报文的IP地址
}DECODE_RESULT;
```

2.4 用实现的 tracert 程序查询到 jd.com 的每一跳路由器 IP 地址，查询 IP 名称并分析层级关系，画出一个可能的 IP 层次关系图

3 程序源码

3.1 ping.c

```
#include <stdio.h>
#include <signal.h>
#include <arpa/inet.h>
#include <sys/types.h>
#include <sys/socket.h>
#include <unistd.h>
#include <netinet/in.h>
#include <netinet/ip.h>
#include <netinet/ip_icmp.h>
#include <netdb.h>
#include <setjmp.h>
#include <errno.h>

#define PACKET_SIZE 4096
#define MAX_WAIT_TIME 5
#define MAX_NO_PACKETS 3

char sendpacket[PACKET_SIZE];
```

```
char recvpacket[PACKET_SIZE];
int sockfd, datalen = 56;
int nsend = 0, nreceived = 0;
struct sockaddr_in dest_addr;
pid_t pid;
struct sockaddr_in from;
struct timeval tvrecv;

void statistics(int signo);
unsigned short cal_chksum(unsigned short *addr,
   int len);
int pack(int pack_no);
void send_packet(void);
void recv_packet(void);
int unpack(char *buf, int len);
void tv_sub(struct timeval *out, struct timeval *
   in);

void statistics(int signo)
{
    printf("\n--------------------PING statistics
       -------------------\n");
    printf("%d packets transmitted, %d received ,
       %%%d lost\n", nsend, nreceived,
        (nsend - nreceived) / nsend * 100);
    close(sockfd);
    exit(1);
}
/*校验和算法*/
unsigned short cal_chksum(unsigned short *addr,
   int len)
{
    int nleft = len;
    int sum = 0;
    unsigned short *w = addr;
    unsigned short answer = 0;
```

```
    /*把ICMP报头二进制数据以2字节为单位累加起来*/
    while (nleft > 1)
    {
        sum += *w++;
        nleft -= 2;
    }
    /*若ICMP报头为奇数个字节，会剩下最后一字节。把
       最后一个字节视为一个2字节数据的高字节，这个
       2字节数据的低字节为0，继续累加*/
    if (nleft == 1)
    {
        *(unsigned char *)(&answer) = *(unsigned
           char *)w;
        sum += answer;
    }
    sum = (sum >> 16) + (sum & 0xffff);
    sum += (sum >> 16);
    answer = ~sum;
    return answer;
}
/*设置ICMP报头*/
int pack(int pack_no)
{
    int i, packsize;
    struct icmp *icmp;
    struct timeval *tval;
    icmp = (struct icmp *)sendpacket;
    icmp->icmp_type = ICMP_ECHO;
    icmp->icmp_code = 0;
    icmp->icmp_cksum = 0;
    icmp->icmp_seq = pack_no;
    icmp->icmp_id = pid;
    packsize = 8 + datalen;
    tval = (struct timeval *)icmp->icmp_data;
    gettimeofday(tval, NULL);
```

```
                                                    /*记
        录发送时间*/
    icmp->icmp_cksum = cal_chksum((unsigned short
        *)icmp, packsize); /*校验算法*/
    return packsize;
}
/*发送三个ICMP报文*/
void send_packet()
{
    int packetsize;
    while (nsend < MAX_NO_PACKETS)
    {
        nsend++;
        packetsize = pack(nsend); /*设置ICMP报头*/
        if (sendto(sockfd, sendpacket, packetsize,
            0,
                (struct sockaddr *)&dest_addr,
                    sizeof(dest_addr)) < 0)
        {
            perror("sendto error");
            continue;
        }
        sleep(1); /*每隔一秒发送一个ICMP报文*/
    }
}
/*接收所有ICMP报文*/
void recv_packet()
{
    int n, fromlen;
    extern int errno;
    signal(SIGALRM, statistics);
    fromlen = sizeof(from);
    while (nreceived < nsend)
    {
        alarm(MAX_WAIT_TIME);
        if ((n = recvfrom(sockfd, recvpacket,
```

```
            sizeof(recvpacket), 0,
                        (struct sockaddr *)&from,
                            &fromlen)) < 0)
        {
            if (errno == EINTR)
                continue;
            perror("recvfrom error");
            continue;
        }
        gettimeofday(&tvrecv, NULL); /*记录接收时
            间*/
        if (unpack(recvpacket, n) == -1)
            continue;
        nreceived++;
    }
}
/*剥去ICMP报头*/
int unpack(char *buf, int len)
{
    int i, iphdrlen;
    struct ip *ip;
    struct icmp *icmp;
    struct timeval *tvsend;
    double rtt;
    ip = (struct ip *)buf;
    iphdrlen = ip->ip_hl << 2;              /*求ip
        报头长度,即ip报头的长度标志乘4*/
    icmp = (struct icmp *)(buf + iphdrlen); /*越过
        ip报头,指向ICMP报头*/
    len -= iphdrlen;                        /*ICMP
        报头及ICMP数据报的总长度*/
    if (len < 8)                            /*小于
        ICMP报头长度则不合理*/
    {
        printf("ICMP packets\'s length is less
            than 8\n");
```

```
            return -1;
        }
        /*确保所接收的是我所发的的ICMP的回应*/
        if ((icmp->icmp_type == ICMP_ECHOREPLY) && (
           icmp->icmp_id == pid))
        {
            tvsend = (struct timeval *)icmp->icmp_data
               ;
            tv_sub(&tvrecv, tvsend);
                                        /*接收和发送
               的时间差*/
            rtt = tvrecv.tv_sec * 1000 + tvrecv.
               tv_usec / 1000; /*以毫秒为单位计算rtt*/
            /*显示相关信息*/
            printf("%d byte from %s: icmp_seq=%u ttl=%
               d rtt=%.3f ms\n",
                len,
                inet_ntoa(from.sin_addr),
                icmp->icmp_seq,
                ip->ip_ttl,
                rtt);
        }
        else
            return -1;
    }
    int main(int argc, char *argv[])
    {
        struct hostent *host;
        struct protoent *protocol;
        unsigned long inaddr = 0l;
        int waittime = MAX_WAIT_TIME;
        int size = 50 * 1024;
        if (argc < 2)
        {
            printf("usage:%s hostname/IP address\n",
               argv[0]);
```

```
        exit(1);
    }
    if ((protocol = getprotobyname("icmp")) ==
       NULL)
    {
        perror("getprotobyname");
        exit(1);
    }
    /*生成使用ICMP的原始套接字,这种套接字只有root
       才能生成*/
    if ((sockfd = socket(AF_INET, SOCK_RAW,
       protocol->p_proto)) < 0)
    {
        perror("socket error");
        exit(1);
    }
    /* 回收root权限,设置当前用户权限*/
    setuid(getuid());
    /*扩大套接字接收缓冲区到50K这样做主要为了减小
       接收缓冲区溢出的
        的可能性,若无意中ping一个广播地址或多播地
           址,将会引来大量应答*/
    setsockopt(sockfd, SOL_SOCKET, SO_RCVBUF, &
       size, sizeof(size));
    bzero(&dest_addr, sizeof(dest_addr));
    dest_addr.sin_family = AF_INET;
    /*判断是主机名还是ip地址*/
    if (inaddr = inet_addr(argv[1]) == INADDR_NONE
       )
    {
        if ((host = gethostbyname(argv[1])) ==
           NULL) /*是主机名*/
        {
            perror("gethostbyname error");
            exit(1);
        }
```

```
            memcpy((char *)&dest_addr.sin_addr, host->
                h_addr, host->h_length);
        }
        else /*是ip地址*/
            memcpy((char *)&dest_addr, (char *)&inaddr
                , host->h_length);
        /*获取main的进程id,用于设置ICMP的标志符*/
        pid = getpid();
        printf("PING %s(%s): %d bytes data in ICMP
            packets.\n", argv[1],
             inet_ntoa(dest_addr.sin_addr), datalen);
        send_packet();        /*发送所有ICMP报文*/
        recv_packet();        /*接收所有ICMP报文*/
        statistics(SIGALRM); /*进行统计*/
        return 0;
    }
    /*两个timeval结构相减*/
    void tv_sub(struct timeval *out, struct timeval *
        in)
    {
        if ((out->tv_usec -= in->tv_usec) < 0)
        {
            --out->tv_sec;
            out->tv_usec += 1000000;
        }
        out->tv_sec -= in->tv_sec;
    }
```

3.2 tracert.cpp

```
#include <iostream>
#include <winsock2.h>
#include <ws2tcpip.h>
using namespace std;

#pragma comment(lib, "Ws2_32.lib")
```

```
//IP报头
typedef struct IP_HEADER
{
    unsigned char hdr_len:4;        //4位头部长度
    unsigned char version:4;        //4位版本号
    unsigned char tos;              //8位服务类型
    unsigned short total_len;       //16位总长度
    unsigned short identifier;      //16位标识符
    unsigned short frag_and_flags; //3位标志加13位
        片偏移
    unsigned char ttl;              //8位生存时间
    unsigned char protocol;         //8位上层协议号
    unsigned short checksum;        //16位校验和
    unsigned long sourceIP;         //32位源IP地址
    unsigned long destIP;           //32位目的IP地
        址
} IP_HEADER;

//ICMP报头
typedef struct ICMP_HEADER
{
    BYTE type;     //8位类型字段
    BYTE code;     //8位代码字段
    USHORT cksum; //16位校验和
    USHORT id;     //16位标识符
    USHORT seq;    //16位序列号
} ICMP_HEADER;

//报文解码结构
typedef struct DECODE_RESULT
{
    USHORT usSeqNo;         //序列号
    DWORD dwRoundTripTime; //往返时间
    in_addr dwIPaddr;       //返回报文的IP地址
}DECODE_RESULT;
```

```
//计算网际校验和函数
USHORT checksum( USHORT *pBuf, int iSize )
{
    unsigned long cksum = 0;
    while( iSize > 1 )
    {
        cksum += *pBuf++;
        iSize -= sizeof(USHORT);
    }
    if( iSize )//如果 iSize 为正, 即为奇数个字节
    {
        cksum += *(UCHAR *)pBuf; //则在末尾补上一
            个字节, 使之有偶数个字节
    }
    cksum  = ( cksum >> 16 ) + ( cksum&0xffff );
    cksum += ( cksum >> 16 );
    return (USHORT)( ~cksum );
}

//对数据包进行解码
BOOL DecodeIcmpResponse(char * pBuf, int
   iPacketSize, DECODE_RESULT &DecodeResult,
                        BYTE ICMP_ECHO_REPLY, BYTE
                             ICMP_TIMEOUT)
{
    //检查数据报大小的合法性
    IP_HEADER* pIpHdr = ( IP_HEADER* )pBuf;
    int iIpHdrLen = pIpHdr->hdr_len * 4;    //ip报
       头的长度是以4字节为单位的

    //若数据包大小 小于 IP报头 + ICMP报头, 则数据
       报大小不合法
    if ( iPacketSize < ( int )( iIpHdrLen + sizeof
       ( ICMP_HEADER ) ) )
        return FALSE;
```

```
//根据ICMP报文类型提取ID字段和序列号字段
ICMP_HEADER *pIcmpHdr = ( ICMP_HEADER * )(
    pBuf + iIpHdrLen );//ICMP报头 = 接收到的缓
    冲数据 + IP报头
USHORT usID, usSquNo;

if( pIcmpHdr->type == ICMP_ECHO_REPLY )    //
    ICMP回显应答报文
{
    usID = pIcmpHdr->id;          //报文ID
    usSquNo = pIcmpHdr->seq;      //报文序列号
}
else if( pIcmpHdr->type == ICMP_TIMEOUT )//
    ICMP超时差错报文
{
    char * pInnerIpHdr = pBuf + iIpHdrLen +
        sizeof( ICMP_HEADER ); //载荷中的IP头
    int iInnerIPHdrLen = ( ( IP_HEADER * )
        pInnerIpHdr )->hdr_len * 4; //载荷中的
        IP头长
    ICMP_HEADER * pInnerIcmpHdr = (
        ICMP_HEADER * )( pInnerIpHdr +
        iInnerIPHdrLen );//载荷中的ICMP头

    usID = pInnerIcmpHdr->id;          //报文ID
    usSquNo = pInnerIcmpHdr->seq;      //序列号
}
else
{
    return false;
}

//检查ID和序列号以确定收到期待数据报
if( usID != ( USHORT )GetCurrentProcessId() ||
    usSquNo != DecodeResult.usSeqNo )
```

```
        {
            return false;
        }
        //记录IP地址并计算往返时间
        DecodeResult.dwIPaddr.s_addr = pIpHdr->
           sourceIP;
        DecodeResult.dwRoundTripTime = GetTickCount()
           - DecodeResult.dwRoundTripTime;

        //处理正确收到的ICMP数据报
        if ( pIcmpHdr->type == ICMP_ECHO_REPLY ||
           pIcmpHdr->type == ICMP_TIMEOUT )
        {
            //输出往返时间信息
            if(DecodeResult.dwRoundTripTime)
                cout<<"      "<<DecodeResult.
                   dwRoundTripTime<<"ms"<<flush;
            else
                cout<<"      "<<"<1ms"<<flush;
        }
        return true;
    }

    void main()
    {
        //初始化Windows sockets网络环境
        WSADATA wsa;
        WSAStartup( MAKEWORD(2,2), &wsa );
        char IpAddress[255];
        cout<<"请输入一个IP地址或域名: ";
        cin>>IpAddress;

        //得到IP地址
        u_long ulDestIP = inet_addr( IpAddress );

        //转换不成功时按域名解析
```

```
if( ulDestIP == INADDR_NONE )
{
    hostent * pHostent = gethostbyname(
       IpAddress );
    if( pHostent )
    {
        ulDestIP = ( *( in_addr* )pHostent->
           h_addr).s_addr;
    }
    else
    {
        cout<<"输入的IP地址或域名无效!"<<endl;
        WSACleanup();
        return;
    }
}
cout<<"Tracing roote to "<<IpAddress<<" with a
    maximum of 30 hops.\n"<<endl;

//填充目的端socket地址
sockaddr_in destSockAddr;
ZeroMemory( &destSockAddr, sizeof( sockaddr_in
    ) );
destSockAddr.sin_family = AF_INET;
destSockAddr.sin_addr.s_addr = ulDestIP;

//创建原始套接字
SOCKET sockRaw = WSASocket( AF_INET, SOCK_RAW,
    IPPROTO_ICMP, NULL, 0, WSA_FLAG_OVERLAPPED
    );

//超时时间
int iTimeout = 3000;

//设置接收超时时间
setsockopt( sockRaw, SOL_SOCKET, SO_RCVTIMEO,
```

```
    (char *)&iTimeout, sizeof( iTimeout ) );

//设置发送超时时间
setsockopt(sockRaw,SOL_SOCKET,SO_SNDTIMEO,(
    char *)&iTimeout,sizeof(iTimeout));

//构造ICMP回显请求消息, 并以TTL递增的顺序发送
    报文
//ICMP类型字段
const BYTE ICMP_ECHO_REQUEST = 8;     //请求回
    显
const BYTE ICMP_ECHO_REPLY   = 0;     //回显应
    答
const BYTE ICMP_TIMEOUT      = 11;    //传输超
    时

//其他常量定义
const int DEF_ICMP_DATA_SIZE   = 32;     //ICMP
    报文默认数据字段长度
const int MAX_ICMP_PACKET_SIZE = 1024;  //ICMP
    报文最大长度 (包括报头)
const DWORD DEF_ICMP_TIMEOUT   = 3000;  //回显
    应答超时时间
const int DEF_MAX_HOP          = 30;     //最大
    跳站数

//填充ICMP报文中每次发送时不变的字段
char IcmpSendBuf[ sizeof( ICMP_HEADER ) +
    DEF_ICMP_DATA_SIZE ];//发送缓冲区
memset( IcmpSendBuf, 0, sizeof( IcmpSendBuf )
    );               //初始化发送缓冲区
char IcmpRecvBuf[ MAX_ICMP_PACKET_SIZE ];
                         //接收缓冲区
memset( IcmpRecvBuf, 0, sizeof( IcmpRecvBuf )
    );               //初始化接收缓冲区
```

```
ICMP_HEADER * pIcmpHeader = ( ICMP_HEADER* )
    IcmpSendBuf;
pIcmpHeader->type = ICMP_ECHO_REQUEST; //类型
    为请求回显
pIcmpHeader->code = 0;                  //代码字
    段为0
pIcmpHeader->id   = (USHORT)
    GetCurrentProcessId();    //ID字段为当前进
    程号
memset( IcmpSendBuf + sizeof( ICMP_HEADER ), '
    E', DEF_ICMP_DATA_SIZE );//数据字段

USHORT usSeqNo      = 0;            //ICMP报文
    序列号
int iTTL            = 1;            //TTL初始
    值为1
BOOL bReachDestHost = FALSE;        //循环退出
    标志
int iMaxHot         = DEF_MAX_HOP;  //循环的最
    大次数
DECODE_RESULT DecodeResult;    //传递给报文解
    码函数的结构化参数
while( !bReachDestHost && iMaxHot-- )
{
    //设置IP报头的TTL字段
    setsockopt( sockRaw, IPPROTO_IP, IP_TTL, (
        char *)&iTTL, sizeof(iTTL) );
    cout<<iTTL<<flush;    //输出当前序号,flush
        表示将缓冲区的内容马上送进cout,把输出缓
        冲区刷新

    //填充ICMP报文中每次发送变化的字段
    ((ICMP_HEADER *)IcmpSendBuf)->cksum = 0;
                          //校验和先置为0
    ((ICMP_HEADER *)IcmpSendBuf)->seq   =
        htons(usSeqNo++);    //填充序列号
```

```
((ICMP_HEADER *)IcmpSendBuf)->cksum =
    checksum( ( USHORT * )IcmpSendBuf,
       sizeof( ICMP_HEADER ) +
       DEF_ICMP_DATA_SIZE ); //计算校验和

//记录序列号和当前时间
DecodeResult.usSeqNo          = ( (
   ICMP_HEADER* )IcmpSendBuf )->seq;    //
   当前序号
DecodeResult.dwRoundTripTime =
   GetTickCount();
                              //当前时间

//发送TCP回显请求信息
sendto( sockRaw, IcmpSendBuf, sizeof(
   IcmpSendBuf), 0, (sockaddr*)&
   destSockAddr, sizeof(destSockAddr) );

//接收ICMP差错报文并进行解析处理
sockaddr_in from;             //对端socket地
   址
int iFromLen = sizeof(from);//地址结构大小
int iReadDataLen;             //接收数据长度
while(1)
{
    //接收数据
    iReadDataLen = recvfrom( sockRaw,
       IcmpRecvBuf, MAX_ICMP_PACKET_SIZE,
       0, (sockaddr*)&from, &iFromLen );
    if( iReadDataLen != SOCKET_ERROR )//有
       数据到达
    {
        //对数据包进行解码
        if(DecodeIcmpResponse( IcmpRecvBuf
           , iReadDataLen, DecodeResult,
           ICMP_ECHO_REPLY, ICMP_TIMEOUT )
```

```
                    )
                {
                    //到达目的地, 退出循环
                    if( DecodeResult.dwIPaddr.
                        s_addr == destSockAddr.
                        sin_addr.s_addr )
                         bReachDestHost = true;
                    //输出IP地址
                    cout<<'\t'<<inet_ntoa(
                        DecodeResult.dwIPaddr )<<
                        endl;
                    break;
                }
            }
            else if( WSAGetLastError() ==
                WSAETIMEDOUT )    //接收超时, 输出*
                号
            {
                cout<<"          *"<<'\t'<<"Request
                    timed out."<<endl;
                break;
            }
            else
            {
                break;
            }
        }
        iTTL++;    //递增TTL值
    }
}
```