

示例使用的相关表和数据

```
select * from emp;
```

EMPNO	ENAME	JOB	MGR	HIREDATE	SAL	COMM	DEPTNO
7369	SMITH	CLERK	7902	17-DEC-1980	800		20
7499	ALLEN	SALESMAN	7698	20-FEB-1981	1600	300	30
7521	WARD	SALESMAN	7698	22-FEB-1981	1250	500	30
7566	JONES	MANAGER	7839	02-APR-1981	2975		20
7654	MARTIN	SALESMAN	7698	28-SEP-1981	1250	1400	30
7698	BLAKE	MANAGER	7839	01-MAY-1981	2850		30
7782	CLARK	MANAGER	7839	09-JUN-1981	2450		10
7788	SCOTT	ANALYST	7566	09-DEC-1982	3000		20
7839	KING	PRESIDENT		17-NOV-1981	5000		10
7844	TURNER	SALESMAN	7698	08-SEP-1981	1500	0	30
7876	ADAMS	CLERK	7788	12-JAN-1983	1100		20
7900	JAMES	CLERK	7698	03-DEC-1981	950		30
7902	FORD	ANALYST	7566	03-DEC-1981	3000		20
7934	MILLER	CLERK	7782	23-JAN-1982	1300		10

```
select * from dept;
```

DEPTNO	DNAME	LOC
10	ACCOUNTING	NEW YORK
20	RESEARCH	DALLAS
30	SALES	CHICAGO
40	OPERATIONS	BOSTON



Part 2 数值处理

- 2.1 计算平均值
- 2.2 计算最大值最小值
- 2.3 求和
- 2.4 计算行数
- 2.5 累计求和
- 2.6 计算众数
- 2.7 计算中位数
- 2.8 计算百分比
- 2.9 计算平均值时去掉最大值和最小值
- 2.10 修改累计值



2.1 计算平均值

```
1 select avg(sal) as avg_sal  
2   from emp
```

```
      AVG_SAL  
-----  
2073.21429
```

遇到空值怎么办？

```
create table t2(sal integer)  
insert into t2 values (10)  
insert into t2 values (20)  
insert into t2 values (null)
```

```
select avg(sal)  
from t2
```

```
AVG(SAL)  
-----  
15
```

```
select avg(coalesce(sal,0))  
from t2
```

```
AVG(COALESCE(SAL,0))  
-----  
10
```



2.1 计算平均值

```
1 select deptno, avg(sal) as avg_sal
2   from emp
3  group by deptno
```

DEPTNO	AVG_SAL
10	2916.66667
20	2175
30	1566.66667

```
1 select avg(sal)
2   from emp
3  group by deptno
```

AVG(SAL)
2916.66667
2175
1566.66667



2.2 查找最大值和最小值

```
1 select min(sal) as min_sal, max(sal) as max_sal
2   from emp
```

MIN_SAL	MAX_SAL
800	5000

```
1 select deptno, min(sal) as min_sal, max(sal) as max_sal
2   from emp
3  group by deptno
```

DEPTNO	MIN_SAL	MAX_SAL
10	1300	5000
20	800	3000
30	950	2850



2.3 求和

```
1 select sum(sal)
2 from emp
```

SUM(SAL)

29025

```
1 select deptno, sum(sal) as total_for_dept
2 from emp
3 group by deptno
```

DEPTNO TOTAL_FOR_DEPT

10	8750
20	10875
30	9400



2.4 计算行数

```
1 select count(*)
2   from emp
```

COUNT(*)
14

```
1 select deptno, count(*)
2   from emp
3  group by deptno
```

DEPTNO	COUNT(*)
10	3
20	5
30	6

计算某一列的非空个数

```
select count(comm)
  from emp
```

COUNT(COMM)
4



2.5 累计求和 (Running Total)

Oracle and DB2 (MySQL已经支持了)

```
1 select ename, sal,  
2    sum(sal) over (order by sal,empno)  
3    as running_total  
4 from emp  
5 order by 2
```

ENAME	SAL	RUNNING_TOTAL
-----	-----	-----
SMITH	800	800
JAMES	950	1750
ADAMS	1100	2850
WARD	1250	4100
MARTIN	1250	5350
MILLER	1300	6650
TURNER	1500	8150
ALLEN	1600	9750
CLARK	2450	12200
BLAKE	2850	15050
JONES	2975	18025
SCOTT	3000	21025
FORD	3000	24025
KING	5000	29025

MySQL and PostgreSQL and SQL Server

```
1 select e.ename, e.sal,  
2    (select sum(d.sal) from emp d  
3    where d.empno <= e.empno) as running_total  
4 from emp e  
5 order by 3
```

ENAME	SAL	RUNNING_TOTAL
-----	-----	-----
SMITH	800	800
ALLEN	1600	2400
WARD	1250	3650
JONES	2975	6625
MARTIN	1250	7875
BLAKE	2850	10725
CLARK	2450	13175
SCOTT	3000	16175
KING	5000	21175
TURNER	1500	22675
ADAMS	1100	23775
JAMES	950	24725
FORD	3000	27725
MILLER	1300	29025



2.6 计算众数

```
select sal
  from emp
 where deptno = 20
 order by sal
```

SAL

800

1100

2975

3000

3000

Oracle

```
1 select max(sal)
2    keep(dense_rank first order by cnt desc) sal
3  from (
4 select sal, count(*) cnt
5  from emp
6 where deptno=20
7  group by sal
8   )
```

MySQL and PostgreSQL

```
1 select sal
2  from emp
3 where deptno = 20
4  group by sal
5 having count(*) >= all ( select count(*)
6                        from emp
7                        where deptno = 20
8                        group by sal )
```



2.7 计算中位数

```
select sal
  from emp
 where deptno = 20
 order by sal
```

SAL
800
1100
2975
3000
3000

MySQL and PostgreSQL

```
1 select avg(sal)
2   from (
3 select e.sal
4   from emp e, emp d
5  where e.deptno = d.deptno
6    and e.deptno = 20
7  group by e.sal
8 having sum(case when e.sal = d.sal then 1 else 0 end)
9           >= abs(sum(sign(e.sal - d.sal)))
10    ) x
```

Oracle

```
1 select median(sal)
2   from emp
3  where deptno=20
```



2.8 计算百分比

MySQL and PostgreSQL

```
1 select (sum(  
2     case when deptno = 10 then sal end)/sum(sal)  
3     )*100 as pct  
4 from emp
```

DB2, Oracle, and SQL Server

```
1 select distinct (d10/total)*100 as pct  
2 from (  
3 select deptno,  
4     sum(sal)over( ) total,  
5     sum(sal)over(partition by deptno) d10  
6 from emp  
7     ) x  
8 where deptno=10
```



2.9 计算平均值时去掉最大值和最小值

MySQL and PostgreSQL

```
1 select avg(sal)
2   from emp
3  where sal not in (
4    (select min(sal) from emp),
5    (select max(sal) from emp)
6  )
```

DB2, Oracle, and SQL Server

```
1 select avg(sal)
2   from (
3    select sal, min(sal)over() min_sal, max(sal)over( ) max_sal
4    from emp
5    ) x
6  where sal not in (min_sal,max_sal)
```



2.10 修改累计值

- 问题，你想依据另一列的值来修改累计值。有这样一个场景，你希望显示一个信用卡账户的交易历史，并显示每一笔交易完成后的余额。

```
create view V (id,amt,trx)
```

```
as
```

```
select 1, 100, 'PR' from t1 union all
select 2, 100, 'PR' from t1 union all
select 3, 50, 'PY' from t1 union all
select 4, 100, 'PR' from t1 union all
select 5, 200, 'PY' from t1 union all
select 6, 50, 'PY' from t1
```

```
select * from V
```

```
ID    AMT  TR
--  -----  ---
1      100  PR
2      100  PR
3       50  PY
4      100  PR
5      200  PY
6       50  PY
```

TRX_TYPE	AMT	BALANCE
-----	-----	-----
PURCHASE	100	100
PURCHASE	100	200
PAYMENT	50	150
PURCHASE	100	250
PAYMENT	200	50
PAYMENT	50	0



2.10 修改累计值

DB2 and Oracle

```
1 select case when trx = 'PY'
2     then 'PAYMENT'
3     else 'PURCHASE'
4 end trx_type,
5 amt,
6 sum(
7     case when trx = 'PY'
8         then -amt else amt
9     end
10 ) over (order by id,amt) as balance
11 from V
```

MySQL, PostgreSQL, and SQL Server

```
1 select case when v1.trx = 'PY'
2     then 'PAYMENT'
3     else 'PURCHASE'
4 end as trx_type,
5 v1.amt,
6 (select sum(
7     case when v2.trx = 'PY'
8         then -v2.amt else v2.amt
9     end
10 )
11 from V v2
12 where v2.id <= v1.id) as balance
13 from V v1
```



思考题

- 2.5是进行累加，你看看怎么做累计乘法，和累计减法。
- 如果有时间，希望你把这一讲中所有的例子在你的数据库中尝试一下



End

下一讲，我们讲讲日期

