

Computer Science I

Error Handling

Dr. Chris Bourke
cbourke@cse.unl.edu

Outline

1. Introduction
2. Error Codes
3. Defensive Programming
4. Enumerated Types
5. Unit Testing

Part I: Introduction

Error Handling

- ▶ Errors in computer systems are *inevitable*
- ▶ Bugs vs. errors
- ▶ Bug: a flaw or defect in a computer program that causes it to produce an incorrect or unexpected result, or to behave in an unintended way
- ▶ Error: potential condition or state that can be reasonably anticipated by a programmer
- ▶ Bugs are flaws that should be resolved with rigorous *testing*

Errors

- ▶ Errors cannot be “prevented” only mitigated, anticipated, and *handled*
- ▶ Common errors:
 - ▶ Bad input leads to bad output (GIGO)
 - ▶ Illegal operations: dividing by zero
 - ▶ Dereferencing `NULL` pointers
 - ▶ More general problems: missing file, limited resources (memory), bad password, no network connection,
- ▶ Some errors may be unexpected/catastrophic/fatal
- ▶ Others are *recoverable*

Error Handling

- ▶ Dealing with error conditions is called *error handling*
- ▶ Two general approaches
- ▶ Defensive programming:
 - ▶ Check for dangerous/illegal/invalid operations before doing them; if an error would result, we “choose” not to do them
 - ▶ We can then “fail silently” or communicate the type of error and let the calling function decide *how to handle it*
 - ▶ “Look before you leap”
- ▶ Exception handling

Exception Handling

- ▶ Modern programming support *Exceptions*
- ▶ Exception: an *event* during the execution of a program that disrupts the normal control flow of the program
- ▶ Exceptions are *thrown* and may be *caught* (and handled)
- ▶ "Go ahead and leap without looking, you'll be *caught* if you fall"
- ▶ Many advantages to exception handling over defensive programming
- ▶ Not supported in C

Error Handling in C

- ▶ C generally uses defensive programming
- ▶ Error handling is generally on the function-level
- ▶ Functions validate input, check for error conditions, etc. before proceeding
- ▶ If an error is detected, the function aborts and returns
- ▶ Error condition is communicated to the calling function via an *error code*
- ▶ Error code: a number (integer) indicating the type of error (or none)

Part II: Error Codes

Error Codes

- ▶ C provides a standard error library: `errno.h` (error number)
- ▶ Defines standard *errors codes* and some (limited) utilities
- ▶ A global `int` variable named `errno` can be set by standard functions in the event of an error
- ▶ Value can be checked for an error "state"
- ▶ Zero: no error
- ▶ Only three "standard" error codes:
 - ▶ `EDOM` indicates an error in the domain of a function
 - ▶ `ERANGE` indicates an error in the range of a function
 - ▶ `EILSEQ` illegal byte sequence
- ▶ Error codes defined via macros `#define`

EDOM

`EDOM`

- ▶ Error in the domain value of a function
- ▶ Functions map a *domain* to a *range*
- ▶ Domain is the set of all possible inputs
- ▶ In other words: illegal input
- ▶ Example: \sqrt{x} is only defined for values ≥ 0
- ▶ `sqrt(-1)` would result in an `EDOM` error

ERANGE

`ERANGE`

- ▶ Error in the range value of a function
- ▶ Range is the set of all possible outputs
- ▶ Illegal or aberrant output value from a function
- ▶ Example: $\log(0)$ is undefined (but converges to $-\infty$)
- ▶ `log(0)` would result in an `ERANGE` error
- ▶ Demonstration

POSIX Error Codes

- ▶ Portable Operating System Interface (POSIX) standard defines many more error codes
- ▶ Mostly for systems programming
- ▶ Examples:
 - ▶ No such file or directory
 - ▶ Out of memory
 - ▶ Network is down
- ▶ Demonstration

Exit Codes

- ▶ Similar: *exit codes*
- ▶ When a program quits, it can “return” a value to the operating system
- ▶ Can be used externally to determine if a program was successful
- ▶ Example: Segmentation Faults usually exit with an error code of 139
- ▶ Actual numbers are not standardized
- ▶ Two standard flags defined in `stdlib.h`
- ▶ `EXIT_FAILURE` (usually 1)
- ▶ `EXIT_SUCCESS` (usually 0, no error)
- ▶ Demonstration

Part III: Defensive Programming

Defensive Programming

- ▶ Don't generally use standard error codes for user-defined functions
- ▶ Can use the same approach: defensive error checking with error codes
 1. Look before you leap: check for invalid state before a dangerous operation
 2. If invalid, return an error code to communicate the *type of error*

Defensive Programming

General design philosophy:

- ▶ You *communicate* the error to the calling function
- ▶ You *don't* decide (dictate) what how to *handle* the error
- ▶ The calling function is responsible for deciding what to do

Defensive Programming

Advantages:

- ▶ Makes your functions more flexible
- ▶ Leaves the decision making process to the user of the library
- ▶ Different error codes means the calling function can decide to apply different solutions to different errors
- ▶ Avoids unrecoverable state

Common Implementations

- ▶ Input validation (ranges)
- ▶ Null pointer checks
- ▶ Outputs are “returned” via pass-by-reference variables
- ▶ Preserve the return value to return an error code
- ▶ Convention: use zero for success
- ▶ Similar to booleans: 0 = no error, non-zero = some kind of error

Demonstration

Modify the `euclideanDistance` and `computeLine` functions to use error codes.

Pitfalls

- ▶ In general: functions should *not exit*
 - ▶ Takes the decision away from the calling function
 - ▶ Makes all errors fatal errors
 - ▶ Defeats the purpose of *error handling*
- ▶ In general: functions should *not print error output*
 - ▶ Most programs are not interactive, messages are pointless
 - ▶ Standard error/output may not be monitored
 - ▶ Proper logging systems should be used in practice
- ▶ Error checking should always *come first*
 - ▶ Look *before* you leap
 - ▶ Dangerous operations could leave a program in an illegal state, unable to actually *handle* an error

Part IV: Enumerated Types

Enumerated Types

- ▶ Some pieces of data have a limited number of possible values
- ▶ Examples: days of the week, months in a year, *error codes*
- ▶ You can define an *enumerated type* with pre-defined human-readable values
- ▶ An *enumeration* is a complete, ordered listing of all items in a collection

Syntax & Style

Syntax:

```
1 typedef enum {  
2     SUNDAY,  
3     MONDAY,  
4     TUESDAY,  
5     WEDNESDAY,  
6     THURSDAY,  
7     FRIDAY,  
8     SATURDAY  
9 } DayOfWeek;
```

- ▶ `typedef` (type definition) and `enum` (enumeration)
- ▶ Opening/closing curly brackets
- ▶ Comma-delimited list of possible values
- ▶ Name of the enumerated type followed by a semicolon

Syntax & Style

```
1 typedef enum {
2     SUNDAY,
3     MONDAY,
4     TUESDAY,
5     WEDNESDAY,
6     THURSDAY,
7     FRIDAY,
8     SATURDAY
9 } DayOfWeek;
```

Style:

- ▶ UPPER_UNDERSCORE_CASING for values
- ▶ One value per line for readability
- ▶ Name: UpperCamelCasing (modern convention)
- ▶ Typically declared in a header file

Using

- ▶ Once declared you can use an enumerated type like other built-in variable types

```
1 DayOfWeek today;
2 today = TUESDAY;
```

```
1 if(today == FRIDAY) {
2     printf("Have a good weekend!\n");
3 }
```

Pitfall

- ▶ In reality, C uses `int` values for enumerated types
- ▶ Default usually starts at 0
- ▶ `SUNDAY = 0`, `MONDAY = 1`, ..., `SATURDAY = 6`
- ▶ You *can* perform integer arithmetic on enumerated types

```
1 DayOfWeek today = FRIDAY;
2 today = today + 1;
3 today++;
```

```
1 DayOfWeek someday = 99999;
```

- ▶ *Can*, but **shouldn't**

Use Cases

- ▶ Using enumerated types allows you to use human-readable terms
- ▶ Without enumerated types, you are forced to use *magic numbers*
- ▶ Makes your code more readable and easily understood
- ▶ Slight advantage over `#define` "constants": understood by debuggers; name conflicts are compile-time errors.
- ▶ Demonstration

Part V: Unit Testing

Software Testing

- ▶ Overview of types of testing/levels of testing

Unit Testing

- ▶ Ad-hoc Testing
- ▶ Test cases
- ▶ Unit testing
- ▶ Testing suite

Informal Unit Testing

- ▶ Design and code input/output pairs
- ▶ Test for edge cases
- ▶ Describe failures
- ▶ Summarize results
- ▶ Re-runnable and reproducible results
- ▶ Regression tests

Unit Testing Frameworks

- ▶ cmocka?